Building Genomic Analysis Pipelines in a Hackathon Setting with Bioinformatician Teams: DNA-seq, Epigenomics, Metagenomics and RNA-seq

Ben Busby[1*], Allissa Dillman[2], Claire L. Simpson[3], Ian Fingerman[1], Sijung Yun[4], David M. Kristensen[1], Lisa Federer[5], Naisha Shah[6], Matthew C. LaFave[7], Laura Jimenez-Barron[8-9], Manjusha Pande[10], Wen Luo[11], Brendan Miller[12], Cem Meydan[13], Dhruva Chandramohan[13-14], Kipper Fletez-Brant[15-16], Paul W. Bible[17], Sergej Nowoshilow[18], Alfred Chan[19], Eric JC Galvez[20], Jeremy Chignell[21], Joseph N. Paulson[22-23], Manoj Kandpal[24], Suhyeon Yoon[25], Esther Asaki[26-27], Abhinav Nellore[15,28], Adam Stine[1], Robert Sanders[1], Jesse Becker[1], Matt Lesko[1], Mordechai Abzug[1], Eugene Yaschenko[1]

[1] National Center for Biotechnology Information, National Library of Medicine, National Institutes of Health, Bethesda, Maryland, United States of America

[2] Surgery, Center for Prostate Disease Research, Uniformed Services University of the Health Sciences, Bethesda, Maryland, United States of America

[3] Computational and Statistical Genomics Branch, National Human Genome Research Institute, National Institutes of Health, Baltimore, Maryland, United States of America

[4] Laboratory of Cell Biology, National Institute of Diabetes and Digestive and Kidney Diseases, National Institutes of Health, Bethesda, Maryland, United States of America

[5] NIH Library, Division of Library Services, Office of Research Services, National Institutes of Health, Bethesda, Maryland, United States of America

[6] Systems Genomics and Bioinformatics Unit, National Institute of Allergy and Infectious Diseases, National Institutes of Health, Bethesda, Maryland, United States of America

[7] Translational and Functional Genomics Branch, National Human Genome Research Institute, National Institutes of Health, Bethesda, Maryland, United States of America

[8] Stanley Institute for Cognitive Genomics, Cold Spring Harbor Laboratory, Cold Spring Harbor, New York, United States of America

[9] Centro de Ciencias Genomicas, Universidad Nacional Autonoma de Mexico, Cuernavaca, Morelos, Mexico

[10] Bioinformatics Core, University of Michigan, Ann Arbor, Michigan

[11] Cancer Genomics Research Laboratory, Division of Cancer Epidemiology and Genetics, National Cancer Institute, National Institutes of Health, Gaithersburg, Maryland, United States of America

[12] Department of Biology, Johns Hopkins University, Baltimore, Maryland, United States of America

[13] Institute for Computational Biomedicine, Weill Cornell Medical College, New York, New York, United States of America

[14] Tri-Institutional Training Program in Computational Biology and Medicine, New York, New York, United States of America

[15] Department of Biostatistics, Johns Hopkins Bloomberg School of Public Health, Baltimore, Maryland, United States of America

[16] McKusick-Nathans Institute of Genetic Medicine, Johns Hopkins University School of Medicine, Baltimore, Maryland, United States of America

[17] Laboratory of Skin Biology, National Institute of Arthritis and Musculoskeletal and Skin

Diseases, National Institutes of Health, Bethesda, Maryland, United States of America

[18] Center for Regenerative Therapies, Technische Universität Dresden, Dresden, Germany

[19] Translational Immunology, John Wayne Cancer Institute at Saint John's Health Center, Santa

Monica, California, United States of America

[20] Microbial Immune Regulation Group, Helmholtz Centre for Infection Research,

Braunschweig, Germany

[21] Chemical and Biological Engineering, Colorado State University, Fort Collins, Colorado,

United States of America

[22] Graduate Program in Applied Mathematics & Statistics, and Scientific Computation,

University of Maryland, College Park, Maryland, United States of America

[23] Center for Bioinformatics and Computational Biology, University of Maryland, College Park,

Maryland, United States of America

[24] Division of Health and Biomedical Informatics, Department of Preventive Medicine, Feinberg

School of Medicine, Northwestern University, Chicago, Illinois, United States of America

[25] Genetics and Molecular Biology Branch, National Human Genome Research Institute,

National Institutes of Health, Bethesda, Maryland, United States of America

[26] Bioinformatics and Molecular Analysis Section, Center for Information Technology, National

Institutes of Health, Bethesda, Maryland, United States of America

[27] SRA International, Fairfax, Virginia, United States of America

[28] Department of Computer Science, Johns Hopkins University, Baltimore, Maryland, United

States of America

*Corresponding author

Email: ben.busby@gmail.com (BB)

Abstract

We assembled teams of genomics professionals to assess whether we could rapidly

develop pipelines to answer biological questions commonly asked by biologists and others new

to bioinformatics by facilitating analysis of high-throughput sequencing data. In January 2015,

teams were assembled on the National Institutes of Health (NIH) campus to address questions in

the DNA-seq, epigenomics, metagenomics and RNA-seq subfields of genomics. The only two

rules for this hackathon were that either the data used were housed at the National Center for

Biotechnology Information (NCBI) or would be submitted there by a participant in the next six

months, and that all software going into the pipeline was open-source or open-use. Questions

proposed by organizers, as well as suggested tools and approaches, were distributed to

participants a few days before the event and were refined during the event. Pipelines were

published on GitHub, a web service providing publicly available, free-usage tiers for

collaborative software development (https://github.com/features/). The code was published at

https://github.com/DCGenomics/ with separate repositories for each team, starting with

hackathon_v001.

Introduction

Genomic analysis leverages large datasets generated by sequencing technologies in order

to gain better understanding of the genomes of humans and other species. Given its reliance on

large datasets with complex interactions and its fairly regularized metadata, genomic analysis is

an exemplar of "big data" science (1). Genomic analysis has shown great promise in finding

actionable variants for rare diseases (2), as well as directing more specific clinical action for

common diseases (3, 4).

Due to its potential for significant clinical and basic science discoveries, genomics has

drawn many newcomers from the biological and computational sciences, as well as investigators

from new graduate programs in bioinformatics. While many of these investigators can run

established pipelines on local, public, or combined datasets, most do not have the expertise or

resources to establish and validate novel pipelines. Additionally, highly experienced genomic

investigators often lack the resources necessary to generate and distribute pipelines with broader

applicability outside their specific area of research. In this study, we aimed to assess whether we

could close this gap by bringing genomics experts from around the world together to establish

public pipelines that can be both used by newcomers to genomics and refined by other seasoned

professionals.

We sought to achieve this by hosting a hackathon at the National Institutes of Health

(NIH) in Bethesda, Maryland. Hackathons are events in which individuals with expertise in

various areas of software development and science come together to collaborate intensively over

a period of several days, typically focusing on a specific goal or application. This form of

crowdsourcing facilitates innovative ideas and agile development of solutions for challenging

questions (5). Hackathon participants also benefit from the opportunity to learn new skills,

network with other professionals, and gain the personal satisfaction of using their expertise to

help the community.

Those of us who had previously attended hackathons had been motivated by learning

from the experience, personal curiosity, professional networking, and the satisfaction of applying

one's skills to help the community. These previously attended hackathons included

IT/programming-centric events, such as the Kaiser Permanente-sponsored hackathon for apps

that could help prevent and fight obesity (6); bioinformatics-oriented events, such as the

Illumina-sponsored hackathon to create apps in their proprietary BaseSpace cloud computing

environment (7); and events focused on social issues, such as exploring women's empowerment

and nutrition in the developing world (8).

Hackathons are more common in software development communities than in

bioinformatics and medicine, and may represent a valuable opportunity to accelerate biomedical

discovery and innovation. Hackathons have gained popularity in the bioinformatics community

in the last several years, though the environment and culture of a bioinformatics hackathon

differs from that of typical IT/programming-centric hackathons (9). Bioinformatic hackathons

more closely resemble a scientific discussion and provide an opportunity to learn and delve more

deeply into specific areas. Typically a successful hackathon requires participants with both

coding/programming skills and domain-specific knowledge (e.g. DNA-seq and RNA-seq).

Four teams of 4-6 participants came together for this hackathon to answer questions in

the fields of DNA-seq, RNA-seq, metagenomics and epigenomics. The initial topics for

exploration were based on questions bioinformaticians frequently ask computational cores.

Massive amounts of data have been generated and made publicly available in these fields using

high-throughput experimental technologies. Powerful computational pipelines are needed to

handle such large datasets, and to help analyze the data to answer biomedical questions. In

addition, these topics have seen a significant increase in publications in recent years, as

demonstrated in Figure 1.

Fig. 1: Articles indexed in MEDLINE for topics related to each of the four teams.

Background for Hackathon Team Goals

DNA-seq Team

The goal for the DNA-seq Team was to create an easy-to-use integrated pipeline using

existing tools to predict somatic variants from exome sequencing data, find shared and unique

variants between samples, and filter and annotate the variants. Somatic mutation calling is

particularly relevant to cancer genome characterization (10). Several methods exist to predict

somatic variants by interrogating genomic sequences of tumor-germline paired samples (11-13).

Issues with these variant calling algorithms are well known; each of the algorithms have

strengths and weaknesses, and are sensitive to the datasets used (14). One way to test the

reliability of the called variants and gain more confidence is to combine putative calls from

several algorithms and use strict filtering criteria. Thus, we wanted to create a pipeline that

included several existing calling algorithms. In addition, we intended to build a module within

the pipeline to predict eQTLs using the called somatic variants and RNA-seq data from the same

individuals. To achieve our goal of building an integrated pipeline, a paired exome sequence

dataset as well as an RNA sequence dataset were required.

Epigenomics Team

Computational cores contain an abundance of epigenetic data encompassing a wide

variety of markers over many different cell types. This abundance of information empowers labs

to infer how these different markers contribute to gene expression and chromatin state. However,

little standardization or collaboration exists among investigators seeking to elucidate

relationships among epigenetic modifiers, leading to inconsistencies between analyses. The

Epigenomics Team sought to analyze the extent to which DNA methylation and histone

modifications affect gene expression using regression models. In addition to modelling, we

wanted to create a framework for integrating experimental ChIP-seq or DNA methylation data

provided by users into models of gene expression that were informed by publicly available data.

A resource that allows users to make sense of their data in the context of the existing wealth of

public data on epigenetic regulation provided an attractive and worthwhile goal.

Metagenomics Team

The Metagenomics Team worked on the problem of identifying the presence of viral

sequences within human genomic or metagenomic sequences. The ability to locate these viral

sequences offers the prospect of using computational tools for diagnostic purposes (15). Viral

sequences may be embedded within human genomic sequence data as endogenous retroviruses

or associated with bacterial consortia of the human microbiome as either lytic phages or

prophages integrated into the bacterial genomes. Several studies have demonstrated the

association between human-specific endogenous retroviruses (HERV) and diseases such as

breast cancer (16, 17). In the context of the human microbiome, previous studies have used

metagenomics to describe differences in bacterial consortia (18), but only a few studies have

applied a metagenomics workflow to viral sequences present in human microbiome data (19,

20).

This team's aim was to develop and compare analytical pipelines to identify and quantify

viral sequences within human genomic and metagenomic datasets. The pipeline could be used in

the characterization of the viral community in understanding the role viruses play in various

environmental niches and diseases eventually associating differentially abundant viruses in

disease or phenotype, despite database and sparsity issues potentially using marker-gene

methodologies (21).

RNA-seq Team

RNA sequencing (RNA-seq) has become a useful technique for detecting gene

expression levels, alternate splicing, and gene fusions (22). RNA variant detection can be

important in cancer research to detect significant changes in tumor progression (23). The team's

initial goal was to build a variant calling pipeline using RNA-seq data from melanoma samples

to differentiate germline and somatic mutations from RNA editing. Some sample datasets from

the National Center for Biotechnology Information's (NCBI) Sequence Read Archive (SRA)

were suggested. Data could then be used to compare germline variants with known germline

variants from the dbGaP version of the 1000 Genomes Project and ClinVar (24, 25). Another

task was to determine isoform specificity based on mapping to 454 data using available software

for the correlation with RNA structure prediction. Data could also be compared with the NCI-60

cell line variants. Also, we could try to determine mosaicism with germ-line vs intratumor data.

Additional tasks were to detect systematic quality score variants indicating RNA editing with

Illumina and Pacbio reads, correlate with RNA structure prediction and to fix HTseq annotation

of tiny exons in UTRs.

Materials and Methods

Advertising, Preparation, and Logistics

Four team leads were selected by Busby to participate in the event. Team leads were

experts in particular areas and they suggested scientific areas, datasets, or tools that they were

familiar with. In order to recruit participants, we sent an announcement (Supporting Information

1) to contacts in Busby's network encouraging genomics professionals to apply for the

hackathon, as well as posting it on several NCBI social media outlets, such as Facebook, Twitter,

and Meetup.

After the application deadline, Busby reviewed the applicants for minimum necessary

experience, and sent the applicants' written statements to team leads, encouraging them to pick

five members and two alternates. Team leads reviewed the 131 qualified applicants and selected

a total of 27 people to fill the four teams of about 6 people each. Members were chosen solely on

the interest and motivational statements on their forms, and credentials and experience were not

further researched. One goal of the hackathon was to bring together scientists with different

expertise. Some of the participants were more traditional bench biologists and some were

bioinformaticists with more computational knowledge. This was a networking experience for

local and international scientists, including two who traveled from Germany and several from

outside of Maryland.

Technical professional staff from NCBI, including programmers and system

administrators, were also brought in and "embedded" with the team to facilitate programming

knowledge transfer and debugging. In addition, a librarian from the NIH Library served as an

editor, providing guidance on writing and organization of the manuscript.

The teams convened in a large meeting space that had Wi-Fi access, a nearby cafeteria,

plenty of tables to provide adequate room to spread out, and easels with markers for easier team

discussion. Space was available outside of the meeting room if participants needed a quiet space

apart from the larger group. To optimize time available to work on the projects, an hour was set

aside each day for a "working lunch" with the option to order in as a group. There was also an

optional group dinner each night that provided more time to network, socialize, and continue

work on the scientific problems.

The schedule was circulated the week prior to the hackathon. The agenda was semi-

structured with time allocated for various activities such as obtaining data, pipeline building, and

code checking. There were several checkpoints for each team to present their progress to the

larger group. A tour of the NCBI data center was conducted, as well as several brief

informational presentations. For example, Eugene Yaschenko of NCBI presented a group of

application program interfaces (APIs) relating to the SRA Toolkit collectively known as the

software development kit (26). The schedule was designed to give team members a common

starting point, but allowed for modification as needed for each team.

Delegation of roles/responsibilities

One of the first tasks at the hackathon was for each team to assign roles/responsibilities to

the team members. Most of the members were meeting each other for the first time, so it was a

good way to learn about each other's strengths. Roles were loosely distributed to cover areas

including:

• Systems administration: decided where data and tools went, implemented git for

versioning, and dealt with any technical issues;

• Metadata: tracked and recorded the information describing the contents of the datasets;

•   Data Acquisition: located and downloaded appropriate publicly available datasets for

analysis;

•   Data Normalization: prepared data from multiple datasets to work in a pipeline, such as

making read counts comparable between collection sites.

•   Downstream Analysis: assigned annotation or function to genomic predictions and

looked at statistically meaningful overrepresentation

•   Documentation: prepared code and text summaries, including drafting this manuscript.

Team Organization and Communication

In order to facilitate communication among team members, Google mail groups were

created for each team. Most team members did not know each other prior to the start of the

hackathon, but some teams used their Google mail group to communicate prior to the event.

Other collaboration tools included GitHub for program version control and Gitter, an instant

messaging tool, for sharing links, especially while teams were looking for datasets. Documents

were collaboratively edited using Google Docs.

Data Sources and Computational Tools

The basic workflow for the teams' activities is demonstrated in Fig. 2. Scripting and data

analysis took place in an Amazon Elastic Compute Cloud (EC2) where team players downloaded

data from NCBI repositories and used open source bioinformatic tools. System administrators

(SysAdmin) for each team were charged with code installation, compilation, storage and nodes

expansion while the teams were developing the pipelines, which were pushed to GitHub.

Figure 2. Hackathon teams workflow.

DNA-seq Team

The DNA-seq team acquired high-throughput sequencing data for matched tumor-normal

pairs from the NCBI SRA. The first three datasets found were unusable due to corrupted files,

mismatched samples, or missing header information (see Discussion below for more details).

The data used for designing the DNA-seq pipeline were found by searching the BioProject

database for the terms "homo sapiens NOT cell line," filtering for exome and SRA datasets, and

rejecting the 81 datasets that matched the term "HapMap".

We designed our pipeline around a publicly available exome dataset submitted to SRA,

BioProject PRJNA268172 (27). It consisted of exome sequences from four meningioma samples

and a peripheral blood DNA sample from a 61-year-old female suffering from sporadic multiple

meningiomas. Meningiomas are tumors originating from the membranous layers surrounding the

central nervous system and are generally considered benign. Malignant meningiomas, while rare,

are associated with a higher risk of local tumor recurrence and have a median survival time of

less than two years (28). We were interested in finding and comparing somatic mutations,

specifically SNPs, found in each of the meningioma tumor samples from the patient.

We downloaded the relevant files by using the SRA Toolkit, and converted the SRA files

to SAM and BAM files for further analysis. We found that the SAM files contained reads with

sequence and quality scores of different length, which would halt the BAM file conversion, so

we added a filter in our pipeline to remove such reads. Ideally, a module for trimming/masking

and re-aligning the FASTQ file would have been the most appropriate; however, due to time

restrictions we were unable to add such a module to our pipeline. Here, we assumed that the

SRA submitted files were properly aligned and followed appropriate quality control steps.

We used five different algorithms to call somatic variants. Four of these were in the Cake

pipeline (29), namely Bambino (11), CaVEMan (30), SAMtools mpileup (31), and VarScan2

(12). To further increase our confidence in the called variants, we added the MuTect algorithm

(13) to those used by Cake. Xu et al have compared somatic variation calling algorithms (14).

A first level of filtering is provided in the pipeline for the resulted VCF files containing

called somatic variants. This was accomplished using the Cake filtering module. We kept most

of the default parameters, and those that were changed are explained in Table 1. Once the VCF

files were filtered, they would be annotated using the ANNOVAR software, downloaded on

January 5th, 2015 (32), with five different databases (RefGene, KnownGene, ClinVar, Cosmid

and Cosmic), and the top 1% most deleterious CADD scores.

Table 1: Cake filtering module parameters modified by the DNA-seq Team.

Parameter	Explanation	Flag or Value Used
EXONIC_FILTER	Exome data is being used	FALSE
INDEL_FILTER	Only SNPs are being considered	FALSE
COSMIC_ANNOTATION_FLAG	Cosmic Annotations are added with ANNOVAR	FALSE
TUMOR_MIN_DEPTH	As the coverage of these samples was too low, we set the threshold to a less stringent value.	5
NORMAL_MIN_DEPTH	As the coverage of these samples was too low, we set the threshold to a less stringent value.	5
EMPTY_CONSEQ_FILTER	VEP annotations were not used	FALSE

To compare the predicted somatic variations between two matched tumor-control

samples, we created a module in our pipeline that used VCFtools to find shared and unique

variations (33). Lastly, we combined these modules into a single pipeline using Bpipe (34), as

well as a Unix Bash script. The full list of software used by the DNA-seq Team is included in

Table 2.

Table 2: Tools and software used by the DNA-seq Team.

Software/Tool	URL
SRA tool kit	http://www.ncbi.nlm.nih.gov/sra
Cake	http://sourceforge.net/projects/cakesomatic/
MuTect	https://github.com/broadinstitute/mutect/releases/tag/1.1.5
somatic sniper	http://gmt.genome.wustl.edu/packages/somatic-sniper/install.html
varscan	http://sourceforge.net/projects/varscan/
bambino	https://cgwb.nci.nih.gov/goldenPath/bamview/documentation/index.html
picard	http://broadinstitute.github.io/picard/
Annovar	http://www.openbioinformatics.org/cgi-bin/annovar_download.cgi
SAMtools	http://www.htslib.org/
bpipe	http://github.com/ssadedin/bpipe
Python	https://www.python.org/
GNU Parallel	http://ftp.gnu.org/gnu/parallel/
VCFtools	http://vcftools.sourceforge.net

Epigenomics Team

We gathered data with the intention of modeling transcription (mRNA-seq) based on

DNA methylation (RRBS or Bisulfite-seq) and histone states (ChIP-seq). To simplify analysis,

we focused on marks associated with enhancers and their regulatory status: H3K27ac,

H3K4me1, and H3K4me3. Ultimately, we required that included tissues have matching

H3K27ac, RNA-seq and DNA methylation data for preliminary modeling. Data files were drawn

from human cell lines and tissues in the NIH Epigenomic Roadmap that fit our criteria (outlined

in Table 3), from the site's FTP mirror (35) using the rsync command with the -av option. All

files were already aligned, and were required to have been generated using the hg19 reference

genome. Several files were identified that appeared to be re-aligned or uncorrected versions of

other downloaded files, and were removed from the analysis. Tissues acceptable for analysis

were identified by using the data matrix view on the Roadmap site, as well as searching for non-

partial datasets with the Data Grid view of the International Human Epigenome Consortium

(IHEC) Data Portal (36). Samples were initially downloaded from ENCODE: Encyclopedia of

DNA Elements (37), but were not included in initial analysis for reasons of uniformity and time.

Table 3: NIH Epigenomic Roadmap Cell Lines/Tissues used by Epigenomics Team

Cell/Tissue Type	
H1	Left_Ventricle
IMR90	Pancreas
CD34_mobilized_primary_cells	Right_Atrium
hESC-derived_CD184+_endoderm_cultured_cells	Sigmoid_Colon
HUES64_cell_line	Spleen
pancreatic_islets	Penis_Foreskin_Fibroblast_Primary_Cells
Skeletal_muscle	Penis_Foreskin_Keratinocyte_Primary_Cells
Adrenal_Gland	Penis_Foreskin_Melanocyte_Primary_Cells
Aorta	Neurosphere_Cultured_Cells_Ganglionic_Eminence_Derived
Esophagus	Brain_Hippocampus_Middle
Gastric	Ovary

Metagenomics Team

We designed six pipelines to compare different strategies for identifying and quantifying

viral sequences among human genomic information. The pipelines are:

1. Identify and quantify HERV sequences in assembled reads using blastn,

2. Identify and quantify HERV sequences in non-assembled reads from a human genome

using search tools from NCBI's SRA Toolkit,

3. Identify and quantify HERV sequences in non-assembled reads from a human genome

using a standard blastn search of reads in FASTA format.

Pipelines 4-6 repeat pipelines 1-3 to identify all viral sequences within a sample from a human

bacterial microbiome.

For pipeline 1, whole genome sequence raw reads of human CEU NA12878 (38) were

obtained from NCBI's SRA database and converted from SRA to FASTQ file format using the

fastq-dump command provided by the SRA Toolkit with default filter settings. The resulting

FASTQ file was moved to an Amazon Elastic Compute Cloud (EC2) node and assembled into

contigs with the ABySS assembler (39, 40). Contigs were used as queries for blastn against a

database consisting of all *Retroviridae* RefSeq genomes that was constructed using the

makeblastdb command. For pipeline 2, the SRA files containing raw reads for NA12878 were

used directly as a database for a SRA blast (blastn_vdb) using the *Retroviridae* RefSeq genomes

as query. For pipeline 3**,** the FASTA file of non-assembled reads from pipeline 1 was used as a

query for a blastn search against the database of *Retroviridae* RefSeq genomes from pipeline 1.

For pipelines 4 – 6, we used samples from the Human Microbiome Project (HMP) that

had passed preliminary quality checks (41). The plan for pipeline 4 was the same as for pipeline

1, except for using SOAPdenovo2 for the assembly of the microbiome FASTQ reads. For

pipeline 5, rather than start with SRA files, raw Illumina WGS reads in FASTQ format first were

converted to SRA format using the FASTQ loader tool latf-load within the SRA Toolkit.

Pipeline 6 follows pipeline 3, but uses the microbiome FASTA as its query and the total viral

RefSeq genome as its database. Full details about the data and tools we used are located in

Tables 4 and 5, respectively.

Table 4. Data sources used by Metagenomics Team

Data Source	FTP Location
refseq viral	ftp://ftp.ncbi.nlm.nih.gov/refseq/release/viral
1000 genomes contigs	ftp://ftp.1000genomes.ebi.ac.uk/vol1/ftp/technical/reference/
Human microbiome	ftp://public-ftp.hmpdacc.org/HMASM/PGAs/
Human microbiome raw reads for right_retroauricular_crease	ftp://public-ftp.hmpdacc.org/Illumina/right_retroauricular_crease/SRS015381.tar.bz2
Homo_sapiens_dna	ftp://ftp.ensembl.org/pub/current_fasta/homo_sapiens/dna/Homo_sapiens.GRCh38.dna.chromosome.10.fa.gz

352 **Table 5: Tools and software used by the Metagenomics Team.**

Software/Tool	URL
SRAtoolkit	http://www.ncbi.nlm.nih.gov/Traces/sra/?view=software
ABySS (from source, version 1.5.2)	http://www.bcgsc.ca/platform/bioinfo/software/abyss/releases/1.5.2
R statistical package	http://www.r-project.org/
BLAST+	ftp://ftp.ncbi.nlm.nih.gov/blast/executables/blast+/LATEST/

RNA-seq Team

The RNA-seq Team determined that the samples initially suggested by the team lead

were not appropriate, so we looked for paired tumor/normal datasets from the NCBI Sequence

Read Archive (SRA). One dataset was a deep high-throughput transcriptome sequencing (RNA-

seq) performed on three pairs of matched tumor and adjacent non-tumors (NT) tissues from HCC

patients of Chinese origin, accession PRJNA149267 (42, 43) Another identified dataset was a

study to identify a prognostic signature in colorectal cancer (CRC) patients with diverse

progression and heterogeneity of CRCs, accession PRJNA218851 (44, 45). Thirty-six paired

samples from this study (18 tumor samples: GSM1228184-GSM1228201 and 18 matched

normal samples GSM1228202-GSM1228219) were also determined to suitable. Additional tools

used by the RNA-seq Team are listed in Table 6.

Table 6: Tools and software used by the RNA-seq Team.

Software/Tool	URL
HISAT	http://www.ccb.jhu.edu/software/hisat/index.shtml
Illumina iGenome	http://support.illumina.com/sequencing/sequencing_software/igenome.html
Bowtie	http://bowtie-bio.sourceforge.net/index.shtml
tophat	http://ccb.jhu.edu/software/tophat/index.shtml
Bambino	https://cgwb.nci.nih.gov/goldenPath/bamview/documentation/index.html
SAMtools	http://SAMtools.sourceforge.net/
SRA Toolkit	http://www.ncbi.nlm.nih.gov/Traces/sra/?view=software
R	http://www.r-project.org/
python	https://www.python.org/
perl	http://www.perl.org/

Results

Evolution of the Projects

DNA-seq team

Our initial goal was to build a bioinformatics pipeline to predict somatic mutations using

several calling algorithms and integrate the mutations with RNA-seq data to find eQTLs.

However, one of the main hurdles we encountered was finding an appropriate dataset that could

be used to test and help create our pipeline. Initially, we found a neuroblastoma dataset

submitted to SRA that included both the exome and RNA-seq data for matched samples.

However, the dataset was unusable because of corrupted files. The majority of our time at the

hackathon was spent on finding an appropriate dataset and debugging issues with the publicly

available files. This hindered our efforts to create a fully functional pipeline to achieve our goals.

Due to a lack of a working dataset of both DNA-seq and RNA-seq from the same individuals, we

were unable to write a module within our pipeline to find eQTLs. However, we were able to

design a pipeline that would find somatic mutations using five calling algorithms for given

matched samples using five different algorithms, filter and annotate mutations, and find shared

and unique mutations between two matched sample pairs (see Methods for more details).

Epigenomics Team

We initially considered different scenarios in which a lab might utilize our proposed

pipeline based upon their available datasets and how investigators might want to model their

datasets. For example, investigators might want to find a relationship between DNA methylation

levels and histone enrichment. Given the variation in epigenetic data available as part of publicly

available datasets, we recognized the need for flexibility about which data components would be

required to model different epigenetic relationships. Time limitations prevented us from

generating a workflow for every potential scenario (for example, RNA-seq and ChIP-seq, or

ChIP-seq and DNA methylation but no RNA-seq). Instead, we considered common questions

that might interest a general epigenetics laboratory. Investigators with epigenetic data often want

to understand how this data correlates to gene expression. Thus, we decided to focus our model

on elucidating relationships between a given variable collection of epigenetic data and gene

expression. A lab can use publicly available datasets to create a model with which to test their

own epigenetic data.

Metagenomics Team

We considered several different options for metagenomics searches before the final six

pipelines were settled. We spent significant time discussing the requirements for filtering or

other QC steps on raw reads prior to running assembly (pipelines 1 and 4) or SRA blast steps.

We also debated the relative merits of assembly for each task, eventually deciding to compare

searches with and without assembly in different pipelines, which significantly added to our

workload and may have contributed to the fact that only two pipelines were completed during the

hackathon. With regard to assembly, our group considered using the established MG-RAST

pipeline for a "brute force" blastn into raw reads (46), as well as using metAMOS (47), a

comprehensive pipeline for metagenomics analysis for comparison. Eventually we decided to

forego established pipelines, due to computational requirements within the timeframe of the

hackathon and the desire to focus on developing novel workflows of our own.

For pipelines 1-3 we initially planned to use human genomic information from 1000

Genomes (24) but found the format (base genomic sequence with list of variants) more difficult

to handle for our purposes than the human CEU NA12878 data that we eventually used.

Likewise, for the microbiome task, we initially planned to apply our pipelines to several

microbiome sample types, but eventually decided to focus on a skin microbiome, since skin

samples tend to contain abundant viruses and multiple datasets may be available due to ease of

sampling.

RNA-seq Team

Our original goals were very ambitious, especially the task of determining RNA editing

without DNA controls. We were interested in looking at the variants in paired cancer samples,

and spent a fair amount of time to find an appropriate dataset. We decided to align the samples

using HISAT and determine the types and counts of variants (particularly A-I transitions) that

may suggest RNA editing. We also wanted to determine variants in genes and then possibly

correlate the genes to Gene Ontology.

We discussed a variety of aligners, such as STAR (48) and HISAT (49), which are very

fast. Information about the recently released HISAT program was shared via the Google Group

prior to the start of the hackathon so everyone had a chance to review this program. We selected

HISAT because of its speed, a decision partly driven by the time constraints of the hackathon.

We encountered some technical difficulties processing these in HISAT, so we ran the dataset

with the 3 pairs of tumor/normal using tophat and bowtie so that we had some results for

downstream processing, while another team member continued to develop the HISAT portion of

the pipeline.

We selected bambino as our variant caller based on team members' past successes with

using this tool. A collection of Python and Perl scripts was written to filter out unmapped and

low-quality reads and, more importantly, multi-mapped reads that did not map to a unique locus

within the genome, since bambino would call each of these multiple alignments separately. The

BAMs also had to be sorted by chromosome to prepare input for bambino. Bambino was then

used to generate a variant call table and a Perl script was created to filter for coverage on both

strands and give a sparser table for downstream analysis. Another program counted the variant

info. We then applied the Fisher's exact test to the data using R.

We discussed creating a command line to get gene ontologies of the set of genes, but

were concerned about users keeping up-to-date versions of the GO database. Gene ontology

could be determined by using web sites such as PANTHER (50) or DAVID (51, 52).

Technical Problems

DNA-seq Team

We found the SRA website challenging to use for locating data, and the quality of

available datasets was inconsistent. Although many data sources validate user-submitted files, a

number of files that had been improperly validated and thus were not usable. Some files were

corrupted and could not be used, such as those in BioProject PRJNA76777 (53). Our pipeline

needed datasets that had a paired tumor-normal sample from the same patient. For some datasets,

paired samples were not available, and other datasets were marked as being paired, when in fact

they were not, such as BioProject PRJNA217947 (54). In addition, we observed that multiple

datasets in the SRA database were missing the header information required to create BAM files

used by downstream analysis tools, such as BioProject PRJDB1903 (55). In other cases, SRA

data were found to be malformed, and caused certain tools to crash. Specifically, files from

BioProject PRJNA268172 (27) contained reads with differing length sequence and quality scores

(e.g. 34 bases of sequences, 70 bases of quality information). Files with such mismatches cannot

be used in SAMtools to convert to BAM files, as a difference in these field lengths is

inconsistent with the SAM format specification (56).

We also encountered problems with upstream bioinformatics code quality, such as poor

or incorrect documentation. The tools we employed had a variety of installation methods, and

few were available for easy installation through a package manager. For example, core software,

such as R version 3, was not available as a package from the operating system vendor. Installing

from a third-party repository is not complex, but may be daunting to someone inexperienced in

systems administration.

Epigenomics Team

When searching for epigenetic datasets that belong to a given cell type, we found that in

many cases all of the necessary data were not available in one centralized location. Thus, we had

to search through multiple websites and databases to find enough epigenetic data for a given cell

type we wanted to model. In some cases, the metadata for a given file was either corrupt or

unavailable. In other cases, the assembly used to align reads for a given set of files was not

clearly indicated, so these files were discarded. When dealing with wiggle (wig) and bigWig

files, sometimes the format of the file was inconsistent and needed to be edited on the fly.

Metagenomics Team

Technical difficulties generally were resolved expediently, but still hindered timely

analysis within the hackathon context. For example, some Amazon EC2 nodes would suddenly

become completely unresponsive for unexplained reasons, requiring that we shut down and re-

initiate the nodes. By the end of the hackathon, results were only available from the pipelines

that used the SRA BLAST, in part because the SRA BLAST took about an order of magnitude

less computing time than the standard blast program. In both cases, many Amazon compute

nodes were available, but only the SRA BLAST was able to handle the large volume of human

genome and human microbiome read data efficiently. In contrast, a huge amount of the

processing power available to the standard blast program (several tens of nodes) was simply

wasted while the program waited for data.

RNA-seq Team

It is important to recognize the difficulties of variant calling, especially with RNA-seq

data. First, bias impacts genes expressed at lower levels. As gene expression itself varies from

sample to sample, depth of coverage for any particular variant may differ. For instance, a variant

in a sample with high gene expression would be called without difficulties, but may not be called

in a sample that also carries the variant but whose expression is too low to call with confidence.

Another source of variance lies within the heterogeneity of the tissue sample. Most tissue

samples harbor multiple cell types, and not all of these cells will carry a somatic mutation. This

problem is encountered in both DNA-seq and RNA-seq data, but results can be difficult to

interpret on a per-variant basis when the fluctuation in overall coverage in gene expression is

also considered. Thus, we decided to deal with overall global effects rather than selecting

particular singular changes.

Project Results

DNA-seq Team

The test dataset was downloaded from SRA website. The SRA Toolkit utility called

prefetch allows the user to download SRA data files, but we found it initially troublesome to use

due to configuration and storage issues; by default, prefetch stores all files in user home

directories, which are often limited in storage capacity. We therefore wrote a faster web-scraper

script to download the files from the SRA website. Given our time limitations, we had to rely on

the user-submitted aligned and trimmed files, but we recommend that files submitted to the SRA

should be validated prior to upload.

Our pipeline was designed to find somatic mutations using five different algorithms, filter

and annotate the mutations, and compare the predicted mutations between matched tumor-

normal samples. However, due to time constraints and initial difficulties with finding an

appropriate data set and software installation, we were unable to complete our analysis. A

diagram of the final DNA-seq Team pipeline design is presented in Fig 3.

Figure 3. DNA-seq Team pipeline.

Epigenomics Team

We sought to rectify previously described inconsistencies in analyses by developing a

more efficient, novel pipeline. Our pipeline uses RNA-seq counts, ChIP-seq peaks, and DNA

methylation data in order to generate a model to predict relationships between gene expression

and epigenetic data. These models can then be used to predict changes in gene expression with

respect to changes in these epigenetic signals. Publicly available datasets can be utilized to

generate a model, which investigators can then use to predict the state of the chromatin based on

their own epigenetic data. The pipeline uses a combination of Python, R, and command line-

based tools.

For each gene in a given cell type, epigenetic marks positioned locally to the gene are

considered, as are distal enhancer elements that may also play in a role in that gene's expression.

To calculate the local epigenetic effects on transcription, an arbitrary distance on the 5' and 3'

ends of a gene is binned into regions and the scores of epigenetic marks that reside in each of

these bins are collected. The distal effect of transcription on a given gene is given by peak scores

of enhancer elements that are at most one megabase (Mb) upstream or downstream of the gene.

The scores for each epigenetic mark and enhancer for a given gene are standardized and

stored in a data matrix, where each row corresponds to a given gene for a given sample condition

or cell type. Transcript gene counts generated from RNA-seq data are also stored. This pipeline

generates a unique model for each gene in a given cell type by considering the gene count values

as Y-values and each of the epigenetic scores as X-values. Corresponding coefficients are

calculated for each X-value. Investigators can use these coefficients to input a new set of

epigenetic data and receive a testable hypothesis of predicted levels of expression for each gene

based on the new epigenetic data. Over time, different datasets can be used to train a given

model to make it more reliable. A diagram of the final DNA-seq Team pipeline is presented in

Fig 4.

Figure 4. Epigenomics Team pipeline.

Metagenomics Team

Although the goals were similar across all six of our pipelines, differences in file formats

and analysis approaches between the pipelines required the team to split their efforts rather than

work together on a single pipeline. One result of this fragmentation was some lack of consistency

in analytical methods (for example, choice of query versus database) between the pipelines.

Moreover, due to time limitations of the hackathon only one assembly was completed: the

ABySS assembly of the NA12878 human genome. Likewise, while we completed a versatile

script for conversion of FASTQ files to SRA format with the latf-load tool, time allowed only for

its demonstration on a single human microbiome sample.

Initially our plan included comparison of ERV sequence abundances between NA12878

genomes sequenced by several different sequencing technologies. Likewise, we initially planned

to compare viral sequence abundances between several different microbiome sample types. Due

to the complexity of these tasks, we decided to demonstrate our pipelines with a single sample

type for each application: Illumina HiSeq 2000 reads from NA12878 and a single sample from

the right retroauricular crease for the HMP application. Of the six pipelines that were planned

and designed, we built four (pipelines 1-3 and 5).

We found that the most successful approach for searching a human genome for

endogenous retroviruses was to use reads converted to SRA format (pipeline 2) via latf-load. The

blastn in pipeline 2 was completed in 50-60 minutes. For pipeline 1, while an assembly of

NA12878 was completed using ABySS within the time constraints of the hackathon, the blastn

search using the assembled contigs to query the ERV database required excessive computational

time; after more than 4 hours using 30 cores, the search still had not finished. In contrast, the

blastn for pipeline 3 finished in 5 hours. Part of the increased time for the blastn search in

pipeline 3 may have been due to alteration of the FASTA database by merging of forward and

reverse paired-ends.

Pipeline 5 includes a set of scripts that we developed to create a versatile pipeline for

searching a human microbiome sample for all viruses. These scripts may be adjusted to conduct

BLAST searches using other types of SRA files. A shell script downloads the relevant datasets

for the assembled and non-assembled sequences from HMP as well as for total viral sequences

from RefSeq. Scripts and a wrapper, written in R, were developed to convert FASTQ data to

SRA format with the latf-loader tool, convert the loaded data to .kar format, run a BLAST search

with the blast_vdb command, and parse the data into a viral-by-sample count matrix. The

resulting sparse matrix may be normalized and handled in a way similar to previously published

methods for sparse matrices of high-throughput 16S survey data (21). Additional available code

executes blastn on the assembled contigs. A diagram of the final Metagenomics Team pipeline is

presented in Fig 5.

Figure 5: Metagenomics Team pipeline.

RNA-seq Team

We developed and ran a Python script that reads a user-defined manifest file to extract

the read sequence information from the SRA files, stores the data in FASTQ format, and

launches the jobs to align the sequences using HISAT. Due to technical difficulties and time

constraints, we decided to manually download and process a smaller set of 3 pairs of

tumor/normal samples, as opposed to the set of 18 pairs we had initially considered. We aligned

the sequences using HISAT to prepare the data for use in subsequent parts of the pipeline. The

aligned SAM files were filtered to remove the unmapped, low-quality or ambiguous reads, such

as reads that map at multiple different locations.

The filtered data were run through bambino to create a variant call table in which each

line contains a call variant at a particular location within the genome and the reference base at

the same location. We counted nucleotide change variants in the tumor and normal samples and

ran a Fisher's exact statistical test using R to identify potential RNA editing. We found no

significant global changes of overrepresentation, but it is important to recognize the limitations

of our small sample size and our focus on specific changes. RNA editing most likely only

comprises a small number of A to G variants, and we would not be able to identify these changes

by considering global total numbers as opposed to looking at each site's overall counts

individually. This limitation does not affect overrepresentation in a global manner, but a small

set of specific local changes might not be identified with this study design.

Before the end of the hackathon, we were able to use the initial Python script to

download all 36 samples and launch the alignment tool jobs, but were able to complete fewer

than 10 samples given the amount of time required to finish debugging. However, when

completed, this automation script will greatly simplify the process of accessing and launching of

alignment jobs for RNA-seq datasets. A diagram of the final RNA-seq Team pipeline is

presented in Fig 6.

Figure 6: RNA-seq Team pipeline.

Discussion and Conclusions

Feedback from hackathon participants was generally positive, and the enthusiasm that participants felt was evident during the event. Participants voluntarily stayed past the planned ending time each night, and many participants did not even want to take a break when lunch arrived. Even more than a week after the hacakathon had ended, teams continued to communicate about and work on the problems, as well as this paper.

Every participant in the hackathon contributed not only to the research but also to drafting the paper. Each group appointed a lead writer, who worked closely with the librarian editor and coordinated with the other members of their team. Because each of the team members worked on different parts of the project, every individual wrote at least a portion of the sections of the paper covering their work. The use of Google Docs allowed multiple authors to work on the paper simultaneously and all changes to be reflected in real time. Google Docs' comment functionality also facilitated communication among authors. Once the writing was considered complete, the librarian editor organized and edited the draft in order to create a coherent and consistent paper, then returned this final draft to all authors for their approval. Though coordinating with so many authors is challenging, here we demonstrated that it is possible for a large group of individuals to contribute substantively to an article.

Participants reported that they appreciated having structured roles within the teams. Team leads were also important for the success of the team, though their presence was not necessary for the entire hackathon. For example, inclement weather on the second day prevented one of the team leads from attending, but the team still made progress on pipeline production. Given that members of each team came from diverse backgrounds with experience working with a multitude of different data types and resources, the hackathon promoted innovation through team

science and consensus-building. For example, it was essential that each pipeline utilize an

appropriate test dataset, but many teams had difficulty with data that were located across

multiple repositories or could not be used due to errors in metadata or formatting. Thus, teams

had to brainstorm other datasets to use or create new ways to process the data. Because each

problem encompassed technical challenges inherent in many biological fields, teams needed to

consolidate ideas from each member. This allowed teams to not only transcend the difficult data

landscape, but fostered a strong learning environment.

Although the ultimate goal of the hackathon was to solve biological problems,

participants emphasized that they appreciated this unique opportunity for career development

and networking. Participants with strong backgrounds in computer science effectively mentored

those who were less computationally savvy, and those with strong biology backgrounds were

able to share insights with those who lacked this expertise. Additionally, the hackathon brought

together individuals from different research communities who otherwise may have never met and

created the potential for establishing new collaborations. In particular, participants early in their

careers were able to meet prominent researchers in various fields and receive helpful training

advice from the more senior participants. We anticipate that the participants will share their

experiences upon returning to their respective institutes.

The organizers learned some valuable lessons from this event. Surprisingly, although the

organizers had kept the goals somewhat loosely structured, participants generally asked for more

structure, particularly concerning datasets. In the future, the organizers intend to prepare videos

for team members concerning the scientific directions of the projects prior to the event. Other

informational materials distributed in advance of the event could help participants learn how to

complete tasks that took time away from pipeline development, such as how to locate and

download datasets. Specific attention will be paid to using the SRA SDK to process small parts

of many genomes simultaneously. One team was unable to complete their pipeline, and other

teams were affected by time constraints, so moving some of the preparatory work of locating and

downloading datasets would help ensure that the teams had adequate time for more substantive

work on the pipelines.

From an institutional perspective, the hackathon was also helpful as a means to test NCBI

public data repositories. Over the course of this hackathon, several technical issues with respect

to data storage, metadata and corruptions were illuminated. These issues as well as constructive

feedback about how NCBI should host data were discussed directly with NCBI Director David

Lipman.

Finally, we hope that this hackathon will help to stimulate the community to continue to

improve these pipelines. We chose these topics and questions because they are of interest to

many biologists and introductory bioinformaticians. Because the data is publicly available,

investigators should be able to access the datasets from NCBI in order to replicate the work done

in creating these pipelines. We encourage members of the community to extend, expand and alter

these pipelines, which are licensed under a Creative Commons Attribution License (CC-BY). We

hope that the community will continue working with these pipelines to suit their needs and repost

them as they see fit.

664 Acknowledgements

669   guidance about BLAST.

References

1.   Schadt EE, Linderman MD, Sorenson J, Lee L, Nolan GP. Computational solutions to large-scale
data management and analysis. Nature reviews Genetics. 2010;11(9):647-57. doi: 10.1038/nrg2857.
PubMed PMID: PMC3124937.
2.   Strauss KA, Puffenberger EG, Morton DH. One Community's Effort to Control Genetic Disease.
American Journal of Public Health. 2012;102(7):1300-6. doi: 10.2105/AJPH.2011.300569. PubMed PMID:
PMC3477994.
3.   Dewey FE, Grove ME, Pan C, Goldstein BA, Bernstein JA, Chaib H, et al. Clinical interpretation
and implications of whole-genome sequencing. Jama. 2014;311(10):1035-45. Epub 2014/03/13. doi:
10.1001/jama.2014.1717. PubMed PMID: 24618965; PubMed Central PMCID: PMCPmc4119063.
4.   Palomaki GE, Melillo S, Neveux L, Douglas MP, Dotson WD, Janssens AC, et al. Use of genomic
profiling to assess risk for cardiovascular disease and identify individualized prevention strategies--a
targeted evidence-based review. Genetics in medicine : official journal of the American College of
Medical Genetics. 2010;12(12):772-84. Epub 2010/11/04. doi: 10.1097/GIM.0b013e3181f8728d.
PubMed PMID: 21045709.
5.   Celi LA, Ippolito A, Montgomery RA, Moses C, Stone DJ. Crowdsourcing Knowledge Discovery
and Innovations in Medicine. Journal of Medical Internet Research. 2014;16(9):e216. doi:
10.2196/jmir.3761. PubMed PMID: PMC4180345.
6.   The Health 2.0 Developer Challenge. Health 2.0's Washington DC HD&IW Code-a-thon:
Preventing Obesity 2012 [cited 2015 January 13]. Available from:
http://www.health2con.com/devchallenge/washington-dcs-hdi-code-a-thon-preventing-obesity/.
7.   Illumina. Illumina BaseSpace Worldwide Developers Conference (WWDC) 2014 [cited 2015
January 13]. Available from: http://eventregistration.illumina.com/events/illumina-basespace-
worldwide-developers-conference-at-embl-heidelberg/event-summary-
3fd0d62eb6d94cc2bc017d682e9bca51.aspx.
8.   HelpMeViz. Hackathon: Women's Empowerment & Nutrition 2014 [cited 2015 January 13].
Available from: http://helpmeviz.com/2014/06/28/hackathon-womens-empowerment-nutrition/.
9.   DePasse JW, Carroll R, Ippolito A, Yost A, Santorino D, Chu Z, et al. Less noise, more hacking:
how to deploy principles from MIT's hacking medicine to accelerate health care. International journal of
technology assessment in health care. 2014;30(3):260-4. Epub 2014/08/07. doi:
10.1017/s0266462314000324. PubMed PMID: 25096225.
10.   Cancer Genome Atlas Research Network. Comprehensive genomic characterization of squamous
cell lung cancers. Nature. 2012;489(7417):519-25. Epub 2012/09/11. doi: 10.1038/nature11404.
PubMed PMID: 22960745; PubMed Central PMCID: PMCPmc3466113.
11.   Edmonson MN, Zhang J, Yan C, Finney RP, Meerzaman DM, Buetow KH. Bambino: a variant
detector and alignment viewer for next-generation sequencing data in the SAM/BAM format.
Bioinformatics (Oxford, England). 2011;27(6):865-6. Epub 2011/02/01. doi:
10.1093/bioinformatics/btr032. PubMed PMID: 21278191; PubMed Central PMCID: PMCPmc3051333.
12.   Koboldt DC, Zhang Q, Larson DE, Shen D, McLellan MD, Lin L, et al. VarScan 2: somatic mutation
and copy number alteration discovery in cancer by exome sequencing. Genome research.

2012;22(3):568-76. Epub 2012/02/04. doi: 10.1101/gr.129684.111. PubMed PMID: 22300766; PubMed
Central PMCID: PMCPmc3290792.
13.   Cibulskis K, Lawrence MS, Carter SL, Sivachenko A, Jaffe D, Sougnez C, et al. Sensitive detection
of somatic point mutations in impure and heterogeneous cancer samples. Nature biotechnology.
2013;31(3):213-9. Epub 2013/02/12. doi: 10.1038/nbt.2514. PubMed PMID: 23396013; PubMed Central
PMCID: PMCPmc3833702.
14.   Xu H, DiCarlo J, Satya RV, Peng Q, Wang Y. Comparison of somatic mutation calling methods in
amplicon and whole exome sequence data. BMC genomics. 2014;15:244. Epub 2014/04/01. doi:
10.1186/1471-2164-15-244. PubMed PMID: 24678773; PubMed Central PMCID: PMCPmc3986649.
15.   Pallen MJ. Diagnostic metagenomics: potential applications to bacterial, viral and parasitic
infections. Parasitology. 2014;141(14):1856-62. Epub 2014/03/01. doi: 10.1017/s0031182014000134.
PubMed PMID: 24576467; PubMed Central PMCID: PMCPmc4255322.
16.   Barbulescu M, Turner G, Seaman MI, Deinard AS, Kidd KK, Lenz J. Many human endogenous
retrovirus K (HERV-K) proviruses are unique to humans. Current biology : CB. 1999;9(16):861-8. Epub
1999/09/02. PubMed PMID: 10469592.
17.   Wang-Johanning F, Frost AR, Jian B, Epp L, Lu DW, Johanning GL. Quantitation of HERV-K env
gene expression and splicing in human breast cancer. Oncogene. 2003;22(10):1528-35. Epub
2003/03/12. doi: 10.1038/sj.onc.1206241. PubMed PMID: 12629516.
18.   Pop M, Walker AW, Paulson J, Lindsay B, Antonio M, Hossain MA, et al. Diarrhea in young
children from low-income countries leads to large-scale alterations in intestinal microbiota composition.
Genome biology. 2014;15(6):R76. Epub 2014/07/06. doi: 10.1186/gb-2014-15-6-r76. PubMed PMID:
24995464; PubMed Central PMCID: PMCPmc4072981.
19.   Reyes A, Haynes M, Hanson N, Angly FE, Heath AC, Rohwer F, et al. Viruses in the faecal
microbiota of monozygotic twins and their mothers. Nature. 2010;466(7304):334-8. Epub 2010/07/16.
doi: 10.1038/nature09199. PubMed PMID: 20631792; PubMed Central PMCID: PMCPmc2919852.
20.   Waller AS, Yamada T, Kristensen DM, Kultima JR, Sunagawa S, Koonin EV, et al. Classification and
quantification of bacteriophage taxa in human gut metagenomes. The ISME journal. 2014;8(7):1391-
402. Epub 2014/03/14. doi: 10.1038/ismej.2014.30. PubMed PMID: 24621522; PubMed Central PMCID:
PMCPmc4069399.
21.   Paulson JN, Stine OC, Bravo HC, Pop M. Differential abundance analysis for microbial marker-
gene surveys. Nature methods. 2013;10(12):1200-2. Epub 2013/10/01. doi: 10.1038/nmeth.2658.
PubMed PMID: 24076764; PubMed Central PMCID: PMCPmc4010126.
22.   Han L, Vickers KC, Samuels DC, Guo Y. Alternative applications for distinct RNA sequencing
strategies. Briefings in bioinformatics. 2014. Epub 2014/09/24. doi: 10.1093/bib/bbu032. PubMed PMID:
25246237.
23.   Antonarakis ES, Lu C, Wang H, Luber B, Nakazawa M, Roeser JC, et al. AR-V7 and resistance to
enzalutamide and abiraterone in prostate cancer. The New England journal of medicine.
2014;371(11):1028-38. Epub 2014/09/04. doi: 10.1056/NEJMoa1315815. PubMed PMID: 25184630;
PubMed Central PMCID: PMCPmc4201502.
24.   Abecasis GR, Auton A, Brooks LD, DePristo MA, Durbin RM, Handsaker RE, et al. An integrated
map of genetic variation from 1,092 human genomes. Nature. 2012;491(7422):56-65. Epub 2012/11/07.
doi: 10.1038/nature11632. PubMed PMID: 23128226; PubMed Central PMCID: PMCPmc3498066.
25.   National Center for Biotechnology Information. ClinVar 2015 [cited 2015 January 13]. Available
from: http://www.ncbi.nlm.nih.gov/clinvar/.
26.   National Center for Biotechnology Information. SRA Toolkit 2015 [cited 2015 January 13].
Available from:
http://www.ncbi.nlm.nih.gov/Traces/sra/sra.cgi?cmd=show&f=software&m=software&s=software.

27.   National Center for Biotechnology Information. Whole exome sequencing in a case of sporadic
multiple meningiomas 2014 [cited 2015 January 13]. Available from:
http://www.ncbi.nlm.nih.gov/bioproject/?term=PRJNA268172.
28.   Perry A, Scheithauer BW, Stafford SL, Lohse CM, Wollan PC. "Malignancy" in meningiomas: a
clinicopathologic study of 116 patients, with grading implications. Cancer. 1999;85(9):2046-56. Epub
1999/05/01. PubMed PMID: 10223247.
29.   Rashid M, Robles-Espinoza CD, Rust AG, Adams DJ. Cake: a bioinformatics pipeline for the
integrated analysis of somatic variants in cancer genomes. Bioinformatics (Oxford, England).
2013;29(17):2208-10. doi: 10.1093/bioinformatics/btt371. PubMed PMID: PMC3740632.
30.   Stephens PJ, Tarpey PS, Davies H, Van Loo P, Greenman C, Wedge DC, et al. The landscape of
cancer genes and mutational processes in breast cancer. Nature. 2012;486(7403):400-4. Epub
2012/06/23. doi: 10.1038/nature11017. PubMed PMID: 22722201; PubMed Central PMCID:
PMCPmc3428862.
31.   Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, et al. The Sequence Alignment/Map
format and SAMtools. Bioinformatics (Oxford, England). 2009;25(16):2078-9. Epub 2009/06/10. doi:
10.1093/bioinformatics/btp352. PubMed PMID: 19505943; PubMed Central PMCID: PMCPmc2723002.
32.   Wang K, Li M, Hakonarson H. ANNOVAR: functional annotation of genetic variants from high-
throughput sequencing data. Nucleic acids research. 2010;38(16):e164. Epub 2010/07/06. doi:
10.1093/nar/gkq603. PubMed PMID: 20601685; PubMed Central PMCID: PMCPmc2938201.
33.   Danecek P, Auton A, Abecasis G, Albers CA, Banks E, DePristo MA, et al. The variant call format
and VCFtools. Bioinformatics (Oxford, England). 2011;27(15):2156-8. Epub 2011/06/10. doi:
10.1093/bioinformatics/btr330. PubMed PMID: 21653522; PubMed Central PMCID: PMCPmc3137218.
34.   Sadedin SP, Pope B, Oshlack A. Bpipe: a tool for running and managing bioinformatics pipelines.
Bioinformatics (Oxford, England). 2012;28(11):1525-6. Epub 2012/04/14. doi:
10.1093/bioinformatics/bts167. PubMed PMID: 22500002.
35.   National Center for Biotechnology Information. NIH Epigenomic Roadmap 2015 [cited 2015
January 5]. Available from: ftp://ftp.ncbi.nlm.nih.gov/pub/geo/DATA/roadmapepigenomics/.
36.   International Human Epigenome Consortium. IHEC Data Portal 2015 [cited 2015 January 13].
Available from: http://epigenomesportal.ca/ihec/grid.html.
37.   ENCODE Consortium. ENCODE: Encyclopedia of DNA Elements 2015 [cited 2015 January 13].
Available from: https://www.encodeproject.org/.
38.   National Center for Biotechnology Information. ERX069505: Whole Genome Sequencing of
human CEU NA12878 2015 [cited 2015 January 13]. Available from:
http://www.ncbi.nlm.nih.gov/sra/ERX069505%5Baccn%5D.
39.   BC Cancer Agency. ABySS: Assembly By Short Sequences - a de novo, parallel, paired-end
sequence assembler 2014 [cited 2015 January 13]. Available from:
http://www.bcgsc.ca/platform/bioinfo/software/abyss.
40.   Simpson JT, Wong K, Jackman SD, Schein JE, Jones SJ, Birol I. ABySS: a parallel assembler for
short read sequence data. Genome research. 2009;19(6):1117-23. Epub 2009/03/03. doi:
10.1101/gr.089532.108. PubMed PMID: 19251739; PubMed Central PMCID: PMCPmc2694472.
41.   National Institutes of Health. NIH Human Microbiome Project 2015 [cited 2015 January 13].
Available from: http://hmpdacc.org/.
42.   Chan TH, Lin CH, Qi L, Fei J, Li Y, Yong KJ, et al. A disrupted RNA editing balance mediated by
ADARs (Adenosine DeAminases that act on RNA) in human hepatocellular carcinoma. Gut.
2014;63(5):832-43. Epub 2013/06/15. doi: 10.1136/gutjnl-2012-304037. PubMed PMID: 23766440;
PubMed Central PMCID: PMCPmc3995272.

43.   National Center for Biotechnology Information. Transcriptome sequencing of human
hepatocellular carcinoma (human) 2011 [cited 2015 January 13]. Available from:
http://www.ncbi.nlm.nih.gov/bioproject/?term=PRJNA149267.
44.   Kim SK, Kim SY, Kim JH, Roh SA, Cho DH, Kim YS, et al. A nineteen gene-based risk score classifier
predicts prognosis of colorectal cancer patients. Molecular oncology. 2014;8(8):1653-66. Epub
2014/07/23. doi: 10.1016/j.molonc.2014.06.016. PubMed PMID: 25049118.
45.   National Center for Biotechnology Information. Gene expression profiling study by RNA-seq in
colorectal cancer (human) 2013 [cited 2015 January 13]. Available from:
http://www.ncbi.nlm.nih.gov/bioproject/?term=PRJNA218851.
46.   Meyer F, Paarmann D, D'Souza M, Olson R, Glass EM, Kubal M, et al. The metagenomics RAST
server - a public resource for the automatic phylogenetic and functional analysis of metagenomes. BMC
bioinformatics. 2008;9:386. Epub 2008/09/23. doi: 10.1186/1471-2105-9-386. PubMed PMID:
18803844; PubMed Central PMCID: PMCPmc2563014.
47.   Center for Bioinformatics and Computational Biology. metAMOS: assembly and analysis toolkit
for metagenomics 2015 [cited 2015 January 13]. Available from:
http://cbcb.umd.edu/software/metAMOS.
48.   Dobin A, Davis CA, Schlesinger F, Drenkow J, Zaleski C, Jha S, et al. STAR: ultrafast universal RNA-
seq aligner. Bioinformatics (Oxford, England). 2013;29(1):15-21. Epub 2012/10/30. doi:
10.1093/bioinformatics/bts635. PubMed PMID: 23104886; PubMed Central PMCID: PMCPmc3530905.
49.   Kim D, Langmead B, Salzberg S. HISAT: Hierarchical Indexing for Spliced Alignment of
Transcripts2014 2014-01-01 00:00:00.
50.   Mi H, Muruganujan A, Thomas PD. PANTHER in 2013: modeling the evolution of gene function,
and other gene attributes, in the context of phylogenetic trees. Nucleic acids research.
2013;41(Database issue):D377-86. Epub 2012/11/30. doi: 10.1093/nar/gks1118. PubMed PMID:
23193289; PubMed Central PMCID: PMCPmc3531194.
51.   Huang da W, Sherman BT, Lempicki RA. Systematic and integrative analysis of large gene lists
using DAVID bioinformatics resources. Nature protocols. 2009;4(1):44-57. Epub 2009/01/10. doi:
10.1038/nprot.2008.211. PubMed PMID: 19131956.
52.   Huang da W, Sherman BT, Lempicki RA. Bioinformatics enrichment tools: paths toward the
comprehensive functional analysis of large gene lists. Nucleic acids research. 2009;37(1):1-13. Epub
2008/11/27. doi: 10.1093/nar/gkn923. PubMed PMID: 19033363; PubMed Central PMCID:
PMCPmc2615629.
53.   National Center for Biotechnology Information. Sequencing of multiple tumors from a
neuroblastoma patient 2011 [cited 2015 January 13]. Available from:
http://www.ncbi.nlm.nih.gov/bioproject/?term=PRJNA76777.
54.   National Center for Biotechnology Information. Homo sapiens exome and transcriptome 2013
[cited 2015 January 13]. Available from: http://www.ncbi.nlm.nih.gov/bioproject/?term=PRJNA217947.
55.   National Center for Biotechnology Information. Whole exome analysis of myelodysplastic
syndromes 2014 [cited 2015 January 13]. Available from:
http://www.ncbi.nlm.nih.gov/bioproject/?term=PRJDB1903.
56.   The SAM/BAM Format Specication Working Group. Sequence Alignment/Map Format
Specication 2014 [cited 2015 January 13]. Available from: http://samtools.github.io/hts-
specs/SAMv1.pdf.
847