Tools and techniques for computational reproducibility

Stephen R. Piccolo[1][*], Adam B. Lee[1], Michael B. Frampton[2]

Department of Biology, Brigham Young University, Provo, UT, USA

Department of Computer Science, Brigham Young University, Provo, UT, USA

* Corresponding author: 4102 LSB, Brigham Young University, Provo, UT, 84602;

801-422-7116; Stephen_Piccolo@byu.edu

Abstract

When reporting research findings, scientists document the steps they followed so
that others can verify and build upon the research. When those steps have been
described in sufficient detail that others can retrace the steps and obtain similar
results, the research is said to be reproducible. Computers play a vital role in many
research disciplines and present both opportunities and challenges for
reproducibility. Computers can be programmed to execute analysis tasks, and those
programs can be repeated and shared with others. Due to the deterministic nature
of most computer programs, the same analysis tasks, applied to the same data, will
often produce the same outputs. However, in practice, computational findings often
cannot be reproduced, due to complexities in how software is packaged, installed,
and executed—and due to limitations in how scientists document analysis steps.
Many tools and techniques are available to help overcome these challenges. Here we
describe six such strategies. With a broad scientific audience in mind, we describe
strengths and limitations of each approach, as well as circumstances under which
each might be applied. No single strategy is sufficient for every scenario; thus we
emphasize that it is often useful to combine approaches.

Introduction

When reporting a research study, scientists document the steps they followed to obtain their results. If the description is comprehensive enough that they and others can repeat the procedures and obtain semantically consistent results, the findings are considered to be "reproducible"[1-6]. Reproducible research forms the basic building blocks of science, insofar as it allows researchers to verify and build on each other's work with confidence.

Computers play an increasingly important role in many scientific disciplines[7]. For example, in the United Kingdom, 92% of academic scientists use some type of software in their research, and 69% of scientists say their research is feasible only with software tools[8]. Thus efforts to increase scientific reproducibility should consider the ubiquity of computers in research.

Computers present both opportunities and challenges for scientific reproducibility. On one hand, due to the deterministic nature of most computer programs, computational analyses can be performed such that others can obtain exactly identical results when applied to the same input data[9]; accordingly, computational research can be held to a higher reproducibility standard than other types of research. On the other hand, in practice, scientists often cannot reproduce computational findings due to complexities in how software is packaged, installed, and executed—and due to limitations in how scientists document these steps[10]. This problem is acute in many disciplines, including genomics, signal processing, and ecological modeling[11-13], where data sets are large and computational tools are

evolving rapidly. However, the same problem can affect any scientific discipline that

requires computers for research, irrespective of data type or size. Seemingly minor

differences in computational approaches can have major influences on analytical

outputs[9,14-19]. The effects of these differences may meet or exceed those that result

from experimental factors[20].

Journal editors, funding agencies, governmental institutions, and individual

scientists have increasingly made calls for the scientific community to embrace

practices that support computational reproducibility[21-28]. This movement has been

motivated, in part, by scientists' failed efforts to reproduce previously published

analyses. For example, Ioannidis, et al. evaluated 18 published research studies that

used computational methods to evaluate gene-expression data but were able to

reproduce only 2 of those studies[29]. In many cases, failure to share the study's data

was the culprit; however, incomplete descriptions of software-based analyses were

also common. Nekrutenko and Taylor examined 50 papers that analyzed next-

generation sequencing data and observed that fewer than half provided any details

about software versions or parameters[30]. Recreating analyses that lack such details

can require hundreds of hours of effort[31,32] and may be impossible, even after

consulting the original authors. Worse, failure to reproduce research can lead to

retractions[33,34].

Noting such concerns, some journals have emphasized the value of placing

computer source code in open-access repositories, such as *GitHub*

(http://www.github.com) or *BitBucket* (http://www.bitbucket.org). In addition,

journals have extended requirements for "Methods" sections, now asking

researchers to provide detailed descriptions of 1) how to install software and its

dependencies and 2) what parameters and data-preprocessing steps were used in

analyses[7,21]. A recent Institute of Medicine report emphasized that, in addition to

computer code and research data, "fully specified computational procedures"

should be made available to the scientific community[22]. They elaborated that such

procedures should include "all of the steps of computational analysis" and that "all

aspects of the analysis need to be transparently reported"[22]. Such policies represent

important progress in the quest for better policies. However, it is ultimately the

responsibility of individual scientists to ensure that others can verify and build upon

their analyses.

Describing a computational analysis sufficiently—such that others can reexecute it,

validate it, and refine it—requires more than simply stating what software was

used, what commands were executed, and where to find the source code[10,24,35–37].

Software is executed within the context of an operating system (for example,

Windows, *Mac OS*, or *Linux*), which enables the software to interface with computer

hardware (Figure 1). In addition, most software relies on a hierarchy of software

dependencies, which perform complementary functions and must be installed

alongside the main software tool. One version of a given software tool or

dependency may behave differently or have a different interface than another

version of the same software. In addition, most analytical software offers a range of

parameters (or settings) that the user can specify. If any of these variables differs

from what the original experimenter used, the software may not execute properly or

analytical outputs may differ considerably from what the original experimenter

observed.

Scientists can use various tools and techniques to overcome these challenges and to

increase the likelihood that their computational analyses will be reproducible.

These techniques range in complexity from simple (e.g., providing written

documentation) to advanced (e.g., providing a "virtual" environment that includes

an operating system and all software necessary to execute the analysis). This review

describes six strategies across this spectrum. We describe strengths and limitations

of each approach, as well as circumstances under which each might be applied. No

single strategy will be sufficient for every scenario; therefore, in many cases, it will

be most practical to combine multiple approaches. This review focuses primarily on

the computational aspects of reproducibility. The related topics of empirical

reproducibility, statistical reproducibility, and data sharing have been described

elsewhere[38-44]. We believe that with greater awareness and understanding of

computational-reproducibility techniques, scientists—including those with limited

computational experience—will be more apt to perform computational research in

a reproducible manner.

Narrative descriptions are a simple but valuable way to support

computational reproducibility

The most fundamental strategy for enabling others to reproduce a computational

analysis is to provide a detailed, written description of the process. When reporting

computational results in a research article, authors customarily provide a narrative

that describes the software they used and the analytical steps they followed. Such

narratives can be invaluable in enabling others not only to evaluate the scientific

approach but also to reproduce the findings. In many situations—for example, when

software execution requires interaction from the user or when proprietary software

is used—narratives are the only feasible option for documenting such steps.

However, even when a computational analysis uses open-source software and can

be fully automated, narratives help others understand how to execute the analysis.

Although most research articles that use computational methods provide some type

of narrative, these descriptions often lack sufficient detail to enable others to retrace

those steps[29,30]. To ensure that others can reproduce a computational analysis,

narrative descriptions should indicate the operating system(s), software

dependencies, and analytical software that were used and where to obtain them. In

addition, narratives should indicate the exact software versions used, the order in

which they were executed, and all non-default parameters that were specified. Such

descriptions should account for the fact that computer configurations differ vastly,

even for computers that use the same operating system. A limitation of narratives is

that it can be difficult to remember such details post hoc; thus the documentation

process will be most efficient when scientists record these steps throughout the

research process, rather than at the time of manuscript preparation.

The following sections describe techniques for automating software execution and

thus characterizing analytical steps in computer-readable formats. These techniques

can diminish the need for scientists to write narratives. However, because it is often

not practical to automate all computational steps, we expect that, for the foreseeable

future, narratives will play a vital role in enabling computational reproducibility.

141 Computer code and scripts can automate the analysis process

Scientific software can often be executed in an automated manner via text-based

commands. In these cases, no amount of narrative can substitute for providing the

actual commands that were used to automate the analysis. Using a command-line

interface, a scientist can indicate which software program(s) to execute and which

parameter(s) to use. When multiple commands must be executed, they can be

compiled into scripts, which specify the order in which the commands should be

executed and whether they can be executed in parallel. In many cases, scripts also

include commands for installing and configuring software. Such scripts serve as

valuable documentation not only for individuals who wish to reexecute the analysis

but also for the researcher who performed the original analysis.

When writing command-line scripts, it is essential to document any software

dependencies and input data required for each step in the analysis. The *Make*

utility[45] provides one way to specify such requirements[35]. Before any command is

executed, *Make* verifies that each documented dependency is available. Accordingly,

researchers can use *Make* to specify the full hierarchy of operating-system

components and dependent software that must be present. In addition, *Make* can be

configured to automatically identify any commands that can be executed in parallel,

potentially reducing the amount of time required to execute the analysis. Although

Make was designed originally for UNIX-based operating systems (such as *Mac OS* or

Linux), similar utilities have since been developed for *Windows* operating systems[46].

Box 1 lists various other utilities that can be used to automate software execution.

In many scientific analyses, authors write custom computer code. Such code may

perform relatively simple tasks, such as reformatting data files or invoking third-

party software libraries. In other cases, code may constitute a manuscript's key

intellectual contribution. In either situation, when authors provide code alongside a

manuscript, readers can evaluate the authors' computational approach in full

detail[47]. A common way to manage code is to place it in a source-control repository

such as *Git* (http://git-scm.com) or *Mercurial* (http://mercurial.selenic.com). Such

repositories then can be shared via openly accessible services like *GitHub*

(https://github.com) or *Bitbucket* (https://bitbucket.org/), along with a full history

of changes that have been made to the code. Other researchers may then access

previous versions of the code, extend the code, and contribute revisions[48].

Although it is common for code to be published as a standalone software package,

much can be gained from incorporating code into a preexisting software framework.

Bioconductor[49], written in the *R* statistical programming language[50], is a popular

framework that contains hundreds of software packages for analyzing genomic

data[51]. The *Bioconductor* framework facilitates the processes of versioning,

documenting, and distributing code. Once computer code has been incorporated

into a *Bioconductor* software package, other researchers can find, download, install,

and configure it on most operating systems with relative ease. In addition,

Bioconductor installs software dependencies automatically. These features ease the

process of performing a scientific analysis and enabling other scientists to

reproduce the work. Various software frameworks exist for other scientific

disciplines[52–57].

Box 1: Utilities that can be used to automate software execution.

- *GNU Make*[45] and Make for Windows[46]: Tools for building software from source files and for ensuring that the software's dependencies are met.
- *Snakemake*[58] = An extension of Make that provides a more flexible syntax and makes it easier to execute tasks in parallel.
- *BPipe*[59] = A tool that provides a flexible syntax for users to specify commands to be executed; it maintains an audit trail of all commands that have been executed.
- *GNU Parallel*[60] = A tool for executing commands in parallel across one or more computers.
- *Makeflow*[61] = A tool that can execute commands simultaneously on various types of computer architectures, including computer clusters and cloud environments.

Literate programming combines narratives directly with code

Although computer code and narratives support reproducibility individually,

additional value can be gained from combining these entities. Even though

computer code may be provided alongside a research article, other scientists may

have difficulty interpreting how the code accomplishes its scientific objectives. A

longstanding way to address this problem is via code comments, which are human-

readable annotations interspersed throughout computer code. Going a step further,

scientists can use a technique called *literate programming*[62]. With this approach, the

scientist writes a narrative of the scientific analysis and intermingles code directly

within the narrative. As the code is executed, a document is created that includes the

code, narratives, and any outputs that the code produces. Accordingly, literate

programming helps ensure that readers understand exactly how a particular result

was obtained. In addition, this approach motivates the scientist to keep the target

audience in mind when performing a computational analysis, rather than simply to

write code that a computer can parse[62]. Consequently, by reducing barriers of

understanding among scientists, literate programming can help to engender greater

trust in computational findings.

One popular literate-programming tool is *IPython*[63]. Using its Web interface,

scientists can create interactive "notebooks" that combine code, data, mathematical

equations, plots, and rich media[64]. As its name implies, *IPython* was designed

originally for the *Python* programming language; however, a recent iteration of the

tool, *Jupyter* (https://jupyter.org), makes it possible to execute code in a variety of

programming languages. Such functionality may be important to scientists who

prefer to combine the strengths of different programming languages.

knitr[65] has also gained considerable popularity as a literate-programming tool. It is

written in the *R* programming language and thus can be integrated seamlessly with

the array of statistical and plotting tools available in that environment. However,

like *IPython*, *knitr* can execute code written in multiple programming languages.

Commonly, *knitr* is applied to documents that have been authored using *RStudio*

(http://www.rstudio.com), an open-source tool with advanced editing and package-

management features.

IPython notebooks and *knitr* reports can be saved in various output formats,

including HTML and PDF. Increasingly, scientists include such documents with

journal manuscripts as supplementary material, enabling others to repeat analysis

steps and recreate manuscript figures[66-69].

Literate-programming tools are suitable for applied research because they enable

scientists to apply computational methods in specific scenarios. However, scientists

often desire to generalize code so it can be applied in additional contexts. Current

literate-programming tools may not be well suited to extensive software

development and testing. However, they can aid in the process of illustrating

scenarios in which the software might be applied.

Workflow-management systems enable reproducible software

execution via a graphical user interface

Writing computer code and scripts may seem daunting to many researchers.

Although various courses and tutorials are helping to make this task less

formidable[70-73], many scientists use "workflow management systems" to facilitate

the process of executing scientific software[74]. Typically managed via a Web

interface, a workflow management system enables scientists to upload data and

process it using existing tools. For multistep analyses, the output from one tool can

be used as input to another tool, resulting in a series of commands known as a

workflow.

Galaxy[75,76] has gained considerable popularity within the bioinformatics

community—especially for performing next-generation sequencing analysis. As

users construct workflows, *Galaxy* provides descriptions of how software

parameters should be used, examples of how input files should be formatted, and

links to relevant discussion forums. To help with processing large data sets and

computationally complex algorithms, *Galaxy* also provides an option to execute

workflows on cloud-computing services[77]. In addition, researchers can share

workflows with each other (see https://usegalaxy.org/workflow/list_published);

this feature has enabled the *Galaxy* team to build a community that helps to

encourage reproducibility, define best practices, and reduce the time required for

novices to get started.

Various other workflow systems are freely available to the research community (see

Box 2). For example, *VisTrails* is used by researchers from many disciplines,

including climate science, microbial ecology, and quantum mechanics[78]. It enables

scientists to design workflows visually, connecting data inputs with analytical

modules and the resulting outputs. In addition, *VisTrails* tracks a full history of how

each workflow was created. This capability, referred to as "retrospective

provenance", makes it possible for others not only to reproduce the final version of

an analysis but also to examine previous incarnations of the workflow and examine

how each change influenced analytical outputs[79].

Box 2: Workflow management tools freely available to the research community.

- Galaxy[75,76] - https://usegalaxy.org
- VisTrails[78] - http://www.vistrails.org
- Kepler[80] - https://kepler-project.org
- iPlant Collaborative[81] - http://www.iplantcollaborative.org
- GenePattern[82,83] - http://www.broadinstitute.org/cancer/software/genepattern
- Taverna[84] - http://www.taverna.org.uk
- LONI Pipeline[85] - http://pipeline.bmap.ucla.edu

Although workflow-management systems offer many advantages, users must accept

tradeoffs. For example, although the teams that develop these tools often provide

public servers where users can execute workflows, many scientists share these

limited resources, so the public servers may not have adequate computational

power or storage space to execute large-scale analyses in a timely manner. As an

alternative, many scientists install these systems on their own computers; however,

configuring and supporting them requires time and expertise. In addition, if a

workflow tool does not yet provide a module to support a given analysis, the

scientist must create a new module to support it. This task constitutes additional

overhead; however, utilities such as the *Galaxy Tool Shed*

(https://toolshed.g2.bx.psu.ed) are helping to facilitate this process.

Virtual machines encapsulate an operating system and software dependencies

Whether an analysis is executed at the command line, within a literate-programming notebook, or via a workflow-management system, an operating system and software dependencies must be installed before the analysis can be performed. The process of identifying, installing, and configuring such dependencies consumes a considerable amount of scientists' time. Different operating systems (and versions thereof) may require different installation and configuration steps. Furthermore, earlier versions of software dependencies, which may currently be installed on a given computer, may be incompatible with—or produce different outputs than—newer versions.

One solution is to use virtual machines, which can encapsulate an entire operating system and all software, scripts, and code necessary to execute a computational analysis[86,87] (Figure 2). Using virtualization software—such as *VirtualBox* or *VMWare* (see Box 3)—a virtual machine can be executed on practically any desktop, laptop, or server, irrespective of the main ("host") operating system on the computer. For example, even though a scientist's computer may be running a *Windows* operating system, the scientist may perform an analysis on a *Linux* operating system that is running concurrently—within a virtual machine—on the same computer. The scientist has full control over the virtual ("guest") operating system and thus can install software and modify configuration settings as necessary. In addition, a virtual machine can be constrained to use limited computational

resources (e.g., computer memory, processing power); thus multiple virtual

machines can be executed simultaneously on the same computer without impacting

each other's performance. After executing an analysis, the scientist can export the

entire virtual machine to a single, binary file. Other scientists can then use this file to

reconstitute the same computational environment that was used for the original

analysis. With a few exceptions (see Discussion), these scientists will obtain exactly

the same results that the original scientist obtained. This process provides the

added benefits that 1) the scientist must only document the installation and

configuration steps for a single operating system, 2) other scientists need only

install the virtualization software and not individual software components, and 3)

analyses can be reexecuted indefinitely, so long as the virtualization software

remains compatible with current computer systems[88]. Also useful, a team of

scientists can employ virtual machines to ensure that each team member has the

same computational environment, even though the team members may have

different configurations on their host operating systems.

One criticism of using virtual machines to support computational reproducibility is

that virtual-machine files are large (typically multiple gigabytes); this imposes a

barrier for researchers to share such files with the research community. One option

is to use cloud-computing services (see Box 4). Scientists can execute an analysis in

the cloud, take a "snapshot" of their virtual machine, and share it with others in that

environment[86,89]. Cloud-based services typically provide repositories where virtual-

machine files can be stored and shared easily among users. Despite these

advantages, some researchers may prefer that their data reside on local computers,

rather than in the cloud—at least while the research is being performed. In addition,

cloud-based services may use proprietary software, so virtual machines may only be

executable within each provider's infrastructure. Furthermore, to use a cloud-

service provider, scientists may need to activate a fee-based account.

Another criticism of using virtual machines to support computational

reproducibility is that the software and scripts used in the analysis will be less easily

accessible to other scientists—details of the analysis are effectively concealed

behind a "black box"[90]. Although other researchers may be able to reexecute the

analysis within the virtual machine, it may be more difficult for them to understand

and extend the analysis[90]. This problem can be ameliorated when all narratives,

scripts, and code are stored in public repositories—separate from the virtual

machine—and then imported when the analysis is executed[91]. Another solution is to

use a prepackaged virtual machine, such as *Cloud BioLinux*, that contains a variety of

software tools commonly used within a given research community[92].

Scientists can automate the process of building and configuring virtual machines

using tools such as *Vagrant* or *Vortex* (see Box 3). For either tool, users can write

text-based configuration files that provide instructions for building virtual machines

and allocating computational resources to them. In addition, these configuration

files can be used to specify analysis steps[91]. Because these files are text based and

relatively small (usually a few kilobytes), scientists can share them easily and track

different versions of the files via source-control repositories. This approach also

mitigates problems that might arise during the analysis stage. For example, even

when a computer's *host* operating system must be reinstalled due to a computer

hardware failure, the virtual machine can be recreated with relative ease.

Box 3: Virtual-machine software.

Virtualization hypervisors:

- VirtualBox (open source) - https://www.virtualbox.org
- Xen (open source) - http://www.xenproject.org
- VMWare (partially open source) - http://www.vmware.com

Virtual-machine management tools:

- Vagrant (open source) - https://www.vagrantup.com
- Vortex (open source) - https://github.com/websecurify/node-vortex

---

Box 4: Commercial cloud-service providers.

- Amazon Web Services - http://aws.amazon.com
- Rackspace Cloud - http://www.rackspace.com/cloud
- Google Cloud Platform - https://cloud.google.com/compute
- Windows Azure - https://azure.microsoft.com

---

349 Software containers ease the process of installing and configuring

350 dependencies

Software containers are a lighter-weight alternative to virtual machines. Like virtual

machines, containers encapsulate operating-system components and software into a

single package that can be shared with others. Thus, as with virtual machines,

analyses executed within a software container should produce identical outputs,

irrespective of the underlying operating system or whatever software may be

installed outside the container (see Discussion for caveats). As is true for virtual

machines, multiple containers can be executed simultaneously on a single computer,

and each container may contain different software versions and configurations.

However, whereas virtual machines include an entire operating system, software

containers interface directly with the computer's main operating system and extend

it as needed (Figure 3). This design provides less flexibility than virtual machines

because containers are specific to a given type of operating system; however,

containers require considerably less computational overhead than virtual machines

and can be initialized much more quickly[93].

The open-source *Docker* utility (https://www.docker.com)—which has gained

popularity among informaticians since its release in 2013—provides the ability to

build, execute, and share software containers for Linux-based operating systems.

Users specify a *Docker* container's contents using text-based commands. These

instructions can be placed in a "Dockerfile," which other scientists can use to rebuild

the container. As with virtual-machine configuration files, Dockerfiles are text

based, so they can be shared easily and can be tracked and versioned in source-

control repositories. Once a *Docker* container has been built, its contents can be

exported to a binary file; these files are generally much smaller than virtual-machine

files, so they can be shared more easily—for example, via *DockerHub*

(https://hub.docker.com).

A key feature of *Docker* containers is that their contents can be stacked in distinct

layers (or "images"). Each image includes software component(s) that address a

particular need (see Figure 4 for an example). Within a given research lab, scientists

might create general-purpose images that support functionality for multiple

projects, and they might create specialized images that address the needs of specific

projects. *Docker's* modular design provides the advantage that when images within a

container are updated, *Docker* only needs to track the specific components that have

changed; users who wish to update to a newer version must download a relatively

small update. In contrast, even a minor change to a virtual machine would require

users to rexport and reshare the entire virtual machine.

Scientists have begun to share *Docker* images with others who are working in the

same subdiscipline. For example, *nucleotid.es* is a catalog of genome-assembly tools

that have been encapsulated in *Docker* images (http://nucleotid.es). Genome-

assembly tools differ considerably in the dependencies that they require and in the

parameters that they support. This project provides a means to standardize these

assemblers, to circumvent the need to install dependencies for each tool, and to

perform benchmarks across the tools. Such projects may help to reduce the

reproducibility burden on individual scientists.

The use of *Docker* containers for reproducible research comes with caveats.

Individual containers are stored and executed in isolation from other containers on

the same computer; however, because all containers on a given machine share the

same operating system, this isolation is not as complete as it is with virtual

machines. This means, for example, that a given container is not guaranteed to have

access to a specific amount of computer memory or processing power—multiple

containers may have to compete for these resources[93]. In addition, containers may

be more vulnerable to security breaches[93]. Another caveat is that *Docker* containers

can only be executed on Linux-based operating systems. For other operating

systems, *Docker* containers must be executed within a virtual machine (for example,

see http://boot2docker.io). Although this configuration offsets some benefits of

using containers, combining virtual machines with containers may provide a happy

medium for many scientists, allowing them to use a non-Linux *host* operating

system, while receiving the benefits of containers within the *guest* operating system.

Efforts are ongoing to develop and refine software-container technologies. Box 5

lists various tools that are currently available. In coming years, these technologies

promise to play an influential role within the scientific community.

Box 5: Open-source containerization software.

- Docker - https://www.docker.com
- Linux Containers - https://linuxcontainers.org
- lmctfy - https://github.com/google/lmctfy
- OpenVZ - http://openvz.org
- Warden - http://docs.cloudfoundry.org/concepts/architecture/warden.html

---

Discussion

Scientific advancement requires trust. This review provides a comprehensive, though inexhaustive, list of techniques that can help to engender such trust. Principally, scientists must perform research in such ways that they can trust their own findings[3,94]. Science philosopher Karl Popper contended that "[w]e do not take even our own observations quite seriously, or accept them as scientific observations, until we have repeated and tested them"[2]. Indeed, in many cases, the individuals who benefit most from computational reproducibility are those who performed the original analysis. But reproducibility practices can also help scientists garner each other's trust[94,95]. When other scientists can reproduce an analysis and determine exactly how its conclusions were drawn, they may be more apt to cite the work and build upon it. In contrast, when others fail to reproduce research findings, it can lead to embarrassment, accusations, and retractions.

We have described six tools and techniques for computational reproducibility. None of these approaches is sufficient for every scenario in isolation. Rather scientists will often find value from combining approaches. For example, a researcher who uses a literate-programming notebook (which by its nature combines narratives with code) might incorporate the notebook into a software container so that others can execute it without needing to install specific software dependencies. The container might also include a workflow-management system to ease the process of integrating multiple tools and incorporating best practices for the analysis (see Figure 4). This container could be packaged within a virtual machine to ensure that

it can be executed on many operating systems. In determining a reproducibility

strategy, scientists must evaluate the tradeoff between robustness and practicality.

The call for computational reproducibility relies on the premise that reproducible

science will bolster the efficiency of the overall scientific enterprise[96]. Although

reproducibility practices may require additional time and effort, these practices

provides ancillary benefits that help offset those expenditures[94]. Primarily, the

scientists who perform a study may experience increased efficiency. For example,

before and after a manuscript is submitted for publication, it faces scrutiny from co-

authors and peer reviewers who may suggest alterations to the analysis. Having a

complete record of all analysis steps and being able to retrace those steps precisely,

makes it faster and easier to implement the requested alterations[94,97].

Reproducibility practices can also improve the efficiency of team science because

colleagues can more easily communicate their research protocols and inspect each

other's work; one type of relationship where this is important is that between

academic advisors and mentees[97]. Finally, when research protocols are shared

transparently with the broader community, scientific advancement increases

because scientists can learn more easily from each other's work and duplicate each

other's efforts less frequently[97].

Reproducibility practices do not necessarily ensure that others can obtain results

that are perfectly identical to what the original scientists obtained. Indeed, this

objective may be infeasible for various types of computational analysis, including

those that use randomization procedures, floating-point operations, or specialized

computer hardware[87]. In such cases, the goal may shift to ensuring that others can

obtain results that are semantically consistent with the original findings[5,6]. In

addition, in studies where vast computational resources are needed to perform an

analysis or where data sets are distributed geographically[98-100], full reproducibility

may be infeasible; in these cases, researchers can provide relatively simple

examples that demonstrate the methodology. When legal restrictions prevent

researchers from sharing software or data publicly, or when software is available

only via a Web interface, researchers should document the analysis steps as well as

possible and describe why such components cannot be shared[22].

Computational reproducibility does not guarantee against analytical biases or

ensure that software produces scientifically valid results[101]. As with any research, a

poor study design, confounding effects, or improper use of analytical software may

plague even the most reproducible analyses[101,102]. On one hand, increased

transparency puts scientists at a greater risk that such problems will be exposed. On

the other hand, scientists who are fully transparent about their scientific approach

may be more likely to avoid such pitfalls, knowing that they will be more vulnerable

to such criticisms. Either way, the scientific community benefits.

Lastly, we emphasize that some reproducibility is better than none. As Voltaire said,

the perfect should not be the enemy of the good[103]. However, the practices

described in this review are accessible to all scientists and can be implemented with

a modest extra effort. As scientists act in good faith to perform these practices,

where feasible, the pace of scientific progress will surely increase.

Figure Legends

Figure 1: Basic computer architecture. Computer hardware consists of hardware devices, including central processing units, hard drives, random access memory, keyboard, mouse, etc. Operating systems enable software to interface with hardware; popular operating-system families are *Windows*, *Mac OS*, and *Linux*. Users interact with computers via software interfaces. In scientific computing, software enables users to execute algorithms, analyze data, generate graphics, etc. To execute properly, most software tools depend on specific versions of software dependencies, which must be installed on the same operating system.

Figure 2: Architecture of virtual machines. Virtual machines encapsulate

analytical software and dependencies within a "guest" operating system, which may

be different than the main ("host") operating system. A virtual machine executes in

the context of virtualization software, which executes alongside whatever other

software is installed on the computer.

Figure 3: Architecture of software containers. Software containers encapsulate

analytical software and dependencies. In contrast to virtual machines, containers

execute within the context of the computer's main operating system.

Figure 4: Example of a *Docker* container that could be used for genomics

research. This container would enable researchers to preprocess various types of

molecular data, using tools from *Bioconductor* and *Galaxy*, and to analyze the

resulting data within an *IPython* notebook. Each box within the container represents

a distinct *Docker* image. These images are layered such that some images depend on

others (for example, the *Bioconductor* image depends on *R*). At its base, the

container includes operating-system libraries, which may not be present (or may be

configured differently) on the computer's main operating system.

References

1. Fisher, R. A. *The Design of Experiments*. (Hafner Press, 1935). 509

2. Popper, K. R. *The Logic of Scientific Discovery*. 23 (Routledge, 2002). 510

3. Peng, R. D. Reproducible research in computational science. *Science (New York,* 511
N.Y.) **334,** 1226–7 (2011). 512

4. Russell, J. F. If a job is worth doing, it is worth doing twice. *Nature* **496,** 7 (2013). 513

5. Feynman, R. P., Leighton, R. B. & Sands, M. *Six Easy Pieces: Essentials of Physics* 514
Explained by Its Most Brilliant Teacher. 34–35 (Perseus Books, 1994). 515

6. Murray-Rust, P. & Murray-Rust, D. in *Implementing reproducible research* (eds. 516
Stodden, V. C., Leisch, F. & Peng, R. D.) 113 (CRC Press, 2014). 517

7. Software with impact. *Nature Methods* **11,** 211 (2014). 518

8. Chue Hong, N. We are the 92%. in *Second workshop on sustainable software for* 519
science: Practice and experiences (2014). 520
doi:http://dx.doi.org/10.6084/m9.figshare.1243288 521

9. Sacks, J., Welch, W. J., Mitchell, T. J. & Wynn, H. P. Design and Analysis of Computer 522
Experiments. *Statistical Science* **4,** 409–423 (1989). 523

10. Garijo, D. *et al.* Quantifying reproducibility in computational biology: The case of 524
the tuberculosis drugome. *PLoS ONE* **8,** (2013). 525

11. Error prone. *Nature* **487,** 406 (2012). 526

12.Vandewalle, P., Barrenetxea, G., Jovanovic, I., Ridolfi, A. & Vetterli, M. Experiences

with Reproducible Research in Various Facets of Signal Processing Research. in

2007 iEEE international conference on acoustics, speech and signal processing -

iCASSP '07 **4,** IV–1253–IV–1256 (IEEE, 2007).

13.Cassey, P., Cassey, P., Blackburn, T. & Blackburn, T. Reproducibility and

Repeatability in Ecology. *BioScience* **56,** 958–9 (2006).

14.Murphy, J. M. *et al.* Quantification of modelling uncertainties in a large ensemble

of climate change simulations. *Nature* **430,** 768–772 (2004).

15.McCarthy, D. J. *et al.* Choice of transcripts and software has a large effect on

variant annotation. *Genome Medicine* **6,** 26 (2014).

16.Neuman, J. A., Isakov, O. & Shomron, N. Analysis of insertion-deletion from deep-

sequencing data: Software evaluation for optimal detection. *Briefings in*

Bioinformatics **14,** 46–55 (2013).

17.Fonseca, N. A., Marioni, J. A. & Brazma, A. *RNA-seq gene profiling - a systematic*

empirical comparison. *BioRxiv* 005207 (2014). doi:10.1101/005207

18.Bradnam, K. R. *et al.* Assemblathon 2: evaluating de novo methods of genome

assembly in three vertebrate species. *GigaScience* **2,** 10 (2013).

19.Bilal, E. *et al.* Improving Breast Cancer Survival Analysis through Competition-

Based Multidimensional Modeling. *PLoS Computational Biology* **9,** e1003047 (2013).

20. Moskvin, O., McIlwain, S. & Ong, I. *Making sense of RNA-Seq data: from low-level*

processing to functional analysis. *BioRxiv* 010488 (Cold Spring Harbor Labs Journals,

2014). doi:10.1101/010488

21. Reducing our irreproducibility. *Nature* **496,** 398–398 (2013).

22. *Evolution of Translational Omics: Lessons Learned and the Path Forward*. (The

National Academies Press, 2012).

23. Collins, F. S. & Tabak, L. a. Policy: NIH plans to enhance reproducibility. *Nature*

505, 612–3 (2014).

24. Chambers, J. M. S as a Programming Environment for Data Analysis and Graphics.

in *Problem solving environments for scientific computing, proc. 17th symp. on the*

interface of stat. and comp. 211–214 (1985).

25. LeVeque, R. J., Mitchell, I. M. & Stodden, V. Reproducible research for scientific

computing: Tools and strategies for changing the culture. *Computing in Science and*

Engineering **14,** 13 (2012).

26. Stodden, V., Guo, P. & Ma, Z. Toward Reproducible Computational Research: An

Empirical Analysis of Data and Code Policy Adoption by Journals. *PLoS ONE* **8,** 2–9

(2013).

27. Morin, A. *et al.* Shining Light into Black Boxes. *Science* **336,** 159–160 (2012).

28. Rebooting review. *Nature Biotechnology* **33,** 2015 (2015).

29. Ioannidis, J. P. a *et al.* Repeatability of published microarray gene expression

analyses. *Nature genetics* **41**, 149–55 (2009).

30. Nekrutenko, A. & Taylor, J. Next-generation sequencing data interpretation:

enhancing reproducibility and accessibility. *Nature reviews. Genetics* **13**, 667–72

(2012).

31. Baggerly, K. a. & Coombes, K. R. Deriving chemosensitivity from cell lines:

Forensic bioinformatics and reproducible research in high-throughput biology.

Annals of Applied Statistics **3**, 1309–1334 (2009).

32. Sainani, K. It's easy to make mistakes in computational models … and hard to

catch them . *Biomedical Computation Review* **Fall**, 12–19 (2011).

33. Decullier, E., Huot, L., Samson, G. & Maisonneuve, H. Visibility of retractions: a

cross-sectional one-year study. *BMC Research Notes* **6**, 238 (2013).

34. Fang, F. C. & Casadevall, A. Retracted science and the retraction index. *Infection*

and Immunity **79**, 3855–3859 (2011).

35. Claerbout, J. F. & Karrenbach, M. Electronic Documents Give Reproducible

Research a New Meaning. in *Meeting of the society of exploration geophysics* (1992).

36. Stodden, V. & Miguez, S. Best Practices for Computational Science: Software

Infrastructure and Environments for Reproducible and Extensible Research. *Journal*

of Open Research Software **2**, 21 (2014).

37. Ravel, J. & Wommack, K. E. All hail reproducibility in microbiome research.

Microbiome **2,** 8 (2014).

38. Stodden, V. 2014: What scientific idea is ready for retirement? (2014). at

<http://edge.org/response-detail/25340>

39. Birney, E. *et al.* Prepublication data sharing. *Nature* **461,** 168–170 (2009).

40. Hothorn, T. & Leisch, F. Case studies in reproducibility. *Briefings in Bioinformatics*

12, 288–300 (2011).

41. Schofield, P. N. *et al.* Post-publication sharing of data and tools. *Nature* **461,** 171–

173 (2009).

42. Piwowar, H. a., Day, R. S. & Fridsma, D. B. Sharing detailed research data is

associated with increased citation rate. *PLoS ONE* **2,** (2007).

43. Johnson, V. E. Revised standards for statistical evidence. *Proceedings of the*

National Academy of Sciences of the United States of America **110,** 19313–7 (2013).

44. Halsey, L. G., Curran-everett, D., Vowler, S. L. & Drummond, G. B. The fickle P

value generates irreproducible results. *Nature Methods* **12,** 179–185 (2015).

45. Foundation, F. S. GNU Make. at <https://www.gnu.org/software/make>

46. Make for Windows. at <http://gnuwin32.sourceforge.net/packages/make.htm>

47. Code share. *Nature* **514,** 536 (2014).

48. Loeliger, J. & McCullough, M. *Version Control with Git: Powerful Tools and*

Techniques for Collaborative Software Development. 456 ('O'Reilly Media, Inc.',

2012).

49. Gentleman, R. C. *et al.* Bioconductor: open software development for

computational biology and bioinformatics. *Genome biology* **5**, R80 (2004).

50. R Core Team. *R: A Language and Environment for Statistical Computing*. (R

Foundation for Statistical Computing, 2014). at <http://www.r-project.org/>

51. Huber, W. *et al.* Orchestrating high-throughput genomic analysis with

Bioconductor. *Nature Methods* **12**, 115–121 (2015).

52. Tóth, G. *et al.* Space Weather Modeling Framework: A new tool for the space

science community. *Journal of Geophysical Research* **110**, A12226 (2005).

53. Tan, E., Choi, E., Thoutireddy, P., Gurnis, M. & Aivazis, M. GeoFramework:

Coupling multiple models of mantle convection within a computational framework.

Geochemistry, Geophysics, Geosystems **7**, n/a–n/a (2006).

54. Heisen, B. *et al.* Karabo: An Integrated Software Framework Combining Control,

Data Management, and Scientific Computing Tasks. in *14th international conference*

on accelerator & large experimental physics control systems, iCALEPCS2013 (2013).

55. Schneider, C. A., Rasband, W. S. & Eliceiri, K. W. NIH Image to ImageJ: 25 years of

image analysis. *Nature Methods* **9**, 671–675 (2012).

56. Schindelin, J. *et al.* Fiji: an open-source platform for biological-image analysis.

Nature methods **9,** 676–82 (2012).

57. Biasini, M. *et al.* OpenStructure: an integrated software framework for

computational structural biology. *Acta crystallographica. Section D, Biological*

crystallography **69,** 701–9 (2013).

58. Köster, J. & Rahmann, S. Snakemake–a scalable bioinformatics workflow engine.

Bioinformatics (Oxford, England) **28,** 2520–2 (2012).

59. Sadedin, S. P., Pope, B. & Oshlack, A. Bpipe : A Tool for Running and Managing

Bioinformatics Pipelines. *Bioinformatics (Oxford, England)* **28,** 1525–1526 (2012).

60. Tange, O. GNU Parallel - The Command-Line Power Tool. *;login: The USENIX*

Magazine **36,** 42–47 (2011).

61. Albrecht, M., Donnelly, P., Bui, P. & Thain, D. Makeflow: A portable abstraction for

data intensive computing on clusters, clouds, and grids. in *Proceedings of the 1st aCM*

sIGMOD workshop on scalable workflow execution engines and technologies (2012).

62. Knuth, D. E. Literate Programming. *The Computer Journal* **27,** 97–111 (1984).

63. Pérez, F. & Granger, B. E. IPython: a System for Interactive Scientific Computing.

Computing in Science and Engineering **9,** 21–29 (2007).

64. Shen, H. Interactive notebooks: Sharing the code. *Nature* **515,** 151–152 (2014).

65. Xie, Y. *Dynamic Documents with R and knitr*. 216 (CRC Press, 2013).

66. Gross, A. M. *et al.* Multi-tiered genomic analysis of head and neck cancer ties

TP53 mutation to 3p loss. *Nature Genetics* **46,** 1–7 (2014).

67. Ding, T. & Schloss, P. D. Dynamics and associations of microbial community types

across the human body. *Nature* **509,** 357–60 (2014).

68. Ram, Y. & Hadany, L. The probability of improvement in Fisher's geometric

model: A probabilistic approach. *Theoretical population biology* **99,** 1–6 (2015).

69. Meadow, J. F. *et al.* Bacterial communities on classroom surfaces vary with

human contact. *Microbiome* **2,** 7 (2014).

70. White, E. Programming for Biologists. at

<http://www.programmingforbiologists.org>

71. Software Carpentry. at <https://software-carpentry.org>

72. Peng, R. D. Coursera course: Computing for Data Analysis. at

<https://www.coursera.org/course/compdata>

73. Bioconductor Courses & Conferences. at

<http://master.bioconductor.org/help/course-materials>

74. Gil, Y. *et al.* Examining the challenges of scientific workflows. *Computer* **40,** 24–32

(2007).

75. Giardine, B. *et al.* Galaxy: a platform for interactive large-scale genome analysis.

Genome research **15,** 1451–5 (2005).

76. Goecks, J., Nekrutenko, A. & Taylor, J. Galaxy: a comprehensive approach for

supporting accessible, reproducible, and transparent computational research in the

life sciences. *Genome biology* **11,** R86 (2010).

77. Afgan, E. *et al.* Harnessing cloud computing with Galaxy Cloud. *Nature*

Biotechnology **29,** 972–974 (2011).

78. Callahan, S. P. *et al.* VisTrails: Visualization Meets Data Management. in

Proceedings of the 2006 aCM sIGMOD international conference on management of

data 745–747 (ACM, 2006). doi:10.1145/1142473.1142574

79. Davidson, S. B. & Freire, J. Provenance and scientific workflows. in *Proceedings of*

the 2008 aCM sIGMOD international conference on management of data - sIGMOD '08

1345 (2008). doi:10.1145/1376616.1376772

80. Altintas, I. *et al.* Kepler: an extensible system for design and execution of

scientific workflows. in *Proceedings. 16th international conference on scientific and*

statistical database management, 2004. 423–424 (IEEE, 2004).

doi:10.1109/SSDM.2004.1311241

81. Goff, S. A. *et al.* The iPlant Collaborative: Cyberinfrastructure for Plant Biology.

Frontiers in plant science **2,** 34 (2011).

82. Reich, M. *et al.* GenePattern 2.0. *Nature genetics* **38,** 500–1 (2006).

83. Reich, M. *et al.* GenomeSpace: An environment for frictionless bioinformatics.

Cancer Research **72,** 3966–3966 (2012).

84.Wolstencroft, K. *et al.* The Taverna workflow suite: designing and executing

workflows of Web Services on the desktop, web or in the cloud. *Nucleic acids*

research **41,** 557–561 (2013).

85.Rex, D. E., Ma, J. Q. & Toga, A. W. The LONI Pipeline Processing Environment.

NeuroImage **19,** 1033–1048 (2003).

86.Dudley, J. T. & Butte, A. J. In silico research in the era of cloud computing. *Nature*

biotechnology **28,** 1181–1185 (2010).

87.Hurley, D. G., Budden, D. M. & Crampin, E. J. Virtual Reference Environments: a

simple way to make research reproducible. *Briefings in Bioinformatics* 1–3 (2014).

doi:10.1093/bib/bbu043

88.Gent, I. P. The Recomputation Manifesto. *arXiv* (2013). at

<http://arxiv.org/abs/1304.3674>

89.Howe, B. Virtual Appliances, Cloud Computing, and Reproducible Research.

Computing in Science & Engineering **14,** 36–41 (2012).

90.Brown, C. T. Virtual machines considered harmful for reproducibility. *Living in an*

ivory basement: Stochastic thoughts on science, testing, and programming. (2012). at

<http://ivory.idyll.org/blog/vms-considered-harmful.html>

91.Piccolo, S. R. Building portable analytical environments to improve sustainability

of computational-analysis pipelines in the sciences. *Figshare* (2014). at

<http://dx.doi.org/10.6084/m9.figshare.1112571>

92. Krampis, K. *et al.* Cloud BioLinux: pre-configured and on-demand bioinformatics

computing for the genomics community. *BMC Bioinformatics* **13,** 42 (2012).

93. Felter, W., Ferreira, A., Rajamony, R. & Rubio, J. An Updated Performance

Comparison of Virtual Machines and Linux Containers. (2014). at

<http://domino.research.ibm.com/library/CyberDig.nsf/papers/0929052195DD81

9C85257D2300681E7B/\$File/rc25482.pdf>

94. Sandve, G. K., Nekrutenko, A., Taylor, J. & Hovig, E. Ten Simple Rules for

Reproducible Computational Research. *PLoS Computational Biology* **9,** 1–4 (2013).

95. Hones, M. J. . Reproducibility as a Methodological Imperative in Experimental

Research. in *PSA: Proceedings of the biennial meeting of the philosophy of science*

association **One,** 585–599 (Philosophy of Science Association, 1990).

96. Crick, T., Hall, B. A., Ishtiaq, S. & Takeda, K. 'Share and Enjoy': Publishing Useful

and Usable Scientific Models. in *1st international workshop on recomputability* 1–5

(2014). at <http://arxiv.org/abs/1409.0367>

97. Donoho, D. L. An invitation to reproducible computational research. *Biostatistics*

(Oxford, England) **11,** 385–8 (2010).

98. Shirts, M. & Pande, V. S. COMPUTING: Screen Savers of the World Unite! *Science*

(New York, N.Y.) **290,** 1903–1904 (2000).

99. Bird, I. Computing for the Large Hadron Collider. *Annual Review of Nuclear and*

Particle Science **61,** 99–118 (2011).

100.Anderson, D. P. BOINC: A System for Public Resource Computing and Storage. in

Proceedings of the fifth iEEE/ACM international workshop on grid computing

(gRID'04) (2004).

101.Ransohoff, D. F. Bias as a threat to the validity of cancer molecular-marker

research. *Nature reviews. Cancer* **5,** 142–9 (2005).

102.Bild, A. H., Chang, J. T., Johnson, W. E. & Piccolo, S. R. A field guide to genomics

research. *PLoS biology* **12,** e1001744 (2014).

103.Ratcliffe, S. *Concise Oxford Dictionary of Quotations*. 389 (Oxford University

Press, 2011).

Analytical Software

Software Dependencies

Operating System

Hardware