One Codex: A Sensitive and Accurate Data Platform for

Genomic Microbial Identification

Samuel S. Minot[*], Niklas Krumm and Nicholas B. Greenfield

One Codex (Reference Genomics, Inc.), San Francisco, California, USA

*To whom correspondence should be addressed: sam@onecodex.com

1 ABSTRACT

High-throughput sequencing (HTS) is increasingly being used for broad applications of microbial char-

acterization, such as microbial ecology, clinical diagnosis, and outbreak epidemiology. However, the

analytical task of comparing short sequence reads against the known diversity of microbial life has

proved to be computationally challenging. The One Codex data platform was created with the dual goals

of analyzing microbial data against the largest possible collection of microbial reference genomes, as

well as presenting those results in a format that is consumable by applied end-users. One Codex identi-

fies microbial sequences using a "*k*-mer based" taxonomic classification algorithm through a web-based

data platform, using a reference database that currently includes approximately 40,000 bacterial, viral,

fungal, and protozoan genomes. In order to evaluate whether this classification method and associated

database provided quantitatively different performance for microbial identification, we created a large

and diverse evaluation dataset containing 50 million reads from 10,639 genomes, as well as sequences

from six organisms novel species not be included in the reference databases of any of the tested classifi-

ers. Quantitative evaluation of several published microbial detection methods shows that One Codex has

the highest degree of sensitivity and specificity (AUC = 0.97, compared to 0.82-0.88 for other methods),

both when detecting well-characterized species as well as newly sequenced, "taxonomically novel" or-

ganisms.

2 INTRODUCTION

As the efficiency, accuracy, and speed of high-throughput genomic sequencing (HTS) has continued to

improve, a larger set of microbiologists working in clinical medicine, public health, and industry is

adopting this powerful technology. Public health agencies are already beginning to use HTS to track the

spread of outbreaks (Neimark 2015), and there is an increasing number of applications for which the ex-

quisite precision and accuracy of genome-level identification justifies the (presently) higher marginal

per-test cost. However, the broader adoption of HTS by scientists that may lack experience in bioinfor-

matic analysis has created a need for bioinformatic solutions that are accessible for non-experts and pro-

vide high-quality analytical results (Grad 2014; Caboche 2014).

Taxonomic classification is the analytical basis of a wide range of applied microbiology supporting ap-

plications in public health, clinical diagnosis, and industrial production. Strain- and species-level taxo-

nomic classification allows a user to identify specific pathogens, perform genomic epidemiology, and

characterize microbial communities that may be associated with a particular phenotype. A variety of al-

gorithms have been developed for such taxonomic classification, including the use of marker gene li-

braries (Segata 2012; Liu 2011), local alignment (Naccache 2014; Mitra 2011), and k-mer matching

(Ames 2013; Wood 2014; Břinda 2015; Ounit 2015). *K*-mer-based analysis, the method used by Kraken,

Seed-Kraken, CLARK, and One Codex, identifies short sequences (typically ranging from 17 - 31 bp)

that are unique to specific taxa within a set of input reads. Based on the collection of k-mers that are

found in a given read, it can be assigned to a particular taxon. By extension, a sample can be character-

ized according to the proportion of reads that are assigned to different taxa. Using this approach, micro-

bial samples either from isolates or mixed samples can be characterized to the level needed to perform a

large number of tasks needed for public health, clinical diagnosis, and industrial microbiology. As a

public resource for academic data analysis, we believe it is valuable to provide the research community

with a description of the performance and operation of the One Codex platform, while providing the raw

data and analytical details needed to replicate or update such an evaluation as metagenomic methods

continue to improve. In this paper we describe the functioning of One Codex and a rigorous functional

evaluation of the state-of-the-art metagenomic classification methods, including the effect of database

size on classification accuracy.

3   MATERIALS & METHODS

3.1   Taxonomic Classification Algorithm

One Codex classifies individual sequence reads according to the set of k-mers in that read that are

unique to specific taxonomic groups. This analytical approach has been described extensively (Ames

2014; Wood 2014) and is implemented by One Codex using a default value of $k=31$. Briefly, each read

is broken into the complete set of overlapping sequences of length 31bp that comprise it. These k-mers

are compared against an exhaustive database that contains every k-mer and the taxonomic grouping to

which it is unique (e.g., a specific clade of bacteria, archaea, or viruses). A compressed data structure is

used to index and rapidly search k-mer databases generated from approximately 40,000 microbial ge-

nomes. Each read can then be summarized as a "k-mer hit chain" that describes the complete set of taxo-

nomically-informative k-mers found in that read, as well as their positions. Individual reads are then as-

signed on the basis of the highest weighted taxonomic root-to-leaf path amongst these k-mer hits. For

example, if a read has k-mers unique to *Enterobacteriaceae*, *Escherichia*, and *Escherichia coli*, it would

be given the label *E. coli*. However, if it had k-mers unique to *Enterobacteriaceae*, *Escherichia*, and

Klebsiella, it would be given the label *Enterobacteriaceae* – the most specific taxon that encompasses

all detected k-mers, as *Klebsiella* and *Escherichia* are separate genera of *Enterobacteriaceae*. Finally,

the distribution of reads from a single sample across different organisms and taxa is used to construct a

comprehensive report that displays the organisms present in a sample.

3.2   Classification Accuracy

74   The goal of this evaluation effort was to assess the ability of a suite of bioinformatic methods to assign

75   nucleotide sequences to the most accurate taxonomic group.

3.2.1. One Codex Classification

Data were processed on the One Codex platform according to the instructions outlined in Section 2.3 – One Codex User Interface. One Codex uses two reference databases, the full One Codex database of approximately 40,000 bacteria, viruses, fungi, archaeal, and protists, and a smaller database containing the over 8,000 microbial genomes contained in the NCBI RefSeq database. Both the One Codex full database (referred to here as "One Codex") and the One Codex RefSeq Database represent sequences available on July 8, 2015.

3.2.2. Additional Classification Algorithms

The following metagenomic classification algorithms were downloaded, compiled, and installed according to the provided instructions in an Ubuntu environment on standard AWS EC2 instances (r3.8xlarge). In each case the indicated dependencies were installed as described and default run settings were used, except in the case of Clark in which the "RAM-light" flag was used in order not exceed system memory capacity.

- Metaphlan (2.1.0) - https://bitbucket.org/biobakery/metaphlan2
- GOTTCHA (1.0b) - https://github.com/poeli/GOTTCHA (database GOTTCHA_BACTERIA_c3514_k24_u2)
- Kraken (v0.10.5-beta) - http://ccb.jhu.edu/software/kraken/
- Seed-Kraken (seedmod128b_from_0.10.6) - http://seed-kraken.readthedocs.org/
- Clark (v1.1.3) – http://clark.cs.ucr.edu/

3.2.3. Additional Classification Databases

Metaphlan is distributed with a complete standalone database. Kraken is distributed with a reduced ref-

erence database ("Minikraken" - Dec. 8, 2014). In addition, we constructed the full Kraken database on

July 5, 2015 according to the instructions provided at

http://ccb.jhu.edu/software/kraken/MANUAL.html. Given the contemporaneous snapshot of NCBI, the

genomic content of the full Kraken database is roughly equivalent to that of the One Codex RefSeq Da-

tabase, albeit with some differences in the exact repositories used. The Seed-Kraken database was con-

structed using the same complement of reference genomes as the Kraken database. The Clark bacterial

reference database was constructed on Aug. 21, 2015 using the provided default instructions.

3.2.4. Test Datasets

Two complementary approaches were employed to test the accuracy of these microbial detection meth-

ods. In the first, 500 sets of simulated reads (100,000 reads each) were generated from complete micro-

bial genomes at a wide range of abundance levels in order to simulate a variety of biological assemblag-

es (Mavromatis 2007). Each read set contained reads from 214 random genomes with roughly 100,000

reads simulated each, and additional reads from 10,425 genomes simulated at much lower abundance (1

– 30,000 reads each) (Figure 1). In total, 50 million reads were simulated from 10,639 genomes to pro-

vide a robust resource for the evaluation of metagenomic analysis methods. In every case, the genome

was selected randomly from the set of complete genomes available in public sequence repositories, re-

gardless of whether they were included in the One Codex database. Approximately 78% of the simulated

genomes were also indexed in the One Codex Database, while 8.8% were indexed in the One Codex

RefSeq Database. Importantly, the taxonomic ID for each read was encoded in the FASTQ header, al-

lowing the direct comparison of the known source of each sequence against the taxonomic prediction

made by each method.

Figure 1. A frequency histogram of the number of reads simulated for the set of low-abundance ge-

nomes (10,425 genomes, $1 - 30,000$ reads each). The horizontal axis shows the number of reads simu-

lated per genome, and the vertical axis indicates the number of genomes simulated at that depth ($\log_{10}$).

An additional set of 214 genomes were used to simulate at least 100,000 reads each.

In the second testing approach, a set of six organisms identified in the public repositories that were se-

quenced recently enough as to not be included in any of the reference databases. These "taxonomically

novel" genomes did not have any other members of their species present in the reference database. Three

of the six "taxonomically novel" test datasets were simulated from complete genome assemblies at 5X,

two were raw Illumina reads, and one was an unassembled PacBio dataset (Table 1). While these da-

tasets may contain contaminating or misidentified organisms, each analytical method will be challenged

equally by those potentially confounding factors.

For both the single-isolate samples and the 500 sets of simulated reads (100,000 reads each), simulated

150bp single-ended reads were generated using the ART next-generation sequencing read simulator

(v3.19.15) (Huang 2012) using the Illumina quality profile. For the single-isolate "taxonomically novel"

test datasets, reads were generated at 5-fold coverage depth.

NCBI Accession	Organism	Source	Type	Number of Simulated Reads
GCA_001045455	Chryseobacterium sp. FH2	Assembly	Illumina	132,905
GCA_001050135	Cyclobacterium amurskyense KCTC-12363	Assembly	Illumina	205,290
SRR2106399	Leptolyngbya sp. Y-WT-2000	Unassembled reads	Illumina	11,060,814
GCA_001258055	Nautella italica CECT7645	Assembly	Illumina	134,905
SRR2106282	Thermincola ferriacetica Z-0001	Unassembled reads	Illumina	2,053,515
SRR2080278	Wenzhouxiangella marina KCTC42284	Unassembled reads	PacBio	163,476

Table 1. Datasets used to assess the performance of each method in identifying organisms not contained

in the reference database.

3.2.5. Statistical Summary

Kraken, Seed-Kraken, Clark, and One Codex provide taxonomic assignments for every read in a dataset,

while Metaphlan and GOTTCHA provide an overall summary of dataset composition. Kraken, Seed-

Kraken, Clark, and One Codex were evaluated with the complete set of 50 million simulated reads,

while all methods were evaluated on the six single-organism "taxonomically novel" datasets. Each

method was executed on an equivalent AWS EC2 instance (r3.8xlarge) with 12 processors available for

parallelized steps.

For the set of 50 million simulated reads, the accuracy of classification by One Codex, Seed-Kraken and

Kraken was evaluated on a read-by-read basis. One Codex was run with both the One Codex Database

(~40,000 genomes) and the One Codex RefSeq Database (~8,000 genomes). Kraken was run with both

the full database and the "Minikraken" database. Those methods assign an NCBI taxonomic identifier

('taxid') to each read. Given the known source of each read, the accuracy of the classification can be as-

sessed across all levels of the taxonomy. For example, a read simulated from *E. coli* O157:H7 str. Sakai

may be assigned to *Escherichia fergusonii*, in which case the species-level assignment is incorrect, while

the genus-level assignment is correct (as is the family-, order-, class-, and phylum-). Similarly, a read

simulated from *E. coli* O157:H7 str. Sakai may be assigned to *Enterobacteriaceae*, in which case the

family-level assignment is correct and there is no assignment at the rank of genus, species, or strain.

Accuracy metrics were calculated as follows: Let A be the number of reads assigned correctly at a given

taxonomic rank, B be the number of reads with any assignment at the given rank, C be the number of

reads classified incorrectly at a less-specific rank, and D be the total number of reads. Sensitivity is de-

fined as A / D, or the proportion of all reads assigned correctly at the given rank. Specificity is defined

as A / (B + C), following Wood et al. (2015). For a set of reads simulated from *E. coli,* the classification

of a read as *E. coli* would increase both species-level sensitivity and species-level specificity, classifica-

tion as *Escherichia* would not increase species-level sensitivity, but it would increase species-level spec-

ificity, and classification as *E. fergusonii* would decrease both species-level sensitivity and species-level

specificity.

Metaphlan and GOTTCHA do not assign taxa to individual reads, but rather predict the proportion of the

dataset composed of different taxa. Therefore the specificity presented for those methods is the propor-

tion assigned to the correct taxon at a given rank and no sensitivity metrics are reported.

3.3   One Codex User Interface

Samples are uploaded in FASTA or FASTQ format to the One Codex platform through a graphical up-

load tool with both drag-and-drop and folder navigation options. A command-line tool and API are also

available for large-volume data upload (https://docs.onecodex.com). Once uploaded, reads are taxonom-

ically classified and the interactive report is populated and linked to the user's account (Supplemental

Figures 1 and 2). The One Codex platform can be accessed at https://www.onecodex.com, and can be

used freely to analyze public data.

3.4   Availability

Simulated datasets are available in a compressed FASTQ file containing 50M simulated reads at

www.onecodex.com/data/papers/minot-krumm-greenfield-2015/simulated.reads.fastq.gz. The true taxo-

nomic origin of each read is encoded in the FASTQ header as an NCBI taxid, allowing other researchers

to replicate this analytical framework. One Codex is freely available for public use by academic re-

searchers at https://www.onecodex.com. Supplemental Figures 1 and 2 show example screenshots of the

One Codex platform.

4   RESULTS

4.1 Read-level Accuracy

We first summarized the accuracy of each tool on a per-read basis. One Codex showed the highest de-

gree of sensitivity and specificity at each rank and the performance of the other methods varied with the

database and assignment method used. It is notable that although the content of the Kraken and Seed-

Kraken databases was identical, Seed-Kraken was more sensitive and less specific than Kraken at all

taxonomic levels (Table 2 and Figure 2). While the reduced Minikraken database resulted in lower sen-

sitivity and higher specificity than the full Kraken database, the reduced One Codex RefSeq Database

was less accurate using both metrics. As noted above, ~78% of the simulated genomes were indexed in

the One Codex Database, while 8.8% were indexed in the One Codex RefSeq Database. Accuracy met-

rics were also calculated for One Codex and One Codex RefSeq using only the subset of reads simulated

from genomes not indexed in those databases. Species-level sensitivity and specificity for One Codex

was 0.532 and 0.875, respectively, while One Codex RefSeq was 0.511 and 0.835. Similar comparisons

could not be made for other methods without better characterization of the genome accessions used to

create those reference indices.

Sensitivity

Rank	Kraken	Minikraken	Seed-Kraken	Clark	One Codex	One Codex - RefSeq
superking-dom	0.743	0.714	0.758	0.682	**0.951**	0.748
phylum	0.742	0.713	0.755	0.681	**0.943**	0.745
class	0.740	0.711	0.752	0.679	**0.906**	0.743
order	0.737	0.709	0.748	0.678	**0.903**	0.740
family	0.734	0.706	0.743	0.675	**0.897**	0.737
genus	0.694	0.662	0.711	0.668	**0.852**	0.704
species	0.546	0.516	0.574	0.605	**0.621**	0.563
strain	0.030	0.027	0.031	0.000	**0.118**	0.080

Specificity

Rank	Kraken	Minikraken	Seed-Kraken	Clark	One Codex	One Codex - RefSeq
superking-dom	**0.999**	**0.999**	0.996	0.996	**0.999**	0.994
phylum	0.997	**0.998**	0.994	0.994	**0.998**	0.992
class	0.995	**0.997**	0.991	0.992	**0.997**	0.990
order	0.993	**0.996**	0.987	0.989	**0.996**	0.988
family	0.989	0.994	0.982	0.986	**0.996**	0.984
genus	0.980	0.991	0.970	0.975	**0.995**	0.974
species	0.893	0.936	0.869	0.883	**0.979**	0.864
strain	0.157	0.203	0.114	0.000	**0.824**	0.181

Table 2. Summary of accuracy for six methods identifying the taxonomic origin of 50 million short se-

quence reads simulated from 10,639 microbial genomes. The maximum value at each rank is bolded.

Figure 2. Summary of accuracy for six methods identifying the taxonomic origin of 50 million short se-

quence reads simulated from 10,639 microbial genomes.

4.2   Species-level presence/absence accuracy

We characterized the species-level accuracy of each classifier using a receiver operating characteristic

(ROC) curve (Fig. 3). The ROC curve displays the true positive rate (TPR) and false positive rate (FPR)

of species presence/absence across a range of read thresholds. Each dataset can be summarized as a set

of species, each detected with a certain number of reads, and each marked as truly present, or truly ab-

sent. For any given number of reads, the species detected with at least that number of reads is marked as

present, and any species with fewer than that number of reads is marked as absent. The TPR is calculat-

ed for a given read threshold as the number of true positive detections divided by the total number of

total positives, and the FPR is calculated as the number of true negatives divided by the number of total

negatives. The ROC curve for each method is shown in Figure 3.

Figure 3. ROC curve displaying the performance of six taxonomic classification methods as species-

level binary classifiers. Horizontal axis shows the False Positive Rate, and the vertical axis shows the

True Positive Rate. Area Under Curve (AUC) is inset. The FPR and TPR are shown for a read cutoff

value of 100 detected reads (150bp), which corresponds to roughly 0.003X coverage of a typical bacteri-

al genome.

4.3   "Taxonomically Novel" Accuracy

Each of the "taxonomically novel" test datasets was selected because that species was not present in the

reference database for any method. Due to the relative taxonomic novelty of these organisms, the closest

match found by any method for these datasets was either at the genus-, family-, or order-level. For ex-

ample, the most taxonomically similar reference organisms to *Wenzhouxiangella marina* KCTC 42284

(SRR2080278) share the order *Chromatiales*, as the family *Wenzhouxiangellaceae* was only proposed

very recently (Wang 2015). Sensitivity and specificity metrics are shown in Table 3 alongside the rank

at which the closest correct match was found by any method. GOTTCHA did not report any taxa above

its threshold of detection for the three datasets showing '0' in Table 3, and we provided the authors of

that method with those datasets in order to confirm those results. Using the GOTTCHA 'v20150825'

database they reported that dataset GCA_001045455 was assigned correctly at the family level and

above, dataset SRR2106399 was assigned correctly at the order level, and dataset SRR2080278 did not

have any assignments above the threshold of reporting (personal communication). Across all six da-

tasets, One Codex displayed the highest sensitivity (0.391) while One Codex - RefSeq had the highest

specificity (0.696).

Dataset	GCA_001045455	GCA_001050135	SRR2106399	GCA_001258055	SRR2106282	SRR2080278	
Assignment	Chryseobacterium	Cyclobacterium	Leptolyngbya	Rhodobacteraceae	Thermincola	Chromatiales	
Rank	Genus	Genus	Genus	Family	Genus	Order	
Sensitivity							**Mean**
Kraken	0	0.149	0	0.203	0.831	0.005	0.198
Minikraken	0	0.096	0	0.093	0.787	0.001	0.163
Seed-Kraken	0	0.211	0.001	0.352	0.836	0.004	0.234
Clark	0	0.065	0.001	0.072	0.595	0.002	0.122
One Codex	0.313	0.225	0.01	0.965	0.827	0.005	0.391
One Codex - RefSeq	0.191	0.142	0.002	0.244	0.83	0.005	0.236
Metaphlan	-	-	-	-	-	-	-
GOTTCHA	-	-	-	-	-	-	-
Specificity							**Mean**
Kraken	0	0.961	0.013	0.920	0.995	0.102	0.499
Minikraken	0	0.985	0.04	0.943	0.998	0.266	0.539
Seed-Kraken	0	0.932	0.207	0.947	0.993	0.156	0.539
Clark	0	0.939	0.002	0.823	0.991	0.011	0.461
One Codex	0.920	0.927	0.109	0.999	0.988	0.082	0.671
One Codex - RefSeq	0.928	0.919	0.186	0.942	0.995	0.208	0.696
Metaphlan	0.935	1.000	0	1.000	0	0	0.489
GOTTCHA	0	1.000	0	1.000	0.971	0	0.495

Table 3. Accuracy of prediction for six organisms not found in any of the reference databases used by

these methods. Note that Metaphlan and GOTTCHA results are presented as specificity metrics, as the

abundance metrics reported by those methods are relative to the total classified composition of each

sample (rather than the number of input reads).

4.4 Analysis Time

The time required for completing analysis of the 50M simulated reads for each method is presented in

Table 4 (GOTTCHA and Metaphlan are not shown because they were not run on the read-level evalua-

tion datasets). Although the complete set of 50M simulated reads were run in parallel batches of 10M

reads, the time presented here is the cumulative processing time, rather than the shorter start-to-finish

period of parallelized execution across multiple computational nodes. All methods were run with 12

processors on equivalent computational resources. Of these read-classification methods, Minikraken and

Clark were the most rapid, and Seed-Kraken was the slowest.

	Analysis Time (min:sec)
Clark	04:50
Minikraken	05:15
Kraken	06:26
One Codex	22:13
One Codex - RefSeq	21:49
Seed-Kraken	45:58

Table 4. Computational time required for each method to classify the 50M simulated reads.

5   DISCUSSION

The widespread adoption of high-throughput sequencing for the detailed characterization of mixed mi-

crobial samples presents an immense opportunity and challenge to the field of microbial genomics. Alt-

hough genomic sequences can be used pinpoint the organisms in a sample down to the level of a single

strain, accurate detection of each strain completely depends on the ability of a computational method to

search for genomic sequences across the extent of known life. Not only does the volume of microbial

reference genomes exceed that of the human genome by many-fold (181 billion bases of prokaryotic ge-

nome sequence can be found in NCBI as of Aug. 25, 2015), but the sequences found in wild-caught mi-

crobes may differ significantly from those of their domesticated relatives (Rinke, et al. 2013). In the face

of these serious computational challenges, a large panel of computational methods have been proposed

recently to perform the task of microbial detection (Oulas, 2015). However, it can be prohibitively diffi-

cult for a microbial researcher to rigorously evaluate all of the possible options in order to select the

most appropriate method. To address that challenge, we have provided a comprehensive analysis of the

performance of a wide range of the most widely adopted analytical methods. Moreover, we have made

the test data and analytical framework available for others to evaluate future methods against a common

reference. We believe that the large volume (over 50M simulated reads), phylogenetically complexity

(10,639 randomly selected source organisms), and analytical portability (NCBI taxonomic identifiers

recorded within read headers), makes this dataset a valuable resource for the research community.

One Codex provides the highest degree of accuracy, both sensitivity and specificity, across all taxonom-

ic ranks, with 62.1% per-read sensitivity and 98.7% per-read specificity at the species-level (Table 2).

The absolute performance of any detection method as a binary classifier was summarized by ROC anal-

ysis, showing that One Codex had the best performance (AUC: 0.97), with other methods performing

roughly equally (AUC: 0.82 – 0.88). For purposes of illustration, the accuracy of each method was

shown at an absolute abundance cutoff of 100 reads (Fig. 3). At that threshold for calling a species as

present in a sample, One Codex showed a much lower FPR than other methods, suggesting that the larg-

er set of reference organisms in the One Codex database serves to significantly reduce the number of

species-level false positive detections with that method.

The array of methods evaluated here allows for an intriguing comparison of the effect of reference data-

base and classification algorithm on overall performance. Kraken and Seed-Kraken use differing as-

signment algorithms and a common reference database, with Seed-Kraken providing higher sensitivity

and Kraken providing higher specificity. This finding replicates similar precision/sensitivity trade-off

that was observed previously for Seed-Kraken at the species-level (Břinda, 2015). While the perfor-

mance of both Kraken and One Codex is presented with two alternate databases, the smaller Minikraken

database was constructed by selecting a smaller number of kmers per organism, and the smaller One

Codex RefSeq database was constructed by selecting a restricted number of reference organisms, so the

resulting differences in sensitivity and specificity are not directly comparable. As the genomes encoun-

tered in real-world metagenomic samples rarely exactly match those found in reference databases, it is

important to quantify the accuracy of detection for 'out-of-reference' genomes. Considering only the

reads simulated from reads not found in those reference databases, the sensitivity and specificity of de-

tection for One Codex was 0.532 and 0.875, respectively, while One Codex RefSeq was 0.511 and

0.835, reflecting only a modest decline in performance for that large group of 'out-of-reference' ge-

nomes. Further research into the effect of reference database composition on predictive accuracy could

conceivably enable the creation of classification methods with smaller computational footprints and im-

proved performance.

The largest difference in performance between classification methods can be seen in the "taxonomically

novel" test datasets. Each method detects a different subset of organisms, indicating that the composition

of each reference database highly determines the ability of a method to detect a given organism. Overall,

One Codex had the highest average sensitivity (39.1%), which was far higher than the next-most sensi-

tive methods One Codex RefSeq (23.6%) and Seed-Kraken (23.4%). This set of six datasets is a useful

demonstration of the fundamental challenge of accurately classifying sequences from organisms not

found in any reference database. Even when the closest possible rank is at the genus or above, each

method varies widely in its ability to assign sequences correctly to that rank. The highly sensitive per-

formance of One Codex against these samples suggests that a large and comprehensive reference data-

base not only enables more accurate detection of well-characterized taxa, but also enables more accurate

detection of taxonomically-novel and phylogenetically divergent organisms.

By evaluating a wide range of taxonomic classification algorithms against a large and complex set of

10,639 simulated genomes, as well as a set of six recently sequenced and phylogenetically-distinct or-

ganisms, we have generated important insight into the ability of microbial researchers to accurately

characterize unknown metagenomic samples. Most notably, because Kraken, Minikraken, One Codex,

and One Codex RefSeq all classify reads using taxonomically-unique 31mers, the differing performance

of these methods is undoubtedly due to the much different composition of those databases, with larger

reference databases leading to greater analytical accuracy. These results show the value of continually

expanding reference database collections in order to more accurately classify the vast pool of unknown,

unsequenced microbial 'dark' matter (Rinke 2013), as well as the specific strains of well-known patho-

gens that cause human disease.

6   ACKNOWLEDGEMENTS

Conflict of Interest: Authors are employed by Reference Genomics, Inc., which develops the One Codex

platform.

7   REFERENCES

Ames SK, Hysom DA, Gardner SN, Lloyd GS, Gokhale MB, Allen JE. Scalable metagenomic taxono-
my classification using a reference genome database. Bioinformatics. 2013; 29(18):2253-60.
Břinda K, Sykulski M, Kucherov G. Spaced seeds improve k-mer-based metagenomic classification.
Bioinformatics. 2015 Jul 25; pii: btv419
Caboche S, Audebert C, Hot D. High-Throughput Sequencing, a Versatile Weapon to Support Genome-
Based Diagnosis in Infectious Diseases: Applications to Clinical Bacteriology. Pathogens. 2014 Apr
2;3(2):258-79. doi: 10.3390/pathogens3020258.
Grad YH, Lipsitch M. Epidemiologic data and pathogen genome sequences: a powerful synergy for pub-
lic health. Genome Biol. 2014 Nov 18;15(11):538. doi: 10.1186/s13059-014-0538-4.
Huang W, Li L, Myers JR, Marth GT. ART: a next-generation sequencing read simulator. Bioinformat-
ics. 2012 Feb 15;28(4):593-4. doi: 10.1093/bioinformatics/btr708.
Liu B, Gibbons T, Ghodsi M, Treangen T, Pop M. Accurate and fast estimation of taxonomic profiles
from metagenomic shotgun sequences. BMC Genomics. 2011;12 Suppl 2:S4. doi: 10.1186/1471-2164-
12-S2-S4.

Mavromatis K, Ivanova N, Barry K, Shapiro H, Goltsman E, McHardy AC, et al. Use of simulated data
sets to evaluate the fidelity of metagenomic processing methods. Nat Methods. 2007 Jun;4(6):495-500.
Mitra S, Rupek P, Richter DC, Urich T, Gilbert JA, Meyer F, et al. Functional analysis of metagenomes
and metatranscriptomes using SEED and KEGG. BMC Bioinformatics. 2011 Feb 15;12 Suppl 1:S21.
doi: 10.1186/1471-2105-12-S1-S21.
Naccache SN, Federman S, Veeraraghavan N, Zaharia M, Lee D, Samayoa E, et al. A cloud-compatible
bioinformatics pipeline for ultrarapid pathogen identification from next-generation sequencing of clini-
cal samples. Genome Res. 2014 Jul;24(7):1180-92. doi: 10.1101/gr.171934.113.
Neimark, J. Quick DNA Scans Could Ensure Food Is Safe to Eat. Scientific American. 2015 Feb.
Oulas A, Pavloudi C, Polymenakou P, Pavlopoulos GA, Papanikolaou N, Kotoulas G, et al. Meta-
genomics: Tools and Insights for Analyzing Next-Generation Sequencing Data Derived from Biodiversi-
ty Studies. Bioinform Biol Insights. 2015 May 5;9:75-88. doi: 10.4137/BBI.S12462.
Rinke C, Schwientek P, Sczyrba A, Ivanova NN, Anderson IJ, Cheng JF, et al. Insights into the phylog-
eny and coding potential of microbial dark matter. Nature. 2013 Jul 25;499(7459):431-7. doi:
10.1038/nature12352.
Segata N, Waldron L, Ballarini A, Narasimhan V, Jousson O, Huttenhower C. Metagenomic microbial
community profiling using clade-specific marker genes. Nat Methods. 2012 Jun 10;9(8):811-4. doi:
10.1038/nmeth.2066.
Wang G, Tang M, Li T, Dai S, Wu H, Chen C, et al. Wenzhouxiangella marina gen. nov, sp. nov, a ma-
rine bacterium from the culture broth of Picochlorum sp. 122, and proposal of Wenzhouxiangellaceae
fam. nov. in the order Chromatiales. Antonie Van Leeuwenhoek. 2015 Jun;107(6):1625-32. doi:
10.1007/s10482-015-0458-7.
Wood DE, Salzberg SL. Kraken: ultrafast metagenomic sequence classification using exact alignments.
Genome Biol. 2014 Mar 3;15(3):R46. doi: 10.1186/gb-2014-15-3-r46.

8   SUPPLEMENTAL FIGURES

Supplemental Figure 1. Example of dataset browser page on the One Codex platform. Datasets are orga-

nized by metadata (e.g. name, date, size, environment, platform, etc.) and user-defined tags. Figure dis-

plays an example of the user searching for datasets containing *Salmonella enterica* above a specified

abundance threshold.

Supplemental Figure 2. Example of metagenomic analysis display for a single sample. Users have the

option of downloading read-level assignments or dataset summaries, comparing the abundance profile

against that of other samples, and navigating to additional analyses for each dataset.