Contour junctions underlie neural representations of scene categories in high-level human visual cortex

Contour junctions underlie neural code of scenes

Heeyoung Choo[1], & Dirk. B. Walther[1]

[1]Department of Psychology, University of Toronto

100 St. George Street, Toronto, ON, M5S 3G3 Canada

Correspondence should be addressed to Heeyoung Choo,

100 St. George Street, Toronto, ON, M5S 3G3 Canada.

Phone: +1-416-946-3200

Email: heeyoung.choo@utoronto.ca

Conflict of Interest: The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Abstract

Humans efficiently grasp complex visual environments, making highly consistent judgments of entry-

level category despite their high variability in visual appearance. How does the human brain arrive at the

invariant neural representations underlying categorization of real-world environments? We here show that

the neural representation of visual environments in scenes-selective human visual cortex relies on statistics

of contour junctions, which provide cues for the three-dimensional arrangement of surfaces in a scene. We

manipulated line drawings of real-world environments such that statistics of contour orientations or

junctions were disrupted. Manipulated and intact line drawings were presented to participants in an fMRI

experiment. Scene categories were decoded from neural activity patterns in the parahippocampal place

area (PPA), the occipital place area (OPA) and other visual brain regions. Disruption of junctions but not

orientations led to a drastic decrease in decoding accuracy in the PPA and OPA, indicating the reliance of

these areas on intact junction statistics. Accuracy of decoding from early visual cortex, on the other hand,

was unaffected by either image manipulation. We further show that the correlation of error patterns

between decoding from the scene-selective brain areas and behavioral experiments is contingent on intact

contour junctions. Finally, a searchlight analysis exposes the reliance of visually active brain regions on

different sets of contour properties. Statistics of contour length and curvature dominate neural

representations of scene categories in early visual areas and contour junctions in high-level scene-selective

brain regions.

Keywords: Neural representations of scenes; encoding of scene structure; contour junctions; scene

categorization; parahippocampal place area; occipital place area; visual cortex; fMRI; multi-voxel pattern

analysis

1. Introduction

When humans view their complex natural environment, they have rapid access to several aspects of its content, such as identity and category of the scene, presence of particular object categories, or global layout (Potter & Levy, 1969; Thorpe, Fize, & Marlot, 1996; Fei-Fei, Iyer, Koch, & Perona, 2007; Greene & Oliva, 2009a, 2009b, 2010). We here investigate the neural mechanisms for the detection of cues to the three-dimensional structure of complex real-world scenes in human visual cortex: We show that the neural representation of scene categories in several high-level visual brain regions, but not in early visual cortex, critically depends on contour junctions.

Entry-level category of a scene is a central aspect of the human visual perception of real-world environment (Tversky & Hemenway 1983). Recent evidence suggests that humans compulsively categorize scenes even if it is detrimental to their task (Greene & Fei-Fei, 2014). Scene categories can be decoded from the parahippocampal place area (PPA) of humans passively viewing scene images (Walther, Caddigan, Fei-Fei, & Beck, 2009; Park, Bradly, Greene, & Oliva, 2011; Walther, Chai, Caddigan, Fei-Fei, & Beck, 2011). Moreover, error patterns for category decoding from the PPA match the pattern of human errors during a rapid scene categorization task (Walther et al., 2009).

There has been considerable debate over the visual properties that underlie the neural representation of scene categories. According to one popular hypothesis, statistics of orientations at different scales as captured by the Fourier amplitude spectrum make accurate computational predictions about entry-level categories of real-world scene images. Subsequent principal component analysis revealed that several diagnostic structures in the Fourier amplitude spectrum are directly related to global scene properties, such as openness, naturalness, or mean distance (Oliva & Torralba, 2001; Torralba & Oliva, 2003). These global properties, in turn, are thought to give rise to a representation of scene categories (Greene & Oliva, 2009a, 2009b, 2010). For instance, the "beach" category is represented as an open natural environment whereas the highway category is represented as an open and man-made environment. In support of this hypothesis, several global scene properties have been found to be represented in activity patterns in the PPA (Harel, Kravitz, & Baker, 2013; Kravitz, Peng, & Baker, 2011; Park et al., 2011, Park, Konkle, & Oliva, 2015).

Here, we posit that real-world scene categories are built by recovering the three-dimensional

shape of the visual world rather than relying on orientation statistics. The visual world can be described

by the relations of surfaces and shapes in space (e.g., by the 2½-dimensional sketch of a scene; Marr,

1982). Contour junctions available in the two-dimensional scene images diagnostically describe these

spatial relations. For instance, L-junctions indicates points of termination of surfaces, T-junctions signify

occlusion in depth, and Y- and arrow-junctions indicate corners facing toward or away from the viewer.

Angles of contour junctions indicate the extent to which depth changes over surfaces (Biederman, 1987).

The diagnostic value of contour junction properties holds for simple artificial scenes consisting of

geometric objects (Guzman, 1968) as well as for real-world object recognition (Biederman, 1987).

Furthermore, a computational model based on category-specific statistics of contour junction properties

explained human errors in rapid categorization of real-world scene images (Walther & Shen, 2014).

According to this structural representation hypothesis, contour junctions should be tied to the neural

representation of complex real-world scenes.

Line drawings are a powerful tool to investigate scene recognition, even though they are

impoverished depictions of scenes, compared to full-textured color photographs. In fact, line drawings can

be categorized or recognized as quickly and accurately as full-textured color photographs (Biederman &

Ju, 1988). Line drawings contain sufficient visual information to allow humans to rapidly judge perceptual

and semantic aspects of scenes (Biederman, Mezzanotte, & Rabinowitz, 1982; Biederman, Teitelbaum, &

Mezzanotte, 1983; Kim & Biederman, 2010; 2011). In addition to resulting in similar behavioral error

patterns (Walther and Shen, 2014), color photographs and line drawings of natural scenes also elicit

similar neural representations of scene categories in the PPA (Walther et al., 2011). More importantly,

line drawings provide explicit descriptions of several informative contour properties not readily accessible

in full-textured color photographs, such as contour orientation, length, curvature, and types and angles of

junctions created by multiple contours (Walther & Shen, 2014). The current study benefits from this

direct access to important contour properties by manipulating predictability of either orientation or

junction statistics for scene categories.

We tested the causal role of these two sets of candidate features, orientation statistics and

junction properties, for the neural representation of scene categories in the human brain. Scene categories

were decoded from the fMRI activity of participants, who passively viewed blocks of line drawings of six

scene categories: beaches, forests, mountains, city streets, highways, and offices. A block design was

employed for its robust signal and for its proven capability to detect category-specific signals in common

to multiple stimuli in a block (Cox & Savoy, 2003; Epstein & Kanwisher 1998; Haxby, Gobbini, Furey,

Ishai, Schouten, & Pietrini, 2001; Kim & Biederman, 2010; Park et al., 2011; Walther et al., 2009). We

devised two image manipulations that allowed for selective disruption of orientation or junction statistics:

One is to rotate line drawings by random angles, which selectively disrupts orientation statistics. The other

is to shift randomly contours of line drawings, which disrupts contour junctions. We then attempted to

decode scene categories from the brain activity of participants while they viewed these manipulated

images. Comparing the results to decoding scene categories from intact images allowed us to assess the

causal involvement of the respective scene properties in the representation of scene categories. Note that

these manipulations *alter* category-specific statistics of the targeted property to be spurious and

uninformative. Although deletion of junctions could be a direct manipulation, pixel removal around

junction locations inevitably affects non-targeted contour properties, such as statistics of orientation,

curvature and length of contours. Our image manipulations, therefore, were to ensure that only one of the

two candidate properties was disrupted by each of the manipulations.

We found that the category representation in two high-level visual areas involved in scene

processing, the PPA, and to some extent, the occipital place area (OPA) and the lateral occipital complex

(LOC) relies heavily on junction properties. It was not possible to decode scene categories from these

areas when junctions were disrupted. Disrupting orientation statistics, on the other hand, did not affect the

representation of scene categories. By contrast, scene categories could be decoded from neural activity

patterns in early visual cortex well above chance for images with disrupted junction or orientation

statistics just as from intact images. We further found that correlation of decoding error patterns from the

PPA with behavioral error patterns was contingent on the preservation of junction properties, whereas

disrupting orientations had no effect on error correlations. Finally, we mapped the reliance of the neural

representations of scene categories on several visual properties throughout visual cortex by matching

patterns of neural decoding errors to error patterns from five computational models of scene categorization

from Walther and Shen (2014).

2. Materials and Methods

2.1 Participants   Sixteen healthy participants (5 females; mean age = 21.6, Standard Deviation (*SD*) =

2.8; one left-handed) were recruited from The Ohio State University community for the functional

magnetic resonance imaging (fMRI) experiment, for which they received monetary compensation of $15

per hour. A separate group of 49 undergraduates at the Ohio State University participated in the behavioral

experiment for course credit. Participants gave written informed consent. Both experiments were approved

by the institutional review board of The Ohio State University. All participants had normal or corrected-

to-normal vision and normal color vision and reported no history of neurological abnormalities. One

participant (female, right-handed) was excluded from further analysis of the fMRI experiment due to

excessive head movement during scans. Three participants were excluded from the analysis of the

behavioral experiment because they did not complete the entire experiment or did not comply with the

instructions.

2.2 Stimuli & Apparatus   Stimuli consisted of 475 vectorized line drawings of six categories of real-

world scenes (beaches, forests, mountains, city streets, highways, and offices) from Walther et al. (2011).

We generated three versions of each line drawing. Intact line drawings were generated by applying a

curcular aperture (Figure 1A). Rotated line drawings were rotated the whole image by an angle randomly

selected from 10 – 340° with 30° increments (Figure 1B). Distributions of contour orientation peaked at 0°

and 90° in most of the six scene categories (Walther & Shen, 2014). Thus, rotation by 90°, 180° and 270°

were deliberately avoided. Contour-shifted line drawings were generated by randomly translating

individual contours within the circular aperture (Figure 1C). This manipulation ensured the disruption of

the relations between contours, represented by contour junctions, while keeping all other contour

properties constant. Note that both image rotation and random contour-shifting change local contour

property statistics. Random image rotation not only systematically alters the original orientation statistics

within a local image patch, but it also changes the contour junction statistics within that local patch (i.e.,

the contour junction statistics of a different portion of the image will substitute the original local

statistics). Similarly, random contour-shifting alters orientation statistics within a local image patch, and

also generates new spurious contour junctions in the patch. The difference between these manipulations is

their effect on *global* image statistics. Rotation preserves the 3D relationships between surfaces and

objects, and contour shifting does not.

As a result of these two manipulations, we obtained a total of 475 triplets, each of which

consisted of an *intact*, a *rotated*, and a *contour-shifted* line drawing derived from the same color

photograph of a real-world scene[1]. The same triplets were used for all participants in both fMRI and

behavioral experiment.

Both experiments were controlled using Python 2.5 with VisionEgg 1.2 on a PC with Microsoft

Windows XP. Stimuli for the fMRI experiment were back-projected onto a screen mounted in the back of

the scanner bore with a DLP projector (Christie DS+6K-M 3-chip SXGA+) at a resolution of 1280 x 1024

pixels. Participants viewed stimuli through a mirror mounted on the head coil. Line drawings were

rendered as black lines on a white background (2 pixels width) at a resolution of 1023 x 1023 pixels,

which subtended approximately 17º x 17º of visual angle. Line drawings were seen through a circular

aperture of 1023 pixels diameter. The part of the screen outside the circular aperture was 50% gray. A

white fixation cross with a black outline was drawn at the center of the screen and subtended 0.5º x 0.5º of

visual angle. Stimuli for the behavioral experiment were displayed on a CRT monitor with 1024 x 768

pixels resolution and 150 Hz refresh rate. Line drawings were rendered as black lines of 1-pixel width on a

white background at a resolution of 600 x 600 pixels (approximately 18º x 18º), and seen through a

circular aperture of 600 pixels diameter. The fixation cross had a size of 1º x 1º.

2.3. Experiment Design   In the fMRI experiment, participants were asked to attentively view the line

drawings while fixating on the central cross. To ensure that participants followed the instruction, we

monitored participants' eye-movements in real-time using an MR compatible Eyelink 1000 system, but

eye-movements were not recorded. Each participant viewed a total of 384 triplets (64 per scene category)

randomly chosen from the 475 triplets. All participants had eight runs, 6 min and 12 sec in length. Each

---

[1] 2D-fast Fourier transform analysis of the triplets confirmed that our manipulation targeting the orientation statistics held in the Fourier space as well. Random contour-shifting had little impact on the Fourier amplitude spectrum, and the correlation in the Fourier amplitude spectrum were high between intact and rotated line drawings, Fisher's $z = 3.278$ ($r = .997$). In contrast, the average correlation between the intact and rotated line drawings was relatively low, Fisher's $z = 1.475$ ($r = .901$). The difference becomes even more pronounced when adjusting for the average correlation between images from different triplets; between intact and contour-shifted: $z_{adj} = 1.073$ ($r_{adj} = .791$), between intact and rotated: $z_{adj} = .030$ ($r_{adj} = .030$).

run included 18 blocks of all possible combinations of the three line drawing types (intact, rotated, and

contour-shifted), and the six basic scene categories (beaches, forests, mountains, city streets, highways,

and offices). During each block, eight line drawings from the same image type and scene category were

shown for 800 ms, followed by a 200 ms blank per scene image. 12 sec of a blank fixation periods were

inserted between blocks as well as at the beginning and the end of each run. The order of blocks within

runs was counterbalanced across runs and participants according to image type and scene category.

In the behavioral experiment images from all six scene categories were randomly interleaved.

Participants were asked to indicate the categories of scene images by pressing one of six keys (s, d, f, j, k,

and l) on a computer keyboard. The mapping between categories and keys was assigned randomly to each

participant. Each trial started with a fixation period of 500 ms, followed by a line drawing for a variable

amount of time (250 ms initially), which was followed by a texture mask for 500 ms and a blank period

for another 2000 ms. The texture mask was derived from a mixture of textures synthesized from all six

scene categories (Loschky, Hansen, Sethi, & Pydimarri, 2010; Portilla & Simoncelli, 2000). Participants'

key responses were recorded from the onset of the image until the end of the blank period. If no response

was made by the end of the blank period, the trial was recorded as incorrect. In the first phase of the

experiment, participants practiced the response mapping until they achieved 90% accuracy. In the

following stair-casing phase the stimulus onset asynchrony (SOA) was adjusted to 65% accuracy using the

QUEST algorithm (Watson & Pelli, 1983) for each participant. By using the stair-cased SOA and the

perceptual masking procedure, we aimed to provoke erroneous responses, so that we could compare the

error patterns between behavior and neural decoding reliably. A randomly selected subset of twelve

triplets of each category was shown for practice and stair-casing, leaving 60-68 triplets per category for

testing. In practice and stair-casing, images were presented in their intact version, and participants were

alerted to their mistakes by a beep.

During the testing phase, 60 triplets per category were randomly selected from the unused sets.

Each image was shown only once during testing, either as an intact line drawing, a rotated line drawing, or

a line drawing with randomly contour-shifted contours. 360 trials were grouped into 18 blocks of 20

images. All three line drawing types and six scene categories were presented intermixed within a block.

Participants no longer received feedback during the testing phase of the experiment. The SOA was fixed

to the final SOA of the stair-casing procedure. We excluded data from the seven participants with SOAs

exceeding 100 ms from further analysis[2]. As a result, the final SOAs of the remaining 39 participants

ranged from 17 – 87 ms (M = 34 ms, SD = 19 ms). The behavioral data were recorded in three confusion

matrices, one for each image type. The rows of a confusion matrix indicate the scene categories presented

to a participant, and the columns indicate the participant's response. Cells contain the relative frequency of

participants responding with the category indicated by the column, given that the presented image was of

the category indicated by the row. Thus, diagonal entries contain correct responses of a scene

categorization task, and off-diagonal entries contain errors in scene categorization.

2.4. fMRI Data Acquisition and Preprocessing   MRI images were recorded on a 3 Tesla Siemens

MAGNETOM Trio MRI scanner with a 12-channel head coil at the Center for Cognitive and Behavioral

Brain Imaging (CCBBI) at The Ohio State University. High-resolution anatomical images were obtained

with a 3D-MPRAGE (magnetization-prepared rapid acquisition with gradient echo) sequence with sagittal

slices covering the whole brain; inversion time = 930 ms, repetition time (TR) = 1900 ms, echo time (TE)

= 4.44 ms, flip angle = 9°, voxel size = 1 x 1 x 1 mm, matrix size = 224 x 256 x 160 mm. Functional

images were recorded with T2*-weighted echo-planar sequences with coronal slices, covering

approximately the posterior 70% of the brain: for the main experiment, TR = 2000 ms, TE = 28 ms, flip

angle = 72°, voxel size = 2.5 x 2.5 x 2.5 mm, matrix size = 90 x 100 x 35 mm. fMRI data were registered

to a reference volume (the first volume of the fourth run) using AFNI to correct for head motion during

the experiment. Then, fMRI data were smoothed using a 2 mm full-width-at-half-maximum (FWHM)

Gaussian filter and converted to percentage signal change with respect to the mean of each run.

2.5. ROI-Based Neural Decoding

2.5.1. Decoding Accuracy   As a preprocessing step for neural decoding we regressed out nuisance

parameters using a general linear model (GLM) with regressors only for head motion and scanner drift.

The residuals of the GLM analysis were averaged over the durations of individual blocks, subject to a

---

[2] Including these participants to the analysis did not change the pattern of results. However, as they acquire experience on the task, their relatively long presentation time reduced erroneous observations. Since our objective of having a brief presentation was to compare error patterns between neural decoding and behavior, we decided a priori not to include participants with SOAs < 100 ms to maximize the variance in error patterns.

hemodynamic delay of 4 sec. The resulting 144 brain volumes (one for each block) were used as input for

multi-voxel pattern analysis (MVPA).

MVPA was performed within pre-specified ROIs using a linear support vector machine (SVM)

classifier (linear kernel, using LIBSVM, Chang & Lin, 2001). The classifier was trained to associate the

correct category label to the blocks in seven of the eight runs, leaving out one run for testing. The

categories for the blocks in the left-out run were predicted by the trained classifier. This leave-one-run-out

(LORO) cross-validation was repeated until each of the eight runs was left out once. The fraction of

blocks with correct test predictions was recorded as accuracy, and misclassifications were recorded in a

confusion matrix (for example see Figure 2B). To investigate the effect of image rotation and contour-

shifting on the representation of scene categories, LORO cross validation was performed both within

image type (using the same image type for training and testing) and across image types (training on one

and testing on another image type). In each case, accuracy was compared to chance (1/6) at the group

level using one-tailed one-sample t-tests.

2.5.2. Error Pattern Correlation between Brain and Behavior   We measured the similarity of

underlying categorical representations by correlating decoding error patterns from each of the ROIs to

behavioral error patterns from the rapid scene categorization experiment (Walther, Beck, & Fei-Fei,

2012). The vector consisting of the 30 off-diagonal entries of the confusion matrix from an ROI was

correlated to the vector of 30 off-diagonal entries of the confusion matrix from behavioral scene

categorization. Statistical significance of the correlation was established non-parametrically against the

null distribution of all error correlations obtained from jointly permuting rows and columns of the

behavioral confusion matrix.

How does disruption of contour orientation or junction properties modulate error correlations

between neural decoding and behavior? Since we had the same three image types (i.e., intact, rotated, and

contour-shifted) for both neural decoding and behavioral rapid scene categorization, we could examine

effects of property disruption in a 3-by-3 pattern of correlations. We modeled these correlation patterns as

a linear combination of three models of the interaction between behavior and patterns of brain activity

(Figure 4C). The first model is straightforward in that error correlations between neural decoding and

behavior for the same image types are correlated (*same type* model). The second model states that error

patterns from neural decoding for intact line drawings correlate to error patterns from the behavioral

categorization of rotated line drawings and vice versa. This *intact–rotated* model prediction is based on

the idea that junction properties are necessary for maintaining the error pattern similarities between neural

decoding and behavior, which had been reported using intact line drawings (Walther et al. 2011). The last

model assumes that orientation statistics leads to similarities in error patterns between neural decoding and

behavior. This *intact–contour-shifted* model predicts high error correlation between neural decoding and

behavior between intact and contour-shifted line drawings. The weights belonging to the three models

were obtained by linearly regressing the error correlation patterns for all MRI participants onto the model

regressors shown in Figure 2C.

We tested which of the three models explain the relationships in the 3-by-3 error correlation

patterns using a linear mixed-effects model (lme4 package in R, Bates, Maechler, Bolker, & Walker,

2014), which included the three idealized models as fixed effects, and participants as random effects. Prior

to the regression analysis, error pattern correlation values were normalized using Fisher's z

transformation. Thus, the coefficients of the predictors provided estimates of how well each of the three

models predicts the error correlations between neural decoding and behavior.

2.6. Searchlight Analysis

2.6.1. Decoding Accuracy   We explored how the human visual cortex outside of the pre-defined

ROIs represents categorical information about scenes using the Searchmight toolbox (Pereira & Botvinick,

2011). Searchlight analysis was performed with partial coverage in the coronal direction, which was

sufficient to encompass approximately the posterior 70% of the brain on average across the participants.

The same block-averaged data used in the previous ROI-based analysis entered the searchlight analysis.

We defined a cubic "searchlight" of 125 voxels, whose size was matched to the average size of unilateral

PPA across participants (142.9 voxels, *SD* = 66.8 voxels) as closely as possible. The searchlight was

centered on each voxel at a time (Kriegeskorte, Göbel, & Bandettini, 2006), and LORO cross-validation

analysis was performed within each searchlight location using a Gaussian Naïve Bayes classifier until all

voxels served as the center of the searchlight. Decoding accuracy, as well as the full confusion matrix at a

given searchlight location, were assigned to its central voxel. We performed the searchlight analysis

separately for decoding of each of the three line drawing types, resulting in three individual accuracy maps

for each participant.

To examine the agreement between the searchlight and the ROI-based analysis, we counted

overlap between searchlight results and the areas V1-4, PPA, OPA, RSC, LOC, and FFA. Accuracy maps

were thresholded at $p < .005$ (one-tailed p-values were obtained by the analytic methods provided by the

Searchmight toolbox), and cluster-corrected using α probability simulation separately per each participant.

Overlap with ROIs was computed as a percentage of ROI voxels that were included in the thresholded

accuracy maps.

For group-analysis, we first co-registered each participant's anatomical brain to the Montreal

Neurological Institute (MNI) 152 template (Fonov, Evans, McKinstry, Almli, & Collins, 2011) using a

diffeomorphic transformation as calculated by AFNI's 3dQWarp. We then used the same transformation

parameters to register individual decoding accuracy maps to MNI space using 3dNWarpApply, followed

by spatial smoothing with a 2 mm FWHM Gaussian filter. To identify voxels with decodable categorical

information, we performed one-tailed t-tests to test whether decoding accuracy at each searchlight location

was above chance (1/6). After thresholding at $p < .005$ (one-tailed) we conducted a cluster-level correction

for multiple comparisons, applying a minimum cluster size of 12 voxels, the average cluster size obtained

from the α probability simulations conducted individually ($SD = 0.7$ voxels). After thresholding by

decoding accuracy, error pattern correlations were computed between decoding from a searchlight

location and each of the five computational models to determine max property of each searchlight

location.

The group-level ROIs were drawn by registering ROIs of individual participants to MNI space

using the same transformation parameters and overlaying them. Voxels counted in at least four

participants were defined as group-level ROIs. This decision was made to ensure reasonably sized group-

level ROIs while minimizing overlap between them. Finally, we excluded any voxels counted in more

than a single group-level ROI.

2.6.2. Error Pattern Correlation to Computational Models   We asked which contour properties

contribute to the categorical representations contained in each searchlight location by comparing error

patterns (Walther, Beck, & Fei-Fei, 2012). Previously, we had developed computational descriptions of

the same line drawings based on five contour properties – orientation, length, curvature, junction types,

and junction angles (Walther & Shen, 2014). These five image properties were computed directly from the

vectorized line drawings. Separate linear support vector machine classifiers were trained to predict

categories of line drawings of scenes using histograms of each of these five properties in turn. Test errors

from a ten-fold cross-validation analysis were recorded in separate confusion matrices, one for each image

property. Here, we correlated error patterns from decoding scene categories at each searchlight location

with those from the computational analysis based on each of the five properties. We call the property with

the highest correlation at a given searchlight location "max property". This analysis was performed

separately for each type of line drawing and restricted to voxels with above-chance decoding accuracy.

3. Results

3.1. ROI-Based Neural Decoding

3.1.1. Within-Type Decoding   Separate classifiers were trained to discriminate scene categories

based on neural activity patterns recorded while participants viewed intact, rotated, or contour-shifted line

drawings. The classifiers were then tested on independent data in an LORO cross-validation procedure,

separately for V1-4, PPA, OPA, RSC, LOC, and FFA. Consistent with previous findings, one-tailed t-tests

showed that scene categories of intact line drawings were correctly decoded significantly above chance

(1/6) in most of the visually active ROIs: V1-4, PPA, OPA, and LOC. Decoding accuracy for the RSC

was comparable to the previously reported accuracy from the same 6-way category decoding (Walther et

al., 2011), but failed to reach significance. As expected, decoding accuracy from the FFA was not

significantly above chance.

How does disruption of orientation or junction statistics affect the neural representation of scene

categories? In V1-4, scene categories could be decoded significantly above chance for both rotated and

contour-shifted just as for intact line drawings. In the PPA, OPA, and the LOC, however, scene categories

could only be decoded from rotated line drawings, but not from contour-shifted line drawings. The RSC

showed a similar pattern of results, but category decoding for rotated line drawings was only marginally

above chance (for average decoding accuracies and standard error of means see Figure 1B, for detailed

statistical results see Table 1).

Table 1. Results of one-tailed t-tests for within-type decoding. Significance was adjusted using the false discovery rate for multiple comparisons correction.

| ROI | df | Within-Type Decoding | | | | | |
| | | Intact | | Rotated | | Contour-Shifted | |
		t	q	t	q	t	q
V1	14	5.047	$2.67 \cdot 10^{-4}$	4.551	$3.40 \cdot 10^{-4}$	4.044	$6.04 \cdot 10^{-4}$
V2	14	3.041	$5.37 \cdot 10^{-3}$	2.941	$5.37 \cdot 10^{-3}$	3.900	$2.40 \cdot 10^{-3}$
V3	14	3.453	$1.94 \cdot 10^{-3}$	4.491	$3.81 \cdot 10^{-3}$	4.544	$3.81 \cdot 10^{-3}$
V4	12	3.892	$1.07 \cdot 10^{-3}$	5.825	$1.22 \cdot 10^{-4}$	4.324	$7.42 \cdot 10^{-4}$
PPA	14	2.492	.0194	2.763	.0194	.871	.199
OPA	11	3.276	$5.54 \cdot 10^{-3}$	3.325	$5.54 \cdot 10^{-3}$	.635	.269
RSC	14	1.746	.0882	1.667	.0882	.698	.248
LOC	14	2.037	.0458	2.944	.0160	-1.108	.857
FFA	14	.575	.431	.000	.500	.636	.431

A) Examples of Line-drawing Scene Images

B) Within-Type Decoding

C) Cross-Type Decoding

Figure 1. Example stimuli and neural decoding results. A) Examples of intact, rotated, and contour-shifted line drawings were derived from the same color photograph of a forest scene. The set of contours is identical across the three images within a triplet. The circular outline is shown here only for illustration and was absent in the stimuli seen by participants. B) Average accuracy rates of within-type category decoding from ROIs. C) Average accuracy rates of cross-type category decoding from the ROIs. The only significant difference in cross-type decoding accuracy between Intact-to-Rotated/Rotated-to-Intact and Intact-to-Contour-Shifted/Contour-Shifted-to-Intact was found in the PPA, as indicated above the bracket bridging the two bars. Error bars are standard errors of means. Dashed lines indicate chance performance (1/6). The significance of the one-sample t-test (one-tailed) was adjusted for multiple comparisons and marked above each bar, *$q < .05$, **$q < .01$, ***$q < .001$.

3.1.2. Cross-Type Decoding   If the neural representation of scene categories is indeed preserved

under random image rotation but destroyed by shifting contours, then we should expect that a decoder

trained on intact line drawings should be able to predict scene categories for rotated but not contour-

shifted line drawings (and vice versa). We tested these predictions in several visual areas. Using the same

LORO cross-validation procedure, we compared decoding performance across four conditions: intact-to-

rotated (IR), rotated-to-intact (RI), intact-to-contour-shifted (IS), and contour-shifted-to-intact (SI).

Figure 1C shows the group average accuracies of the four cross-type conditions. The one-tailed t-

test comparing decoding accuracy to chance showed that cross-type decoding from the early visual areas

was successful for all four cross-type decoding conditions. By contrast, cross-type decoding from the PPA

was significantly more accurate than expected by chance only for IR and RI, but not for IS and SI. The

same pattern was also found in the RSC, although to a reduced extent. Interestingly, in the OPA, cross-

type decoding was possible not only between intact and rotated line drawings but also between intact and

contour-shifted line drawings, although less accurately. Similarly, accuracy from the LOC was

significantly above chance for IR, RI, and IS, also marginally above chance for SI (for details on statistical

tests, see Table 2).

To further examine the differences across the brain regions, we conducted a repeated measures

ANOVA by using two factors: (1) Which *type* of disruption was used for the cross-type decoding, rotated

(IR and RI) vs. contour-shifted (IS and SI), and (2) in which *direction* the decoding was conducted,

trained on intact line drawings and tested on disrupted line drawings (IR and IS) vs. trained on disrupted

line drawings and tested on intact line drawings (RI and SI). Consistent with the results from the one-

sample t-tests, the main effect of type was significant in the PPA, $F(1, 14) = 17.681$, $p = 8.82 \cdot 10^{-4}$, $\eta^2 =$

.558. In other scene-sensitive areas, however, it failed to reach significance: in the OPA, $F(1, 11) = 1.983$,

$p = .188$, $\eta^2 = .152$, in the RSC, $F(1, 14) = 3.278$, $p = .0917$, $\eta^2 = .190$, and in the LOC, $F < 1$. As

expected, in the early visual areas the main effect of type was not significant; $Fs < 1$ in V1-3, and $F(1, 12)$

$= 1.370$, $p = .265$, $\eta^2 = .102$ in V4. Neither the main effect of *direction* nor the interaction between *type*

and *direction* was significant in any of the ROIs.

Table 2. Results of one-tailed one-sample t-tests for cross-type decoding. Significance was adjusted using the false discovery rate for multiple comparisons correction.

		Cross-Type Decoding							
ROI	df	Intact to Rotated		Rotated to Intact		Intact to Contour-Shifted		Contour-Shifted to Intact	
		t	q	t	q	t	p	t	q
V1	14	6.738	$1.86 \cdot 10^{-5}$	3.757	$1.06 \cdot 10^{-3}$	5.778	$3.18 \cdot 10^{-5}$	6.330	$1.86 \cdot 10^{-5}$
V2	14	3.410	$4.23 \cdot 10^{-3}$	2.882	$7.60 \cdot 10^{-3}$	2.764	$7.60 \cdot 10^{-3}$	5.955	$7.02 \cdot 10^{-5}$
V3	14	7.378	$6.92 \cdot 10^{-6}$	5.013	$1.90 \cdot 10^{-4}$	3.780	$1.02 \cdot 10^{-3}$	4.326	$4.64 \cdot 10^{-4}$
V4	12	4.484	$7.48 \cdot 10^{-4}$	5.126	$5.02 \cdot 10^{-4}$	4.156	$8.90 \cdot 10^{-4}$	2.756	$8.70 \cdot 10^{-3}$
PPA	14	3.572	$3.89 \cdot 10^{-3}$	3.452	$3.89 \cdot 10^{-3}$	-.642	.734	.564	.388
OPA	11	4.231	$2.82 \cdot 10^{-3}$	2.469	.0312	2.031	.0336	2.093	.0336
RSC	14	2.200	.0451	2.978	.0120	1.126	.139	1.261	.139
LOC	14	2.099	.0363	3.246	.0112	2.193	.0363	1.512	.0752
FFA	14	-.105	.631	-.341	.631	-.188	.631	1.183	.513

3.1.3. Correlation between Neural and Behavioral Error Pattern   To explore the similarity of the

underlying categorical representations between neural decoding and behavior, we performed a behavioral

categorization experiment with a separate group of 49 participants. Participants were shown a line drawing

of natural scenes, followed by the perceptual mask, and asked to indicate its scene category as either a

beach, a forest, a mountain, a city street, a highway, or an office. Following practice and stair-casing,

participants' performance stabilized at stimulus-onset-asynchronies (SOA) of 13 – 87 ms (M = 34 ms, SD

= 19 ms). Average accuracy during the test phase pooled over all line drawing types was 45.5 % (Standard

Errors of Means (*SEM*) = 1.8%). A repeated-effects ANOVA of accuracy showed a significant effect for

type of line drawing, $F(1.69, 64.06) = 148.476$, $p = 2.22 \cdot 10^{-16}$, $\eta^2 = .796$ (degrees of freedom were adjusted

due to a violation of sphericity). Accuracy was highest for intact line drawings (M = 62.3%, *SEM* = 2.9%),

followed by rotated line drawings (M = 44.1%, *SEM* = 2.2%), and lowest for contour-shifted line drawings

(M = 30.0%, *SEM* = 1.2%). The accuracy of contour-shifted line drawings was still significantly above

chance, $t(38)=11.051$, $p = 9.88 \cdot 10^{-14}$.

Responses from the behavioral experiments were recorded in confusion matrices, separately for

the three types of line drawings (see Figure 2A for intact; for behavioral confusion matrices of all three

image types, see Figure S1). Off-diagonal elements of the confusion matrices represent categorization

errors. Errors from the behavioral experiment were correlated with the errors made when decoding scene

categories from brain activity for each of the three types of line drawings, separately per ROI and

participant (see Figure 2B for the confusion matrix for decoding rotated line drawings from the PPA of

one participant; for exclusive confusion matrix for neural decoding see Figure S2-S3). As can be seen in

Figure 3A, error correlation was high when comparing the behavior and neural decoding for the same

types of images (the diagonal of the three-by-three correlation matrices). In the PPA and OPA, the

correlation was also high between intact and rotated, but not between intact and contour-shifted line

drawings. In V1, no particular pattern of error correlations is discernible.

We modeled the error correlation patterns as a linear combination of three idealized models. The

same-type model hypothesized that error patterns would match between behavior and decoding only for

the same types of line drawings. The intact–rotated model predicts high brain-behavior error correlations

between intact and rotated line drawings, assuming that disruption of orientation leaves error correlations

largely unaffected. The intact–contour-shifted model, by contrast, predicts high brain-behavior error

correlations between intact and contour-shifted line drawings, assuming that error correlations are

maintained when junctions are disrupted, (Figure 2C).

A) Behavior

Perceived Category

Confusion Matrix

	beaches	forests	mountains	city streets	highways	offices
beaches	.57	.07	.12	.08	.13	.04
forests	.09	.67	.08	.06	.05	.05
mountains	.12	.07	.68	.04	.05	.04
city streets	.06	.08	.05	.61	.16	.05
highways	.05	.05	.05	.14	.65	.06
offices	.04	.06	.04	.16	.10	.59

Accuracy, 62.6%

Error Pattern

B) Neural Decoding

Decoded Category

Confusion Matrix (PPA)

	beaches	forests	mountains	city streets	highways	offices
beaches	.12	.50	.25	.00	.12	.00
forests	.38	.50	.12	.00	.00	.00
mountains	.38	.25	.25	.00	.00	.12
city streets	.12	.12	.12	.25	.00	.38
highways	.12	.12	.00	.00	.38	.38
offices	.00	.12	.12	.38	.25	.12

Accuracy, 27.1%

Error Pattern

C) Correlation between Neural and Behavioral Error Pattern

Neural Decoding (PPA)

	Intact	Rotated	Contour-Shifted
Intact	.52	.50	-.13
Rotated	.53	.46	.04
Contour-Shifted	-.12	.17	-.03

Error Correlations

$= \beta_0 + \beta_{\text{Same Type}} \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} + \beta_{\text{I-R}} \begin{bmatrix} 0 & 1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix} + \beta_{\text{I-S}} \begin{bmatrix} 0 & 0 & 1 \\ 0 & 0 & 0 \\ 1 & 0 & 0 \end{bmatrix} + \epsilon$

Figure 2. A schematic description correlation between brain and behavior error pattern. A) Group-average confusion matrix for behavioral scene categorization of rapidly presented intact line drawings. B) Confusion matrix obtained from decoding scene categories from rotated line drawings in the PPA for an individual participant. C) Off-diagonal entries of the confusion matrices were correlated for all three image types, resulting in a three-by-three error correlation matrix. The error correlations entered a linear regression analysis to measure how much each of the hypothesized models explains the observed patterns of error correlations.

The coefficients corresponding to each of the three idealized models were computed using a

mixed-effects linear regression model with prediction models as fixed effects and participants as random

effects. Figure 3B shows the estimated coefficients of the fixed effects for the prediction models for all

ROIs. In V1-3, none of the three models significantly explained the error correlation patterns between

neural decoding and behavior. However, further along in the visual processing stream, both the same type

and the intact–rotated model significantly explained error correlation in V4, PPA, OPA, RSC, and LOC.

The intact–contour-shifted model, on the other hand, did not contribute to the patterns in any of the ROIs

(for details on statistical tests see Table 3).

Table 3. Results of two-tailed t-tests for coefficients of the three idealized models for explaining patterns of error correlation between neural decoding and behavior. Significance was adjusted using false discovery rate for multiple comparisons correction.

ROI	df	Same Type		Intact-Rotated		Intact-Contour-Shifted	
		t	q	t	q	t	q
V1	14	1.166	.732	.391	.999	$-1.646 \cdot 10^{-5}$	.999
V2	14	1.878	.0718	2.229	.0718	-.103	.918
V3	14	1.786	.111	2.289	.0663	-.912	.362
V4	12	3.376	$1.10 \cdot 10^{-3}$	3.267	$3.27 \cdot 10^{-3}$	-.103	.918
PPA	14	3.035	$3.62 \cdot 10^{-3}$	4.440	$2.69 \cdot 10^{-5}$	-.912	.362
OPA	11	3.056	$5.61 \cdot 10^{-3}$	2.899	$5.61 \cdot 10^{-3}$	-.107	.915
RSC	14	2.439	.0312	2.311	.0312	.238	.812
LOC	14	2.831	$8.31 \cdot 10^{-3}$	2.774	$8.31 \cdot 10^{-3}$	.795	.427
FFA	14	.568	.570	1.315	.189	-.0324	.974

A) Error Correlations between Neural Decoding and Behavior

B) Estimated Coefficients (β) of the Idealized Models

Figure 3. Results of error pattern correlations between neural decoding and behavior. A) Error correlations between neural decoding and behavior in V1-4, PPA, OPA, RSC, and LOC. Three-by-three correlation matrices were created by correlating group average confusion matrices obtained from fMRI and group average confusion matrices from the behavioral experiment. I stands for intact, R for rotated, and S for contour-shifted line drawing conditions for both neural decoding and behavior. The rows represent behavioral conditions, and the columns represent neural decoding conditions. Thus, each entry of a correlation matrix indicates an error pattern correlation value, r, between neural decoding and behavior. The significance of the correlation was determined non-parametrically using a permutation test, in which we computed correlations for all 720 permutations of the six category labels. B) Estimated coefficients of the three idealized models obtained from the ROIs. Error bars are estimated standard errors of means. The significance of the one-sample t-test (two-tailed) was corrected for multiple comparisons using false discovery rate and marked above each bar, *q < .05, **q < .01, ***q < .001.

3.2. Searchlight Analysis

3.2.1 Decoding Accuracy To further characterize the representation of scene categories throughout visual

cortex, we performed a searchlight analysis of the posterior 70% of the brain that was included in the

partial acquisition scans. At each searchlight location, we attempted to decode scene categories using

LORO cross-validation, separately for intact, rotated and contour-shifted line drawings. This analysis

resulted in spatial maps of decoding accuracy and confusion matrices for each location. To assess the

agreement between the searchlight analysis and the ROI-based analysis we computed the percentage of

voxels in each of the ROIs that overlapped with the searchlight accuracy maps separately for each

participant. The average of the amount of overlap is shown in Table 4. The searchlight maps for decoding

intact line drawings showed the largest amount of overlap with all ROIs. More importantly, the overlap of

searchlight maps with the PPA and the OPA was larger for rotated than for contour-shifted line drawings.

By contrast, a similar amount of overlap was found for V1-4. In fact, the accuracy map of contour-shifted

line drawings overlapped with slightly more V1 and V2 voxels than the accuracy map of rotated line

drawings.

Table 4. Average percentages (%) of overlap of each ROI with searchlight maps computed for the three image types. Standard errors of means are shown in parentheses.

ROI	Intact		Rotated		Contour-Shifted	
V1	19.3	(4.1)	13.2	(2,9)	18.8	(3.3)
V2	11.4	(2.7)	9.3	(2.1)	11.4	(1.9)
V3	9.8	(2.0)	8.6	(2.5)	7.8	(2.3)
V4	10.5	(2.5)	11.6	(4.2)	6.8	(2.1)
PPA	29.3	(6.0)	19.3	(5.4)	4.8	(1.6)
OPA	28.8	(6.5)	16.8	(6.8)	10.2	(3.9)
RSC	17.5	(4.9)	8.7	(3.1)	2.8	(1.5)
LOC	8.1	(2.2)	4.5	(1.9)	3.0	(1.1)
FFA	4.3	(1.5)	3.3	(1.5)	2.3	(1,1)

The group-mean accuracy map of decoding intact line drawings (Figure 4A) showed a large

cluster of voxels in the posterior visual cortex, including the bilateral parahippocampi, left precuneus, and

the lateral end of the left transverse occipital sulcus, as well as the bilateral fusiform and calcarine gyri.

This large cluster extended to the cerebellum bilaterally, but more to the left than the right cerebellum.

The second large cluster encompassed the right middle occipital gyrus extending to the right transverse

occipital sulcus. Another cluster included the right precuneus and the right posterior cingulate gyrus,

which partially overlapped with the right retrosplenial cortex. The group-mean accuracy map of decoding

rotated line drawings (Figure 4C) showed two clusters that largely overlapped with the accuracy map of

decoding intact line drawings. One large cluster encompassed the left parahippocampal gyrus, the

bilateral fusiform gyri, and bilateral calcarine gyri and extended to the bilateral cerebellum. The other

cluster included the right parahippocampal gyrus. By contrast, the group-mean accuracy map of decoding

contour-shifted line drawings (Figure 4E) revealed only one large cluster, which included bilateral

calcarine gyri, fusiform gyri, lingual gyri, and the cuneus, and extended bilaterally to the cerebellum (for

an exhaustive list of peak coordinates, see Table 5).

Table 5. Clusters identified in the searchlight analysis for within-type decoding of intact, rotated, and contour-shifted line drawings.

Decoding Condition	Peak (MNI coordinates)				Volume (μl)	Description
	x	y	z	Accuracy (%)		
Intact						
	2.5	90.5	-4.2	30.4	63234	Occipital pole, calcarine gyri, fusiform gyri, parahippocampal gyri, left precuneus, left transvers occipital sulcus, bilateral cerebellum
	-35.0	85.5	25.8	25.4	5219	Right middle occipital gyrus, right transvers occipital sulcus
	-25.0	63.0	18.2	25.6	1922	Right parieto-occipital sulcus, right retrosplenial cortex
	30.0	45.5	68.2	22.0	391	Left superior parietal gyrus
	-32.5	30.5	-26.8	19.6	188	Right lateral occipito-temporal gyrus (fusiform gyrus)
Rotated						
	10.0	98.0	-14.2	28.0	50938	Occipital pole, calcarine gyri, fusiform gyri, left parahippocampal gyrus, bilateral cerebellum
	-22.5	50.5	-9.2	26.9	4531	Right parahippocampal gyrus
	27.5	85.5	33.2	22.7	375	Left inferior parietal angular gyrus, left middle occipital gyrus
	-47.5	80.5	-1.8	21.8	188	Right middle occipital gyrus
Contour-shifted						
	-15.0	90.5	-6.8	29.3	54938	Occipital pole, calcarine gyri, precuneuses, fusiform gyri, lingual gyri, bilateral cerebellum
	-30.0	30.5	56.2	22.5	703	Right precentral gyrus
	42.5	33.0	28.2	23.7	563	Left posterior lateral fissure, left inferior parieto-supramarginal gyrus.
	-27.5	53.0	-9.2	21.9	484	Right medial occipito-temporal sulcus, right lingual gyrus
	50.0	25.5	48.2	22.6	453	Left inferior parieto-supramarginal gyrus
	-2.5	20.5	76.2	21.7	422	Right paracentral gyrus, right paracentral sulcus
	-57.5	20.5	78.2	17.8	344	Right inferior parieto-supramarginal gyrus
	10.0	38.0	55.8	21.7	250	Left paracentral gyrus, left paracentral sulcus
	-10.0	43.0	78.2	21.4	234	Right paracentral gyrus, right paracentral sulcus
	35.0	93.0	0.8	21.9	219	Left middle occipital gyrus
	-25.0	88.0	25.8	21.0	203	Right superior occipital gyrus.

Figure 4. Neural decoding accuracy and max property maps. A) Searchlight locations with above-chance decoding of intact line drawings are highlighted in red. B) Property with the highest error correlation between searchlight decoding and computational feature model (max property) at the searchlight locations with above-chance decoding of intact line drawings. C) Searchlight locations with above-chance decoding of rotated line drawings are highlighted in green. D) Max property at the searchlight locations with above-chance decoding of rotated line drawings. E) Searchlight locations with above-chance decoding of contour-shifted line drawings are highlighted in blue. F) Max property at the searchlight locations with above-chance decoding of contour-shifted line drawings.

3.2.2. Important Image Property for Neural Decoding   To determine the influence of several kinds

of structural properties of line drawings on the neural representation of scene categories, we correlated

error patterns from each searchlight location (that is, the off-diagonal elements of the confusion matrices)

to those from five computational models of scene categorization. Each of these computational models

relies exclusively on one of five structural properties: contour orientation, length, curvature, and types

and angles of contour junctions (Walther & Shen, 2014). Each searchlight location was labeled according

to the contour property with the highest error correlation, the *max property*. Figure 4B, D, and F show

max property maps for the three image types, restricted to the locations that allowed for decoding of scene

categories significantly above chance (see Figures S4-S6 for unrestricted maps of error correlations and of

max property).

Representation of scene categories in early visual areas relies most heavily on contour length and

curvature for intact line drawings. Junction types are particularly important in foveal regions of early

visual cortex, and also the PPA, the OPA, and the RSC. For rotated line drawings, curvature dominates

early visual areas, while high-level visual areas continue to rely on junction properties. For contour-shifted

line drawings, early visual areas rely most on contour length and curvature. Only a few searchlight

locations in high-level visual areas allow for decoding of scene categories from contour-shifted line

drawings. These effects are quantified more precisely by assessing overlap of these maps with ROIs

(Figure 5).

Voxel statistics for the pre-defined ROIs show several interesting effects. First, representation of

natural scene categories in V1 and V2 relies most heavily on contour length and curvature for intact line

drawings. The importance of junctions increases steadily through V3 and V4, until junctions dominate the

representation of scene categories in the PPA (81.6% of PPA voxels have junction angle or type as max

property), the OPA (66.7%), and the LOC (97.9%). The high reliance on junction properties strongly

manifested even though L-junctions, critical to surface analysis (Biederman, 1987; Guzman, 1968), were

not considered in the computational category prediction (Walther & Shen, 2014). Orientation statistics, by

comparison, play a minor role in the high-level visual areas, except for the RSC (51.8%).

Second, the involvement of orientation statistics in the representation of scene categories is

absent for randomly rotated line drawings as expected. Whereas contour orientation was the max property

for 291 out of 2575 (11.3%) searchlight locations with significant decoding for intact line drawings, this

number fell to 22 out of 2402 (0.9%) searchlight locations with significant decoding for rotated line

drawings. Similarly, junction properties ceased to be the max property almost everywhere for contour-

shifted line drawings. Junction types and angles were the max property for 1469 out of 2575 (57.0%)

searchlight locations for intact but only 38 out of 2021 (1.9%) searchlight locations for contour-shifted

line drawings. These findings confirm the effectiveness of our image manipulations as a tool for probing

the role of structural scene properties in the neural representation of scene categories.

451   Moreover, this shift in the reliance to other structural properties when deprived of contour

452   orientation or junctions demonstrates the flexibility of early visual areas to make use of any visual

453   regularities present in the images. However, junction properties appear to be critical for the neural

454   representation of scene categories in high-level visual areas. Rather than shifting to other structural

455   properties, these areas show a dramatic decrease in the number of searchlight locations that allowed for

456   the decoding of scene categories when junctions were disrupted.

Figure 5. Distribution of max properties within group-level ROIs for decoding of intact (I), rotated (R), and contour-shifted (S) line drawings. Only searchlight locations with above-chance decoding accuracy were counted. Coloring follows the same convention as Figure 4.

4. Discussion

In this study, we used multi-voxel pattern analysis (MVPA) to identify visual properties critical

to the categorical representation of real-world environments in the brain. Consistent with our previous

findings (Walther et al., 2009; 2011), we showed that categorical representations of scenes are distributed

across the human visual cortex. Importantly, they rely on different sets of contour properties along the

course of visual processing. In the PPA, OPA, and LOC, structural relations between contours as

embodied by the distribution of junctions need to be preserved to maintain category-specific brain activity

patterns. Whereas random shifting of contours led to chance-level decoding accuracy, random image

rotation did not undermine decoding accuracy in the PPA, OPA, and LOC.

Cross-type decoding was successful between intact and rotated, but not between intact and

contour-shifted line drawings in the PPA. Note that contour-shifted line drawings still preserved the

statistics of contour orientation, length, and curvature. Yet, this information was not sufficient to give rise

to a decodable neural representation of scene categories in the PPA, underscoring the necessity of junction

properties and, thereby, structural relations between contours for the PPA to encode scene categories.

In contrast, category decoding was successful with contour-shifted line drawings as well as

rotated line drawings from V1 to V4, suggesting that none of the image manipulations was detrimental to

the category-specificity of neural activity patterns for line drawings in early visual areas. Furthermore,

cross-type decoding was successful not only between intact and rotated but also between intact and

contour-shifted line drawings, indicating that the neural representations of scene categories were

compatible across the three line drawing types. In the early visual areas, category-specific neural activity

patterns are not undermined by disrupting a single type of visual statistics, suggesting that the early visual

areas represent scene categories only implicitly by relying on any available statistics indicative of scene

categories in a parsimonious manner.

Analysis of decoding errors confirmed previous findings that error patterns of decoding from the

neural activity in the PPA significantly correlate with those of human scene categorization of intact line

drawings (Walther et al. 2011). Critically, we here show that junction properties but not orientation

statistics of line drawings have to be preserved to maintain such brain-behavior correlation (for searchlight

analysis of error pattern correlation to behavior and its results, see supplementary material; Figure S7).

Preservation of junctions starts to be important for brain-behavior error correlation as early as in V2. This

finding agrees well with neurophysiological studies in non-human primates showing that area V2 is

sensitive to changes in types or angles of contour junctions (Pasupathy & Connor, 2002; Peterhans & von

der Heydt, 1989).

In a searchlight analysis, we found early visual areas to rely on the distributions of orientation,

length and curvature of contours for the neural representation of scene categories. Junction properties, on

the other hand, became increasingly important in near-foveal regions of V1-4 and peaked in the PPA and

OPA. The importance of junctions for the neural representation of scene categories in the PPA persisted

when scene images were rotated by a random angle but disappeared when junctions were disrupted by

randomly shifting contours.

As should be expected, the importance of orientation statistics for the representation of intact line

drawings throughout visual cortex disappeared for rotated images and was supplanted by an increased

reliance on contour length and curvature. Searchlight analysis confirms the hierarchical aspect of neural

representations of scene categories. Once an image of real-world environments proceeds through the

cortical hierarchy, its neural representation relies progressively more on complex visual properties, from

orientation and length extracted in V1 (Hubel & Wiesel, 1962) to curvature and junction properties

extracted in V2 and V4 (Pasupathy & Connor, 2002; Peterhans & von der Heydt, 1989). Recent

computational work showed that junction-like feature representations arise naturally when representations

of complex scenes are learned in simulated multi-layer neural networks (Zeiler & Fergus, 2014).

What would be the mechanisms for contour junctions affecting a neural representation of scene

categories in the PPA? While surface features such as color and orientation gradient may initiate contour

detection and surface delineation (by the primal sketch; Marr, 1982), they do not directly give a rise to the

high-level representation for visual recognition. In fact, visual recognition and categorization hardly

benefit from surface features once important contours are analyzed and their relations are determined

(Biederman & Ju, 1988). Instead, junctions present in two-dimensional (2D) images are informative of

three-dimensional (3D) structural information, because their types and angles are indicative of

arrangements and relations of surfaces in 3D space (Biederman, 1987; Guzman, 1968). The 3D structure

of natural environments can be inferred from the distribution of these viewpoint-invariant properties,

namely junction types and angles. Furthermore, their invariance to changes in viewpoint makes these

properties particularly useful for visual recognition and categorization

516   In fact, 3D structure of scenes is likely to be related to some global scene properties, such as

whether a scene has an open or closed layout (Harel et al., 2013; Park et al., 2011). For example, scenes

with an open layout are usually clutter-free and contain surfaces not obstructing one another, resulting in a

relatively small number of junctions. In contrast, a closed layout is likely to contain more objects and

multiple surfaces overlaying one another, thus creating proportionally more junctions. Consistent with this

idea, recent neuroimaging evidence showed that the PPA is not only sensitive to changes in the statistics

of simple shapes (Cant & Xu, 2012), but also to junction angles (Nasr, Echavarria, & Tootell, 2014).

When combining these results with the sensitivity of the PPA to global scene properties (Kravitz et al.

2011; Park et al. 2011; Harel et al. 2013), a picture of the PPA arises as a visual area sensitive to several

high-level aspects of scenes, such as semantic category, global layout, or relation of the scene to real-

world locations (Marchette, Vass, Ryan, & Epstein, 2014). A recent study clearly shows that the PPA

indeed can encode several aspects of a scene image such as its entry-level category, spatial layout (open

vs. closed), surface texture property, and content (man-made vs. natural) (Lowe, Gallivan, Ferber, & Cant,

in press). With scenes being spatial arrangements of surfaces and objects, the image properties driving

these diverse visual aspects of scenes are those encoding the relationship between surfaces in 3D space,

namely junction types and their angles.

532   Similar to the PPA, the OPA also relies more heavily on junction properties than contour

orientation. Considering its anatomical proximity to the early visual cortex, the OPA is likely to subserve

relatively primitive scene analysis. In fact, receptive fields in the OPA were reported to be smaller than

those in the PPA (MacEvoy & Epstein, 2007). Furthermore, the OPA preferentially activates to spatial

layouts over collections of multiple objects (Bettencourt & Xu, 2013; MacEvoy & Epstein, 2007). The

OPA has been suggested to contain precursory representations of spatial layout of scenes based on

relatively simple features (Baldassano et al., 2013; Dilks, Julian, Paunov, & Kanwisher, 2013; MacEvoy

& Epstein, 2007). We here propose that contour junctions are critical for these representations.

540   Objects are often diagnostic for scene category (Bar & Aminoff, 2003; Greene, 2013). For

instance, a beach scene is more likely to contain palm trees, beach balls, and umbrellas than desks, swivel

chairs, and computer monitors, and *vice versa* in the case of an office scene. It is, therefore, natural that

the object-sensitive LOC contains information about objects, which can be exploited for decoding scene

category or identity (Harel et al., 2013; MacEvoy & Epstein, 2011). The LOC not only activates linearly

to the number of displayed objects (MacEvoy & Epsten, 2011), but it also encodes inter-object

relationships (Kim & Biederman, 2010; 2011). Given recent evidence for a strong functional relationship

between the LOC and PPA, it is highly likely that information about object relations in the LOC is

projected to the PPA (Baldassano et al., 2013), thus contributing the category-specific activity in the PPA.

Our finding that the neural representation of scene categories in the LOC relies almost exclusively on

junction properties is consistent with the reliance of invariant object recognition on non-accidental

properties, most specifically contour junctions (Biederman 1987), which provide cues to the three-

dimensional structure of objects. In addition to their role in defining objects, contour junctions are crucial

to reconstruct spatial arrangements between large-scale surfaces that define the terrain and layout of a

scene, thereby contributing to the neural representations of real-world scene categories.

Random contour shifting also affected grouping properties that were not modeled explicitly in

our computation analysis (Walther & Shen, 2014): proximity between parallel contours, colinearity and

curvilinearity of contours indicating parallel surfaces in depth, and to some extent symmetry involving

multiple contours (Biederman, 1987). These non-accidental properties have in common that they are

defined by spatial relations between contours rather than by properties of individual contours. Junction

statistics capture these spatial relations to only a limited extent. It is therefore remarkable that decoding

error patterns in the PPA, OPA and LOC are predicted so well by junction statistics.

Unlike the other scene-selective visual regions, the RSC has been found to be critical for

embedding scenes in their real-world context or memory representations rather than for perceptual

analysis of scenes. For instance, the RSC plays a critical role in navigation and route learning (Aguirre &

D'Esposito, 1999; Maguire, 2001), and shows preferential neural activity for landmark buildings

compared to non-landmark buildings (Schinazi & Epstein, 2010). The RSC also mediates between

individual scenes in a broad view rather than representing exact perceptual instances of scenes (Epstein,

Parker, & Feiler, 2007; Epstein, Higgins, Jablonksi, & Feiler, 2007; Park & Chun, 2009). We found

neither significant decoding accuracy nor even significant activation in the RSC for line drawings of

scenes (Table S1; for detailed analysis and results see Supplementary materials). We surmise that this may

be because line drawings too dissimilar from actual real-world settings that afford navigation or context-

based memory retrieval.

5. Conclusion

We have shown that the neural representations of scene categories rely on different image

properties throughout the processing hierarchy in the human visual cortex. In early visual areas, any

statistical regularities available in an image had the potential to elicit category-specific patterns of neural

activity. In the scene-selective high-level visual regions, especially in the PPA, accurate statistics of

junction properties was necessary to generate category-specific activity patterns and, importantly, to

establish high correlation of decoding error patterns with patterns of errors observed in human scene

categorization behavior. We conclude that non-accidental 2D cues to 3D structure, in particular contour

junctions, are causally involved in eliciting a neural representation of scene categories in the PPA and the

OPA by providing a reliable description of the 3D structure of real-world environments. Summary

statistics of orientations, on the other hand, are insufficient to elicit a decodable representation of scene

categories in these brain regions.

Acknowledgments

References

Aguirre, G. K., & D'Esposito, M. (1999). Topographical disorientation: A synthesis and taxonomy.

Brain, 122, 1613-1628.

Bar, M., & Aminoff, E. (2003). Cortical analysis of visual context, *Neuron, 38*, 347-358.

Baldassano, C., Beck, D. M., & Fei-Fei, L. (2013). Differential connectivity within the parahippocampal

place area. *NeuroImage, 75,* 236-245.

Bates D, Maechler M, Bolker B and Walker S (2014). lme4: Linear mixed-effects models using Eigen and

S4. R package version 1.1-7, http://CRAN.R-project.org/package=lme4.

Bettencourt, K. C., & Xu, Y. (2013). The role of transverse occipital sulcus in scene perception and its

relationship to object individuation in inferior intraparietal sulcus. *Journal of Cognitive*

Neuroscience, 25(10), 1711-1722.

Biederman, I. (1987). Recognition-by-components: A theory of human image understanding.

Psychological Review, 94(2), 115-147.

Biederman, I., & Ju, G. (1988). Surface versus edge-based determinants of visual recognition. *Cognitive*

Psychology, 20, 38-64.

Biederman, I., Mezzanote, R. J., & Rabinowitz, J. C. (1982). Scene perception: Detecting and judging

objects undergoing relational violation. *Cognitive Psychology, 14,* 143-177.

Biederman, I., Teitelbaum, R. C., & Mexxanote, R. J. (1983). Scene perception: A failure to find benefit

from prior expectancy or familiarity. *Journal of Experimental Psychology, 9*(3), 411-429.

Cant, J. S. & Xu, Y. (2012). Object ensemble processing in human anterior -medial ventral visual cortex.

Journal of Neuroscience, 32, 7885-7700.

Chang, C-C., & Lin, C-J. (2001). LIBSVM: A Library for support vector machines. Software available at

http://www.csie.ntu.edu.tw/~cjlin/libsvm.

Cox, D. D., & Savoy, R. L. (2003). Functional magnetic resonance imaging (fMRI) "brain reading":

Detecting and classifying distributed patterns of fMRI activity in human visual cortex.

Neuroimage, 19(2), 261-270.

Dilks, D. D., Julian, J. B., Paunov, A. M., & Kanwisher, N. (2013). The occipital place area is causally
and selectively involved in scene perception. *Journal of Neuroscience, 33*(4), 1331-1336.

Epstein, R. A., Higgins, J. S., Jablonksi, K, & Feiler, A. M, (2007). Visual scene processing in familiar
and unfamiliar environments. *Journal of Neurophysiology, 97,* 3670-3683.

Epstein, R., & Kanwisher, N. (1998). A cortical representation of the local visual environment. *Nature*
392, 598 –601.

Epstein, R., Parker,W. E., & Feiler, A. M. (2007). Where am I now? Distinct roles for parahippocampal
and retrosplenial cortices in place recognition. *Journal of Neuroscience, 27*, 6141-6149.

Fei-Fei, L., Iyer, A., Koch, C., & Perona, P. (2007). What do we perceive in a glance of a real-world
scene? *Journal of Vision, 7*(1), 1-29.

Fonov, V., Evans, A. C., Botteron, K., Almli, C. R.,McKinstry, R. C., & Collins, D. L. (2011). Unbiased
average age-appropriate atlases for pediatric studies. *NeuroImage, 54*(1), 313-327

Greene, M. R. (2013). Statistics of high-level scene context. *Frontiers in Perception Science, 4,* 777

Greene, M. R. & Fei-Fei, L. (2014). Visual Categorization is Automatic and Obligatory: Evidence from a
Stroop-like Paradigm. *Journal of Vision, 14*(1), 1-11.

Greene, M. R., & Oliva, A. (2009a). Recognition of natural scenes from global properties: Seeing the
forest without representing the trees. *Cognitive Psychology, 58*(2), 137-176.

Greene, M. R., & Oliva, A. (2009b). The briefest of glances: The time course of natural scene
understanding. *Psychological Science, 20*(4), 464-472.

Greene, M. R., & Oliva, A. (2010). High-level aftereffects to global scene properties. *Journal of*
Experimental Psychology: Human Perception & Performance, 36(6), 1430-1442.

Guzmá, A. (1968). Decomposition of a visual scene into three-dimensional bodies. *Proceedings of the*
Fall Joint Computer Conference, Part Im 291-304.

Haxby, J. V., Gobbini, M. I., Furey, M. L., Ishai, A., Schouten, J. L., & Pietrini, P. (2001). Distributed
and overlapping representations of faces and objects in ventral temporal cortex. *Science,*
293(5539), 2425-2430.

Harel, A., Kravitz, D. J., & Baker, C. I. (2013). Deconstructing visual scenes in cortex: gradients of object
and spatial layout information. *Cerebral Cortex, 23*(4), 947-957.

Hubel, D. H., & Wiesel, T. N. (1962). Receptive fields, binocular interaction and functional architecture

in the cat's visual cortex. *Journal of Physiology, 160,* 106–154

Kim, J. G., & Biederman, I. (2010). Where do objects become scenes? *Cerebral Cortex, 21,* 1738-1746.

Kim, J. G., & Biederman, I. (2011). The benefit of object interactions arises in the lateral occipital cortex

independent of attentional modulation from the intraparietal sulcus: A transcranial magnetic

stimulation study. *Journal of Neuroscience, 31*(22), 8320-8324.

Kravitz, D. J., Peng, C. S., & Baker, C. I. (2011). Real-world scene representations in high-level visual

cortex – it's the space more than the places. *Journal of Neuroscience, 31*(20), 7322-7333.

Kriegeskorte, N., Goebel R, Bandettini, P. (2006). Information-based functional brain mapping.

Proceedings of the National Academy of Sciences USA, 103, 3863–3868

Loschky, L. C., Hansen, B. C., Sethi, A., & Pydimarri, T. N. (2010). The role of higher order image

statistics in masking scene gist recognition. *Attention, Perception, & Psychophysics, 72*(2), 427-

444.

MacEvoy, S. P., & Epstein, R., A. (2007). Position selectivity in scene- and object-responsive

occipitotemporal regions. *Journal of Neurophysiology, 98,* 2089-2098.

MacEvoy, S. P., & Epstein, R., A. (2011). Constructing scenes from objects in human occipitotemporal

cortex. *Nature Neuroscience, 14,* 1323-1329.

Maguire, E. A., (2001). The retrosplenial contribution to human navigation: a review of lesion and

neuroimaging findings. *Scandinavian Journal of Psychology. 42,* 225–238.

Marchette, S. A., Vass, L. K., Ryan, J., & Epstein, R. A.,(2014). Anchoring the neural compass: coding of

local spatial reference frames in human medial parietal lobe. *Nature Neuroscience, 17,* 1598–

1606.

Marr, D. (1982). *Vision: A Computational Approach.* San Francisco, CA: Freeman & Company.

Nasr, S., Echavarria, C. E., Tootell, R. (2014). Thinking outside the box: rectilinear shapes selectively

activate scene-selective cortex. *Journal of Neuroscience, 34*(20), 6121-6735.

Oliva, A., & Torralba, A. (2001). Modeling the shape of the scene: a holistic representation of the spatial

envelope. *International Journal of Computer Vision, 42*(3), 145-175.

Park, S., Brady, T. F., Greene, M. R. & Oliva, A. (2011). Disentangling scene content from spatial

boundary: Complementary roles for the PPA and LOC in representing real-world scenes.

Journal of Neuroscience. 31(4), 1333-1340.

Park, S., & Chun, M. M. (2009). Different roles of the parahippocampal place area (PPA) and

retrosplenial cortex (RSC) in panoramic scene perception. *Neuroimage, 47*(4), 1747-1756.

Park, S., Konkel, T., & Oliva, A. (2015). Parametric coding of scene size and clutter independent of

semantic category. *Cerebral Cortex*, 25(7), 1792-1805.Pasupathy, A., & Connor, C. E. (2002).

Population coding of shape in area V4. *Nature Neuroscience, 5*(12), 1332-1338.

Pereira, F. & Botvinick, M. (2011). Information mapping with pattern classifiers: a comparative study.

Neuroimage, 56, 476-496.

Peterhans, E., & von der Heydt, R. (1989). Mechanisms of contour perception in monkey visual cortex. II.

Contours bridging gaps. *Journal of Neuroscience, 9,* 1749–1763.

Portilla, J., & Simoncelli, E. P. (2000). A parametric texture model based on joint statistics of complex

wavelet coefficients. *International Journal of Computer Vision, 40,* 49–71.

Potter, M. C., & Levy, E. I. (1969). Recognition memory for a rapid sequence of pictures. *Journal of

Experimental Psychology, 81*, 10–15.

Thorpe, S., Fize, D., & Marlot, C. (1996). Speed of processing in the human visual system. *Nature, 381,*

520–522.

Torralba, A., & Oliva, A. (2003). Statistics of natural image categories. *Network: Computation in Neural

Systems, 14,* 391-412

Tversky, B., & Hemenway, K. (1983). Categories of environmental scenes. *Cognitive Psychology, 15*,

121–149.

Walther, D. B., Beck, D. M., & Fei-Fei, L. (2012). To err is human: correlating fMRI decoding and

behavioral errors to probe the neural representation of natural scene categories. In: Nikolaus

Kriegeskorte and Gabriel Kreiman (Eds.), *Visual Population Codes – Towards a Common

Multivariate Framework for Cell recording and Functional Imaging.* MIT Press: Cambridge,

Massachusetts, pp. 391-415.

Walther, D. B., Caddigan, E., Fei-Fei, L., & Beck, D. M. (2009). Natural scene categories revealed in

distributed patterns of activity in the human brain. *Journal of Neuroscience, 29*, 10573–10581.

Walther, D. B., Chai, B., Caddigan, E., Beck, D. M., & Fei-Fei, L. (2011). Simple line drawings suffice

for functional MRI decoding of natural scene categories. *Proceedings of the National Academy of*

Sciences USA, 108, 9661–9666.

Walther, D. B., & Shen, D. (2014). Nonaccidental properties underlie human categorization of complex

natural scenes. *Psychological Science, 25*(4). 851-860.

Watson, A. B., & Pelli, D. G. (1983). QUEST: a Bayesian adaptive psychometric method. *Perception &*

Psychophysics, 33 (2), 113-120.

Zeiler, M. D., & Fergus, R. (2014). Visualizing and understanding convolutional networks. In: D. Fleet

et al. (Eds.), *ECCV 2014*, Part I, LNCS 8689, Springer International Publishing: Switzerland, pp.

818–833.

Supplementary Materials

Localizing regions of interest

Following the main experiment scans, participants viewed blocks of color photographs of faces, scenes, objects, and grid-scrambled objects as part of a standard face-place-object localizer scan (Epstein & Kanwisher, 1998). Participants were asked to indicate immediate repetitions of images to maintain their attention to images. Images subtended 640 x 640 pixels (approximately 11 ° of visual angle) and were presented for 500 ms, followed by a blank screen for 500 ms. Participants saw five blocks of 72 images, sub-divided into four mini-blocks of 18 randomly drawn images for each of the four categories. Including 12 second fixation periods before, between, and after the blocks, the entire scan lasted for 7 minutes and 12 seconds. Scanning parameters for the face-place-object localizer differed from those of the main experiment: TR = 3000 ms, TE = 28ms, flip angle = 80°, voxel size = 2.5 x.2.5 x 2.5 mm, matrix size = 90 x 100 x 40 voxels, 40 coronal slices.

The fMRI data were motion corrected, registered to the anatomical scans that had been aligned to the functional volumes of the main experiment, spatially smoothed using a 4 mm FWHM Gaussian filter and converted to percent signal change with respect to the mean of each run. The pre-processed data entered a GLM analysis with regressors for all four image types. ROIs were defined as contiguous clusters of voxels with significant contrasts ($q < 0.05$; corrected using false discovery rate) of scenes > (faces and objects) for PPA, RSC (Epstein & Kanwisher, 1998) and OPA (Dilks et al., 2013); faces > (scenes and objects) for FFA (Kanwisher et al. 1997); and objects > (scrambled objects) for LOC (Grill-Spector, Knouf, & Kanwisher, 2004; Grill-Spector, Kourtzi, & Kanwisher 2001). To obtain robust clusters for the RSC, the threshold had to be relaxed to $p < 0.01$ (uncorrected). We could not find significant clusters corresponding to the OPA in three participants and used data of the remaining twelve participants to perform decoding from the OPA.

Boundaries of early visual areas were established by stimulating the horizontal and vertical meridians of the visual field (HV) in alternation (Kastner, Weerd, Desimone, & Ungerleider, 1998). During two HV scans (only one HV scan for four participants, because we ran out of time), participants viewed flickering checkerboard patterns (2 Hz, a mix of white, red, green, blue, and yellow checkerboards), filling pairs of wedges (width: 10°) aligned with the horizontal or vertical meridians, respectively. Fixation periods of 20 seconds were included between each alternation

as well as at the beginning and the end of the scan (total scan duration: 3 min 20 sec). In order to establish the

anterior boundary of V4, a scan with alternating stimulation of the upper and lower visual field (UL) with similar

flickering checkerboard patterns along the diagonals was included as well, which lasted approximately 3 min. Scan

parameters for the HV and UL scans were as follows; TR = 2000 ms, TE = 28 ms, flip angle = 72°, voxel size =

1.953 x 1.953 x 2 mm, matrix size = 114 x 128 x 30 voxels, 30 coronal slices.

Data from the HV and UL scans were motion-corrected, registered to the anatomical scan that had been

aligned to the functional volume of the main experiment, spatially smoothed (4 mm FWHM) and converted to

percent signal change. In separate GLM analyses, data from the HV scans were analyzed for a horizontal-versus-

vertical meridian contrast and data from the UL scans for an upper-versus-lower visual field contrast.

Cortical surfaces for each participant's brain were reconstructed from their anatomical scans (MPRAGE)

using Freesurfer. To flatten the cortical surface, each hemisphere was virtually cut along the calcarine fissure and

four additional relaxation cuts. The corpus callosum and mid-brain structures on the medial surface were removed.

Boundaries between early visual areas were identified by projecting the beta-weight maps of the HV and UL

contrasts onto the flattened cortical surfaces using AFNI and SUMA. Following Hansen, Kay, and Gallant (2007)

we identified the V1/V2 border as the first vertical meridian, the V2/V3 border as the second horizontal meridian,

and V3/V4 border as the second vertical meridian. Since V4 represents the entire contralateral hemifield on the

lower bank of the calcarine fissure, we identified the anterior border of V4 as the closest boundary that encompassed

both upper and lower visual field. For two participants, the anterior V4 border could not be clearly delineated. Thus,

we only used data from the remaining thirteen participants to perform decoding from V4. ROIs were drawn

conservatively to minimize the amount of overlap between neighboring areas. Following projection of surface-based

ROIs back into the brain volume of each participant, we excluded voxels that were assigned to more than one ROI.

Univariate analysis

To explore the effect of the disruption of contour properties on the magnitude of the average neural activity

we conducted a standard general linear model (GLM) analysis using the AFNI software package, and deconvolved

block responses to the three image conditions for each voxel within the ROIs. Nuisance variables were included to

capture variance due to head motion (six affine transform parameters) and scanner drift (4th-degree polynomial).

Beta parameters were extracted for the three contrasts: Intact > Fixation, Rotated > Fixation, and Contour-shifted >

Fixation. The beta parameters were averaged over voxels within each ROI. The GLM analysis showed that the line

drawing images significantly activated all of the ROIs except for the RSC (Table S1). A one-way ANOVA showed

no significant difference in neural activity between intact, rotated, and contour-shifted line drawings in any of the

ROIs; $Fs < 1$ in V1, V2, PPA, RSC, and OPA; $F(2, 28) = 1.327$, $p = .281$, $\eta^2 = .087$ in the V3; $F(2, 24) = 1.785$, p

$= .189$, $\eta^2 = .110$ in V4; $F(2, 28) = 1.923$, $p = .165$, $\eta^2 = .121$ in the LOC; and $F(2, 28) = 1.727$, $p = .196$, $\eta^2 = .110$ in

the FFA. The mean activity might not be sensitive enough to differentiate between the three types of line drawings

despite some variety in neural tuning properties in the visual cortex. The line drawing scenes had naturalistic visual

statistics that often contain various visual features and objects, thus equating the mean activity to an image.

Moreover, the overall neural activity for any specific line drawings were likely to be smoothed out over the course

of a block. These findings are consistent to the previous report that the multivariate approach can often recover the

visual content despite the equivalent univariate results (e.g., Kamitami & Tong, 2005).

Table S1. Results of univariate analysis. One-sample t-tests were conducted to compare average neural activity during presentation of the intact, rotated, and contour-shifted line drawings to average neural activity during fixation presentation. The mean (*M*) and standard errors of means (*SEM*), t-statistics, and the adjusted significance q are shown separately for each of the three contrasts: Intact > Fixation, Rotated > Fixation, and Contour-Shifted > Fixation.

ROI	df	Intact > Fixation				Rotated > Fixation				Contour-Shifted > Fixation			
		M	*SEM*	*t*	*q*	*M*	*SEM*	*t*	*q*	*M*	*SEM*	*t*	*q*
V1	14	.901	.152	5.923	$5.51 \cdot 10^{-5}$	.872	.146	5.972	$5.51 \cdot 10^{-5}$	.858	.158	5.442	$8.67 \cdot 10^{-5}$
V2	14	.855	.140	6.108	$5.66 \cdot 10^{-5}$	.828	.146	5.683	$5.66 \cdot 10^{-5}$	.847	.148	5.725	$5.66 \cdot 10^{-5}$
V3	14	.823	.104	7.918	$1.85 \cdot 10^{-6}$	.782	.100	7.793	$1.85 \cdot 10^{-6}$	.814	.102	8.019	$1.85 \cdot 10^{-6}$
V4	12	1.15	.127	8.391	$6.90 \cdot 10^{-6}$	1.07	.136	7.329	$9.11 \cdot 10^{-6}$	1.11	.133	7.770	$7.59 \cdot 10^{-6}$
PPA	14	.234	.0629	3.723	$5.18 \cdot 10^{-3}$	.213	.0645	3.308	$5.18 \cdot 10^{-3}$	.228	.0654	3.486	$5.18 \cdot 10^{-3}$
OPA	11	.577	.126	4.105	$1.75 \cdot 10^{-3}$	.554	.116	4.282	$1.75 \cdot 10^{-3}$	.572	.121	4.247	$1.75 \cdot 10^{-3}$
RSC	14	.0225	.134	.427	.938	.0107	.135	.242	.938	.0718	.0966	.762	.938
LOC	14	.572	.113	5.082	$3.86 \cdot 10^{-4}$	.496	.107	4.634	$3.86 \cdot 10^{-4}$	.543	.117	4.640	$3.86 \cdot 10^{-4}$
FFA	14	.371	.0907	4.088	$1.66 \cdot 10^{-3}$	.308	.0747	4.127	$1.66 \cdot 10^{-3}$	.371	.0998	3.716	$2.30 \cdot 10^{-3}$

Confusion Matrices: Behavior

Figure S1. Group average confusion matrices of intact, rotated and contour-shifted line drawings obtained from a separate behavioral scene categorization experiment. The rows indicate true category labels presented to the participants, and columns indicate perceived category labels. In each entry, the probability of a perceived category given a presented category. The entries are also shaded according to the conditional probability: 0 as white, and 0.25 and higher as black.

Confusion Matrices: Early Visual Areas

Figure S2. Group average confusion matrices of neural decoding from V1-4.

Confusion Matrices: Domain-specific Areas

Figure S3. Group average confusion matrices of neural decoding from the PPA, OPA, RSC, and LOC.

Intact

Figure S4. Un-thresholded error correlation maps between searchlight analysis of intact line drawings and computational scene categorization of the same intact line drawings. All searchlight locations were included regardless of their decoding accuracy. A-E) Searchlight locations are colored according to the strength of correlation between their neural decoding error patterns and computational error patterns (warm colors for positive and cold colors for negative correlation). F) Each searchlight location is colored according to the type of contour properties showing the maximum error correlation: orientation in dark blue, length in sky blue, curvature in green, junction types in red, and junction angles in orange.

Rotated

Figure S5. Un-thresholded error correlation and max property maps for rotated line drawings. Coloring follows the same conventions as Figure S4.

Contour-Shifted

Figure S6. Un-thresholded error correlation and max property maps for contour-shifted line drawings. Coloring follows the same conventions as Figure S4.

Error pattern correlation between brain and behavior: Searchlight analysis

We explored how disruption in contour orientation or junction properties affected the strength of error pattern correlation between neural decoding and behavior in a voxel-wise manner, using the same linear regression analysis as used for ROI-based analysis (see Methods in the main text). The linear mixed-effects modeling was performed with the fitlme function in MATLAB R2014b for faster computation speed compared to R. For each participant, the pattern of errors from the neural decoding analysis, i.e., the off-diagonal elements of the confusion matrix, was stored at each voxel location and registered to MNI space. Separately for each of the three line drawing types, neural decoding error patterns were Pearson-correlated to the group-averaged error patterns obtained from the separate behavioral experiment, resulting in 3-by-3 error correlation values for each voxel. Error correlations were transformed using Fisher's z-transform. Using the same linear mixed-effects modeling shown in Figure 4C, we tested the extent to which the three idealized models can predict the three-by-three error correlation patterns between neural decoding and behavior. The coefficients were thresholded at $p < .01$ (two-tailed) with cluster correction of a minimum cluster size of 12 voxels. The three coefficient maps and their overlap are shown in Figure S7. Significant contributions from all three models (positive from same-type and intact-rotated, negative from intact-contour-shifted) are clearly discernible in both PPAs and the right RSC (red in Figure S7B). The overlap between the same-type and intact-rotated models is wide-spread throughout visual cortex (orange in Figure S7B). Significant contributions from all three models (positive from same-type and intact-rotated, negative from intact-contour-shifted) are clearly discernible in both PPAs and the right RSC (red in Figure S7B).

Figure S7. Searchlight analysis of patterns of error correlation between brain and behavior. At each searchlight locations the error correlation analysis were performed using the same three models used in the ROI analysis. A) The coefficient maps of the same type, intact–rotated, and intact–contour-shifted model. Each searchlight location is colored according to the coefficients, warm colors for positive and cold colors for negative. B) Each searchlight location is colored according to the set of models explaining patterns of error correlations at that location: only one model (yellow, green and blue), two of the models (orange, violet, and pink), or all three models (red). Consistent to the ROI results, the three idealized models significantly predicted

A) Within-Type Decoding (N =11)

B) Cross-Type Decoding (N =11)

Figure S8. Neural decoding results from 11 participants in which we can delineate all nine ROIs (V1-4, PPA, OPA, RSC, LOC, and FFA). The patterns of results were identical to those from all 15 participants. A) Average accuracy rates of within-type category decoding from ROIs. C) Average accuracy rates of cross-type category decoding from the ROIs. The only significant difference in cross-type decoding accuracy between Intact-to-Rotated/Rotated-to-Intact and Intact-to-Contour-Shifted/Contour-Shifted-to-Intact was found in the PPA, $F(1,10) = 12.154$, $p = .006$, η^2 = .549 as indicated above the bracket bridging the two bars. Error bars are standard errors of means. Dashed lines indicate chance performance (1/6). The significance of the one-sample t-test (one-tailed) was adjusted for multiple comparisons (FDR) and marked above each bar, $*q < .05$, $**q < .01$, $***q < .001$.

797 **Cross-type decoding between rotated and contour-shifted line drawings**

Figure S9. Average accuracy rates of cross-type category decoding between rotated and contour-shifted line drawings from the ROIs. Across the two types of line drawings, statistics of contour length and curvature are preserved, which is likely to underlie the robust cross-decoding accuracy in the early visual areas as well as in the OPA. By comparison, cross-decoding in the PPA is relatively weak. Error bars are standard errors of means. Dashed lines indicate chance performance (1/6). False discovery rate correction was employed to adjust significance for multiple comparisons. The significance of the one-sample t-test (one-tailed) is marked above each bar, $*q < .05$, $**q < .01$, $***q < .001$.

Supplementary References

Epstein, R., & Kanwisher, N. (1998). A cortical representation of the local visual environment. *Nature 392*, 598 –

601.

Grill-Spector, K., Knouf, N., & Kanwisher, N. (2004). The fusiform face area subserves face perception, not

generic within-category identification. *Nature Neuroscience, 7*(5) 555-562.

Grill-Spector, K., Kourtzi, Z., & Kanwisher, N. (2001). The Lateral Occipital Complex and its Role in Object

Recognition. *Vision Research. 41,* 1409-1422.

Hansen, K. A., Kay, K. N., & Gallant, J. L. (2007). Topographic organization in and near human visual area V4.

Journal of Neuroscience, 27, 11896–11911.

Kastner, S., De Weerd, P., Desimone, R., & Ungerleider, (1998). Mechanisms of directed attention in the human

extrastriate cortex as revealed by functional MRI. *Science*, 282, 108–111.

Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human brain. *Nature*

Neuroscience, 8, 679-585.