FastGT: an alignment-free method for calling common SNVs directly from raw sequencing reads

Fanny-Dhelia Pajuste[1*], Lauris Kaplinski[1*], Märt Möls[1,2], Tarmo Puurand[1], Maarja Lepamets[1] & Maido Remm[1,3]

*These authors contributed equally to this work.

[1]Institute of Molecular and Cell Biology, University of Tartu, Tartu, Estonia

[2]Institute of Mathematics and Statistics, University of Tartu, Tartu, Estonia

[3]Correspondence to maido.remm@ut.ee

We have developed a computational method that counts the frequencies of unique *k*-mers in FASTQ-formatted genome data and uses this information to infer the genotypes of known variants. FastGT can detect the variants in a 30x genome in less than 1 hour using ordinary low-cost server hardware. The overall concordance with the genotypes of two Illumina "Platinum" genomes[1] is 99.96%, and the concordance with the genotypes of the Illumina HumanOmniExpress is 99.82%. Our method provides *k*-mer database that can be used for the simultaneous genotyping of approximately 30 million single nucleotide variants (SNVs), including >23,000 SNVs from Y chromosome. The source code of FastGT software is available at GitHub (https://github.com/bioinfo-ut/GenomeTester4/).

Next-generation sequencing (NGS) technologies are widely used for studying genome variation. Variants in the human genome are typically detected by mapping sequenced reads and then performing genotype calling[2–5]. A standard pipeline requires 40-50 h to process a human genome with 30x coverage from raw sequence data to variant calls on a multi-thread server. Mapping and calling are state-of-the-art processes that require expert users familiar with numerous available software options. It is not surprising that different pipelines generate slightly different genotype calls[6–10]. Fortunately, inconsistent genotype calls are associated with certain genomic regions only[11–13], whereas genotyping in the remaining 80-90% of the genome is robust and reliable.

The use of *k*-mers (substrings of length *k*) in genome analyses has increased because computers can handle large volumes of sequencing data more efficiently. For example, phylogenetic trees of all known bacteria can be easily built using *k*-mers from their genomic DNA[14–16]. Bacterial strains can be quickly identified from metagenomic data by searching for strain-specific *k*-mers[17–19]. *K*-mers have also been used to correct sequencing errors in raw reads[20–23]. One recent publication has described an alignment-free SNV calling method that is based on counting the frequency of k-mers[24]. This method converts sequences from raw reads into Burrows-Wheeler transform and then calls genotypes by counting using a variable-length unique substring surrounding the variant.

We developed a new method that offers the possibility of directly genotyping known variants from

NGS data by counting unique k-mers. The method only uses reliable regions of the genome and is

approximately 1-2 orders of magnitude faster than traditional mapping-based genotype detection. Thus,

it is ideally suited for a fast, preliminary analysis of a subset of markers before the full-scale analysis is

finished.

The method is implemented in the C programming language and is available as the FastGT software

package. FastGT is currently limited to the calling of previously known genomic variants because

specific k-mers must be pre-selected for all known alleles. Therefore, it is not a substitute for traditional

mapping and variant calling but a complementary method that facilitates certain aspects of NGS-based

genome analyses. In fact, FastGT is comparable to a large digital microarray that uses NGS data as an

input. Our method is based on three original components: 1) the procedure for the selection of unique

k-mers, 2) the customized data structure for storing and counting k-mers directly from a FASTQ file,

and 3) a maximum likelihood method designed specifically for estimating genotypes from k-mer

counts.

RESULTS

Compilation of the database of unique k-mer pairs

The crucial component of FastGT is a pre-compiled flat-file database of genomic variants and

corresponding k-mer pairs that overlap with each variant. Every bi-allelic single nucleotide variant

(SNV) position in the genome is covered by k k-mer pairs, where pair is formed by k-mers

corresponding to two alternative alleles (Figure S4). FastGT relies on the assumption that at least a

number of these k-mer pairs are unique and appear exclusively in this location of the genome;

therefore, the occurrence counts of these unique k-mer pairs in sequencing data can be used to identify

the genotype of this variant in a specific individual.

The database of variants and unique k-mers is assembled by identifying all possible k-mer pairs for

each genomic variant and subjecting them to several steps of filtering. The filtering steps remove

variants for which unique k-mers are not observed and variants that produce non-canonical genotypes

(non-diploid in autosomes and non-haploid in male X and Y chromosomes) in a sequenced test-set of

individuals. Filtering of k-mers was performed using high coverage NGS data of 50 individuals from

Estonian Genome Project (published elsewhere). The filtering steps are described in Methods section

and in Supplementary File (Figure S5).

Although one k-mer pair is theoretically sufficient for genotyping, mutations occasionally change the

genome sequence in the neighborhood of an SNV, effectively preventing the detection of the SNV by a

chosen *k*-mer. If the mutation is allele-specific, then the wrong genotype could be easily inferred.

Therefore, we use up to three *k*-mer pairs per variant to prevent erroneous calls caused by the

occasional loss of *k*-mers because of rare mutations.

In the current study, we compiled a database of all bi-allelic SNVs from dbSNP and tested the ability of

FastGT to detect these SNVs with 25-mers. After the filtering steps, 30,238,283 (64%) validated and

bi-allelic SNVs remained usable by FastGT. We also used a subset of autosomal SNV markers present

on the Illumina HumanOmniExpress microarray for a concordance analysis. In this set, 78% of the

autosomal markers from this microarray were usable by FastGT. The number of SNV markers that

passed each filtering step is shown in Table S1.

Algorithm and software for *k*-mer-based genotyping

The genotyping of individuals is executed by reading the raw sequencing reads and counting the

frequencies of *k*-mer pairs described in the pre-compiled database of variants using the custom-made

software `gmer_counter` and `gmer_caller` (Figure 1).

The database of genomic variants and corresponding *k*-mers is stored as a text file. The frequencies of

k-mers listed in the database are counted by `gmer_counter`. It uses a binary data structure, which

stores both *k*-mer sequences and their frequencies in computer memory during the counting process. A

good compromise between memory consumption and lookup speed is achieved by using adaptive radix

tree (see Supplementary File for detailed description of the data structure). The first 14 nucleotides of a

k-mer form an index into a table of sparse bitwise radix trees that are used for storing the remaining

sequence of the *k*-mers. Two bytes per *k*-mer are allocated for storing frequencies. The current

implementation of `gmer_counter` accepts *k*-mers with lengths between 14 and 32 letters. The

frequencies of up to three *k*-mer pairs from `gmer_counter` are saved in a text file that is passed to

`gmer_caller`, which infers the genotypes based on *k*-mer frequencies and prints the results to a text

file.

Empirical Bayes' method for inferring genotypes from *k*-mer counts

`Gmer_caller` uses the Empirical Bayes classifier for calling genotypes from *k*-mer frequency data,

which assigns the most likely genotype to each variant. Allele frequency distributions are modeled by

negative binomial distribution, described by eight parameters (see description in the Supplementary

File). The model parameters are estimated separately for each analyzed individual using *k*-mer counts

of 100,000 autosomal markers. The model allows us to estimate the most likely copy number for both

alleles. Given the observed allele counts, `gmer_caller` calculates the probability of genotypes by

applying the Bayes rule. As we do not require allele copy numbers to sum to 2 we can also call mono-,

tri-, or tetra-allelic genotypes (which might correspond to deletions and duplications) in addition to

traditional bi-allelic (diploid) genotypes (Figure 2). The model parameters can be saved and re-used in

subsequent analyses of the same dataset.

The gender of the individual is determined automatically from the sequencing data using the median

frequency of markers from the X chromosome (chrX). If the individual is female, only the autosomal

model is used in the calling process and Y chromosome (chrY) markers are not called. For men, an

additional haploid model of Bayes' classifier is trained for calling genotypes from sex chromosomes.

Parameters for the haploid model are estimated using 100,000 markers from chrX.

Assessment of genotype calling accuracy through simulations

In order to test the performance of FastGT, we generated simulated raw sequencing reads from the

reference genome and analyzed the ability of the Bayesian classifier of FastGT to reproduce genotypes

of the reference genome (see Methods for detailed description of data simulation methods). Throughout

this paper we denote A as reference allele and B as alternative allele. In this simulation, the reference

genome was assumed to be homozygous in all positions. Thus, the correct genotype for all 30,238,283

tested markers would be AA genotype. The fraction of AA genotypes recovered from simulated reads

varied between 98.94% (at 5x coverage) and 99.95% (at 20x coverage). The fraction of uncalled

markers was between 0.001% (at 20x coverage) and 1.036% (at 5x coverage). The fraction of AB calls

was in range of 0.02% to 0.05% at all coverages. The results are shown in Table 1.

The performance of calling AB and BB genotypes cannot be estimated from the reference genome. We

created simulated genomes using genotypes from 5 sequenced individuals, each from different

population (Yoruban, Chinese Han, CEPH, Puerto Rican and Estonian). This analysis helped to test the

performance of Bayesian classifier (`gmer_caller`) on calling the AB and BB variants from real-life

data. Secondly, this analysis indicates whether the selection of markers that was done using Estonian

individuals introduces any population-specific bias in genotype calling. The sensitivity (fraction of

correctly called AB and BB variants) was strongly affected by coverage (61% at 5x coverage, 99.8% at

20x coverage), but remained almost identical for individuals from different populations: 99.7 – 99.8%

at 30x coverage (Figure 3). The specificity (fraction of correctly called AA calls) was more uniform

over different coverage levels and remained between 99.60% to 99.95%. These results show that our

set of 30 million markers is usable for studying different populations without strong bias in sensitivity

or specificity.

Assessment of genotype calling accuracy through concordance analysis

The accuracy of FastGT genotype calls was analyzed by comparing the results to genotypes reported in

two Illumina Platinum individuals, NA12877 and NA12878, which were sequenced to 50x coverage.

These are high-confidence variant calls derived by considering the inheritance constraints in the
pedigree and the concordance of variant calls across different methods[1]. We determined genotypes for
30,238,283 millions of markers from the FastGT database using raw sequencing data from the same
individuals and compared them to genotypes shown in the Platinum dataset.
163
The overall concordance of bi-allelic FastGT genotypes with genotypes from two Platinum genomes is
99.96%. The concordance of the non-reference (AB or BB) calls was 99.93%. The distribution of
differences between the two sets for different genotypes is shown in Table 2. All of the genotypes
reported in the Platinum datasets were bi-allelic; thus, we included only bi-allelic FastGT genotypes in
this comparison. The fraction of uncertain (no-call) genotypes in the FastGT output was 0.24%. The
uncertain genotypes are primarily mono-allelic (A) and tri-allelic (AAA) genotypes that might
correspond to deletions or insertions in a given region. However, non-canonical genotypes in the
default output are not reported, and they are replaced by NC ("no call"). All of the genotypes and/or
their likelihoods can be shown in `gmer_caller` optional output.
173
We also compared the genotypes obtained by the FastGT method with the data from the Illumina
HumanOmniExpress microarray. We used 504,173 autosomal markers that overlap our whole-genome
dataset (Table S2), and the comparison included ten individuals from the Estonian Genome Center for
whom both microarray data and Illumina NGS data were available. In these 10 individuals, the
concordance between the genotypes from the FastGT method and microarray genotypes was 99.82%
(Table 2), and the concordance of non-reference alleles was 99.69%. The fraction of mono-allelic and
tri-allelic genotypes (no-call genotypes) in 10 test individuals is rather low (<0.01% of all markers),
indicating that our conservative filtering procedure is able to remove most of the error-prone SNVs.
182
183
184 **Markers from Y chromosome**
185
FastGT is able to call genotypes from the Y chromosome (chrY) for 23,832 markers that remain in the
whole-genome dataset after all filtering steps. The genotypes on chrY cannot be directly compared with
the Platinum genotypes because chrY calls were not provided in the VCF file of the Platinum
individuals. To assess the performance of chrY genotyping, we compared our results to the genotypes
of 11 men from the HGDP panel[25] (http://cdna.eva.mpg.de/denisova/). The overall concordance of the
haploid genotype calls of FastGT and the genotype calls in these VCF files was 99.97%. The fraction
of non-canonical genotypes (no-calls) in the FastGT output was 1.27% (Table S3).
193
We also tested the concordance of chrY genotypes in seven father-son pairs in CEPH pedigree 1463
(http://www.ebi.ac.uk/ena/data/view/ERP001960). We assume that changes in chrY genotypes should
not occur within one generation. Only one marker (rs199503278) showed conflicting genotypes in any
of these father-son pairs. A visual inspection revealed problems with the reference genome assembly in
this region, which resulted in conflicting k-mer counts and conflicting genotypes from different k-mer

pairs of the same SNV. This marker was removed from the dataset because it had a high likelihood of
causing similar problems in other individuals.
201
202

203 **Effect of genome coverage on FastGT performance**
204

We also studied how the genome sequencing depth affects the performance of FastGT. The Platinum
genomes have a coverage depth of approximately 50x, but in most study scenarios, sequencing to a
lower coverage is preferred because it optimizes costs. For this analysis, we compiled different-sized
subsets of FASTQ sequences from the Platinum individual NA12878 and measured the concordance
between called genotypes and genotypes from the Platinum dataset. We observed that the concordance
rate of non-reference genotypes (AB and BB) declines significantly as the coverage drops below 20x
(Figure 4).
212
213

214 **Relationship between k-mer length and number of usable variants**
215

An obvious question is how the k-mer length affects the performance of FastGT. We used 25
nucleotides long k-mers throughout this article, but FastGT is able to use other k-mer lengths between
16 and 32 as well. We tested how many markers from dbSNP would remain usable for FastGT at
different values of k. From 47 millions validated markers 7-17% markers are removed in filtering step
1 due to closely located SNVs (Figure 5). In filtering step 2 markers are removed if they have no
unique k-mer pairs in the expanded reference genome. As expected, a rather large number of markers
are eliminated from the dataset if k-mers shorter than 20 nucleotides are used. However, the number of
usable markers does not increase significantly for k larger than 24. Thus, k values between 24 and 32
should be equally suitable for analyzing the human genome with FastGT. We have not compared the
accuracy of genotype calls of different k-mer lengths. However, we expect it to be relatively
independent of k-mer length. Two main factors that might influence the accuracy (concordance) of
genotypes are non-specific counts from shorter k-mers and drop of effective coverage of k-mers. The
effective coverage is negatively correlated with k-mer length. This negative correlation is caused by the
higher chance of accumulating sequencing errors within longer k-mers and by the end effects of the
reads (lower number of long k-mers per sequencing read). On the other hand, shorter k-mers are more
likely to pick up non-specific sequences due to sequencing errors and unknown variations in human
genomes. Overall, these effects influence the effective coverage of k-mers and are only critical if
genome coverage is low or if k-mer is shorter than 20 nucleotides. At high coverage (>20x) conditions
the k-mer length should not have significant influence to genotype accuracy.
235
236

237 **Time and memory usage**
238

The entire process of detecting 30 million SNV genotypes from the sequencing data of a single

individual (30x coverage, 2 FASTQ files, 115GB each) takes approximately 40 minutes on a server

with 32 CPU cores. Most of this time is allocated to counting k-mer frequencies by `gmer_counter`.

The running time of `gmer_counter` is proportional to the size of the FASTQ files because the

speed-limiting step of `gmer_counter` is reading the sequence data from a FASTQ file. However, the

running time is also dependent on the number of FASTQ files (Figure 6) because simultaneously

reading from multiple files is faster than processing a single file. Genotype calling with

`gmer_caller` takes approximately 2-3minutes with 16 CPU cores.

The minimum amount of required RAM is determined by the size of the data structure stored in

memory by `gmer_counter`. We have tested `gmer_counter` on Linux computer with 8 GB of

RAM. However, server-grade hardware (multiple CPU cores and multiple fast hard drives in RAID) is

required to achieve the full speed of `gmer_counter` and `gmer_caller`.

METHODS

Compilation of database of unique *k*-mers

A k-mer length of 25 was used throughout this study, and the k-mers for genotyping were selected by

the following filtering process (see also Figure S4). First, the validated single nucleotide variants

(SNVs), as well as the validated and common indels, were extracted from the dbSNP database build

146[26,27]. Indels were used for testing the uniqueness of k-mers only; they are not included in the

database of variants. For every bi-allelic SNV from this set, two sequences surrounding this SNV

location were created: the sequence of the human reference genome (GRCh37) and the sequence

variant corresponding to the alternative allele. The sequences were shortened to eliminate any possible

overlap with neighboring SNVs or common indels. Essentially, this filtering step removed all of the

SNVs that were located between two other SNVs (or indels) with less than 25bp between them. This

step was chosen to avoid the additional complexity of counting and calling algorithms because of the

multiple combinations of neighboring SNV alleles. For all these SNVs that had variant-free sequences

of at least 25bp, the sequences were divided into 25-mer pairs.

In the second filtering step, we tested the uniqueness of the 25-mers compiled in the previous step. The

uniqueness parameter was tested against the "expanded reference genome," which is a set of 25-mers

from the reference genome plus all possible alternative 25-mers containing the non-reference alleles of

the SNVs and indels. A k-mer pair is considered unique if both k-mers occur no more than once in the

"expanded reference genome". All non-unique k-mer pairs were removed from the list. The

`Glistcompare` tool[28], which performs set operations with sorted k-mer lists, was used in this step.

The k-mer pairs demonstrating uniqueness even with one mismatch were preferred. This constraint was

added to reduce the risk of forming an identical k-mer by a rare point mutation or a sequencing error.

In the third step, the *k*-mers were further refined using the *k*-mer frequencies and genotypes in a set of

sequenced individual genomes. For this purpose, the *k*-mer counts and genotypes were calculated for

all SNVs of 50 random individuals whose DNA was collected and sequenced during the Center of

Translational Genomics project at the University of Tartu. Twenty-five men and 25 women were used

for filtering the autosomal SNVs; for chrX and chrY, 50 men were used. The sequencing depth in these

individuals varied between 21 and 45. Three different criteria were used for removing k-mer pairs and

SNVs in this step. First, we excluded all chrY markers that had *k*-mer frequency higher than 3 in more

than one woman. Second, autosomal *k*-mers showing abnormally high frequencies (greater than 3 times

the median count) in more than one individual were removed. Third criterion was based on unexpected

genotypes: the SNVs that produced a non-canonical allele count in more than one individual out of 50

were removed from the dataset. The non-canonical allele count is any value other than two alleles in

autosomes or a single allele in male chrX and chrY. The criteria used in filtering step 3 should remove

SNVs located in the regions that are unique in the reference genome, but frequently duplicated or

deleted in real individuals.

The final set contained 30,238,283 SNVs usable by FastGT, with 6.8% (2,063,839) located in protein-

coding regions. A detailed description of the filtering steps used in this article is shown in in Figure S5.

The number of markers removed in each step is shown in Table S1.

Statistical framework

The statistical framework for Empirical Bayes Classifier implemented in `gmer_caller` is described

in Supplementary File.

Generating and analyzing simulated data

FastGT was tested on simulated reads. Simulated sequencing reads were generated using WgSim

(version 0.3.1-r13) software from samtools package[3]. The following parameters were used:

base_error_rate=0.005, outer_distance_between_the_two_ends=500, standard_deviation=50,

length_of_the_first_read=100, length_of_the_second_read=100. We used the base error rate 0.005

(0.5%) because this is similar to error rate typically observed in Illumina HiSeq sequencing data. We

estimated average error rate in the raw reads of high-coverage genomes from Estonian Genome Center

by counting the fraction of erroneous *k*-mers. The error rates in 100 individuals varied between 0.0030

and 0.0082, with average 0.0048 (CI95%=0.0002). Previous studies have reported similar overall error

rate in raw reads generated by Illumina HiSeq, varying between 0.002 and 0.004[29,30]. The sequencing

reads were simulated with different coverages: about 5, 10, 20, 30 and 40. The number of read pairs

generated were 80 million, 160 million, 320 million, 480 million and 640 million respectively.

Reads were generated from standard reference genome, version GRCh37. For Figure 3 the reads were

also simulated using real SNV information for 5 individuals from 5 different populations (CEU, CHS,

YRI, PUR and EST). The following individuals were used in simulations: HG00512 (CHS), NA19238

(YRI), HG00731 (PUR), NA12877 (CEU) and V00055 (EST). Their sequencing data was retrieved

from 1000G project repository at

ftp://ftp.1000genomes.ebi.ac.uk/vol1/ftp/data_collections/hgsv_sv_discovery/data/ (CHS, YRI and

PUR), from the ftp://ftp.sra.ebi.ac.uk/vol1/ERA172/ERA172924/bam/ (CEU) or from the Estonian

Genome Center. For each of these individuals, the standard reference genome was used as base and the

corresponding SNV genotypes from their VCF files were added to generate the reads with realistic

variants. The SNV genotypes were calculated from BAM or CRAM files using Genome Analysis

Toolkit version 3.6[4].

The sensitivity and specificity were calculated for each individual and for each coverage. True positive

was defined as AB or BB genotype that was correctly called by FastGT in simulated data. True

negative values were defined as correctly called AA genotypes. The genotypes called from sex

chromosomes were not used for sensitivity and specificity calculations.

Testing genotype concordance

Version 20160503 of the FastGT package was used throughout this study. For the concordance analysis

with the Platinum genotypes, `gmer_counter` and `gmer_caller` were run with the default options.

The performance was tested on a Linux server with 32 CPU cores, 512GB RAM, and IBM 6Gbps and

SAS 7200rpm disk drives in a RAID10 configuration.

High-quality genotypes were retrieved from the Illumina Platinum Genomes FTP site at

ftp://ussd-ftp.illumina.com/hg38/2.0.1/.

BAM-format files of NA12877 and 12878 were downloaded from

ftp://ftp.sra.ebi.ac.uk/vol1/ERA172/ERA172924/bam/NA12877_S1.bam and

ftp://ftp.sra.ebi.ac.uk/vol1/ERA172/ERA172924/bam/NA12878_S1.bam.

FASTQ files were downloaded from the European Nucleotide Archive at

http://www.ebi.ac.uk/ena/data/view/ERP001960. FASTQ files for the chrY genotype comparison were

created from the corresponding BAM files using SAMtools bam2fq version 0.1.18. The read length of

the Platinum genomes was 101 nucleotides.

Illumina HumanOmniExpress microarray genotypes and Illumina NGS data (read length 151 nt) for

individuals V00278, V00328, V00352, V00369, V00402, V08949, V09325, V09348, V09365, and

V09381 were obtained from the Estonian Genome Center. For the concordance analysis with the

microarray genotypes, `gmer_caller` was run with the microarray markers (504,173) only.

The 5x, 10x 20x, 30x, and 40x data points for Figure 4 were created using random subsets of reads

from raw FASTQ files of 50x coverage from the Platinum individual NA12878.

Code availability

The binaries of FastGT package and *k*-mer databases described in the current paper are available on our

website, http://bioinfo.ut.ee/FastGT/. The source code is available at GitHub

(https://github.com/bioinfo-ut/GenomeTester4/). `Gmer_counter` and `gmer_caller` are

distributed under the terms of GNU GPL v3, and the *k*-mer databases are distributed under the Creative

Commons CC BY-NC-SA license.

DISCUSSION

FastGT is a flexible software package that performs rapid genotyping of a subset of previously known

variants without a loss of accuracy. Another similar approach of genotype calling has been published

before[24]. Both methods need to pre-process the reference genome and personal short-read data. Our

method pre-processes the genome by selecting the SNVs and compiling the database of *k*-mers that can

be used for calling these SNVs. The short-read data is pre-processed by counting and storing the *k*-mer

frequencies using `gmer_counter`. The method by Kimura and Koike uses dictionary-based approach

for storing both reference sequence and short reads. The dictionary is implemented by means of the

Burrows-Wheeler transform (BWT). The main advantage of BWT is the ability of storing and

comparing long strings efficiently. Therefore, this method can be used to call all SNVs, including those

that are in repeated genomic regions. FastGT uses fixed length *k*-mer with maximum length of 32. This

limits the number of variants that can be called from the human genome. On the other hand, using fixed

length k-mers allows faster processing of data due to 64-bit architecture of computer hardware. Thus,

FastGT essentially sacrifices calling some SNVs (up to 36%) from difficult genomic regions to

minimize data processing time. Another difference between FastGT and the method used by Kimura

and Koike is handling of the *de novo* mutations. Kimura and Koike implemented two methods (drop-

scan and step-scan) to detect de novo variants based on k-mer coverage and/or by local alignment of

surrounding region. FastGT has currently no ability to call *de novo* variants and is limited to calling

sub-sets of pre-defined variants. Thus, FastGT functions in principle as a large digital microarray with

millions of probes.

Numerous software packages can organize the raw sequencing data of each individual into

comprehensive *k*-mer lists[28,31–34], which can be later used for fast retrieval of *k*-mer counts. However,

the compilation of full-genome lists is somewhat inefficient if the lists are only used once and then

immediately deleted. FastGT uses adaptive radix tree, which allows us to store frequencies for only the

k-mers of interest, instead of for all *k*-mers from the genome. This approach is particularly useful for

genotyping only a small number of variants from each individual. Storing only the frequencies of

relevant k-mers avoids the so-called "curse of deep sequencing," in which a higher coverage genome

can overwhelm the memory or disk requirements of the software[35]. The disk and memory requirements

of FastGT are not directly affected by the coverage of sequencing data.

Our analysis focuses on genotyping SNVs. However, FastGT is not limited to identifying SNVs. Any

known variant that can be associated with a unique and variant-specific k-mer can be detected with

FastGT. For example, short indels could be easily detected by using pairs of indel-specific k-mers. In

principle, large indels, pseudogene insertions, polymorphic Alu-elements, and other structural variants

could also be detected by k-mer pairs designed over the breakpoints. However, the detection of

structural variants relies on the assumption that these variants are stable in the genome and have the

same breakpoint sequences in all individuals, which is not always true for large structural variants. The

applicability of FastGT for detecting structural variants requires further investigation and testing.

This software has only been used with Illumina sequencing data, which raises the question of whether

our direct genotyping algorithm is usable with other sequencing technologies. In principle, k-mer

counting should work with most sequencing platforms that produce contiguous sequences of at least k

nucleotides. The uniformity of coverage and the fraction of sequencing errors in raw data are the main

factors that influence k-mer counting because a higher error rate reduces the number of usable k-mers

and introduces unwanted noise. The type of error is less relevant because both indel-type and

substitution-type errors are equally deleterious for k-mer counting.

NGS data are usually stored in BAM format, and the original FASTQ files are not retained. In this

case, the FASTQ file can be created from available BAM files. This can be performed by a number of

software packages (Picard, bam2fq from SAMtools package[1], bam2fastx from TopHat package[36]). We

have tested FastGT software with raw FASTQ files and FASTQ files generated from the BAM-

formatted files and did not observe significant differences in the k-mer counts or genotype calls. In

principle, care should be taken to avoid multiple occurrences of the same reads in the resulting FASTQ

file. Regardless of the method of genome analysis, contamination-free starting material, diligent sample

preparation, and sufficient genome coverage are the ultimate pre-requisites for reliable results. The

"garbage in, garbage out" principle applies similarly to mapping-based genome analyses and k-mer

based genome analyses.

424
425
426 **REFERENCES**
427

1.   Eberle, M. A. *et al*. A reference dataset of 5.4 million phased human variants validated by
genetic inheritance from sequencing a three-generation 17-member pedigree. *bioRxiv* (2016).
2.   Li, H. & Durbin, R. Fast and accurate long-read alignment with Burrows-Wheeler transform.
Bioinformatics **26,** 589–95 (2010).
3.   Li, H. *et al*. The Sequence Alignment/Map format and SAMtools. *Bioinformatics* **25,** 2078–
2079 (2009).
4.   McKenna, A. *et al*. The Genome Analysis Toolkit: a MapReduce framework for analyzing
next-generation DNA sequencing data. *Genome Res*. **20,** 1297–303 (2010).
5.   Langmead, B. & Salzberg, S. L. Fast gapped-read alignment with Bowtie 2. *Nat. Methods* **9,**
357–9 (2012).
6.   Highnam, G. *et al*. An analytical framework for optimizing variant discovery from personal
genomes. *Nat. Commun*. **6,** 6275 (2015).
7.   Zook, J. M. *et al*. Integrating human sequence data sets provides a resource of benchmark SNP
and indel genotype calls. *Nat. Biotechnol*. **32,** 246–251 (2014).
8.   O'Rawe, J. *et al*. Low concordance of multiple variant-calling pipelines: practical implications

443    for exome and genome sequencing. *Genome Med*. **5,** 28 (2013).

444 9. Pirooznia, M. *et al*. Validation and assessment of variant calling pipelines for next-generation
445    sequencing. *Hum. Genomics* **8,** 14 (2014).

446 10. Li, H. Toward better understanding of artifacts in variant calling from high-coverage samples.
447    *Bioinformatics* **30,** 2843–51 (2014).

448 11. Derrien, T. *et al*. Fast computation and applications of genome mappability. *PLoS One* **7,**
449    (2012).

450 12. Lee, H. & Schatz, M. C. Genomic dark matter: The reliability of short read mapping illustrated
451    by the genome mappability score. *Bioinformatics* **28,** 2097–2105 (2012).

452 13. Weisenfeld, N. I. *et al*. Comprehensive variation discovery in single human genomes. *Nat.*
453    *Genet*. **46,** 1350–5 (2014).

454 14. Wen, J., Chan, R. H. F., Yau, S.-C., He, R. L. & Yau, S. S. T. K-mer natural vector and its
455    application to the phylogenetic analysis of genetic sequences. *Gene* **546,** 25–34 (2014).

456 15. Ondov, B. D. *et al*. *Mash: fast genome and metagenome distance estimation using MinHash*.
457    (2015). doi:10.1101/029827

458 16. Haubold, B., Klötzl, F. & Pfaffelhuber, P. andi: fast and accurate estimation of evolutionary
459    distances between closely related genomes. *Bioinformatics* **31,** 1169–75 (2015).

460 17. Hasman, H. *et al*. Rapid whole-genome sequencing for detection and characterization of
461    microorganisms directly from clinical samples. *J. Clin. Microbiol*. **52,** 139–46 (2014).

462 18. Wood, D. E. & Salzberg, S. L. Kraken: ultrafast metagenomic sequence classification using
463    exact alignments. *Genome Biol*. **15,** R46 (2014).

464 19. Roosaare, M. *et al*. *StrainSeeker: fast identification of bacterial strains from unassembled*
465    *sequencing reads using user-provided guide trees*. (2016). doi:10.1101/040261

466 20. Song, L., Florea, L. & Langmead, B. Lighter: fast and memory-efficient sequencing error
467    correction without counting. *Genome Biol*. **15,** 509 (2014).

468 21. Marçais, G., Yorke, J. A. & Zimin, A. QuorUM: An Error Corrector for Illumina Reads. *PLoS*
469    *One* **10,** e0130821 (2015).

470 22. Lim, E.-C. *et al*. Trowel: a fast and accurate error correction module for Illumina sequencing
471    reads. *Bioinformatics* **30,** 3264–5 (2014).

472 23. Zhao, X. *et al*. EDAR: an efficient error detection and removal algorithm for next generation
473    sequencing data. *J. Comput. Biol*. **17,** 1549–60 (2010).

474 24. Kimura, K. & Koike, A. Ultrafast SNP analysis using the Burrows-Wheeler transform of short-
475    read data. *Bioinformatics* **31,** 1577–83 (2015).

476 25. Meyer, M. *et al*. A high-coverage genome sequence from an archaic Denisovan individual.
477    *Science* **338,** 222–6 (2012).

478 26. NCBI Resource Coordinators. Database resources of the National Center for Biotechnology
479    Information. *Nucleic Acids Res*. **44,** D7-19 (2016).

480 27. Sherry, S. T., Ward, M. & Sirotkin, K. dbSNP-database for single nucleotide polymorphisms
481    and other classes of minor genetic variation. *Genome Res*. **9,** 677–9 (1999).

482 28. Kaplinski, L., Lepamets, M. & Remm, M. GenomeTester4: a toolkit for performing basic set
483    operations - union, intersection and complement on k-mer lists. *Gigascience* **4,** 58 (2015).

484 29. Ross, M. G. *et al*. Characterizing and measuring bias in sequence data. *Genome Biol*. **14,** R51
485    (2013).

486 30. Schirmer, M., D'Amore, R., Ijaz, U. Z., Hall, N. & Quince, C. Illumina error profiles: resolving
487    fine-scale variation in metagenomic sequencing data. *BMC Bioinformatics* **17,** 125 (2016).

488 31. Marçais, G. & Kingsford, C. A fast, lock-free approach for efficient parallel counting of
489    occurrences of k-mers. *Bioinformatics* **27,** 764–770 (2011).

490 32. Deorowicz, S., Kokot, M., Grabowski, S. & Debudaj-Grabysz, A. KMC 2: Fast and resource-
491    frugal k-mer counting. *Bioinformatics* **31,** 1569–1576 (2014).

492 33. Rizk, G., Lavenier, D. & Chikhi, R. DSK: K-mer counting with very low memory usage.
493    *Bioinformatics* **29,** 652–653 (2013).

494 34. Roy, R. S., Bhattacharya, D. & Schliep, A. Turtle: Identifying frequent k-mers with cache-
495    efficient algorithms. *Bioinformatics* **30,** 1950–1957 (2014).

496 35. Roberts, A. & Pachter, L. RNA-Seq and find: entering the RNA deep field. *Genome Med*. **3,** 74
497    (2011).

498 36. Trapnell, C., Pachter, L. & Salzberg, S. L. TopHat: Discovering splice junctions with RNA-
499    Seq. *Bioinformatics* **25,** 1105–1111 (2009).

500
501

ACKNOWLEDGEMENTS

This work was funded by institutional grant IUT34-11 from the Estonian Ministry of Education and Research, grant SP1GVARENG from the University of Tartu, and the EU ERDF grant No. 2014-2020.4.01.15-0012 (Estonian Center of Excellence in Genomics and Translational Medicine). The cost of the NGS sequencing of the individuals from the Estonian Genome Center was partly covered by the Broad Institute (MA, USA) and the PerMed I project from the TERVE program. The genome data was collected and used with ethical approval Nr. 206T4 (obtained for the project SP1GVARENG). The computational costs were partly covered by the High Performance Computing Centre at the University of Tartu. The authors thank Märt Roosaare, Ulvi Talas, and Priit Palta for performing a critical reading of the manuscript.

AUTHOR CONTRIBUTIONS

FDP compiled the databases of unique k-mers and conducted the genotype concordance analyses. LK invented the data structures and algorithms for `gmer_counter` and `gmer_caller` and implemented their code in C. MM wrote the initial code of the Bayesian classifier for genotype calling and supervised the development of a statistical framework. TP validated the genotyping results by performing a manual analysis of BAM files and providing expertise for NGS data management. ML performed an initial survey of the optimal number of k-mer pairs per variant. MR supervised the work and wrote the final version of the manuscript.

COMPETING FINANCIAL INTERESTS

The authors declare no competing financial interests.

FIGURES

Figure 1. Overall principle of k-mer-based genotyping.

Figure 2. Illustration of genotype calling based on the frequencies of two k-mers. The parameters that define boundaries between genotypes are estimated from the k-mer frequency data of each individual. By default, only conventional genotypes are reported in the output. "A" denotes the reference allele, and "B" denotes an alternative allele. The estimated depth of coverage (λ) of the individual used in this example was 38.6.

Figure 3. Performance of Bayesian classifier with simulated data. Sensitivity and specificity of calling alternative alleles is shown for reference genome and simulated genome of individuals from 5 different populations. Populations are abbreviated as follows: EST – Estonian; CHS – Southern Han Chinese; PUR – Puerto Rican; CEU – Utah residents with Northern and Western European Ancestry; YRI – Yoruban from Ibadan, Nigeria. Specificities are nearly identical for all individuals and thus their lines are overlapping with the green dotted line.

Figure 4. Effect of genome coverage on the concordance of genotypes. The accuracy of calling non-reference variants starts to decline as the genome coverage drops below 20x. Only the accuracy of the non-reference allele (genotypes AB and BB) calls declines significantly as the coverage drops because the higher prior probability of the reference allele has a stronger influence on the final decision of the Bayesian classifier in situations where the coverage is low (which increases the bias toward the more common allele).

Figure 5. Effect of k-mer length on filtering SNV markers. Lines show the fraction of remaining markers after filtering steps 1 and 2. The step 1 removes SNVs that have other marker within k nucleotides on both sides. The step 2 removes SNVs that have no unique k-mers in the expanded reference genome. Y-axis indicates the fraction of remaining markers after each filtering step. 100% in this figure corresponds to 46,954,719 SNVs from the dbSNP that were fed to filtering pipeline.

Figure 6. The time spent counting k-mer frequencies is proportional to the genome coverage (because of the larger FASTQ files). `Gmer_counter` is able to read data from multiple files simultaneously; thus, it runs faster if the sequence data are distributed between different files (e.g., files with paired reads).

 TABLES

563 **Table 1**. Genotypes retrieved from the simulated reads generated from the reference genome. "A"

564 denotes the allele from the reference genome, and "B" denotes the alternative allele. "NC" is no-call.

		Coverage				
		5x	10x	20x	30x	40x
FastGT genotype calls	AA	28,734,597 (98.943%)	29,025,104 (99.943%)	29,027,872 (99.952%)	29,025,157 (99.943%)	29,011,146 (99.895%)
	AB	6,140 (0.021%)	12,107 (0.042%)	13,567 (0.047%)	11,007 (0.038%)	10,898 (0.038%)
	BB	0 (0%)	0 (0%)	0 (0%)	0 (0%)	0 (0%)
	NC	300,941 (1.036%)	4,467 (0.015%)	239 (0.001%)	5,514 (0.019%)	19,634 (0.068%)

568 **Table 2**. Concordance between the autosomal genotypes of two individuals from the Platinum dataset

569 and bi-allelic FastGT genotypes called from the same individuals. The reference allele is denoted by

570 "A" and the alternative allele is denoted by "B" denotes the alternative allele.

		Platinum genotype calls		
		AA	AB	BB
FastGT genotype calls	AA	54,246,425 (93.39%)	987 (0.00%)	68 (0.00%)
	AB	20,041 (0.03%)	2,427,315 (4.18%)	1,516 (0.00%)
	BB	2,261 (0.00%)	156 (0.00%)	1,245,902 (2.14%)
	NC	126,513 (0.22%)	1,787 (0.00%)	10,376 (0.02%)
	concordant (%)	99.96%	99.95%	99.87%