Habits without Values

Kevin J. Miller*[,1,] Amitai Shenhav*[,1,2,] Elliot A. Ludvig[3]

[1]Princeton Neuroscience Institute, Princeton University, Princeton, NJ, USA

[2]Department of Cognitive, Linguistic, and Psychological Sciences, Brown Institute for Brain Science, Brown University, Providence, RI, USA

[3]Department of Psychology, University of Warwick, Coventry, UK

* These authors contributed equally to this work

Abstract

Habits form a crucial component of behavior. In recent years, key computational models have conceptualized habits as behaviors arising from model-free reinforcement learning (RL) mechanisms, which typically represent the expected value associated with the possible outcomes of each action before one of those actions is chosen. Traditionally, however, habits have been understood as arising from mechanisms that are independent of outcomes. Here, we develop a computational model instantiating this traditional view, in which habits are acquired through the direct strengthening of recently taken actions, independent of outcome. We demonstrate how this model accounts for key behavioral manifestations of habits, including insensitivity to outcome devaluation and contingency degradation, as well as the dependence of formation rates on the reinforcement schedule. The model also explains the prevalent observation of perseveration in repeated choice tasks as an additional behavioral manifestation of the habit system. We suggest that mapping habitual behaviors onto value-free mechanisms provides a parsimonious account of existing behavioral and neural data. This mapping may provide a new foundation for building robust and comprehensive models of the interaction of habits with other, more goal-directed types of behaviors, and help to better guide research into the neural mechanisms underlying control of instrumental behaviors more generally.

Introduction

A critical distinction exists between behaviors that are directed toward goals and those that are habitual. A large and growing body of work indicates that these behaviors depend on different sets of computations and different underlying neural circuits, suggesting that separable goal-directed and habitual systems implement fundamentally different strategies for the control of behavior (Balleine & O'Doherty, 2010; Dickinson, 1985; Dolan & Dayan, 2013; Wood & Rünger, 2016; Yin & Knowlton, 2006). Goal-directed behaviors are understood to be driven by consideration of the outcomes that they are likely to bring about (i.e. "action-outcome" representations). Habits, on the other hand, are understood to be driven by direct links between cues in the environment and the actions that have often followed those cues (i.e. "stimulus-response" associations). The same action may be taken under either goal-directed or habitual control in different circumstances: For example, you may take a left turn at an intersection because you have determined that turning left will get you home fastest given the specific layout of the roads and other relevant circumstances (goal-directed) or because that is what you have always done in the past at that intersection (habitual).

Habitual behaviour tends to form most strongly in circumstances where actions are repeated very consistently (Dickinson, 1985; Wood & Rünger, 2016). For example, behavior in a novel environment is never habitual – habits form only with extensive experience with an environment and often depend upon behaviors initially undertaken under goal-directed control (Wood & Neal, 2007). The nature of an environment also has a profound influence on whether and how quickly habits are likely to form. Habits form slowly in environments where different behaviors lead to very different outcomes (Adams, 1982), and quickly when the environment is relatively unpredictable (Derusso et al., 2010) or when behavior is repeated with a high rate of consistency (Lally, van Jaarsveld, Potts, & Wardle, 2010). Once a behavior has become a habit, that behavior is rendered inflexible to changes in the environment, including those which make the behavior undesirable (Adams & Dickinson, 1981; Hammond, 1980).

Together, these findings support a traditional view of the role of habits in instrumental control, in which they result from direct (e.g. Hebbian) strengthening of stimulus-response associations (Figure 1, left). In contrast to this view, modern computational accounts typically model habits as arising from reinforcement learning mechanisms which are outcome sensitive (Figure 1, right). Here, we argue that such computational accounts stand in tension with key data on the

psychology and neuroscience of habits. We introduce a novel computational account instantiating the traditional view of habits and argue that this account provides a more parsimonious explanation for the behavioral and neural data.

Figure 1. Left: Traditional view of the relationship between habits and goal-directed control. Habits are viewed as stimulus-response associations which become stronger with use, while goal-directed control takes into account knowledge of action-outcome relationships as well as current goals in order to guide choice. Right: Common computational view. Habits are implemented by a model-free RL agent which learns a value function over states and actions, while goal-directed control is implemented by a model-based RL agent which learns about the structure of the environment.

Popular computational models of habits commonly appeal to Thorndike's "Law of Effect," which holds that an action that has been followed by rewarding outcomes is likely to be repeated in the future (Thorndike, 1911). Modern reinforcement learning (RL) has elaborated this law into a set of computational algorithms, according to which actions are selected based on cached values learned from previous experience (Daw, Niv, & Dayan, 2005; Dolan & Dayan, 2013). This class of computations focuses only on potential rewards, ignoring all reward-unrelated elements of one's environment (discussed below); it is therefore referred to as "model-free" RL. This formulation for habits has become so prevalent that the terms "habit" and "model-free" are now used interchangeably (Dolan & Dayan, 2013; Doll, Simon, & Daw, 2012) in much of the computational literature. Equating these terms, however, carries a critical assumption: that habits are driven by a reward-maximization process (i.e., a process that depends directly on potential outcomes).

Model-free algorithms typically operate by learning the expected future reward associated with each possible action or

state, relying crucially on these value representations. This idea, that habits are *value-based*, strains against traditional interpretations of habits as stimulus-response (S-R) associations that are blind to potential outcomes (Dickinson, 1985; Hull, 1943). The latter, *value-free* definition for habits drove the development of critical assays that have been used to discriminate between actions that are habitual versus goal-directed (i.e., outcome-sensitive), testing whether an animal continues to pursue a previous course of action when that action is no longer the most beneficial (Adams & Dickinson, 1981; Hammond, 1980). Such a value-free formulation of habits aligns well with Thorndike's second law, the "Law of Exercise." This law holds that an action that has been taken often in the past is likely to be repeated in the future, independent of its past consequences; in other words, it describes habits as a form of perseveration. This category of value-free habits has been maintained in modern theorizing on habits, where it has been referred to as "direct cuing" of behavior, as distinct from value-based forms of habits ("motivated curing"; Wood & Neal, 2007; Wood & Rünger, 2016).

Here, we develop a computational implementation of the Law of Exercise and show that it offers a plausible and appealing alternative mechanism for habits. This value-free habit mechanism accounts for key findings in the animal learning literature that dissociate habitual and goal-directed actions, namely the tendency for an animal to continue performing a previously learned action when that action is no longer predictive of the reinforcing outcome (contingency degradation; Hammond, 1980) or when the predicted outcome ceases to be desired by the subject (outcome devaluation; Adams & Dickinson, 1981). In addition, this model provides what is to our knowledge the first computational account of the difference in rate of habit formation under variable interval and variable ratio schedules of reinforcement (Adams, 1982; Dickinson, 1985; Gremel & Costa, 2013). Furthermore, a value-free habit mechanism explains a variety of other behavioral phenomena in which responses are facilitated by simple repetition (i.e. perseveration; Akaishi, Umeda, Nagase, & Sakai, 2014; Bertelson, 1965; Cho et al., 2002; Gold, Law, Connolly, & Bennur, 2008; Gore, Dorris, & Munoz, 2002; Kim, Sul, Huh, Lee, & Jung, 2009; Lau & Glimcher, 2005; D. Lee, McGreevy, & Barraclough, 2005).

In addition to reformulating the computational underpinnings of habits, we will show that our model offers a critical realignment to prevailing models of instrumental control. According to this prevailing computational framework (Figure 1, right), an equivalence between habitual control and model-free RL computations is paralleled by an equivalence between goal-directed behavior and another set of RL computations, referred to as "model-based" RL (Daw et al., 2005;

Dolan & Dayan, 2013). Model-based RL guides behavior through an internal model of the environment that is used to estimate values for each action. This internal model of the environment includes both the expected likelihood of transitioning between environmental states and the expected rewards for each action. A substantial theoretical and empirical literature has been built around the idea that the habitual/goal-directed distinction can be equated with the model-free/model-based distinction from RL, and this presumed equivalence has been used to glean insight into complex decision-making phenomena, such as addiction (Lucantonio, Caprioli, & Schoenbaum, 2014; Redish, Jensen, Johnson, & Kurth-Nelson, 2007), impulsivity (Kurth-Nelson, Bickel, & Redish, 2012; Rangel, 2013), compulsivity (Gillan, Kosinski, Whelan, Phelps, & Daw, 2016; Gillan, Otto, Phelps, & Daw, 2015), and moral judgement (Buckholtz, 2015; Crockett, 2013; Cushman, 2013). By offering a fresh perspective on the nature of habits – replacing model-free RL with a value-free mechanism – our model forces a critical realignment of this prevailing framework, thereby prompting a deeper consideration of how the computations and circuitry for model-free and model-based reinforcement learning might share more commonalities than differences.

Figure 2: Schematic description of the model components and their interactions. See main text for details

Methods

Computational Model

As proof of concept, we implemented the proposed mechanisms for habitual and goal-directed control in a computational

model. The model contains goal-directed (GD) and habitual (H) controllers. The goal-directed controller is sensitive to

outcomes, selecting actions that are likely to lead to outcomes that have high value. The habitual controller, on the other

hand, is sensitive only to the history of selected actions. It tends to repeat actions that have frequently been taken in the

past (e.g., because they were in the past selected by the goal-directed controller), regardless of their outcomes. On each

trial, the decision of the model is driven by the combined influence of both controllers, and the weight assigned to each

controller is determined by an arbitration mechanism that takes into account action-outcome contingency.

Habitual Controller

The habitual controller is sensitive only to the history of selected actions, and not to the outcomes of those actions. This

action history is tracked by a matrix of habit strengths, **h***(s,a)* that acts as an exponentially weighted memory of past

actions in each state. These habit strengths are updated after each trial according to the following equation:

$$\mathbf{h}_{t+1}(s_t) = \mathbf{h}_t(s_t) + \alpha_h(\mathbf{A}_t - \mathbf{h}_t(s_t)) \qquad\qquad 1$$

where s_t is the current state, α_H is a step-size parameter that determines the rate of learning, and A_t is a vector over actions

in which all elements are zero except for the one corresponding to the action taken on trial *t*. This update takes place after

every trial, and affects all actions available in state s_t, with the strength for at increasing towards one, and the strength for

all other available actions decreasing towards zero. Habit strengths for states other than s_t are not affected.

Goal-Directed Controller

The goal-directed controller is composed of a model-based RL system, sensitive not only to the actions taken, but also to

their outcomes. In contrast to traditional reinforcement learning methods, this model does not consider "common

currency" reward, but rather learns separately about reinforcers of different types *m*. It maintains an estimate both of the

reinforcers it expects to receive upon taking each action in each state *R(s,a,m)*, as well as the probability *T(s,a,s')* with

which it expects each action taken in each state to lead to each possible subsequent state. After each trial, the agent

updates these quantities according to the following equations (Sutton & Barto, 1998):

$$R_{t+1}(s_t, a, m) = R_t(s_t, a, m) + \alpha_R\big(r_t(m) - R_t(s_t, a, m)\big) \qquad 2$$

$$T_{t+1}(s_t, a_t, s') = \begin{cases} T_t(s_t, a_t, s') + \alpha_T\big(1 - T_t(s_t, a_t, s')\big) & s = s_{t+1} \\ T_t(s_t, a_t, s') + \alpha_T\big(1 - T_t(s_t, a_t, s')\big) & s' \neq s_{t+1} \end{cases} \qquad 3$$

where s_t is the current state, at is the action taken in that state, r_t is the reinforcer received following that action, and s_{t+1} is

the subsequent state. Step-size parameters α_R and α_T govern the rate of each of these types of learning. To ensure proper

normalization, T is initialized to $1/n$, where n is the total number of states in the environment (with the exception of

known terminal states). The goal-directed controller calculates the expected future value associated with each action in

each state, defined recursively by the Bellman optimality equation:

$$Q_t(s, a) = \sum_m U(m) * R_t(s, a, m) + \sum_{s'} T_t(s, a, s') * \max_{a'}\big(Q_t(s', a')\big) \qquad 4$$

where $U(m)$ is a utility function (typically unity, but see *Simulation Three: Outcome Devaluation*) giving the value that

the agent assigns to reinforcers of each type m. In this implementation of the model, we use value iteration to numerically

approximate a solution to this recursive equation, to within a threshold of 10^{-3}.

Arbiter

The arbiter governs the relative influence of each controller on each trial. It computes an overall drive D in favor of each

action on each trial as a weighted sum of the habit strength h and the goal-directed value Q.

$$D(s, a) = w * \theta_H * h(s, a) + (1 - w) * \theta_{GD} * Q(s, a) \qquad 5$$

Where θ_H, and θ_{GD} are scaling parameters, and w is a weight computed on each trial by the arbiter to determine the relative

influence of each controller (see Equation 9). The model then selects actions according to a softmax on D:

$$\pi(s, a) = \frac{e^{D(s,a)}}{\sum_{a'} e^{D(s,a')}} \qquad\qquad 6$$

To determine the appropriate weight w, the arbiter computes two quantities, the *action-outcome contingency* (AO) and the overall *habitization* (H), which promote goal-directed and habitual control, respectively. Action-outcome contingency is a measure of the extent to which the expected outcome received varies according to the action that is performed. Here, we quantify this as the variance in expected outcome, given a particular policy π:

$$AO(s, m) = \left\langle \left(R - \langle R \rangle \right)^2 \right\rangle = \sqrt{\sum_{a} \pi(s, a) \left(R(s, a, m) - \sum_{a'} \pi(s, a') R(s, a', m) \right)^2} \qquad 7$$

AO is minimal when all actions have the same expected outcome and increases as the outcomes associated with some actions are increasingly distinct from the outcomes associated with other actions. Note that this measure considers the degree to which *average expected* outcome varies with action. It does not consider the degree to which *particular outcomes* vary conditional on particular actions (e.g., an environment in which one action led to one pellet with certainty and another led to two pellets with 0.5 probability would be rated as having zero action-outcome contingency because the average outcome is identical for both actions). In our simulations, we include two types of reinforcers: "food pellets" and "leisure". Because leisure is not a true outcome in the environment, we compute AO with respect to food pellets only.

The arbiter also computes an analogous quantity for the habitual controller, the variance in habit strength across actions:

$$H(s) = \sqrt{\sum_{a} \left(h(s, a) - \text{mean}\left(h(s, a) \right) \right)^2} \qquad\qquad 8$$

H is minimal when no action has a large habit strength, or when all action have approximately equal habit strengths. H is maximized when one or a few actions have much larger habits strengths than the others. The arbiter then computes the weighting parameter w on the basis of these two quantities:

$$w = \frac{1}{1 + e^{W_{GD}*AO(s) - W_{H}*H(s) + B}} \qquad\qquad 9$$

where W_{GD} and W_{H} are scaling parameters controlling the relative strengths of the goal-directed and habitual systems, and B is a bias parameter, which shifts control toward the goal-directed system. This calculation represents a push-pull

relationship whereby goal-directed control is facilitated to the extent action-outcome contingency is high, while habits are facilitated to the extent that variance in habit strengths is large. Figure 3 provides an intuition for how each of the values described above evolve in a setting where the more valuable of two actions reverses at some point in a session.

Simulated Task Environments

Simulation 1: Reversal Learning

To illustrate the behavior of the model and the dynamics of its various internal variables, we simulated behavior in a probabilistic reversal learning task (Fig 3). In this task, the agent was presented with an environment consisting of a single state in which two actions were available. In the first phase of the task (1000 trials), performance of one action (Action A) resulted in a reinforcer 50% of the time, while performance of Action B never did. In the second phase (reversal), Action A never resulted in a reinforcer, while Action B resulted in one 50% of the time that it was taken.

Simulation 2: Omission Contingency

We simulated behavior in an omission experiment using a similar environment with one state and two available actions. In the first phase, performance of one action (Press Lever) resulted in a reinforcer of one type (Pellet) 25% of the time, while performance of the other action (Withhold Press) resulted in a reinforcer of another type (Leisure) 100% of the time. In the second phase, performance of Press Lever was never reinforced, but performance of Withhold Press resulted in both a 25% chance of Pellet and a 100% chance of Leisure. We set the agent's utilities for Pellet and Leisure to 1.0 and 0.1, respectively. To investigate the effect of training duration on behavioral flexibility in the face of omission, we varied the number of trials in the training phase from 100 to 2000, in intervals of 100. The omission phase was always 500 trials in duration. We simulated ten agents for each duration of phase one, and report the average rate of performance of Press Lever for the final trial in each phase.

Simulation 3: Outcome Devaluation

We simulated behavior in an outcome devaluation experiment in a similar way. The training phase was identical to that used for omission. The omission phase was followed by a devaluation manipulation, in which we set the agent's utility for the Pellet reinforcer to 0, and then an extinction phase. In the extinction phase, performance of Press Lever results in no outcome, while performance of Withhold Press continues to result in Leisure with probability 100%. To investigate the

effect of training duration on behavioral flexibility in the face of devaluation, we again varied the number of trials in the training phase from 10 to 2000 in intervals of 100, and report the average rate of performance of Press Lever for the final trial in each phase.

Simulation 4: Framework for Free-Operant Tasks

Assays of goal-directed and habitual behavior are typically performed not in two-alternative forced-choice environments like those we describe above, but rather in free-operant tasks in which subjects are not constrained by a discrete trial structure, but are free to perform one or more actions (e.g., lever presses) at any rate they wish. To simulate these environments, we adjusted our model to accommodate choices along this continuous variable (lever press rate). In this simulation, the actions (*a*) were press rates, which ranged between 0 and 150 presses per minute. This extension to a larger action space required two changes to the model. The first was the use of function approximation to compute the reinforcer function *R(a,m)* and the habit strength *h(a)*. Instead of learning these functions directly over each value of a, as in equation 1 or 2, the model approximated them using a set of basis functions. For the reinforcement function *R(s,a,m)*, we used a Taylor basis set with four bases:

$$R(a, m) = \sum_{i=0}^{3} w_{i,m} \left(\frac{a - 75}{75} \right)^i \qquad 10$$

where $w_{i,m}$ are learned weights (see Equation 12) for each component of the Taylor expansion for each reinforcer type. For the habit strength function *h(s,a)*, we used a set of 30 Gaussians bumps with means at intervals of 5 and standard deviation 5:

$$h(a) = \sum_{i=1}^{30} w_i e^{-\frac{(a-5i)^2}{2*5^2}} \qquad 11$$

The update equations then become:

$$\mathbf{w}_{t+1,m} = \mathbf{w}_{t,m} + \alpha_R \left[r_t(m) - R(a_t) \right] \nabla_{\mathbf{w}_{t,m}} R(a_t)$$

$$\mathbf{w}_{t+1} = \mathbf{w}_t + \alpha_H \left[\mathbf{A}_t - \mathbf{h} \right] \nabla_{\mathbf{w}_t} h$$

for goal-directed and habitual weights, respectively. The second change we made was to introduce an "action density"

measure *M*, which can be thought of as controlling how many actions are available for a particular press rate. Selecting an

action density measure that is sharply peaked at zero ensures that a "random choice" agent will on average press at a low

rate, rather than selecting at random from a uniform distribution of press rates (i.e., on average pressing at half of the

maximum possible rate). We used an exponentially decaying action density function with a scale of 5.

$$M(a) = e^{-\frac{a}{5}}$$ 13

This measure influences action selection, tending to prefer rates for which more actions are available. In place of Equation

6, the model now selects actions according to:

$$\pi(s, a) = \frac{e^{M(a)D(s,a)}}{\sum_{a'} e^{M(a')D(s,a')}}$$ 14

Habitization in Variable Interval vs. Variable Ratio Reinforcement Schedules

We used the above framework to simulate behavior under two reinforcement schedules commonly used in experiments on

animal learning, termed "variable interval" (VI) and "variable ratio" (VR). In a VR schedule, the probability of receiving a

reinforcer is constant after each lever press. Reinforcement rate is therefore directly proportional to response rate and

potentially unbounded. In a VI schedule, reinforcers are "baited" at variable intervals, and the first press following baiting

will lead to a reinforcer. The probability that a press will be reinforced therefore increases as a function of the time since

the last press, and reinforcement rate is a sub-linear function of response rate, saturating at the average baiting rate. In both

environments, lever pressing is thought to involve some effort cost, which increases superlinearly with the rate of

responding. To model acquisition in a VR environment, we used VR10, in which each press had a 10% chance of being

followed by a pellet. To model acquisition in a VI environment, we used VI10, in which pellets were baited on average

ten times per minute. In both cases, we included an effort cost that was quadratic in press rate. Specifically, each action

resulted in reinforcers of two types: Pellet Rate and Effort Rate.

Omission and Devaluation in VR vs. VI Schedules

To investigate the effects of training duration on behavioral flexibility in these free operant environments, we exposed agents given limited training (5,000 trials) or extended training (30,000 trials) in either a VR or a VI schedule to both Omission and Devaluation manipulations. In the Omission manipulation, we changed the reinforcement schedule such that the magnitude of the Pellet Rate reinforcer was inversely related to the Press Rate action. The magnitude of the Effort Rate reinforcer was not changed. In the Devaluation manipulation, we left the reinforcement schedule unchanged, but changed the agent's utility for the Pellet Rate outcome to 0.

Lesions of Goal-Directed vs. Habitual Controllers

To simulate lesions of goal-directed and habitual controllers on behavior in free operant tasks, we repeated the above experiments with the parameters of the model altered. Specifically, to model lesions of the goal-directed controller, we decreased the parameters θ_{GD} and W_{GD}, whereas to model lesions to the habitual controller, we decreased the parameters θ_H and W_H (see Table 2 for details).

Two-Armed Bandit Task

To illustrate the role of habits in producing perseveration in free choice tasks, we simulated data from our agent performing a two-armed bandit task. The model was tested in an environment consisting of one state in which two actions are available. Performing either of these actions led to a reinforcer with some probability. Reinforcer probabilities were initialized uniformly between 0 and 1, and changed slowly across trials according to independent Gaussian random walks (SD = 0.15; bounded at 0 and 1), requiring the agent to continuously learn. The agent performed 10,000 trials in this environment, using the parameters in Table 1. Task parameters were selected to facilitate comparison to a rodent behavior dataset using a similar task (Miller, Botvinick, & Brody, in prep; Miller, Erlich, Kopec, Botvinick, & Brody, 2013) . To simulate a dataset with similar characteristics to the rat dataset, we generated data from 50 copies of our model, with parameters sampled from the range described in Table 2.

We analyzed these datasets using a logistic regression model that quantifies the influence of previous choices and their outcomes on future choice (Lau & Glimcher, 2005; Miller et al., in prep).

$$\log \frac{P_t}{1 - P_t} = \sum_{\tau=1}^{N} \beta_A(\tau)a_{t-\tau} + \sum_{\tau=1}^{N} \beta_R(\tau)r_{t-\tau} + \sum_{\tau=1}^{N} \beta_X(\tau)a_{t-\tau}r_{t-\tau} \qquad 14$$

where P_t is the probability that the model believes the agent will select action 1 on trial t, a_t is the action taken on trial t, r_t is the reinforcer received, N is a parameter of the analysis governing how many past trials to consider, and β_A, β_R, and β_X are vectors of length N containing fit parameters quantifying the influence of past actions, reinforcers, and their interaction, respectively. Positive fit values of β_A indicate a tendency of the agent to repeat actions that were taken in the past, independently of their outcomes, while positive values of β_X indicate a tendency to repeat actions that led to reinforcement and to switch away from actions that do not.

Table 1. Parameter values used in simulations

	Two-Alternative Forced Choice	Operant Conditioning	Operant Conditioning GD Lesion	Operant Conditioning Habit Lesion
α_H	10^{-3}	10^{-5}	10^{-5}	10^{-5}
α_R	10^{-2}	10^{-1}	10^{-1}	10^{-1}
θ_H	5	10^3	10^3	0
θ_{GD}	5	20	2	20
W_H	5	15	15	0
W_{GD}	5	6	0	6
W_0	1	1	1	1

Results

Our model proposes that behavior arises from the combined influence of two controllers: one driven by value-free perseveration (habitual) and one driven by model-based reinforcement learning (goal-directed). Figure 3 illustrates the learning dynamics of these two controllers in a simple reversal learning task, where an animal first learns to associate Action A with a higher probability (0.5) of reinforcement than Action B (0) and, after 1000 trials, this contingency reverses (Figure 3A). Initially, behavior is driven by the goal-directed controller, which gradually learns the relative reinforcement rates (Figure 3B) and thus increasingly selects Action A. As it does so, the habitual controller strengthens its association between the current stimuli and Action A (Figure 3C). As these habits strengthen, the habitual controller

increasingly drives the choice of which action to select (Figure 3D). As a result, when the reversal occurs, the agent

continues to select Action A for an extended period, past the point where the goal-directed controller has learned that

Action B is more likely to be reinforced (compare Figures 3B and 3E). In addition to demonstrating the different kinds of

learning that drive each of these controllers, this example demonstrates that our model captures the observation that

behavioral control in a novel environment tends to evolve from goal-directed to habitual (i.e., habits form from actions

that were originally selected in a value-based manner). In the following sections we demonstrate that this model can

capture all of the key diagnostic features of habitual behavior previously identified in animal behavior, including

sensitivity to repetition frequency, reinforcement schedule, and selective modulation by lesions to one of two dissociable

neural circuits.

Figure 3. A) Simulations of a reversal-learning environment: Action A is initially reinforced with higher

probability (0.5) than Action B (0), but after 1000 trials, the relative dominance of the actions reverses. B)

Soon after the reversal, the goal-directed system learns that Action B is more valuable. C) The habit

system increasingly favors Action A the more often it is chosen and only begins to favor Action B once

that action is chosen more consistently (long after reversal). D) The weight of the goal-directed controller

gradually decreases as habits strengthen, then increases post-reversal as the global and goal-directed

reinforcement rates diverge. E) Actions are selected on each trial by a weighted combination of the

goal-directed values (Q) and the habit strengths (H) according to the weight (w).

Effects of Training Duration on Behavioral Flexibility

We first test whether our model can capture a central finding from research on habits: that extensive training in a static

environment (overtraining) can render behavior inflexible in the face of changes to that environment. This is classically

demonstrated in two ways: by altering the contingencies between actions and outcomes, or by devaluing the outcomes

themselves. The first of these manipulations involves altering the probability that an outcome (e.g., a food pellet) will be

delivered following an action (e.g., a lever-press) and/or the probability that it will be delivered in the absence of the

action (contingency degradation). Overtrained animals will often continue to perform an action even when it no longer

causes the desired outcome (indeed, even when it *prevents* the delivery of the outcome). This perseverative behavior is

diagnostic of habitual control (Dickinson, 1998). The second manipulation involves rendering the outcome no longer

desirable to the animal (e.g., by pairing its consumption with physical illness) – in this setup, overtrained animals will

often continue performing an action that leads to an outcome they no longer desire (Adams, 1982).

We simulated the effect of overtraining on sensitivity to an omission contingency by running the model through simulated

sessions with two stages. The agent was initially trained in an environment where performance of Action A ("press lever")

was followed by a reinforcer of one type ("food pellet") 50% of the time, and Action B ("withhold press") was followed

by a reinforcer of another type ("leisure") 100% of the time. The agent's utility for the food pellet reinforcer was set to 1,

while the utility of the leisure reinforcer was set to 0.1, and with experience in this environment the agent learns to press

the lever on a large fraction of trials (Figure 4, blue curves). After a number of trials that varied between simulations, the

reinforcement probabilities for the food pellet were reversed, such that pressing the lever resulted in no reinforcement, and

withholding resulted in leisure 100% of the time and a food pellet 50% of the time.. When the agent was given a small

number of training trials, it successfully learned to decrease probability of lever pressing following this reversal. With

longer training sessions, however, the model failed to reverse its actions within the same time period (Figure 3, left). This

is consistent with data from animal learning, in which overtraining abolishes behavioral sensitivity to omission

contingencies (Dickinson, 1998)

Figure 4. Behavior becomes inflexible after overtraining. Rate of pressing in a simulated instrumental

conditioning task at the end of the training period (blue) as well as following omission or devaluation

manipulations (orange), as a function of the duration of the training period. As this duration increases, the

agent is increasingly unlikely to alter its behavior (blue and orange curves become similar). These

simulations are consistent with the finding that overtraining results in behavior that is insensitive to

omission and to devaluation. Error bars represent standard errors over ten simulations.

We simulated the effect of overtraining on outcome devaluation in a similar manner. The first stage of training was

similar, with lever pressing being followed by reward 50% of the time, and withholding being followed by leisure 100%

of the time. At the end of this first stage, the agent's utility for the food pellet reinforcer was decreased to zero, simulating

a devaluation manipulation. In the final stage (testing), the agent was placed back in the choice state, and had the

opportunity to again select between pressing and not pressing, with the outcome of pressing no longer delivering any

reinforcement. We found that the frequency of choosing to lever-press in the testing stage strongly depended on the

duration of the training stage (Figure 3, right), indicating that overtraining caused the agent to perseverate on the habitized

behavior (lever-pressing).

Effects of Reinforcement Schedule on Habit Formation

Another central finding from research on habitual control is that the reinforcement schedule has a profound effect on habit formation. Actions followed by a constant probability of reinforcement (variable-ratio [VR] schedules) take a long time to habitize (Adams, 1982). By contrast, when an action is "baited" at a constant probability per unit time, and only the first press following baiting results in reinforcement (variable-interval [VI] schedules), the action habitizes much more quickly, even when performance and overall rate of reinforcement are matched across these two reinforcement schedules (Dickinson, Nicholas, & Adams, 1983). The finding that VI schedules result in rapid habit formation has been widely replicated and represents a key element of the experimental toolkit for the study of habits (Gremel & Costa, 2013; Yin & Knowlton, 2006). We sought to replicate this effect using our model.

To do this, we adapted the model to operate in a continuous action space (see Methods for details). Briefly, at each timestep, instead of making a binary decision (e.g., between pressing the lever or not pressing), the agent instead selected a scalar lever pressing *rate*. Accordingly, the agent then observed a rate for each reinforcer rather than binary reinforcement. As the action Press Rate increased, two types of reinforcement increased, one with positive utility (Pellet Rate) and the other with negative utility (Effort Rate). For VR schedules, Pellet Rate is a linear function of Press Rate (Figure 4, top right), because each press results in reinforcement with equal probability. For VI schedules, Pellet Rate is a sublinear function of Press Rate, saturating at the rate of baiting (no matter how often a rat in a VI experiment presses the lever, reinforcers are only available as they are baited; Figure 4, top left). In both schedules, we modeled Effort Rate as a superlinear function of Press Rate (see Methods). The agents used function approximation to learn estimates for these functions, as well as for habit learning.

Consistent with empirical findings, we found that simulated agents trained on VI schedules lever-pressed at a moderate rate and habitized early in training (Figure 4, left) whereas agents trained on VR schedules lever-pressed at a high rate and habitized much later in training (Figure 4, right). This difference was largely driven by the difference in action-outcome contingencies inherent to each schedule: a small change in press rate resulted in a much larger change in reinforcement rate for a VR schedule relative to a VI schedule (compare the slope of the green curve in the right panel relative to the left panel of Figure 4).

Figure 5. Variable-Interval (VI) schedules produce more rapid habit formation than Variable-Ratio (VR) schedules. Top: Cross-sections of the state of the agent acquiring lever pressing on a VI (left) or VR (right) schedule, taken 5,000 trials into training. Solid curves indicate the rate of pellets or effort as a function of the rate of pressing. Note that in the VR schedule, pellet rate is linear in press rate, whereas in the VI schedule, the relationship is sublinear. Dashed red and green curves indicate the goal-directed system's estimates of these quantities (Q). The dashed orange curve indicates the habit strength (h) associated with each press rate. Bars give a histogram of the responses of the agent between trial 4,000 and trial 5,000. Bottom: Time courses of key model variables over the course of training.

Effects of Striatal Lesions on Habit Formation and Behavioral Flexibility

The degree to which an animal behaves flexibly in a given environment can be affected profoundly by manipulating specific brain structures. Lesions to regions of a putative "habit system," such as the dorsolateral striatum (DLS), promote behavioral flexibility (i.e., alleviate perseveration) following overtraining (Graybiel, 2008; Yin & Knowlton, 2006). Conversely, lesions to regions of a putative "goal-directed system," such as the dorsomedial striatum (DMS) impair flexibility (Yin, Ostlund, Knowlton, & Balleine, 2005). In particular, relative to control rats, rats with lesions to DMS lever-press at a lower rate and are less able to decrease their press rate when reinforcers are omitted or devalued (Yin et al., 2005); rats with lesions to DLS lever-press at a similar rate to controls, and are more successful than controls at adapting their press rate to omitted or devalued reinforcement (Yin, Knowlton, & Balleine, 2004, 2006).

We lesioned the goal-directed controller (DMS) or habitual controller (DLS) in our model while simulated agents performed the free-operant task (see Table 1 for details). These agents received either limited training (5,000 trials) or extensive training (15,000) in the VR environment. They were then subjected to either an omission contingency (greater rates of lever pressing caused lower rates of reinforcement) or a devaluation manipulation (the utility of the reinforcer was set to zero). Consistent with empirical findings described above, we found that lesioning the goal-directed system produced a low press rate that was unaffected by either omission or devaluation, whereas lesioning the habitual controller led to a high press rate that adapted to both manipulations (Figure 5). A "control" agent, with intact habitual and goal-directed controllers, adopted a high press rate that adapted to both manipulations when given limited training, but did not adapt to either following extensive training. Lesions to our model's goal-directed and habitual controllers thus reproduce behavioral patterns typical of DMS and DLS lesioned rats, respectively, in classic experiments on instrumental conditioning.

Figure 6. Model Reproduces Effects of Lesions on Behavioral Flexibility. Rate of lever pressing

before (blue) and after (orange) omission (top) or devaluation manipulations (bottom rows) performed

following either limited or extensive training (left and right columns). We simulated lesions by impairing

the goal-directed or habitual controllers, respectively (see Methods for details). The unlesioned model

responded flexibly to both manipulations following limited, but not extensive training. Goal-directed

lesions caused the model to acquire lever pressing at a much lower rate, and rendered it inflexible to all

manipulations, a pattern seen in rats with DMS lesions (Yin et al., 2005). Habit lesions caused the model

to respond flexibly to all manipulations, a patterns seen in rats with DLS lesions (Yin et al., 2004, 2006).

Perseverative Behavior in Sequential Choice Tasks

Finally, we turn to the ubiquitous and poorly understood phenomenon of perseveration, which we argue can be understood

as a manifestation of habitual control. In tasks where humans and animals make repeated decisions between similar

alternatives, a near-universal observation is a tendency to select actions that have frequently been selected in the past, regardless of their outcome or of the task stimuli. For instance, in instructed task settings with human subjects, the speed and accuracy of an action are enhanced when that action has been recently performed (Bertelson, 1965; Cho et al., 2002). Similar effects are seen in monkeys (Gore et al., 2002). They are also seen in difficult perceptual decision tasks, in which decisions are nominally driven by stimuli that vary from trial to trial in a random way – these effects span monkeys (Gold et al., 2008), rats (Scott, Constantinople, Erlich, Tank, & Brody, 2015), and humans (Akaishi et al., 2014). Perseveration in reward-guided tasks has been seen with the aid of trial-by-trial analyses in rats (Ito & Doya, 2009; Kim et al., 2009), monkeys (Lau & Glimcher, 2005; D. Lee et al., 2005), and humans (Rutledge, Dean, Caplin, & Glimcher, 2010).

In one recent example, rats performing a dynamic two-armed bandit task exhibited behavioral patterns consistent with both reinforcement-seeking (i.e., being more likely to select an recently reinforced action), as well with choice perseveration (i.e., being more likely to choose a recently chosen action). Figure 7 shows the time course of this sensitivity to recent reinforcers (left panel) and recent choices (middle panel) in one example rat (data from Miller et al., in prep). We simulated performance in such an environment and found that the model was able to simultaneously reproduce both the reinforcement-seeking (value-based) and perseverative (value-free) components of these behaviors (Figure 7, right, blue points). Replacing the habitual component of our model with a model-free reinforcement learning system rendered it unable to reproduce the perseverative pattern (Figure 7, right, red points). This example not only begins to validate the predictive abilities of our particular model, but also highlights the importance of a value-free habitual controller more generally in explaining habit-like behaviors that cannot otherwise be accounted for by a model-free RL-based algorithm alone.

Figure 7. Left/middle: Rats performing a sequential choice task exhibit both reinforcer-seeking behavior (left) as well as repetition of recently chosen actions (middle), as has been observed in other species. Reinforcement and choice sensitivity are shown as a function of trial lag for one example rat (Example taken from Miller et al., in prep.). **Right:** To compare the ability of our model and a MB/MF agent to capture key tendencies in these data, we show total reinforcement and choice sensitivity (summing over trial lags shown in left/middle panels) for these rats (green; mean and standard deviation) as well as for simulated model-based/perseverative agents and model-based/model-free agents. Overall the rats exhibit similar choice and reinforcement sensitivity on average. Our model is able to capture this with a relatively limited parameter range (blue scatter; see Methods); across a much broader parameter range, however, we find that MB/MF agents are unable to generate this same pattern of behavior (red scatter).

Discussion

Habits are classically thought of as simple, value-free, associations between a situation and the actions most commonly performed there (Dickinson, 1985; Hull, 1943; Wood & Neal, 2007; Wood & Rünger, 2016). Despite this legacy, popular computational models of habits hold that they are implemented by value-based mechanisms, learning the expected future reward associated with each action in each situation (Daw et al., 2005; Dolan & Dayan, 2013; Keramati, Dezfouli, & Piray, 2011; S. W. Lee, Shimojo, & O'Doherty, 2014). Here, we have shown computationally that such value-based mechanisms are not strictly necessary, and that a value-free mechanism can account for the major behavioral phenomena that define habits.

We have constructed a computational model in which habits consist of value-free associations between stimuli and actions, and in which these associations are strengthened each time that action is performed in response to that stimulus. This model reproduces key features of the behavioral literature on habits. The first of these features is that habits form slowly over time and depend on behaviors that are initially taken under goal-directed control. In situations where goal-directed control consistently produces the same behavior in response to the same stimulus, that behavior is likely to become a habit. Once a habit has formed, behavior can become inflexible in the face of changes to the environment that render it no longer desirable, such as contingency omission (in which the reinforcer that drove initial acquisition of the

behavior is delivered only when the behavior is *not* performed) and outcome devaluation (in which the reinforcer is rendered no longer valuable to the subject). When combined with another classic idea from the literature on habits – the idea that large action-outcome contingencies delay habit formation – our model is able to explain another classic finding in the literature on habitual control: the effect of reinforcement schedule on the rate of habit formation. Additionally, the proposal that value-free stimulus-response associations exist in the brain explains the ubiquitous observation that human and animal subjects show reinforcer-independent perseverative behaviors in a wide variety of tasks.

This computational account in which habits are understood as value-free stimulus response associations therefore provides a closer match to classic psychological theories of habits, an account for classic behavioral data on habit formation, and a novel framework for understanding additional behavioral phenomena. As we will describe in the next section, such a mechanism is also more consistent with findings on the neural basis for habitual behavior, and would in turn help to resolve tensions that have emerged in interpreting those findings through the lens of model-free RL.

Tensions in Neuroscientific Data

Separable Neural Substrates for Habits vs. Goal-directed Control

The idea that separate goal-directed and habitual controllers exist in the brain, supported by distinct neural circuits, is strongly supported by lesion data from both humans and other animals. In particular, goal-directed behavior can be disturbed by perturbations to any of a network of interconnected brain regions, including prelimbic cortex (PL; Balleine & Dickinson, 1998; Corbit & Balleine, 2003; Killcross & Coutureau, 2003), dorsomedial striatum (DMS; Yin et al., 2005), mediodorsal thalamus (Corbit, Muir, & Balleine, 2003), basolateral amygdala (Balleine, Killcross, & Dickinson, 2003), and orbitofrontal cortex (Jones et al., 2012; Miller, Botvinick, & Brody, in press; OFC; McDannald, Lucantonio, Burke, Niv, & Schoenbaum, 2011). Habitual behavior, on the other hand, can be disturbed by perturbations to infralimbic cortex (Coutureau & Killcross, 2003) as well as the dorsolateral striatum (DLS; Yin et al., 2004, 2006). In human subjects, comparable data are more sparse, but impaired goal-directed behavior has been found in subjects with lesions to ventromedial prefrontal cortex (vmPFC), a candidate homolog of rodent OFC (Reber et al., 2017), as well as following perturbations to dorsolateral prefrontal cortex (dlPFC), a possible homolog of PL (Smittenaar, FitzGerald, Romei, Wright, & Dolan, 2013).

Further support for this idea comes from data measuring neural activity. In rodents, goal-directed behavior results in greater activity in OFC and DMS, while habitual behavior results in greater activity in DLS (Gremel & Costa, 2013). In human subjects, goal-directed value signals during outcome devaluation have been identified in vmPFC (Valentin, Dickinson, & O'Doherty, 2007), and similar signals during contingency degradation have been identified both in vmPFC and in the caudate nucleus, a homolog of DMS (Tanaka, Balleine, & O'Doherty, 2008). Activity in the putamen, a homologue of rodent DLS, has been found to track the behavioral development of habits (Tricomi, Balleine, & O'Doherty, 2009).

In sum, considerable evidence supports the idea that anatomically separate goal-directed and habitual controllers exist in the brain, and that either can be responsible for a given action. Work in rodents points to a number of structures that are necessary for the operation of each of these systems, while work using human subjects, though limited, suggests that the prefrontal and striatal components (at least) are preserved across species (Balleine & O'Doherty, 2010; Liljeholm & O'Doherty, 2012).

No Clear Separation for Model-Free vs. Model-Based Control

In contrast to the literature on the habitual/goal-directed dichotomy, such clean dissociations have largely evaded investigations into the neural substrates of model-based and model-free computations, which can theoretically be differentiated in several ways (Doll et al., 2012). The first of these is based on a neuron's response to an action's outcome: whereas activity in model-free circuits should only reflect actual reinforcement received (or omitted) and/or the degree to which this deviates from similarly constrained expectations (e.g., temporal difference-based prediction error), activity in model-based circuits should (also) reflect hypothetical (cf. counterfactual/fictive) outcomes that could have been obtained, and should reflect prediction errors based on a richer set of expectations that incorporates, for instance, information about state transition probabilities.

In both of these cases, researchers have been unable to identify circuits that carry uniquely model-based value signals (Bornstein & Daw, 2011; Doll et al., 2012; D. Lee, Seo, & Jung, 2012; Shohamy, 2011). Rather, regions that respond to hypothetical outcomes (a model-based construct) – such as the OFC, vmPFC, and dorsal ACC – tend also to respond to

actual outcomes (Abe, Seo, & Lee, 2011; Camille et al., 2004; Coricelli et al., 2005; Hayden, Pearson, & Platt, 2011; Lohrenz, McCabe, Camerer, & Montague, 2007; Rushworth, Noonan, Boorman, Walton, & Behrens, 2011; Strait, Blanchard, & Hayden, 2014). Regions that respond to model-free prediction errors and/or model-free representations of expected value – such as ventral striatum, vmPFC, and even dopaminergic midbrain – also respond to their model-based analogs (Bromberg-Martin, Matsumoto, Hong, & Hikosaka, 2010; Daw, Gershman, Seymour, Dayan, & Dolan, 2011; Kishida et al., 2016; Wimmer, Daw, & Shohamy, 2012). Moreover, ventral striatum also displays signatures of value "preplay" or the covert expectation of reward (Redish, 2016; van der Meer & Redish, 2009), reflective of a classically model-based computation that has been observed in the hippocampus as well. While there are a few notable exceptions to the neuroimaging patterns above – studies that implicate separate regions of striatum in model-free versus model-based valuation (S. W. Lee et al., 2014; Wunderlich, Dayan, & Dolan, 2012) –these studies have not explicitly teased apart model-free valuation from forms of perseveration, leaving open the possibility that model-free value signals in those studies served as proxies for value-free signals of habit strength.

Historically, some of the strongest support for the idea of uniquely model-free computations in the brain has come from studies showing that activity in midbrain dopamine neurons exhibits key characteristics of a computational signal which plays a key role in many model-free learning algorithms: the temporal difference reward prediction error (Schultz, Dayan, & Montague, 1997). More recent data, however, suggest that dopamine neurons likely carry model-based information as well. In a reversal learning task, these neurons carry information consistent with model-based inference (Bromberg-Martin et al., 2010), while dopamine release in human subjects encodes information about both real and counterfactual reinforcement (Kishida et al., 2016). Perhaps most tellingly, dopamine neurons in a sensory preconditioning task encode prediction errors indicative of knowledge only a model-based system is expected to have (Sadacca, Jones, & Schoenbaum, 2016). Patients with Parkinson's Disease, in which dopamine neurons die in large numbers, show both impaired model-based behavior (Sharp, Foerde, Daw, & Shohamy, 2015) and increased perseveration (Rutledge et al., 2009), both of which are mitigated by dopamine-restoring drugs. These data indicate that dopamine neurons are unlikely to play a role in a uniquely model-free control system, but instead have access to model-based information and play a role in model-based control.

Collectively, these findings are at odds with the idea that the brain contains separable model-based and model-free systems. Instead, they suggest that to the extent that model-free computations exist in the brain, they are intimately integrated with model-based control, consistent with some existing computational models (Gershman, Markman, & Otto, 2014; Johnson & Redish, 2005; Pezzulo, van der Meer, Lansink, & Pennartz, 2014; Silver, Sutton, & Müller, 2008; Sutton, 1990). This lack of clear dissociation between model-based and model-free computations stands in stark contrast to the dissociations (described above) between circuits for goal-directed and for habitual control. This casts doubt on the idea that a one-to-one mapping exists between these two dichotomies, and motivates the search for alternative accounts.

A Proposed Realignment

To overcome the obstacles just described, we propose a revised framework with two key alterations: a divorce and a union. We first propose severing the tie between habits and model-free RL, and instead defining a category of behaviors that are "value-free" and therefore distinct from either type of RL computation. These behaviors would consist of S-R associations whose strengths are modified primarily through repetition, consistent with Thorndike's Law of Exercise and some more contemporary notions of habit learning (Wood & Rünger, 2016). They would be value-free in the sense that such a behavior could be fully described from the triggering of the stimulus to the emission of a response without requiring the representation of expected reinforcement along the way. Being value-free, however, would not entirely prevent these behaviors from being sensitive to one's surroundings. S-R associations can be learned in a fashion such that their likelihood of being triggered is influenced by the spatial, temporal, and motivational contexts. Moreover, and perhaps counterintuitively, being value-free would by no means prevent S-R associations from being *value-sensitive*. In particular, while the mechanism for S-R learning might be through repetition, the strength of the resulting association might be influenced by the value of the action being repeated. That is, the behavior that becomes habitual may initially be performed, and gradually strengthened, while in the pursuit of value under the goal-directed controller, but once a habit has formed, behavior is no longer driven by value (Tricomi et al., 2009; Wood & Rünger, 2016).

Our second proposal is to re-unify model-free and model-based computations as being two different drivers of goal-directed (i.e., value-based) behavior, distinct from the class of value-free behaviors just described. Rather than

viewing these two computations as categorically distinct, we further suggest that it may be more appropriate to view them as falling along a continuum, varying according to the amount of information used to make decisions. On this view, the available information would range from recent rewards, through simple relationships between stimuli, up to a full world model of all possible states. All of these computations are goal-directed, but their informational content directs them toward different goals. This latter proposal carries an additional benefit in that it obviates the need to cache value in a "common currency" (i.e., without reference to a specific outcome like juice or food type). Storage of such a common currency signal is typically required for model-free RL, but evidence for such signals in the brain remains weak (Morrison & Nicola, 2014; O'Doherty, 2014; Schoenbaum, Takahashi, Liu, & McDannald, 2011). This realignment therefore offers the possibility of bypassing model-free RL computations entirely, but our current model is agnostic as to whether such a drastic revision is appropriate based on the available evidence.

Relationship to Previous Models

A large and influential body of computational work is built on the assumption that habitual control arises from model-free reinforcement learning algorithms (Dolan & Dayan, 2013; O'Doherty, Lee, & McNamee, 2015). This work originates from a proposal by Daw and colleagues (Daw et al., 2005) that the parallel goal-directed and habitual controllers described by animal learning theory can be understood computationally as model-based and model-free reinforcement learning agents, operating in parallel and competing with one another for control of behavior. Subsequent work in this line has proposed different mechanisms for this competition (Keramati et al., 2011), or suggested ways in which model-based and model-free controllers might cooperate rather than compete (Keramati, Smittenaar, Dolan, & Dayan, 2016; S. W. Lee et al., 2014), but has retained the basic premise that habits are instantiated by model-free RL mechanisms and that habitization can be understood as a process by which these mechanisms come to dominate model-based mechanisms for the control of behavior.

This view of habitization is most successful at explaining the inflexibility of habits in the face of outcome devaluation: because model-free mechanisms associate actions with common-currency values only, rather than particular outcomes, they are unable to respond flexibly when a particular outcome is no longer desired. This view is in tension, however, with the inflexibility of habits in the face of contingency omission: learning that an action which previously led to reinforcement now instead prevents reinforcement should be well within the capabilities of a model-free system. The only

resolution to this tension that we are aware of requires invoking an additional habitization mechanism: a slow decrease in the learning rate of the model-free system when faced with stable environments (Dayan, Kakade, & Montague, 2000). Our proposal avoids this tension entirely by positing that habits are instantiated not by model-free RL, but by mechanisms that are entirely value-free. It therefore explains the inflexibility of habitual behavior in the face of both devaluation and omission using only one mechanism: the handoff of control from a value-based to a value-free system.

In a similar vein to the current proposal, Dezfouli and Balleine (2012) developed a model of habits that dropped the mapping between habits and model-free reinforcement learning. Instead, they proposed that habits should be modeled as learned action sequences ("chunks"). In contrast to our model, however, those action sequences are initiated under (outcome-sensitive) goal-directed control, after which they proceed in an outcome-insensitive manner until the sequence is completed. A particular sequence of actions can be executed more quickly when selected as a chunk than when each action is selected individually in series, and this strategy is preferred when the benefit of speeded responses outweighs the cost of such temporarily open-loop control. In contrast, the model of habits we are proposing completely cuts the tie between reinforcement learning and the habitual controller. Actions become habitized merely from use in a particular state, independent of any costs or benefits. This view provides an alternative explanation for the observation of habitized action sequences: when actions are typically performed in a particular order, the proprioceptive or other feedback associated with each action can become the "stimulus" that directly cues the subsequent action in the sequence (see James, 1890, chapter 4). Exploring this idea using using computational RL algorithms would involve building environments in which information about previous action is incorporated into the state space. Constructing such models, and designing experiments to dissociate them from the Dezfouli and Balleine account, is a promising direction for research into habit formation. Such experiments might involve interposing additional instructed actions into traditional sequential behavior assays of habit formation.

Many formalizations of the standard mapping from habits/goals to model-free/model-based reinforcement learning also include a perseveration kernel (e.g. Daw et al., 2011; Lau & Glimcher, 2005). That is, in addition to the two types of value learning, subsequent choice is also influenced by the most recent choice. Similar Hebbian strengthening components also appear in models of working memory (O'Reilly & Frank, 2006) and categorization learning (Ashby, Ennis, & Spiering, 2007). A similar tendency to repeat actions appears due to predictive coding in the free energy framework, whereby

actions are repeated for maximal predictability (Pezzulo, Rigoli, & Friston, 2015). This extra piece of computational machinery allows the models to account for the tendency to repeat choices, independent of values. Here, we bring this perseveration kernel to the foreground. Our proposed framework re-maps habits to the perseveration kernel and provides an account of how that kernel might plausibly operate in tandem with a goal-directed controller so as to account for behaviors that have previously been described by RL models. In effect, we are showing that the model-free component of some of these previous formalizations might not be necessary, and that a variation on this perseveration kernel actually serves as a better model of habits.

In our model, control of behavior is allocated on each trial to either the habitual or the goal-directed system by an arbiter. This arbiter is similar to mechanisms found in computational accounts mapping habitual/goal-directed control onto model-free/model-based reinforcement learning. In the initial formalization of this idea (Daw et al., 2005), each system determined the uncertainty in its value estimates, and the arbiter selected the system with less overall uncertainty. The extra computational complexity associated with the goal-directed system was a source of uncertainty, leading the arbiter to favor the habitual system in well-learned environments. Subsequent accounts have developed arbiters that consider proxies for this uncertainty (S. W. Lee et al., 2014), or other possible advantages of habitual over goal-directed control, such as response time (Keramati et al., 2011). The arbiter in our model is motivated by a classic observation in research on habits: habits are promoted in situations where the contingencies between actions and outcomes are weak (Dickinson, 1985). Future research should explore the conditions under which these arbiters make similar or diverging predictions for habitual control, and systematically test the relative success of these arbitration approaches at accounting for empirical data under those conditions.

Implications

The realignment we are proposing carries important implications and testable predictions for future work. First and foremost, our account predicts that neural circuits associated with habitual behavior (e.g., DLS) should also be related to (value-free) perseveration. We might therefore expect greater activity in this circuit with additional repetitions of a previous action, and that lesioning parts of this circuit will reduce the tendency to perseverate. Secondly, we predict that elicitation of action repetition (in the absence of reinforcement) should be sufficient to construct new habits. For instance,

generating actions with microstimulation in a particular context may facilitate the subsequent performance of those actions in that same context. Such evidence would provide strong support for our model. This prediction also provides a mechanistic underpinning for the repetition strategies that have shown to be effective at improving workplace and health-related performance through habit formation (Gardner, Lally, & Wardle, 2012; Lally et al., 2010; Wood & Rünger, 2016). Related to both of these claims, our model suggests that disorders of habitual behavior (e.g., Obsessive-Compulsive Disorder, Tic Disorders) need not result from dysfunction in valuation. Our model can help to tease apart the degree to which value-free versus value-based processes are implicated in each of these disorders, and this will have important implications for considerations of etiology and treatment.

Our model makes additional but weaker predictions with respect to the relationship between model-free and model-based processes. If these represent related manifestations of a common value-based system, we expect brain regions that reflect model-free value signals to also reflect model-based value signals, as has been the case in many previous studies (Abe et al., 2011; Bornstein & Daw, 2011; Doll et al., 2012; D. Lee et al., 2012; Shohamy, 2011).

For instance, model-free prediction errors should not be found in regions that fail to exhibit model-based prediction errors. Related to this, one should not be able to lesion part of the model-free valuation circuit without influencing model-based behavior. To the extent that model-based forms of decision-making draw on additional mechanisms, including hippocampally-mediated stimulus-stimulus associations (Bornstein & Daw, 2013; Bunsey & Eichenbaum, 1996; Dusek & Eichenbaum, 1997) and prefrontal control mechanisms (E. K. Miller & Cohen, 2001), the reverse need not be true; we would predict that inactivating (K. J. Miller, Botvinick, & Brody, 2017; Smittenaar et al., 2013) or otherwise drawing resources away from (Otto, Gershman, Markman, & Daw, 2013; Otto, Skatova, Madlon-Kay, & Daw, 2015) such additional mechanisms would selectively impair model-based behavior, as has been observed. Thus, our model accommodates data that fails to identify a model-free learning component in behavior and/or neural activity, while also accommodating a growing literature demonstrating factors that selectively engender or inhibit model-based control.

Importantly, the value-free mechanisms we have proposed for habits by no means preclude a role for value or motivational state (e.g., hunger or satiety) in habit learning. These may modulate the strengthening of habit associations either directly (e.g., through a feedback mechanism that influences the S-R association) or indirectly (e.g., by influencing

the vigor of an action, which in turn results in greater associative strengths). The particular form of such a mechanism that best accounts for available data is a matter of further research, and one which we aim to pursue in extending our model.

Conclusions

We have provided evidence that a value-free learning process -- according to which S-R associations are strengthened through action repetition in a Hebbian-like manner -- may be sufficient to generate behaviors that have been traditionally classified as habits, and held up in contrast to goal-directed behaviors. We demonstrate that such a mechanism will lead to perseveration on a previously higher-value action following contingency degradation or outcome devaluation. It will also create perseverative choice kernels in a probabilistic choice task with varying action-outcome contingencies. We further show that such habitual behaviors are diminished by simulating lesions to a habitual system, consistent with classic findings in the animal behavior literature. Crucially, the system that generates these habitual behaviors does so without engaging in any manner of reinforcement learning (model-free or otherwise), underscoring the possibility that habits need not be equated with model-free RL.

In spite of the absence of a model-free controller, we also show that our model can still capture key features of behavior for a task that is thought to rely on both model-free and model-based control, bringing into sharper focus recurring questions about whether and/or when a purely model-free controller is necessary to explain these behaviors. Collectively, we argue that these findings support a realignment of current decision-making frameworks, towards (re-)associating goal-directed/habitual with value-based/value-free rather than model-based/model-free. Beyond providing a potentially more parsimonious account of previous behavioral results, such a realignment may offer a better account of extant neural findings, including the fact that structures associated with model-free and model-based computations (i.e., value-based computations) tend to overlap, whereas lesion/inactivation studies have revealed clear dissociations between structures associated with goal-directed behavior versus (potentially value-free) habits.

Acknowledgements

We would like to thank Nathaniel Daw, Yael Niv, Matthew Botvinick, Jonathan Cohen, and Sebastiaan van Opheusden for helpful discussions.

References

Abe, H., Seo, H., & Lee, D. (2011). The prefrontal cortex and hybrid learning during iterative competitive games. *Annals of the New York Academy of Sciences*, *1239*, 100–108.

Adams, C. D. (1982). Variations in the sensitivity of instrumental responding to reinforcer devaluation. *The Quarterly Journal of Experimental Psychology Section B*, *34*(2), 77–98.

Adams, C. D., & Dickinson, A. (1981). Instrumental responding following reinforcer devaluation. *The Quarterly Journal of Experimental Psychology Section B*, *33*(2), 109–121.

Akaishi, R., Umeda, K., Nagase, A., & Sakai, K. (2014). Autonomous mechanism of internal choice estimate underlies decision inertia. *Neuron*, *81*(1), 195–206.

Ashby, F. G., Ennis, J. M., & Spiering, B. J. (2007). A neurobiological theory of automaticity in perceptual categorization. *Psychological Review*, *114*(3), 632–656.

Balleine, B. W., & Dickinson, A. (1998). Goal-directed instrumental action: contingency and incentive learning and their cortical substrates. *Neuropharmacology*, *37*(4-5), 407–419.

Balleine, B. W., Killcross, A. S., & Dickinson, A. (2003). The effect of lesions of the basolateral amygdala on instrumental conditioning. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *23*(2), 666–675.

Balleine, B. W., & O'Doherty, J. P. (2010). Human and rodent homologies in action control: corticostriatal determinants of goal-directed and habitual action. *Neuropsychopharmacology: Official Publication of the American College of Neuropsychopharmacology*, *35*(1), 48–69.

Bertelson, P. (1965). Serial choice reaction-time as a function of response versus signal-and-response repetition. *Nature*, *206*(980), 217–218.

Bornstein, A. M., & Daw, N. D. (2011). Multiplicity of control in the basal ganglia: computational roles of striatal subregions. *Current Opinion in Neurobiology*, *21*(3), 374–380.

Bornstein, A. M., & Daw, N. D. (2013). Cortical and hippocampal correlates of deliberation during model-based decisions for rewards in humans. *PLoS Computational Biology*, *9*(12), e1003387.

Bromberg-Martin, E. S., Matsumoto, M., Hong, S., & Hikosaka, O. (2010). A pallidus-habenula-dopamine pathway

signals inferred stimulus values. *Journal of Neurophysiology*, *104*(2), 1068–1076.

Buckholtz, J. W. (2015). Social norms, self-control, and the value of antisocial behavior. *Current Opinion in Behavioral Sciences*, *3*, 122–129.

Bunsey, M., & Eichenbaum, H. (1996). Conservation of hippocampal memory function in rats and humans. *Nature*, *379*(6562), 255–257.

Camille, N., Coricelli, G., Sallet, J., Pradat-Diehl, P., Duhamel, J.-R., & Sirigu, A. (2004). The Involvement of the Orbitofrontal Cortex in the Experience of Regret. *Science*, *304*(5674), 1167–1170.

Cho, R. Y., Nystrom, L. E., Brown, E. T., Jones, A. D., Braver, T. S., Holmes, P. J., & Cohen, J. D. (2002). Mechanisms underlying dependencies of performance on stimulus history in a two-alternative forced-choice task. *Cognitive, Affective & Behavioral Neuroscience*, *2*(4), 283–299.

Corbit, L. H., & Balleine, B. W. (2003). The role of prelimbic cortex in instrumental conditioning. *Behavioural Brain Research*, *146*(1-2), 145–157.

Corbit, L. H., Muir, J. L., & Balleine, B. W. (2003). Lesions of mediodorsal thalamus and anterior thalamic nuclei produce dissociable effects on instrumental conditioning in rats. *The European Journal of Neuroscience*, *18*(5), 1286–1294.

Coricelli, G., Critchley, H. D., Joffily, M., O'Doherty, J. P., Sirigu, A., & Dolan, R. J. (2005). Regret and its avoidance: a neuroimaging study of choice behavior. *Nature Neuroscience*, *8*(9), 1255–1262.

Coutureau, E., & Killcross, S. (2003). Inactivation of the infralimbic prefrontal cortex reinstates goal-directed responding in overtrained rats. *Behavioural Brain Research*, *146*(1-2), 167–174.

Crockett, M. J. (2013). Models of morality. *Trends in Cognitive Sciences*, *17*(8), 363–366.

Cushman, F. (2013). Action, outcome, and value: a dual-system framework for morality. *Personality and Social Psychology Review: An Official Journal of the Society for Personality and Social Psychology, Inc*, *17*(3), 273–292.

Daw, N. D., Gershman, S. J., Seymour, B., Dayan, P., & Dolan, R. J. (2011). Model-based influences on humans' choices and striatal prediction errors. *Neuron*, *69*(6), 1204–1215.

Daw, N. D., Niv, Y., & Dayan, P. (2005). Uncertainty-based competition between prefrontal and dorsolateral striatal systems for behavioral control. *Nature Neuroscience*, *8*(12), 1704–1711.

Dayan, P., Kakade, S., & Montague, P. R. (2000). Learning and selective attention. *Nature Neuroscience*, *3 Suppl*,

1218–1223.

Derusso, A. L., Fan, D., Gupta, J., Shelest, O., Costa, R. M., & Yin, H. H. (2010). Instrumental uncertainty as a

determinant of behavior under interval schedules of reinforcement. *Frontiers in Integrative Neuroscience*, *4*.

https://doi.org/10.3389/fnint.2010.00017

Dezfouli, A., & Balleine, B. W. (2012). Habits, action sequences and reinforcement learning. *The European Journal of*

Neuroscience, *35*(7), 1036–1051.

Dickinson, A. (1985). Actions and Habits: The Development of Behavioural Autonomy. *Philosophical Transactions of*

the Royal Society of London. Series B, Biological Sciences, *308*(1135), 67–78.

Dickinson, A. (1998). Omission Learning after Instrumental Pretraining. *The Quarterly Journal of Experimental*

Psychology Section B, *51*(3), 271–286.

Dickinson, A., Nicholas, D. J., & Adams, C. D. (1983). The effect of the instrumental training contingency on

susceptibility to reinforcer devaluation. *The Quarterly Journal of Experimental Psychology Section B*, *35*(1), 35–51.

Dolan, R. J., & Dayan, P. (2013). Goals and habits in the brain. *Neuron*, *80*(2), 312–325.

Doll, B. B., Simon, D. A., & Daw, N. D. (2012). The ubiquity of model-based reinforcement learning. *Current Opinion in*

Neurobiology, *22*(6), 1075–1081.

Dusek, J. A., & Eichenbaum, H. (1997). The hippocampus and memory for orderly stimulus relations. *Proceedings of the*

National Academy of Sciences of the United States of America, *94*(13), 7109–7114.

Gardner, B., Lally, P., & Wardle, J. (2012). Making health habitual: the psychology of "habit-formation"and general

practice. *The British Journal of General Practice: The Journal of the Royal College of General Practitioners*,

62(605), 664–666.

Gershman, S. J., Markman, A. B., & Otto, A. R. (2014). Retrospective revaluation in sequential decision making: a tale of

two systems. *Journal of Experimental Psychology. General*, *143*(1), 182–194.

Gillan, C. M., Kosinski, M., Whelan, R., Phelps, E. A., & Daw, N. D. (2016). Characterizing a psychiatric symptom

dimension related to deficits in goal-directed control. *eLife*, *5*. https://doi.org/10.7554/eLife.11305

Gillan, C. M., Otto, A. R., Phelps, E. A., & Daw, N. D. (2015). Model-based learning protects against forming habits.

Cognitive, Affective & Behavioral Neuroscience, *15*(3), 523–536.

Gold, J. I., Law, C.-T., Connolly, P., & Bennur, S. (2008). The relative influences of priors and sensory evidence on an

oculomotor decision variable during perceptual learning. *Journal of Neurophysiology*, *100*(5), 2653–2668.

Gore, J. L., Dorris, M. C., & Munoz, D. P. (2002). Time course of a repetition effect on saccadic reaction time in non-human primates. *Archives Italiennes de Biologie*, *140*(3), 203–210.

Graybiel, A. M. (2008). Habits, Rituals, and the Evaluative Brain. *Annual Review of Neuroscience*, *31*(1), 359–387.

Gremel, C. M., & Costa, R. M. (2013). Orbitofrontal and striatal circuits dynamically encode the shift between goal-directed and habitual actions. *Nature Communications*, *4*, 2264.

Hammond, L. J. (1980). The effect of contingency upon the appetitive conditioning of free-operant behavior. *Journal of the Experimental Analysis of Behavior*, *34*(3), 297–304.

Hayden, B. Y., Pearson, J. M., & Platt, M. L. (2011). Neuronal basis of sequential foraging decisions in a patchy environment. *Nature Neuroscience*, *14*(7), 933–939.

Hull, C. L. (1943). Principles of behavior: an introduction to behavior theory. Retrieved from http://doi.apa.org/psycinfo/1944-00022-000

Ito, M., & Doya, K. (2009). Validation of Decision-Making Models and Analysis of Decision Variables in the Rat Basal Ganglia. *Journal of Neuroscience*, *29*(31), 9861–9874.

James, W. (1890). *The principles of psychology*. NY, US: Henry Holt and Company.

Johnson, A., & Redish, A. D. (2005). Hippocampal replay contributes to within session learning in a temporal difference reinforcement learning model. *Neural Networks: The Official Journal of the International Neural Network Society*, *18*(9), 1163–1171.

Jones, J. L., Esber, G. R., McDannald, M. A., Gruber, A. J., Hernandez, A., Mirenzi, A., & Schoenbaum, G. (2012). Orbitofrontal cortex supports behavior and learning using inferred but not cached values. *Science*, *338*(6109), 953–956.

Keramati, M., Dezfouli, A., & Piray, P. (2011). Speed/accuracy trade-off between the habitual and the goal-directed processes. *PLoS Computational Biology*, *7*(5), e1002055.

Keramati, M., Smittenaar, P., Dolan, R. J., & Dayan, P. (2016). Adaptive integration of habits into depth-limited planning defines a habitual-goal-directed spectrum. *Proceedings of the National Academy of Sciences of the United States of America*. https://doi.org/10.1073/pnas.1609094113

Killcross, S., & Coutureau, E. (2003). Coordination of actions and habits in the medial prefrontal cortex of rats. *Cerebral*

Cortex , *13*(4), 400–408.

Kim, H., Sul, J. H., Huh, N., Lee, D., & Jung, M. W. (2009). Role of striatum in updating values of chosen actions. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *29*(47), 14701–14712.

Kishida, K. T., Saez, I., Lohrenz, T., Witcher, M. R., Laxton, A. W., Tatter, S. B., … Montague, P. R. (2016). Subsecond dopamine fluctuations in human striatum encode superposed error signals about actual and counterfactual reward. *Proceedings of the National Academy of Sciences*, *113*(1), 200–205.

Kurth-Nelson, Z., Bickel, W., & Redish, A. D. (2012). A theoretical account of cognitive effects in delay discounting. *The European Journal of Neuroscience*, *35*(7), 1052–1064.

Lally, P., van Jaarsveld, C. H. M., Potts, H. W. W., & Wardle, J. (2010). How are habits formed: Modelling habit formation in the real world. *European Journal of Social Psychology*, *40*(6), 998–1009.

Lau, B., & Glimcher, P. W. (2005). Dynamic response-by-response models of matching behavior in rhesus monkeys. *Journal of the Experimental Analysis of Behavior*, *84*(3), 555–579.

Lee, D., McGreevy, B. P., & Barraclough, D. J. (2005). Learning and decision making in monkeys during a rock–paper–scissors game. *Cognitive Brain Research*, *25*(2), 416–430.

Lee, D., Seo, H., & Jung, M. W. (2012). Neural basis of reinforcement learning and decision making. *Annual Review of Neuroscience*, *35*, 287–308.

Lee, S. W., Shimojo, S., & O'Doherty, J. P. (2014). Neural computations underlying arbitration between model-based and model-free learning. *Neuron*, *81*(3), 687–699.

Liljeholm, M., & O'Doherty, J. P. (2012). Contributions of the striatum to learning, motivation, and performance: an associative account. *Trends in Cognitive Sciences*, *16*(9), 467–475.

Lohrenz, T., McCabe, K., Camerer, C. F., & Montague, P. R. (2007). Neural signature of fictive learning signals in a sequential investment task. *Proceedings of the National Academy of Sciences of the United States of America*, *104*(22), 9493–9498.

Lucantonio, F., Caprioli, D., & Schoenbaum, G. (2014). Transition from "model-based" to "model-free" behavioral control in addiction: Involvement of the orbitofrontal cortex and dorsolateral striatum. *Neuropharmacology*, *76 Pt B*, 407–415.

McDannald, M. A., Lucantonio, F., Burke, K. A., Niv, Y., & Schoenbaum, G. (2011). Ventral striatum and orbitofrontal

cortex are both required for model-based, but not model-free, reinforcement learning. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *31*(7), 2700–2705.

Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annual Review of Neuroscience*, *24*, 167–202.

Miller, K. J., Botvinick, M. M., & Brody, C. D. (2017). Dorsal hippocampus plays a causal role in model-based planning. *bioRxiv*. Retrieved from http://biorxiv.org/content/early/2017/05/30/096594.abstract

Morrison, S. E., & Nicola, S. M. (2014). Neurons in the nucleus accumbens promote selection bias for nearer objects. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *34*(42), 14147–14162.

O'Doherty, J. P. (2014). The problem with value. *Neuroscience and Biobehavioral Reviews*, *43*, 259–268.

O'Doherty, J. P., Lee, S. W., & McNamee, D. (2015). The structure of reinforcement-learning mechanisms in the human brain. *Current Opinion in Behavioral Sciences*, *1*, 94–100.

O'Reilly, R. C., & Frank, M. J. (2006). Making working memory work: a computational model of learning in the prefrontal cortex and basal ganglia. *Neural Computation*, *18*(2), 283–328.

Otto, A. R., Gershman, S. J., Markman, A. B., & Daw, N. D. (2013). The Curse of Planning: Dissecting Multiple Reinforcement-Learning Systems by Taxing the Central Executive. *Psychological Science*, *24*(5), 751–761.

Otto, A. R., Skatova, A., Madlon-Kay, S., & Daw, N. D. (2015). Cognitive control predicts use of model-based reinforcement learning. *Journal of Cognitive Neuroscience*, *27*(2), 319–333.

Pezzulo, G., Rigoli, F., & Friston, K. (2015). Active Inference, homeostatic regulation and adaptive behavioural control. *Progress in Neurobiology*, *134*, 17–35.

Pezzulo, G., van der Meer, M. A. A., Lansink, C. S., & Pennartz, C. M. A. (2014). Internally generated sequences in learning and executing goal-directed behavior. *Trends in Cognitive Sciences*, *18*(12), 647–657.

Rangel, A. (2013). Regulation of dietary choice by the decision-making circuitry. *Nature Neuroscience*, *16*(12), 1717–1724.

Reber, J., Feinstein, J. S., O'Doherty, J. P., Liljeholm, M., Adolphs, R., & Tranel, D. (2017). Selective impairment of goal-directed decision-making following lesions to the human ventromedial prefrontal cortex. *Brain: A Journal of Neurology*, *140*(6), 1743–1756.

Redish, A. D. (2016). Vicarious trial and error. *Nature Reviews. Neuroscience*, *17*(3), 147–159.

Redish, A. D., Jensen, S., Johnson, A., & Kurth-Nelson, Z. (2007). Reconciling reinforcement learning models with behavioral extinction and renewal: implications for addiction, relapse, and problem gambling. *Psychological Review*, *114*(3), 784–805.

Rushworth, M. F. S., Noonan, M. P., Boorman, E. D., Walton, M. E., & Behrens, T. E. (2011). Frontal cortex and reward-guided learning and decision-making. *Neuron*, *70*(6), 1054–1069.

Rutledge, R. B., Dean, M., Caplin, A., & Glimcher, P. W. (2010). Testing the reward prediction error hypothesis with an axiomatic model. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *30*(40), 13525–13536.

Rutledge, R. B., Lazzaro, S. C., Lau, B., Myers, C. E., Gluck, M. A., & Glimcher, P. W. (2009). Dopaminergic drugs modulate learning rates and perseveration in Parkinson's patients in a dynamic foraging task. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *29*(48), 15104–15114.

Sadacca, B. F., Jones, J. L., & Schoenbaum, G. (2016). Midbrain dopamine neurons compute inferred and cached value prediction errors in a common framework [Data set]. https://doi.org/10.7554/eLife.13665

Schoenbaum, G., Takahashi, Y., Liu, T.-L., & McDannald, M. A. (2011). Does the orbitofrontal cortex signal value? *Annals of the New York Academy of Sciences*, *1239*, 87–99.

Schultz, W., Dayan, P., & Montague, P. R. (1997). A neural substrate of prediction and reward. *Science*, *275*(5306), 1593–1599.

Scott, B. B., Constantinople, C. M., Erlich, J. C., Tank, D. W., & Brody, C. D. (2015). Sources of noise during accumulation of evidence in unrestrained and voluntarily head-restrained rats. *eLife*, *4*, e11308.

Sharp, M. E., Foerde, K., Daw, N. D., & Shohamy, D. (2015). Dopamine selectively remediates "model-based"reward learning: a computational approach. *Brain: A Journal of Neurology*, awv347.

Shohamy, D. (2011). Learning and motivation in the human striatum. *Current Opinion in Neurobiology*, *21*(3), 408–414.

Silver, D., Sutton, R. S., & Müller, M. (2008). Sample-based Learning and Search with Permanent and Transient Memories. In *Proceedings of the 25th International Conference on Machine Learning* (pp. 968–975). New York, NY, USA: ACM.

Smittenaar, P., FitzGerald, T. H. B., Romei, V., Wright, N. D., & Dolan, R. J. (2013). Disruption of dorsolateral prefrontal cortex decreases model-based in favor of model-free control in humans. *Neuron*, *80*(4), 914–919.

Strait, C. E., Blanchard, T. C., & Hayden, B. Y. (2014). Reward value comparison via mutual inhibition in ventromedial prefrontal cortex. *Neuron*, *82*(6), 1357–1366.

Sutton, R. S. (1990). Integrated architectures for learning, planning, and reacting based on approximating dynamic programming. In *Proceedings of the seventh international conference on machine learning* (pp. 216–224).

Sutton, R. S., & Barto, A. G. (1998). *Reinforcement learning: An introduction* (Vol. 1). MIT press Cambridge.

Tanaka, S. C., Balleine, B. W., & O'Doherty, J. P. (2008). Calculating consequences: brain systems that encode the causal effects of actions. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *28*(26), 6750–6755.

Thorndike, E. L. (1911). *Animal Intelligence: Experimental Studies*. Macmillan.

Tricomi, E., Balleine, B. W., & O'Doherty, J. P. (2009). A specific role for posterior dorsolateral striatum in human habit learning. *The European Journal of Neuroscience*, *29*(11), 2225–2232.

Valentin, V. V., Dickinson, A., & O'Doherty, J. P. (2007). Determining the Neural Substrates of Goal-Directed Learning in the Human Brain. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *27*(15), 4019–4026.

van der Meer, M. A. A., & Redish, A. D. (2009). Covert Expectation-of-Reward in Rat Ventral Striatum at Decision Points. *Frontiers in Integrative Neuroscience*, *3*, 1.

Wimmer, G. E., Daw, N. D., & Shohamy, D. (2012). Generalization of value in reinforcement learning by humans. *The European Journal of Neuroscience*, *35*(7), 1092–1104.

Wood, W., & Neal, D. T. (2007). A new look at habits and the habit-goal interface. *Psychological Review*, *114*(4), 843–863.

Wood, W., & Rünger, D. (2016). Psychology of Habit. *Annual Review of Psychology*, *67*, 289–314.

Wunderlich, K., Dayan, P., & Dolan, R. J. (2012). Mapping value based planning and extensively trained choice in the human brain. *Nature Neuroscience*, *15*(5), 786–791.

Yin, H. H., & Knowlton, B. J. (2006). The role of the basal ganglia in habit formation. *Nature Reviews. Neuroscience*, *7*(6), 464–476.

Yin, H. H., Knowlton, B. J., & Balleine, B. W. (2004). Lesions of dorsolateral striatum preserve outcome expectancy but disrupt habit formation in instrumental learning. *The European Journal of Neuroscience*, *19*(1), 181–189.

Yin, H. H., Knowlton, B. J., & Balleine, B. W. (2006). Inactivation of dorsolateral striatum enhances sensitivity to changes in the action–outcome contingency in instrumental conditioning. *Behavioural Brain Research*, *166*(2), 189–196.

Yin, H. H., Ostlund, S. B., Knowlton, B. J., & Balleine, B. W. (2005). The role of the dorsomedial striatum in instrumental conditioning. *The European Journal of Neuroscience*, *22*(2), 513–523.