1 **DIABLO: from multi-omics assays to biomarker discovery, an integrative approach**
2

3 Amrit Singh[1,2,3], Casey P. Shannon[3], Benoît Gautier[4], Florian Rohart[5], Michaël Vacher[6,9], Scott
4 J. Tebbutt[1,3,7], Kim-Anh Lê Cao[8]
5
[1]Centre for Heart Lung Innovation, St. Paul's Hospital, University of British Columbia,
Vancouver, BC, Canada;
[2]Department of Pathology and Laboratory Medicine, University of British Columbia, Vancouver,
BC, Canada;
[3]Prevention of Organ Failure (PROOF) Centre of Excellence, Vancouver, BC, Canada.
[4]The University of Queensland Diamantina Institute, Translational Research Institute,
Woolloongabba, QLD 4102, Australia
[5]Institute for Molecular Bioscience, The University of Queensland, St Lucia, QLD 4072,
Australia
[6]Australian Research Council Centre of Excellence in Plant Energy Biology, The University of
Western Australia, Crawley, Western Australia, Australia
[7]Department of Medicine (Respiratory Division), University of British Columbia, Vancouver,
BC, Canada.
[8]Melbourne Integrative Genomics, School of Mathematics and Statistics, The University of
Melbourne, Melbourne, Australia
[9]current address: Australian eHealth Research Centre, Commonwealth Scientific and Industrial
Research Organisation, Brisbane, Queensland, Australia
23
24
25
Corresponding author:
Dr Kim-Anh Lê Cao
Melbourne Integrative Genomics and School of Mathematics and Statistics, The University of
Melbourne, Melbourne, Australia
T: +61 (0)3834 43971
kimanh.lecao@unimelb.edu.au

Abstract

Systems biology approaches, leveraging multi-omics measurements, are needed to capture the

complexity of biological networks while identifying the key molecular drivers of disease

mechanisms. We present DIABLO, a novel integrative method to identify multi-omics

biomarker panels that can discriminate between multiple phenotypic groups. In the multi-omics

analyses of simulated and real-world datasets, DIABLO resulted in superior biological

enrichment compared to other integrative methods, and achieved comparable predictive

performance with existing multi-step classification schemes. DIABLO is a versatile approach

that will benefit a diverse range of research areas, where multiple high dimensional datasets are

available for the same set of specimens. DIABLO is implemented along with tools for model

selection, and validation, as well as graphical outputs to assist in the interpretation of these

integrative analyses (http://mixomics.org/).

Keywords: Systems biology, biomarkers, data integration, data visualization, asthma,

classification, breast cancer, multi-omics, network analysis

Background

Technological improvements have allowed for the collection of data from different molecular compartments (*e.g.*, gene expression, methylation status, protein abundance) resulting in multiple omics (multi-omics) data from the same set of biospecimens (*eg.*, transcriptomics, proteomics, metabolomics). The large number of omic variables compared to the limited number of available biological samples presents a computational challenge when identifying the key drivers of disease. Further, technological limitations differ with respect to different omic platforms (*e.g.*, sequencing *vs.* mass spectrometry), and biological effect sizes differ with respect to different omic variable-types (e.g., methylation status *vs.* protein expression). Effective integrative strategies are needed, to extract common biological information spanning multiple molecular compartments that explains phenotypic variation. Already, systems biology approaches which incorporated data from multiple biological compartments, have shown improved biological insights compared to traditional single omics analyses [1–3]. This may be because single omics analyses cannot account for the interactions between omic layers and, consequently, are unable to reconstruct accurate molecular networks. These molecular networks are dynamic, changing under perturbed conditions such as disease, response to therapy, and environmental exposures. Therefore, adopting a holistic approach by integrating multi-omics data may bridge this information gap, and uncover networks that are representative of the underlying molecular mechanisms [4,5].

Preliminary approaches to data integration included multi-step approaches that leveraged existing single-omics methods: multi-omics data were concatenated, or ensembles of single omics models created [6]. These approaches can be biased towards certain omics data types, however, and do not account for interactions between omic layers [7,8]. Recently, more

sophisticated integrative approaches have been proposed (**Supplementary Fig. 1**) [4,9–12].

They can be broadly divided into unsupervised analyses, which identify coherent relationships

across multi-omics datasets when samples are unlabeled, and supervised analyses, which identify

multi-omics patterns that discriminate between known phenotypic sample groups. However these

supervised strategies are unable to capture the shared information across multiple biological

domains when identifying the key molecular drivers associated with a phenotype. Such methods

are needed to capture the dynamic nature of molecular networks under various disease conditions

and ultimately provide robust biomarkers that are both biologically and clinically relevant.

To address these knowledge gaps, we introduce DIABLO, a method that incorporates

information across high dimensional multi-omics data while discriminating phenotypic groups.

DIABLO uncovers robust biomarkers of dysregulated disease processes that span multiple

functional layers. We demonstrate the capabilities and versatility of DIABLO both in simulated

and real-world data, integrating multi-omics datasets to identify relevant biomarkers of various

diseases. DIABLO is available through the mixOmics data integration toolkit

(www.mixomics.org [12]) which contains a wide range of multivariate methods for the

exploration and integration of high dimensional biological datasets.

Results

DIABLO (**D**ata **I**ntegration **A**nalysis for **B**iomarker discovery using **L**atent c**O**mponents)

maximizes the common or correlated information between multiple omics (multi-omics) datasets

while identifying the key omics variables (mRNA, miRNA, CpGs, proteins, metabolites, *etc.*)

and characterizing the disease sub-groups or phenotypes of interest. DIABLO uses Projection to

Latent Structure models (PLS) [13], and extends both sparse PLS-Discriminant Analysis [14] to

multi-omics analyses and sparse Generalized Canonical Correlation Analysis [15] to a

supervised analysis framework. In contrast to existing penalized matrix decomposition methods

[16], DIABLO is a component-based method (or a dimension reduction technique) that

transforms each omic dataset into latent components and maximizes the sum of pairwise

correlations between latent components (user-defined) and a phenotype of interest [17].

DIABLO is, therefore, an integrative classification method that builds predictive multi-omics

models that can be applied to multi-omics data from new samples to determine their phenotype.

Users can specify the number of variables to select from each dataset and visualize the omics

data and the multi-omics panel into a reduced data. The method is highly flexible in the type of

experimental design it can handle, ranging from classical single time point to cross-over and

repeated measures studies. Modular-based analysis can also be incorporated using pathway-

based module matrices [18] instead of the original omics matrices, as illustrated in one of our

case studies.

DIABLO selects correlated and discriminatory variables

Briefly, three omic datasets consisting of 200 samples (split equally over two groups) and 260

variables were generated by modifying the degree of correlation and discrimination, resulting in

four types of variables: 30 correlated-discriminatory (corDis) variables, 30 uncorrelated-

discriminatory (unCorDis) variables, 100 correlated-nondiscriminatory (corNonDis) variables,

and 100 uncorrelated-nondiscriminatory (unCorNonDis) variables (**Supplementary Note,**

Supplementary Fig. 2). Three integrative classification methods were applied to generate multi-

omic biomarkers panels of 90 variables each (30 variables from each omic dataset): a DIABLO

model with either a full design (where the correlation between all pairwise combinations of

datasets, as well as between each dataset and the phenotypic outcome, were maximised) or the

null design (where only the correlation between each dataset and the phenotypic outcome was

maximised, **see Methods**), a concatenation-based sPLSDA classifier which consists of naively

combining all datasets into one, and an ensemble of sPLSDA classifiers where a separate

sPLSDA classifier was fitted for each omics dataset and the consensus predictions were

combined using a majority vote scheme (see **Supplementary Fig. 3**). The purpose of the

simulation study was to compare DIABLO models with existing multi-step integrative classifiers

with respect to the error rate and types of variables selected as part of the multi-omic biomarker

panels. A secondary aim was to determine the effect of design matrix on the resulting multi-omic

biomarker panels identified using DIABLO.

The concatenation, ensemble and DIABLO_null classifiers performed similarly across

the various noise and fold-change thresholds. At lower noise levels (simulated using a

multivariate normal distribution with mean of zero and standard deviation of 0.2 or 0.5) the

DIABLO_full classifier had a slightly higher error rate compared to the other approaches (**Fig.**

1a), but consistently selected mostly correlated and discriminatory (corDis) variables, unlike the

other integrative classifiers (**Fig. 1b**). All methods behaved similarly with respect to the error

rate and types of variables selected at higher noise thresholds (simulated using a multivariate

normal distribution with mean of zero and standard deviation of 1 or 2). This simulation

highlights how the design (connection between datasets) affects the flexibility of the DIABLO

model, resulting in a trade-off between discrimination or correlation. DIABLO_null focused on

selecting discriminatory variables and disregarded most of the correlation between datasets (null

design), whereas DIABLO_full selected highly correlated variables across all datasets. Since the

variables selected by DIABLO_full reflect the correlation structure between biological

compartments, we hypothesized that they might provide a balance between prediction accuracy

and biological insight.

DIABLO identifies molecular networks with superior biological enrichment

To assess this, we turn to real biological datasets. We applied various integrative approaches to

cancer multi-omics datasets (mRNA, miRNA, and CpG) – colon, kidney, glioblastoma (gbm)

and lung – and identified multi-omics biomarker panels that were predictive of high and low

survival times (**Table 1**). We then compared the network properties and biological enrichment of

the selected features across approaches.

Multi-omics biomarker panels were developed using component-based integrative

approaches that also performed variable selection: supervised methods included concatenation

and ensemble schemes using the sPLSDA classifier [14], and DIABLO with either the null or

full design (DIABLO_null, and DIABLO_full); unsupervised approaches included sparse

generalized canonical correlation analysis [15] (sGCCA), Multi-Omics Factor Analysis

(MOFA), and Joint and Individual Variation Explained (JIVE) [23] (see **Supplementary Note**

for parameter settings). Both supervised and unsupervised approaches were considered in order

to compare and contrast the types of omics-variables selected, network properties and biological

enrichment results. A distinction was made between DIABLO models in which the correlation

between omics datasets was not maximized (DIABLO_null) and those when the correlation

between omics datasets was maximized (DIABLO_full).

Each multi-omics biomarker panel included 180 features (60 features of each omics type

across 2 components). Approaches generally identified distinct sets of features. **Fig. 2a** depicts

the distinct and shared features between the seven multi-omics panels obtained from the

unsupervised (purple, sGCCA, MOFA and JIVE) and supervised (green, Concatenation,

Ensemble, DIABLO_null and DIABLO_full) methods. Supervised methods selected many of the

same features (blue), but DIABLO_full had greater feature overlap with unsupervised methods

(orange). The level of connectivity of each of the seven multi-omics panels was assessed by

generating networks from the feature adjacency matrix at various Pearson correlation coefficient

cut-offs (**Fig. 2b**). At all cut-offs, unsupervised approaches produced networks with greater

connectivity (number of edges) compared to supervised approaches. In addition, biomarker

panels identified by DIABLO_full, were more similar to those identified by unsupervised

approaches, including high graph density, low number of communities and large number of

triads, indicating that DIABLO_full identified discriminative sets of features that were tightly

correlated across biological compartments (**Supplementary Fig. 4**). For example, **Fig. 2c** (upper

panel) depicts the networks of all multi-omics biomarker panels for the colon cancer dataset,

which show higher modularity (a limited number of large clusters of variables; circled) for the

DIABLO_full and the unsupervised approaches as compared to the supervised ones. The

corresponding component plots show a clear separation between the high and low survival

groups for the panels derived using supervised approaches, whereas the unsupervised approaches

could not segregate the survival groups [**Fig. 2c** (lower panel), see **Supplementary Fig. 5 and 6**

for other cancer datasets].

Finally, we carried out gene set enrichment analysis on each multi-omics biomarker panel

(using gene symbols of mRNAs and CpGs) against 10 gene set collections (see **Methods**) and

tabulated the number of significant (FDR=5%) gene sets (**Table 2**). The DIABLO_full model

identified the greatest number of significant gene sets across the 10 gene set collections and

generally ranked higher than the other methods in the colon (7 collections), gbm (5 collections)

and lung (5 collections) cancer datasets, whereas JIVE outperformed all other methods in the

kidney cancer datasets (6 collections). Unlike all other approaches considered, DIABLO_full,

which aimed to explain both the correlation structure between multiple omics layers and a

phenotype of interest, implicated the greatest number of known biological gene sets

(pathways/functions/processes *etc.*).

Case study 1: DIABLO identified known and novel multi-omics biomarkers of breast

cancer subtypes

We next demonstrate that DIABLO can identify novel biomarkers in addition to biomarkers with

known biological associations using a case study of human breast cancer. We applied our

biomarker analysis workflow to breast cancer datasets to characterize and predict PAM50 breast

cancer subtypes (**Supplementary Fig. 7**). After preprocessing and normalization of each omics

data-type, the samples were divided into training and test sets (**Methods, Table 1**). The training

data consisted of four omics-datasets (mRNA, miRNA, CpGs and proteins) whereas the test data

included all remaining samples for which the protein expression data were missing. The optimal

multi-omics biomarker panel size was identified using a grid approach where, for any given

combination of variables, we assessed the classification performance using a 5-fold cross-

validation repeated 5 times (**Supplementary Fig. 8**). The number of variables that resulted in the

minimum balanced error rate were retained as previously described in [12]. The optimal multi-

omics panel consisted of 45 mRNA, 45 miRNAs, 25 CpGs and 55 proteins selected across three

components with a balanced error rate of 17.9±1.9%. This panel identified many variables with

previously known associations with breast cancer, as assessed by looking at the overlap between

the panel features and gene sets related to breast cancer based on the Molecular Signature

database (MolSigDB) [23], miRCancer [24], Online Mendelian Inheritance in Man (OMIM)

[25], and DriverDBv2 [26]. **Figure 3a** depicts the variable contributions of each omics-type

indicated by their loading weight (variable importance). Variables not found in any database may

represent novel biomarkers of breast cancer. **Figure 3b** shows the consensus and individual

omics component plots based on this biomarker panel, along with 95% confidence ellipses

obtained from the training data and superimposed with the samples from the test data. The

majority of the samples were within the ellipses, suggesting a reproducible multi-omics

biomarker panel from the training to the test set, that was predictive of breast cancer subtypes

(balanced error rate = 22.9%). The consensus plot corresponded strongly with the mRNA

component plot, depicting a strong separation of the Basal (error rate = 4.9%) and Her2 (error

rate = 20%) subtypes. We observed a weak separation of Luminal A (LumA, error rate = 13.3%)

and Luminal B (LumB, error rate = 53.3%) subtypes. Similarly, the heatmap showing the scaled

expression of all features of the multi-omics biomarker panel, depicted a strong clustering of the

Basal and Her2 samples whereas the Luminal A and B were mixed (**Fig. 3c**). Overall, the

features of the multi-omics biomarker panel formed a densely connected network comprising of

four communities where variables in each community (cluster) were densely connected with

themselves and sparsely connected with other clusters (**Fig. 3d**). The largest cluster in **Fig. 3d**

consisted of 72 variables; 20 mRNAs, 21 miRNAs, 15 CpGs and 16 proteins (red bubble) and

was further investigated using gene set enrichment analysis. We identified many cancer-

associated pathways (*e.g.* FOXM1 pathway, p53 signaling pathway), DNA damage and repair

pathways (*e.g.* E2F mediated regulation of DNA replication, G2M DNA damage checkpoint)

and various cell-cycle pathways (*e.g.* G1S transition, mitotic G1/G1S phases), demonstrating the

ability of DIABLO to identify a biologically plausible multi-omics biomarker panel. This panel

generalized to new breast cancer samples and implicated previously unknown molecular features

in breast cancer, which could be further validated in experimental studies.

Case study 2: DIABLO for repeated measures designs and module-based analyses

Next, we demonstrate the flexibility of DIABLO by extending its use to a repeated measures

cross-over study [27], as well as incorporating module-based analyses that incorporate prior

biological knowledge [28–30]. We use a small multi-omics asthma dataset, including pre and

post intervention timepoints, to compare a DIABLO model that can account for repeated

measures (multilevel DIABLO) with the standard DIABLO model as described above [20,21].

An allergen inhalation challenge was performed as we previously described in [20,21] in 14

subjects and blood samples were collected before (pre) and two hours after (post) challenge; cell-

type frequencies, leukocyte gene transcript expression and plasma metabolite abundances were

determined for all samples (**Table 1**). We observed a net decline in lung function after allergen

inhalation challenge (**Supplementary Fig. 9**), and the goal of this study was to identify

perturbed molecular mechanisms in the blood in response to allergen inhalation challenge. A

module based approach (also known as eigengene summarization [18], **see Methods**) was used

to transform both the gene expression and metabolite datasets into pathway datasets.

Consequently, each variable in those two datasets now represented the scaled pathway activity

expression level for each sample instead of direct gene/metabolite expression. The mRNA

dataset was transformed into a dataset of metabolic pathways (based on the Kyoto Encyclopedia

of Genes and Genomes, KEGG) whereas the metabolite dataset was transformed into a

metabolite pathway dataset based on annotations provided by Metabolon Inc. (Durham, North

Carolina, USA) (**Fig. 4a**). To account for the repeated measures experimental design, a

multilevel approach [27] was first used to isolate the within-sample variation from each dataset

(see **Methods**), and then DIABLO was applied to identify a multi-omics biomarker panel

consisting of cells, gene and metabolite modules that discriminated pre- from post-challenge

samples. We contrast the resulting 'multilevel DIABLO' (mDIABLO) with a standard DIABLO

model that disregards the paired nature of this study by comparing their cross-validation

classification performances (**Fig. 4b**). mDIABLO outperformed DIABLO (AUC=98.5% vs.

AUC=62.2%, leave-one-out cross-validation, **see Methods**), and we observed a greater degree of

separation between the pre- and post-challenge samples for mDIABLO compared to DIABLO

(**Fig. 4c**). Common features (pathways) were identified across omics-types in the mDIABLO

model, but not in the standard DIABLO model (**Fig. 4d**). Tryptophan metabolism and Valine,

leucine and isoleucine metabolism pathways were identified in both the gene and metabolite

module datasets using mDIABLO. The heatmap of pairwise associations of all features identified

with mDIABLO demonstrated the ability of DIABLO to select groups of correlated features

which were predictive of pre- and post-challenge samples. The Asthma pathway was also

identified [even though individual gene members were not significantly altered post-challenge

(**Supplementary Fig. 10**)] and was negatively associated with Butanoate metabolism and

positively associated with basophils, a hallmark cell-type in asthma (**Fig. 4e**). These findings

depict DIABLO's flexibility and sensitivity to detect subtle differences between repeated

designs, and its ability to identify common molecular processes spanning different biological

layers. The biological pathways identified suggest a mechanistic link with response to allergen

challenge.

Discussion

DIABLO aims to identify coherent patterns between datasets that change with respect

different phenotypes. This purely data-driven, holistic, and hypothesis-free tool can be used to

derive robust biomarkers and, ultimately, improve our understanding of the molecular

mechanisms that drive disease.

We found that unsupervised methods identified features that formed strong

interconnected multi-omics networks, but had poor discriminative ability. In contrast, features

identified by supervised methods were discriminative, but formed sparsely connected networks.

This trade-off between correlation and discrimination is a fundamental challenge when trying to

identify biologically relevant biomarkers that are also clinically relevant [31]. DIABLO controls

this trade-off by incorporating *a priori* relationships between different omic domains to

adequately model dysregulated biological mechanisms between phenotypic conditions. This may

explain the superior biological enrichment of the DIABLO_full models in our benchmarking

experiments where the mRNA and miRNA expression as well as methylation activity were

assumed to be correlated (**Table 2**). Since these omic domains are known to form real regulatory

relationships in order to control complex biological processes, these multi-omic biomarker

panels may be capturing this biological complexity. In contrast, these biomarkers were not

uncovered when no association was assumed between omic datasets, as in the case of the

DIABLO_null models and existing multi-step integrative strategies. Therefore, by controlling the

trade-off between correlation and discrimination, DIABLO uncovered novel multi-omics

biomarkers that have not previously been identified using existing integrative strategies. These

novel biomarkers were part of densely connected clusters of omic variables which have prior

known biological associations, further suggesting their potential biological plausibility.

There are areas of improvement that DIABLO will benefit from in the near future. The

assumption of linear relationship between the selected omics features to explain the phenotypic

response may not apply in some biological research areas, for example when integrating

distance-based metagenomics studies, where kernel approaches could be further explored [32].

Selecting the optimal number of variables requires repeated cross-validation to ensure unbiased

classification error rate evaluation. A grid approach was deemed reasonable and provided very

good performance results, but several iterations to refine the grid may be required depending on

the complexity of the classification problem. The grid search algorithm was recently improved

[12], but we advise using a broad filtering strategy to alleviate computational time when dealing

with extremely large datasets (e.g. > 50,000 features each). DIABLO was primarily developed

for omics-measurements on a continuous scale after normalization, and further developments are

needed for categorical data types, such as genotype data, as mentioned in [12]. Finally,

DIABLO, like other methods we benchmarked, will be affected by technical artifacts of the data,

such as batch effects and presence of confounding variables that may affect downstream

integrative analyses. Therefore, we recommend exploratory analyses be carried out in each single

omics dataset to assess the effect, if any, of technical factors and use of batch removal methods

prior to the integration analysis [33–35].

To summarize, DIABLO is a versatile, component-based method that can integrate

multiple high dimensional datasets and identify key variables that discriminate between

phenotypic groups. DIABLO identified more biologically relevant and tightly correlated features

across datasets when compared to existing multi-step classification schemes and integrative

methods. The framework is highly flexible, suitable for single point or repeated measures study

designs, and can accommodate various data transformations, such as feature summarization at

the pathway level to enhance biological interpretability. DIABLO's implementation includes

intuitive graphical outputs to facilitate the interpretation of integrative analyses.

Online Methods

Code availability and software tool requirements. The DIABLO framework is implemented in the mixOmics R package [12]. mixOmics currently includes 19 multivariate methodologies, for single-omics and integrative analyses. All scripts and tutorials are provided in our companion web-page http://www.mixomics.org/mixDIABLO. All analyses were performed using the R statistical computing program (version 3.4.1) and the mixOmics package (version 6.3.0).

Statistical methods and analysis

General multivariate framework to integrate multiple datasets measured on the same samples. DIABLO extends sparse generalized canonical correlation analysis (sGCCA) [15] to a classification (supervised) framework. sGCCA is a multivariate dimension reduction technique that uses singular value decomposition and selects co-expressed (correlated) variables from several omics datasets in a computationally and statistically efficient manner. sGCCA maximizes the covariance between linear combinations of variables (latent component scores) and projects the data into the smaller dimensional subspace spanned by the components. The selection of the correlated molecules across omics levels is performed internally in sGCCA with l_1 –penalization on the variable coefficient vector defining the linear combinations. *Note that since all latent components are scaled in the algorithm, sGCCA maximizes the correlation between components. However, we will retain the term 'covariance' instead of 'correlation' throughout this section to present the general sGCCA framework.*

Denote K normalized, centered and scaled datasets X_1 $(n$ x $p_1)$, …, X_K $(n$ x $p_K)$, measuring the expression levels of $p_1, p_2, …, p_K$ omics variables on the same n samples, $k = 1, …, K$, sGCCA solves the optimization function:

$$\max_{\boldsymbol{a}^1,\dots,\boldsymbol{a}^K} \sum_{k,j=1,k\neq j}^{K} c_{jk} cov(X_k \boldsymbol{a}^k, X_j \boldsymbol{a}^j), \quad s.t. \; \left|\left|\boldsymbol{a}^k\right|\right|_2 = 1 \; \text{and} \; \left|\left|\boldsymbol{a}^k\right|\right|_1 < \lambda_k \qquad (1)$$

where c_{jk} indicates whether to maximize the covariance between the datasets X_k and X_j according to the design matrix, with c_{jk} values ranging from 0 (no relationship modelled between the datasets) to 1 otherwise, $\boldsymbol{a}^k$ is the variable coefficient vector for each dataset X_k, λ_k is a non-negative parameter that controls the amount of shrinkage and thus the number of non-zero coefficients in $\boldsymbol{a}^k$. Similar to Lasso [36] and other l_1 – penalized multivariate models developed for single omics analysis [14], the l_1 penalization improves the interpretability of the component scores $X_k \boldsymbol{a}^k$ that is now only defined on a subset of variables with non-zero coefficients in X_k. The result is the identification of variables that are highly correlated between and within omics datasets.

Equation (1) describes the sGCCA model for the first dimension. Once the first set of coefficient vectors $\boldsymbol{a}_1^k$ and associated component scores $\boldsymbol{t}_1^k = X_k \boldsymbol{a}_1^k$ are obtained, residual matrices are calculated during the 'deflation' step for the second dimension, such that $X_k^2 = X_k^1 - \boldsymbol{t}_1^k \boldsymbol{a}_1^k$, where X_k^1 is the original centered and scaled data matrix. The subsequent set of components scores and coefficient vectors are then obtained by substituting X_k by X_k^2 in (1). This process is repeated until a sufficient number of dimensions (or set of components) is obtained.

The underlying assumption of the sGCCA model is that the major source of common biological variation can be extracted via the first sets of component scores $X_k \boldsymbol{a}^k$, while any unwanted variation due to heterogeneity across the datasets X_K does not impact the statistical model. The optimization problem (1) is solved using a monotonically convergent algorithm [15].

DIABLO for supervised analysis and prediction. To extend sGCCA for a classification

framework, we substitute one omics dataset X_k in (1) with a dummy indicator matrix Y of size (n

x G), where G is the number of phenotype groups that indicate the class membership of each

sample. In addition, and for easier use of the method, we replaced the l_1 penalty parameter λ_k by

the number of variables to select in each dataset and each component, as there is a direct

correspondence between both parameters.

Denote a new sample i which is measured across the different types of omics datasets $\boldsymbol{x}_k^i$,

its class membership is predicted by the fitted sGCCA model with the estimated variable

coefficients vectors $\widehat{\boldsymbol{a}^k}$ to obtain the predicted scores $\boldsymbol{t}^{k,i} = \boldsymbol{x}_k^i \, \widehat{\boldsymbol{a}^k}, \, k = 1, \dots, K$. Therefore, to

each dataset k corresponds a predicted continuous score $\boldsymbol{t}^{k,i}$. The predicted class of sample i for

each dataset is obtained from the predicted score using one of the distances Maximum, Centroids

or Mahalanobis [37] as described in [12]. The consensus class membership is determined using

either a majority vote, or by averaging all $\boldsymbol{t}^{k,i}$ across all K datasets before using the prediction

distance of choice ('average prediction' scheme). In case of ties in the majority vote scheme,

'NA' is allocated as a prediction but is counted as a misclassification error during the

performance evaluation. As the class prediction relies on individual vote from each omics set,

DIABLO allows for some missing datasets X_k during the prediction step, as illustrated in the

Breast Cancer case study. We used the centroid distance for the weighted majority vote scheme

(breast cancer study) and the maximum distance for the average vote scheme (asthma study) as

those led to best performance (see [12] for details about distance measures and voting schemes

that can be used).

406   ***Design matrix in DIABLO.*** The design matrix *C* is a (K x K) matrix with values ranging from 0

407   to 1 which specifies whether the covariance between two datasets should be maximized

408   DIABLO (see equation (1)). In our simulation study, we evaluated two scenarios: a null design

409   (DIABLO_null) when no omics datasets are connected, and a full design when all datasets are

410   connected (DIABLO_full):

$$C_{null} = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix} \qquad C_{full} = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 1 \\ 1 & 1 & 0 \end{bmatrix}$$

However, every dataset is connected to the outcome *Y* internally in the method. For the two case

studies (breast cancer and asthma) the design matrix was chosen based on our proposed method

(see below ***Parameters tuning***). Note that the design matrix is not restricted to 0 and 1 values

only and a compromise between correlation and discrimination can also be modelled as

described in [12].

Input data in DIABLO. While DIABLO does not assume particular data distributions, all

datasets should be normalized appropriately according to each omics platform and preprocessed

if necessary (see normalization steps described below for each case study). Samples should be

represented in rows in the data matrices and match the same sample across omics datasets. The

phenotype outcome *Y* is a factor indicating the class membership of each sample. The R function

in mixOmics will internally center and scale each variable as is conventionally performed in

PLS-based models and will create the dummy matrix outcome from Y. A multilevel variance

decomposition option is available for repeated measures study designs (see below).

Parameters tuning.

The first parameter to tune is the design matrix C, which can be determined using either prior

biological knowledge, or a data-driven approach. The latter approach uses PLS method

implemented in mixOmics that models pair-wise associations between omics datasets. If the

correlation between the first component of each omics dataset is above a given threshold (e.g.

0.8) then a connection between those datasets is included in the DIABLO design as a 1 value.

The second parameter to tune is the total number of components. In several analyses we

found that $G - 1$ components were sufficient to extract sufficient information to discriminate all

phenotype groups [14], but this can be assessed by evaluating the model performance across all

specified components (described below) as well as using graphical outputs such as sample plots

to visualize the discriminatory ability of each component.

Finally, the third set of parameters to tune is the number of variables to select per dataset

and per component. Such tuning can rapidly become cumbersome, as there might be numerous

combinations of selection sizes to evaluate across all *K* datasets. For the breast cancer study, we

used 5-fold cross-validation repeated 50 times to evaluate the performance of the model over a

grid of different possible values of variables to select (**Supplementary Fig. 8**). The performance

of the model for a given set of parameters (including number of component and number of

variables to select) was based on the balanced classification error rate using majority vote or

average prediction schemes with centroids distance. The balanced classification error rate is

useful in the case of imbalanced class sizes, where the majority classes can have strong influence

on the overall error rate. The balanced error rate measure calculates the weighted average of the

individual class error rates with respect to their class sample size. In our experience, the number

of variables to select in each dataset provided less of an improvement on the error rate compared

to tuning the number of components. Therefore, even a grid composed of a small number of

variables (<50 with steps of 5 or 10) may suffice as it does not substantially change the

classification performance. This is because of the use of regularization constraints which reduces

the variability in the variable coefficients and thus maintains the predictive ability of the model.

Further, the variable selection size can also be guided according to the downstream biological

interpretation to be performed. For example, a gene-set enrichment analysis may require a larger

set of features than a literature-search interpretation.

Visualization outputs with DIABLO. To facilitate the interpretation of the integrative analysis,

several types of graphical outputs were implemented in mixOmics.

Sample plots. The consensus plot which depicts the samples is computed by calculating the

average of the components from each dataset. Omics specific samples plots can also be obtained

by plotting components associated to each data set. The sample plot are useful to visualize the

ability of the DIABLO model to extract common information at the sample level for each

dataset, and the discriminatory power of each data type to separate the phenotypic groups. The

scatterplot matrix represents the correlation between components for the same dimension but

across all omics datasets. This plot assesses the model's ability to maximize the correlation as

indicated in the design matrix. Separation of subjects according to their phenotypic groups can

be visualized.

Variable plots. To visualize selected variables, we proposed circos plot to represent correlations

between and within variables from each dataset at the variable level. The association between

variables is computed using a similarity score that is analogous to a Pearson correlation

coefficient, as previously described in [38]. For each omics dataset, DIABLO produces a

variable coefficient matrix of size (p_k x H), where H is the total number of components in the

model. The product of any two matrices approximates the association score between variables of

the two omics datasets. The association between variables is displayed as a color-coded link

inside the plot to represent a positive or negative correlation above a user-specified threshold.

The selected variables are represented on the side of the circos plot, with side colors indicating

each omics type, optional line plots represent the expression levels in each phenotypic group.

Clustered Image Map (CIM). A clustered image map [38] based on the Euclidean distance and

the complete linkage displays an unsupervised clustering between the selected variables

(centered and scaled) and the samples. Color bars represent the sample phenotypic groups

(columns) and the type of omics (rows) variables.

Gene-set enrichment analyses

Significance of enrichment was determined using a hypergeometric test of the overlap between

the selected features (mapped to official HUGO gene symbols or official miRNA symbols) and

the various gene sets contained in the collections. In order to carry out the comparison, each

feature set was mapped back to official HUGO gene symbols. This was done as follows across

the respective data types: mRNA, CpGs and proteins. The following collections were used as

gene-sets for the enrichment analysis [39]: C1 - positional gene sets for each human chromosome

and cytogenetic band. C2 – curated gene sets (Pathway Interaction DB [PID], Biocarta

[BIOCARTA], Kyoto Encyclopedia of Genes and Genomes [KEGG], Reactome [REACTOME],

and others), C3 - motif gene sets based on conserved cis-regulatory motifs from a comparative

analysis of the human, mouse, rat, and dog genomes. C4 – computational gene sets (from the

Cancer Gene Neighbourhoods [CGN] and Cancer Modules [CM] – citation available via the

MolSigDB [23]. C5 - GO gene sets consist of genes annotated by the same GO terms. C6 –

ontologic gene sets (Gene sets represent signatures of cellular pathways which are often dis-

regulated in cancer). C7 - immunologic gene sets defined directly from microarray gene

expression data from immunologic studies. H - hallmark gene sets are coherently expressed

signatures derived by aggregating many MSigDB gene sets to represent well-defined biological

states or processes. & A. BTM - Blood Transcriptional Modules [40]. B. TISSUES - cell-specific

expression from Benita *et al.* [41].

Modular analysis: Eigengene summarization is a common approach to decompose a n x p

dataset (where n is the number of samples and p is the number of variables in a module), to a

component (linear combination of all p variables) that represents the summarized expression of

genes in the module [18]. For the asthma study, 15,683 genes were reduced to 229 KEGG

pathways and 292 metabolites were reduced to 60 metabolic pathways using eigengene

summarization.

Multilevel transformation: For multivariate analyses, A multilevel approach separates the

within subject variation matrix (X_w) and the between subject variation (X_b) for a given dataset (X)

[42], ie. $X = X_w + X_b$. In the case of a two-repeated measured problem (e.g. pre vs post

challenge), the within subject variation matrix is similar to calculating the net difference for each

individual between the data obtained for pre and post challenge. For each omics dataset, the

within-subject variation matrix was extracted prior to applying DIABLO. In the asthma study,

the multilevel approach (called variance decomposition step) was applied to the cell-type, gene

and metabolite module datasets.

Declarations

• **Acknowledgements**

• The authors would like to thank Mr Kevin Chang (University of Auckland) for some preliminary

exploratory analyses of the breast cancer dataset. We would also like to thank Dr Chao Liu

(University of Queensland) for obtaining the PAM50 phenotypic information for the TCGA

datasets.

• **Competing interests**

The authors declare no competing interests.

• **Funding**

AS is the recipient of the Canadian Institutes of Health Research Doctoral Award – Frederick

Banting and Charles Best Canada Graduate Scholarship and the Michael Smith Foreign Study

Supplement award. Research reported in this publication was supported in part by the National

Institute Of Allergy And Infectious Diseases of the National Institutes of Health under Award

Number U19AI118608 (CPS and SJT). The content is solely the responsibility of the authors and

does not necessarily represent the official views of the National Institutes of Health. KALC is

supported in part by the National Health and Medical Research Council (NHMRC) Career

Development fellowship (GNT1087415).

•

• **Authors' contributions**

• AS performed the data pre-processing, the statistical analyses and developed the DIABLO

method. BG implemented the R scripts for DIABLO and graphical outputs, CPS performed the

gene enrichment analyses, MV implemented the circos plots, FR and BG implemented the R

scripts in mixOmics along with the S3 functions, SJT supervised AS and participated in the

design of the study. KALC supervised AS, BG, MV and FR, participated in the development of

the DIABLO method and provided statistical advice. AS and KALC edited the manuscript, with

editorial input from SJT and CPS.

Table 1. Overview of multi-omics datasets analyzed for method benchmarking and in two
case studies. The breast cancer case study includes training and test datasets for all omics types
except proteins.

Analysis	Dataset	Number of samples	Sample size in each subtype			Omics	Number of variables
Benchmark cancer datasets (Wang et al. [3])	Colon	92	High (33) Low (59)			mRNA	17,814
						miRNA	312
						CpGs	23,088
	Kidney	122	High (61) Low (61)			mRNA	17,665
						miRNA	329
						CpGs	24,960
	Glioblastoma (gbm)	213	High (105) Low (108)			mRNA	12,042
						miRNA	534
						CpGs	1,305
	Lung	106	High (53) Low (53)			mRNA	12,042
						miRNA	353
						CpGs	23,074
Case study 1 (The Cancer Genome Atlas) [19]	Breast cancer	989		Train	Test	mRNA	16,851
			Basal	76	102	miRNA	349
			Her2	38	40	CpGs	9,482
			LumA	188	346	Proteins	Train: 115 Test: 0
			LumB	77	122		
Case study 2 (Singh et al. [20,21])	Asthma	28	Pre (14) Post (14)			Cell-types	9
						mRNA-modules	229
						metabolite-modules	60

554 **Table 2. Number of significant gene sets for each integrative method and benchmarking**
555 **cancer dataset.** Best performing method is indicated in the shaded cell. Each row represents a
556 gene set collection (**see Methods** for details, FDR = 5%).

		Unsupervised, integrative			Supervised, non-integrative			Supervised, integrative
disease	collection	JIVE	MOFA	sGCCA	Concatenation	Ensemble	DIABLO_null	DIABLO_full
Colon	**BTM**	0	4	0	0	0	0	23
	C1	0	0	0	0	0	0	0
	C2	15	14	5	12	3	21	113
	C3	8	5	14	11	2	6	0

	C4	0	1	0	1	2	1	46
	C5	19	36	147	7	0	0	216
	C6	0	0	0	0	0	0	0
	C7	1	87	11	61	10	62	218
	H	0	0	0	0	0	2	7
	TISSUES	2	12	0	0	0	0	16
	TOTAL	45	159	177	92	17	92	639
Gbm	BTM	0	0	19	10	9	10	30
	C1	0	0	0	0	0	0	0
	C2	275	337	193	258	358	312	426
	C3	94	64	37	14	15	15	34
	C4	49	43	68	47	50	62	125
	C5	825	708	706	526	669	776	693
	C6	22	25	18	30	24	24	21
	C7	460	82	526	432	173	147	869
	H	12	8	8	19	23	20	19
	TISSUES	18	29	21	10	12	14	44
	TOTAL	1755	1296	1596	1346	1333	1380	2261
Kidney	BTM	1	0	0	0	0	0	0
	C1	0	0	1	0	0	0	1
	C2	42	33	7	10	5	15	4
	C3	8	80	1	4	35	23	1
	C4	17	6	0	7	1	3	0
	C5	157	110	1	55	27	46	0
	C6	0	0	0	0	0	0	0
	C7	0	74	15	93	13	10	18
	H	6	3	0	1	0	1	0
	TISSUES	2	0	0	0	0	0	0
	TOTAL	233	306	25	170	81	98	24
Lung	BTM	0	0	0	0	0	2	0
	C1	0	0	0	1	0	0	1
	C2	4	17	2	0	0	1	33
	C3	48	20	57	50	26	21	19
	C4	17	0	47	0	0	18	13
	C5	35	127	42	0	25	22	193
	C6	1	0	1	3	2	5	7
	C7	18	13	78	0	7	72	100
	H	0	2	0	0	1	0	0

TISSUES	0	0	0	0	0	9	20
TOTAL	123	179	227	54	61	150	386

 Figure captions

560
Figure 1. Simulation study: performance assessment and benchmarking. Simulated datasets
included different types of variables: correlated & discriminatory (corDis); uncorrelated &
discriminatory (unCorDis); correlated & nondiscriminatory (corNonDis) and uncorrelated &
nondiscriminatory (unCorNonDis) for different fold-changes between sample groups and
different noise levels (**see Supplementary Note**). Integrative classifiers included DIABLO with
either the full or null design, concatenation and ensemble-based sPLSDA classifiers and were all
trained to select 90 variables across three multi-omics datasets. **a)** Classification error rates (10-
fold cross-validation averaged over 50 simulations). Dashed line indicates a random performance
(error rate = 50%). All methods perform similarly with the exception of DIABLO_full which has
a higher error rate. **b)** Number of variables selected according to their type. DIABLO_full
selected mainly variables that were correlated & discriminatory (corDis, red), whereas the other
methods selected an equal number of correlated or uncorrelated discriminatory variables (corDis
and unCorDis, red and blue).

574
Figure 2. Benchmarking integrative methods using multi-omics biomarker panels for
different cancers. a) Overlap of selected features using both supervised (green) and
unsupervised approaches (purple): a strong overlap was observed between the supervised
approaches with the exception of DIABLO_full (blue bars) which showed more similarity to
unsupervised methods (dark orange bars). **b)** Number of edges within each panel network at
various Pearson correlation cut-offs: unsupervised approaches panels were more connected than
those from supervised approaches, with the exception of DIABLO_full which led to a highly-
connected panel. An edge is present if the association between two omic variables is greater than
a given correlation cut-off. **c)** Upper panel: network modularity of each multi-omic biomarker
panel for colon cancer showed that unsupervised approaches and DIABLO_full resulted in a few
groups of highly connected features, whereas supervised approaches identified networks with
many groups of sparsely connected features. Lower panel: component plots depicting the clear
separation of subjects in the high and low survival groups for supervised methods as opposed to
the unsupervised methods.

589
Figure 3. Identification of a multi-omics biomarker panel predictive of breast cancer
subtypes. a) Variable contributions of each omics-type biomarker that are important to
discriminate breast cancer subtypes. **b)** DIABLO component plots and the derived biomarker
panel: 95% confidence ellipses were calculated from the training data set and points depict
samples from the test set. **c)** Heatmap of the scaled expression of variable from the biomarker
panel. **d)** Network visualization of the biomarker panel highlights correlated variables (Pearson
correlation > |0.4|) and four communities based on edge betweeness scores. **e)** A gene set
enrichment analysis was conducted on the largest community from d (red cluster) where many
cancer related pathways were identified.

599
Figure 4. Asthma study: cross-over design and module-based analysis with DIABLO.
a) DIABLO design includes a module-based decomposition approach to discriminate pre-and
post-inhalation challenge samples. **b)** Receiver operating characteristic curves comparing the
performance of the standard DIABLO and 'multilevel DIABLO' for repeated measures

(mDIABLO) using leave-one-out cross-validation. **c)** Component plots depicting the separation
of the pre- and post-challenge samples based on DIABLO and mDIABLO. **d)** Overlapping
features selected from either DIABLO or mDIABLO. **e)** Heatmap of the Pearson correlation
values between the features selected with mDIABLO. **f)** Circos plot depicting the strongest
correlations between different omics features from the mDIABLO panel.
609
610
611

References

1. Zhu J, Sova P, Xu Q, Dombek KM, Xu EY, Vu H, et al. Stitching together multiple data dimensions reveals interacting metabolomic and transcriptomic networks that modulate cell regulation. Levchenko A, editor. PLoS Biol [Internet]. 2012 [cited 2016 Jan 19];10:e1001301. Available from: http://dx.plos.org/10.1371/journal.pbio.1001301

2. Kim D, Li R, Dudek SM, Ritchie MD. ATHENA: Identifying interactions between different levels of genomic data associated with cancer clinical outcomes using grammatical evolution neural network. BioData Min. 2013;6:23.

3. Wang B, Mezlini AM, Demir F, Fiume M, Tu Z, Brudno M, et al. Similarity network fusion for aggregating data types on a genomic scale. Nat Methods [Internet]. 2014 [cited 2016 Jan 19];11:333–7. Available from: http://www.nature.com/doifinder/10.1038/nmeth.2810

4. Ritchie MD, Holzinger ER, Li R, Pendergrass SA, Kim D. Methods of integrating data to uncover genotype–phenotype interactions. Nat Rev Genet [Internet]. 2015 [cited 2015 Jul 10];16:85–97. Available from: http://www.nature.com/doifinder/10.1038/nrg3868

5. Yugi K, Kubota H, Hatano A, Kuroda S. Trans-Omics: How To Reconstruct Biochemical Networks Across Multiple 'Omic' Layers. Trends Biotechnol [Internet]. 2016 [cited 2018 Feb 21];34:276–90. Available from: http://linkinghub.elsevier.com/retrieve/pii/S0167779915002735

6. Günther O, Chen V, Freue GC, Balshaw R, Tebbutt S, Hollander Z, et al. A computational pipeline for the development of multi-marker bio-signature panels and ensemble classifiers. 2012 [cited 2016 Jan 19];13:326. Available from: http://summit.sfu.ca/item/13303

7. Aben N, Vis DJ, Michaut M, Wessels LFA. TANDEM: a two-stage approach to maximize interpretability of drug response models based on multiple molecular data types. Bioinformatics [Internet]. 2016 [cited 2017 Aug 2];32:i413–20. Available from: https://academic.oup.com/bioinformatics/article-lookup/doi/10.1093/bioinformatics/btw449

8. Ma S, Ren J, Fenyö D. Breast cancer prognostics using multi-omics data. AMIA Summits Transl Sci Proc [Internet]. 2016 [cited 2017 May 30];2016:52. Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5001766/

9. Bersanelli M, Mosca E, Remondini D, Giampieri E, Sala C, Castellani G, et al. Methods for the integration of multi-omics data: mathematical aspects. BMC Bioinformatics [Internet]. 2016 [cited 2016 May 8];17. Available from: http://www.biomedcentral.com/1471-2105/17/S2/15

10. Meng C, Zeleznik OA, Thallinger GG, Kuster B, Gholami AM, Culhane AC. Dimension reduction techniques for the integrative analysis of multi-omics data. Brief Bioinform [Internet]. 2016 [cited 2018 Feb 21];17:628–41. Available from: https://academic.oup.com/bib/article-lookup/doi/10.1093/bib/bbv108

11. Huang S, Chaudhary K, Garmire LX. More Is Better: Recent Progress in Multi-Omics Data
Integration Methods. Front Genet [Internet]. 2017 [cited 2018 Feb 21];8. Available from:
http://journal.frontiersin.org/article/10.3389/fgene.2017.00084/full

12. Rohart F, Gautier B, Singh A, Cao K-AL. mixOmics: An R package for 'omics feature
selection and multiple data integration. PLOS Comput Biol [Internet]. 2017 [cited 2018 Jan
29];13:e1005752. Available from:
http://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1005752

13. Wold H. Estimation of Principal Components and Related Models by Iterative Least squares.
Multivar Anal. 1966;391–420.

14. Lê Cao K-A, Boitard S, Besse P. Sparse PLS discriminant analysis: biologically relevant
feature selection and graphical displays for multiclass problems. BMC Bioinformatics [Internet].
2011 [cited 2015 Jul 15];12:253. Available from: http://www.biomedcentral.com/1471-
2105/12/253/

15. Tenenhaus A, Philippe C, Guillemot V, Le Cao K-A, Grill J, Frouin V. Variable selection for
generalized canonical correlation analysis. Biostatistics [Internet]. 2014 [cited 2015 Jul
15];15:569–83. Available from:
http://biostatistics.oxfordjournals.org/cgi/doi/10.1093/biostatistics/kxu001

16. Witten DM, Tibshirani R, Hastie T. A penalized matrix decomposition, with applications to
sparse principal components and canonical correlation analysis. Biostatistics [Internet]. 2009
[cited 2016 Jul 27];10:515–34. Available from:
http://biostatistics.oxfordjournals.org/cgi/doi/10.1093/biostatistics/kxp008

17. Lee HK, Hsu AK, Sajdak J, Qin J, Pavlidis P. Coexpression analysis of human genes across
many microarray data sets. Genome Res [Internet]. 2004 [cited 2016 Mar 30];14:1085–1094.
Available from: http://genome.cshlp.org/content/14/6/1085.short

18. Langfelder P, Horvath S. WGCNA: an R package for weighted correlation network analysis.
BMC Bioinformatics [Internet]. 2008 [cited 2016 Apr 4];9:559. Available from:
http://www.biomedcentral.com/1471-2105/9/559

19. The TCGA Research Network. The Cancer Genome Atlas [Internet]. Available from:
http://cancergenome.nih.gov/

20. Singh A, Yamamoto M, Kam SHY, Ruan J, Gauvreau GM, O'Byrne PM, et al. Gene-
metabolite expression in blood can discriminate allergen-induced isolated early from dual
asthmatic responses. Hsu Y-H, editor. PLoS ONE [Internet]. 2013 [cited 2015 Jul 18];8:e67907.
Available from: http://dx.plos.org/10.1371/journal.pone.0067907

21. Singh A, Yamamoto M, Ruan J, Choi JY, Gauvreau GM, Olek S, et al. Th17/Treg ratio
derived using DNA methylation analysis is associated with the late phase asthmatic response.
Allergy Asthma Clin Immunol [Internet]. 2014 [cited 2016 Mar 2];10:32. Available from:
http://www.biomedcentral.com/content/pdf/1710-1492-10-32.pdf

22. Lock EF, Hoadley KA, Marron JS, Nobel AB. Joint and individual variation explained
(JIVE) for integrated analysis of multiple data types. Ann Appl Stat [Internet]. 2013 [cited 2018
Jan 24];7:523–42. Available from: http://projecteuclid.org/euclid.aoas/1365527209

23. Liberzon A, Birger C, Thorvaldsdóttir H, Ghandi M, Mesirov JP, Tamayo P. The Molecular
Signatures Database Hallmark Gene Set Collection. Cell Syst [Internet]. 2015 [cited 2018 Jan
30];1:417–25. Available from: http://linkinghub.elsevier.com/retrieve/pii/S2405471215002185

24. Xie B, Ding Q, Han H, Wu D. miRCancer: a microRNA-cancer association database
constructed by text mining on literature. Bioinformatics [Internet]. 2013 [cited 2018 Jan
30];29:638–44. Available from: https://academic.oup.com/bioinformatics/article-
lookup/doi/10.1093/bioinformatics/btt014

25. Hamosh A. Online Mendelian Inheritance in Man (OMIM), a knowledgebase of human
genes and genetic disorders. Nucleic Acids Res [Internet]. 2004 [cited 2018 Jan 30];33:D514–7.
Available from: https://academic.oup.com/nar/article-lookup/doi/10.1093/nar/gki033

26. Chung I-F, Chen C-Y, Su S-C, Li C-Y, Wu K-J, Wang H-W, et al. DriverDBv2: a database
for human cancer driver gene research. Nucleic Acids Res [Internet]. 2016 [cited 2018 Jan
30];44:D975–9. Available from: https://academic.oup.com/nar/article-
lookup/doi/10.1093/nar/gkv1314

27. Liquet B, Lê Cao K-A, Hocini H, Thiébaut R. A novel approach for biomarker selection and
the integration of repeated measures experiments from two assays. BMC Bioinformatics
[Internet]. 2012 [cited 2015 Jul 18];13:325. Available from:
http://www.biomedcentral.com/1471-2105/13/325/

28. Allahyar A, de Ridder J. FERAL: network-based classifier with application to breast cancer
outcome prediction. Bioinformatics [Internet]. 2015 [cited 2018 Feb 1];31:i311–9. Available
from: https://academic.oup.com/bioinformatics/article-lookup/doi/10.1093/bioinformatics/btv255

29. Cun Y, Fröhlich H. Network and data integration for biomarker signature discovery via
network smoothed t-statistics. Boccaletti S, editor. PLoS ONE [Internet]. 2013 [cited 2017 May
30];8:e73074. Available from: http://dx.plos.org/10.1371/journal.pone.0073074

30. Sokolov A, Carlin DE, Paull EO, Baertsch R, Stuart JM. Pathway-based genomics prediction
using generalized elastic net. PLoS Comput Biol [Internet]. 2016 [cited 2017 May
30];12:e1004790. Available from:
http://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1004790

31. Wang TJ. Assessing the Role of Circulating, Genetic, and Imaging Biomarkers in
Cardiovascular Risk Prediction. Circulation [Internet]. 2011 [cited 2018 Feb 23];123:551–65.
Available from: http://circ.ahajournals.org/cgi/doi/10.1161/CIRCULATIONAHA.109.912568

32. Mariette J, Villa-Vialaneix N. Unsupervised multiple kernel learning for heterogeneous data
integration. Bioinformatics [Internet]. 2017 [cited 2018 Mar 6]; Available from:
http://academic.oup.com/bioinformatics/advance-
article/doi/10.1093/bioinformatics/btx682/4565592

33. Johnson WE, Li C, Rabinovic A. Adjusting batch effects in microarray expression data using
empirical Bayes methods. Biostatistics [Internet]. 2007 [cited 2016 May 12];8:118–27. Available
from: http://biostatistics.oxfordjournals.org/cgi/doi/10.1093/biostatistics/kxj037

34. Gagnon-Bartsch JA, Speed TP. Using control genes to correct for unwanted variation in
microarray data. Biostatistics [Internet]. 2012 [cited 2018 Mar 6];13:539–52. Available from:
https://academic.oup.com/biostatistics/article-lookup/doi/10.1093/biostatistics/kxr034

35. Parker HS, Corrada Bravo H, Leek JT. Removing batch effects for prediction problems with
frozen surrogate variable analysis. PeerJ [Internet]. 2014 [cited 2016 May 12];2:e561. Available
from: https://peerj.com/articles/561

36. Tibshirani R. Regression shrinkage and selection via the lasso. J R Stat Soc Ser B Methodol.
1996;58:267–88.

37. Le Cao K-A, Gonzalez I, Dejean S. integrOmics: an R package to unravel relationships
between two omics datasets. Bioinformatics [Internet]. 2009 [cited 2016 Apr 3];25:2855–6.
Available from: http://bioinformatics.oxfordjournals.org/cgi/doi/10.1093/bioinformatics/btp515

38. González I, Lê Cao K-A, Davis MJ, Déjean S. Visualising associations between paired
'omics' data sets. BioData Min [Internet]. 2012 [cited 2015 Jul 15];5:1–23. Available from:
http://link.springer.com/article/10.1186/1756-0381-5-19

39. Subramanian A, Tamayo P, Mootha VK, Mukherjee S, Ebert BL, Gillette MA, et al. Gene set
enrichment analysis: a knowledge-based approach for interpreting genome-wide expression
profiles. Proc Natl Acad Sci [Internet]. 2005 [cited 2016 Jul 26];102:15545–15550. Available
from: http://www.pnas.org/content/102/43/15545.short

40. Chaussabel D, Quinn C, Shen J, Patel P, Glaser C, Baldwin N, et al. A Modular Analysis
Framework for Blood Genomics Studies: Application to Systemic Lupus Erythematosus.
Immunity [Internet]. 2008 [cited 2016 Jul 22];29:150–64. Available from:
http://linkinghub.elsevier.com/retrieve/pii/S1074761308002835

41. Benita Y, Cao Z, Giallourakis C, Li C, Gardet A, Xavier RJ. Gene enrichment profiles reveal
T-cell development, differentiation, and lineage-specific transcription factors including ZBTB25
as a novel NF-AT repressor. Blood [Internet]. 2010 [cited 2018 Mar 5];115:5376–84. Available
from: http://www.bloodjournal.org/cgi/doi/10.1182/blood-2010-01-263855

42. Westerhuis JA, van Velzen EJJ, Hoefsloot HCJ, Smilde AK. Multivariate paired data
analysis: multilevel PLSDA versus OPLSDA. Metabolomics [Internet]. 2010 [cited 2016 Jul
27];6:119–28. Available from: http://link.springer.com/10.1007/s11306-009-0185-z