Title

HiC-bench: comprehensive and reproducible Hi-C data analysis designed for parameter exploration and benchmarking

Authors

Charalampos Lazaris[1,2], Stephen Kelly[3,4], Panagiotis Ntziachristos[5], Iannis Aifantis[1,2*] and Aristotelis Tsirigos[1,2,3,4*]

1. Department of Pathology, NYU School of Medicine, New York, NY 10016, USA
2. Laura and Isaac Perlmutter Cancer Center and Helen L. and Martin S. Kimmel Center for Stem Cell Biology, NYU School of Medicine, New York, NY 10016, USA
3. Applied Bioinformatics Laboratories, Office of Science & Research, NYU School of Medicine, NY 10016, USA
4. Genome Technology Center, Office of Science & Research, NYU School of Medicine, NY 10016, USA
5. Department of Biochemistry and Molecular Genetics, Feinberg School of Medicine, Northwestern University, Chicago, IL 60611, USA

E-mail addresses

charalampos.lazaris@nyumc.org
stephen.kelly@nyumc.org
panos.ntz@northwestern.edu
ioannis.aifantis@nyumc.org
aristotelis.tsirigos@nyumc.org

* Address correspondence to: Aristotelis Tsirigos (AT) (aristotelis.tsirigos@nyumc.org) or Iannis Aifantis (IA) (ioannis.aifantis@nyumc.org)

Abstract

Background

Chromatin conformation capture techniques have evolved rapidly over the last few years and have provided new insights into genome organization at an unprecedented resolution. Analysis of Hi-C data is complex and computationally intensive involving multiple tasks and requiring robust quality assessment. This has led to the development of several tools and methods for processing Hi-C data. However, most of the existing tools do not cover all aspects of the analysis and only offer few quality assessment

options. Additionally, availability of a multitude of tools makes scientists wonder how

these tools and associated parameters can be optimally used, and how potential

discrepancies can be interpreted and resolved. Most importantly, investigators need to

be ensured that slight changes in parameters and/or methods do not affect the

conclusions of their studies.

Results

To address these issues (compare, explore and reproduce), we introduce HiC-bench, a

configurable computational platform for comprehensive and reproducible analysis of Hi-

C sequencing data. HiC-bench performs all common Hi-C analysis tasks, such as

alignment, filtering, contact matrix generation and normalization, identification of

topological domains, scoring and annotation of specific interactions using both published

tools and our own. We have also embedded various tasks that perform quality

assessment and visualization. HiC-bench is implemented as a data flow platform with an

emphasis on analysis reproducibility. Additionally, the user can readily perform parameter

exploration and comparison of different tools in a combinatorial manner that takes into

account all desired parameter settings in each pipeline task. This unique feature facilitates

the design and execution of complex benchmark studies that may involve combinations

of multiple tool/parameter choices in each step of the analysis. To demonstrate the

usefulness of our platform, we performed a comprehensive benchmark of existing and

new TAD callers exploring different matrix correction methods, parameter settings and

sequencing depths. Users can extend our pipeline by adding more tools as they become

available.

Conclusions

HiC-bench consists an easy-to-use and extensible platform for comprehensive analysis

of Hi-C datasets. We expect that it will facilitate current analyses and help scientists

formulate and test new hypotheses in the field of three-dimensional genome organization.

Keywords

64 Hi-C, Chromosome Conformation, Computational pipeline, Data provenance, Parameter

65 exploration, Benchmarking

Background

Nuclear organization is of fundamental importance to gene regulation. Recently, proximity

ligation assays have greatly enhanced our understanding of chromatin organization and

its relationship to gene expression [1]. Here we focus on Hi-C, a powerful genome-wide

chromosome conformation capture variant, which detects genome-wide chromatin

interactions [2,3]. In Hi-C, chromatin is cross-linked and DNA is fragmented using

restriction enzymes, the interacting fragments are ligated forming hybrids that are then

sequenced and mapped back to the genome. Hi-C is a very powerful technique that has

led to important discoveries regarding the organizational principles of the genome. More

specifically, Hi-C has revealed that the mammalian genome is organized in active and

repressed areas (A and B compartments) [2] that are further divided in "meta-TADs" [4],

TADs [5] and sub-TADs [6]. TADs consist evolutionarily conserved, megabase-scale,

non-overlapping areas with increased frequency of intra-domain compared to inter-

domain chromatin interactions [5,7]. Despite the fact that Hi-C is very powerful, it is known

to be prone to systematic biases [8-10]. Moreover, as the sequencing costs plummet

allowing for increased Hi-C resolution, Hi-C poses formidable challenges to computational

analysis in terms of data storage, memory usage and processing speed. Thus, various

tools have been recently developed to mitigate biases in Hi-C data and make Hi-C

analysis faster and more efficient in terms of resource usage. HiC-Box [11], hiclib [9] and

HiC-Pro [12] perform various Hi-C analysis tasks, such as alignment and binning of Hi-C

sequencing reads into Hi-C contact matrices, noise reduction and detection of specific

DNA-DNA interactions. Hi-Corrector [13] has been developed for noise reduction of Hi-C

data, allowing parallelization and effective memory management, whereas Hi-Cpipe [14]

offers parallelization options and includes steps for alignment, filtering, quality control,

detection of specific interactions and visualization of contact matrices. Other tools that

allow parallelization are HiFive [15], HOMER [16] and HiC-Pro [12]. Allele-specific Hi-C

contact maps can be generated using HiC-Pro and HiCUP [17] (with SNPsplit [18]).

TADbit can be used to map raw reads, create interaction matrices, normalize and correct

the matrices, call topological domains and build three-dimensional (3D) models based on

the Hi-C matrices [19]. HiCdat performs binning, matrix normalization, integration of other

data (e.g. ChIP-seq) and visualization [20]. HIPPIE offers similar functionality with HiCdat

and allows detection of specific enhancer-promoter interactions [21]. Other tools mainly

focus on visualization of Hi-C data (e.g. Sushi [22] and HiCPlotter [23]). Despite the recent

boom in the development of computational methods for Hi-C analysis, most of these tools

only focus on certain aspects of the analysis, thus failing to encompass the entire Hi-C

data analysis workflow. More importantly, these tools or pipelines are not easily

extensible, and, for any given Hi-C task, they do not allow the integration of multiple

alternative tools (use of alternative TAD calling methods for example) whose performance

could then be qualitatively or quantitatively compared. Available tools do not support

comprehensive reporting of the parameters used for each task and they do not enable

reproducible computational analysis which is an imperative requirement in the era of big

data [24], especially given the complexity of Hi-C analyses. The recently released HiFive

is an exception as it offers a Galaxy interface [15]. However, use of Galaxy [25] can

become problematic for data-heavy analyses, especially when the remote Galaxy server

is used.

To facilitate comprehensive processing, reproducibility, parameter exploration and

benchmarking of Hi-C data analyses, we introduce HiC-bench, a data flow platform which

is extensible and allows the integration of different task-specific tools. Current and future

tools related to Hi-C analysis can be easily incorporated into HiC-bench by implementing

simple wrapper scripts. HiC-bench covers all current aspects of a standard Hi-C analysis

workflow, including read mapping, filtering, quality control, binning, noise correction and

identification of specific interactions (**Table 1**). Moreover, it integrates multiple alternative

tools for performing each task (such as matrix correction tools and TAD-calling

algorithms), while at the same time allowing simultaneous exploration of different

parameter settings that are propagated from one task to all subsequent tasks in the

pipeline. HiC-bench also generates a variety of quality assessment plots and offers other

visualization options, such as generating genome browser tracks as well as snapshots

using HiCPlotter. We have built this platform with reproducibility in mind, as all tools,

versions and parameter settings are recorded throughout the analysis. HiC-bench is

released as open-source software and the source code is available on GitHub and

Zenodo (for details please refer to "Availability of data and material" section). Our team

provides installation and usage support.

Implementation

The HiC-bench workflow

HiC-bench is a comprehensive computational pipeline for Hi-C sequencing data analysis.

It covers all aspects of Hi-C data analysis, ranging from alignment of raw reads to

boundary-score calculation, TAD calling, boundary detection, annotation of specific

interactions and enrichment analysis. Thus, HiC-bench consists the most complete

computational Hi-C analysis pipeline to date (**Table 1**). Importantly, every step of the

pipeline includes summary statistics (when applicable) and direct comparative

visualization of the results. This feature is essential for quality control and facilitates

troubleshooting. The HiC-bench workflow (**Figure 1**) starts with the alignment of Hi-C

sequencing reads and ends with the annotation and enrichment of specific interactions.

More specifically, in the first step, the raw reads (fastq files) are aligned to the reference

genome using Bowtie2 [26] (*align*). The aligned reads are further filtered in order to

determine those Hi-C read pairs that will be used for downstream analysis (*filter*). A

detailed statistics report showing the numbers and percentages of reads assigned to the

different categories is automatically generated in the next step (*filter-stats*). The reads

that satisfy the filtering criteria are used for the creation of Hi-C contact matrices (*matrix-*

filtered). These contact matrices can either be directly visualized in the WashU

Epigenome Browser [27] as Hi-C tracks (*tracks*), or further processed using three

alternative matrix correction methods: (a) matrix scaling (*matrix-prep*), (b) iterative

correction (*matrix-ic*) [9] and (c) HiCNorm (*matrix-hicnorm*) [28]. As quality control, plots

of the average number of Hi-C interactions as a function of the distance between the

interacting loci are automatically generated in the next step (*matrix-stats*). The Hi-C

matrices, before and after matrix correction, are used as inputs in various subsequent

pipeline tasks. First, they are directly compared in terms of Pearson or Spearman

correlation (*compare-matrices* and *compare-matrices-stats*) in order to estimate the

similarity between Hi-C samples. Second, they are used for the calculation of boundary

scores (*boundary-scores* and *boundary-scores-pca*), identification of topological domains

(*domains*) and comparison of boundaries (*compare-boundaries* and *compare-*

boundaries-stats). Third, high-resolution Hi-C matrices are used for detection and

annotation of specific chromatin interactions (*interactions* and *annotations*), enrichment

analysis in transcription factors, chromatin marks or other segmented data (*annotation-*

stats) and visualization of chromatin interactions in certain genomic loci of interest

(*hicplotter*). We should note here that HiC-bench is totally extensible and customizable

as new tools can be easily integrated into the HiC-bench workflow (see User Manual for

more details). In addition to the multiple alternative tools that can be used to perform

certain tasks, HiC-bench allows simultaneous exploration of different parameter settings

that are propagated from one task to all subsequent tasks in the pipeline (for details

please refer to "Main concepts and pipeline architecture" section). For example, after

contact matrices are generated and corrected using alternative methods, HiC-bench

proceeds with TAD calling using all computed matrices as inputs (**Figure 1** and **Figure**

2A). This unique feature enables the design and execution of complex benchmark studies

that may include combinations of multiple tool/parameter choices in each step. HiC-bench

 focuses on the reproducibility of the analysis by keeping records of the source code, tool

 versions and parameter settings, and it is the only HiC-analysis pipeline that allows

 combinatorial parameter exploration facilitating benchmarking of Hi-C analyses.

176
177 **Table 1. Comparison of HiC-bench with published Hi-C analysis or visualization tools.**

Hi-C tasks	HiC-bench	HiFive	Hi-Cpipe	HiCNorm	hiclib	HiTC	HOMER	Hi-Corrector	HiC-Pro	TADbit	HiCUP	HiC-Box	HiCdat	HIPPIE	Sushi	HiCPlotter
alignment	x		x		x				x	x	x	x		x		
filtering	x	x	x		x				x	x	x	x		x		
genome browser tracks	x															
quality assessment plots	x	x	x			x			x		x		x	x		
contact matrices	x	x	x		x		x		x				x	x		
matrix correction	x	x		x	x	x	x	x	x	x			x	x		
matrix comparison	x												x			
boundary scores	x															
domains	x									x						
boundary comparison	x															
specific interactions	x		x		x		x		x		x	x	x	x		
annotations	x					x							x			
allele-specific interactions									x		x					
visualization	x	x	x			x	x						x		x	x
integration with ChIP-seq data	x												x	x		
parallelization	x	x	x				x	x	x	x						
integration of alternative tools	x															
parameter exploration	x															
reproducibility	x	x														

The HiC-bench toolkit

HiC-bench performs various tasks of Hi-C analysis ranging from read alignment to

annotation of specific interactions and visualization. We have developed two new tools,

gtools-hic and *hic-matrix*, to execute the multiple tasks in the HiC-bench pipeline, but we

have also integrated existing tools to allow comparative and complementary analyses and

facilitate benchmarking. More specifically, the alignment task is performed either with

Bowtie2 [26] or with the "align" function of *gtools-hic*, our newest addition to

GenomicTools [29]. Likewise, filtering, creation of Hi-C tracks and generation of Hi-C

contact matrices are performed using the functions "filter", "bin/convert" and "matrix" of

gtools-hic respectively. For advanced users, we have implemented a series of novel

features for these common Hi-C analysis tasks. For example, the operation "matrix" of

gtools-hic allows generation of arbitrary chimeric Hi-C contact matrices, a feature

particularly useful for the study of the effect of chromosomal translocations on chromatin

interactions. Another example is the generation of distance-restricted matrices (up to

some maximum distance off the diagonal) in order to save storage space and reduce

memory usage at fine resolutions. For matrix correction we use either published

algorithms (iterative correction (IC/ICE) [9], HiCNorm [28]) or our "naïve scaling" method

where we divide the Hi-C counts by (a) the total number of (usable) reads, and (b) the

"effective length" [8,28] of each genomic bin. We also integrated published TAD callers

like DI [5], Armatus [30], TopDom [31], insulation index (Crane) [32] and our own TAD

calling method (similar but not identical to contrast index [33,34]) implemented as the

"domains" operation in *hic-matrix*. Additionally, the "domains" operation produces

genome-wide boundary scores using multiple methods and allowing flexibility in choosing

parameters. Boundaries are simply defined as local maxima of the boundary scores. For

the detection of specific interactions, we introduce the "loops" function of *hic-matrix*, while

GenomicTools is used for annotation of these interactions with gene names, ChIP-seq

and other user-defined data. Finally, we implemented a wrapper for HiCPlotter, taking

advantage of its advanced visualization features in order to allow the user to quickly

generate snapshots of areas of interest in batch. The HiC-bench toolkit is summarized in

Table 2. All the tools we developed appear in bold. Further information on the toolkit is

provided in the User Manual found online and in the Supplemental Information section.

210
211   **Table 2. The HiC-bench toolkit.** The HiC-bench toolkit consists mostly of newly-developed tools
212   (shown in bold) but we have also incorporated existing tools to allow comparisons and
213   benchmarking.

Hi-C tasks	HiC-bench toolkit
alignment	bowtie2, **gtools-hic[align]**
filtering	**gtools-hic[filter]**
genome browser tracks	**gtools-hic[bin/convert]**
matrix generation	**gtools-hic[matrix]**
matrix correction	IC, HiCNorm, **hic-matrix[preprocess/normalize]**
boundary scores	**hic-matrix[domains]**
domain calling	DI, Armatus, TopDom, **hic-matrix[domains]**
interactions	**hic-matrix[loops]**
annotations	**genomic-tools**
visualization	HiCPlotter

214
Main concepts and pipeline architecture

We built our platform based on principles outlined in scientific workflow systems such as

Kepler [35], Taverna [36] and VisTrails [37]. The main idea behind our platform is the

ability to track data provenance [37,38], the origin of the data, computational tasks, tool

versions and parameter settings used in order to generate a certain output (or collection

of outputs) from a given input (or collection of inputs). Thus, our pipeline ensures

reproducibility which is a particularly important feature for such a complex computational

task. In addition, HiC-bench enables combinatorial analysis and parameter exploration by

implementing the idea of computational "trails": a unique combination of inputs, tools and

parameter values can be imagined as a unique (computational) trail that is followed

simultaneously with all the other possible trails in order to generate a collection of output

objects (**Figure 2A**). Our platform consists of three main components: (a) data, (b) code

and (c) pipelines. These components are organized in respective directories in our local

repository, and synchronized with a remote GitHub repository for public access. The data

directory is used to store data that would be used by any analysis, for example genome-

related data, such as DNA sequences and indices (e.g. Bowtie2), gene annotations and,

in general, any type of data that is required for the analysis. The code directory is used to

store scripts, source code and executables. More details about the directory structure can

be found in the User Manual. Finally, the "pipelines" directory is used to store the structure

of each pipeline. Here, we will focus on our Hi-C pipeline, but we have also implemented

a ChIP-seq pipeline, which is very useful for integrating CTCF and histone modification

ChIP-seq data with Hi-C data. The structure of the pipeline is presented to the user as a

numbered list of directories, each one corresponding to one operation (or task) of the

pipeline. As shown in **Figure 1**, our Hi-C pipeline currently consists of several tasks

starting with alignment and reaching completion with the identification and annotation of

specific DNA-DNA interactions and annotations with ChIP-seq and other genome-wide

data (see also **Table 2** and **Supplemental Table 1**). We will examine these tasks in detail

in the Results section of this manuscript.

243
Parameter exploration, input and output objects

In conventional computational pipelines, several computational tasks (operations) are

executed on their required inputs. However, in existing genomics pipelines, each task

generates a single result object (e.g. TAD calling using one method with fixed parameter

settings) which is then used by downstream tasks. To allow full parameter (and

method/tool) exploration, we introduce instead a data flow model, where every task may

accommodate an arbitrary number of output objects. Downstream tasks will then operate

on all computed objects generated by the tasks they depend on. Pipeline tasks are

implemented as shown in the diagram of **Figure 2B**. First, input objects are filtered

according to user-specified criteria (e.g. TAD calling is only done for Hi-C contact matrices

at 40kb resolution). Then, *pipeline-master-explorer* (implemented as an R script; see User

Manual for usage and input arguments) generates the commands that create all desired

output objects. In principle, all combinations of input objects with all parameter settings

will be created, subject to user-defined filtering criteria. In the interest of extensibility, new

pipeline tasks can be conveniently implemented using a single-line *pipeline-master-*

explorer command (see **Supplemental Table 2**), provided that wrapper scripts for each

task (e.g. TAD calling using TopDom) have been properly set up. In the simplest scenario,

any task in our pipeline will generate computational objects for each combination of

parameter file and input objects obtained from upstream tasks. For example, suppose the

aligned reads from 12 Hi-C datasets are filtered using three different parameter settings,

and that we need to create contact matrices at four resolutions (1Mb, 100kb, 40kb and

10kb). Then, the number of output objects (contact matrices in this case) will be 144 (i.e.

12 x 3 x 4). Although many computational scenarios can be realized by this simple one-

to-one mapping of input-output objects, more complex scenarios are frequently

encountered, as described in the next section.

Filtering, splitting and grouping input objects into new output objects

Oftentimes, a simple one-to-one mapping of input objects to output objects is not

desirable. For this reason, we introduce the concepts of filtering, splitting and grouping of

input objects which are used to modify the behavior of pipeline-master-explorer (see

Figure 2B). *Filtering* is required when some input objects are not relevant for a given

task, e.g. TAD calling is not performed on 1Mb-resolution contact matrices, and specific

DNA-DNA interactions are not meaningful for resolutions greater than 10-20kb. *Splitting*

is necessary in some cases: for example, we split the input objects by genome assembly

(hg19, mm10) when comparing contact matrices or domains across samples, since only

matrices or domains from the same genome assembly can be compared directly. In our

platform, the user is allowed to split a collection of input objects by any variable contained

in the sample sheet (except fastq files), thus allowing user-defined splits of the data, such

as by cell type or treatment. Complementary to the splitting concept, *grouping* permits the

aggregation of a collection of input objects (sharing the same value of a variable defined

in the sample sheet) into a single output object. For example, the user may want to create

genome browser tracks or contact matrices of combined technical and/or biological

replicates, or group all input objects (samples) together in tasks such as Principal

Component Analysis (PCA) or alignment/filtering statistics.

Combinatorial objects

Even after introducing the concepts described above, more complex scenarios are

possible as some tasks require the input of pairs (or triplets etc.) of objects. This feature

has also been implemented in our pipeline (tuples in **Figure 2B**) and is currently used in

the *compare-matrices* and *compare-boundaries* tasks. However, it should be utilized

wisely (for example in conjunction with filtering, splitting and grouping) because it may

lead to a combinatorial "explosion" of output objects.

296
Parameter scripts

The design of our platform is motivated by the need to facilitate the use of different

parameter settings for each pipeline task. For this reason, we have implemented wrapper

scripts for each tool/method used in each task. For example, we have implemented a

wrapper script for alignment, filtering, correcting contact matrices using IC or HiCNorm

(separate wrappers), TAD calling using Armatus [30], TopDom [31], DI [5] and insulation

index (Crane) [32] (separate wrappers). The main motivation is to hide most of the

complexity inside the wrapper script and allow the user to modify the parameters using a

simple but flexible parameter script. Unlike static parameter files, parameter scripts allow

for dynamic calculation of parameters based on certain input variables (e.g. enzyme

name, group name etc.). Within this framework, by adding and/or modifying simple

parameter scripts, the user can explore the effect of different parameters (a) on the task

directly affected by these parameters, and (b) on all dependent downstream tasks.

Additionally, these parameter scripts serve as a record of parameters and tool versions

that were used to produce the results, facilitating analysis reproducibility as well as

documentation in scientific reports and manuscripts.

Results stored as computational trails

All the concepts described above have been implemented in a single R script named

pipeline-master-explorer. This script maintains a database of input-output objects for each

task, stored in a hidden directory under results (results/.db). It also creates a "run" script

which is executed in order to generate all the desired results. All results are stored in the

results directory in a tree structure that reveals the computational trail for each object (see

examples shown in **Figure 2B** and **Supplementary Table 2**). Therefore, the user can

easily infer how each object was created, including what inputs and what parameters

were used.

323
Initiating a new reproducible analysis

In the interest of data analysis reproducibility, any new analysis requires creating a copy

of the code and pipeline structure into a desired location, effectively creating a branch.

This way, any changes in the code repository will not affect the analysis and conversely,

the user can customize the code according to the requirements of each project without

modifying the code repository. Copying of the code and initiating a new analysis is done

simply by invoking the script "*pipeline-new-analysis.tcsh*" as described in the User

Manual.

332
Pipeline tasks

A pipeline consists of a number of (partially) ordered tasks that can be described by a

directed acyclic graph which defines all dependencies. HiC-bench implements a total of

20 tasks as shown in the workflow of **Figure 1**. In the analysis directory structure, each

task is assigned its own subdirectory found inside the pipeline directory starting from the

top level. This directory includes a symbolic link to the inputs of the analysis (fastq files,

sample sheet, etc.), a link to the code, a directory (*inpdirs*) containing links to all

dependencies, a directory containing parameter scripts (see below) and a "*run*" script

which can be used to generate all the results of this task. The "*run*" scripts of each task

are executed in the specified order by the master "*run*" script located at the top level (see

User Manual for details on pipeline directory structure).

Input data and the sample sheet

Before performing any analysis, a computational pipeline needs input data. All input data

for our pipeline tasks are stored in their own "*inputs*" directory accessible at the top level

(along with the numbered pipeline tasks) and via symbolic links from within the directories

assigned to each task to allow easy access to the corresponding input data. A "*readme*"

file explains how to organize the input data inside the inputs directory (see User Manual

for details). Briefly, the *fastq* subdirectory is used to store all fastq files, organized into

one subdirectory per sample. Then, the sample sheet needs to be generated. This can

be done automatically using the "*create-sample-sheet.tcsh*" script, but the user can also

manually modify and expand the sample sheet with features beyond what is required.

Currently required features are the sample name (to be used in all downstream analyses),

fastq files (R1 and R2 in separate columns), genome assembly version (e.g. hg19, mm10)

and restriction enzyme name (e.g. HindIII, NcoI). Adding more features, such as different

group names (e.g. sample, cell type, treatment), allows the user to perform more

sophisticated downstream analyses, such as grouping replicates for generating genome

browser tracks, or splitting samples by genome assembly to compare boundaries (see

previous section on grouping and splitting).

362
Executing the pipeline

The entire pipeline can be executed automatically by the "*pipeline-execute.tcsh*" script,

as shown below:

code/code.main/pipeline-execute <project name> <user e-mail address>

where <project name> will be substituted by the name of the project and <user e-mail

address> by the preferred e-mail address of the person who runs the analysis in order to

be notified upon completion. The "*pipeline-execute.tcsh*" script essentially executes the

"run" script for each task (following the specified order). At the completion of every task,

the log files of all finished jobs are inspected for error messages. If error messages are

found, the pipeline aborts with an error message.

Timestamping

Besides creating the "*run*" script used to generate all results, the "*pipeline-master-*

explorer.r" script, also checks whether existing output objects are up-to-date when

compared to their dependencies (i.e. input objects and parameter scripts; can be

expanded to include code dependencies as well). Currently, the pipelines are set up so

that out-of-date objects are not deleted and recomputed automatically, but only presented

to the user as a warning. The user can then choose to delete them manually and re-

compute. The reason for this is to protect the user against accidentally repeating

computationally demanding tasks (e.g. alignments) without given first the chance to

review why certain objects may be out-of-date. From a more philosophical point of view,

and in the interest of keeping a record of all computations (when possible), the user may

never want to modify parameter files or the code for a given project, but instead only add

new parameter files. Then, no object will be out-of-date, and only new objects will need

to be recomputed every time.

388
Alignment and filtering

Paired-end reads were mapped to the reference genome (hg19 or mm10) using Bowtie2

[26]. Reads with low mapping quality (MAPQ<30) were discarded. Local alignments of

input read pairs were performed as they consist of chimeric reads between two (non-

consecutive) interacting fragments. This approach yielded a high percentage of mappable

reads (> 95%) for all datasets (**Supplementary Figure 1**). Mapped read pairs were

subsequently filtered for known artifacts of the Hi-C protocol such as self-ligation,

mapping too far from the enzyme's known cutting sites etc. More specifically, reads

mapping in multiple locations on the reference genome (*multihit*), double-sided reads that

mapped to the same enzyme fragment (*ds-same-fragment*), reads whose 5'-end mapped

too far (*ds-too-far*) from the enzyme cutting site, reads with only one mappable end

(*single-sided*) and unmapped reads (*unmapped*), were discarded. Read pairs that

corresponded to regions that were very close (less than 25 kilobases, *ds-too-close*) in

linear distance on the genome as well as duplicate read pairs (*ds-duplicate-intra* and *ds-*

duplicate-inter) were also discarded. In **Supplementary Figure 1**, we show detailed

paired-end read statistics for the Hi-C datasets used in this study. We include the read

numbers (**Supplementary Figure 1A**) and their corresponding percentages

(**Supplementary Figure 1B**). Eventually, approximately 10-50% of paired-reads passed

all filtering criteria and were used for downstream analysis (**Supplementary Figure 1B**).

The statistics report is automatically generated for all input samples. The tools and

parameter settings used for the alignment and filtering tasks are fully customizable and

can be defined in the corresponding parameter files.

411
Contact matrix generation, normalization and correction

The read-pairs that passed the filtering task were used to create Hi-C contact matrices

for all samples. The elements of each contact matrix correspond to pairs of genomic

"bins". The value in each matrix element is the number of read pairs aligning to the

corresponding genomic regions. In this study, we used various resolutions, ranging from

fine (10kb) to coarse (1Mb). The resulting matrices either remained unprocessed

(filtered), or they were processed using different correction methods including HiCNorm

[28], iterative correction (IC or ICE) [9] as well as "naïve scaling". In **Supplementary**

Figure 2, we present the average Hi-C count as a function of the distance between the

interacting fragments, separately for each Hi-C matrix for not corrected (filtered) and IC-

corrected matrices.

423
Comparison of contact matrices

Our pipeline allows direct comparison and visualization of the generated Hi-C contact

matrices. More specifically, using our *hic-matrix* tool, all pairwise Pearson and Spearman

correlations were automatically calculated for each (a) input sample, (b) resolution, and

(c) matrix correction method. The corresponding correlograms were automatically

generated using the corrgram R package [39]. A representative example is shown in

Supplementary Figure 3. The correlograms summarizing the pairwise Pearson

correlations for all samples used in this study are presented before and after matrix

correction using the iterative correction algorithm. These plots are very useful because

the user can quickly assess the similarity between technical and biological replicates as

well as differences between various cell types. As shown before (Supplementary Figure

3 in [5]), iterative correction improves the correlation between enzymes at the expense of

a decreased correlation between samples prepared using the same enzyme.

Boundary scores

Topological domains (TADs) are defined as genomic neighborhoods of highly interacting

chromatin, with relatively more infrequent inter-domain interactions [5,40,41]. Topological

domains are demarcated by boundaries, i.e. genomic regions bound by insulators thus

hampering DNA contacts across adjacent domains. For each genomic position, in a given

resolution (typically 40kb or less), we define a "boundary score" to quantify the insulation

strength of this position. The higher the boundary score, the higher the insulation strength

and the probability that this region actually acts as a boundary between adjacent domains.

The idea of boundary scores is further illustrated in **Supplementary Figure 4**, where two

adjacent TADs are shown. The upstream TAD on the left (L) is separated from the

downstream TAD on the right (R) by a boundary (black circle). We define two parameters,

the distance from the diagonal of the Hi-C contact matrix to be excluded from the

boundary score calculation (δ) (not shown) and the maximum distance from the diagonal

to be considered (d). The corresponding parameter values can be selected by the user.

For this analysis, we used δ=0 and d=2Mb as suggested before [5]. In addition to the

published directionality index [5], we defined and computed the "*inter*", "*intra-max*" and

"*ratio*" scores, defined as follows:

$$\text{inter} = \text{mean}(X)$$

$$\text{intra}_{max} = \max(\text{mean}(L), \text{mean}(R))$$
$$\text{ratio} = \text{intra}_{max}/\text{inter}$$

456
457
458
459 Principal component analysis (PCA) of boundary scores across samples in this study,

460 before and after matrix correction, shows that biological replicates tend to cluster

461 together, either in the case of filtered or corrected (IC) matrices (**Supplementary Figure**

462 **5**).

463
Topological domains

Topologically-associated domains (TADs) are increasingly recognized as an important

feature of genome organization [5]. Despite the importance of TADs in genome

organization, very few Hi-C pipelines have integrated TAD calling (e.g. TADbit [19]). In

HiC-bench, we have integrated TAD calling as a pipeline task and we demonstrate this

integration using different TAD callers: (a) Armatus [30], (b) TopDom [31], (c) DI [5], (d)

insulation index (Crane) [32] and (e) our own hic-matrix (domains). Our pipeline makes it

straightforward to plug in additional TAD callers, by installing these tools and setting up

the corresponding wrapper scripts. HiC-bench also facilitates the direct comparison of

TADs across samples by automatically calculating the number of TAD boundaries and all

the pairwise overlaps of TAD boundaries across all inputs, generating the corresponding

graphs (as in the case of matrix correlations described in a previous section). We define

boundary overlap as the ratio of the intersection of boundaries between two replicates (A

and B) over the union of boundaries in these two replicates, as shown in the equation

below:

$$\text{boundary\_overlap} = (A \cap B)/(A \cup B)$$

For the boundary overlap calculation, we extended each boundary by 40kb on both sides

(+/-40kb flanking region, i.e. the size of one bin). The fact that HiC-bench allows

simultaneous exploration of all parameter settings for all installed TAD-calling algorithms,

greatly facilitates parameter exploration, optimization as well as assessment of algorithm

effectiveness. Pairwise comparison of boundaries (boundary overlaps) across samples is

shown in **Figure 3** and **Supplementary Figure 6**.

Visualization

In our pipeline, we also take advantage of the great visualization capabilities offered by

the recently released HiCPlotter [23], in order to allow the user to visualize Hi-C contact

matrices along with TADs (in triangle format) for multiple genomic regions of interest. The

user can also add binding profiles in BedGraph format for factors (e.g. CTCF), boundary

scores, histone marks of interest (e.g. H3K4me3, H3K27ac) etc. An example is shown in

Supplementary Figure 7, where an area of the contact matrix of human embryonic stem

cells (H1) (HindIII) is presented along with the corresponding TADs (triangles), various

boundary scores, the CTCF binding profile and annotations of selected genomic

elements, before and after matrix correction (IC). The integration of HiCPlotter in our

pipeline, allows the user to easily create publication-quality figures for multiple areas of

interest simultaneously.

499
Specific interactions, annotations and enrichments

The plummeting costs of next-generation sequencing have resulted in a dramatic

increase in the resolution achieved in Hi-C experiments. While the original Hi-C study

reported interaction matrices of 1Mb resolution [2], recently 1kb resolution was reported

[42]. Thus, the characterization and annotation of specific genomic interactions from Hi-

C data is an important feature of a modern Hi-C analysis pipeline. HiC-bench generates

a table of the interacting loci based on parameters defined by the user. These parameters

include the resolution, the lowest number of read pairs required per interacting area as

well as the minimum distance between the interacting partners. The resulting table

contains the coordinates of the interacting loci, the raw count of interactions between

them, the number of interactions after "scaling" and the number of interactions between

the partners after distance normalization (observed Hi-C counts normalized by expected

counts as a function of distance). This table is further annotated with the gene names or

the factors (e.g. CTCF) and histone modification marks (e.g. H3K4me1, H3K27ac,

H3K4me3) that overlap with the interacting loci. The user can provide bed files with the

features of interest to be used for annotation. As an example, the enrichment of chromatin

marks in the top 50000 chromatin interactions in the H1 and IMR90 samples is presented

in **Supplementary Figure 8**.

Software requirements

The main software requirements are: Bowtie2 aligner [26], Python (2.7 or later) (along

with Numpy, Scipy and Matplotlib libraries), R (3.0.2) [43] and various R packages (lattice,

RColorBrewer, corrplot, reshape, gplots, preprocessCore, zoo, reshape2, plotrix,

pastecs, boot, optparse, ggplot2, igraph, Matrix, MASS, flsa, VennDiagram, futile.logger

and plyr). More details on the versions of the packages can be found in the User Manual

(sessionInfo()). In addition, installation of mirnylib Python library [44] is required for matrix

balancing based on IC (ICE). The pipeline has been tested on a high-performance

computing cluster based on Sun Grid Engine (SGE). The operating system used was

Redhat Linux GNU (64 bit).

Results

We used HiC-bench to analyze several published Hi-C datasets and the results of our

analysis are presented below. Additionally, we performed a comprehensive benchmark

of existing and new TAD callers exploring different matrix correction methods, parameter

settings and sequencing depths. Our results can be reproduced by re-running the

corresponding pipeline snapshot available upon request as a single compressed archive

file (too big to include as a Supplemental file).

Comprehensive reanalysis of available Hi-C datasets using HiC-bench

Our platform is designed to facilitate and streamline the analysis of a large number of

available Hi-C datasets in batch. Thus, we collected and comprehensively analyzed

multiple Hi-C samples from three large studies [5,42,45]. From the first study we analyzed

IMR90 (HindIII) samples, from the second we analyzed Hi-C samples from

lymphoblastoid cells (GM12878), human lung fibroblasts (IMR90 (MboI)),

erythroleukemia cells (K562), chronic myelogenous leukemia (CML) cells (KBM-7) and

keratinocytes (NHEK), and from the third one, we analyzed samples from human

embryonic stem cells (H1) and all the embryonic stem-cell derived lineages mentioned,

including mesendoderm, mesenchymal stem cells, neural progenitor cells and

trophectoderm cells. All datasets yielded at least 40 million usable intra-chromosomal

read pairs in at least two biological replicates. We performed extensive quality control on

all datasets, calculating the read counts and percentages per classification category

(**Supplementary Figure 1**), the attenuation of Hi-C signal over genomic distance

(**Supplementary Figure 2**), the correlation of Hi-C matrices before and after matrix

correction (**Supplementary Figure 3**), the similarity of boundary scores (**Supplementary**

Figure 5) and all pairwise boundary overlaps across samples (**Supplementary Figure**

6). In addition, we performed a comprehensive benchmarking of our own and published

TAD callers, across all reanalyzed Hi-C datasets. The results of our benchmark are

presented in the following sections.

Iterative correction of Hi-C contact matrices improves reproducibility of TAD
boundaries
560
Iterative correction has been shown to correct for known biases in Hi-C [9]. Thus, we

hypothesized that IC may increase the reproducibility of TAD calling. We performed a

comprehensive analysis calculating the TAD boundary overlaps for biological replicates

of the same sample (as described in Methods section), using different TAD callers and

different main parameter values for each TAD caller (**Figure 3A**). After comparing TAD

boundary overlaps between filtered (uncorrected) and IC-corrected matrices, we

observed an improvement in the boundary overlap when corrected matrices were used,

irrespective of TAD caller and parameter settings (**Figure 3B)**. The only exception was

DI. Careful examination of the overlaps per sample revealed that IC introduced outliers

only in the case of DI (in general, the opposite was true for the other callers). We

hypothesize that IC may occasionally negatively affect the computation of the

directionality index, especially because its calculation depends on a smaller number of

bins (1-dimensional line) compared to the rest of the methods (2-dimensional triangles).

In addition to the increase in the mean value of boundary overlap upon correction, we

observed that the standard deviation of boundary overlaps among replicates decreased

(again, with the exception of DI) (**Figure 3C**). While this seems to be the trend for almost

all TAD caller/parameter value combinations, the effect of correction in variance is more

profound in certain cases (e.g. hicintra-max) than others. It is also worth mentioning that

increased size of the insulation window (in the case of Crane), the resolution parameter

γ (Armatus) or the distance d (hicinter, hicintra-max, hicratio) may result in certain cases

in increased boundary overlap (e.g. Armatus), but this is not generalizable (e.g. hicintra-

max). Interestingly, increased TAD boundary overlap does not necessarily mean

increased consistency in the number of predicted TADs across sample types, as would

be expected since TADs are largely invariant across cell types [5]. For example, the TAD

calling algorithm which is based on insulation score (Crane), predicted similar TAD

overlaps and similar TAD numbers for different insulation windows (ranging from 0.5Mb

to 2Mb), whereas Armatus performed well in terms of TAD boundary reproducibility

(**Figure 3A**) but the corresponding predicted TAD numbers varied considerably (**Figure**

3D). This may be partly due to the nature of the Armatus algorithm, as it has been built to

reveal multiple levels of chromatin organization (TADs, sub-TADs etc.). We conclude that

while iterative correction improves the reproducibility of TAD boundary detection across

replicates, the number of predicted TADs should be also taken into account when

selecting TAD calling method for downstream analysis. The method of choice should be

the one that is robust in terms of both reproducibility and number of predicted TADs.

Increased sequencing depth improves the reproducibility of TAD boundaries

After selecting the parameter setting that optimized TAD boundary overlap between

biological replicates of the same sample per TAD caller, we also investigated the effect

of sequencing depth on the reproducibility of TAD boundary detection. Since some of the input samples were limited to only 40 million usable intra-chromosomal Hi-C read pairs, we resampled 10 million, 20 million and 40 million read pairs from each sample and evaluated the effect of increasing sequencing depth on TAD boundary reproducibility. The results are depicted in **Figure 4A**. We noticed that increased sequencing depth resulted in increased TAD boundary overlap, regardless of the TAD calling algorithm used (**Figure 4A,C**). As far as the TAD numbers are concerned, increased sequencing depth decreased TAD number variability for certain callers (e.g. hicratio) but not in all cases (e.g. Armatus) (**Figure 4B**). In many cases, increased sequencing depth, decreased the variance of TAD boundary overlap among replicates (**Figure 4C**). In summary, based on this benchmark, we recommend that Hi-C samples should be sufficiently sequenced as sequencing depth seems to affect TAD calling reproducibility.

Conclusions

Recently, several computational tools and pipelines have been developed for Hi-C analysis. Some focus on matrix correction, others on detection of specific chromatin interactions and their differences across conditions and others on visualization of these interactions. However, very few of these tools offer a complete Hi-C analysis (e.g. HiC-Pro), addressing tasks which range from alignment to interaction annotation. HiC-bench is a comprehensive Hi-C analysis pipeline with the ability to process many samples in parallel, record and visualize the results in each task, thus facilitating troubleshooting and further analyses. It integrates both existing tools but also new tools that we developed to perform certain Hi-C analysis tasks. In addition, HiC-bench focuses on parameter exploration, reproducibility and extensibility. All parameter settings used in each pipeline

task are automatically recorded, while future tools can be easily added using the supplied

wrapper template. More importantly, HiC-bench is the only Hi-C pipeline so far that allows

extensive parameter exploration, thus facilitating direct comparison of the results obtained

by different tools, methods and parameters. This unique feature helps users test the

robustness of the analysis, optimize the parameter settings and eventually obtain reliable

and biologically meaningful results. To demonstrate the usefulness of HiC-bench, we

performed a comprehensive benchmark of popular and newly-introduced TAD callers,

varying the matrix preprocessing (filtered or corrected matrices with IC method), the

sequencing depth, and the value of the main parameter of each TAD caller, which is

usually the window used for the calculation of directionality index or insulation score. We

found that the matrix correction has a positive effect on the boundary overlap between

replicates and that increased sequencing depth leads to higher boundary overlap.

In conclusion, HiC-bench is an easy-to-use framework for systematic, comprehensive,

integrative and reproducible analysis of Hi-C datasets. We expect that use of our platform

will facilitate current analyses and enable scientists to further develop and test interesting

hypotheses in the field of chromatin organization and epigenetics.

List of abbreviations

642 **DI:** directionality index

643 **IC or ICE:** iterative correction

644 **PCA:** Principal Component Analysis

645 **TAD:** Topological Domain or Topologically Associating Domain

Ethics approval and consent to participate

648   Not applicable.

Consent for publication

651   Not applicable.

Availability of data and material

Published Hi-C data were downloaded from Gene Expression Omnibus, using the

corresponding accession numbers: GSE35156 [5], GSE63525 [42] and GSE52457 [45].

HiC-bench source code is freely available on GitHub and Zenodo.

Project name: HiC-bench

Project home page: https://github.com/NYU-BFX/hic-bench/wiki

Archived version: https://zenodo.org/badge/latestdoi/20915/NYU-BFX/hic-bench

Operating system: Redhat Linux GNU (64 bit)

Programming language: R, C++, Python, Unix shell scripts

Other requirements: mentioned in "Software requirements" section and the manual.

License: MIT

Any restrictions to use by non-academics: None

Competing interests

666   The authors have no competing interests to declare.

Funding

669   The study was supported by a Research Scholar Grant, RSG-15-189-01 - RMC from the

670   American Cancer Society and a Leukemia & Lymphoma Society New Idea Award, 8007-

671   17 to Aristotelis Tsirigos (AT). NYU Genome Technology Center (GTC) is a shared

672   resource, partially supported by the Cancer Center Support Grant, P30CA016087, at the

673   Laura and Isaac Perlmutter Cancer Center

Author contributions

676   CL performed computational analyses, generated figures and implemented certain

677   wrapper scripts. SK wrote the user manual. PN and IA offered biological insights and

678   helped with the interpretation of Hi-C data. AT designed and implemented the pipeline.

679   CL and AT wrote the manuscript.

Acknowledgements

Aristotelis Tsirigos was supported by a Research Scholar Grant, RSG-15-189-01 - RMC

from the American Cancer Society and a Leukemia & Lymphoma Society New Idea

Award, 8007-17. We would like to thank Dennis Shasha and Juliana Freire for inspiring

discussions on data flows. We would also like to thank Kadir Caner Akdemir for useful

discussions on the usage of HiCPlotter. We also like to thank the NYU Applied

Bioinformatics Laboratories for providing bioinformatics support and helping with the

analysis and interpretation of the data. This work has used computing resources at the

High Performance Computing Facility (HPCF) at the NYU Langone Medical Center.

Figure legends

Figure 1. HiC-bench workflow. Raw reads (input fastq files) are aligned and then filtered

(*align* and *filter* tasks). Filtered reads are used for the creation of Hi-C track files (*tracks*)

that can be directly uploaded to the WashU Epigenome Browser [27]. A report with a

statistics summary of filtered Hi-C reads, is also automatically generated (*filter-stats*).

Raw Hi-C matrices (*matrix-filtered*) are normalized using (a) scaling, (b) iterative

correction [9] or (c) HiCNorm [28]. A report with the plots of the normalized Hi-C counts

as function of the distance between the interacting partners (*matrix-stats*) is automatically

generated for all methods. The resulting matrices are compared across all samples in

terms of Pearson and Spearman correlation (*compare-matrices* and *compare-matrices-*

stats). Boundary scores are calculated and the corresponding report with the Principal

Component Analysis (PCA) is automatically generated (*boundary-scores* and *boundary-*

scores-pca). Domains are identified using various TAD calling algorithms (*domains*)

followed by comparison of TAD boundaries (*compare-boundaries* and *compare-*

boundaries-stats). A report with the statistics of boundary comparison is also

automatically generated. Hi-C visualization of user-defined genomic regions is performed

using HiCPlotter (*hicplotter*) [23]. Specific chromatin interactions (*interactions*) are

detected and annotated (*annotations*). Finally, enrichment of top interactions in certain

chromatin marks, transcription factors etc. provided by the user, is automatically

calculated (*annotations-stats*).

Figure 2. (A) Computational trails. Each combination of tools and parameter settings

can be imagined as a unique computational "trail" that is executed simultaneously with all

the other possible trails to create a collection of output objects. As an example, one of

these possible trails is presented in red. The raw reads were aligned, filtered and then

binned in 40kb resolution matrices. Our own naïve matrix scaling method was then used

for matrix correction and domains were called using TopDom [31]. **(B) HiC-bench**

pipeline task architecture. All pipeline tasks are performed by a single R script,

"*pipeline-master-explorer.r*". This script generates output objects based on all

combinations of input objects and parameter scripts while taking into account the split

variable, group variable and tuple settings. The output objects are stored in the

corresponding "*results*" directory. As an example, domain calling for IMR90 is presented.

The filtered reads of the IMR90 Hi-C sample (digested with HindIII) are used as input.

The pipeline-master-explorer script tests if TAD calling with these settings has been

performed and if not it calls the domain calling wrapper script (*code/hicseq-domains.tcsh*)

with the corresponding parameters (e.g. *params/params.armatus.gamma_0.5.tcsh*).

After the task is complete, the output is stored in the corresponding "results" directory.

Figure 3. Comparison of topological domain calling methods subject to Hi-C

contact matrix preprocessing by simple filtering or iterative correction (**IC**). The

methods were assessed in terms of boundary overlap between replicates (**A**), change

(%) in mean boundary overlap after matrix correction (**B**), change (%) in standard

deviation of mean overlap across replicates after matrix correction (**C**) and number of

identified topological domains per cell type (**D**). The different colors correspond to the

different callers. Gradients of the same color are used for the different values of the same

parameter, ranging from low (light color) to high (dark color) values. The TAD callers

along with the corresponding parameter settings are presented in the legend. For this

analysis all available read pairs were used.

Figure 4. **Comparison of topological domain calling methods for different**

preprocessing method and sequencing depth. TAD calling methods were assessed

in terms of boundary overlap between replicates (**A**), number of identified topological

domains (**B**) and boundary overlap across replicates upon increasing sequencing depth

(**C**) for different matrix preprocessing (filtered and IC corrected) and different sequencing

depths (10 million, 20 million and 40 million reads). For TAD calling, only the optimal

caller/parameter value pairs are shown (defined as the ones achieving the maximum

boundary overlap for IC and 40 million reads). The boxplot and line colors correspond to

the different TAD callers.

Supplementary Figure 1. Hi-C reads filtering statistics. Number **(A)** and percentage

(**B**) of the various read categories identified during filtering for all datasets used in the

study. Mappable reads were over 95% in all samples. Duplicate (*ds-duplicate-intra* and

ds-duplicate-inter; red and pink), non-uniquely mappable (*multihit*; light blue) and single-

end mappable (*single-sided*; dark blue) reads were discarded. Self-ligation products (*ds-*

same-fragment) and reads mapping too far (*ds-too-far*; light purple) from restriction sites

or too close to one another (*ds-too-close*; orange) were also discarded. Only double-sided

uniquely mappable *cis* (*ds-accepted-intra*; dark green) and *trans* (*ds-accepted-inter*; light

green) read pairs were used for downstream analysis. The *x* axis represents either the

raw read number (A) or the percentage of reads (B) falling within each of the categories

described in the legend. The *y* axis represents the samples.

Supplementary Figure 2. Matrix statistics. Normalized Hi-C counts are presented as a

function of the distance between the interacting partners for all samples and correction

methods. The Hi-C samples analyzed were GM12878 (light blue), hESCs (H1) (blue),

mesenchymal cells (light green), mesendoderm (dark green), neural progenitors (pink),

trophectoderm (red), IMR90 (light and dark orange), K562 (light purple), KBM7 (dark

purple) and NHEK (yellow). The matrices were either unprocessed (filtered) (top) or

corrected using IC (bottom). The *y* axis represents the normalized count of Hi-C

interactions and the *x* axis the distance between the interacting partners in kilobases.

Supplementary Figure 3. Pairwise Pearson correlation of Hi-C matrices.

Correlograms summarizing all pairwise Pearson correlations for all Hi-C samples used in

this study: raw (filtered) matrices (left panel) and matrices after iterative correction (right

panel). Dark red indicates strong positive correlation and dark blue strong negative. The

resolution of the matrices is 40kb.

Supplementary Figure 4. Boundary score calculation. Two adjacent topological

domains (red triangles) are depicted. The left domain (*L*) is separated from the right

domain (*R*) by a boundary (black circle). The areas of more-frequent intra-domain

interactions are in red. The area of less-frequent cross-domain (or inter-domain)

interactions is *X*. We also introduce parameter *d* which is the maximum distance from the

diagonal to be considered for the calculation of boundary scores (default value: *d*=2Mb).

Supplementary Figure 5. Principal component analysis of boundary scores.

Boundary scores were calculated using *ratio* score, for all samples either before (filtered)

(left panel) or after iterative correction (IC) (right panel).

Supplementary Figure 6. Pairwise overlaps of TAD boundaries. The pairwise

overlaps of TAD boundaries are shown for all samples of this study, after calling

boundaries using hicratio (all reads, *d*=0500). Before TAD calling, the Hi-C matrices were

either unprocessed (filtered) or corrected using iterative correction (IC) (resolution =

40kb).

Supplementary Figure 7. Visualization of TADs and certain areas of interest. HiC-bench integrates HiCPlotter [23] and it offers the ability to easily prepare publication-quality figures. We present the area surrounding *NANOG*, a gene of particular importance for the maintenance of pluripotency. The Hi-C matrix corresponding to the chr12:3940389-11948655 genomic region is presented for H1 cells, before and after matrix correction. The matrix is also rotated 45° to facilitate TAD visualization. Various boundary scores (intra-max, DI, ratio) are shown as individual tracks along with CTCF binding. The location of *NANOG* is presented as a blue line.

Supplementary Figure 8. Enrichment of chromatin interactions in human fibroblasts (IMR90) and embryonic stem cells (H1). The enrichment of certain chromatin marks and CTCF in the top 50000 chromatin interactions in the IMR90 and H1 samples is shown. Deep blue and larger circle size indicate higher enrichment.

Table legends

Table 1. Comparison of HiC-bench with published Hi-C analysis or visualization tools. HiC-bench is a comprehensive and feature-rich Hi-C analysis pipeline that performs various Hi-C tasks by combining our newly-developed tools with existing tools.

Table 2. The HiC-bench toolkit. The HiC-bench toolkit consists mostly of newly-developed tools (shown in bold) but we have also incorporated existing tools to allow comparisons and benchmarking.

Supplementary Table 1. HiC-bench task implementation. The table summarizes how the pipeline tasks are implemented, which are the requirements for their execution and

how they are handled by the *pipeline-master-explorer* script. The first column lists all the

tasks performed by pipeline ranging from alignment to annotation. The second column

lists the input directory required for each task while the third one lists the parameter files.

Certain tasks depend on the reference genome (human or mouse), thus the genome

assembly acts as split variable (column 4). In some tasks, replicates can be grouped

using the group variable (column 5). Pairwise comparisons between replicates or samples

are also allowed using tuples (column 6). The last column lists the full pipeline-master-

explorer command for each pipeline task.

Supplementary Table 2. HiC-bench input-output objects. The table summarizes the

inputs and outputs of the TAD-calling task using three different methods with parameter

values stored in the params files (column 2). The first column describes the tree structure

of the input directories that are essentially the different Hi-C matrices for each sample,

before (filtered) and after matrix correction using different methods (e.g. IC). The second

column lists all the different parameter scripts and the third column corresponds to the

tree structure of the generated output objects.

References

1. Dekker J, Marti-Renom MA, Mirny LA. Exploring the three-dimensional organization of
genomes: interpreting chromatin interaction data. Nat Rev Genet. 2013;14:390–403.

2. Lieberman-Aiden E, van Berkum NL, Williams L, Imakaev M, Ragoczy T, Telling A, et al.
Comprehensive mapping of long-range interactions reveals folding principles of the human
genome. Science. 2009;326:289–93.

3. Belton J-M, McCord RP, Gibcus JH, Naumova N, Zhan Y, Dekker J. Hi-C: a comprehensive
technique to capture the conformation of genomes. Methods. 2012;58:268–76.

4. Fraser J, Ferrai C, Chiariello AM, Schueler M, Rito T, Laudanno G, et al. Hierarchical folding

and reorganization of chromosomes are linked to transcriptional changes in cellular
differentiation. Molecular Systems Biology. 2015;11:852–2.

5. Dixon JR, Selvaraj S, Yue F, Kim A, Li Y, Shen Y, et al. Topological domains in mammalian
genomes identified by analysis of chromatin interactions. Nature. 2012;485:376–80.

6. Phillips-Cremins JE, Sauria MEG, Sanyal A, Gerasimova TI, Lajoie BR, Bell JSK, et al.
Architectural protein subclasses shape 3D organization of genomes during lineage
commitment. Cell. 2013;153:1281–95.

7. Vietri Rudan M, Barrington C, Henderson S, Ernst C, Odom DT, Tanay A, et al. Comparative Hi-
C Reveals that CTCF Underlies Evolution of Chromosomal Domain Architecture. Cell Rep.
2015;10:1297–309.

8. Yaffe E, Tanay A. Probabilistic modeling of Hi-C contact maps eliminates systematic biases to
characterize global chromosomal architecture. Nat Genet. 2011;43:1059–65.

9. Imakaev M, Fudenberg G, McCord RP, Naumova N, Goloborodko A, Lajoie BR, et al. Iterative
correction of Hi-C data reveals hallmarks of chromosome organization. Nat Meth. 2012;9:999–
1003.

10. Cournac A, Marie-Nelly H, Marbouty M, Koszul R, Mozziconacci J. Normalization of a
chromosomal contact map. BMC Genomics. 2012;13:436.

11. Koszul R. HiC-Box. https://github.com/rkoszul/HiC-Box. Accessed 20 February 2016.

12. Servant N, Varoquaux N, Lajoie BR, Viara E, Chen C-J, Vert J-P, et al. HiC-Pro: an optimized
and flexible pipeline for Hi-C data processing. Genome Biol. 2015;16:259.

13. Li W, Gong K, Li Q, Alber F, Zhou XJ. Hi-Corrector: a fast, scalable and memory-efficient
package for normalizing large-scale Hi-C data. Bioinformatics. 2015;31:960–2.

14. Castellano G, Le Dily F, Hermoso Pulido A, Beato M, Roma G. Hi-Cpipe: a pipeline for high-
throughput chromosome capture. bioRxiv. 2015; doi: 10.1101/020636

15. Sauria ME, Phillips-Cremins JE, Corces VG, Taylor J. HiFive: a tool suite for easy and efficient
HiC and 5C data analysis. Genome Biol. 2015;16:237.

16. Heinz S, Benner C, Spann N, Bertolino E, Lin YC, Laslo P, et al. Simple Combinations of
Lineage-Determining Transcription Factors Prime cis-Regulatory Elements Required for
Macrophage and B Cell Identities. Molecular Cell. 2010;38:576–89.

17. Wingett S, Ewels P, Furlan-Magaril M, Nagano T, Schoenfelder S, Fraser P, et al. HiCUP:
pipeline for mapping and processing Hi-C data. F1000Res. 2015;4:1310.

18. Krueger F, Andrews SR. SNPsplit: Allele-specific splitting of alignments between genomes

with known SNP genotypes. F1000Res. 2016;5:1479.

19. Serra F, Baù D, Filion G, Marti-Renom MA. Structural features of the fly chromatin colors
revealed by automatic three-dimensional modeling. bioRxiv. 2016; doi: 10.1101/036764.

20. Schmid MW, Grob S, Grossniklaus U. HiCdat: a fast and easy-to-use Hi-C data analysis tool.
BMC Bioinformatics. 2015;16:390–6.

21. Hwang Y-C, Lin C-F, Valladares O, Malamon J, Kuksa PP, Zheng Q, et al. HIPPIE: a high-
throughput identification pipeline for promoter interacting enhancer elements. Bioinformatics.
2015;31:1290–2.

22. Phanstiel DH, Boyle AP, Araya CL, Snyder MP. Sushi.R: flexible, quantitative and integrative
genomic visualizations for publication-quality multi-panel figures. Bioinformatics.
2014;30:2808–10.

23. Akdemir KC, Chin L. HiCPlotter integrates genomic data with interaction matrices. Genome
Biol. 2015;16:198.

24. Editorial. Rebooting review. Nat Biotechnol. 2015;33:319–9.

25. Goecks J, Nekrutenko A, Taylor J, Galaxy Team. Galaxy: a comprehensive approach for
supporting accessible, reproducible, and transparent computational research in the life
sciences. Genome Biol. 2010;11(8):R86.

26. Ben Langmead, Salzberg SL. Fast gapped-read alignment with Bowtie 2. Nat Meth.
2012;9:357–9.

27. Zhou X, Lowdon RF, Li D, Lawson HA, Madden PAF, Costello JF, et al. Exploring long-range
genome interactions using the WashU Epigenome Browser. Nat Meth. 2013;10:375–6.

28. Hu M, Hu M, Deng K, Deng K, Selvaraj S, Selvaraj S, et al. HiCNorm: removing biases in Hi-C
data via Poisson regression. Bioinformatics. 2012;28:3131–3.

29. Tsirigos A, Haiminen N, Bilal E, Utro F. GenomicTools: a computational platform for
developing high-throughput analytics in genomics. Bioinformatics. 2012;28:282–3.

30. Filippova D, Patro R, Duggal G, Kingsford C. Identification of alternative topological domains
in chromatin. Algorithms for Molecular Biology. 2014;9:14.

31. Shin H, Shi Y, Dai C, Tjong H, Gong K, Alber F, et al. TopDom: an efficient and deterministic
method for identifying topological domains in genomes. Nucleic Acids Res. 2016;44(7):e70.

32. Crane E, Bian Q, McCord RP, Lajoie BR, Wheeler BS, Ralston EJ, et al. Condensin-driven

remodelling of X chromosome topology during dosage compensation. Nature. 2015;523:240–4.

33. Van Bortle K, Nichols MH, Li L, Ong C-T, Takenaka N, Qin ZS, et al. Insulator function and
topological domain border strength scale with architectural protein occupancy. Genome Biol.
2014;15:R82.

34. Alekseyenko AA, Walsh EM, Wang X, Grayson AR, Hsi PT, Kharchenko PV, et al. The
oncogenic BRD4-NUT chromatin regulator drives aberrant transcription within large topological
domains. Genes Dev. 2015;29:1507–23.

35. Ludäscher B, Altintas I, Berkley C, Higgins D, Jaeger E, Jones M, et al. Scientific workflow
management and the Kepler system. Concurrency and Computation: Practice and Experience.
2006;18:1039–65.

36. Oinn T, Addis M, Ferris J, Marvin D, Senger M, Greenwood M, et al. Taverna: a tool for the
composition and enactment of bioinformatics workflows. Bioinformatics. 2004;20:3045–54.

37. Freire J. Making Computations and Publications Reproducible with VisTrails. Computing in
Science & Engineering 2012;14:18–25.

38. Bavoil L, Callahan SP, Crossno PJ, Freire J, Scheidegger CE, Silva CT, et al. VisTrails: enabling
interactive multiple-view visualizations. VIS 05 IEEE; 2005. pp. 135–42.

39. Wright K. Plot a Correlogram. R package. http://CRAN.R-project.org/package=corrgram

40. Sexton T, Yaffe E, Kenigsberg E, Bantignies F, Leblanc B, Hoichman M, et al. Three-
Dimensional Folding and Functional Organization Principles of the Drosophila Genome. Cell
2012;148:458–72.

41. Nora EP, Lajoie BR, Schulz EG, Giorgetti L, Okamoto I, Servant N, et al. Spatial partitioning of
the regulatory landscape of the X-inactivation centre. Nature. 2012;485:381–5.

42. Rao SSP, Huntley MH, Durand NC, Stamenova EK, Bochkov ID, Robinson JT, et al. A 3D Map
of the Human Genome at Kilobase Resolution Reveals Principles of Chromatin Looping. Cell.
2014;159:1665–80.

43. R Core Team. R: A language and environment for statistical computing. R Foundation for
statistical Computing Vienna, Austria 2016. https://www.R-project.org/

44. mirnylib. https://bitbucket.org/mirnylab/mirnylib. Accessed on 20 May 2016.

45. Dixon JR, Jung I, Selvaraj S, Shen Y, Antosiewicz-Bourget JE, Lee AY, et al. Chromatin
architecture reorganization during stem cell differentiation. Nature. 2015;518:331–6.

Figure 3

Figure 4

Filtered

IC

Ratio