1 **Spatial tuning shifts increase the discriminability and fidelity of population codes in visual**
2 **cortex**
3
4 Running title: Spatial attention from units to populations
5

Vy A. Vo[1*], Thomas C. Sprague[1,2], John T. Serences[1,3,4*]
[1]Neurosciences Graduate Program, University of California, San Diego, La Jolla, CA 92093
[2]Department of Psychology and Center for Neural Science, New York University, New York,
New York 10003
[3]Department of Psychology, University of California, San Diego, La Jolla, CA 92093
[4]Kavli Institute for Brain and Mind, University of California, San Diego, La Jolla, CA 92093
12
13 [*]**Correspondence:**
14 Neurosciences Graduate Program
15 University of California, San Diego
16 La Jolla, CA 92093-0634
17 vyaivo@ucsd.edu or jserences@ucsd.edu
18
19

Acknowledgements
Many thanks to the lab and particularly to Rosanne Rademaker and Edward Vul for comments
on analyses and on the manuscript. This work was supported by National Science Foundation
Graduate Research Fellowships to V.A.V. and T.C.S., and a grant from the National Eye
Institute (R01-EY025872) and a Scholar Award from the James S. McDonnell Foundation to
J.T.S.

ABSTRACT

Selective visual attention enables organisms to enhance the representation of behaviorally

relevant stimuli by altering the encoding properties of single receptive fields (RFs). Yet we know

little about how the attentional modulations of single RFs contribute to the encoding of an entire

visual scene. Addressing this issue requires (1) measuring a group of RFs that tile a continuous

portion of visual space, (2) constructing a population-level measurement of spatial

representations based on these RFs, and (3) linking how different types of RF attentional

modulations change the population-level representation. To accomplish these aims, we used

fMRI to characterize the responses of thousands of voxels in retinotopically organized human

cortex. First, we found that the response modulations of voxel RFs (vRFs) depend on the spatial

relationship between the RF center and the visual location of the attended target. Second, we

used two analyses to assess the spatial encoding quality of a population of voxels. We found that

attention increased fine spatial discriminability and representational fidelity near the attended

target. Third, we linked these findings by manipulating the observed vRF attentional modulations

and recomputing our measures of the fidelity of population codes. Surprisingly, we discovered

that attentional enhancements of population-level representations largely depend on position

shifts of vRFs, rather than changes in size or gain. Our data suggest that position shifts of single

RFs are a principal mechanism by which attention enhances population-level representations in

visual cortex.

SIGNIFICANCE STATEMENT

While changes in the gain and size of RFs have dominated our view of how attention modulates

information codes of visual space, such hypotheses have largely relied on the extrapolation of

single-cell responses to population responses. Here we use fMRI to relate changes in single

voxel receptive fields (vRFs) to changes in the precision of representations based on larger

populations of voxels. We find that vRF position shifts contribute more to population-level

enhancements of visual information than changes in vRF size or gain. This finding suggests that

position shifts are a principal mechanism by which spatial attention enhances population codes

for relevant visual information in sensory cortex. This poses challenges for labeled line theories

of information processing, suggesting that downstream regions likely rely on distributed inputs

rather than single neuron-to-neuron mappings.

INTRODUCTION

Spatial receptive fields (RFs) are a core component of visual information processing

throughout the visual system. They are modified by selective visual attention to improve the

fidelity of sensory representations, likely enabling more precise, accurate perception (Desimone

and Duncan, 1995; Anton-Erxleben and Carrasco, 2013). Prior studies in non-human primates

have found that covert spatial attention changes the position, size, and amplitude of responses in

single-cell RFs in early cortical areas such as V1, V4, and MT (Moran and Desimone, 1985;

Connor et al., 1996, 1997, Womelsdorf et al., 2006, 2008; Roberts et al., 2007; David et al.,

2008). Recent neuroimaging studies have also shown that single-voxel RFs (vRFs) undergo

similar response changes with attention, shifting towards the attended target or changing in size

(de Haas et al., 2014; Klein et al., 2014; Kay et al., 2015; Sheremata and Silver, 2015). Most

accounts suggest that these RF modulations improve the spatial representations of the attended

target, either by boosting the signal-to-noise ratio (SNR) by increasing response amplitude, or by

increasing the spatial resolution by decreasing RF size (Desimone and Duncan, 1995; Anton-

Erxleben and Carrasco, 2013; Cohen and Maunsell, 2014). These mechanisms are akin to turning

up the volume (gain increase) or to using smaller pixels to encode a digital image (size decrease).

Despite these documented modulations, it is not yet clear how different types of RF

modulations are combined to facilitate robust population codes. Recent studies have only begun

to explore how interactions between neurons may affect the coding properties of the population

(Anton-Erxleben and Carrasco, 2013; Cohen and Maunsell, 2014). Yet analyzing these data at a

population level is crucial for understanding how spatial attention changes the overall

representation of an attended area. Prior fMRI studies that measured many vRFs across space

were often unable to report the full pattern of response modulations with respect to the attended

target because subjects attended to the mapping stimulus, rather than to a fixed point in space

(Sprague and Serences, 2013; Kay et al., 2015; Sheremata and Silver, 2015). Studies which fixed

the locus of attention have reported mixed results on vRF modulations (de Haas et al., 2014;

Klein et al., 2014). The first aim of this study was thus to evaluate how properties of vRFs in

retinotopic areas change with attention, especially near the peripheral attention target.

The second aim of the study was to evaluate how different types of RF modulations

contribute to population-level enhancements of an attended region of space. Single RFs in early

visual areas are fundamentally local encoding models that are relatively uninformative about

regions outside their immediate borders. To study their relationship to a population-level

representation of space, other metrics are needed to integrate information across all local

encoding units – e.g., vRFs – to evaluate how attentional modulations impact the quality of

population codes. Here, we used two different population-level metrics of spatial encoding

fidelity to investigate these questions, and to determine how changes in vRF amplitude, size, or

position affect the population-level representations. First, we used a measure related to Fisher

Information to evaluate the spatial discriminability of population codes. Second, we used a

spatial encoding model that incorporates information across voxels to form representations of

stimuli in the mapped visual field (Brouwer and Heeger, 2009; Sprague and Serences, 2013;

Sprague et al., 2015).

99   We found that vRF position shifts increase both the spatial discriminability around the

attended region as well as the fidelity of stimulus reconstructions near the attended target.

Surprisingly, shifts in vRF position accounted for more of the population-level enhancements

with attention than changes in vRF size or gain. This finding is unexpected in the context of

'labeled-line' models of information processing, which posit that visual representations rely on

RFs that transmit consistent 'labels' for visual features such as spatial position. Our findings

suggest that apparent shifts in the labels of RFs play an important role in the attentional

enhancement of visual information.

MATERIALS & METHODS

Task design and participants

We collected data from 9 human participants (4 female), 6 of whom had previously completed a

set of retinotopic mapping scans in the lab (participants AA, AB, AC, AI, and AL in Sprague &

Serences, 2013; participants AA, AC, and AI in Sprague et al., 2014; all participants in Ester et

al., 2015). All participants provided written informed consent and were compensated for their

time ($20/hour) as approved by the local UC San Diego Institutional Review Board. Participants

practiced both the attention task and the localizer task before entering the scanner. A minimum

of four hours of scanning was required to complete the entire analysis, so one participant was

excluded due to insufficient data (they only completed 2 hours). Another participant was

excluded for inconsistent behavioral performance, with average task accuracy at chance (48.6%).

This yielded a total of 7 participants who completed the entire experiment (3 2-hour scan

sessions per participant).

Participants centrally fixated a gray rectangular screen (120x90 cm) viewed via a head-

coil mounted mirror (~3.85 m viewing distance). They attended one of three fixed locations on

the screen: the fixation point or a target to the lower left or lower right of fixation. During each

2000 ms trial, subjects reported a change in the attention target. When subjects attended fixation,

they reported whether a brief contrast change (100 – 400 ms, starting 300 – 1000 ms into the

trial) was dimmer or brighter than the baseline contrast. The peripheral attention targets were two

pentagons (0.17° radius; 50% contrast) centered 2.1º to the left and right of fixation (**Fig 1a**).

When subjects attended a peripheral target, they reported whether it rotated clockwise or

counter-clockwise (rotation duration 100 - 300 ms, starting 300 - 1600 ms into the trial). Inter

trial intervals (ITIs) randomly varied between 1000 to 3000 ms in 500 ms increments (mean ITI:

2000 ms). The magnitude of the contrast change or the rotation was adjusted on each run to keep

task performance for each participant near 75% (mean = 75.90%, bootstrapped 95% C.I.

[72.46%, 79.20%]), with no significant difference between conditions as evaluated with a one-

way repeated measures ANOVA randomization test ($F(1,11) = 0.220$, randomized $p = 0.800$).

For four participants, we collected 6 runs on the attend periphery tasks without a change in the

luminance of the fixation stimulus. Performance on the attend periphery tasks was stable across

runs with and without the luminance change (repeated-measures ANOVA with run type x

random participants factor; $p = 0.439$, null F distribution using randomized labels for 10,000

iterations). Therefore, these data were collapsed across scan sessions with and without changes

in fixation luminance.

On 51 of the 61 trials in each run, a full-contrast 6 Hz flickering checkerboard (0.68°

radius; 1.67 cycles/deg) appeared for 2000 ms at one of 51 different locations across the screen

to map the spatial sensitivity of visually responsive voxels. These mapping stimuli covered a

region of the screen roughly subtending 9° horizontal and 6° vertical when their position was

jittered. When one of these checkerboards overlapped with any of the static attention targets,

they were partially masked with a small circular aperture the same color as the screen

background (0.16°/0.25° radius aperture for fixation/pentagon, respectively) that allowed the

stimulus to remain visible. Participants were instructed to ignore the task-irrelevant flickering

checkerboards throughout the experiment. During the 10 null trials on each scan, the participant

continued to perform the attention task but no checkerboard was presented. Null trials and

mapping stimulus trials were presented in a pseudorandom interleaved order.

The location of the checkerboard mapping stimulus on each trial was determined by

generating an evenly spaced triangular grid (0.84° between grid points) and centering the

checkerboard on one of these grid points. The location of the checkerboard mapping stimulus

was then jittered a random amount from these grid points (+/- 0.42°/0.37° horizontal/vertical).

When subjects attended the peripheral target, half of the runs were presented at the discrete grid

positions so that we could achieve more stable stimulus reconstructions (see **Population analysis**

(2)).

Magnetic resonance imaging

We obtained all structural and functional MR images using a GE 3T MR750 scanner at

University of California, San Diego. We collected all functional images (19.2 cm x 19.2 cm

FOV, 64 x 64 acquisition matrix, 35 interleaved slices, 3 mm^3 voxels with 0 mm slice gap, 128

volumes per scan run) using a gradient echo planar pulse sequence (2000 ms TR, 30 ms TE, 90°

flip angle) and a 32-channel head coil (Nova Medical, Wilmington, MA). Five dummy scans

preceded each functional run. A high-resolution structural image was acquired at the end of each

session using a FSPGR T1-weighted pulse sequence (25.6 cm x 25.6 cm FOV, 256 x 192

acquisition matrix, 8.136/3.172 ms TR/TE, 192 slices, 9° flip angle, 1 mm^3 voxels). All

functional scans were co-registered to the anatomical images acquired during the same session,

and this anatomical was in turn co-registered to the anatomical acquired during the retinotopy

scan.

EPI images were unwarped with a custom script from UCSD's Center for Functional

Magnetic Resonance Imaging using FSL and AFNI. All subsequent preprocessing was

performed in BrainVoyager 2.6.1, including slice-time correction, six-parameter affine motion

correction, and temporal high-pass filtering to remove slow signal drifts over the course of each

run. Data were then transformed into Talairach space and resampled to have a 3x3x3 mm voxel

size. Finally, the BOLD signal in each voxel was transformed into Z-scores on a scan-by-scan

basis. All subsequent analyses were performed in MATLAB using custom scripts (available

online on Open Science Framework: osf.io/s9vqv).

Independent localizer task

We constrained our analyses to visually responsive voxels in occipital and parietal cortex

using a separate localizer task (3-5 runs per participant). On 14 trials, participants fixated

centrally and viewed a full-field flickering checkerboard (10 Hz, 11.0/8.3° width/height) for

8000 ms. Participants detected whether a small area (2D Gaussian, $\sigma = 0.2°$) within the

checkerboard dimmed in contrast. Contrast dimming occurred between 500 to 4000 ms after the

start of the trial, and lasted between 2000 to 3000 ms (all uniformly sampled in 500 ms steps).

This contrast change occurred infrequently (randomly on 5 out of 14 trials) at a random location

within the checkerboard. The average contrast change was varied between runs to maintain

consistent performance at ~75% accuracy (mean performance 78.0%). On 8 trials participants

simply fixated throughout the trial without a checkerboard being presented. We then used a

standard general linear model (GLM) with a canonical two-gamma hemodynamic response

function (HRF, peak at 5 s, undershoot peak at 15 s, response undershoot ratio 6, response

dispersion 1, undershoot dispersion 1) to estimate the response to the checkerboard stimulus in

each voxel. For all subsequent analyses, only voxels in the retinotopically defined areas V1, V2,

V3, V4, V3A/B and IPS0 with a significantly positive BOLD response to the localizer task (at

FDR q = 0.05) were included (Benjamini and Yekutieli, 2001).

Estimating single trial BOLD responses

199   For all subsequent analyses, we used trial-wise BOLD z-scores. We estimated these by

creating a boxcar model marking the duration of each checkerboard mapping stimulus and

convolving it with a canonical two-gamma HRF (peak at 5 s, undershoot peak at 15 s, response

undershoot ratio 6, response dispersion 1, undershoot dispersion 1). To standardize our data

across runs, we z-scored the BOLD responses within each run and concatenated the z-scores

across runs. We then solved a GLM to find the response to each predictor.

Statistical procedures

All reported confidence intervals (CIs) are computed by resampling the data with replacement

(i.e. bootstrapping). The number of iterations for each bootstrapping procedure varied

(depending on available computing power and time for that procedure) and are therefore reported

with each result. For tests comparing a bootstrapped distribution against zero, p-values were

computed by conducting two one-tailed tests against 0 (e.g., mean(param_change < 0) &

mean(param_change > 0)) and doubling the smaller p-value. All repeated tests were FDR

corrected (q = 0.05).

Voxel receptive field (vRF) estimation, fitting, and parameter analysis

216   We first estimated vRFs for each attention condition to investigate (1) how vRF

parameters changed when participants attended to different locations and (2) the spatial pattern

of vRF changes across visual space. We note here that prior reports have referred to similar

voxel RF models as population receptive fields, or pRFs, to emphasize the fact that each voxel

contains a population of spatially tuned neurons (Dumoulin and Wandell, 2008; Wandell and

Winawer, 2015). However, since we are comparing modulations at different scales in the present

study (i.e. modulations in single voxels and in patterns of responses across many voxels), we will

refer to these single voxel measurements as voxel receptive fields (vRFs), and will reserve the

term 'population' exclusively for multivariate measures involving several voxels, allowing our

terminology to align with theories of population coding (Ma et al., 2006).

226   We estimated voxel receptive fields (vRFs) using a modified version of a previously

described technique (Sprague and Serences, 2013). This method estimates a single voxel's

spatial sensitivity by modeling its BOLD responses as a linear combination of discrete, smooth

spatial filters tiled evenly across the mapped portion of the visual field. These spatial filters (or

spatial channels) form our modeled basis set. We then regressed the BOLD z-scores (v voxels x

n trials) onto a design matrix with predicted channel responses for each trial (C, k channels x n

trials) by solving Equation 1:

(1) $B = WC$

for the matrix W (v voxels x k channels).

Each of the k channels in the basis set was defined as a two-dimensional cosine that was

fixed to reach 0 at a set distance from the filter center:

(2) $f(r) = \left(0.5 \left(\cos\left(\frac{r\pi}{s}\right) + 0.5 \right) \right)^7 \; for \; r < s,$

where r is the distance from the filter center and s is the size constant. Setting a zero baseline in

this function ensured that we could estimate a stable baseline for each voxel by restricting the

response of the channel to a known subregion of the visual display. Since the estimated vRF size

depends on the size of the filters, we made the filters fairly small (1.08° FWHM) and dense (91

filters arranged in a 13 horizontal / 7 vertical grid, each spaced 0.83° apart). We then discretized

the filters by sampling them in a high-resolution 2D grid of 135 by 101 pixels spanning 10° by

5°. The discretized filters (k filters by p pixels) were multiplied with a mask of the checkerboard

stimulus on every trial (p pixels by n trials) so that the design matrix C contained predictions of

the spatial channel responses on every trial of the mapping task.

To fit our estimated vRFs with a unimodal function, we used ridge regression to solve

Equation 1. This is a common regularization method which sparsifies the regression solution by

penalizing the regressors with many small weights (Hoerl and Kennard, 1970; Lee et al., 2013).

This meant solving for an estimate of W by the following:

(3) $\widehat{W}^T = (CC^T + \lambda I)^{-1} CB^T,$

where λ is the ridge parameter penalty term, and I is a $k \times k$ identity matrix. We estimated an

optimal λ for each voxel by evaluating Equation 3 over a range of λ values (0 to 750) for a

balanced number of runs of the attention task (e.g., an equal number of runs from each attention

condition). We then computed the Bayesian Information Criterion (BIC) for each of these λ

values, estimating the degrees of freedom in the ridge regression as:

(4) $df = trace(C\ (C^T C + \lambda I)^{-1} C^T)$

The λ with the smallest BIC was selected for each voxel. Since the attention comparisons are

done within voxels, the varying λ penalty across voxels could not explain the attention effects we

observed.

261   To select reliable voxels for analysis, we next implemented a set of conservative

thresholding steps (**Table 1**). We first needed to select voxels with reliable visual responses, so

we only kept voxels with trial beta weights that predicted at least 50% of the BOLD time courses

in each scan session. Second, we only used voxels that could be successfully regularized with

ridge regression. Any voxels with the maximum λ (750) were discarded, as this indicated that the

ridge regression solution had not converged. Finally, we verified that the resulting regression

model could predict an independent dataset, so we performed exhaustive leave-one-run-out cross

validation for each attention condition. This ensured that the λ estimated across attention

conditions produced reliable data for each condition separately. We estimated *W* using data from

all but one run (Equation 3) and used this to predict the BOLD GLM trial estimate of the left-out

run (Equation 2), separately for each condition. We then computed the mean correlation between

the predicted & real BOLD GLM trial estimates across cross-validation folds for each voxel.

Note that it is not possible to calculate a coefficient of determination on regularized data, since

the process of ridge regression changes the scale of the predicted data (see supplemental

discussion in Huth et al., 2012). We only kept voxels where this cross-validation r > 0.25 for all

3 conditions.

To quantify each vRF, we fit the spatial RF profile of each voxel with a smooth 2D

function with 4 parameters: center, size, baseline, and amplitude (**Fig 1b**; Equation 2). Here, we

define the vRF baseline as the voxel's response that does not reliably depend on the position of

the mapping stimulus (i.e., its constant offset). The vRF amplitude is defined as the spatially-

selective increase in a voxel's response above this baseline. Together, these two parameters

index how much of the voxel's response is due to a change in mapping stimulus position.

Finally, the size and location parameters estimate the spatial selectivity and the spatial position

preference of the vRFs, respectively. We first downsampled the vRFs by multiplying the

estimated weights $\widehat{W}$ for each voxel (a $1 \times k$ channel vector) by a smaller version of the spatial

grid that contained the basis set (68 by 51 pixel grid; 10° by 5°). This speeded up the process of

fitting the pixelwise surface with Eq. 2. This fitting process began with a coarse grid search that

first found the best fit in a discrete grid of possible vRF parameters (center sampled in 1° steps

over the mapped portion of the visual field; size constant logarithmically sampled at 20 points

between FWHM of $10^{0.01}$° and 10^{1}°). At each grid point, we estimated the best fit amplitude

and baseline using linear regression. The grid point fit with the smallest root mean square error

(RMSE) provided the initialization seed to a continuous error function optimization algorithm

(fmincon in MATLAB). This fit had several constraints: the final solution must place the center

within 2 grid points of the seeded fit (parameterized by position and size) and within the mapped

visual field; the amplitude must be between 0 and 5; the baseline must be between -5 and 5

BOLD z-score units. Occasionally, this nonlinear fitting algorithm did not converge and resulted

in a larger error than the original seed. In this case we took the best fit grid point as the final fit.

To test whether vRF fit parameters changed when participants focused spatial attention at

different positions, we compared fits during each attend periphery condition with fits during the

attend fixation condition. We computed a difference score (attend peripheral – attend fixation) to

describe the magnitude of the attentional modulation. For example, a difference score of –2° in

the FWHM of the vRF would indicate that the response profile width decreased when the

participant attended to the peripheral target. This analysis revealed a subset of voxels with very

large difference scores, which we determined to be due to noisy data or poor fits via manual

inspection. Accordingly, we performed a final threshholding step for all vRF-based analyses: an

elimination of outlier voxels with difference scores greater than three times the standard

deviation of the population mean, where the population consists of the parameter difference

scores for a given ROI (**Table 1**). After removing these outliers, we tested whether the vRF

parameter difference scores differed significantly from 0 within a visual region of interest (ROI)

by bootstrapping the distribution of difference scores across participants 10,000 times.

To determine if these vRF changes were modulated by their position in the visual field,

we first calculated each vRF's distance from the attended location (*v_dist_attn*) using its position

during the fixation task. We then fit an *n*th order polynomial to the vRF difference scores as a

function of *v_dist_attn*, where $n = 0, 1,$ or 2. This corresponds to a constant offset (0^{th} order), a

linear fit (1^{st} order), or a quadratic or parabolic fit (2^{nd} order). These fits were cross-validated by

fitting on 50% of the vRF difference scores and calculating goodness-of-fit (residual sum of

squares and R^2) on each of the 10,000 cross-validation iterations. These cross-validation

iterations also provided confidence intervals on the coefficients for each polynomial. The most

parsimonious fit was chosen by performing a nested F-test on the average residual sum of

squares for each polynomial model.

We also tested whether vRF attentional modulations depended on hemisphere or visual

hemifield, akin to the results reported for IPS0 – IPS5 in Sheremata and Silver, 2015. We sorted

the voxels in each attention condition as contralateral or ipsilateral to the attended target. We

then performed a series of non-parametric bootstrapped tests similar to a two-way ANOVA with

attended hemifield and voxel hemisphere as factors. The vRFs were resampled with replacement

across subjects 10,000 times. We then evaluated the two main effects and the interaction by

computing a difference in the means of the groups or a difference in the slope between the group

means, respectively. None of the tests for the effect of hemisphere and the interaction survived

FDR correction, so we do not report those results here. We speculate that this null result is likely

due to a lack of reliable voxels in anterior parietal cortex areas IPS1-5 in our study, where

previous reports have found larger laterality effects (Sheremata and Silver, 2015).

Population analysis (1): Fine spatial discriminability metric

To compute the spatial discriminability of a population of vRFs, we estimated the spatial

derivative of each vRF at every point in the mapped visual field in 0.1° steps (**Fig 1C**). This was

done by taking the slope of the vRF along the x and y direction at each pixel in the image of the

visual field and squaring this value (Scolari and Serences, 2009, 2010). This measurement is a

descriptor of how well a population code can discriminate small changes in the spatial

arrangement of the stimulus array, which depends on the rising and falling edges of a tuning

curve rather than the difference between the peak response and a baseline response (Regan and

Beverley, 1985; Pouget et al., 2003; Butts and Goldman, 2006; Navalpakkam and Itti, 2007;

Scolari and Serences, 2009, 2010). To restrict our measurements to the relevant area near the

peripheral target, we computed discriminability values within 1 degree of the center of each

target across both spatial dimensions (x and y). These were summed and divided by the

maximum discriminability value in that population to make the results comparable despite

changes in vRF coverage or responsiveness.

Population measurements (2): Stimulus reconstructions using an inverted spatial encoding

model

In addition to computing the discriminability metric described above, we also reconstructed an

image of the entire visual field on each trial using a population-level encoding model. Compared

to the local spatial discriminability index, this is a more sensitive method of assessing the amount

of spatial information encoded in an entire population of voxels because it exploits the pattern of

response differences across voxels, rather than treating each voxel as an independent encoding

unit (Serences and Saproo, 2012; Sprague et al., 2015).

We trained the spatial encoding model using a procedure similar to the vRF estimation

analysis described above (**Fig 4a**). This yields an estimated matrix of weights, $\widehat{W_2}$, which

specifies how much each voxel in a region of interest responds to each of the spatial channels

(Brouwer and Heeger, 2009; Serences and Saproo, 2012; Sprague and Serences, 2013; Sprague

et al., 2015). We then solved Eq. 1 using the Moore-Penrose pseudoinverse with no

regularization:

(5) $\widehat{W_2} = BC^T(CC^T)^{-1}$

C was constructed using a set of 54 evenly tiled spatial filters (Eq. 2; 9 horizontal / 6 vertical;

spaced 1.25° apart; 1.56° FWHM). $\widehat{W_2}$ was estimated using the data from the jittered position

runs. This was done separately for each participant, using a training set balanced across the

conditions of interest (e.g., an equal number of attend left and attend right runs and all attend

fixation runs, since fixation is the neutral condition).

To reconstruct a representation of the mapped visual space, we inverted the model and

multiplied the pseudoinverse of the estimated weight matrix $\widehat{W_2}$ with a test dataset from the

discrete position runs (B_2), yielding estimated channel activations for each trial (C_2; k_2 channels

by t test trials) (Equation 6). Thus, we refer to this analysis as the inverted encoding model

(IEM).

(6) $\hat{C}_2 = \left(\widehat{W_2}^T \widehat{W_2} \right)^{-1} \widehat{W_2}^T B_2$

Because of mathematical constraints on inverting W_2 (number of voxels must be greater than

number of channels), we included all voxels in each ROI instead of just the subset of well-fit

voxels used in the vRF analyses described above. We computed Eq. 6 twice using different test

datasets, once for the discrete position attend left runs and once for the discrete position attend

right runs.

When we multiply the resulting channel activations by a grid of pixels that define the

spatial channels, we obtain a spatial representation of the entire visual field on each trial. This

image contains a stimulus reconstruction showing where the checkerboard should have been

given the trained model and the activation pattern across all voxels in the independent test set.

The stimulus reconstructions were then fit in the same manner as the vRFs, using Eq. 1 to

estimate the center, size, amplitude, and baseline (mean fit RMSE across all ROI reconstructions

0.114; 95% CI [0.102, 0.312]). Here, the baseline is an estimate of the multivariate

reconstruction that is spatially non-selective—i.e., not significantly modulated by the position of

the mapping stimulus. The amplitude describes the maximal increase in that reconstruction

relative to baseline when the mapping stimulus is on the screen.

To assess how attention changed reconstructions of the mapping stimulus across the

visual field, we first computed a difference score that described the effect of attention by folding

the visual field in half (i.e. collapsing across hemifield) and comparing parameters in the

attended vs. ignored hemifield. We excluded the reconstructions that fell along the vertical

meridian (3 of 51 stimulus positions). This allowed us to control for the overall effect of

eccentricity while remaining sensitive to other spatial patterns in stimulus reconstruction

modulations.

We then set up a single factor repeated measures omnibus ANOVA to determine which

pairs of ROI and parameter (e.g., V1 size, V1 amplitude, etc.) were affected by either attention or

Euclidean distance from the target stimuli. The attention factor had two levels (attend/ignore)

and the distance factor had 6 levels (6 evenly spaced distance bins from 0° to 2.54°). Based on

the results of this omnibus test, we tested any significant ROI-parameter combination in a 2-way

repeated measures ANOVA of attention by distance. To estimate the p-values for these tests, we

generated empirical null distributions of the F-scores by randomizing the labels within each

factor 10,000 times within each participant. Reported p-values are the percentage of the

randomized F-scores that are greater than or equal to the real F-scores.

Population analysis (3): Layered spatial encoding model to link vRFs to multivariate

stimulus reconstructions

In order to test how changes in the response properties of the underlying vRFs contributed to

changes in the fidelity of region-level stimulus reconstructions, we generated simulated patterns

of voxel activity on every trial by predicting the response to each stimulus based on the vRF fit

parameters. We then used this simulated data to estimate and invert a population-level spatial

encoding model, as described above (**Fig 6a**).

Note that for these simulations, we could only use well-fit voxels to generate simulated

BOLD timeseries. This constrained the analysis to ROIs with at least as many vRFs as spatial

filters used to estimate the spatial encoding model. To ensure that we could include most

participants in the layered encoding model analysis, we created two large ROIs by merging the

smaller retinotopically defined regions described above. The occipital ROI consisted of V1, V2,

V3, and V4 defined for each subject. The posterior parietal ROI consisted of V3A/B and IPS0.

The vRFs in the parietal ROI show distinct patterns of attentional modulations (**Fig 2e**),

suggesting that V3A/B and IPS0 are both anatomically and functionally distinct from the

occipital regions (see also de Haas et al, 2014). Although merging ROIs increased the number of

voxels available for the encoding model analysis, we still did not have enough voxels in the

parietal ROI to estimate the layered encoding model for 3 of the 7 participants (AL, AR, AU).

However, the remaining data from 4 participants were sufficient to produce stable, subject-

averaged results.

To simulate each voxel's BOLD response on every trial that the participant completed in

the real experiment, we first created a high-resolution set of spatial channels (21 by 11 channels

spaced 0.5° apart, FWHM = 0.65°) and generated weights for each channel based on the vRF fit

obtained from prior analysis. That is, we evaluated Eq. 2 for each channel at the vRF's fit center

and adjusted the response gain by multiplying this result by the fit amplitude and adding the fit

baseline. We then added independent Gaussian noise to each of these channel weights,

simulating a small amount of variance in the voxel's response ($\sigma = 0.5$). Each voxel's channel

weights were then multiplied by the idealized channel response on each trial (that is, the channel

filter convolved with the stimulus mask), effectively simulating the BOLD response on each trial

for the entire population of voxels based on their measured vRFs. We added Gaussian noise to

this simulated response as well ($\sigma = 0.5$). We then computed stimulus reconstructions using the

same method as described above (the IEM in **Population analysis (2)**), averaging resulting

reconstructions across participants and like positions before fitting.

To ensure the stability of the reconstructions that were based on simulated data, we

repeated the simulations 100 times and averaged across the fits of all iterations to generate the

plots in **Fig 6b**. Then, to compare how well the layered model reproduced the attentional

modulations observed in stimulus reconstructions generated with real data, we calculated an

error metric between the layered IEM and the real data. We first calculated reconstruction

difference scores across attention condition (attended – ignored; see **Population analysis (2)**).

This yielded 24 difference scores each for both attention conditions in both the layered IEM data

and the empirical data. Since the empirical data did not have any repeated iterations, we

averaged across all 100 iterations of the layered model to match the dimensionality of the real

reconstructions (2 conditions x 24 difference scores x 4 parameters). We could then calculate the

root mean square error (RMSE) between the difference scores from the full empirical dataset (i.e.

the data shown in **Fig 5**) and the modeled data. This was used as a metric to describe the

goodness-of-fit of each layered IEM.

We then tested how different vRF attentional modulations contributed to changes in the

population-level stimulus reconstructions. To test how shifts in vRF centers contributed to

population-level information, we modeled voxels that had the same fit center across both

attention conditions, simulated their BOLD responses on each trial, and generated stimulus

reconstructions from these data. The voxel's vRF center was defined as the vRF center fit from

the neutral attend fixation data. A similar procedure was repeated for all reported combinations

of parameter changes across conditions. Again, whichever parameter was held constant took its

value from the neutral attend fixation condition.

To calculate the confidence intervals on the RMSE changes in **Fig 6c**, we resampled with

replacement across the 100 model iterations and refit the average across these 100 instances.

This resampling procedure was repeated 500 times to generate a distribution of fits to the model

data. We then took the difference between the RMSE of the null model, in which no parameters

varied between attention conditions, and the RMSE of the model which held some number of

vRF parameters constant across attention conditions.

RESULTS (3,709 words)

Modulations of vRF properties with spatial attention

We estimated single voxel receptive fields (vRFs) for each voxel in 6 retinotopically-identified

visual areas from V1 to IPS0. The estimation of vRFs was done independently for each attention

condition so that we could compare a single voxel's spatial tuning across conditions.

To confirm that the fit sizes were consistent with previous results, we fit a line to the

estimated sizes as a function of the vRF center eccentricity. First, we combined all vRFs across

participants and conditions in each ROI. We then binned the vRF centers every 0.25° from

fixation and calculated the mean size (**Fig 2b**). We first replicated an increase in vRF size with

increasing eccentricity, and an increase in the slope of this relationship across visual regions

(Gattass et al., 2005; Dumoulin and Wandell, 2008; Amano et al., 2009; Harvey and Dumoulin,

2011) (**Fig 2b**). These observations confirm that our method produced reasonable vRF estimates

that were consistent with previous reports.

Next, we examined how covert attention to the peripheral attention targets modulated

vRF properties, relative to the attend fixation condition. Overall, the center position of vRFs

shifted significantly closer to the attended location (p < 0.005 in all ROIs, **Fig 2d**). This finding

is consistent with previous reports in humans and in monkeys for both covert attention tasks and

saccade tasks (Womelsdorf et al., 2006, 2008; Klein et al., 2014; Zirnsak et al., 2014).

While we did observe changes in the size of individual vRFs, the mean change was not

significantly different from zero (p > 0.05 in all ROIs). Size increases have been previously

reported in tasks that required subjects to attend to the mapping stimulus, which moved on each

trial (Sprague and Serences, 2013; Kay et al., 2015; Sheremata and Silver, 2015). Accordingly, if

attention causes the center of RFs to shift toward the attended target, these combined shifts in

position would average out to form a larger RF estimate. In contrast, mapping vRFs while

maintaining a fixed locus of attention would nullify the size increase, consistent with the results

we observed (**Fig 2d**). Another study which also found increases in vRF size with attention

required subjects to attend the fixation point while they manipulated the cognitive load, or

difficulty, of the attention task (de Haas et al., 2014). In our study, we intentionally kept task

performance constant and could not evaluate effects of difficulty on the parameters of vRFs.

We also found an overall increase in vRF amplitude with attention (p < 0.001 for all

tests). Since these measures were calculated relative to a fixation task, these data suggest that

covert spatial attention to a peripheral location caused widespread position and gain modulations

in all vRFs across the visual field.

It is unclear whether these attentional modulations are limited to areas near the attended

target, or whether they are uniform across the visual field. For example, vRF position shifts

could result in a radial convergence of RFs towards the attended target, or a uniform shift of RFs

along a vector extending from fixation to the attention or saccade target (Tolias et al., 2001;

Klein et al., 2014; Zirnsak et al., 2014). Furthermore, reports of other RF properties (such as

size) modulating with attention have been mixed (Connor et al., 1996, 1997; Womelsdorf et al.,

2008; Niebergall et al., 2011; Sprague and Serences, 2013; de Haas et al., 2014; Klein et al.,

2014; Kay et al., 2015; Sheremata and Silver, 2015). We therefore examined whether each of the

vRF parameter changes was dependent on the vRF's location in the visual field, relative to the

attended location. First, we created radial distance bins centered on the left or right attended

locations, and sorted voxels into these bins based on their preferred position during the fixation

condition. After this sorting procedure, data from the right condition were flipped and collapsed

with the left condition.

When we plotted vRF position changes in each bin, we found that spatial attention caused

vRF position shifts that converged on the attended location (two-tailed sign test on vector

direction, $p < .001$ in all ROIs). That is, vRFs shifted closer to the attended location (**Fig 2c**),

compared to when subjects attended fixation (mean shift across all vRFs and ROIs: -0.239°, 95%

C.I. [-0.566, -0.048], **Fig 2d**). Note that small eye movements toward the attended location

cannot explain receptive field convergence: this would cause all vRFs to shift in the same

horizontal direction, rather than radially converging on one point. These data are consistent with

results from both humans (Klein et al., 2014) and macaques (Connor et al., 1996, 1997,

Womelsdorf et al., 2006, 2008) that use a similar task. However, the prior study in humans

focused only on vRFs with preferred locations that were foveal to the attended location, and the

studies in macaques only report RF position changes in V4 and MT. By contrast, our data show

that vRF centers converge on the attended location across all visual areas, including primary

visual cortex, and that this pattern of modulations includes vRFs peripheral to the attended target.

These plots (**Fig 2a, 2d**) also suggested that vRFs farther from the attended location

underwent larger position changes than vRFs near the attended location. That is, the magnitude

of the attentional modulation may be dependent on the distance between the vRF and the

attended target. To test for this, we fit a polynomial to the vRF parameter changes as a function

of distance from the attended location (**Materials and Methods**). We selected the most

parsimonious fit ranging from a mean change in vRF parameter (0^{th} order polynomial) to a

parabolic change (2^{nd} order polynomial) by conducting a nested F-test (**Table 2**). The best

polynomial fits are plotted in **Fig 2e**.

This analysis allowed us to characterize trends in vRF attentional modulations across

space. Note that it also implicitly tests whether voxels contralateral to the attended target respond

differently than ipsilateral voxels. This is because vRFs near the attended target will mostly

originate from the contralateral side of visual cortex. Therefore, any fit lines with a significant

slope imply there is a difference between contralateral and ipsilateral voxels (Sheremata and

Silver, 2015). A separate test described in **Materials and Methods** confirmed that contralateral

voxels differed significantly from ipsilateral voxels in the areas where we saw the highest fit

slopes in **Fig 2e** (FDR-corrected $p < .05$ for position: V1, V2; size: V3; amplitude: V3, IPS0).

However, since the fit lines illustrate how these changes occur over space, we discuss those data

here instead (**Fig 2e**).

In early visual areas V1 through V3, vRFs near the attention target were slightly repelled

from the target, whereas vRFs farther from the target were attracted towards the target. In later

visual areas, vRFs were uniformly attracted towards the attention target. We saw a similar

pattern of results with size modulations: early visual areas showed an increase in vRF size near

the attention target, and decreased size farther away. However, in areas V3A/B and IPS0, vRF

size decreased near the attention target.

The pattern of vRF amplitude modulations was also segregated between the early and

later visual areas. All vRFs increased in amplitude with attention, but the slope of this

relationship inverted from early to later visual areas. In V1 – V3, the slope if positive, such that

voxels ~2° away from the attention target increase in amplitude more than voxels right at the

target position. The amplitude increase is constant in V4 and V3A/B. Finally, in IPS0, the slope

inverts to become negative, so that voxels near the attention target increase in amplitude more

than voxels farther away. Lastly, we found an increase in vRF baseline near the attended target in

V1 – V4, but a uniform increase in baseline in IPS0. Overall, we found that the type and

magnitude of the attentional modulation in different visual areas changes as a function of the

spatial relationship between vRFs and the attended target. This is consistent with findings from

macaque neurophysiology, which had suggested that amplitude and size changes depend on

where the RF is located in relation to the attended target (Connor et al., 1996; Niebergall et al.,

2011).

Note that these fits only describe the gain modulations with respect to the voxel's

position during the attend fixation task. However, these parameter changes likely interact with

one another, such that a voxel that shifts toward the attended location will also increase in

amplitude. Hence, to determine how the joint patterns of vRF modulations change the spatial

information content of a representation, in the next section we discuss two different population-

level measures that combine data across the population of vRFs in each ROI.

Increases in spatial discriminability depend primarily on vRF position shifts

Next, we assessed how different types of RF modulations influenced the precision of

population-level codes for spatial position. We first computed a discriminability metric that

described the ability of a population of tuning curves (here, voxel receptive fields) to support fine

spatial judgments (**Materials and Methods**). When we computed this metric based on the

measured vRF properties from each condition, spatial discriminability near the attended target

increased relative to the ignored target in the opposite visual hemifield (**Fig 3a**).

We then tested how different types of vRF modulations (such as size changes or position

shifts) affected this spatial discriminability metric. As a baseline comparison, we first computed

discriminability based on vRFs estimated during the attend fixation runs for each subject. We

then added different sets of observed attentional modulations to the population before

recomputing spatial discriminability. For example, we shifted all the vRF centers to match the

measurements when a subject was attending to the left target and computed discriminability near

the attended target. Since the response baseline of a vRF does not affect the discriminability

metric, we excluded this type of attentional modulation from these analyses.

Across all ROIs, we found that vRF position shifts played the biggest role in increasing

fine spatial discriminability compared to changes in size or changes in amplitude (**Fig 3b**).

Position modulations alone led to a large increase in spatial discriminability, while other

combinations of parameter modulations only had an impact if we added in position shifts (i.e. a

change in size and position increased discriminability, but size alone did not). The only departure

from these patterns was observed in IPS0, where all attentional modulation types increased

spatial discriminability, but position changes increased spatial discriminability the most.

Spatial attention increases the fidelity of population-level stimulus reconstructions

By design, the spatial discriminability metric we computed is only informative about

local spatial representations, and cannot assess how different patterns of vRF modulations might

result in representational changes across the visual field. To address this point, we built a

multivariate spatial encoding model to measure how attention changes the representations of

visual information in disparate parts of space. This also allowed us to further test the effects of

vRF modulations on the encoding properties of the population, including response baseline

changes that were not captured by our discriminability metric.

The spatial inverted encoding model (IEM) reconstructed an image of the entire visual

field on each test trial. We first trained the model using the responses of each voxel on a set of

training trials with known mapping stimulus positions. We then created image reconstructions on

independent test trials by inverting the model and multiplying it by the voxel responses during

each test trial (**Fig 4a**; **Materials and Methods**). Each image contained a representation of

where the mapping stimulus should have been given the pattern of voxel activations on that

particular trial. The IEM successfully reconstructed the task-irrelevant mapping stimuli using

activation patterns across voxels in each visual area from V1 through IPS0 (**Fig 4b**; grand mean

error between fit and actual position 2.40°, 95% CI [0.55°, 4.97°]).

We used these stimulus reconstructions as a proxy for the quality of the spatial

representations encoded in a population of voxels. This is line with previous studies showing that

stimulus reconstructions change in amplitude or size as a function of cognitive demands.

(Brouwer and Heeger, 2013; Ester et al., 2013; Sprague and Serences, 2013; Sprague et al., 2014,

2015, 2016).

First, we compared how reconstructed representations of each mapping stimulus changed

as subjects shifted their spatial attention. We ran a repeated measures ANOVA of *attention* x

distance bin for each reconstruction fit parameter (**Materials and Methods**). Here, a main effect

of attention would suggest that stimulus reconstructions in the attended hemifield changed in a

consistent way compared to the ignored hemifield. A main effect of distance would suggest that

stimulus reconstruction changes had a consistent spatial pattern across both the attended and

ignored hemifields. This would occur when a stimulus' representation was altered with distance

from the attention target. For example, the stimulus reconstruction center should vary linearly

with the stimulus' true distance from the attention target. And lastly, an interaction effect would

suggest that the distance effect was dependent on whether the reconstruction belonged to the

attended or ignored hemifield. In our task, the reconstructed stimuli are always irrelevant to the

task of the observer. We therefore predicted an interaction effect where spatial attention would

selectively modulate stimulus reconstructions within the hemifield of the attended location, but

not the opposite hemifield (Connor et al., 1996, 1997).

We found that reconstruction amplitude was selectively increased near the attended

location in V4, V3A/B, and IPS0 (interaction effect, bootstrapped $p < 0.005$; **Fig 5**; **Table 3**).

This can be interpreted as a local boost in SNR. Prior reports found that attending to the mapping

stimulus – as opposed to attending to a peripheral target in the current experiment – caused an

increase in the amplitude of all stimulus reconstructions (Sprague and Serences, 2013). That is,

representations of task-relevant stimuli increased in SNR. We find here that even representations

of task-*irrelevant* stimuli near the attended region of space increase in amplitude, consistent with

the idea of an attentional 'spotlight' which boosts the fidelity of spatial representations near the

attention target.

Although the amplitude interaction effect was present in most visual areas we tested (**Fig**

5), we found other effects limited to V3A/B and IPS0 that involved modulations in stimulus

representations in the ignored hemifield. In these regions, we found that stimulus reconstructions

in the ignored hemifield shifted away from the ignored target location (interaction, bootstrapped

$p < 0.005$). We also observed a relative size increase near the ignored attention stimulus in IPS0

(interaction, bootstrapped $p < 0.005$). These results suggest that stimulus reconstructions in the

ignored hemifield are less spatially precise in posterior parietal cortex. Finally, there was also a

main effect of attention on reconstruction size and baseline in areas V3, V4 & V3A/B

(bootstrapped p's <= 0.005). However, unlike the interaction effect in IPS0, these size and

baseline changes did not vary as a function of distance between the reconstruction and the

attended target location.

Using a layered encoding model to explore how single voxel RFs change population-level

codes

652   In our final analysis, we used a layered spatial encoding model to determine how changes

in vRF properties affected the representations of mapping stimuli in the multivariate

reconstructions discussed in the previous section (**Fig 1c**; **Fig 4a**). The goal of this analysis was

to determine which vRF modulations contribute the most to the observed increase in the

amplitude of stimulus representations around the attended location (**Fig 5**). This analysis thus

complements our analysis of the spatial discriminability metric which demonstrated that vRF

position changes significantly increased the ability of the population to make fine spatial

discriminations near the attention target (**Fig 3c**).

660   The layered spatial encoding model we built links the response properties of single

voxels to the encoding properties of a whole population of voxels in a region of visual cortex

(**Fig 6a**). In the first layer of the model, we used the fit vRFs to generate simulated BOLD data

from each voxel under different attention conditions. We then repeated the multivoxel stimulus

reconstruction analysis on this simulated data to model population results for the second layer of

the model. This approach allowed us to perform virtual experiments to test how changes in the

first layer impacted the second layer. That is, we manipulated which vRF parameters changed

with attention (first layer) and observed the resulting changes in the population-based stimulus

reconstructions (second layer). For example, we could test whether an overall increase in vRF

response gain with attention would be necessary or sufficient to reproduce the amplitude

increases observed in the empirical stimulus reconstructions reported in **Fig 5**. These virtual

experiments also allowed us to compare the relative impact of one type of response modulation

(e.g. size changes) with other types of response modulations (e.g. position shifts).

Since the population-level stimulus reconstructions require many voxels from each

subject to produce stable and reliable results, we combined the data across several regions in

each individual subject before estimating the IEM (see **Materials and Methods** for a longer

discussion). This yielded one occipital region that combined data from areas V1, V2, V3 and V4,

and one posterior parietal region that combined data from V3A/B and IPS0. We repeated the

IEM analysis described in the previous section on these larger regions, and found that the pattern

of attentional modulations observed earlier was consistent in the large ROIs (**Figure 5**). Next, to

verify whether we could perform the layered IEM using a reduced number of voxels, we re-ran

the IEM analysis but only used the data from voxels with well-fit vRFs. The reduced dataset with

fewer voxels reproduced the main pattern of results we observed in the previous section. In

particular, covert attention led to an increase in the amplitude of reconstructions near the locus of

attention (**Fig 6b**, black vs. gray bars).

We then investigated the contribution of each vRF parameter to the population-level

stimulus reconstructions, in a comparison akin to the spatial discriminability analysis in **Fig 3**. A

model that only simulated the observed vRF amplitude or vRF size modulations did not predict

the observed increase in reconstruction amplitude near the attention target (**Fig 6b**, red lines).

However, a layered model that only simulated vRF position changes did predict a large increase

in reconstruction amplitude near the attention target in the parietal ROI (**Fig 6b**, blue line on

right). This is consistent with the effects observed in the full dataset (**Fig 5**, **Table 3**), where we

only observed an interaction of stimulus distance and attention in the parietal ROI.

To more formally quantify each manipulation of the layered IEM, we calculated an error

metric to describe how well each model reproduced the attentional modulations in the empirical

data (using the root mean square error, or RMSE). We compared each model's RMSE to a

baseline model, which did not simulate any vRF attentional modulations (far left in **Fig 6c**). This

null baseline should have the highest error, and any good models should decrease the RMSE

between the simulated data and the empirical data. Conversely, a model with higher RMSE is

worse at accounting for the empirical data compared to the null model. In both the occipital and

parietal ROIs, adding vRF position shifts to the layered model decreased RMSE, while

abolishing position shifts generally increased the model error (**Fig 6c**). These data are consistent

with the results from the spatial discriminability analysis. Altogether, they suggest that shifts in

vRF position have the largest impact on population-level representations, while changes in vRF

size or gain play smaller roles in changing the fidelity of the population code.

DISCUSSION (Max 1500 words; current 1500)

By simultaneously measuring the response properties of both single voxels and populations of

voxels within retinotopic areas of visual cortex, we could link attentional modulations of spatial

encoding properties across scales. Our data provide an initial account of how different types of

RF modulations improve the quality of population codes for visual space. First, we show how

vRF attentional modulations depended on the distance between the vRF's preferred position and

the static attention target (**Fig 2**). We then found that shifts in the preferred position of vRFs near

the attended target increased the spatial discrimination capacity of a population of voxels (**Fig 3**),

as well as the amplitude of stimulus reconstructions based on response patterns across all voxels

in a ROI (**Fig 5, 6**).

Attentional modulations of spatial RFs

We provide new data on how vRF responses are modulated around a covertly attended

static target (Sprague and Serences, 2013; de Haas et al., 2014; Klein et al., 2014; Kay et al.,

2015; Sheremata and Silver, 2015). Like prior macaque studies, we find that vRF position shifts

depend on the vRF's distance from the attended target (Connor et al., 1996, 1997). However, we

also found that the pattern of attentional modulations differs across the visual hierarchy. In V4,

V3A/B, and IPS0 voxels shift towards the attended target, while in earlier areas, vRFs near the

attended target are slightly repelled from it (**Fig 2e**). We also found distinct patterns of size

modulations: vRF size increased near the attention target in early visual areas, but decreased in

parietal areas V3A/B and IPS0. Comparison to the existing literature suggests that patterns of RF

size modulations likely depend on the nature of the spatial attention task. In fMRI tasks where

subjects attended to the mapping stimulus, rather than a static position, researchers report

average vRF size increases with attention (Sprague and Serences, 2013; Kay et al., 2015;

Sheremata and Silver, 2015). RFs in macaque area MT shrink when measured with a mapping

probe smaller than the stimulus, but increase in size when macaques track the mapping probes as

they move across the screen (Womelsdorf et al., 2006, 2008; Anton-Erxleben et al., 2009;

Niebergall et al., 2011). This may be because the RFs shift position to track the probe, causing an

apparent increase in overall size. Lastly, manipulating cognitive load at fixation also increases

vRF size in human visual cortex (de Haas et al., 2014). Taken together, these observations

demonstrate that the pattern of RF response modulations depends both on task demands and on

the spatial relationship between the attended target and the encoding unit's RF.

We note that while the similarity between attentional modulations of single cell RFs and

single voxel RFs is compelling, their properties are derived from different input signals, and are

not interchangeable. fMRI voxels in retinotopically organized regions of visual cortex sample

from a broad array of neurons with roughly the same spatial tuning preferences, so a position

shift in a vRF could either be driven by a change in the preferred position of single neurons, or

by a change in the gain profile across neurons tuned to slightly different locations in the visual

field. Similarly, single neuron RFs receive input from smaller RFs in earlier visual areas, and a

position shift could arise from either mechanism described above (McAdams and Maunsell,

1999; Baruch and Yeshurun, 2014; Dhruv and Carandini, 2014). Because of this inherent

ambiguity when measuring the encoding properties of a locally tuned unit, it is useful to compare

them with attentional modulations of population-level representations.

Attention boosts the spatial encoding fidelity of a population

We first measured the overall capacity of a population of voxels to make fine spatial

discriminations in a region of space. We found that attention increased spatial discriminability

near the attended target, relative to the ignored target. We then performed virtual experiments on

the vRFs contributing to the population to determine how they affected the spatial

discriminability metric. We report that vRF position shifts increased spatial discriminability

significantly more than vRF size changes or gain changes (**Fig 3**).

755   Since the spatial discriminability metric (**Fig 3**) is only informative about a local portion

of space, we performed a second population analysis to reconstruct an image of the entire visual

field on each trial using a multivariate IEM. Attention increased the amplitude of stimulus

reconstructions near the attention target, indicating an increase in representational fidelity that

accompanied the increase in spatial discriminability. In addition, a layered spatial encoding

model revealed that shifts in vRF position could account for these attentional enhancements in

the population-level stimulus reconstructions, but changes in vRF size could not. Altogether, our

data demonstrate that shifts in position of many RFs may be a dominant way that single encoding

units alter the properties of a population spatial code.

764   Although population-level information increased the most with changes in vRF position,

765   we reiterate that these position changes could arise from spatially-specific patterns of gain

766   modulations in input RFs. If this is true, it is possible that gain modulations with attention may

767   exert their largest effects on the downstream population, where these patterns of gain changes

768   become apparent shifts in vRF position. However, this remains an open question for future work

769   to address.

770   Our findings also underscore the fact that changes in the spatial encoding properties of

single units do not directly translate into analogous changes in the encoding properties of a

population of those same units. For example, an overall change in vRF size does not necessarily

change the size of the population-level representation (Sprague and Serences, 2013; Kay et al.,

2015). Although we found that single units shifted their preferred position towards the attended

target, population-level representations did not generally shift with attention. When the

population code did shift its encoded position, we found that it was typically representations of

the ignored stimulus that shifted farther from the true stimulus location (**Fig 5**), consistent with

more error-prone representations of irrelevant stimuli. These types of differences further

emphasize the need to understand the effects of cognitive state on population codes for the entire

visual scene, rather than focusing solely on single units.

781   Lastly, we note that our population-level data do not address the open question of

whether RF attentional modulations have perceptual consequences, since it is not clear how the

spatial encoding models measured here are linked to visual perception and behavior

(Koenderink, 1990; Rose, 1999; Anton-Erxleben and Carrasco, 2013; Klein et al., 2016). Further

investigation into these topics should include task manipulations to investigate how attentional

modulations of both vRFs and population-level metrics track psychophysical performance.

Tuning shifts and labeled lines

789   Historically, shifts in the tuning of a RF have not been considered one of the main

mechanisms by which attention modulates population-level information, although recent reports

suggest that this view is being reconsidered (David et al., 2008; Anton-Erxleben and Carrasco,

2013). This may be due to 'labeled-line' theories of visual information processing, which posit

that a single neuron has a consistent feature label which downstream neurons rely on to perform

computations and transmit stable information (Barlow, 1972; Doetsch, 2000; David et al., 2008).

When a spatial RF shifts position as a function of cognitive state (e.g., attention), that single

neuron's feature label is no longer consistent. Without an accompanying shift in the downstream

neurons receiving the changing feature label, such a change could disrupt the stability of the

population code. However, our results suggest that population-level spatial representations

remain relatively stable – and are even enhanced – when the tuning of the underlying vRFs shift

in position, size, and gain.

An alternate proposal to a labeled line code relies on the joint information encoded across

a population of cells (Erickson, 1982; Doetsch, 2000). This may occur at several scales–for

example, V2 could use the pattern of information from V1 inputs to form a visual representation.

This idea is more akin to an encoder-decoder model in which the downstream decoder does not

need information about the altered representations in each of the encoder units, but instead relies

on a population readout rule (Seriès et al., 2009). The population readout rule could incorporate

knowledge about the 'labels' of the encoder units, but could perform equally well by relying on

relative changes in the pattern across units to resolve the information encoded in the population.

However, further exploration of population readout rules in visual cortex are needed to test this

hypothesis.

Conclusions

The spatial encoding properties of the visual system can be measured and modeled at

many different spatial scales. Here, we report how these properties change with attention for

single voxels and for a group of voxels in each ROI. Notably, single vRF modulations do not

propagate directly to analogous changes in large-scale codes. Instead, we observed that

attentional modulations of vRF position play a dominant role in modulating the amplitude of

population-level representations. Future research is needed to resolve how shifts in RF labels are

generated, how information is read out from a population, and how these multi-scale attentional

modulations affect visual perception and behavior.

REFERENCES

Amano K, Wandell B a, Dumoulin SO (2009) Visual field maps, population receptive field sizes,

and visual field coverage in the human MT+ complex. J Neurophysiol 102:2704–2718.

Anton-Erxleben K, Carrasco M (2013) Attentional enhancement of spatial resolution: linking

behavioural and neurophysiological evidence. Nat Rev Neurosci 14:188–200 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/23422910 [Accessed December 19, 2013].

Anton-Erxleben K, Stephan VM, Treue S (2009) Attention reshapes center-surround receptive

field structure in macaque cortical area MT. Cereb Cortex 19:2466–2478 Available at:

http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=2742598&tool=pmcentrez&ren

dertype=abstract [Accessed December 19, 2013].

Barlow HB (1972) Single units and sensation: A neuron doctrine for perceptual psychology?

Perception 1:371–394.

Baruch O, Yeshurun Y (2014) Attentional attraction of receptive fields can explain spatial and

temporal effects of attention. Vis cogn 22:704–736 Available at:

http://www.tandfonline.com/doi/abs/10.1080/13506285.2014.911235.

Benjamini Y, Yekutieli D (2001) The control of the false discovery rate in multiple testing under

dependency. Ann Stat 29:1165–1188.

Brouwer GJ, Heeger DJ (2009) Decoding and reconstructing color from responses in human

visual cortex. J Neurosci 29:13992–14003 Available at:

http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=2799419&tool=pmcentrez&ren

dertype=abstract [Accessed January 31, 2014].

Brouwer GJ, Heeger DJ (2013) Categorical clustering of the neural representation of color. J

Neurosci 33:15454–15465 Available at:

http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=3782623&tool=pmcentrez&ren

dertype=abstract.

Butts DA, Goldman MS (2006) Tuning Curves, Neuronal Variability, and Sensory Coding. PLoS

Biol 4:e92 Available at: http://biology.plosjournals.org/perlserv/?request=get-

document&doi=10.1371%252Fjournal.pbio.0040092.

Cohen MR, Maunsell JHR (2014) Neuronal mechanisms of spatial attention in visual cerebral

cortex. In: The Oxford Handbook of Attention, pp 318–345.

Connor CE, Gallant JL, Preddie DC, Van Essen DC (1996) Responses in Area V4 Depend on the

Spatial Relationship Between Stimulus and Attention. J Neurophysiol 75:1306–1308.

Connor CE, Preddie DC, Gallant JL, Van Essen DC (1997) Spatial attention effects in macaque

area V4. J Neurosci 17:3201–3214 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/9096154.

David S V, Hayden BY, Mazer JA, Gallant JL (2008) Attention to stimulus features shifts

spectral tuning of V4 neurons during natural vision. Neuron 59:509–521 Available at:

http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=2948549&tool=pmcentrez&ren

dertype=abstract [Accessed December 17, 2013].

de Haas B, Schwarzkopf DS, Anderson EJ, Rees G (2014) Perceptual load affects spatial tuning

of neuronal populations in human early visual cortex. Curr Biol 24:R66–R67 Available at:

http://linkinghub.elsevier.com/retrieve/pii/S0960982213015169 [Accessed January 20,

2014].

Desimone R, Duncan J (1995) Neural mechanisms of selective visual attention. Annu Rev

Neurosci 18:193–222.

Dhruv NT, Carandini M (2014) Cascaded Effects of Spatial Adaptation in the Early Visual

System. Neuron 81:529–535 Available at: http://dx.doi.org/10.1016/j.neuron.2013.11.025.

Doetsch GS (2000) Patterns in the brain. Neuronal population coding in the somatosensory

system. Physiol Behav 69:187–201 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/10854929.

Dumoulin SO, Wandell BA (2008) Population receptive field estimates in human visual cortex.

Neuroimage 39:647–660 Available at:

http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=3073038&tool=pmcentrez&ren

dertype=abstract [Accessed December 16, 2013].

Erickson RP (1982) The across-fiber pattern theory: An organizing principle for molar neural

function. In: Contributions to sensory physiology, Vol. 6, pp 79–110.

Ester EF, Anderson DE, Serences JT, Awh E (2013) A Neural Measure of Precision in Visual

Working Memory. J Cogn Neurosci 25:754–761.

Ester EF, Sprague TC, Serences JT (2015) Parietal and Frontal Cortex Encode Stimulus-Specific

Mnemonic Representations during Visual Working Memory. Neuron 87:893–905 Available

at: http://dx.doi.org/10.1016/j.neuron.2015.07.013.

Gattass R, Nascimento-Silva S, Soares JGM, Lima B, Jansen AK, Diogo ACM, Farias MF,

Botelho MMEP, Mariani OS, Azzi J, Fiorani M (2005) Cortical visual areas in monkeys:

location, topography, connections, columns, plasticity and cortical dynamics. Philos Trans

R Soc Lond B Biol Sci 360:709–731.

Harvey BM, Dumoulin SO (2011) The relationship between cortical magnification factor and

population receptive field size in human visual cortex: constancies in cortical architecture. J

Neurosci 31:13604–13612 Available at: http://www.ncbi.nlm.nih.gov/pubmed/21940451

[Accessed January 2, 2014].

Hoerl AE, Kennard RW (1970) Ridge Regression: Biased Estimation for Nonorthogonal

Problems. Technometrics 12:55–67.

Huth AG, Nishimoto S, Vu AT, Gallant JL (2012) A continuous semantic space describes the

representation of thousands of object and action categories across the human brain. Neuron

76:1210–1224.

Kay KN, Weiner KS, Grill-Spector K (2015) Attention reduces spatial uncertainty in human

ventral temporal cortex. Curr Biol 25:595–600 Available at:

http://linkinghub.elsevier.com/retrieve/pii/S0960982214016534.

Klein BP, Harvey BM, Dumoulin SO (2014) Attraction of Position Preference by Spatial

Attention throughout Human Visual Cortex. Neuron:1–11 Available at:

http://linkinghub.elsevier.com/retrieve/pii/S089662731400748X [Accessed September 18,

2014].

Klein BP, Paffen CLE, Pas SF, Dumoulin SO (2016) Predicting bias in perceived position using

attention field models. J Vis 16:1–15.

Koenderink JJ (1990) The brain a geometry engine. Psychol Res 52:122–127.

Lee S, Papanikolaou A, Logothetis NK, Smirnakis SM, Keliris G a (2013) A new method for

estimating population receptive field topography in visual cortex. Neuroimage 81:144–157

Available at: http://www.ncbi.nlm.nih.gov/pubmed/23684878 [Accessed February 6, 2014].

Ma WJ, Beck JM, Latham PE, Pouget A (2006) Bayesian inference with probabilistic population

codes. Nat Neurosci 9:1432–1438 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/17057707 [Accessed February 28, 2013].

McAdams CJ, Maunsell JHR (1999) Effects of attention on orientation-tuning functions of single

neurons in macaque cortical area V4. J Neurosci 19:431–441 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/9870971.

Moran J, Desimone R (1985) Selective attention gates visual processing in the extrastriate

cortex. Science (80-) 229:782–784.

Navalpakkam V, Itti L (2007) Search Goal Tunes Visual Features Optimally. Neuron 53:605–

617.

Niebergall R, Khayat PS, Treue S, Martinez-Trujillo JC (2011) Expansion of MT neurons

excitatory receptive fields during covert attentive tracking. J Neurosci 31:15499–15510

Available at: http://www.ncbi.nlm.nih.gov/pubmed/22031896 [Accessed December 19,

2013].

Pouget A, Dayan P, Zemel RS (2003) Inference and computation with population codes. Annu

Rev Neurosci 26:381–410 Available at:

http://www.annualreviews.org/doi/abs/10.1146/annurev.neuro.26.041002.131112.

Regan D, Beverley KI (1985) Postadaptation orientation discrimination. J Opt Soc Am 2:147–

155.

Roberts M, Delicato LS, Herrero J, Gieselmann M a, Thiele A (2007) Attention alters spatial

integration in macaque V1 in an eccentricity-dependent manner. Nat Neurosci 10:1483–

1491.

Rose D (1999) The historical roots of the theories of local signs and labelled lines. Perception

28:675–685.

Scolari M, Serences JT (2009) Adaptive Allocation of Attentional Gain. J Neurosci 29:11933–

11942 Available at: http://www.jneurosci.org/cgi/doi/10.1523/JNEUROSCI.5642-08.2009.

Scolari M, Serences JT (2010) Basing perceptual decisions on the most informative sensory

neurons. J Neurophysiol 104:2266–2273.

Serences JT, Saproo S (2012) Computational advances towards linking BOLD and behavior.

Neuropsychologia 50:435–446 Available at:

http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=3384549&tool=pmcentrez&ren

dertype=abstract [Accessed January 30, 2014].

Seriès P, Stocker A a, Simoncelli EP (2009) Is the homunculus "aware" of sensory adaptation?

Neural Comput 21:3271–3304.

Sheremata SL, Silver MA (2015) Hemisphere-Dependent Attentional Modulation of Human

Parietal Visual Field Representations. J Neurosci 35:508–517 Available at:

http://www.jneurosci.org/cgi/doi/10.1523/JNEUROSCI.2378-14.2015 [Accessed January

14, 2015].

Sprague TC, Ester EF, Serences JT (2014) Reconstructions of information in visual spatial

working memory degrade with memory load. Curr Biol 24:2174–2180 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/25201683 [Accessed January 6, 2015].

Sprague TC, Ester EF, Serences JT (2016) Restoring Latent Visual Working Memory

Representations in Human Cortex. Neuron 91:694–707 Available at:

http://linkinghub.elsevier.com/retrieve/pii/S089662731630352X.

Sprague TC, Saproo S, Serences JT (2015) Visual attention mitigates information loss in small-

and large-scale neural codes. Trends Cogn Sci:1–12 Available at:

http://linkinghub.elsevier.com/retrieve/pii/S1364661315000297.

Sprague TC, Serences JT (2013) Attention modulates spatial priority maps in the human

occipital, parietal and frontal cortices. Nat Neurosci 16:1879–1887 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/24212672 [Accessed December 11, 2013].

Tolias AS, Moore T, Smirnakis SM, Tehovnik EJ, Siapas AG, Schiller PH (2001) Eye

movements modulate visual receptive fields of V4 neurons. Neuron 29:757–767.

Wandell BA, Winawer J (2015) Computational neuroimaging and population receptive fields.

Trends Cogn Sci:1–9 Available at: http://dx.doi.org/10.1016/j.tics.2015.03.009.

Womelsdorf T, Anton-Erxleben K, Pieper F, Treue S (2006) Dynamic shifts of visual receptive

fields in cortical area MT by spatial attention. Nat Neurosci 9:1156–1160 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/16906153 [Accessed December 16, 2013].

Womelsdorf T, Anton-Erxleben K, Treue S (2008) Receptive field shift and shrinkage in

macaque middle temporal area through attentional gain modulation. J Neurosci 28:8934–

8944 Available at: http://www.ncbi.nlm.nih.gov/pubmed/18768687 [Accessed December

16, 2013].

Zirnsak M, Steinmetz N a, Noudoost B, Xu KZ, Moore T (2014) Visual space is compressed in

prefrontal cortex before eye movements. Nature 507:504–507 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/24670771 [Accessed May 23, 2014].

FIGURES & TABLES

Figure 1. Covert spatial attention task and hypothesized representation changes with shifts of

spatial attention. (**a**) Subjects fixated centrally and attended to brief rotations in the pentagon

stimulus on the left or right while a flickering checkerboard probe stimulus appeared at one of 51

grid locations across the visual field. On control runs, subjects attended to a contrast change at

fixation. fMRI data measured during this attention task is used to create visualizable estimates of

voxel receptive fields (vRFs) and stimulus reconstructions. (**b**) A receptive field model is fit to

the responses of each voxel, and can be described by its x and y position (center), its response

baseline, response amplitude, and its size (full-width half maximum). (**c**) Given a population of

voxels in a retinotopic region, such as V1, we examine two different measures of spatial

information in the population. The first, a spatial discriminability metric, scales with the slope of

the tuning curve at a given location in space (**Materials and Methods**). The second relies on a

multivariate inverted encoding model (IEM) for space. By reconstructing images of the mapping

stimulus on each test trial, we can measure how population-level spatial information changes

with attention. We then can model how changes in individual vRFs affect both of these

population measures.

Figure 2. Changes in voxel receptive fields (vRFs) across attention conditions. We separately

estimated vRFs for every voxel in visual and posterior parietal areas, discarding poorly estimated

or noisy voxels (**Table 1**). Unless otherwise specified, figure data is averaged across subjects and

error bars show 95% confidence intervals computed by resampling the data distribution. (**a**) An

example vRF shows that attending covertly to the left location shifts the center of the receptive

field profile to the left, when compared to the neutral attend fixation condition. Voxel is from

subject AR in area V3A/B. (**b**) Our vRF estimates reproduced the canonical size-eccentricity

relationship (positive slope in all ROIs, p < minimum possible p-value, e.g., 1/10000 iterations)

and the increase in slope between visual regions. (**c**) Preferred position changes of V4 vRFs with

covert spatial attention. We binned each vRF by its position during the attend fixation condition.

The origin of each arrow is the center of each position bin. The end of the arrow shows the

average position shift of the vRFs within that position bin during the attend peripheral conditions

(left/right are collapsed and shown as attend left). The majority of vRFs shift toward the attended

location (blue-green color map vs. red-yellow). (**d**) Mean changes in vRF parameters (attend

peripheral target – attend fixation) in each visual area. (**e**) Attentional modulations of each vRF

parameter plotted by the vRF's distance from the attention target computed from its position

during the attend fixation task (**Table 2**).

1010

Figure 3. Spatial discriminability increases with attention and is mediated by position changes in

vRFs. Error bars depict bootstrapped 95% CIs. (**a**) We formulated a measurement to describe the

ability of a population of voxels to make fine spatial discriminations around the attention target.

We used the properties of each voxel's spatial tuning curve to make this measurement

(**Materials and Methods**). Spatial discriminability increased when subjects attended the target,

compared to when they ignored the target in the opposite hemifield (resampled p < minimum

possible p-value (1/1000) for all ROIs for all ROIs). (**b**) The discriminability metric was

recomputed for vRFs with a variety of attentional modulations. (*none* = vRF parameters during

the neural attend fixation condition; *a* = amplitude; *s* = size; *p* = position). Spatial

discriminability increased significantly when we applied position changes measured during the

attend L/R task to the vRFs compared to when we applied no parameter changes (solid bar). By

contrast, applying size changes did not change spatial discriminability in most ROIs, although it

did cause a small increase in IPS0.

Figure 4. Multivariate inverted encoding model (IEM) used to reconstruct the mapping probe

stimuli. (**a**) To train the IEM, we first take the BOLD data from all voxels within a visual region

from a subset of training trials. Then, we solve for a set of channel weights using least squares

regression. To reconstruct the stimulus, we invert this weight matrix and multiply it with BOLD

data from the same voxels during a test trial. This yields a reconstructed channel response

profile, which can be transformed into a reconstruction of the mapping stimulus on every trial in

each attention condition. Data shown are examples from participant AR for a subset of V1

voxels. (**b**) Example stimulus reconstructions for participant AI, V1. These reconstructions were

averaged across trials with the same position, yielding 51 reconstructions – one for each unique

position in the test dataset. In the left panel, the same averaged position reconstructions are

shown for each condition. The amplitude on the left is higher when attending left, and on the

right when attending right. (**c**) Average reconstruction sizes and amplitudes for each stimulus

position (collapsed across condition; left is attended). The diameter of the circle depicts the

average fit FWHM of the reconstructions at that spatial position. Reconstruction amplitude was

greater in the attended hemifield compared to the ignored hemifield in areas V3A/B and V4 (p

<= 0.005; **Table 3; Fig. 5**).

1041

1042 **Figure 5**. Reconstruction parameters as a function of mapping stimulus distance from the

1043 covertly attended locations and attention hemifield (attended vs. ignored). See **Table 3** for

1044 complete list of p-values.

Figure 6. A layered spatial encoding model reveals how different sets of vRF changes lead to

enhancements in multivariate stimulus reconstructions. (**a**) The first layer of the model uses the

vRF fits to generate BOLD data from every subject's real trial sequence. Then the BOLD data

from all voxels within one ROI is used to train a multivariate spatial encoding model and

reconstruct the mapping stimuli. (**b**) Change in reconstruction amplitude in the attended vs. the

ignored hemifield. We only show reconstruction parameters with significant attentional

modulations in the prior IEM analysis (**Fig 5**, **Table 3**). Stimulus reconstructions computed with

a reduced number of voxels (gray bar) largely reproduce the pattern of attentional modulations

observed in IEMs computed with all voxels (black bar). Furthermore, a comparison of layered

IEMs using simulated data revealed that vRF position changes (blue lines) in the first layer of the

model are better at reproducing the amplitude modulations in the stimulus reconstructions of the

parietal ROI than models which simulate changes in vRF size or amplitude (yellow & red lines).

(**c**) RMSE between each set of IEM fits and the full empirical dataset fits shown in **Fig 5**. The

null baseline model (far left) is a layered IEM where the vRF parameters are the same across all

attention conditions. We then added vRF attentional modulations for each parameter as shown in

the matrix below the plot, where all models with position changes are on the left side. * indicate

an FDR-corrected p-value <.05 for models that differed significantly from the null baseline

model. Gray asterisks indicate an increase in RMSE from the null model, whereas black asterisks

indicate a decrease.

1065

1066   **TABLES**

1067   **Table 1**. vRF selection statistics, pooled across participants (N = 7)

Region of interest	Total no. of localized voxels	No. of voxels after GLM thresholding	No. of voxels after regular- izability threshold	No. of voxels after cross- validation threshold	No. of voxels after removing difference score outliers	Percent that survive all thresholds	RMSE fit error for surviving voxels
V1	3,723	3,540	2,438	989	931	25.01%	0.1105
V2	4,154	3,970	3,115	1,405	1,339	32.23%	0.1087
V3	3,698	3,519	2,839	1,520	1,435	38.81%	0.0994
V3A/B	1,988	1,922	1,440	443	416	20.93%	0.0893
V4	1,702	1,492	1,118	361	336	19.74%	0.0783
IPS0	1,567	1,492	800	114	110	7.02%	0.0882
V1 – V4	13,277	12,521	9,510	4,275	4,041	30.44%	0.1032
V3A/B & IPS0	3,555	3,414	2,240	557	526	14.80%	0.0894
TOTAL	16,832	15,935	11,750	4,832	4,567	27.13%	0.1016

1068

1069   **Table 2**. Mean coefficients for polynomial fits of how vRF parameter change is modulated by

1070   distance from the attended location (*v_dist_attn*)

	Position	Size	Amplitude	Baseline
V1	-.069, .095	-.064	-.019, .137, .135	.011, -.073, .010
V2	.015, -.133, .082	-.064, .160	-.016, .125, .046	.011, -.066, .061
V3	.017, -.135, .033	-.073, .163	-.025, .170, .032	.009, -.053, .054
V4	-.162	-.181	.308	.011, -.078, .085
V3A/B	-.318	-.091, .461, -.520	.210	<.001
IPS0	-.425	-.445	-.076, .495	.073

1071

1072   [a] Number of reported coefficients in the table correspond to the polynomial order which was

1073   yielded the most parsimonious fit to the data (e.g., 1 coefficient for n = 0, 2 coefficients for n = 1,

1074   etc.).

1075   **Table 3**. 2-way ANOVA results for reconstruction parameter changes (*s_dist_attn* x attention

1076   hemifield).

	V1	V2	V3	V3A/B	V4	IPS0	V1 – V4	V3A/B & IPS0
Omnibus test								
Position	**<.001**	**<.001**	**<.001**	**<.001**	**<.001**	**.001**	**<.001**	**<.001**
Size	.216	.565	.019	**.006**	.428	.121	**.001**	.110
Amplitude	.174	.579	**.024**	**<.001**	**<.001**	**.008**	**.016**	**<.001**
Baseline	.088	.734	.934	**.001**	**<.001**	.937	**.015**	.241
Main effect of distance								
Position	**<.001**	**<.001**	**<.001**	**<.001**	**<.001**	.192	**<.001**	**<.001**
Size				.484			**.019**	
Amplitude			.140	**.005**	**.002**	.478	.100	**.002**
Baseline				.916	.829		.210	
Main effect of attention								
Position	.371	.916	.346	**.005**	.067	.254	.401	.343
Size				**.003**			**.005**	
Amplitude			.069	**.005**	**<.001**	.158	**.049**	.004
Baseline				**<.001**	**.001**		**.004**	
Interaction of distance & attention								
Position	.052	.588	.541	**<.001**	.657	**<.001**	.121	.026
Size				.077			.271	
Amplitude			.064	**<.001**	**<.001**	**.004**	.224	**<.001**
Baseline				.011	.019		.370	

1077

1078   [a] **bold** numbers indicate that the p-value passed FDR-correction (q = .05, corrected across ROIs

1079   and comparisons within each parameter).

1080   **Table 4**. RMSE (and 95% CIs) between reconstructions from the reduced dataset (only using voxels with RFs) or from different

1081   versions of the layered IEM using the same voxels.

	Reduced data	**p/s/a/b**	**p/a/b**	**p/s/b**	**s/a/b**	**p/a**	**s/a**	**p/s**	**p**	**a**	**s**	**none**
Combined occipital V1 – V4	0.133 [0.109, 0.170]	0.146 [0.146, 0.146]	0.148 [0.147, 0.148]	0.142 [0.141,0. 143]	0.194 [0.194, 0.194]	0.148 [0.148, 0.148]	0.194 [0.194, 0.194]	0.141 [0.141, 0.141]	0.143 [0.143, 0.143]	0.194 [0.194, 0.194]	0.194 [0.194, 0.194]	0.193 [0.193, 0.193]
Combined parietal V3A/B & IPS0	0.834 [0.744, 0.959]	0.415 [0.410, 0.419]	0.426 [0.422, 0.431]	0.411 [0.407, 0.416]	0.443 [0.439, 0.447]	0.425 [0.421, 0.430]	0.451 [0.447, 0.456]	0.410 [0.405, 0.416]	0.410 [0.406, 0.414]	0.441 [0.437, 0.445]	0.447 [0.442, 0.452]	0.834 [0.744, 0.959]

1082

1083   [a] To generate CIs, the resampling of the real data is performed at the level of the fits to the reconstructions, whereas resampling

1084   layered IEM RMSEs is described in **Materials and Methods**