1 Neural dynamics at successive stages of the ventral visual stream are
2 consistent with hierarchical error signals

Running title: Error signaling in the ventral stream

Elias B. Issa[1]*, Charles F. Cadieu[2], and James J. DiCarlo

McGovern Institute for Brain Research and Department of Brain and Cognitive Sciences
Massachusetts Institute of Technology, Cambridge, Massachusetts 02139

*Correspondence: Elias Issa, elias.issa@columbia.edu

[1]Current address: Department of Neuroscience, Zuckerman Mind Brain Behavior Institute, Columbia
University, New York, NY 10027
[2] Current address: Bay Labs, Inc. San Francisco, CA 94102

AUTHOR CONTRIBUTIONS
Conceptualization, E.B.I and J.J.D.; Methodology, E.B.I., C.F.C, and J.J.D.; Investigation, E.B.I.; Formal
Analysis: E.B.I. and C.F.C; Writing – Original Draft, E.B.I., C.F.C., and J.J.D.; Writing – Review &
Editing, E.B.I. and J.J.D.; Funding Acquisition, E.B.I., C.F.C., and J.J.D.; Resources, J.J.D.;
Supervision, J.J.D.

ABSTRACT

Ventral visual stream neural responses are dynamic, even for static image presentations. However,

dynamical neural models of visual cortex are lacking as most progress has been made modeling static,

time-averaged responses. Here, we studied population neural dynamics during face detection across

three cortical processing stages. Remarkably, ~30 milliseconds after the initially evoked response, we

found that neurons in intermediate level areas decreased their preference for faces, becoming anti-face

preferring on average even while neurons in higher level areas achieved and maintained a face

preference. This pattern of hierarchical neural dynamics was inconsistent with extensions of standard

feedforward circuits that implemented recurrence within a cortical stage. Rather, recurrent models

computing errors between stages captured the observed temporal signatures. Without additional

parameter fitting, this model of neural dynamics, which simply augments the standard feedforward

model of online vision to encode errors, also explained seemingly disparate dynamical phenomena in

the ventral stream.

INTRODUCTION

The primate ventral visual stream is a hierarchically organized set of cortical areas beginning with the

primary visual cortex (V1) and culminating with distributed patterns of neural firing across the inferior

temporal cortex (IT) that explicitly encode objects (i.e. linearly decodable object identity) (Hung,

Kreiman, Poggio, & DiCarlo, 2005) and quantitatively account for core invariant object discrimination

behavior in primates (Majaj, Hong, Solomon, & DiCarlo, 2015). Formalizing object recognition as the

result of a series of feedforward computations yields models that achieve impressive performance in

object categorization (Krizhevsky, Sutskever, & Hinton, 2012)(Zeiler & Fergus, 2013) similar to the

absolute level of performance achieved by IT neural populations, and these models are the current best

predictors of neural responses in IT cortex and its primary input layer, V4 (Cadieu et al., 2014)(Yamins

et al., 2014). Thus, the feedforward inference perspective provides a simple but powerful, first-order

framework for the ventral stream and core invariant object recognition.

However, visual object recognition behavior may not be executed via a single feedforward neural

processing pass (a.k.a. feedforward inference) because IT neural responses are well-known to be

dynamic even in response to images without dynamic content (Brincat & Connor, 2006)(Sugase,

Yamane, Ueno, & Kawano, 1999)(Chen et al., 2014)(Meyer, Walker, Cho, & Olson, 2014), raising the

question of what computations those neural activity dynamics might reflect. Prior work has proposed

that such neuronal response dynamics could be the result of different types of circuits executing

different types of computation such as: 1) recurrent circuits within each ventral stream processing stage

implementing local normalization of the feedforward information as it passes through the stage

(Carandini, Heeger, & Movshon, 1997)(Schwartz & Simoncelli, 2001)(Carandini & Heeger, 2012), 2)

feedback circuits between each pair of ventral stream stages implementing the integration of top-down

with bottom-up information to improve the current (online) inference (Seung, 1997)(Lee, Yang, Romero,

& Mumford, 2002)(Zhang & Heydt, 2010)(Epshtein, Lifshitz, & Ullman, 2008), or 3) feedback circuits

between each pair of stages comparing top-down and bottom-up information to compute prediction

errors that guide changes in synaptic weights so that neurons are better tuned to features useful for

future feedforward behavior (learning) (Rao & Ballard, 1999). Thus, neural dynamics may reflect the

various adaptive computations (within-stage normalization, top-down Bayesian inference) or reflect the

underlying error intermediates that could be generated during those processes (e.g. predictive coding).

These computationally motivated ideas can each be implemented as neural circuits to ask which

idea best predicts response dynamics across the visual hierarchy. Here, our main goal was to look

beyond the initial, feedforward response edge to see if we could disambiguate among dynamics that

might result from stacked feedforward, lateral, and feedback operations. Rather than record from a

single processing level, we measured the dynamics of neural signals across three hierarchical levels

(pIT, cIT, aIT) within macaque IT. We focused on face processing subregions within each of these

levels for three reasons. First, prior evidence argues that these three subregions are tightly

anatomically and functionally connected and that the subregion in pIT is the dominant input to the

higher subregions (Grimaldi, Saleem, & Tsao, 2016)(Moeller, Freiwald, & Tsao, 2008). Second,

because prior work argues that a key behavioral function of these three subregions is to distinguish

faces from non-faces, this allowed us to focus our testing on a relatively small number of images

targeted to engage that processing function. Third, prior knowledge of pIT neural tuning properties (Issa

& DiCarlo, 2012) allowed us to design images that were quantitatively matched in their ability to drive

neurons in the pIT input subregion but that should ultimately be processed into two separate groups

(face vs. non-face). We reasoned that these images would force important computations for

disambiguation to occur somewhere between the pIT subregion and the higher level (cIT, aIT)

subregions. With this setup, our aim was to observe the dynamics at all three levels of the hierarchy in

response to that image processing challenge so that we might discover – or at least constrain -- which

type of computation is at work.

Consistent with the idea that the overall system performs face vs. non-face discrimination (i.e.

face detection), we found that in the highest face processing stage (aIT), neurons rapidly developed

and maintained a response preference for faces over non-faces even though our images were

designed to be challenging for frontal face detection. However, we found that many neurons in the early

(pIT) and intermediate (cIT) processing levels of IT had face selectivity that rapidly but paradoxically

decreased. That is, the responses of these neurons evolved to prefer images of non-faces over images

of faces within 30 milliseconds of their feedforward response. We found that standard feedforward

models that employ local recurrences such as adaptation, lateral inhibition, and normalization could not

capture this stage-wise pattern of image selectivity despite our best attempts. However, we found that

decreasing -- rather than increasing -- face preference in early and intermediate processing stages is a

natural dynamical signature of previously suggested "error coding" models (Rao & Ballard, 1999) in

which the neural spiking activity at each processing stage carries both an explicit representation of the

variables of interest (e.g. is a face present?) and an explicit encoding of errors computed between each

pair of stages in the hierarchy (e.g. a face was predicted, but a non-face was present leading to an

error).

RESULTS

We leveraged the hierarchically arranged face processing system in macaque ventral visual cortex to

study the dynamics of neural processing across a hierarchy (Tsao, Freiwald, Tootell, & Livingstone,

2006)(Tsao, Moeller, & Freiwald, 2008) (**Figure 1A**). The serially arranged posterior, central, and

anterior face-selective subregions of IT (pIT, cIT, and aIT) can be conceptualized as building increasing

selectivity for faces culminating in aIT representations (Freiwald & Tsao, 2010)(Chang & Tsao, 2017).

Using serial, single electrode recording, we sampled neural sites across the posterior to anterior extent

of the IT hierarchy in the left hemispheres of two monkeys to generate neurophysiological maps

(**Figure 1A**; example neurophysiological map in one monkey using a faces versus non-face objects

screen set) (Issa, Papanastassiou, & DiCarlo, 2013). We localized the recording locations *in vivo* and

co-registered across all penetrations using a stereo microfocal x-ray system (~400 micron *in vivo*

resolution) (Cox, Papanastassiou, Oreper, Andken, & DiCarlo, 2008)(Issa, Papanastassiou, Andken, &

DiCarlo, 2010) allowing accurate assignment of sites to different face processing stages (n = 633 out of

1891 total sites recorded were assigned as belonging to a face-selective subregion based on their

spatial location; see **Methods**). Results are reported here for sites that were spatially located in a face-

selective subregion, that showed visual drive to any category in the screen set (see **Methods**), and that

were subsequently tested with our face versus non-face challenge set (**Figure 1B**, left panel) (n = 115

pIT, 70 cIT, and 40 aIT sites).

Our experimental design was intended to test previously proposed computational hypotheses of

hierarchical neural dynamics during visual face processing (**Figure 1B**). Briefly, these hypotheses

predict how stimulus preference (in this instance, for faces versus non-faces) might change over time in

a neural population (**Figure 1B**, middle panel): (1) simple spike-rate adaptation predicts that initial rank-

order selectivity (i.e. relative stimulus preference) will be largely preserved (**Figure 1B**, dashed line)

while neurons adapt their absolute response strength over time, (2) local normalization predicts that

stronger responses are in some cases normalized to match weaker responses based on population

activity to specific dimensions (Carandini et al., 1997); importantly, normalization is strongest for

nuisance (non-coding) dimensions (e.g. low versus high stimulus contrast) and in its idealized form

would not alter selectivity along coding dimensions (e.g. face versus non-face) (**Figure 1B**, dashed

line), (3) evidence accumulation through temporal integration, winner-take-all through recurrent

inhibition, or Bayesian inference through top-down feedback mechanisms all predict increasing

selectivity for faces over time (Lee & Mumford, 2003) (**Figure 1B**, light gray line), and (4) predictive

coding posits that, for neurons that are coding error, their responses would show increasing activity for

non-faces (images whose properties are inconsistent with predictions of a face) and thus decreasing

face selectivity over time (Rao & Ballard, 1999) (**Figure 1B**, black line). Note, that error signaling is a

qualitatively different computation than normalization, as error coding predicts a decreased response

along the coding dimension (face versus non-face) whereas normalization would ideally not affect

selectivity for faces versus non-faces and only affect variation along orthogonal, nuisance dimensions.

Properly testing these predictions (no change in face selectivity, increased face selectivity, decreased

selectivity to be anti-face preferring) requires measurements from the intermediate stages of the

hierarchy as all of these models operate under the premise that the system builds and maintains a

preference for faces at the top of the hierarchy (**Figure 1B**, right, and see Introduction). Thus, the

intermediate stages (here pIT, see **Figure 1B**) are most likely to be susceptible to face/non-face

confusion and thus be influenced by, for example, the top-down mechanisms posited in Bayesian

inference and predictive coding where higher areas encode the face predictions that directly influence

the responses of lower areas (Lee & Mumford, 2003)(Rao & Ballard, 1999).

Face and non-face images driving similar initial responses in pIT

Here, we chose to focus our key, controlled tests on pIT – an intermediate stage in the ventral stream

hierarchy, but the first stage within IT where neural specialization for face detection (i.e. face vs. non-

face) has been reported (Grimaldi et al., 2016). Consistent with its intermediate position in the ventral

visual system, we had previously found that pIT face-selective neurons are not truly selective for whole

faces but respond to local face features, specifically those in the eye region (Issa & DiCarlo, 2012).

Taking advantage of this prior result, we created both face and non-face stimuli that challenged the

face processing system by strongly driving pIT responses, thus forcing the higher IT stages to complete

the discrimination between face and challenging non-face images. To generate ambiguous face-like

images, we systematically varied the positions of parts, in particular the eye, within the face (Issa &

DiCarlo, 2012) (see **Methods**). This set included images that contained face parts in positions

consistent with a frontal view of a face or images that only differed in the relative spatial configuration of

the face parts within the face outline (**Figure 1B**, left). Of the 82 images screened, we identified 21 part

configurations that each drove the pIT population response to $\geq$90% of its response to a correctly

configured whole face. Of those 21 images, 13 images were inconsistent with the part configuration of a

frontal face (**Figure 1B**, black box). For the majority of the results that follow, we focus on comparing

the neural responses to these 13 pIT-matched images that could *not* have arisen from frontal faces

(referred to hereafter as "non-face images") with the 8 images that could have arisen from frontal faces

(referred to hereafter as "face images"). Again, we stress that these two groups of images were

selected to evoke closely matched initial pIT population activity.

Importantly, the pIT-matched images used here presented a more stringent test of face vs. non-

face discrimination than prior work. Specifically, most prior work used images of faces and non-face

objects ("classic images") that contain differences across multiple dimensions including local contrast,

spatial frequency, and types of features (Tsao et al., 2006)(Afraz, Kiani, & Esteky, 2006)(Moeller,

Crapse, Chang, & Tsao, 2017)(Sadagopan, Zarco, & Freiwald, 2017). Consistent with this, we found

that the population decoding classification accuracy of our recorded neural populations using these

classic images (faces versus non-face objects) is near perfect (>99% in pIT, cIT, and aIT, n=30 sites

per region). However, we found that population decoding classification accuracy for the pIT-matched

face vs. non-face images we used here was near chance level (50%) in pIT (**Figure 1C**, blue bar; by

comparison, classification accuracy for face versus non-face objects classification was 99.6% using the

same pIT sites). Further downstream in regions cIT and aIT, we found that the linear population

decoding classification of these pIT-matched face vs. non-face images was well above chance,

suggesting that our pIT-matched face detection challenge is largely solved somewhere between pIT

and aIT (**Figure 1C**).

Time course of responses in pIT for images with face versus non-face arrangements of parts

We next closely examined the pIT neural response dynamics. To do this, we defined a face preference

value (d'; see Methods) that measured each site's average selectivity for the face images relative to the

non-face images, and we asked how a given site's preference evolved over time (see alternative

hypotheses in **Figure 1B**). First, we present three example sites which were chosen based on having

the largest selectivity (absolute d') in the late phase (100-130 ms post image onset). In particular, most

standard interpretations of face processing would predict a late phase preference for faces (d' > 0).

However, all three sites with the largest absolute d' had evolved a strong late phase preference for the

non-face images (d' < 0) despite having had very similar rising edge responses to the face and non-

face stimulus classes (response in early phase from 60-90 ms) (**Figure 2**, left column). A late, non-face

preference was not restricted to the example sites as a majority of pIT sites (66%) preferred non-faces

over faces in the late response phase (prefer frontal face arrangement: 60-90 ms = 66% vs. 100-130

ms = 34%; p = 0.000, n = 115) (**Figure 3B**, blue bars).

Next, we examined the dynamics of face selectivity across the pIT population as this is key to

disambiguating among the competing models outlined earlier (**Figure 1B**). In the adaptation and

normalization models, we would expect no change in the average population face selectivity, and the

evidence accumulation, winner-take-all, or Bayesian inference models predict an increase in face

selectivity over the population over time. Instead, we found that many sites significantly decreased their

face preference over time similar to the three example sites. Of the 51 sites in our pIT sample that

showed a significantly changing preference over time (p < 0.01 criterion for significant change in d'),

84% of these sites showed a decreasing preference (n = 43 of 51 sites, p < 10^-6, binomial test, n =

115 total sites) (**Figure 3A**, left column, light gray vs. black lines). This surprising trend -- decreasing

face preference -- was strong enough that it erased any small, initial preference for images of frontally

arranged face parts over the population (median d': 60-90 ms = 0.11 $\pm$ 0.02 vs. 100-130 ms = -0.12 $\pm$

0.03, p = 0.000, n=115 sites), and this trend was observed in both monkeys when analyzed separately

(p_{M1} = 0.000, p_{M2} = 0.002, n_{M1} = 43, n_{M2} = 72 sites; **Figure 4A**). This decreasing face selectivity over

time was driven by decreasing firing rates to the face images containing normally arranged face parts.

Responses to these images were weaker by 18% on average in the late phase of the response

compared to the early phase (Δrate (60-90 vs 100-130 ms) = -18% $\pm$ 4%, p = 0.000; n = 7 images)

while responses to the non-face images with atypical spatial arrangements of face parts -- also capable

of driving high early phase responses -- did not experience any firing rate reduction in the late phase of

the response (Δrate (60-90 vs 100-130 ms) = 2 $\pm$ 1%, p = 0.467; n = 13 images).

The above observation of decreasing face preference over the pIT population seemed most

consistent with the prediction of error coding models, but one potential confound was that initial

responses to faces and challenging non-faces were not perfectly matched across the population (recall

that we only required face and non-face images to drive a response $\geq$90% of the whole face response).

As a result, initial selectivity was non-zero (d' = 0.11, n=115 sites). This residual face preference may

be small, but if this residual face selectivity is driven by nuisance dimensions, for example excess

stimulus contrast in the face class relative to the non-face class, then the face class may have

experienced stronger activity dependent adaptation or normalization resulting in a decreasing face

preference over time. To more adequately limit general activity dependent mechanisms leading to

decreasing face responses, we performed control analyses where initial activity was tightly matched per

site or where the number of parts were matched across images.

Controls in pIT for firing rate and low-level image variation

To strictly control for the possibility that simple initial firing rate differences could predict the observed

phenomenon, we re-computed selectivity after first matching initial responses site-by-site. For this

analysis, images were selected on a per site basis to evoke similar initial firing rates (images driving

initial response within 25% of synthetic whole face response for that site, at least 5 images required per

class). This image selection procedure virtually eliminated any differences in initial responses between

the face and non-face image classes and hence any firing rate difference driven by differences in

nuisance parameters between faces and challenge non-faces (**Figure 3C**, 60-90 ms), yet we still

observed a significant drop in preference for images with typical frontal face part arrangements versus

atypical face part arrangements in pIT ($\Delta_{d'}$ = -0.10 $\pm$ 0.03, p = 0.001, n = 77) (**Figure 3C**, blue line).

Thus, the remaining dependence of firing rate dynamics on the image class and not on initial response

strength argued against an exclusively activity based explanation to account for decreasing neural

responses to faces over time. Further arguing against this hypothesis, we found that the pattern of late

phase population firing rates in pIT across images could not be significantly predicted from early phase

pIT firing rates for each image ($\rho_{pIT\ early,\ pIT\ late}$ = 0.07 $\pm$ 0.17, p = 0.347; n = 20 images).

Thus far, we have performed analyses where images from the face and non-face class were

similar in their initially evoked response which equated images at the level of neural activity but

produced images varying in the number of parts. An alternative is to match the number of face parts

between the face and non-face classes as another means of limiting the differences in nuisance

dimensions such as the contrast, spatial frequency and retinal position of energy across images (see

examples in **Figure 4B**). When we recomputed selectivity across subsets of images containing a

matched number of one, two, or four parts (n=5, 30, and 3 images, respectively), we still observed that

pIT face selectivity decreased. For all three image subsets controlling the number of face parts, d'

began positive on average in the sampled pIT population (i.e. preferred frontal face part arrangements

in 60-90 ms post-image onset) (median d' for 60-90 ms = 0.13 $\pm$ 0.05, 0.05 $\pm$ 0.02, 0.33 $\pm$ 0.09 for one,

two, and four parts) and significantly decreased in the next phase of the response (100-130 ms post-

image onset) becoming negative on average (median d' for 100-130 ms: -0.27 $\pm$ 0.06, -0.14 $\pm$ 0.02, -

0.04 $\pm$ 0.12; one, two, four parts: p = 0.000, 0.000, 0.004, for d' comparisons between 60-90 ms and

100-130 ms, n = 115, 115, 76 sites) (**Figure 4B**). A similar decreasing face selectivity profile was

observed when we re-tested single part images at smaller (3^{o}) and larger (12^{o}) image sizes suggesting

a dependence on the relative configuration of the parts and not on their absolute retinal location or

absolute retinal size (median d' for 60-90 ms vs. 100-130 ms: three degrees = 0.51 $\pm$ 0.09 vs. -0.29 $\pm$

0.14, twelve degrees = 0.07 $\pm$ 0.14 vs. -0.11 $\pm$ 0.14; n = 15; p = 0.000, 0.025, 0.07) (**Figure 4C**). Thus,

we suggest that the decreasing population face selectivity dynamic in pIT is a fairly robust phenomenon

specific to the face versus non-face dimension as this dynamic persists even when limiting potential

variation across nuisance dimensions. This phenomenon can be distinguished from normalization

mechanisms that would operate most strongly to reduce selectivity along nuisance dimensions rather

than along dimensions that directly solve the face versus non-face discrimination challenge.

Time course of responses in aIT and cIT for images with face versus non-face arrangements of

parts

Under the possibility that decreasing face selectivity in intermediate stage pIT is a signature of error

signaling, we next asked whether the source of the prediction signal could be observed in higher

cortical areas. In the anterior face-selective regions of IT which are furthest downstream of pIT and

reflect additional stages of feedforward processing (see block diagram in **Figure 1B**), we did not

observe the strong decreases in the selectivity profile seen in pIT. Indeed, the three sites with the

greatest selectivity (absolute d') in the late response phase (100-130 ms) in our aIT sample all

displayed a preference for frontal face part arrangements (d' > 0) (**Figure 2**, right column). Also, in

contrast to the dynamic selectivity profiles observed in many pIT sites, 98% of aIT sites (39 of 40) did

not significantly change their relative preference for face vs. non-face arrangements of the parts (p <

0.01 criterion for significant change at the site level) (**Figure 3A,** right column, bottom row, dark gray

sites). Rather, we observed a stable selectivity profile over time in aIT (median d': 60-90 ms = 0.13 $\pm$

0.03 vs. 100-130 ms = 0.17 $\pm$ 0.03, p = 0.34, n=40 sites). As a result, the majority of anterior sites

preferred images with typical frontal arrangements of the face parts in the late phase of the response

(prefer face: 60-90 ms = 78% of sites vs. 100-130 ms = 78% of sites; p = 0.451, n = 40 sites; **Figure**

3B, red bars) despite only a minority (34%) of upstream sites in pIT preferring these images in their late

response. Thus, spiking responses of individual aIT sites were as expected from a computational

system whose purpose is to detect faces, as previously suggested (Freiwald & Tsao, 2010), and aIT

serves as one candidate for the putative prediction signal underlying face prediction errors.

In cIT whose anatomical location is intermediate to pIT and aIT, we observed many sites with

decreasing selectivity (**Figure 2C & 3A**, middle columns), a dynamic that persisted even when we

tightly matched initial responses on a site by site basis similar to pIT (**Figure 2C**, green line). The

overall stimulus preference in cIT was intermediate to that of pIT and aIT (**Figure 3B**) consistent with

the intermediate position of cIT in the IT hierarchy. Interestingly, we found that the patterns of

responses across images in the early phases of cIT and aIT activity were significant predictors of late

phase activity in pIT ($\rho_{cIT\ early,\ pIT\ late}$ = -0.52 $\pm$ 0.11, p = 0.000; $\rho_{aIT\ early,\ pIT\ late}$ = -0.36 $\pm$ 0.14, p = 0.012;

n_{pIT}=115, n_{cIT}=70, n_{aIT}=40 sites; n = 20 images), even better predictors than early phase activity in pIT

itself ($\rho_{pIT\ early,\ pIT\ late}$ = 0.07 $\pm$ 0.17, p = 0.347). That is, for images that produced high early phase

responses in cIT and aIT, the following later phase responses of units in the lower level area (pIT)

tended to be low, consistent with error coding models which posit that feedback from higher areas (in

the form of predictions) would contribute to the decreasing selectivity observed in lower areas.

Computational models of neural dynamics in IT

We next proceeded to formalize the conceptual ideas introduced in **Figure 1B** and build neurally

mechanistic, dynamical models of gradually increasing complexity to determine the minimal set of

assumptions that could capture our empirical findings of non-trivial, dynamic selectivity changes during

face detection across face-selective subregions in IT. Previous functional and anatomical data show

that the face-selective subregions in IT are connected forming an anterior to posterior hierarchy and

show that pIT serves as the primary input into this hierarchy (Moeller et al., 2008)(Freiwald & Tsao,

2010)(Grimaldi et al., 2016). Thus, we evaluated dynamics in different hierarchical architectures using a

linear dynamical systems modeling framework where pIT, cIT, and aIT act as sequential stages of

processing (**Figure 5** and see **Methods**). A core principle of feedforward ventral stream models is that

object selectivity is built by stage-wise feature integration in a manner that leads to relatively low

dimensional representations at the top of the hierarchy abstracted from the high-dimensional input

layer. We were interested in how signals temporally evolve across a similar architectural layout. We

used the simplest feature integration architecture where a unit in a downstream area linearly sums the

input from units in an upstream area, and we stacked this computation to form three layer networks

(**Figure 5B**). This simple, generic feedforward encoding model conceptualizes the idea that different

types of evidence, local and global (i.e. information about the parts and the relative spatial arrangement

of parts), have to converge and be integrated to separate face from non-face images in our image set.

We used linear networks as monotonic nonlinearities can be readily accommodated in our framework

(Seung, 1997)(Rao & Ballard, 1999)(also see **Figure 7C**). Importantly, we used a simple encoding

scheme as our goal was not to build full-scale deep neural network encoding models of image

representation (Yamins et al., 2014) but to bring focus to an important biological property that is often

not considered in deep nets, neural dynamics.

We implemented a range of ideas previously proposed in the literature. The functional

implications of these ideas were highlighted in **Figure 1B**, but at a mechanistic level, these functional

properties can be directly realized via different recurrent processing motifs between neurons (**Figure 5**,

base feedforward model (first column) is augmented with recurrent connections to form new models

(remaining columns)). For example, self-connections can be viewed as implementing spike rate

adaptation in a feedforward architecture (**Figure 5A**, top row), lateral connections support winner-take-

all or normalization mechanisms (Carandini et al., 1997) (**Figure 5A**, second, third, and fourth

columns), and top-down connections implement Bayesian inference (Seung, 1997) (**Figure 5A**, fifth

and sixth columns). Here, normalization is implemented by a leak term that scales adaptation (the

degree of decay in the response) and is controlled recursively by the summed activity of the network

(Carandini et al., 1997), ultimately scaling down responses to strong driving stimuli over time. To

constrain our choice of a feedback-based model, we took a normative approach minimizing a quadratic

reconstruction cost between stages as the classical reconstruction cost is at the core of an array of

hierarchical generative models including hierarchical Bayesian inference (Lee & Mumford, 2003),

Boltzmann machines (Ackley, Hinton, & Sejnowski, 1985), analysis-by-synthesis networks (Seung,

1997), sparse coding (Olshausen & Field, 1996), predictive coding (Rao & Ballard, 1999), and

autoencoders in general (Rifai, Vincent, Muller, Glorot, & Bengio, 2011). Optimizing a quadratic loss

results in feedforward and feedback connections that are symmetric -- reducing the number of free

parameters -- such that inference on the represented variables at any intermediate stage is influenced

by both bottom-up sensory evidence and current top-down interpretations. Critically, a common feature

of this large model family is the computation of between-stage error signals via feedback, which is

distinct from state-estimating model classes (i.e. feedforward models) that do not compute or propagate

errors. A dynamical implementation of such a network uses leaky integration of error signals which, as

shared computational intermediates, guide gradient descent of the values of the represented variables

to a previously learned target value (Δactivity of each neuron => online inference) or descend the

connection weights to values that give the best future behavior (Δsynaptic strengths => offline learning),

here defined as an unsupervised reconstruction goal (similar results were found using other goals and

networks such as supervised discriminative networks; see **Figure 7C**).

When we fit each of the models to our neural data, they generally produced an increase in

selectivity from the first stage of the network to the later stages of the network. This increase is not

surprising because the models had built-in converging feedforward connections from the first to second

to third stages (**Figure 6A**, first five columns, compare blue to red curves). However, discrepancies

between models emerged in the lower stages where we found that neither the lateral inhibition model,

nor the normalization model, could capture the decreasing selectivity phenomenon observed in pIT.

Instead, the selectivity of these models simply increased to a saturation level set by the leak term

(shunting inhibition) in the system (**Figure 6A**, first five columns). Similar behavior was present when

we tried a nonlinear implementation of the normalization model that more powerfully modulated

shunting inhibition (Carandini et al., 1997). That normalization proved insufficient to generate the

observed neural dynamics can be explained by the fact that the normalized response to a stimulus

cannot easily fall below the response to a stimulus that was initially similar in strength. Thus, a

decreasing average preference for a stimulus across a population of cells (i.e. **Figures 2-4**, pIT data)

for similar levels of average input is difficult when only using a basic normalization model mediated by

surround (within-stage) suppression.

In contrast to the above models, we found that the feedback model capable of computing

hierarchical error signals naturally displayed a strong decrease of selectivity in a sub-component of its

first processing stage -- qualitatively similar behavior to the selectivity decrease that we observed in

many pIT and cIT neural sites. Specifically, this model displayed these dynamics in the magnitude of its

reconstruction error signals but not in its state signals (the feature values) (**Figure 6A,** compare fifth

and sixth columns). These error signals integrate converging state signals from two stages -- one

above (prediction) and one below (sensory evidence). The term "error" is thus meaningful in the hidden

processing stages where state signals from two stages can converge. The top nodes of a hierarchy

receive little descending input and hence do not carry additional errors with respect to the desired

computation; rather, top nodes convey the face predictions that influence errors in bottom nodes. This

behavior in the higher processing stages is consistent with our observation of explicit representation of

faces in aIT in all phases of the response (**Figures 2-3**) and with similar observations of decodable

identity signals by others in all phases of aIT responses for faces (Meyers, Borzello, Freiwald, & Tsao,

2015) and objects (Hung et al., 2005)(Majaj et al., 2015). We also found similar error dynamics when

using a simpler two-layer network as opposed to three layers suggesting that these error signal

dynamics along with prediction signals emerge even in the simplest cascaded architecture (**Figure 7A**).

Predictions of an error coding hierarchical model

While our neural observations at multiple stages of the IT hierarchy led us to the error coding

hierarchical model above, a stronger test of the idea of error signaling is whether it predicts other IT

neural phenomena. To identify stimulus regimes that would lead to insightful predictions, we asked in

what way would the behavior of error-estimating hierarchical models differ most from the behavior of

generic feedforward state-estimating models. Because our feedback-based model uses feedforward

inference at its core, it behaves similarly to a state-estimating hierarchical feedforward model when the

statistics of inputs match the learned feedforward weight pattern of the network (i.e. 'natural' images

drawn from everyday objects and scenes) since for these inputs, feedforward inferences derived from

the sensory data are aligned with top-down expectations. Thus, predictions of feedback-based models

that could distinguish them from feedforward-only models are produced when the natural statistics of

images are altered so that they differ from the feedforward patterns previously learned by the network

and hence differ from the predictions generated in the network. We have (above) considered one such

type of alteration: images where local face features are present but altered from their naturally

occurring (i.e. statistically most likely) arrangement in frontal faces. Next, we tested two other image

manipulations from recent physiology studies which yielded novel neural phenomena that lacked a

principled, model-based explanation (Freiwald, Tsao, & Livingstone, 2009)(Meyer et al., 2014). To test

whether the error coding hierarchical model family displays these behaviors, we fixed the architectural

parameters derived from our fitting procedure in **Figure 6** and simply varied the input to this network,

specifically the correlation between the inputs and the network's feedforward weight pattern, in order to

match the nature of the image manipulations performed in prior experiments.

Sublinear integration of the face features. In the face-selective subregion of cIT, the sum of the

responses to the face parts exceeds the response to the whole face when averaging firing rates over a

200 ms window (Freiwald et al., 2009; see their Figure 2C), and we observed a similar phenomenon in

the face-selective subregion in pIT (Issa & DiCarlo, 2012). Interestingly, examining the dynamics of part

integration more closely within the first 100ms of the response reveals that the response to the whole

face does begin at a level similar to the sum of the responses to the face parts but becomes sublinear

in the late phase (whole face response relatively low compared to linear prediction from parts

responses) (ratio of sum of responses to parts vs. response to whole: 60-90 ms = 1.5 ± 0.1, 100-130

ms = 4.6 ± 0.3; p = 0.000, n = 33 sites) (**Figure 8A**, left panel). This result runs counter to what would

be expected in a model where selectivity for the whole face is built from the conjunction of the parts. In

such a model, the population response to the whole face would be at least as large if not greater

(superlinear) than the summed responses to the individual features. To test whether an error coding

model exhibited the phenomenon of sublinear feature integration at the population level, we compared

the response with all inputs active (co-occurring features) to the sum of the responses when each input

was activated independently (individual features). The reconstruction errors in our feedback-based

model showed a strong degree of sublinear integration of the inputs such that the response to the

simultaneous inputs (whole) was much smaller than what would be predicted by a linear sum of the

responses to each input alone (parts), and the model's sublinear integration behavior qualitatively

replicated the time course observed in pIT without any additional fitting of parameters (**Figure 8A**, right

panel). Although we certainly expect that similar sublinear integration may also be observed in a

normalization model, this would require a particularly strong form of normalization since population

activity to the whole face would have to be normalized to nearly the same level as that for an individual

part in the late response phase (ratio of response to single part vs. response to whole = 0.92 ± 0.06,

100-130 ms, n = 33 sites) despite being three times larger during the early response phase (ratio of

response to single part vs. response to whole = 0.3 ± 0.02, 60-90 ms, n = 33 sites). Furthermore, the

stacked normalization model could not account for the main dynamical phenomenon that we observed

(**Figure 6**); therefore, an error coding perspective may provide a more parsimonious account of the

observed set of dynamical phenomena.

Evolution of neural signals across time. Neural responses to familiar images are known to rapidly

attenuate in IT when compared to responses to novel images (Freedman, Riesenhuber, Poggio, &

Miller, 2006)(Woloszyn & Sheinberg, 2012)(Meyer & Olson, 2011). This observation seems to

contradict what would be predicted by simple Hebbian potentiation for the more exposed stimuli.

Furthermore, familiar image responses show much sharper temporal dynamics than responses to novel

images when presented repeatedly (Meyer et al., 2014). These qualitatively different dynamics for

familiar versus novel images are surprising given that stimuli are drawn from the same distribution of

natural images and are thus matched in their average image-level statistical properties (color, spatial

frequency, contrast). To test whether our network displayed these different dynamical behaviors, we

simulated familiar inputs as those that match the learned weight pattern of a high-level detector and

novel inputs as those with the same overall input level but with weak correlation to the learned network

weights (here, we have extended the network to include two units in the output stage corresponding to

storage of the two familiarized input patterns to be alternated; conceptually, we consider these familiar

pattern detectors as existing downstream of IT in a region such as perirhinal cortex which has been

shown to code familiarized image statistics and memory-based object signals (Murray, Bussey, &

Saksida, 2007)). We repeatedly alternated two familiar inputs or two novel inputs and found that error

coding model responses in the hidden processing stage were temporally sharper for familiar inputs that

matched the network's feedforward weight patterns compared to novel patterns of input (pseudo-

randomly drawn; see **Methods**), consistent with the previously observed phenomenon (**Figure 8B**; data

reproduced with permission from Meyer et al., 2014). Model responses reproduced additional details of

the neural dynamics including a large initial peak followed by smaller peaks for responses to novel

inputs and a phase delay in the oscillations of responses to novel inputs compared to familiar inputs.

Intuitively, these dynamics are composed of two phases after the initial response transient to the onset

of the image sequence. In the first phase, familiar patterns lead to lower errors and hence lower neural

responses than random patterns (**Figure 8B**, red curve drops below the black curve after the onset

response), similar to the observed weaker response to more familiar face-like images present in our

data (**Figure 2**, red curves drop below black curves in pIT example sites). When the familiar pattern *A*

is switched to another familiar pattern *B*, this induces a short-term error in adjusting to the new pattern

(**Figure 8B**, red curve briefly goes above the black curve during pattern switch and then decreases). In

contrast, two unfamiliar patterns are closer together in the high-level encoding space than two learned

patterns (**Figure 8B**, inset at right), and the switch between two unlearned patterns introduces relatively

less shift in top-down signals and hence a smaller dynamical change in error signals. This result

demonstrates that our model, derived from fitting only the first 70 ms (60-130 ms post image onset) of

IT responses to face images, can extend to much longer timescales and may generalize to studies of

images besides face images.

Dynamical properties of neurons across cortical lamina

In the large family of state-error coding hierarchical networks, a number of different cortical circuits are

possible. A key distinction of two such circuit mapping hypotheses (predictive coding versus error

backpropagation) is the expected laminar location of state coding neurons transmitting information

about features in the image. In typical neural network implementations, the feedforward projecting

neurons in superficial lamina are presumed to encode estimates about states of the visual world (e.g.

presence of a face). In contrast, predictive coding posits that superficial layers contain error units and

that errors are projected forward to the next cortical level (Rao & Ballard, 1999)(Friston & Kiebel,

2009)(Hyvärinen, Hurri, & Hoyer, 2009). State and error signals can be distinguished by their dynamical

signatures in our leading model, which was fit on error signals but produces predictions of the

corresponding state signals underlying the generation of errors. Since state units are integrators (see

Methods), they have slower dynamics than error units leading to longer response latencies and a

milder decay in responses (**Figure 8C**, red curve in right panel). To test this prediction, we localized our

recordings relative to the cortical mantle by co-registering the x-ray determined locations of our

electrode (~400 micron *in vivo* accuracy; (Issa et al., 2010)) to structural MRI data (see **Methods**).

When we separated units into those at superficial depths closer to the pial surface (1/3 of our sites;

corresponds to approximately 0 to 1 mm in depth) versus those in the deeper layers (remaining 2/3 of

sites, ~1 to 2.5 mm in depth), we found a longer latency and less response decay in superficial units

consistent with the expected profile of state units (**Figure 8C**, left panel). Thus, the trend toward state-

like signals in superficial layers is more consistent with typical error backpropagation models (states fed

forward, errors fed backward) than with predictive coding proposals. In fact, the latency difference

between cortical lamina in pIT (deep vs superficial: 66.0 ± 1.7 vs 76.0 ± 1.8 ms, p = 0.002) was greater

than the conduction delay from pIT to cIT (i.e. from superficial layers of pIT to the deeper layers of cIT)

(superficial pIT vs deep cIT: 76.0 ± 1.8 vs 75.5 ± 2.0 ms, p = 0.15) even though laminar distances

within pIT are smaller than the distance traveled between cortical stages pIT and cIT. Thus, instead of a

simple conduction delay accounting for latency differences across lamina, our model suggests that

temporal integration of inputs in superficial lamina, more consistent with the behavior of state units as

opposed to error units, may drive the lagged dynamical properties of neurons in superficial lamina.

DISCUSSION

We have measured neural responses during a difficult frontal face detection task across the IT

hierarchy and demonstrated that the population preference for faces in the intermediate (a.k.a hidden)

processing stages decreases over time – that is population responses at lower levels of the hierarchy

(pIT and cIT) rapidly evolved toward preferring unnatural, non-face part arrangements whereas the top

level (aIT) rapidly developed and then maintained a preference for natural, frontal face part

arrangements. The relative speed of selectivity changes in pIT (~30 ms) makes high-level explanations

based on fixational eye movements or shifts in attention (e.g. from behavioral surprise to unnatural

arrangements of face parts) unlikely as saccades and attention shifts occur on slower timescales

(hundreds of milliseconds) (Egeth & Yantis, 1997). The presence of stronger responses to face images

than to non-face images in aIT further argues against general arousal effects as these would have been

expected to cause stronger responses to challenging non-face images in aIT. Rather, the rapid

propagation of neural signals over tens of milliseconds suggested intracortical processing within the

ventral visual stream in a manner that was not entirely consistent with a pure feedforward model, even

when we included strong nonlinearities in these models such as normalization and even when we

stacked these operations to form more complex three stage models. However, augmenting the

feedforward model so that it represented the errors generated during hierarchical processing produced

the observed neural dynamics and hierarchical signal propagation (**Figures 6-7**). This view argues that

many IT neurons code error signals. Using this new modeling perspective, we went on to generate

predictions of previously observed IT neural phenomena (**Figure 8**).

Comparison to previous neurophysiology studies in IT

Our suggestion that many IT neurons code errors is consistent with the observation of strong

responses to extremes in face space (Leopold, Bondar, & Giese, 2006) providing an alternative

interpretation to the prior suggestion that cIT neurons are not tuned for typical faces but are instead

tuned for atypical face features (i.e. extreme feature tuning) (Freiwald et al., 2009). In that prior work,

the response preference of each neuron was determined by averaging over a long time window (~200

ms). By looking more closely at the fine time scale dynamics of the IT response, we suggest that this

same extreme coding phenomenon can instead be interpreted as a natural consequence of networks

that have an actual tuning preference for typical faces (as evidenced by an initial response preference

for typical frontal faces in pIT, cIT, and aIT; **Figure 3B**) but that also compute error signals with respect

to that preference. Under the present hypothesis, some IT neurons are preferentially tuned to typical

spatial arrangements of face features, and other IT neurons are involved in coding errors with respect

to those typical arrangements. We speculate that these intermixed state estimating and error coding

neuron populations are both sampled in standard neural recordings of IT, even though only state

estimating neurons are truly reflective of the tuning preferences of that IT processing stage. This

intermixed view of IT neural signaling is further supported by recent studies demonstrating correlates of

temporal prediction errors to image sequences in IT (Meyer & Olson, 2011) including the face-selective

subregion of cIT (Schwiedrzik & Freiwald, 2017).

The precise fractional contribution of errors to total neural activity is difficult to estimate from our

data. Under the primary image condition tested, not all sites significantly decreased their selectivity

(~60% did not change their selectivity). We currently interpret these sites as coding state (feature)

estimates (**Figure 3A**, light and dark gray lines in top and bottom rows, respectively), and we did

observe evidence of emergence of state-like signals in our superficial neural recordings (**Figure 8C**).

Alternatively, at least some of the non-reversing sites might be found to code errors under other image

conditions than the one that we tested. Furthermore, while in our primary image condition selectivity

decreases only accounted for ~15% of the overall spiking modulation (**Figure 6A**, data panel), larger

modulations in late phase neural firing (50-100%) are possible under other image conditions (**Figure

8A,B**). At a computational level, the absolute contribution of error signals to spiking may not be the

critical factor as even a small relative contribution may have important consequences in the network.

Comparison across dynamical models of neural processing

Our goal was to test a range of existing recurrent models by recording neural dynamics across multiple

cortical stages which provided stronger constraints on computational models than fitting neural

responses from only one area as in prior work (Carandini et al., 1997)(Rao & Ballard, 1999). Crucially,

we found that the multi-stage neural dynamics observed in our data could not be adequately fit by only

using recurrences within a stage such as adaptation, lateral inhibition, and standard forms of

normalization (**Figure 6**). These results did not change when we made our simple networks more

complex by adding more stages (compare **Figure 6** versus **Figure 7**) or by using more realistic model

units with monotonic nonlinearities similar to a spiking nonlinearity (data not shown). Indeed, we

specifically chose our stimuli to evoke similar levels of within stage neural activity to limit the effects of

known mechanisms that depend on activity levels within an area (e.g. adaptation, normalization), and

we fully expect that these activity dependent mechanisms would operate in parallel to top-down,

recurrent processes during general visual processing. We emphasize that we only tested the standard

form of normalization as originally proposed, using within stage pooling and divisive mechanisms

(Carandini et al., 1997). Since that original mechanistic formulation, normalization has evolved to

become a term that broadly encapsulates many forms of suppression phenomena and can include both

lateral interactions within an area and feedback interactions from other areas (Nassi, Gómez-Laberge,

Kreiman, & Born, 2014)(Coen-Cagli, Kohn, & Schwartz, 2015). Thus, while our results do not follow

from the original mechanistic form of normalization, they may yet fall under normalization more broadly

construed as a term for suppression phenomena (error coding would require a similar suppressive

component). Here, we have provided a normative model for how top-down suppression would follow

from the well-defined computational goals of many hierarchical neural network models.

Error signals generated across different hierarchical inference and learning models

The notion of error is inherent to many existing models in the literature that go beyond the basic

feedforward, feature estimation class. Example models use errors for guiding top-down inference by

computing errors implicitly (hierarchical Bayesian inference (Seung, 1997)(Lee & Mumford, 2003)) or by

representing errors explicitly (predictive coding (Rao & Ballard, 1999)). In addition, errors can be used

specifically for driving unsupervised learning (autoencoder (Rifai et al., 2011)) or supervised learning

(classic error backpropagation (Williams & Hinton, 1986)). Recently, models have incorporated aspects

of both inference and learning (Salakhutdinov & Hinton, 2012)(Patel, Nguyen, & Baraniuk, 2015). A

key, unifying feature across inference and learning models is the need to compute an error signal

between processing stages. This error signal can be in the form of a generative, reconstruction cost

(stage *n* predicting stage *n-1*) or a discriminative, construction cost (stage *n-1* predicting stage *n*).

Across-stage "performance" error terms are used in all model cost functions, are typically the only term

combining signals from different model stages, and are distinct from within-stage "regularization" terms

(i.e. sparseness or weight decay) in driving network behavior (Marblestone, Wayne, & Kording, 2016).

The present study provides evidence that such errors are not only computed, but that they are explicitly

encoded in spiking rates. We emphasize that this result at the level of population dynamics was robust

across choices of cost function such as those used in the literature; we tested models with different

unsupervised and supervised performance errors (reconstruction, nonlinear reconstruction, and

discriminative) and found similar population level error signals across these networks in the basic two-

layer implementation (**Figure 7C**). Thus, errors as generally instantiated in the state-error coding

hierarchical model family provide a good approximation to IT population neural dynamics.

Computational utility of coding errors in addition to states

In error-computing networks, errors provide control signals for guiding learning giving these networks

additional adaptive power over basic feature estimation networks. This property helps augment the

classical, feature coding view of neurons which, with only feature activations and Hebbian operations,

does not lead to efficient learning in the manner produced by gradient descent using error

backpropagation (Williams & Hinton, 1986). Observation of error signals may provide insight into how

more intelligent unsupervised and supervised learning algorithms such as backpropagation could be

plausibly implemented in the brain. A potentially important contribution of this work is the suggestion

that gradient descent algorithms are facilitated by using an error code so that efficient learning is

reduced to a simple Hebbian operation at synapses and efficient inference is simply integration of

inputs at the cell body (see *eqn 10* and text in **Methods**). This representational choice, to code the

computational primitives of gradient descent in spiking activity, would simply leverage the existing

biophysical machinery of neurons for inference and learning.

MATERIALS & METHODS

Animals and surgery. All surgery, behavioral training, imaging, and neurophysiological techniques are

identical to those described in detail in previous work (Issa & DiCarlo, 2012). Two rhesus macaque

monkeys (*Macaca mulatta*) weighing 6 kg (Monkey 1, female) and 7 kg (Monkey 2, male) were used. A

surgery using sterile technique was performed to implant a plastic fMRI compatible headpost prior to

behavioral training and scanning. Following scanning, a second surgery was performed to implant a

plastic chamber positioned to allow targeting of physiological recordings to posterior, middle, and

anterior face patches in both animals. All procedures were performed in compliance with National

Institutes of Health guidelines and the standards of the MIT Committee on Animal Care and the

American Physiological Society.

Behavioral training and image presentation. Subjects were trained to fixate a central white fixation

dot during serial visual presentation of images at a natural saccade-driven rate (one image every 200

ms). Although a 4^o fixation window was enforced, subjects generally fixated a much smaller region of

the image ($<1^o$) (Issa & DiCarlo, 2012). Images were presented at a size of 6^o except for control tests at

3^o and 12^o sizes (**Figure 4C**), and all images were presented for 100 ms duration with 100 ms gap

(background gray screen) between each image. Up to 15 images were presented during a single

fixation trial, and the first image presentation in each trial was discarded from later analyses. Five

repetitions of each image in the general screen set were presented, and ten repetitions of each image

were collected for all other image sets. The screen set consisted of a total of 40 images drawn from

four categories (faces, bodies, objects, and places; 10 exemplars each) and was used to derive a

measure of face versus non-face object selectivity. Following the screen set testing, some sites were

tested using an image set containing images of face parts presented in different combinations and

positions (**Figure 1B**, left panel). We first segmented the face parts (eye, nose, mouth) from a monkey

face image. These parts were then blended using a Gaussian window, and the face outline was filled

with pink noise to create a continuous background texture. A face part could appear on the outline at

any one of nine positions on an evenly spaced 3x3 grid. Although the number of possible images is

large (4^9 = 262,144 images), we chose a subset of these images for testing neural sites (n = 82

images). Specifically, we tested the following images: the original whole face image, the noise-filled

outline, the whole face reconstructed by blending the four face parts with the outline, all possible single

part images where the eye, nose, or mouth could be at one of nine positions on the outline (n = 3x9 =

27 images), all two part images containing a nose, mouth, left eye, or right eye at the correct outline-

centered position and an eye tested at all remaining positions (n = 4*8-1 = 31 images), all two part

images containing a correctly positioned contralateral eye while placing the nose or mouth at all other

positions (n = 2*8-2 = 14 images), and all correctly configured faces but with one or two parts missing

besides those already counted above (n = 4+3 = 7 images). The particular two-part combinations

tested were motivated by prior work demonstrating the importance of the eye in early face processing

(Issa & DiCarlo, 2012), and we sought to determine how the position of the eye relative to the outline

and other face parts was encoded in neural responses. The three and four part combinations were

designed to manipulate the presence or absence of a face part for testing the integration of face parts,

and in these images, we did not vary the positions of the parts from those in a naturally occurring face.

In a follow-up test on a subset of sites, we permuted the position of the four face parts under the

constraint that they still formed the configuration of a naturally occurring face (i.e. preserve the 'T'

configuration, n = 10 images; **Figure 4B**). We tested single part images at 3^o and 12^o sizes in a subset

of sites (n = 27 images at each size; **Figure 4C**). Finally, we measured the responses to the individual

face parts in the absence of the outline (n = 4 images; **Figure 8A**).

MR Imaging and neurophysiological recordings. Both structural and functional MRI scans were

collected in each monkey. Putative face patches were identified in fMRI maps of face versus non-face

object selectivity in each subject. A stereo microfocal x-ray system (Cox et al., 2008) was used to guide

electrode penetrations in and around the fMRI defined face-selective subregions of IT. X-ray based

electrode localization was critical for making laminar assignments since electrode penetrations are

often not perpendicular to the cortical lamina when taking a dorsal-ventral approach to IT face patches.

Laminar assignments of recordings were made by co-registering x-ray determined electrode

coordinates to MRI where the pial-to-gray matter border and the gray-to-white matter border were

defined. Based on our prior work estimating sources of error (e.g. error from electrode tip localization

and brain movement), registration of electrode tip locations to MRI brain volumes has a total of <400

micron error which is sufficient to distinguish deep from superficial layers (Issa et al., 2013). Multi-unit

activity (MUA) was systematically recorded at 300 micron intervals starting from penetration of the

superior temporal sulcus such that all sites at these regular intervals were tested with a screen set

containing both faces and non-face objects, and a subset of sites that were visually driven were further

tested with our main image set manipulating the position of face parts. Although we did not record

single-unit activity, our previous work showed similar responses between single-units and multi-units on

images of the type presented here (Issa & DiCarlo, 2012), and our results are consistent with

observations in previous single-unit work in IT (Freiwald et al., 2009). Recordings were made from PL,

ML, and AM in the left hemisphere of monkeys 1 and 2 and additionally from AL in monkey 2. AM and

AL are pooled together in our analyses forming the aIT sample while PL and ML correspond to the pIT

and cIT samples, respectively.

Neural data analysis. The face patches were physiologically defined in the same manner as in our

previous study (Issa & DiCarlo, 2012). Briefly, we fit a graded 3D sphere model (linear profile of

selectivity that rises from a baseline value toward the maximum at the center of the sphere) to the

spatial profile of face versus non-face object selectivity across our sites. We tested spherical regions

with radii from 1.5 to 10 mm and center positions within a 5 mm radius of the fMRI-based centers of the

face patches. The resulting physiologically defined regions were 1.5 to 3 mm in diameter. Sites which

passed a visual response screen (mean response in a 60-160 ms window >2*SEM above baseline for

at least one of the four categories in the screen set) were included in further analysis. All firing rates

were baseline subtracted using the activity in a 25-50 ms window following image onset averaged

across all repetitions of an image. Finally, given that the visual response latencies in monkey 2 were on

average 13 ms slower than those in monkey 1 for corresponding face-selective regions, we applied a

single latency correction (13 ms shift to align monkey 1 and monkey 2's data) prior to averaging across

monkeys. This was done so as not to wash out any fine timescale dynamics by averaging. Similar

results were obtained without using this latency correction as dynamics occurred at longer timescales

(~30 ms). This single absolute adjustment was more straightforward than the site-by-site adjustment

used in our previous work (Issa & DiCarlo, 2012) (though similar results were obtained using this

alternative latency correction); even when each monkey was analyzed separately, we still observed pIT

selectivity dynamics (**Figure 4A**). Images that produced an average population response $\geq$ 0.9 of the

initial response (60-100 ms) to a face image with all face parts arranged in their typical positions in a

frontal face were analyzed further (**Figures 2 and 3**). Stimulus selection was intended to limit

potentially confounding differences in visual drive between image classes. In a control test, we also

repeated our analysis by selecting images on a site-by-site basis where images with frontal face and

non-face arrangements of parts were chosen to be within 0.75x to 1.25x of the initial response to the

complete face image (minimum of five face and five non-face images in this response range for

inclusion of site in analysis). In follow-up analyses of population responses, we specifically limited

comparison to images with the same number of parts (**Figure 4B,C**). For example, for single part

images, we used the image with the eye in the upper, contralateral region of the outline as a reference

requiring a response $\geq$ 0.9 of the initial population response to this reference for inclusion of the images

in this analysis. We found that four other images of the 27 single-part images elicited a response at

least as large as 90% of the response to this standard image. For images containing all four face parts,

we used the complete, frontal face as the standard and found non-face arrangements of the four face

parts that drove at least 90% of the early response to the whole face (2 images out of 10 tested). To

compute individual site d' for each of these stimulus partitions (e.g. typical versus atypical

arrangements of 1 face part), we combined all presentations of images with frontal face arrangements

and compared these responses to responses from all presentations of images with non-face

arrangements using $d' = (u_1 - u_2)/((var_1 + var_2)/2)^{1/2}$ where variance was computed across all trials for that

image class (e.g. all presentations of all typical face images); this was identical to the d' measure used

in previous work for computing selectivity for faces versus non-face objects (Aparicio, Issa, & DiCarlo,

2016; Ohayon, Freiwald, & Tsao, 2012). For example, for the main image set (**Figure 2A**), we

compared all presentations of frontal face arrangements (8 images x 10 presentations/image = 80 total

presentations) to all presentations of non-face arrangements (13 images x 10 presentations/image =

130 total presentations) to compute the d' values for each site in two time windows (60-90 ms and 100-

130 ms) as shown in **Figure 3A**. A positive d' implies a stronger response to more naturally occurring

frontal face arrangements of face parts while a negative d' indicates a preference for unnatural non-

face arrangements of the face parts.

Dynamical models

Modeling framework and equations. To model the dynamics of neural response rates in a hierarchy, we

start with the simplest possible model that might capture those dynamics: a model architecture

consisting of a hidden stage of processing containing two units that linearly converge onto a single

output unit. We use this two-stage cascade for illustration of the basic concepts which can be easily

extended to longer cascades with additional stages, and we ultimately used a three-stage version of the

model to fit our neural data collected from three cortical stages (**Figures 5B & 6**).

An external input is applied separately to each hidden stage unit, which can be viewed as

representing different features for downstream integration. We vary the connections between the two

hidden units within the hidden processing stage (lateral connections) or between hidden and output

stage units (feedforward and feedback connections) to instantiate different model families. The details

of the different architectures specified by each model class can be visualized by their equivalent neural

network diagrams (**Figure 5**). Here, we provide a basic description for each model tested. All two-stage

models utilized a 2x2 feedforward identity matrix *A* that simply transfers inputs ***u*** (2x1) to hidden layer

units ***x*** (2x1) and a 1x2 feedforward vector *B* that integrates hidden layer activations ***x*** into a single

output unit *y*.

$A = aI, \; B = b[1,1]$ (1)

By simply substituting in the appropriate unit vector and weight matrix transforming inputs from one

layer to the next for the desired network architecture, this simple two-stage architecture can be

extended to larger networks (e.g. see three-stage network diagrams in **Figure 5B**). To generate

dynamics in the simple networks below, we assumed that neurons act as leaky integrators of their total

synaptic input, a standard rate-based model of a neuron used in previous work (Seung, 1997)'(Rao &

Ballard, 1999).

Pure feedforward. In the purely feedforward family, connections are exclusively from hidden to output

stages through feedforward matrices *A* and *B*.

759             $$\dot{\mathbf{x}} = A\mathbf{u} - \mathbf{x}/\tau \qquad \dot{y} = B\mathbf{x} - y/\tau \tag{2}$$

761   where τ is the time constant of the leak current which can be seen as reflecting the biophysical

762   limitations of neurons (a perfect integrator with large τ would have almost no leak and hence infinite

763   memory).

765   *Lateral inhibition.* Lateral connections (matrix with off-diagonal terms) are included and are inhibitory.

766   The scalar k_l sets the relative strength of lateral inhibition versus bottom-up input.

768             $$\dot{\mathbf{x}} = A\mathbf{u} - \begin{bmatrix} 0 & k_l \\ k_l & 0 \end{bmatrix}\mathbf{x} - \mathbf{x}/\tau \qquad\qquad \dot{y} = B\mathbf{x} - y/\tau \tag{3}$$

770   *Normalization.* An inhibitory term that scales with the summed activity of units within a stage is

771   included. The scalar k_s sets the relative strength of normalization versus bottom-up input.

773             $$\dot{\mathbf{x}} = A\mathbf{u} - k_s \sum x \cdot \mathbf{x} - \mathbf{x}/\tau \qquad\qquad \dot{y} = B\mathbf{x} - k_s y \cdot y - y/\tau \tag{4}$$

775   *Normalization (nonlinear)* (Carandini et al., 1997). The summed activity of units within a stage is used to

776   nonlinearly scale shunting inhibition.

778             $$\dot{\mathbf{x}} = A\mathbf{u} - \frac{\mathbf{x}}{\tau\sqrt{1 - k_s \sum x}} \qquad\qquad \dot{y} = B\mathbf{x} - \frac{y}{\tau\sqrt{1 - k_s y}} \tag{5}$$

Note that this is technically a nonlinear dynamical system, and since the normalization term in equation

(5) is not continuously differentiable, we used the fourth-order Taylor approximation around zero in the

simulations of equation (5).

Feedback (linear reconstruction). The feedback-based model is derived using a normative framework

that performs optimal inference in the linear case (Seung, 1997) (unlike the networks in equations (2)-

(5) which are motivated from a mechanistic perspective but do not directly optimize a squared error

performance loss). The feedback network minimizes the cost *C* of reconstructing the inputs of each

stage (i.e. mean squared error of layer *n* predicting layer *n-1*).

$$C = \frac{1}{2}(\mathbf{u} - A^T\mathbf{x})^2 + \frac{1}{2}(\mathbf{x} - B^T y)^2 \qquad (6)$$

Differentiating this coding cost with respect to the encoding variables in each layer *x*, *y* yields:

$$\frac{\partial C}{\partial \mathbf{x}} = -A(\mathbf{u} - A^T\mathbf{x}) + (\mathbf{x} - B^T\mathbf{y}) \qquad \frac{\partial C}{\partial \mathbf{y}} = -B(\mathbf{x} - B^T\mathbf{y}) \qquad (7)$$

The cost function *C* can be minimized by descending these gradients over time to optimize the values

of *x* and *y*:

$$\frac{\mathrm{d}\mathbf{x}}{\mathrm{d}t} = -\frac{\partial C}{\partial \mathbf{x}} = A(\mathbf{u} - A^T\mathbf{x}) - (\mathbf{x} - B^T\mathbf{y}) - \mathbf{x}/\tau$$

800   (8)

$$\frac{\mathrm{d}\mathbf{y}}{\mathrm{d}t} = -\frac{\partial C}{\partial \mathbf{y}} = B(\mathbf{x} - B^T\mathbf{y}) - \mathbf{y}/\tau$$

The above dynamical equations are equivalent to a linear network with a connection matrix containing

symmetric feedforward (B) and feedback (B^T) weights between stages x and y as well as within-stage

pooling followed by recurrent inhibition ($-AA^Tx$ and $-BB^Ty$) that resembles normalization. The property

that symmetric connections minimize the cost function C generalizes to a feedforward network of any

size or number of hidden processing stages (i.e. holds for arbitrary lower triangular network connection

matrix). The final activation states (x,y) of the hierarchical generative network are optimal in the sense

that the bottom-up activations (implemented through feedforward connections) are balanced by the top-

down expectations (implemented by feedback connections) which is equivalent to a Bayesian network

combining bottom-up likelihoods with top-down priors to compute the maximum *a posteriori* (MAP)

estimate. Here, the priors are embedded in the weight structure of the network. In simulations, we

include an additional scalar k_{td} that sets the relative weighting of bottom-up versus top-down signals.

$$\dot{\mathbf{x}} = A(\mathbf{u} - A^T\mathbf{x}) - k_{td}(\mathbf{x} - B^Ty) - \mathbf{x}/\tau \qquad\qquad (9)$$

Error signals computed in the feedback model. In equation (9), inference can be thought of as

proceeding through integration of inputs on the dendrites of neuron population x. In this scenario, all

computations are implicit in dendritic integration. Alternatively, the computations in equation (9) can be

done in two steps where, in the first step, reconstruction errors are computed (i.e. $e_0 = u\text{-}A^Tx$, $e_1 = x\text{-}$

B^Ty) and explicitly represented in a separate error coding population. These error signals can then be

integrated by their downstream target population to generate the requisite update to the state signal of

neuron population x.

$$\dot{\mathbf{x}} = A\mathbf{e}_0 - k_{td}\mathbf{e}_1 - \mathbf{x}/\tau \qquad\qquad \dot{\mathbf{y}} = B\mathbf{e}_1 - y/\tau \qquad\qquad (10)$$

An advantage of this strategy is that the a state unit now directly receives errors as inputs, and those

inputs allow implementation of an efficient Hebbian rule for learning weight matrices (Rao & Ballard,

1999) -- the gradient rule for learning is simply a product of the state activation and the input error

activation (weight updates obtained by differentiating equation (6) with respect to weight matrices A and

B: $\Delta A = \mathbf{x} \cdot \mathbf{e_0}^T$, $\Delta A^T = \mathbf{e_0} \cdot \mathbf{x}^T$, $\Delta B = y \cdot \mathbf{e_1}^T$, and $\Delta B^T = \mathbf{e_1} \cdot y$). Thus, the reconstruction errors serve as

computational intermediates for both the gradients of online inference mediated by dendritic integration

(dynamics in state space, equation (10)) and gradients for offline learning mediated by Hebbian

plasticity (dynamics in weight space).

In order for the reconstruction errors at each layer to be scaled appropriately in the feedback

model, we invoke an additional downstream variable z to predict activity at the top stage such that,

instead of $\mathbf{e_2} = y$ which scales as a state variable, we have $\mathbf{e_2} = y\text{-}C^T z$ (**Figure 5A**). This overall model

reflects a state and error coding model as opposed to a state only model.

Feedback (three-stage). For the simulations in **Figures 6 and 8**, three-stage versions of the above

equations were used. These deeper networks were also wider such that they began with four input

units ($\boldsymbol{u}$) instead of only two inputs in the two-stage models. These inputs converged through

successive processing stages ($\boldsymbol{w,x,y}$) to one unit at the top node ($\boldsymbol{z}$) (**Figure 5B**).

Feedback (nonlinear reconstruction). To test the generality of our findings beyond a linear

reconstruction cost, we simulated feedback-based models which optimized different candidate cost

functions proposed for the ventral stream (**Figure 7C**). In nonlinear hierarchical inference,

reconstruction is performed using a monotonic nonlinearity with a threshold (*th*) and bias (*bi*):

$$C = \frac{1}{2}\left(\mathbf{u} - f(A^T\mathbf{x})\right)^2 + \frac{1}{2}\left(\mathbf{x} - f(B^T\mathbf{y})\right)^2, \quad where\ f(x) = tanh(x - th) + bi \quad (11)$$

853     $$\dot{\mathbf{x}} = A(\mathbf{u} - f(A^T\mathbf{x}))(1 - tanh(A^T\mathbf{x} - th)^2) - k_{td}(\mathbf{x} - f(B^T y)) - \mathbf{x}/\tau$$

854   (12)

$$\dot{\mathbf{y}} = B(\mathbf{x} - f(B^T\mathbf{y}))(1 - tanh(B^T\mathbf{y} - th)^2) - \mathbf{y}/\tau$$

Feedback (linear construction). Instead of a reconstruction cost where responses match the input (i.e.

generative model) as in unsupervised learning, we additionally simulated the states and errors in a

feedback network minimizing a linear construction cost where the network is producing responses to

match a given output (i.e. discriminative model) similar to supervised learning:

$$C = \frac{1}{2}\left(A\mathbf{u} - \mathbf{x}\right)^2 + \frac{1}{2}\left(B\mathbf{x} - \mathbf{y}\right)^2 \quad (13)$$

$$\dot{\mathbf{x}} = (A\mathbf{u} - \mathbf{x}) - k_{td}B^T(B\mathbf{x} - \mathbf{y}) - \mathbf{x}/\tau \qquad \dot{\mathbf{y}} = (B\mathbf{x} - \mathbf{y}) - \mathbf{y}/\tau \quad (14)$$

Model simulation. To simulate the dynamical systems in equations (2)-(14), a step input ***u*** was

applied. This input was smoothed using a Gaussian kernel to approximate the lowpass nature of signal

propagation in the series of processing stages from the retina to pIT:

$$\mathbf{u}(t) = \frac{1}{\sqrt{2\pi\sigma^2}}\ e^{\frac{-(t-t_0)^2}{2\sigma^2}} * \mathbf{h}(t) \Rightarrow \dot{\mathbf{u}} = \frac{1}{\sqrt{2\pi\sigma^2}}\ e^{\frac{-(t-t_0)^2}{2\sigma^2}} \cdot \mathbf{h} \quad (15)$$

where the elements of **h** are scaled Heaviside step functions. The input is thus a sigmoidal ramp whose

latency to half height is set by t_0 and rise time is set by σ. For simulation of two-stage models, there

were ten basic parameters: latency of the input t_0, standard deviation of the Gaussian ramp σ, system

time constant τ, input connection strength a, feedforward connection strength b, the four input values

across two stimulus conditions (i.e. h_{11}, h_{12}, h_{21}, h_{22}), and a factor sc for scaling the final output to the

neural activity. In the deeper three-stage network, there were a total of fifteen parameters which

included an additional feedforward connection strength c and additional input values since the three-

stage model had four inputs instead of two. The lateral inhibition model class required one additional

parameter k_l as did the normalization model family k_s, and for feedback model simulations, there was

an additional feedback weight k_{td} to scale the relative contribution of the top-down errors in driving

online inference. For the error coding variants of the feedback model, gain parameters c (two-stage)

and d (three-stage) were included to scale the overall magnitude of the top level reconstruction error

(also see **Figure 5** for locations of parameters in network diagrams).

Model parameter fits to neural data. In fitting the models to the observed neural dynamics, we

mapped the summed activity in the hidden stage (**w**) to population averaged activity in pIT, and we

mapped the summed activity in the output stage (**y**) to population averaged signals measured in aIT. To

simulate error coding, we mapped the reconstruction errors $e_1 = w\text{-}B^T x$ and $e_3 = y\text{-}C^T z$ to activity in pIT

and aIT, respectively. We applied a squaring nonlinearity to the model outputs as an approximation to

rectification since recorded extracellular firing rates are non-negative (and linear rectification is not

continuously differentiable). Analytically solving this system of dynamical equations (2)-(14) for a step

input is precluded because of the higher order interaction terms (the roots of the determinant and hence

the eigenvalues/eigenvectors of a 3x3 or larger matrix are not analytically determined, except for the

purely feedforward model which only has first-order interactions), and in the case of the normalization

models, there is an additional nonlinear dependence on the shunt term. Thus, we relied on

computational methods (constrained nonlinear optimization) to fit the parameters of the dynamical

systems to the neural data with a quadratic (sum of squares) loss function.

Parameter values were fit in a two-step procedure. In the first step, we fit only the difference in

response between image classes (differential mode which is the selectivity profile over time, see **Figure**

6A, right data panel), and in the second step, we refined fits to capture an equally weighted average of

the differential mode and the common mode (the common mode is the average across images of the

response time course of visual drive). This two-step procedure was used to ensure that each model

had the best chance of fitting the dynamics of selectivity (differential mode) as these selectivity profiles

were the main phenomena of interest but were smaller in size (20% of response) compared to overall

visual drive. In each step, fits were done using a large-scale algorithm (interior-point) to optimize

coarsely, and the resulting solution was used as the initial condition for a medium-scale algorithm

(sequential quadratic programming) for additional refinement. The lower and upper parameter bounds

tested were: t_0=[50 70], σ=[0.5 25], τ =[0.5 1000], k_l,k_s,k_{td}=[0 1], a,b,c,d=[0 2], h=[0 20], sc=[0 100], th=[-

20 20], and bi=[-1 1] which proved to be adequately liberal as parameter values converged to values

that did not generally approach these boundaries. To avoid local minima, the algorithm was initialized to

a number of randomly selected points (n = 50), and after fitting the differential mode, we took the top

fits (n = 25) for each model class and used these as initializations in subsequent steps. The single best

fitting instance of each model class is shown in the main figures.

Model predictions. For the predictions in **Figure 8**, all architectural parameters obtained by the fitting

procedure above were held fixed; only the pattern of inputs to the network was varied. For **Figure 8A**,

to test the input integration properties of a model, we used the top-performing model and compared the

response to all inputs presented simultaneously with the sum of the responses to each input alone.

For **Figure 8B**, we approximated novel versus familiar images by parametrically varying the

degree to which input patterns were random (inputs drawn from i.i.d. uniform distributions on the

interval [0,1]) versus structured in a way that matched the weight pattern of the network. Here, we used

a version of the model with two independent outputs reflecting detectors for two familiarized input

patterns (output 1 tuned to pattern A: u_1, u_2, u_3, u_4 active and output 2 tuned to pattern 2: u_5, u_6, u_7, u_8

active) (**Figure 8B**). Alternating between these two input patterns simulates alternation of two

familiarized (learned) images as compared to purely random patterns (u_{1-8} independent and identically

distributed). The first-to-second layer weights were [1,1,1,1,0,0,0,0] for pattern A and [0,0,0,0,1,1,1,1]

for pattern B, so to parametrically vary the degree of correlation of inputs to this weight pattern from

random (correlation = 0) to deterministic (correlation = 1), we drew input values from a joint distribution

$P(u_1,u_2,u_3,u_4,u_5,u_6,u_7,u_8)$ where u_{1-4} were drawn from a high-valued uniform distribution on the interval

$[1-\varepsilon,1]$ and u_{5-8} were drawn from a low-valued uniform distribution $[0, \varepsilon]$ for stimulus pattern A and the

opposite for pattern B (u_{5-8} high-valued and u_{1-4} low-valued). The parameter ε determines the range of

values that could be drawn from purely deterministic (0 or 1, $\varepsilon = 0$) to randomly uniformly distributed

(from 0 to 1, $\varepsilon = 1$). Thus, the correlation of the inputs correspondingly varies according to $\rho(u_i,u_j)$

$= \rho(u_k,u_l) = (\varepsilon-1)^2/((\varepsilon-1)^2+\varepsilon^2/3)$ where $1 \leq i,j \leq 4$, $i \neq j$ and $5 \leq k,l \leq 8$, $k \neq l$ approaching correlation equal to 0 for a

purely, random pattern ($\varepsilon = 1$) that had a low probability of matching the learned patterns A and B.

Code availability. All data analysis and computational modeling were done using custom scripts

written in Matlab. All code is available upon request.

Statistics. Error bars represent standard errors of the mean obtained by bootstrap resampling (n =

1000). All statistical comparisons including those of means or correlation values were obtained by

bootstrap resampling (n = 1000) producing p-values at a resolution of 0.001 so that the lowest p-value

that can be reported is p = 0.000 given the resolution of this statistical analysis. All statistical tests were

two-sided unless otherwise specified. Spearman's rank correlation coefficient was used.

ACKNOWLEDGEMENTS

We thank J. Deutsch, K. Schmidt, and P. Aparicio for help with MRI and animal care and B. Andken

and C. Stawarz for help with experiment software. We are grateful to T. Meyer and C. Olson for sharing

figures from their published work.

REFERENCES

Ackley, D. H., Hinton, G. E., & Sejnowski, T. J. (1985). A learning algorithm for boltzmann machines. *Cognitive Science*, *9*(1), 147–169. https://doi.org/10.1016/S0364-0213(85)80012-4

Afraz, S.-R., Kiani, R., & Esteky, H. (2006). Microstimulation of inferotemporal cortex influences face categorization. *Nature*, *442*(7103), 692–695. https://doi.org/10.1038/nature04982

Aparicio, P. L., Issa, E. B., & DiCarlo, J. J. (2016). Neurophysiological Organization of the Middle Face Patch in Macaque Inferior Temporal Cortex. *Journal of Neuroscience*, *36*(50), 12729–12745. https://doi.org/10.1523/JNEUROSCI.0237-16.2016

Brincat, S. L., & Connor, C. E. (2006). Dynamic Shape Synthesis in Posterior Inferotemporal Cortex. *Neuron*, *49*(1), 17–24. https://doi.org/10.1016/j.neuron.2005.11.026

Cadieu, C. F., Hong, H., Yamins, D. L. K., Pinto, N., Ardila, D., Solomon, E. A., … DiCarlo, J. J. (2014). Deep Neural Networks Rival the Representation of Primate IT Cortex for Core Visual Object Recognition. *PLoS Comput Biol*, *10*(12), e1003963. https://doi.org/10.1371/journal.pcbi.1003963

Carandini, M., & Heeger, D. J. (2012). Normalization as a canonical neural computation. *Nature Reviews Neuroscience*, *13*(1), 51–62. https://doi.org/10.1038/nrn3136

Carandini, M., Heeger, D. J., & Movshon, J. A. (1997). Linearity and Normalization in Simple Cells of the Macaque Primary Visual Cortex. *The Journal of Neuroscience*, *17*(21), 8621–8644.

Chang, L., & Tsao, D. Y. (2017). The Code for Facial Identity in the Primate Brain. *Cell*, *169*(6), 1013-1028.e14. https://doi.org/10.1016/j.cell.2017.05.011

Chen, M., Yan, Y., Gong, X., Gilbert, C. D., Liang, H., & Li, W. (2014). Incremental Integration of Global Contours through Interplay between Visual Cortical Areas. *Neuron*, *82*(3), 682–694. https://doi.org/10.1016/j.neuron.2014.03.023

Coen-Cagli, R., Kohn, A., & Schwartz, O. (2015). Flexible gating of contextual influences in natural vision. *Nature Neuroscience*, *18*(11), 1648–1655. https://doi.org/10.1038/nn.4128

Cox, D. D., Papanastassiou, A. M., Oreper, D., Andken, B. B., & DiCarlo, J. J. (2008). High-Resolution Three-Dimensional Microelectrode Brain Mapping Using Stereo Microfocal X-ray Imaging. *Journal of Neurophysiology*, *100*(5), 2966–2976. https://doi.org/10.1152/jn.90672.2008

Egeth, H. E., & Yantis, and S. (1997). VISUAL ATTENTION: Control, Representation, and Time Course. *Annual Review of Psychology*, *48*(1), 269–297. https://doi.org/10.1146/annurev.psych.48.1.269

996   Epshtein, B., Lifshitz, I., & Ullman, S. (2008). Image interpretation by a single bottom-up top-down
997   cycle. *Proceedings of the National Academy of Sciences*, *105*(38), 14298–14303.
998   https://doi.org/10.1073/pnas.0800968105
999

1000   Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2006). Experience-Dependent Sharpening
1001   of Visual Shape Selectivity in Inferior Temporal Cortex. *Cerebral Cortex*, *16*(11), 1631–1644.
1002   https://doi.org/10.1093/cercor/bhj100
1003

1004   Freiwald, W. A., & Tsao, D. Y. (2010). Functional Compartmentalization and Viewpoint Generalization
1005   Within the Macaque Face-Processing System. *Science*, *330*(6005), 845–851.
1006   https://doi.org/10.1126/science.1194908
1007

1008   Freiwald, W. A., Tsao, D. Y., & Livingstone, M. S. (2009). A face feature space in the macaque temporal
1009   lobe. *Nature Neuroscience*, *12*(9), 1187–1196. https://doi.org/10.1038/nn.2363
1010

1011   Friston, K., & Kiebel, S. (2009). Cortical circuits for perceptual inference. *Neural Networks*, *22*(8), 1093–
1012   1104. https://doi.org/10.1016/j.neunet.2009.07.023
1013

1014   Grimaldi, P., Saleem, K. S., & Tsao, D. (2016). Anatomical Connections of the Functionally Defined "Face
1015   Patches" in the Macaque Monkey. *Neuron*, *90*(6), 1325–1342.
1016   https://doi.org/10.1016/j.neuron.2016.05.009
1017

1018   Hung, C. P., Kreiman, G., Poggio, T., & DiCarlo, J. J. (2005). Fast Readout of Object Identity from
1019   Macaque Inferior Temporal Cortex. *Science*, *310*(5749), 863–866.
1020   https://doi.org/10.1126/science.1117593
1021

1022   Hyvärinen, A., Hurri, J., & Hoyer, P. O. (2009). Lateral interactions and feedback. In *Natural Image
1023   Statistics: A Probabilistic Approach to Early Computational Vision.* (Vol. 39, pp. 307–318).
1024   Springer Science & Business Media.
1025

1026   Issa, E. B., & DiCarlo, J. J. (2012). Precedence of the Eye Region in Neural Processing of Faces. *The
1027   Journal of Neuroscience*, *32*(47), 16666–16682. https://doi.org/10.1523/JNEUROSCI.2391-
1028   12.2012
1029   Issa, E. B., Papanastassiou, A. M., Andken, B. B., & DiCarlo, J. J. (2010). Towards large-scale, high
1030   resolution maps of object selectivity in inferior temporal cortex. Presented at the
1031   Computational and Systems Neuroscience, Salt Lake City, UT: Front in Neuroscienc Abstract.
1032   https://doi.org/10.3389/conf.fnins.2010.03.00154
1033

1034   Issa, E. B., Papanastassiou, A. M., & DiCarlo, J. J. (2013). Large-Scale, High-Resolution
1035   Neurophysiological Maps Underlying fMRI of Macaque Temporal Lobe. *The Journal of
1036   Neuroscience*, *33*(38), 15207–15219. https://doi.org/10.1523/JNEUROSCI.1248-13.2013
1037

1038   Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). ImageNet Classification with Deep Convolutional
1039   Neural Networks. In *Advances in Neural Information Processing Systems* (pp. 1106–1114).

1040
1041   Lee, T. S., & Mumford, D. (2003). Hierarchical Bayesian inference in the visual cortex. *Journal of the*
1042   *Optical Society of America A*, *20*(7), 1434. https://doi.org/10.1364/JOSAA.20.001434
1043
1044   Lee, T. S., Yang, C. F., Romero, R. D., & Mumford, D. (2002). Neural activity in early visual cortex reflects
1045   behavioral experience and higher-order perceptual saliency. *Nature Neuroscience*, *5*(6), 589–
1046   597. https://doi.org/10.1038/nn0602-860
1047
1048   Leopold, D. A., Bondar, I. V., & Giese, M. A. (2006). Norm-based face encoding by single neurons in the
1049   monkey inferotemporal cortex. *Nature*, *442*(7102), 572–575.
1050   https://doi.org/10.1038/nature04951
1051
1052   Majaj, N. J., Hong, H., Solomon, E. A., & DiCarlo, J. J. (2015). Simple Learned Weighted Sums of Inferior
1053   Temporal Neuronal Firing Rates Accurately Predict Human Core Object Recognition
1054   Performance. *The Journal of Neuroscience*, *35*(39), 13402–13418.
1055   https://doi.org/10.1523/JNEUROSCI.5181-14.2015
1056
1057   Marblestone, A. H., Wayne, G., & Kording, K. P. (2016). Toward an Integration of Deep Learning and
1058   Neuroscience. *Frontiers in Computational Neuroscience*, *10*.
1059   https://doi.org/10.3389/fncom.2016.00094
1060
1061   Meyer, T., & Olson, C. R. (2011). Statistical learning of visual transitions in monkey inferotemporal
1062   cortex. *Proceedings of the National Academy of Sciences*, *108*(48), 19401–19406.
1063   https://doi.org/10.1073/pnas.1112895108
1064
1065   Meyer, T., Walker, C., Cho, R. Y., & Olson, C. R. (2014). Image familiarization sharpens response
1066   dynamics of neurons in inferotemporal cortex. *Nature Neuroscience*, *17*(10), 1388–1394.
1067   https://doi.org/10.1038/nn.3794
1068
1069   Meyers, E. M., Borzello, M., Freiwald, W. A., & Tsao, D. (2015). Intelligent Information Loss: The Coding
1070   of Facial Identity, Head Pose, and Non-Face Information in the Macaque Face Patch System. *The*
1071   *Journal of Neuroscience*, *35*(18), 7069–7081. https://doi.org/10.1523/JNEUROSCI.3086-14.2015
1072
1073   Moeller, S., Crapse, T., Chang, L., & Tsao, D. Y. (2017). The effect of face patch microstimulation on
1074   perception of faces and objects. *Nature Neuroscience*, *advance online publication*.
1075   https://doi.org/10.1038/nn.4527
1076
1077   Moeller, S., Freiwald, W. A., & Tsao, D. Y. (2008). Patches with Links: A Unified System for Processing
1078   Faces in the Macaque Temporal Lobe. *Science*, *320*(5881), 1355–1359.
1079   https://doi.org/10.1126/science.1157436
1080
1081   Murray, E. A., Bussey, T. J., & Saksida, L. M. (2007). Visual Perception and Memory: A New View of
1082   Medial Temporal Lobe Function in Primates and Rodents. *Annual Review of Neuroscience*,
1083   *30*(1), 99–122. https://doi.org/10.1146/annurev.neuro.29.051605.113046

1084
1085   Nassi, J. J., Gómez-Laberge, C., Kreiman, G., & Born, R. T. (2014). Corticocortical feedback increases the
1086   spatial extent of normalization. *Frontiers in Systems Neuroscience*, *8*.
1087   https://doi.org/10.3389/fnsys.2014.00105
1088
1089   Ohayon, S., Freiwald, W. A., & Tsao, D. Y. (2012). What Makes a Cell Face Selective? The Importance of
1090   Contrast. *Neuron*, *74*(3), 567–581. https://doi.org/10.1016/j.neuron.2012.03.024
1091
1092   Olshausen, B. A., & Field, D. J. (1996). Emergence of simple-cell receptive field properties by learning a
1093   sparse code for natural images. *Nature*, *381*(6583), 607–609.
1094   https://doi.org/10.1038/381607a0
1095
1096   Patel, A. B., Nguyen, T., & Baraniuk, R. G. (2015). A Probabilistic Theory of Deep Learning.
1097   *ArXiv:1504.00641 [Cs, Stat]*. Retrieved from http://arxiv.org/abs/1504.00641
1098
1099   Rao, R. P. N., & Ballard, D. H. (1999). Predictive coding in the visual cortex: a functional interpretation
1100   of some extra-classical receptive-field effects. *Nature Neuroscience*, *2*(1), 79–87.
1101   https://doi.org/10.1038/4580
1102
1103   Rifai, S., Vincent, P., Muller, X., Glorot, X., & Bengio, Y. (2011). Contractive auto-encoders: Explicit
1104   invariance during feature extraction. In *Proceedings of the 28th international conference on
1105   machine learning (ICML-11)* (pp. 833–840).
1106
1107   Sadagopan, S., Zarco, W., & Freiwald, W. A. (2017). A causal relationship between face-patch activity
1108   and face-detection behavior. *ELife*, *6*, e18558. https://doi.org/10.7554/eLife.18558
1109
1110   Salakhutdinov, R., & Hinton, G. (2012). An Efficient Learning Procedure for Deep Boltzmann Machines.
1111   *Neural Computation*, *24*(8), 1967–2006. https://doi.org/10.1162/NECO_a_00311
1112
1113   Schwartz, O., & Simoncelli, E. P. (2001). Natural signal statistics and sensory gain control. *Nature
1114   Neuroscience*, *4*(8), 819–825. https://doi.org/10.1038/90526
1115
1116   Schwiedrzik, C. M., & Freiwald, W. A. (2017). High-Level Prediction Signals in a Low-Level Area of the
1117   Macaque Face-Processing Hierarchy. *Neuron*, *96*(1), 89-97.e4.
1118   https://doi.org/10.1016/j.neuron.2017.09.007
1119
1120   Seung, H. S. (1997). Pattern analysis and synthesis in attractor neural networks. *Theoretical Aspects of
1121   Neural Computation: A Multidisciplinary Perspective, Singapore*.
1122
1123   Sugase, Y., Yamane, S., Ueno, S., & Kawano, K. (1999). Global and fine information coded by single
1124   neurons in the temporal visual cortex. *Nature*, *400*(6747), 869–873.
1125   https://doi.org/10.1038/23703
1126

1127   Tsao, D. Y., Freiwald, W. A., Tootell, R. B. H., & Livingstone, M. S. (2006). A Cortical Region Consisting
1128   Entirely of Face-Selective Cells. *Science*, *311*(5761), 670–674.
1129   https://doi.org/10.1126/science.1119983
1130
1131   Tsao, D. Y., Moeller, S., & Freiwald, W. A. (2008). Comparing face patch systems in macaques and
1132   humans. *Proceedings of the National Academy of Sciences*, *105*(49), 19514–19519.
1133   https://doi.org/10.1073/pnas.0809662105
1134
1135   Williams, D. R. G. H. R., & Hinton, G. E. (1986). Learning representations by back-propagating errors.
1136   *Nature*, *323*, 533–536.
1137
1138   Woloszyn, L., & Sheinberg, D. L. (2012). Effects of Long-Term Visual Experience on Responses of
1139   Distinct Classes of Single Units in Inferior Temporal Cortex. *Neuron*, *74*(1), 193–205.
1140   https://doi.org/10.1016/j.neuron.2012.01.032
1141
1142   Yamins, D. L. K., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014). Performance-
1143   optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of*
1144   *the National Academy of Sciences*, *111*(23), 8619–8624.
1145   https://doi.org/10.1073/pnas.1403112111
1146
1147   Zeiler, M. D., & Fergus, R. (2013). Stochastic Pooling for Regularization of Deep Convolutional Neural
1148   Networks. *ArXiv:1301.3557 [Cs, Stat]*. Retrieved from http://arxiv.org/abs/1301.3557
1149
1150   Zhang, N. R., & Heydt, R. von der. (2010). Analysis of the Context Integration Mechanisms Underlying
1151   Figure–Ground Organization in the Visual Cortex. *The Journal of Neuroscience*, *30*(19), 6482–
1152   6496. https://doi.org/10.1523/JNEUROSCI.5168-09.2010
1153

Figure 1. **Neural recordings and experimental design in face-selective subregions of the ventral visual stream. (A)** Neurons were recorded along the lateral convexity of the inferior temporal lobe spanning the posterior to anterior extent of IT (+0 to +20 mm AP, Horsely-Clarke coordinates) in two monkeys (data from monkey 1 are shown). Based on prior work, face-selective sites (red) were operationally defined as those with a response preference for images of frontal faces versus images of non-face objects (see **Methods**). While these neurons were found throughout IT, they tended to be found in clusters that mapped to previously identified subdivisions of IT (posterior, central, and anterior IT) and corresponded to face-selective areas identified under fMRI in the same subjects (Issa & DiCarlo, 2012)(Issa et al., 2013) (STS = superior temporal sulcus, IOS = inferior occipital sulcus, OTS = occipitotemporal sulcus). **(B)** (top diagram) The three visual processing stages in IT lie downstream of early visual areas V1, V2, and V4 in the ventral visual stream. (left) We designed our stimuli to focus on the intermediate stage pIT by seeking images of faces and images of non-faces that would, on average, drive equally strong initial responses in pIT. Novel images were generated from an exemplar monkey face by positioning the face parts in different positions within the face outline. This procedure generated both frontal face and non-face arrangements of the face parts, and we identified 21 images (red and black boxes) that drove the mean, early (60-100 ms) pIT population response to $\geq$90% of its response to the intact face (first image in red box is synthesized whole face; compare to the second image which is the original whole face), and of these 21 images, 13 images contained non-face arrangements of the face parts. For example, images with an eye centered in the outline (black box, 3[rd] and 4[th] rows) as opposed to the lateralized position of the eye in a frontal face (red box) have a global interpretation ("cyclops") that is not consistent with a frontal face but still evoked strong pIT responses. Selectivity of neural sites (see **Figs. 3 & 4**) for face versus non-face images was quantified using a d' measure. (middle) Computational hypotheses of cortical dynamics make differing predictions about how neural selectivity in pIT may evolve following an initial, weak preference signal for images of frontal faces. (right) Predictions of how aIT would behave as an output stage building selectivity for images of frontal faces through multiple stages of processing. **(C)** A population decoder, trained on average firing rates (60-200 ms post image onset, linear SVM classifier) for frontal face versus non-face arrangements of the face parts in this image subset, performed poorly in pIT on held-out trials of the same images (trial splits used so that the same images were shown in classifier training and testing). However, the particular class (face vs non-face) could be determined at above chance levels when reading the cIT and aIT population responses.

Figure 2

Figure 2. Responses in example sites to face-like images with typical and atypical face part arrangements. The three sites with the highest selectivity in the late response phase in each region are shown (pIT, cIT, and aIT; left, middle, and right columns, respectively) (d' selectivity measured in a 100-130 ms window, gray shaded region shown in bottom, left panel). While the three aIT sites (right column) demonstrated late phase selectivity for face images, the three pIT sites evolved the opposite preference in their late phase (100-130 ms) responses (red line = mean response of 8 images shown in **Figure 1B** red box, and black line = mean response of 13 images shown in **Figure 1B** black box).

Figure 3

1198

Figure 3. Time course of neural response preferences in pIT, cIT, and aIT for images with face
versus non-face arrangements of the parts. (A) Preferences for frontal face versus non-face part
arrangements for each site are plotted in both early (60-90 ms post image onset) and late (100-130 ms)
time windows. Sites are grouped based on region (pIT, cIT, aIT) and whether they showed a significant
change in selectivity from early to late time windows (light gray = increased preference, black =
decreased preference, and dark gray = no change in preference for face versus non-face images,
significance tested at p < 0.01 level; example sites from **Figure 2** are plotted using thicker, darker
lines). Many sites in pIT and cIT showed a decreasing preference for frontal face versus non-face
images over time (black lines, middle row, left and center panels). In contrast, no sites in aIT had this
dynamic (middle row, right panel). **(B)** The fraction of sites whose responses showed a preference for
images of typical, face-like arrangements of the face parts in pIT (blue), cIT (green) and aIT (red) in the
early (60-90 ms) and late (100-130 ms) phase of the response. Note that, in the late phase of the
response, most pIT neurons paradoxically showed a preference for non-face arrangements of face
parts. **(C)** Selectivity measured for images driving similar responses within a site. This procedure
ensured matched initial responses on a site-by-site basis rather than using a fixed set of images based
on the overall population response (i.e. the fixed image set of **Figure 1B**; here, the initial d' for 60-90
ms is close to zero when images are selected site by site). Although initial response differences were
near zero when using site based image selection, a late phase preference for non-face images still
emerged in pIT and cIT but not in aIT similar to the decreasing selectivity profile observed when using a
fixed image set for all sites.
1219

Figure 4

Figure 4. Individual monkey comparison and image controls for the decreasing selectivity profile in pIT. (A) Preference for images with frontal face part arrangements analyzed separately for each monkey. Median d' of pIT sites in both early and late time windows is shown. **(B)** Preference for images with face versus non-face arrangements of the parts was re-computed using image subsets containing the same number of parts in the outline (the five 1-part and the three 4-part image subsets shown at top; the larger 2-part subset contained 30 images and is not shown). **(C)** The 1-part image subset was further tested at three different sizes (3^o, 6^o, and 12^o). In all cases, pIT responses showed a decreasing preference over time for typically-arranged face parts leading to a preference for atypically arranged face parts in the later time window (100-130 ms).

Figure 5

1232
1233
Figure 5. Model diagrams. (A) Network diagrams of two-stage models used in **Figure 7A,B**. The base
feedforward architecture and parameters are shown in the first column while recurrent models with
added connections and parameters are shown in the remaining columns. All models have two inputs
(u_1, u_2), at least two hidden units (x_1, x_2) (a.k.a. layer 1 of the network), and at least one output unit (y).
For simulations, the inputs u_1, u_2 are set independently to simulate each hidden node receiving different
amounts of external drive, depending on the choice of the applied image relative to the unit's preferred
image. The connection weights B = [b_1, b_2] transforming the hidden stage activations to the output unit
are modeled as the same ($b_1 = b_2$). All units have self-connections that determine the degree of leak
current set by the time constant τ. In the normalization models, the leak term is additionally controlled
(linearly or nonlinearly) by the total activity in each stage (third and fourth columns). In the feedback-
based model, the feedback connections are symmetric to the feedforward connections with weights B^T
= [b_1, b_2]^T, a column vector (fifth and sixth columns). The error coding feedback model (sixth column)
has an additional stage that contributes to computation of error in the second stage (see **Methods** for
details). **(B)** Extensions of the two-stage model architectures to three stages are shown only for the
feedforward and feedback models (compare to two-stage diagrams in **(A)**). The three-stage model has
an additional hidden processing stage compared to the two-stage model. An extra node is introduced at
the top of the hierarchy to produce an error signal in the third stage of the error coding model.
1251

Figure 6

Figure 6. Computational modeling of neural dynamics in IT. (A) Three stage neural networks with recurrent dynamics (network diagrams in top row; see **Methods** and **Figure 5B**) were constructed to model neural signals measured in pIT, cIT, and aIT corresponding to the first (blue), second (green), and third (red) model processing stages. All models received four inputs (gray) into four hidden stage units (blue) which sent feedforward projections that converged onto two units in the next layer (green). Besides this feedforward architecture, additional excitatory and inhibitory connections between units were used to implement recurrent dynamics (self-connections reflecting leak currents are not shown here for clarity; see **Figure 5B** for detailed diagrams). In the five models on the left, the responses of the simulated neurons are assumed to code the current estimates of some set of features in the world (a.k.a states), as is standard in most such networks. The best fit to the population averaged neural data (far right) of the states of each model class are shown (first five columns). These state coding models generally showed increasing selectivity over time from hidden to output layers and did not demonstrate the strong decrease of stimulus preference in their hidden processing stage as observed in the pIT and cIT neural population (blue and green lines). However, the neurons coding errors in a feedback-based hierarchical model did show a strong decrease of stimulus preference in the hidden processing stage (sixth column; reconstruction errors instead of the states were fit directly to the data). This model which codes the error signals (filled circles) also codes the states (open circles) (network diagram in sixth column of top row). **Far right,** population averaged neural selectivity profile for difference between frontal face versus non-face arrangements (normalized by the mean population response to the whole face) used in model fitting. **(B)** Goodness of fit of all three stage models tested to population averaged selectivity profiles (dashed lines represent mean and standard error of reliability of neural data as estimated by bootstrap resampling).

Figure 7

1277
1278
Figure 7. **Two stage model fits to neural dynamics and comparison of variants of error coding**
hierarchical models that use different algorithms for online inference. (A) We tested how well two
stage models could reproduce decreasing selectivity observed in the hidden layer (same format as
Figure 6A). The two stage error coding feedback model displayed similar dynamical phenomena as the
data suggesting that three stages of processing were not necessary to obtain error signal dynamics. **(B)**
Goodness of fit to population neural data (right plot in **(A)**) for all two stage models. **(C)** Existing forms
of error computing networks can be distinguished by the type of online inference algorithm that they
use. In one case, inference does not utilize top-down information between stages (classic error
backpropagation; between-stage feedback connections shown are not used in these networks during
runtime). On the other hand, between-stage feedback can be used such as in more general forms of
error backpropagation and predictive coding. We approximated these two extremes by including a
parameter (k_{td}, see **Methods**) controlling the relative weighting of bottom-up (feedforward) and top-
down (feedback) evidence during online inference (first and second panels). We found that top-down
inference between stages was not necessary to produce the appropriate error signal dynamics, and k_{td}
was equal to zero in our best fitting two-layer and three-layers models (first panel is same model as
two-layer error coding model in **(A)**) although models with $k_{td} \sim 1$ also performed well (second panel).
Models can also differ in their goal (cost function) which directly impacts the error signals required
(equations in top row). Under a nonlinear reconstruction goal (emulating the nonlinear nature of spiking
output), the resulting error signals were still consistent with our data (third column). A simple sigmoidal
nonlinearity, however, did lead to additional details present in our neural data such as a rapid return of
stimulus preference to zero in the hidden layer. When we tested a discriminative, construction goal
more consistent with a supervised learning setting (e.g. classic error backpropagation) where bottom-
up responses simply have to match a downstream target signal in classification tasks, we found that the

errors of construction did not match the data as well as reconstruction errors (compare fourth column to
first three columns) although both types of error outperformed all state-based models and were overall
very similar (compare to **(A)**).
1305

Figure 8

1306
1307
Figure 8. Comparison of neuronal phenomena to predictions of a feedback-based error coding
model. To generate model predictions, the architectural parameters of the model (i.e. connection
weights and time constants) were held fixed, and only the input patterns *u* were varied. **(A)** Neuronal
(left panel): in pIT, we found that the sum of the neuronal response to the face parts presented
individually (black) exceeded the response to the same parts presented simultaneously (i.e. a whole
face, red). Each line is the mean response of 33 pIT sites normalized by the peak response to the
whole face. Model (right panel): The magnitude of errors between stage 1 and stage 2 of the model
showed a similar degree of sublinear integration (responses were normalized by peak response to the
simultaneous input condition). **(B)** We extended the model to include two units in the third, output stage
that responded to two learned input patterns (see **Methods**) with increased separation of patterns *A*
and *B* in this high-level feature space (red markers in far right panel; 50 draws were made from

distributions for *A* and *B* and were compared to pseudo-randomly drawn inputs, black markers). When
alternating the two learned or familiar patterns *A* and *B*, activations in the top layer of the networks
experienced greater changes than when two randomly selected patterns were alternated (compare
distances traversed in high-level feature space by red lines versus black lines, far right panel). Because
of this large change in high-level activations, transient errors were generated back through the network
for learned patterns. Strong oscillations could be observed in the error signals between stage 1 and
stage 2 of the model for alternated familiar inputs *A* and *B* (120 ms period) (red curve, middle right
panel). In contrast, alternating novel inputs with similar amplitude but with patterns not matching the
learned weights led to small amplitude oscillations in upstream error signals (black curve). Note that the
average response strength of state signals to novel and familiar inputs was matched at all network
levels by construction (mean-matched inputs). The differing response dynamics of error signals under
familiar versus novel patterns are qualitatively consistent with the IT findings for novel versus familiar
images (left, reproduced with permission from *Figs. 1 & 2b* of Meyer et al., 2014). **(C)** The average
response to the whole face for pIT sites recorded 0 to 1 mm below the pial surface (left panel;
superficial recordings, red curve) and for sites 1 to 2.5 mm beneath the pial surface (black curve). (right
panel) Average response of state units (red) and error units (black) in stage 1 of the model. Note the
lagged response in state units which is similar to the lagged response of units in superficial recordings
(red curve, left panel).