1
2 **Chunking as a rational strategy for lossy data compression in visual**
3 **working memory.**
4
5
6
7

8 Matthew R. Nassar[1], Julie C. Helmers[1], and Michael J. Frank[1]
9
10
11 [1]Department of Cognitive, Linguistic, and Psychological Sciences; Brown Institute
12 for Brain Science, Brown University 02912-1821

32 Corresponding Author:
33 Matthew R. Nassar
34 Department of Cognitive, Linguistic and Psychological Sciences
35 Brown University
36 Providence, RI 02912-1821
37
38 Phone: 607-316-4932
39 E-mail: matthew_nassar@brown.edu

40
41

Abstract:

The nature of capacity limits for visual working memory has been the subject of an intense debate that has relied on models that assume items are encoded independently. Here we propose that instead, similar features are jointly encoded through a "chunking" process to optimize performance on visual working memory tasks. We show that such chunking can: 1) facilitate performance improvements for abstract capacity-limited systems, 2) be optimized through reinforcement, 3) be implemented by center-surround dynamics, and 4) increase effective storage capacity at the expense of recall precision. Human performance on a variant of a canonical working memory task demonstrated performance advantages, precision detriments, inter-item dependencies, and trial-to-trial behavioral adjustments diagnostic of performance optimization through center-surround chunking. Models incorporating center-surround chunking provided a better quantitative description of human performance in our study as well as in a meta-analytic dataset, and apparent differences in working memory capacity across individuals were attributable to individual differences in the implementation of chunking. Our results reveal a normative rationale for center-surround connectivity in working memory circuitry, call for re-evaluation of memory performance differences that have previously been attributed to differences in capacity, and support a more nuanced view of visual working memory capacity limitations: strategic tradeoff between storage capacity and memory precision through chunking contribute to flexible capacity limitations that include both discrete and continuous aspects.

Keywords: Visual working memory; Data compression; Information theory; Reinforcement learning; Computational modeling; Recurrent neural networks

Introduction:

People are limited in their capacity to retain visual information in short-term memory; however, the exact nature of this limitation is hotly debated (Luck & Vogel, 2013; Ma, Husain, & Bays, 2014; Wei, Wang, & Wang, 2012). Competing theories have stipulated that capacity is constrained by either a discrete item limit (e.g., a fixed number of "slots") or by the distribution of a flexible "resource" across relevant visual information (Bays & Husain, 2008; Wei et al., 2012; Zhang & Luck, 2008). In their simplest form, these competing theories are both philosophically distinct and statistically identifiable, but experimental evidence has been mixed, with some studies favoring each theory and the best-fitting computational models incorporating elements of each (Almeida, Barbosa, & Compte, 2015; Bays & Husain, 2008; Bays, Catalao, & Husain, 2009; Cowan & Rouder, 2009; Chris Donkin, Tran, & Nosofsky, 2013a; Christopher Donkin, Nosofsky, Gold, & Shiffrin, 2013b; Rouder et al., 2008; van den Berg, Awh, & Ma, 2014; van den Berg, Shin, Chou, George, & Ma, 2012; Zhang & Luck, 2008; 2009; 2011). Experimental support for both theories has emerged from delayed report working memory tasks, in which subjects are asked to make a delayed report about a feature (e.g. color) of a single item that was briefly presented as part of a multi-item stimulus display (Bays & Husain, 2008; Wilken & Ma, 2004; Zhang & Luck, 2011). In particular, as the number of items to be retained increases, visual working memory reports tend to become less precise, as predicted by resource models, and more likely to reflect guessing, as predicted by slots models

(Fougnie, Suchow, & Alvarez, 2012; Luck & Vogel, 2013; Ma et al., 2014; van den

Berg et al., 2012; 2014).

While the competing classes of visual working memory models have evolved

substantially over the past decade, the mathematical formalizations of each have

relied on assumptions about what is, and should be, stored in working memory.

Thus, an open question with potentially broad implications is what *should* and *do*

people store in memory during performance of the standard delayed recall tasks,

and how do deviations from the standard assumptions affect our understanding of

memory capacity? To this end, recent work has highlighted the ability of people to

optimize memory encoding and decoding processes by pooling information across

memoranda to enhance performance under different regimes (Brady & Alvarez,

2011; 2015; Brady, Konkle, & Alvarez, 2009; Lew & Vul, 2015; Orhan & Jacobs,

2013; Sims, Jacobs, & Knill, 2012; Wei et al., 2012). Specifically, people can integrate

prior information to improve memory report precision (Bays et al., 2009; Brady &

Alvarez, 2011) and, when stimuli are redundant, lossless compression strategies can

be used to efficiently encode them (Bays et al., 2009; Brady et al., 2009; Zhang &

Luck, 2008). These strategies can improve memory performance, but only to the

extent to which features of upcoming memoranda are predicted by previously

observed stimulus statistics. Since memoranda in standard working memory tasks

are unpredictable and randomly distributed by design, such strategies cannot

improve and may actually impede performance in standard tasks (Bays et al., 2009;

Orhan & Jacobs, 2014; Zhang & Luck, 2008). However, while memoranda in these

tasks are not compressible in the "lossless" sense, it is still possible that people

might employ more fast and frugal techniques to reduce memory storage

requirements at a small but acceptable cost to task performance.

Here we explore this possibility and show that people should, could, and do

implement a lossy form of data compression that sacrifices information about subtle

differences in the feature values of memoranda in order to improve overall task

performance. We do so using an inter-related set of computational models across

different levels of analysis, such that we can constrain our understanding of the

compression algorithm using both computational notions of how information

should be compressed and mechanistic notions of how biological circuits could

implement this compression. We probe our own and published empirical data to

test key predictions of these models. This study thus involves four related

components:

1. *Normative and behavioral analysis.* We begin with an information-theoretic

   analysis of how features of memoranda *should* be stored to maximize task

   performance in an abstract memory-limited system. We show that that under

   high memory load conditions, it is advantageous to jointly encode (chunk) a

   blended representation of similar features and only separately encode

   (partition) features if they are sufficiently dissimilar. This strategy can be

   effectively implemented by setting a criterion for partitioning features based

   on dissimilarity, where the appropriate criterion can be learned based on

   trial feedback (binary reward) and increases with memory load. We show

   that human subject behavior in a delayed report working memory task

conforms to predictions from this form of adaptive chunking and optimization thereof via reward feedback.

2. *Mechanistic implementations of chunking in a biophysical network model.* Given that behavioral data accorded with predictions from the normative model, we next examined how such selective chunking *could* be implemented in a biophysical memory system. Established recurrent neural network models have shown that perceptually similar memoranda can be merged together via attractor "bump collisions" (Wei et al., 2012). However, these simulations showed that such an architecture leads to indiscriminate chunking and – due to lateral inhibition – increased forgetting of non-chunked items, leading to poor performance (Wei et al., 2012). We show that this issue can be remedied by adopting a more biologically motivated center-surround inhibition connectivity that effectively partitions dissimilar color representations; however, it does so at the cost of inter-item repulsions, which reduce the effective precision of memory reports (Almeida et al., 2015).

3. *Algorithmic model of center-surround dynamics.* To systematically explore the impact of center-surround mediated chunking at the behavioral level, we created a parsimonious (i.e., minimal parameter) model that incorporates the key features necessary for effective chunking afforded by the biophysical model without explicitly modeling the temporal dynamics or biophysical

properties. We show that center-surround dynamics facilitate improved

memory recall at the expense of precision, and capture previously

unexplained qualitative patterns of bias and precision in human memory

reports across stimulus arrays.

4. *Quantitative model fitting.* Finally, we fit behavioral data from individual

subjects to show that chunking and center-surround dynamics improve fit

relative to state-of-the-art models, and can account for considerable

performance differences across subjects, with better-performing subjects

best fit by models with more inclusive chunking policies. We validate these

findings in a meta-analytic dataset to show that chunking improves

quantitative model fits across tasks, offers an alternative explanation to

changes in precision with set size, and accounts for individual differences in

working memory task performance under conditions of high memory load.

Results:

Visual working memory capacity is typically measured using either delayed report

or change detection tasks (Bays & Husain, 2008; Wilken & Ma, 2004; Zhang & Luck,

2011). Here we focus on the former, as they have provided nuanced information

about the shape of memory distributions and have formed the basis for competing

models of capacity limitation (Fougnie et al., 2012; Luck & Vogel, 2013; Ma et al.,

2014; van den Berg et al., 2012).

Specifically, we consider a delayed report color reproduction task that requires

storage of color and orientation information (figure 1). Each trial consists of three

core stages: stimulus presentation, delay, and probe. During stimulus presentation,

five oriented colored bars are displayed simultaneously. During the subsequent

delay, the screen is blanked, requiring short-term storage of color and orientation

information. During the probe stage, a single oriented bar is displayed (in gray) and

the participant is required to reproduce the color that had been associated with that

orientation in the preceding stimulus array.

Figure 1: Delayed report color reproduction task. Each trial begins with central fixation for 500

ms, followed by stimulus presentation for 200 ms. Stimuli consist of five colored and oriented bars

evenly distributed around a circle subtending 4 degrees of visual angle and centered on the point of

fixation. Stimulus presentation is followed by a 900 ms delay, after which a single oriented bar is

displayed centrally. The subject is required to report the color associated with the bar with the

probed orientation in the previous stimulus array. After confirming the report, the subject receives

feedback dependent on whether the absolute magnitude of the reproduction error was greater or

less than a fixed threshold. Stimulus colors on any given trial are selected either: 1) randomly and

independently as is standard in such tasks (random spacing; upper left) or 2) ensuring uniform

spacing on the color wheel so as to minimize within-array color similarity (fixed spacing).

Information theoretic analysis of what should be stored in working memory.

To first understand whether, in principle, information encoding could be optimized

in this task, we developed a limited-capacity system for memory storage in which

colors and orientations are represented with binary words (figure 2). We build on

the now classical work of George Miller by conceptualizing working memory

capacity limitation in terms of a strict limit on information storage, in bits (G. A.

Miller, 1956). The precision with which a color is stored depends on the number of

binary digits (bits) used to represent that color: a single bit can be used to specify a

half of the color wheel, a second bit can be added to specify a quarter of the color

wheel, and so on (figure 2A,). Capacity limitations within such a system can be easily

implemented as a fixed limit on the number of bits stored during the delay period.

These bits can be used to represent the individual colors in the target array, by, for

example, dividing them evenly among the available targets (figure 2B).

Alternatively, multiple similar colors could be jointly represented with a single

binary word that is then linked to multiple orientations (figure 2C). An intuitive

advantage of the second encoding strategy is that reducing the number of binary

color words increases the number of bits available to represent each word,

potentially offsetting the biased encoding of the chunked items by better

representing each encoded color.

Figure 2: Binary encoding model of visual working memory. In order to formalize capacity

limitations, it is useful to consider an abstract model of working memory that stores features in

binary words. **A**: Each color can be described by a binary word of fixed length, where the number of

digits in the word determines the storage precision. **B & C**: Stimulus arrays can be stored by linking

ordered pairs of color and orientation words. Capacity limitations are modeled by a fixed limit on the

length of the resulting "sentence" comprised of color and orientation words separated by word

termination symbols (2/3 for color/orientation words, respectively). **B:** One strategy for storing

ordered pairs involves alternating sequences of color and orientation words, such that each color is

"partitioned" from all other colors (dotted lines separating color representations) and linked to a

single orientation. **C**: Another strategy for storage would be to link two or more orientations to a

single color by removing a partition (chunking). This reduces the number of colors that need to be

stored, and thus increases the number of bits allotted to each color. **D**: Full partitioning (top) involves

placing a partition between each set of colors such that each color is represented independently.

Criterion-based partitioning sets a partition between each set of colors that are separated by a

greater distance than the partitioning criterion. Optimal partitioning examines all partitioning

patterns for a given stimulus array and selects the partitioning pattern that would achieve the lowest

theoretical error magnitude**. Colors/Arcs in each model reflect stored representations of a**

particular stimulus array (actual stimuli labeled with numbers) and thick/thin lines indicate

actual/potential partitions. Note that in this case, actual partitions selected by optimal

partitioning do not differ from those selected by the criterion-based partitioning model.

To test this potential advantage quantitatively, we examined task performance of

three models that differ in how they "chunk" feature information. The standard

model employs independent item encoding, through which each color is partitioned,

or represented separately, from all other stored colors (full partitioning; figure

2B&D). We also consider a fully optimal model that considers all possible

partitioning patterns and stores information using the combination of partitioning

and chunking (figure 2C&D) that would lead to the best theoretical performance for

each specific stimulus array, given the possibility that any item could be probed

(optimal partitioning). Although determining the optimal partitioning pattern for

each array is computationally expensive, it is well approximated by a simple and

efficient heuristic, using a single criterion for partitioning, according to the

separation of two targets in color space (criterion-based partitioning; fig 2D). For

this model, chunking was parameterized by a "partitioning criterion" that defines

the minimum distance between two colors required for independent

representation. If the distance between two colors is smaller than the partitioning

criterion, the colors are represented as a single "chunk". Thus, a partitioning

criterion of zero indicates that all items are represented independently, whereas a

partitioning criterion of π indicates that all item colors will be chunked together (i.e.

represented by a single binary word). Performance of all models was assessed for

delayed recall tasks ranging from easy (2 items) to difficult (8 items) and using both

continuous and discrete assumptions regarding the distribution of item information.

Performance of the criterion-based model depended on partitioning criterion as a

function of task difficulty (figure 3). For easier tasks with few items to encode, the

model's memory buffer was large enough to store each item independently with a

reasonable number of bits, such that increasing the partitioning criterion beyond

zero was detrimental to task performance (two targets; figure 3a [dark line]).

However, for harder tasks, in which storing each item with high precision was not

possible due to limited buffer size, performance was best for moderate partitioning

criterions that allow for joint representation of similar, but not dissimilar, colors

(eight targets; figure 3a [light line]). To better understand how chunking interacts

with set size to affect performance, we compared the performance of the best

criterion-based partitioning model to that of a full partitioning model across

different task difficulties. Across task difficulties, there was a monotonic

relationship between the number of targets and the performance advantage of both

fully optimal and criterion-based chunking models over full partitioning (figure 3B;

compare orange and green lines). Furthermore, the performance of the best

criterion-based partitioning was nearly identical to that of the optimal partitioning

model (figure 3B; compare green and yellow lines). Notably, the number of colors

stored by criterion-based and optimal partitioning models saturated around four

with increasing set size, highlighting that the improved performance of these

models comes from chunking similar colors into a single representation that is

linked to multiple orientations. Moreover, this result suggests that even though it is

possible in these models to store more items independently with less precision, it is

more advantageous to restrict the number of stored representations during

standard delayed recall tasks (figure 3C).

Set-size dependent performance advantages of chunking were also relatively

insensitive to modeling assumptions regarding the nature of storage constraints.

While the results described above were generated under the assumption of a

divisible resource framework (figure 3A-C), comparable results were attained when

model behavior was simulated using binary words that roughly correspond to the

slots + averaging framework (figure 3D-F). Thus, the performance advantages

offered by criterion-based chunking are robust to the nature of the actual capacity

limitation.

Adaptation of partitioning criterion via reinforcement learning

The advantages of chunking discussed above were presented for the best

partitioning criterion, which differed as a function of task demands, begging the

question of how a human subject would know to use this criterion. We thus

examined whether the partitioning criterion could be optimized on a trial-to-trial

basis via reinforcement learning to improve performance by allowing the

partitioning criterion to be adjusted on each trial according to the chunking (total

number of chunks) and reward feedback (thresholded binary feedback) from the

previous trial (see Methods). The resulting model increased the partitioning

criterion, and thus chunking, after a trial in which it chunked colors and achieved

better-than-average performance. This led partitioning criterions to increase

rapidly towards a load-dependent asymptote (figure 3G). Trial-to-trial increases in

the partitioning criterion corresponded to rapid improvements in overall task

performance, as measured by average absolute error (figure 3H). These

improvements in task performance were concomitant with reductions in the total

number of color chunks that the model attempted to store (figure 3I). Thus,

chunking can be optimized across conditions through reinforcement learning to

improve performance and reduce effective storage requirements in higher memory

load contexts.

Given the performance advantages offered by criterion-based chunking and the

efficiency with which it could be learned and implemented, we next sought to

identify diagnostic predictions made by the model. One key difference between the

criterion-based and full partitioning models is that the performance of the former

depended heavily on the specific distribution of the colors within each stimulus

array. If the colors were randomly and independently sampled, which is the

standard method in such tasks, chunking offered large advantages. In contrast, the

advantages of chunking were considerably smaller when colors were uniformly

distributed in color space to maximize color separation (fixed spacing; figure 1

inset; compare the solid and dashed lines in figure 3E-F). It is noteworthy that the

prediction of performance decrements under fixed spacing conditions is completely

opposite to that made by a prominent active maintenance model of working

memory, a point that we address in detail with a biologically motivated model of

chunking in a later section (Wei et al., 2012).

3 **Figure 3: Chunking improves memory performance and can be achieved through trial-to-trial**

4 **adjustments of partitioning criterion. A-C**: Criterion-based chunking confers memory

performance advantages and reduces feature storage requirements under resource assumptions. **A:** Mean absolute error (ordinate) for theoretical performance of a binary encoding model on delayed report tasks of varying set size (grayscale) across all possible partitioning criterions (abscissa; 0 = all colors stored independently). **B:** Model error (ordinate) increases as a function of set size (abscissa) for three partitioning strategies: 1) fully partitioned (model always stores all targets independently), 2) optimal partitioning (model considers all possible partitions for each stimulus array and uses the best), 3) criterion-based partitioning (chunking and partitioning is determined by best criterion from **A**). Error increases more shallowly for optimal and criterion-based partitioning strategies that employ strategic chunking. **C:** Total number of chunks requiring storage (ordinate) increases as a function of set size (abscissa) for all three models, but saturates near 4 items for optimal and criterion-based chunking models. **D-F:** Performance advantages of criterion-based chunking hold for binary word storage, analogous to "slots + averaging." **D-F** are analogous to **A-C** except that panels E and F show model performance separately for randomly spaced and fixed spaced stimulus arrays (solid and dotted lines, respectively) and do not include an "optimal partitioning" model, as computing it would be computationally inefficient under this framework. **G-I:** Appropriate partitioning criterions can be learned through reinforcement. **G**: Adjusting the partitioning criterion through reinforcement learning (see Methods) leads simulated criterions (ordinate) to increase over trials (abscissa) in a manner that scales with set size (grayscale; 2 = darkest, 8 = lightest). Adjustments in criterion lead to reduced errors **(H)** and decrease the "chunks" that require storage **(I)**. **J-L:** Chunking selectively benefits performance on trials in which colors are most tightly clustered. Within-cluster variance provides a measure of feature clustering within a stimulus array, with low values indicating more clustering (**J**) and high values indicating less clustering (**K**). Performance of the best chunking model, but not the non-chunking model, depends on the clustering of individual stimulus arrays, as assessed through within-cluster variance. Mean absolute error is plotted for stimulus arrays grouped in bins of within-cluster variance for criterion-based chunking (green) and fully partitioned (orange) models. Triangles reflect the same values computed for fixed spacing trials, in which stimulus features were minimally clustered (as depicted in **K**).

To better characterize the statistical properties of the specific arrays that enabled

better performance in the chunking models, we computed the within-cluster

variance (WCV) as a metric of how efficiently each stimulus array could be chunked

(see Methods). Target arrays with tightly clustered colors have low WCV, whereas

target arrays with distantly spaced colors have high WCV (figure 3J&K). The

performance of chunking models depended monotonically on WCV, with the

smallest errors achieved on low WCV target arrays (figure 3L), supporting the

notion that chunking advantages are achieved by more efficient representation of

similar colors through joint encoding.

Taken together, the results from the binary encoding model suggest that 1)

selectively chunking similar feature values can improve performance in working

memory tasks, 2) performance improvements from selective chunking increase with

target number and are mitigated by uniformly spacing feature values, 3)

performance of chunking models depends monotonically on WCV, and 4) chunking

behavior can be learned through reinforcement of successful chunking behaviors. In

summary, the binary encoding model clarifies why, and under what conditions,

chunking could benefit working memory performance in standard tasks. In the next

section, we test whether performance of human subjects in a delayed recall task

conforms to the predictions of the criterion-based chunking model.

People are more accurate and confident when remembering clustered stimulus arrays.

To directly test key predictions made by the binary encoding model, we collected

behavioral data from human participants in the task described in figure 2. The

critical manipulation in the task is that the colors in some trials were uniformly

spaced on the color wheel (fixed spacing) whereas the colors in interleaved trials

were randomly and independently sampled from the color wheel (random spacing).

This manipulation allowed us to test the prediction of the binary coding model that

more clustered stimulus arrays lead to better performance (figures 3E&I). To

examine the potential for adaptive learning of chunking, we provided reward

feedback to subjects on each trial (by comparing error magnitude to a fixed

threshold, either $\pi/3$ or $\pi/8$ in separate groups). The task also required subjects to

wager about the accuracy of their choices (post-decision) on one third of trials.

These task features allowed us to test the prediction that chunking behaviors are

adjusted from trial-by-trial through reinforcement learning (see figure 3G&H) and

to determine whether participants were aware of any performance bonuses

attributable to chunking.

In accordance with behavioral optimization through selective chunking, participants

were more accurate and confident when presented with randomly spaced stimuli.

Subject accuracy, as assessed using the same error threshold procedure used to

determine feedback, was greater on random spacing trials than on fixed spacing

trials (figure S1A; $t = 4.4$, $p < 10e\text{-}4$). This accuracy improvement was more

prevalent for subjects that experienced a liberal accuracy criterion (low precision,

absolute error < π/3) than for those that experienced a conservative accuracy

criterion (high precision, absolute error < π/8; two sample t-test for group

difference: t = -2.5, p = 0.02, Bayes Factor = 4.8) suggesting the improvement may

have been more pronounced for moderate errors that were interpreted differently

across the groups depending on the accuracy criterion (error < π/3 & error > π/8).

Participants also wagered more frequently on random spacing than fixed spacing

trials, suggesting that they were cognizant of the conferred performance advantage

(figure S1B; t = 3.1, p = 0.003). Subjects tended to gauge their wagering behavior

reasonably well, with subjects who achieved higher levels of accuracy also betting

more frequently (figure S1C; Pearson's rho =0.68, p <10e-6). Furthermore,

individual differences in the adjustment of wagering as a function of color spacing

configuration correlated with the change in accuracy that subjects experienced

across the configurations (figure S1D; Pearson's rho =044, p = 0.002). Taken

together, these data suggest that subjects experienced and were aware of

performance advantages for randomly spaced stimuli, but that the extent of these

advantages differed across individuals.

To better understand these performance advantages, we tested the extent to which

trial-to-trial accuracy and confidence scores depended on stimulus clustering within

the randomly spaced stimulus arrays. Specifically, we computed within-cluster

variance (WCV) for each color array (as for the binary model) to evaluate whether

this clustering statistic could be used to predict subjects' accuracy of, and confidence

in, color reports. As predicted by chunking models (figure 3I), subjects were more

accurate for low WCV trials; performance on high WCV trials was similar to that in

the fixed spacing configuration (figure 4A). Furthermore, subject wagering also

decreased monotonically with WCV, such that betting behavior on the highest WCV

(least clustered) color arrays was similar to that on fixed spacing trials (figure 4B).

Performance advantages are not due to binding errors.

An alternative explanation of these effects is that subjects exhibited higher

performance in low WCV trials simply because they committed binding errors (Bays

et al., 2009), mistaking one color for a nearby related color. To address this issue,

we applied a generalized linear model (GLM) to the binary accuracy and confidence

data. In particular, we included the distances between the target color and each non-

probed color as nuisance variables to determine whether the apparent WCV effects

could be better explained by a tendency to report non-probed colors, which are

often closer to the target color for more clustered stimulus arrays. When this model

was applied separately to subject accuracy and accuracy of reports simulated from a

mixture model that included binding errors, coefficients for WCV were negative in

fits to subject data but negligible when fit to simulated data, suggesting that

performance improvements mediated by WCV were not simply a reflection of

binding errors (figure S2; subject accuracy $\beta = 0.028$, $t = 5.3$, $p < 10e-6$).

Furthermore, when the same model was fit to post-decision wagers, coefficients for

WCV took similarly negative values, suggesting that subjects were aware of the

performance advantages that they gained from the clustered stimulus arrays (β = -

0.049, t = -5.7, p < 10e-7).

Trial-by-trial adjustment in accordance with reinforcement learning

The GLM also included terms to account for other factors that could potentially

affect task performance, including feedback from previous trials. Positive feedback

on the previous trial was predictive of higher accuracy and confidence for the

current trial, in a manner consistent with trial-by-trial behavioral adjustment

(figure S2, "correct (t-1)" coefficient; accuracy β = 0.017, t = 5.0, p < 10e-6;

confidence β = 0.026, t = 4.9, p < 10e-5). This predictive relationship was unlikely to

be driven by autocorrelation in performance, as such an explanation should also

predict that confidence measurements relate to accuracy on future trials, and this

relationship was not evident in the data (figure S2, "correct (t+1)" coefficient;

confidence β = 0.0017, t = 0.3, p = 0.75). Despite seemingly robust feedback-driven

effects, overall performance improvements across the session were somewhat

modest, as evidenced by a relatively small positive coefficient for a term in the GLM

relating block number to accuracy (figure S2, "block" coefficient; accuracy β = 0.007,

t = 2.3, p = 0.02, Bayes Factor = 2.3). Thus, the GLM results suggest that subjects

gained a performance advantage for clustered target arrays, modulated behavior in

response to previous feedback, and improved slightly over the course of task

sessions. Below we provide a more specific test of whether subjects were adjusting

chunking strategies in accordance with the reinforcement learning strategy

employed in the binary encoding model.

Figure 4: Memory recall and confidence are enhanced for clustered stimulus arrays and

adjusted according to trial feedback in accordance with model predictions. A&B: Memory

performance and confidence increase with stimulus clustering. Mean absolute error magnitude (**A**)

and high wager frequency (**B**) were computed per subject in sliding bins of within-cluster variance

(larger values = decreased stimulus clustering) for random (lines) and fixed spacing conditions

(points). Lines and shading reflect mean and SEM across subjects. **C-F**: Mixture model fits reveal

recall benefit of stimulus clustering and hallmark of feedback-driven criterion adjustments. **C**:

Subject data were fit with a mixture model that considered reports to come from a mixture of

processes including 1) a uniform "guess" distribution, 2) a "memory+binding" distribution centered

on the color of the probed target, and 3) a "binding error" distribution including peaks at each non-

probed target [not shown]. Additional terms were included in the model to allow the recall

probability to vary as a logistic function of stimulus clustering, recent feedback, and their interaction.

D-F: Recall probability was modulated by feedback and stimulus clustering in a manner suggestive of

trial-to-trial adjustments of chunking. Mean/SEM coefficients across subjects for each modulator of

recall (log within-cluster variance (WCV), previous trial feedback (pCorr), previous trial log within-

cluster variance (pWCV), pCorr*WCV and pCorr*WCV*pWCV) are represented from left to right as

points/lines. Multiplicative interaction terms were included to capture the form of criterion

adjustments that were used to facilitate criterion learning in the binary encoding model (Fig 3G-I).

E&F: Recall probability of best-fitting descriptive models plotted as a function of the log within-

cluster variance for the current trial and divided according to previous feedback (color) and the log

within-cluster variance from the previous trial [E: pWCV =-1, F: pWCV=-5]. Lines/shading reflect

mean/SEM across subjects. Feedback effects are consistent with reinforcement-learning as

implemented in the binary encoding model: when chunking clustered stimulus arrays is rewarded

with positive feedback, it is reinforced, leading to selective performance improvements for clustered

stimulus arrays on the subsequent trial.

To better understand how working memory fidelity depends on stimulus clustering

and feedback history, we extended a basic mixture model of subject memory reports

(figure 4C; (Bays et al., 2009; Zhang & Luck, 2008)). The model considers memory

reports to come from a mixture distribution that includes a "memory" component

centered on the probed color, a "guessing" component uniformly distributed across

color space and a "binding error" component that assumes reports are centered on

non-probed target colors (not shown in figure; (Bays et al., 2009; Zhang & Luck,

2008)). We allowed the proportion of recall (1-guessing) to vary as a function of the

key factors that should affect performance if subjects are optimizing chunking.

Across subjects, the probability of recall increased with stimulus clustering, as

assessed by within-cluster variance (figure 4D; $t = -5.7$, $p < 10e-6$). Notably,

performance improvements due to stimulus clustering were observed even for

stimulus arrays in which the probed target color was dissimilar to the cluster of

non-probed target colors (figure S3), as predicted by the binary encoding model

(i.e., where chunking increases resources and probability of encoding of other

items). Together with the GLM results above, these findings rule out alternative

explanations in which WCV effects would arise simply by mistaking one color for

another one nearby, and instead support our thesis that clusters of stimuli can be

stored jointly to conserve representational space.

Furthermore, additional coefficients provided evidence that people adjusted

chunking strategies online as a function of reward feedback in a manner similar to

that used to optimize performance in the binary encoding model (figure 3G). In

particular, in our reinforcement learning implementation, the partitioning criterion

was adapted based on the amount of chunking in the previous trial and the

concomitant reward feedback, and it selectively contributed to performance

improvements for the most clustered stimulus arrays (figure 3H-F). To explore the

possibility that people adjust chunking in a similar way, we included additional

terms in the mixture model to allow recall probability to vary as a function of

previous trial feedback (pCorr), proxies for previous and current trial clustering

(pWCV, WCV), and their predicted interactions (see Methods). The best-fitting

coefficients revealed an overall recall bonus on trials following correct feedback

(pCorrect: $t = 5.4$, $p < 10e-5$), but also that the magnitude of this bonus was greater

for trials in which stimuli were more clustered (pCorrect * WCV: $t = -2.1$, $p = 0.04$,

Bayes Factor = 1.6) and for trials in which the level of stimulus clustering matched

that of the previous trial (pCorrect * WCV * pWCV: $t = 2.1$, $p = 0.04$, Bayes Factor =

1.6; figure 4D). Consistent with optimization of chunking via reinforcement learning,

these interactions capture a tendency toward larger feedback-driven changes in

task performance when both the current and previous trial color arrays were highly

clustered (figure 4E&F). Taken in the context of our model, this suggests that when

subjects are rewarded for successfully chunking a stimulus array, they are more apt

to repeat this chunking on the subsequent trial. Moreover, these strategic

adjustments rule out an obligatory alternative mechanism in which chunking occurs

regardless of task demands.

In sum, our abstract model of a memory-limited system predicted performance

advantages and trial-to-trial adjustments associated with selective chunking that

were subsequently validated in empirical data from human subjects performing a

working memory task. Nonetheless, the abstract system that we explored does not

mimic the processing architecture that is used by the brain, leaving open the

question of how selective chunking might be achieved using biological hardware. In

the next section we consider this question in depth, by attempting to endow a

biologically inspired active maintenance model of working memory with the

computational elements necessary to achieve the chunking-based performance

bonus predicted by the abstract model and observed in data from human subjects.

Figure 5: Center-surround connectivity as a mechanism to support chunking and partitioning

operations needed to optimize working memory storage. A&B) Local recurrent excitation and

lateral inhibition are critical for active working memory maintenance in biologically plausible neural

networks (Almeida et al., 2015; Wei et al., 2012). However, the exact form of lateral inhibition has

been varied across studies, with the most common version employing uniform inhibition across the

entire population of tuned excitatory neurons (**A**, (Wei et al., 2012)) whereas others employ broadly

tuned inhibition such that similarly tuned excitatory neurons indirectly exert stronger inhibitory

forces on one another (**B**, (Almeida et al., 2015)). **C)** Simulated firing rates (redder colors indicate

greater firing) of a population of color tuned neurons using the connectivity architecture described in

panel **A** performing a working memory task (ordinate reflects neural tuning preference; abscissa

reflects time in milliseconds; yellow bars indicate 200 ms color inputs delivered in a fixed pattern

across network architectures). As described by Wei and colleagues, bumps of neural activity

sometimes collide, producing "merged" representations (e.g., top activity bump in panel C), a possible

mechanism for chunking. However, also as described by Wei and colleagues, collisions are somewhat

indiscriminate and can increase overall population firing, which in turn can lead to collapse of other

activity bumps (e.g., bottom activity bump) and hence forgetting. **D)** Simulated firing rates from the

same population of neurons for the same task, but using center-surround connectivity (i.e., broadly

tuned inhibition). Note that the closest bumps of activity are selectively chunked (e.g., second and

third bump from top), but the tuned inhibition effectively partitions more distantly separated

representations (e.g., the top from the second and third) and prevents forgetting of unrelated items.

A related consequence of the tuned inhibition is that partitioned representations exert repulsive

forces on one another during the delay period (see differences in separation of activity bumps at pink

arrows). Thus, tuned inhibition affords selective partitioning of representations, but changes

representations through inter-item repulsion.

Center-surround dynamics as a mechanism for chunking and partitioning

The brain is thought to implement visual working memory in neural networks that

include individual neurons tuned to specific visual features and capable of

maintaining representations in the absence of input (Curtis & D'Esposito, 2003;

Fuster & Jervey, 1981; Goldman-Rakic, 1995; E. K. Miller & Cohen, 2001; Warden &

Miller, 2007). In computational models, the ability of a neural network to maintain

feature representations in the absence of inputs depends critically on the recurrent

connections between neurons (Barak, Sussillo, Romo, Tsodyks, & Abbott, 2013;

Durstewitz & Seamans, 2002; Kilpatrick, Ermentrout, & Doiron, 2013; Murray et al.,

2014; X. J. Wang, 1999). In particular, persisting feature representations, like those

of the colors in our task, are facilitated by local excitatory connections between

similarly tuned neurons and by broad inhibition between neurons (X. J. Wang,

1999). Importantly, for simplicity, the most common variant of such models

includes uniformly weighted connections for inhibitory neurons (figure 5A). While

this model exhibits merging of color representations and hence provides a

promising mechanism for chunking, it produces promiscuous merging of individual

color representations (bumps), large and unwieldy bumps of population activity,

and due to uniform lateral inhibition, forgetting of further colors (figure 5C; (Wei et

al., 2012)). Thus in a sense, such bump collisions are analogous to the chunking

implemented in our more abstract binary encoding model, yet they lack the

selectivity necessary to mediate performance optimization, and indeed, predict the

opposite pattern of performance than seen empirically, with worse performance for

randomly spaced arrays and improved performance for fixed arrays (Wei et al.,

2012)

We considered whether other patterns of connectivity would remedy this issue.

Notably, physiological data suggest that neural responses within such networks

obey center-surround receptive field architectures that are present throughout the

visual system (Hubel & Wiesel, 1959; 1965), are supported by lateral connectivity

(Ben-Yishai, Bar-Or, & Sompolinsky, 1995; Kohonen, 1982; Somers, Nelson, & Sur,

1995), and predict biases previously observed in visual working memory reports

(Almeida et al., 2015; Kiyonaga & Egner, 2016). We thus altered the Wei et al. model

to include broadly tuned inhibition in accordance with center-surround recurrence,

whereby Feedback inhibition is stronger for neurons with similar color tuning

(figure 5B). In this case, recurrent excitation promotes merging of nearby color

representations, but tuned inhibition prevents the merged representation from

expanding in width, thereby preventing it from 1) suppressing other activity bumps

through an overpowering lateral inhibition leading to forgetting, and 2)

indiscriminately merging with other activity bumps (figure 5D). Indiscriminate

merging is prevented through repulsive forces exerted by each activity bump on

neighboring representations, which enable separation of dissimilar representations

(see widening gap noted by pink arrows). Thus, center-surround recurrence

provides a dynamic analog to the selective chunking necessary for optimization in

the binary encoding model; nearby representations that share excitatory recurrent

connections are merged into a single representation (chunking) whereas more

distantly separated representations are repulsed by tuned inhibition to effectively

partition moderately dissimilar color representations (partitioning).

This center-surround connectivity profile promotes complex item interactions that

can be summarized by a "difference of Gaussians" function that mediates the

attraction and joint representation of similar colors and the repulsion of dissimilar

ones (figure 6A; yellow shading). If the two stored colors are similar enough to

promote mutual recurrent excitation, each represented color will experience biased

excitation in the direction of its neighboring color, and eventually the two color

"bumps" will merge to form a single representation (figure 6A) (Wei et al., 2012). In

contrast, if the stored colors are separated beyond the narrowly tuned recurrent

excitation function, mutual recurrent inhibition will dominate, leading to a net

repulsion of color representations from one another (Felsen, Touryan, & Dan, 2005;

Kiyonaga & Egner, 2016), which can serve as a selective partition (figure 6A).

Figure 6: Center-surround dynamics facilitate attractive and repulsive inter-item forces that

can improve recall at the cost of precision. A) Local recurrent excitation and broadly tuned lateral

inhibition give rise to two counteracting forces: recurrent excitation facilitates attraction of

neighboring representations through "bump collisions" (Wei et al., 2012), whereas broadly tuned

lateral inhibition facilitates repulsion of distinct bumps of neural activity (Felsen et al., 2005;

Kiyonaga & Egner, 2016). Together, these forces produce a difference of Gaussians tuning function

(yellow shading) that facilitates attraction of closely neighboring representations but repulsion of

more distant ones. Here we model these effects at the cognitive level by assuming that two imprecise

internal representations of color are chunked, and jointly represented by their mean value, with a

fixed probability defined by a narrowly tuned von Mises distribution (green curve; **B**&**C**) in order to

mimic the effects of narrowly tuned excitation. After probabilistic chunking, each color

representation exerts a repulsive influence over all other representations with a magnitude defined

by a broadly tuned von Mises distribution (red curve) in order to mimic the effects of broadly tuned

inhibition. The model stores a Poisson number of the representations, chunked or otherwise, for

subsequent recall. **B**) The influence of center-surround dynamics over model performance can be

manipulated by applying a gain to the amplitude of the excitation and inhibition functions such that

larger values correspond to greater item interdependencies and lead to smaller errors on average

(lighter colors correspond to higher gain). **C&D)** The performance improvement mediated by

increasing center-surround dynamics relies on a tradeoff between recall probability and precision,

through which increased attractive and repulsive forces reduce precision (lighter bars; **C**), but

enhance recall probability (lighter bars; **D**).

We next examined how chunking, as implemented through this framework, would

impact performance as a function of stimulus array size. To do so, we summarized

the impact of center-surround connectivity in an algorithmic model of working

memory performance that contained a small number of intuitive parameters. We

implemented attractive and repulsive forces among stored memories in accordance

with narrowly tuned excitation and broadly tuned inhibition functions (see Methods

for details). On each trial, each color from the target array was: 1) perturbed by a

mean zero random variable to simulate neural noise, 2) chunked with each other

color in the array with probability proportional to the excitation tuning function, 3)

repulsed by each other color in the array with magnitude proportional to the

inhibition tuning function, and 4) probabilistically stored across the delay period

according to a Poisson process. The proportionality constants allowed us to examine

the performance of models ranging from those that were not affected by recurrent

dynamics (zero proportionality constant) to those that were highly affected (large

proportionality constant).

Models implementing greater recurrent dynamics achieved better performance

through a recall/precision tradeoff. Performance was simulated on delayed report

tasks in which target number (array size) ranged from one to eight. Performance of

models employing recurrent dynamics was slightly worse for easier tasks but

dramatically improved for more difficult ones, similar to the effects observed in the

binary model above (figure 6B; lighter lines represent stronger recurrent

dynamics). Here, though, performance differences were characterized by opposing

effects of recurrent dynamics on precision and recall. Models employing recurrent

dynamics showed improved recall, particularly in the hardest tasks, as attractive

forces allowed for the storage of multiple target features in a single representation

(figure 6D). However, these same recurrent dynamics came at the cost of reduced

precision, as both attractive and repulsive forces reduced the fidelity of stored color

representations (figure 6C). In standard models of resource limitations, precision

decrements with increased array sizes have been attributed to the division of a

limited resource. However, in the recurrent dynamics models, the decrement in

precision is caused by the increase in inter-item interactions that occurs when

additional items are added to the memory array. Thus, the inclusion of recurrent

dynamics affects the nature of capacity limitations: minimizing the impact of center-

surround forces leads to a specific decay in recall as a function of array size, as

predicted by "slots" models, whereas maximizing the impact of center-surround

forces leads to decays in precision across set size, which is a key feature of resource

depletion accounts (Bays & Husain, 2008; Luck & Vogel, 2013; Ma et al., 2014; Zhang

& Luck, 2008).

In summary, inter-item dependencies that emerge from center-surround dynamics

are sufficient to mediate the performance bonuses of chunking, but do so at the cost

of precision. Thus, if working memory is optimized through chunking in this way, it

should lead to a higher probability of recall for colors of clustered stimulus arrays

but more precise recall of colors for less clustered ones. In principle, such

optimization could be guided in cognitive or real-world tasks by implicit or explicit

feedback to favor successful chunking strategies and avoid unsuccessful ones.

People are less precise when remembering clustered target arrays.

Our center-surround implementation of chunking and partitioning predicts that

chunking advantages should come at the cost of precision (figure 6B&C). To test this

prediction, we examined the difference in error distributions for random vs. fixed

spacing, pooled across all subjects (figure 7, left column). The error distributions

from both conditions were consistent in shape with those previously reported in

similar tasks (figure 7A&D) (van den Berg et al., 2014). However, the error

distributions differed subtly between the two conditions: in the random-spacing

condition, subjects made more moderately small errors, but did not have more

perfect recalls (figure 7G). This pattern of difference was also evident in data

simulated from the center-surround chunking model (figure 7, middle column) but

not in data simulated from an independent encoding model fit to subject behavior

(figure 7, right column). Thus, both the subjects and the center-surround chunking

model reported more colors that were slightly offset from the target color in the

random-spacing condition than in the fixed-spacing condition, consistent with a

reduction in precision resulting from chunking.

Figure 7: Error distributions reveal evidence for center-surround chunking. A-C) Signed color

reproduction errors made in the random spacing condition by (**A**) subjects, (**B**) center-surround

chunking models, and (**C**) independent encoding models. Data is collapsed across all simulated or

actual sessions. **D-F)** Same as **A-C** but for the fixed spacing condition. Red dashed lines indicate

probed and non-probed target locations. Note that the alignment of non-probed target locations

emphasizes the prominence of non-probed target reports (binding errors), which would appear

uniformly distributed in the random spacing condition. **G-I)** Difference in above error distributions

for random minus fixed. To aid in visualization, bin count differences were smoothed with a Gaussian

kernel (standard deviation = 1 bin). Subjects and the center-surround chunking model show

increased moderately small, but non-zero, errors in the random spacing condition. Note that

differences of reports between the random and fixed conditions near the non-probed targets are

present in both models, as they simply reflect an artifact of the alignment of binding errors in the

fixed spacing condition.

Errors are modulated by nearest neighbors consistent with chunking via recurrence

To better understand the nature of these error distributions, and to what extent

they are predicted by attraction and repulsion forces in center-surround dynamics,

we sorted trials according to the non-probed target color that was most similar to

the probed target color (nearest neighbor color; see Methods for details). This

procedure revealed structure in individual subject color reports related to the

nearest neighbor non-probed color (see figure S4). To determine whether such

structure persisted systematically across subjects, we fit a descriptive mixture

model to error distributions pooled across subjects in sliding windows of nearest

neighbor distance. The model contained free parameters to examine 1) the

precision of error distributions, 2) the bias of error distributions toward (or away

from) the nearest neighbor non-probed target color, and 3) the relative proportion

of trials that were recalled, forgotten, or mis-bound (in keeping with nomenclature

from previous literature (Bays et al., 2009; Fallon, Zokaei, & Husain, 2016)).

The model fits revealed that subject precision and bias depended on neighboring

colors in a manner consistent with chunking through recurrent dynamics. In

particular, subject memory reports were biased towards the nearest neighbor color

if it was sufficiently similar to the probed target color, but biased away from it if it

was sufficiently dissimilar (figure 8A). This pattern of bias maps onto the idea of a

narrowly tuned excitation function promoting attraction of nearby targets and a

broadly tuned inhibition function promoting repulsion of more distant ones (see

figure 8A). Precision also depended on nearest neighbor color distance: subject

precision was maximal when the nearest neighbor color was most dissimilar to the

probe color and minimal when it was moderately similar (figure 8D). In addition,

fits revealed an increase in the proportion of correct recalls, and a corresponding

decrease in the number of uniform guesses, when a nearby neighbor color existed in

the stimulus array (figure S5). This pattern of results was strikingly consistent with

those produced by a chunking model based on recurrent dynamics (figure 8, middle

column) but not with those produced by the best-fitting mixture model (figure 8,

right column).

Figure 8: **Neighboring stimulus features affect bias, precision, and recall probability as**
predicted by the center-surround chunking model. Subject (left) and simulated (center = center-
surround, right = independent encoding) data were collapsed across all sessions and binned in
sliding windows according to the absolute distance between the probed target color and the most
similar non-probed target color (nearest neighbor distance; abscissa). Data in each bin were fit with a
mixture model that included free parameters to estimate 1) the bias of memory reports towards the
closest color in the target array expressed as a fraction of distance to that target (**A-C**), and 2) the
precision of memory reports (**D-F**). The qualitative trends present in subject data are also present in
data simulated from the center-surround chunking model but not in those simulated from the
independent encoding model. Red bars reflect the nearest neighbor distance at which precision fits
to subject data were minimal and also corresponds well with the crossover point of the bias fits.

Quantitative model-fitting of center-surround model reveals empirical evidence of

performance advantage for chunking.

While the above mixture model fits revealed structure across subjects on average,

here we provide a quantitative fit of the center-surround model directly to the trial-

by-trial memory report data for each individual subject, allowing us to quantify

chunking effects and examine the range of behavioral chunking strategies across

individual participants. To make this fitting more tractable (i.e., to facilitate a closed

form likelihood function), we simplified the center-surround model while retaining

its core elements. These simplifications included removal of sensory noise and the

simplification of the center (chunking) and surround (repulsion) forces (see

Methods). We fit three different models to estimate the potentially separable

contributions of center and surround functions using maximum likelihood. The

"center" model estimated the partitioning criterion, which summarized the center

function, as a free parameter, whereas the "surround" model fit the repulsion

coefficient as a free parameter. The "center-surround" model fit both center and

surround with free parameters. All models were also compared to a basic mixture

model. Goodness of fit was evaluated for each model using AIC, which applies a fixed

complexity penalty for each parameter and provided better model recovery for

simulated data than BIC.

Comparison of the center-surround model to a basic mixture model revealed an

explanatory advantage of the former, albeit with considerable heterogeneity across

individual subjects. The center-surround model achieved the lowest mean relative

AIC values of all models (mean[SEM] relative AIC: basic mixture = 4.9[0.9], center =

5.5[0.8], surround = 4.1[0.7], center-surround = 2.9[0.6]). Inclusion of both center

and surround terms was favored by a likelihood ratio test ($\chi^2(94) = 281$, p <10e-5)

and Bayesian model selection favored the center-surround model in terms of

explaining the largest proportion of subject behavior (exceedance probability =

0.85). However, the best-fitting model was not consistent across subjects, with some

subjects best fit by the simple mixture model and others best fit by the center-

surround model (figure 9A). Parameter estimates from the best-fitting center-

surround model were also indicative of heterogeneity. For a large number of

subjects, the best-fitting partitioning criterions were near zero (indicating no

chunking), but partitioning criterions fit to the remainder of subjects were broadly

distributed (figure 9B). Best-fitting repulsion coefficients were more normally

distributed across subjects, tending to take small positive values, indicating a

tendency toward repulsion of partitioned representations (figure 9C).

Heterogeneity in model fits also related to overall task performance in a manner

suggestive of a performance advantage for chunking. Our modeling suggested that

criterion-based chunking could be used to reduce overall errors in a visual working

memory task, and the differences in model fits across our subjects offered us an

opportunity to test this idea. Consistent with chunking facilitating in-task

performance advantages, subjects fit with larger partitioning criterions and

repulsion coefficients achieved better performance on the task (figure 9E&F;

partitioning criterion: Spearman's ρ = -0.54, p = 8.5e-5; repulsion coefficient:

Spearman's ρ = -0.39, p = 7.4e-3). Similar relationships were seen between model

preference and overall performance, with the subjects that were best fit by the

center-surround model also tending to have the lower absolute errors in the task

(figure 9D; Spearman's ρ = -0.59, p = 1.6e-5). In order to examine which parameter

of our model best predicts subject performance, we constructed a GLM to examine

the independent contributions of partitioning criterion and repulsion parameter

estimates on subject performance (as measured by mean absolute error) and found

that when accounting for both variables, only the partitioning criterion maintained

explanatory power, with higher partitioning criterions corresponding to lower

absolute error magnitudes (partitioning criterion β = -0.95, t= -3.2, p = 0.002;

repulsion β = 0.8, t= 0.4, p = 0.7). Thus, individuals who chunked the most liberally

also achieved the best task performance.

Figure 9: Heterogeneous chunking strategies across individual subjects provide empirical

evidence for the performance advantages afforded by chunking. A) AIC difference between

simple mixture model and more complex center (orange), surround (yellow), and center + surround

(blue) models is plotted for each subject, sorted by model preference (positive values indicate that

more complex model is preferred). Aggregate AIC values favored the C+S model, yet there was

substantial variability across subjects in marginal improvement afforded by the C+S model over the

simpler mixture model, with AIC values providing moderate evidence for the mixture in some

subjects, but strong evidence for the C+S model in other subjects. B) Partitioning criterions best fit to

subject data also reflected heterogeneity in strategies across subjects, with a number of subjects best

fit with criterion values near zero, and another subset of subjects taking values across a wider range

from 0.1-0.5. C) Best-fitting repulsion coefficients tended to take positive values across subjects,

indicating that independently represented colors tended to exert repulsive forces on one another by

the best-fitting model parameterization. D-F) Subjects displaying more evidence of center-surround

chunking performed better on the working memory task. D) Mean absolute error was greatest for

the subjects that displayed the least evidence of center-surround chunking, as assessed by the

difference in AIC between C+S and basic mixture models (ρ = -0.59, p = 1.6e-5). E&F) Errors were

also elevated for subjects that were best fit with criterions near zero (E; ρ = -0.54, p = 8.5e-5) or with

small or negative repulsion coefficients (F; ρ = -0.39, p = 7.4e-3).

Center-surround chunking effects generalize across tasks, contribute to set-size

dependent changes in precision, and mediate individual differences in performance.

Finally, to test whether our findings were robust to changes in task conditions and

to examine how chunking effects vary with memory load, we fit a nested set of

models to a meta-analysis dataset that included 101 subjects performing eight

different experiments (James M Gold et al., 2010; van den Berg et al., 2014). The

nested model set included models that varied in their assumptions about chunking,

the distributional form of error reports, and the direct effects of set size on

precision. The model set was built upon a base model that assumed that subjects

would recall a Poisson number of feature representations in the report dimension

and a Poisson number of features in the probe dimension on each trial, with failure

to recall the probe dimension resulting in a binding error and failure to recall the

report feature resulting in a uniform guess. Precision of memory reports was fixed

across trials in this base model. The nested model set included additions to the base

model that allowed it to account for 1) effects of center-surround chunking on the

represented feature value and number of stored features (C in figure 10A), 2) effects

of center-surround chunking on the precision of memory reports (N in figure 10A),

3) differences in error distribution kurtosis through t-distributed memory reports

(T in figure 10A) and 4) changes in precision as a power-function of set size (P in

figure 10A). Performance of the nested model set was compared to that of a variable

precision model with Poisson item storage and binding errors, which was the best-

fitting model in a recent factorial model comparison using most of the same data (VP

in figure 10A, (van den Berg et al., 2014)).

Figure 10: **Center-surround chunking allows better fits of meta-analytic datasets and offers insight into trends and individual differences in how memory degrades with set size. A)** Blue bars/lines represent mean/SEM relative AIC (AIC relative to that of the best model for each subject) and red bars reflect exceedance probability for a nested model set. Base refers to the base model, C includes center-surround chunking, N allows for chunking- and repulsion-induced report variability, T allows for t-distributed errors, and P allows precision to vary as a power-function of set size. Models are compared to the best-fitting model from a factorial model comparison that used this dataset (VP = variable precision, Poisson recall, with binding errors) (van den Berg et al., 2014). Bayesian model selection favored a model that incorporated t-distributed memory reports, power-law precision decrements and all modeled aspects of center-surround chunking (C+N+T+P). A model lacking power-law precision decrements (C+N+T) performed similarly in model comparison to the VP model. **B)** Horizontal bars reflect AIC preference for the winning (C+N+T+P) model over the best model that lacks chunking (VP) for each experiment and are arranged according to mean AIC preference (with experiments providing strongest support for the more center-surround model on top). **C-G**) Posterior predictive checks reveal nuanced discrepancies in the predictions across models. Actual and simulated data were sorted by subject and set size and fit with a flexible mixture model (see Methods) that estimated: guess rate (**C**), binding error rate (not shown), recall rate (**D**), report precision (**E**), modulation of recall by chunking (**F**) and modulation of precision by chunking (**G**). Points and lines reflect mean/SEM fits to subject data whereas lines/shading reflect mean/SEM fits to simulated data for each model (models denoted by color: base = gray, VP = green, C+N+T = blue, C+N+T+P = orange). All models captured guess and recall rates reasonably well (**C&D**), but only models that included either chunking (C+N+T), precision decrements with set size (VP) or both (C+N+T+P) could account for changes in precision of reports across set size (**E**). Only models that included chunking (C+N+T & C+N+T+P) could account for within set size modulation of recall (**F**). Within set size modulation of precision was overestimated by a chunking model with fixed assumptions about precision (C+N+T) and underestimated by models without chunking (base & VP) but well estimated by a model that included chunking and allowed precision to vary with set size

Model comparison favored the most complex model, which incorporated all aspects

of chunking, flexible kurtosis of error distributions, and allowed precision to change

as a function of set size (exceedance probability = 0.96, mean AIC relative to best

AIC = 4.7; figure 10A). Performance of the model that included all aspects of

chunking and kurtosis but not precision decrements was similar to that of the VP

model (mean relative AIC 8.6 and 8.3 for C+N+T and VP models respectively; figure

10A). The advantage of the best performing chunking model was more prominent in

some studies than others. The studies using the widest range of set sizes showed the

largest chunking advantages (the Van den Berg et al. studies all included set sizes 1

through 8), whereas the study using the smallest range of set sizes (Gold et al, 2010;

3 or 4 items) showed a clear preference for the variable precision model over the

best chunking model. It is worthy of note that some of the experiments included in

the meta-analysis included additional manipulations or potential sources of

variability that might have been captured by the variable precision model but could

not possibly be accounted for in our chunking model, such as manipulation of the

duration of stimulus presentation, the duration of delay, and the day of a multi-day

experiment. Thus, despite the overall performance advantage of the best chunking

model, it is still likely that some of the datasets include some residual variability that

could be captured by additional variability in precision across conditions.

In order to better understand why the most complex chunking model offered a

better fit to subject data, we performed a posterior predictive check by simulating

data from each model using the maximum likelihood parameter values and then

examining the simulated and actual data using an extended mixture model fit

separately to data for each set size (figure 10C-G). While all models captured the

general trends in recall and guessing (figure 10C-D), the base model was not capable

of fitting the changes in precision across set size observed in subject data, whereas

both the chunking models and variable precision model could capture these changes

(figure 10E). Only the models that included chunking were capable of accounting for

within-set size fluctuations in recall rate (figure 10F). Similarly, simulated data from

both chunking models produced within-set size modulations of precision that were

qualitatively similar to those observed in subjects, but the chunking model that

lacked the ability to modulate precision according to set size produced much larger

within-set size fluctuations in recall than were actually observed in the data. Thus,

the best-fitting chunking model improved on the VP model by capturing the effects

of center-surround chunking on recall and precision within set size. On the other

hand, the chunking model that did not allow precision to change with set size

seemed to capture set size precision effects by over-estimating the repulsive

interactions between items, leading to a worse fit than the more complex model that

allowed precision to change with set size.

Across experiments and subjects, there were systematic differences in chunking that

related to overall performance. Mean partitioning criterion differed systematically

across experiments in a manner unrelated to overall model preference (figure 10H).

While the number of experiments included in this analysis is small, it should be

noted that two of the experiments that included the least inclusive chunking

behaviors involved storing an orientation rather than a color. The other experiment

with a relatively small mean partitioning criterion (Wilken & Ma 2004) used a color

sampling strategy that prevented fine grain estimation of the best-fitting

partitioning criterion: similar but non-identical colors were never included in a

single color array. Within experiments, subjects also differed in the partitioning

criterion that best described their behavior in a manner that related to performance.

Specifically, subjects that were best fit by the largest partitioning criterion values

also tended to make the smallest absolute errors in the high, but not low, set size

conditions (Figure 10I). Thus, individual differences in chunking may underlie

individual differences in performance for high memory load conditions that have

previously been thought to reflect differences in overall memory capacity.

Discussion:

Our work builds on two parallel lines of research. One has focused on how encoding

and decoding of working memories are optimized under various statistical

contingencies (Brady et al., 2009; Brady & Alvarez, 2011; Brady & Tenenbaum,

2013; Lew & Vul, 2015; Orhan & Jacobs, 2013; Sims et al., 2012), whereas the other

has focused on understanding the nature of capacity limitations in visual working

memory (Bays et al., 2009; Bays & Husain, 2008; van den Berg et al., 2012; 2014;

Zhang & Luck, 2008; 2009; 2011). Here, we explore how people optimize encoding

in the same tasks that have formed the basis of our understanding of capacity

limitations. Our findings shed light on both the nature of memory capacity

limitations and on the encoding strategies employed to minimize their impact.

With regard to encoding strategies, the binary encoding model showed that

selective chunking allowed performance advantages for clustered stimulus arrays

that grew as a function of set size, could be learned according to trial feedback, and

limited asymptotic item storage to approximately four items (figure 3). Unlike

previous models that have examined how non-independent item encoding and

decoding schemes could affect memory performance (Brady et al., 2009; Brady &

Alvarez, 2011; 2015; Lew & Vul, 2015; Orhan & Jacobs, 2013; Sims et al., 2012), our

model shows how memory storage could be optimized without foreknowledge of, or

even the existence of, statistical regularities in memoranda. Because of this, our

model provides unique insight into how subjects might optimize behavior in

standard working memory tasks, in which stimulus dependencies and

foreknowledge thereof are intentionally minimized. As predicted by our model,

human subjects display performance advantages when remembering clustered

stimulus arrays (figure 4&S1) that are not explained by binding errors (Figure

4D&S2) and occur irrespective of whether the recalled item was itself in a stimulus

cluster (Figure S3). Furthermore, trial-to-trial adjustments in performance of

human subjects followed the same basic pattern through which chunking was

learned in our model; namely, rewarded employment of chunking on one trial

increased the probability of chunking on the next (Figure 4E&F). Thus, our model

identifies and provides a normative explanation for a major source of performance

variability across trials in visual working memory tasks: selective chunking of

similar items into working memory and the optimization thereof.

Our findings are in line with previous work that highlights the use of chunking as a

mnemonic strategy in a wide range of working memory tasks (Cowan, 2001).

Chunking was first used to describe mnemonic strategies for storage of sequential

information, for example, encoding the digits 2-0-0-5 as a single date (2005) rather

than as its constituent digits (Chen & Cowan, 2005; Cowan, 2001; G. A. Miller, 1956).

In the visual domain, visual features are in some sense chunked into objects (Luria &

Vogel, 2014). Recent work has suggested that people can chunk arbitrary visual

information when that information is inherently clustered and visible for an

extended duration (Lew & Vul, 2015). Here, we extend on this work to show that a

simple form of chunking, joint encoding of similar feature values, is rapidly

implemented by human visual working memory systems to improve performance in

tasks that have heretofore been thought to lack exploitable statistical structure.

The basic computations necessary to achieve performance advantages through

chunking could be endowed to a recurrent neural network by implementing center-

surround dynamics (figure 5). These dynamics arbitrate a tradeoff between recall

and precision (figure 6) that was supported by empirical evidence of higher

precision representations for unclustered stimulus arrays (figure 7). This sort of

tradeoff between memory precision and item capacity is similar to that observed in

binding pool models of working memory, where the level of connectivity in the

binding pool controls a tradeoff between precision and quantity of representations

(Swan & Wyble, 2014; Swan, Collins, & Wyble, 2016). Here we show that this

tradeoff can be exploited to improve performance, and that human subjects seem to

do so. In particular, subjects demonstrated the performance benefits, response

biases, and costs in precision that were predicted by center-surround chunking and

were quantitatively best described by it (figures 5&7-9). While the quantitative

advantage for the center-surround model was small (figure 9), this advantage was

likely limited in part by technical constraints that required simplification of the

center-surround model for fitting purposes, in particular by the removal of noise in

the initial color representation. Nonetheless, these findings are generally consistent

with previous work that has highlighted the effects of center-surround processing

on perception and memory (Almeida et al., 2015; Johnson, Spencer, Luck, & Schöner,

2009; Störmer & Alvarez, 2014; Xing & Heeger, 2001). Furthermore, the specific

inter-item dependencies predicted by our model and observed in our empirical data

were consistent with those emerging from recurrent neural networks that rely on

tuned inhibition (Almeida et al., 2015), but not with those predicted by hierarchical

models of memory decoding, as the latter do not produce repulsion of dissimilar features (Brady & Alvarez, 2015; Orhan & Jacobs, 2013).

Our center-surround model serves not only to describe nuanced features of behavior, but also to link our findings to potential biological mechanisms. We show that a small change to a prominent neural network model of working memory maintenance, namely the incorporation of tuned inhibition, provides the model with the capability to chunk similar features into a joint representation but partition dissimilar ones through repulsion (figure 5; (Ben-Yishai et al., 1995; Kohonen, 1982; Murray et al., 2014; Somers et al., 1995; X. J. Wang, 1999; Wei et al., 2012)). Our descriptive model based on this mechanistic account is supported by the frequent observation of sustained activity during the delay period of memory tasks in both parietal and prefrontal cortices (Funahashi, Bruce, & Goldman-Rakic, 1989; Fuster & Alexander, 1971; Gottlieb, 2004) (but see also (Lara & Wallis, 2014)). Here we have considered the network to store features on a single dimension (color); however, it is clear that at some level, conjunctive coding across features (e.g. color and orientation) is necessary to bind information to the dimension used to probe memories (Matthey, Bays, & Dayan, 2015). In our task, it is unknown whether any sustained representations reflect information about the report feature (color in our task), probe feature (orientation in our task), or some conjunction of the two. Recent work has hinted that in some cases, sustained representations in prefrontal cortex may only encode the probe dimension, which could point back to relevant sensory representations at time of recall (Ester, Sprague, & Serences, 2015; Kriete, Noelle,

Cohen, & O'Reilly, 2013; Lara & Wallis, 2014; 2015). Previous computational

instantiations of this process have relied on the basal ganglia to learn appropriate

prefrontal representations that can be jointly cued by multiple disparate perceptual

features, based on reward feedback (A. G. E. Collins & Frank, 2013; Frank & Badre,

2012; Kriete et al., 2013). Analogously, feedback effects observed in our data could

be driven by the basal ganglia learning to selectively engage prefrontal units that are

prone to representation of multiple probe feature values. This interpretation could

expand on a large body of work that implicates the basal ganglia in gating working

memory processes by stipulating a novel and testable role for the basal ganglia in

optimizing joint feature encoding (Chatham, Frank, & Badre, 2014; A. G. E. Collins &

Frank, 2013; Hazy, Frank, & O'Reilly, 2006; O'Reilly & Frank, 2006; Voytek & Knight,

2010).

An important question stemming from our work is to what extent chunking can be

adjusted to optimize working memory accuracy under different conditions. Our

modeling shows that a simple learning rule is capable of rapidly adjusting the

amount of chunking to optimize performance given the current memory demands,

leading to greater chunking for higher memory loads. Individual differences in

chunking were selectively related to performance in the highest memory load

conditions (figure 9E & 10I); however, neither our experiment, nor the meta-

analytic dataset explicitly manipulated chunking incentives over a time-course long

enough to measure learning effects. Nonetheless, even in the absence of explicit

manipulation, feedback-dependent modulation of chunking behaviors in our

experimental data was indicative of online optimization of the chunking process

(figure 4D-F), such as the process that allowed learning of the partitioning criterion

in the binary encoding model (figure 4G). Yet these trial-to-trial adjustments occur

despite only minimal performance improvements across task blocks (figure S2).

There are several possible explanations for this discrepancy, including 1) that a

priori processing strategies are well-calibrated to our task, 2) that optimization in

our task occurs on a different timescale than our measurements, and 3) that the

presence of uniformly spaced arrays hindered learning overall. Distinguishing

between these possibilities will require a better understanding of what exactly is

being adjusted in response to feedback. For example, reward feedback could

promote the prioritization of storing chunked arrays over non-clustered ones, or it

could modulate center-surround inhibition dynamics (e.g., via fine tuning of feature

selective attention and/or altering local excitation-inhibition balance (Störmer &

Alvarez, 2014; Wei et al., 2012)). In any case, our work, along with other recent

research showing an adaptive tradeoff of precision and recall (Fougnie, Cormiea,

Kanabar, & Alvarez, 2016), strongly motivate future work to better understand the

scope, time course, and mechanism for this type of optimization process.

Implications for capacity limitations. Working memory limitations have been

theorized to result from either a discrete limitation on available "slots" or a

continuous limitation by a divisible "resource". The distinction between these

theories is most evident when additional targets are added to a memory array. A

discrete limitation predicts that after all slots are filled, additional targets will be

forgotten and will be reported as random guesses (Luck & Vogel, 2013). In contrast,

a resource limitation predicts that additional targets will cause each target to be

encoded with lower precision (Ma et al., 2014). While individual studies have

provided support for each theory (Bays et al., 2009; Bays & Husain, 2008; Cowan &

Rouder, 2009; Chris Donkin et al., 2013a; Christopher Donkin et al., 2013b; Pratte,

Park, Rademaker, & Tong, 2017; Rouder et al., 2008; van den Berg et al., 2012;

Zhang & Luck, 2008; 2009; 2011), a recent meta-analysis provides simultaneous

support for the core predictions of both: increasing memory load leads to both

increased guessing and decreased precision (van den Berg et al., 2014).

Our results suggest that a joint capacity limitation over recall and precision may

result in part from a rational chunking procedure implemented through center-

surround dynamics to effectively trade precision for recall (figure 5&6). This

procedure allows subjects to achieve performance improvements for clustered

stimulus arrays at the cost of precision (figures 6). It is also capable of explaining

decrements in precision with set size, as larger sets of items lead to increased

repulsive forces experienced by each individual item (figure 10E). In addition to

accounting for known influences on precision, our model also predicted that

measured precision should vary across trials, an established feature of human

behavioral data (Fougnie et al., 2012; van den Berg et al., 2012), and correctly

predicted that this variability in precision should depend on the features of non-

probed targets (figure 8D&E; 10G). Nonetheless, the best-fitting center-surround

chunking model employed leptokurtic memory reports in order to capture

additional variability in precision that was not accounted for by the chunking and

repulsion processes alone, suggesting that other factors must also contribute to

variability in precision (figure 10A). Furthermore, the best-fitting model also

allowed memory report precision to vary as a power function of set size, as this

appropriately balanced the magnitude of across set size (figure 10E) and within set

size (figure 10G) precision effects. Thus, center-surround chunking, as we

implemented it, can quantitatively account for most, but not all, of the changes in

precision across trials and set-sizes.

Our findings also call the interpretation of precision measurements into question.

The center-surround model predicts that internal representations apply attractive

and repulsive forces to one another, systematically biasing memory reports. When

averaged across trials with differing stimulus configurations, such interactions are

interpreted as variability in memory reports, as the net forces on a probed target

vary randomly from one stimulus configuration to the next. Yet, since much of this

variability is simply an artifact of averaging across disparate conditions, our work

raises an important question: how much of the variability in memory reports across

trials and individuals is truly reflective of imprecision, rather than bias? While the

notion that imprecision can emerge from systematic inter-item dependencies is

somewhat at odds with the basic resource limitation model, it is consistent with the

recent proposal of a specific form of resource limitation in which the constrained

resource is the representational space itself (M. A. Cohen, Rhee, & Alvarez, 2016;

Franconeri, Alvarez, & Cavanagh, 2013; Oberauer & Lin, 2017).

Within such a framework, it is interesting to reconsider the meaning of individual

differences in memory storage recall and precision. Previous work has shown that

individual differences in the number of items successfully retained in visual working

memory tasks, but not differences in precision, are related to fluid intelligence and

psychiatric conditions such as schizophrenia, among other factors (Fukuda, Vogel,

Mayr, & Awh, 2010; James M Gold et al., 2010). These results have been interpreted

in terms of differences in a discrete capacity for memory storage, or in filtering

irrelevant information (Vogel, McCollough, & Machizawa, 2005), but our results

suggest that some of these individual differences may be driven instead by

differences in chunking behavior or the optimization thereof. To this effect, we

showed both in our own dataset and in the meta-analytic dataset that individual

differences in task performance, particularly at high set sizes, were systematically

related to differences in chunking policy, with subjects that chunked most liberally

achieving the best performance for higher set sizes (figures 9E&10I). Given that the

best chunking policies in our binary encoding model for a set size of five were quite

liberal (figure 3A,C,D,F) we suspect that a number of subjects could have improved

performance dramatically, were they to have chunked more liberally. In fact, a

subset of subjects was best fit by models that fully partitioned color information

(figure 9A), achieved lower overall performance (figure 9E), and likely attenuated

the aggregate performance advantages for clustered stimulus arrays (compare

figure 3L to figure 4A). It is not clear to what extent these individual differences in

chunking policy result from differences in the ability to learn an appropriate

criterion, or from hard-wired differences that might predispose individuals toward

either chunking or partitioning neural representations. Our neural network model

suggests that performance-based measures of capacity may be sensitive to

individual differences in lateral connectivity profiles that favor a spectrum from

independent to merged feature storage policies, and to the ability to override such

policies through learned top-down modulation of lateral connectivity (Freeman,

Driver, Sagi, & Zhaoping, 2003; Freeman, Sagi, & Driver, 2001; Lowe et al., 2016).

In summary, our results show that humans readily exploit chunking strategies to

improve performance on visual working memory tasks. The implementation of

chunking is consistent with a form of center-surround dynamics that combines

similar representations and facilitates mutual repulsion of disparate ones. This

implementation leads to a fundamental tradeoff between the number of items

stored and the precision with which they are stored, providing a natural bridge

between slots and resource accounts of working memory capacity limitations.

People optimize this tradeoff from trial-to-trial according to stimulus statistics and

evaluative feedback in a manner that differs across individuals and is predictive of

working memory task performance. These results provide a normative joint account

of how and why discrete and continuous factors contribute to working memory

capacity limits across individuals and task conditions.

Methods:

Delayed report task. 54 human subjects completed five blocks (100 trials each) of a

delayed report color reproduction task (figure 2). Each trial of the task consisted of

four primary stages: stimulus presentation, delay, probe, and feedback. During

stimulus presentation, subjects were shown five oriented bars (length = 2 degrees

visual angle) arranged in a circle (radius = 4 degrees visual angle) centered on a

fixation point. Bar positions were equally spaced around the circle and jittered

uniformly from trial to trial. Bar orientations were uniformly spaced, jittered from

trial to trial, and independent of position or color. Bar colors were chosen from a

fixed set of colors corresponding to a circle in CIELAB color space (L= 80, radius in

a*, b* = 60) and referred to by angular position for convenience. In the "random

spacing" condition, all five colors were sampled independently of one another from

the color space, allowing for the possibility of two similar colors in the same

stimulus array. In the "fixed spacing" condition, colors were uniformly spaced along

the CIELAB color wheel and randomly assigned to bar locations. Stimuli were

presented for 200 ms, after which the screen was blanked.

The subsequent delay period lasted 900 ms, during which subjects were forced to

remember the colors and orientations of the preceding stimulus array. During the

subsequent probe stage, subjects were shown a gray oriented bar in the center of

the screen for one second, before being asked to report the color that had been

associated with that orientation in the preceding stimulus array. Color reports were

made by adjusting the color of the oriented bar using a mouse. The initial position of

the mouse on the color wheel was randomly initialized on each trial. On a subset

(1/3) of trials, subjects were asked to make a post-decision wager about the

accuracy of their report by choosing to bet either 0 or 2 points. Binary feedback was

provided on each trial based on whether subject reporting accuracy fell within a

certain error tolerance window (π/3 radians – low precision condition [26

subjects] or π/8 radians – high precision condition [28 subjects]). A priori target

sample size for each group was set to twenty-four based on other studies in the field

(without explicit power calculations). Additional subjects were recruited beyond

this to account for potentially unusable data (e.g. subjects guessing on all trials).

Four subjects in the high precision condition and three subjects in the low precision

condition were removed from analyses because of error distributions that were not

statistically distinguishable from uniform guessing (error variance > 0.91), leading

to sample sizes of 23 and 24 for low and high precision conditions respectively. All

subjects were paid bonuses according to total accumulated points. All human

subject procedures were approved by the Brown University Institutional Review

Board and conducted in agreement with the Declaration of Helsinki.

Binary encoding model. To explore the potential advantage of chunking in delayed

report tasks, we developed a flexible and computationally tractable model for

capacity-limited storage. This model stores color and orientation information

symbolically in a set of binary "words" concatenated to form a "sentence". During

the stimulus presentation phase, target colors and orientations are "encoded" as an

alternating sequence of binary words reflecting the position on a circular feature

space (figure 3). The number of binary digits (bits) in a word controls the precision

with which the feature is stored. For example, a single digit can encode which half of

the feature space contains the color of a bar, whereas three bits can narrow the

stimulus color down to one eighth of the color space (figure 3, top). Each binary

word is followed by a "stop" symbol denoting the type of information in the

preceding word (e.g. color or orientation). A capacity limitation is implemented in

the model as a limit on the number of bits that can be stored in memory. Specifically,

we applied a fixed limit of 15 bits for storage of color information. Similar results

were achieved by applying a limit to the total bits, i.e. including orientation

information, but here we allow for perfect orientation storage in order to isolate the

effects of capacity limitations on the recall dimension (color).

Bits were allocated in two different ways: in one set of simulations, bits were

assumed to be continuously divisible (analogous to resource models) and in the

other set of simulations, bits were not divisible beyond binary units (analogous to

slots-and-averaging models). For resource model simulations, performance was

computed analytically according the following error function:

$$Error = \left| \Delta\mu + \int_{r=0}^{R} \left(\frac{R}{2} - r \right) dr \right|$$

1   where Δμ is the difference in the "chunk" mean and the true color and R is the

2   continuous range over possible stimulus values specified by the encoding model,

3   which depends on the number of bits allocated to each item according to the

4   following function:

$$R = \frac{2\pi}{2^b}$$

where b is the number of bits allocated to each target, which in turn depends on the

total number of items and the exact pattern of chunking and partitioning across the

stimulus values. Chunking and partitioning were controlled in three ways: 1) in the

fully partitioning model, all colors were represented separately, 2) in the optimal

partitioning model, all possible partitioning patterns were considered for each

stimulus array and only the performance of the best partitioning pattern was

reported, and 3) in the criterion-based partitioning model, adjacent colors were

partitioned (represented distinctly) if they were separated by a distance that

exceeded the partitioning criterion. Colors that were not separated by partitions

were combined into a single "chunk" and represented by their mean value. This

procedure could sometimes lead two colors that were separated by distances

greater than the partitioning criterion to be included in the same chunk, if they were

both sufficiently close to an intermediate color. The performance of the criterion-

based partitioning model was computed across a range of possible partitioning

criterions and the performance of the best-performing criterion across all trials for a

given set size was reported (see figure 4A).

In the second set of simulations where bits were considered to be indivisible,

analogous to the slots + averaging framework, model performance was assessed

through exhaustive simulations. In this framework, bits were as evenly distributed

among represented colors as was possible for a given stimulus array, as this

strategy for allocation of bits achieved the best performance. During the probe

phase, the model is presented with a single orientation and recalls the color word

that immediately precedes that orientation in the stored binary sentence. A report is

then sampled from a uniform distribution across the range of colors consistent with

that stored binary color word. For example, if the color word contains one, two, or

three bits, it is sampled from uniform distribution over one half, quarter, or eighth

of the color space.

Chunking was parametrically implemented in the binary encoding model by adding

a "partitioning criterion" that specifies the minimum distance between two colors in

color space that is necessary for independent storage. Colors separated by distances

greater than the partitioning criterion are partitioned, and all colors that are not

separated by a partition are combined into a single color representation. The

distance computation is completed during the "encoding" phase, before colors are

converted to binary words. Distances are corrupted with a small amount of

independent noise consistent with variability in the visual representation or the

chunking processes (normally distributed with standard deviation equal to 0.4

times the partitioning criterion). This noise gave rise to variability in the chunking

process, such that a given set of stimuli might be partitioned differently on different trials. After chunking, bits are allocated evenly across all represented colors, as described above.

Model performance was simulated for the delayed estimation task across eight different array sizes (1-8) with two different color generation conditions (fixed- and random-spacing) for nine different partitioning criterions ranging from zero to π. For each condition and model, mean absolute error was computed across 5000 simulated trials. The best chunking model (see figure 4L) was defined as the model with the lowest mean absolute error, whereas the fully partitioned model was the model with partitioning criterion equal to zero (such that every color was stored independently). For each condition, chunking bonus was computed as the difference in absolute error between the non-chunking and best-chunking models.

For the trial-to-trial optimization of the partitioning criterion (figure 4g), we adjusted the partitioning criterion on each trial according to the following rule:

$$PC = PC - \alpha \, \delta \, \Delta C$$

where PC is the partitioning criterion, α is a learning rate, δ is a reward prediction error (previous trial feedback minus long term average feedback), and ΔC is the number of "chunks" into which the previous stimulus array was divided minus the long term average of that quantity. Thus, if by chance the model did more chunking

on a given trial, the ΔC would take a negative value, and positive feedback would

drive a positive δ and a corresponding increase in the partitioning criterion, leading

to an increase in chunking on subsequent trials. Negative feedback for the same trial

would lead to a negative δ and corresponding decrease in the partitioning criterion,

leading to a decrease in chunking on subsequent trials.

Computing array clustering. In order to assess the potential benefits of chunking on

each trial we computed a clustering statistic, within-cluster variance (WCV), for

each stimulus array. WCV was computed by dividing the array colors into two

clusters that minimized the mean variance within the clusters. WCV was defined as

the average circular variance over colors within these clusters.

Logistic regression models. Binary accuracy and betting data were concatenated

across all subjects and interrogated with a mixed-effects logistic regression model

that included terms to account for fixed effects of 1) –log(WCV), a proxy for stimulus

array chunkability, 2) the color distance between the probed target and each other

color in the array, ordered from smallest to largest, 3) feedback on previous and

subsequent trials, 4) spatial distance between the location of the probed target and

the location of the previously probed target, and 5) task block. In addition, the

model included dummy variables to account for random intercepts specific to

individual subjects. The same analysis was applied to data simulated from the best-

fitting mixture model, which considered all reports to come from a weighted

mixture of recall, uniform guess, and binding error distributions (Bays et al., 2009).

Mixture model. We extended the standard mixture model of memory reports (Bays

et al., 2009; Zhang & Luck, 2008) to allow for modulation of recall probability,

precision, and bias according to WCV, nearest neighbor distance, and feedback. The

standard mixture model assumes reports are generated from a mixture of "correct

recall", "guessing", and "binding error" processes. These three mixture components

were specified using two free parameters: one dictating the probability with which

an item would be successfully stored ($correct\ recall + binding\ error$) and one

specifying the probability with which a stored item would be correctly reported

$\left(\frac{correct\ recall}{correct\ recall + binding\ error}\right)$. We allowed the parameter dictating successful storage

to be modified as a logistic function of 1) log(WCV), 2) previous feedback, 3)

previous log(WCV), 4) previous feedback*log(WCV) and 5) previous

feedback*log(WCV)*previous log(WCV). All potential modulators of successful

storage were mean-centered (before and after interaction) and constrained by

priors favoring values near zero [~normal(0, 0.5)]. Since our successful storage

parameter is the probability the subject will not elicit a uniform guess, it affects both

correct recall and binding error mixture components. However, since reports were

far more likely to correspond to correct recalls (median mixture proportion = 0.50

across subjects) than binding errors (median binding error proportion = 0.17 across

subjects), modulator coefficients had larger effects on recall than binding errors,

and we refer to them in the results as modulating recall for simplicity. We also

considered an alternative model in which modulators affected the recall term

directly and found similar results, although this alternative model provided a worse

overall fit of the data. Group mean parameter estimates were tested against the null

hypothesis (estimate = 0) with a classical one sample t-test; however, in cases where

moderate p values were observed (p <0.1 & p > 0.01) Scaled-Information Bayes

factors were computed to quantify the model evidence in favor of the alternative

hypothesis relative to that of the null hypothesis (rscale=0.707) {Rouder:2009ij}.

Neural network simulations. Neural network simulations were conducted using a

basic recurrent neural network that has been described previously (Wei et al.,

2012). The model consists of 2048 pyramidal (excitatory) neurons and 512

inhibitory interneurons. Pyramidal neurons had the following cellular properties:

C_m = 0.5 nF, g_{leak}= 0.025 μS, V_{leak} = -70 mV, V_{thresh} =-50 mV, $V_{res\_}$=-60 mV, τ = 1 ms.

Interneurons had the following cellular properties: C_m = 0.2 nF, g_{leak}= 0.02 μS, V_{leak} =

-70 mV, V_{thresh} =-50 mV, $V_{res\_}$=-60 mV, τ = 1 ms. The model included AMPA, NMDA,

and GABA receptors with properties described previously (Furman & Wang, 2008).

Pyramidal-to-pyramidal connection weights followed a narrowly tuned Gaussian

profile across stimulus space (σ =5, J^+ =5.6). Pyramidal-to-interneuron and

interneuron-to-pyramidal connectivity profiles were identical, and in one set of

simulations fully connected with uniform weights (figure 5C). In the second set of

simulations, the cross-population connectivity was defined by a mixture of uniform

weights and broadly tuned Gaussian weights (σ =20, mixture proportion = 0.1).

Input was delivered to both networks for 200 ms through activation of an AMPA

current with g_{max} = 0.57 using a spatial profile that was centered on 5 "target colors"

with a Gaussian profile (σ =4). Stimulus delivery was followed by a delay period

during which no input was provided to the network and activity was sustained

completely through recurrent connectivity.

Center-surround chunking model. To determine the effects that center-surround

dynamics would have on visual working memory task performance, we extended

the standard descriptive model of delayed memory reports to incorporate features

of center-surround dynamics. In particular, on each trial, internal representations of

each color were generated from a von Mises distribution with fixed concentration (7

for simulations). Pairwise distances (in color space) were computed for each pair of

internal representations. Chunking probability was computed as a scaled von Mises

function of this distance ($\mu = 0$, $\kappa = 12$ for simulation), corresponding to the narrow

excitatory "center" over which local representations are likely to attract one another

(figure 5A-C). Representations were merged in accordance with these chunking

probabilities by replacing the color associated with each merged representation

with the mean of the merged colors. After probabilistic chunking, distances were

recomputed between representations, and each representation applied a repulsive

force on neighboring representations as defined by a scaled von Mises function of

the re-computed distance ($\mu = 0$, $\kappa = 2$ for simulation), corresponding to the broadly

tuned "surround" over which representations repulse one another (figure 5A-C).

Applying these forces leads each representation to be reset according to the

following equation:

$$color_i \leftarrow color_i + \sum_{X \neq i} W_{surround} \ \left(\frac{e^{\kappa \cos(color_i - color_x)}}{2\pi \mathrm{I}_0(k)}\right) \left(\frac{|color_i - color_x|}{color_i - color_x}\right)$$

where $W_{surround}$ is a weight that controls the overall magnitude of surround effects,

the second term in the sum is the probability density function for a von Mises

distribution, and the final term serves to ensure that targets exert repulsive forces

on neighboring targets. For the simulations in figure 5, the weight parameters for

both center and surround were set to equal values ranging from 0 to 0.7. For

comparisons to subject data, $W_{surround}$ was set to 0.6 and W_{center} was set to 1.2.

Probabilistic recall was implemented in the model according to a Poisson memory

process (Sims et al., 2012; van den Berg et al., 2014). On each trial, the model

accurately recalled some number of representations drawn from a Poisson

distribution (λ = 2 for simulations). Similar results were achieved using an

inhibition based forgetting process inspired by Wei and colleagues (Wei et al.,

2012); however, here we use a more standard Poisson process for simplicity. In the

case that a representation that was not successfully recalled was probed, the model

reported either a uniformly distributed guess (p = 0.65) or the color of an

alternative representation (binding error, p = 0.35).

Quantitative model fitting. In order to estimate model-likelihood directly, the center-

surround chunking model was modified to allow for a closed-form likelihood

function. To this end, we stipulated that internal representations would perfectly

reflect the true stimulus colors before being subjected to chunking and repulsion

processes instead of assuming that internal representations were subject to

variability resulting from perceptual processing (as described above). In order to

improve gradient descent, we implemented chunking using a gamma distribution

over partitioning criterions in which the mean of the distribution was fit as a free

parameter and the variance was fixed to 0.01. The repulsion process was simplified

to a linear function of inter-item similarity, with a slope that was fit as a free

parameter and could take either positive values to capture attraction or negative

values to capture repulsion. Three versions of the simplified chunking model were

fit to delayed report data: 1) a center-only model in which the partitioning criterion

mean was fit as a free parameter and the repulsion coefficient was fixed to zero, 2) a

surround-only model in which the partitioning criterion mean was fixed to zero and

the repulsion coefficient was fit as a free parameter and 3) a center-surround model

in which both terms were fit as free parameters. In addition, all models included the

following free parameters: 1) Poisson lambda to describe the number of items that

would be stored on a given trial, 2) binding error fraction to describe the frequency

that reports would be generated from a non-probed representation, and 3)

precision of the report distribution. All models were compared to a basic mixture

model (Bays et al., 2009) using to penalize for complexity, as AIC allowed for better

model recovery from simulated data than did BIC. AIC values are reported for each

model relative to the lowest AIC model achieved by any model for a given subject

(relative AIC). Bayesian model selection was performed using -1/2 AIC as a proxy

for model evidence with the SPM toolbox (Stephan, Penny, Daunizeau, Moran, &

Friston, 2009).

Meta-analysis. In order to test the robustness of our findings and determine how the

behavioral hallmarks of chunking scale with the size of the stimulus array, we

applied a modified version of our mixture model to a meta-analysis dataset. The

meta-analysis dataset included eight studies and a total of 101 subjects (Bays et al.,

2009; James M Gold et al., 2010; Rademaker, Tredway, & Tong, 2012; van den Berg

et al., 2012; Wilken & Ma, 2004; Zhang & Luck, 2008). Seven of the datasets,

available online at http://www.cns.nyu.edu/malab/resources.html, were originally

compiled by van den Berg et al. and have previously been described in detail (van

den Berg et al., 2014). Three of the studies compiled by Van den Berg et al. were

excluded from our analyses due to retraction of the original studies, although the

inclusion of these studies did not qualitatively change our results. The eighth

dataset (28 subjects) comprised the control subjects in a psychiatric comparative

study of visual working memory (James M Gold et al., 2010). Each study differed in

experimental details but involved a delayed report working memory task with at

least two different array sizes.

Quantitative model fitting to meta-analytic data. We constructed a nested set of

models to better understand whether chunking could improve explanations of

behavior in previous studies visual working memory studies. Each model was

extended beyond a "base" model in which the partitioning criterion was fixed to

zero. The base model included one change from the models that were fit to the data

from our experiment in order to account for the possibility that binding errors

depend on set size (which was variable in the meta-analytic data but fixed in our

own study). Specifically, we replaced the fixed-probability of binding errors with a

Poisson distribution that described the number of probe dimension features that

would be recalled on a given trial (s), with lambda of this distribution fit as a free

parameter. For each trial, this distribution was used to compute a probability that

the relevant probe feature would not be stored in memory:

$$p(forgot\ probe) = 1 - \sum_{s=0}^{\infty} p(s) * \min\left(1, \frac{s}{n}\right)$$

where n is the number of targets presented on a given trial and p(s) is the

probability of recalling s probe dimension features on a Poisson distribution. The

minimum term accounts for the case where the number of available items is smaller

than the number of probe dimension features that could have been stored on a given

trial.

The probability of making a binding error, given that the recall feature was

remembered, was then computed as:

$$p(BE) = p(forgot\ probe) - \frac{p(forgot\ probe)}{n}$$

to correct for the possibility that, in the case that the model did not correctly store the probe dimension feature, it could choose the correct report dimension feature by chance. This change allowed the model to capture tendencies for binding errors to increase with set size, as have been reported previously (Bays et al., 2009).

The first extension to the base model allowed the partitioning criterion and repulsion criterion to be fit as free parameters, rather than set to zero as they were in the base model. This extension allowed the model to capture the biases and recall benefits that are predicted by our more general center-surround chunking model (e.g. figures 5-8); however, it would not capture variability in reports that would be expected to occur through the amplification of sensory noise by the chunking and repulsion processes, as the sensory noise was removed in order to allow for a closed form likelihood function.

In order to account for the basic effects of chunking and repulsion on report variability that would be expected based on our center-surround chunking model, but maintain the tractability of our likelihood function, we added two additional parameters to the model to allow the variance in memory reports to scale linearly with 1) the variance of feature values stored within a single chunk [chunking noise], and 2) the total repulsive forces experienced by the recalled feature [repulsion noise].

We also considered an extension that employed a more flexible report distribution

that included an additional free parameter to model differences in kurtosis. In this

extension, memory reports were generated from a t-distribution centered on the

value of the internal representation and truncated at that value plus or minus π

radians. The t-distribution included a base scale parameter fit to each subject, which

accounted for overall variability in memory reports and was incremented by the

additional chunking and repulsion variability as described above. In addition, the t-

distribution included a degrees of freedom parameter that was fit to each individual

subject, which allowed the model to capture report distributions ranging from

leptokurtic (low degrees of freedom) to mesokurtic (high degrees of freedom).

Finally, we considered an extension to the model that included the possibility that

precision depends on set size. Specifically, we stipulated that precision, or inverse

variance, of memory reports would obey a power-law relationship with set size:

$$\frac{1}{\sigma_{report}^2} = J * n^\alpha$$

17   where J is the response precision expected when set size is equal to 1, and α is the

18   power delineating the dependency of precision on set size, with negative values of α

19   corresponding to precision values that decay with set size.

The nested set of models were tested against one another, and also compared to a

variable precision model that includes Poisson item limits and binding errors that

scale linearly with set size, which was the best performing model in a previous

meta-analysis of delayed report working memory behavior (van den Berg et al.,

2014). Model comparison using AIC and Bayesian model selection was done as

described above. Posterior predictive checks were conducted by fitting actual and

model-generated meta-analytic data with a descriptive model of memory report

distributions separately for each subject and set size. The descriptive model

estimated the rate of three response types (guess, binding errors, and correct recall)

and the precision of memory reports as has been described previously (Bays et al.,

2009). However, the model also included two additional terms to capture

fluctuations in recall and precision within a given set size that would be predicted

by chunking. Specifically, the model allowed the probability of recall to vary as a

logistic function of trial-to-trial recall probabilities extracted from the center-

surround chunking model, and allowed the variance of the report distribution to

vary as a linear function of the trial-to-trial prediction for response variance

extracted from the center-surround chunking model. Trial-to-trial model

predictions were extracted from the center-surround chunking model that included

chunking and repulsion noise as well as t-distributed errors, as this model provided

a combination of a good fit to most subject data and relatively well-behaved

parameter estimates.

Nearest neighbor analysis. For each trial, the nearest neighbor color was identified as the color of the non-probed target that was most similar to that of the probed target. Target colors and subject reports were transformed for each trial such that the probed target color corresponded to zero and the nearest neighbor color ranged from zero to π. Trials were then sorted according to absolute nearest neighbor distance (see figure S2) and binned in sliding windows of 50 trials according to nearest neighbor distance. Binned data were combined across all subjects and fit with a mixture model that assumed data were generated from a mixture of 1) a von Mises distributed memory report (free parameters: mean, precision, and mixture weight), 2) uniformly distributed guesses (free parameters: mixture weight), and 3) binding errors that were von Mises distributed and centered on non-probed targets (no free parameters required, as mixture weight forms simplex with the other mixture components). Maximum posterior probability parameter estimates for the mixture model fits to subject and model simulated data are reported in figure 9 (prior distributions for all modulator terms were centered on zero with $\sigma = 0.5$ for recall modulators, $\sigma = 2$ for precision modulators, and $\sigma = 0.05$ for bias modulators).

Author Note:

We thank Ronald van den Berg, Wei Ji Ma and Jim Gold for sharing data from previously published delayed report studies. We thank Xiao-Jing Wang for providing code for neural network simulations. We thank Karen Schloss for help with accurate color rendering. We thank Anish Aitharaju, Anthony Jang, Ji Sun Kim, Michelle Kulowski, and Ezra Nelson for aiding in data collection. We thank Nicholas Franklin

and Nathan Vierling-Claassen for helpful discussion. This work was funded by NIMH

grant F32 MH102009 and NIA grant K99AG054732 (MRN), as well as NIMH grant

R01 MH080066-01 and NSF grant #1460604 (MJF). A previous version of this work

was presented at the New England Research on Decision Making (NERD) conference

and was published as a preprint on biorxiv:

http://biorxiv.org/content/early/2017/01/06/098939 .

Competing interests:

The authors declare no competing interests.

References:

Almeida, R., Barbosa, J., & Compte, A. (2015). Neural circuit basis of visuo-spatial

working memory precision: a computational and behavioral study. *Journal of*

Neurophysiology, *114*(3), 1806–1818. http://doi.org/10.1152/jn.00362.2015

Barak, O., Sussillo, D., Romo, R., Tsodyks, M., & Abbott, L. F. (2013). From fixed points

to chaos: Three models of delayed discrimination. *Progress in Neurobiology*, *103*,

214–222. http://doi.org/10.1016/j.pneurobio.2013.02.002

Bays, P. M., & Husain, M. (2008). Dynamic shifts of limited working memory

resources in human vision. *Science*, *321*(5890), 851–854.

http://doi.org/10.1126/science.1158023

Bays, P. M., Catalao, R. F. G., & Husain, M. (2009). The precision of visual working

memory is set by allocation of a shared resource. *Journal of Vision*, *9*(10), 7.1–11.

http://doi.org/10.1167/9.10.7

Ben-Yishai, R., Bar-Or, R. L., & Sompolinsky, H. (1995). Theory of orientation tuning

in visual cortex. *Proceedings of the National Academy of Sciences of the United*

States of America, *92*(9), 3844–3848.

Brady, T. F., & Alvarez, G. A. (2011). Hierarchical Encoding in Visual Working

Memory: Ensemble Statistics Bias Memory for Individual Items. *Psychological*

Science, *22*(3), 384–392. http://doi.org/10.1177/0956797610397956

Brady, T. F., & Alvarez, G. A. (2015). Contextual effects in visual working memory

reveal hierarchically structured memory representations. *Journal of Vision*,

15(15), 6. http://doi.org/10.1167/15.15.6

Brady, T. F., & Tenenbaum, J. B. (2013). A probabilistic model of visual working

memory: Incorporating higher order regularities into working memory capacity

estimates. *Psychological Review*, *120*(1), 85–109.

http://doi.org/10.1037/a0030779

Brady, T. F., Konkle, T., & Alvarez, G. A. (2009). Compression in visual working

memory: Using statistical regularities to form more efficient memory

representations. *Journal of Experimental Psychology: General*, *138*(4), 487–502.

http://doi.org/10.1037/a0016797

Chatham, C. H., Frank, M. J., & Badre, D. (2014). Corticostriatal Output Gatingduring

Selection from Working Memory. *Neuron*, *81*(4), 930–942.

http://doi.org/10.1016/j.neuron.2014.01.002

Chen, Z., & Cowan, N. (2005). Chunk Limits and Length Limits in Immediate Recall: A

Reconciliation. *Journal of Experimental Psychology. Learning, Memory, and Cognition*, *31*(6), 1235–1249. http://doi.org/10.1037/0278-7393.31.6.1235

Cohen, M. A., Rhee, J. Y., & Alvarez, G. A. (2016). Limits on perceptual encoding can be predicted from known receptive field properties of human visual cortex. *Journal of Experimental Psychology: Human Perception and Performance*, *42*(1), 67–77. http://doi.org/10.1037/xhp0000108

Collins, A. G. E., & Frank, M. J. (2013). Cognitive control over learning: creating, clustering, and generalizing task-set structure. *Psychological Review*, *120*(1), 190–229. http://doi.org/10.1037/a0030852

Cowan, N. (2001). The magical number 4 in short-term memory: a reconsideration of mental storage capacity. *Behavioral and Brain Sciences*, *24*(1), 87–114– discussion 114–85.

Cowan, N., & Rouder, J. N. (2009). Comment on "Dynamic shifts of limited working memory resources in human vision". *Science*, *323*(5916), 877–author reply 877. http://doi.org/10.1126/science.1166478

Curtis, C. E., & D'Esposito, M. (2003). Persistent activity in the prefrontal cortex during working memory. *Trends in Cognitive Sciences*, *7*(9), 415–423. http://doi.org/10.1016/S1364-6613(03)00197-9

Donkin, Chris, Tran, S. C., & Nosofsky, R. (2013a). Landscaping analyses of the ROC predictions of discrete-slots and signal-detection models of visual working memory. *Attention, Perception & Psychophysics*. http://doi.org/10.3758/s13414-013-0561-7

Donkin, Christopher, Nosofsky, R. M., Gold, J. M., & Shiffrin, R. M. (2013b). Discrete-

slots models of visual working-memory response times. *Psychological Review*,

120(4), 873–902. http://doi.org/10.1037/a0034247

Durstewitz, D., & Seamans, J. K. (2002). The computational role of dopamine D1

receptors in working memory. *Neural Networks : the Official Journal of the*

International Neural Network Society, *15*(4-6), 561–572.

Ester, E. F., Sprague, T. C., & Serences, J. T. (2015). Parietal and Frontal Cortex

Encode Stimulus-Specific Mnemonic Representations during Visual Working

Memory. *Neuron*, *87*(4), 893–905. http://doi.org/10.1016/j.neuron.2015.07.013

Fallon, S. J., Zokaei, N., & Husain, M. (2016). Causes and consequences of limitations

in visual working memory. *Annals of the New York Academy of Sciences*, n/a–n/a.

http://doi.org/10.1111/nyas.12992

Felsen, G., Touryan, J., & Dan, Y. (2005). Contextual modulation of orientation tuning

contributes to efficient processing of natural stimuli. *Network (Bristol, England)*,

16(2-3), 139–149.

Fougnie, D., Cormiea, S. M., Kanabar, A., & Alvarez, G. A. (2016). Strategic Trade-Offs

Between Quantity and Quality in Working Memory. *Journal of Experimental*

Psychology: Human Perception and Performance.

http://doi.org/10.1037/xhp0000211

Fougnie, D., Suchow, J. W., & Alvarez, G. A. (2012). Variability in the quality of visual

working memory. *Nature Communications*, *3*, 1229.

http://doi.org/10.1038/ncomms2237

Franconeri, S. L., Alvarez, G. A., & Cavanagh, P. (2013). Flexible cognitive

resources:competitive content maps for attentionand memory. *Trends in*

Cognitive Sciences, *17*(3), 134–141. http://doi.org/10.1016/j.tics.2013.01.010

Frank, M. J., & Badre, D. (2012). Mechanisms of Hierarchical Reinforcement Learning in Corticostriatal Circuits 1: Computational Analysis. *Cerebral Cortex*, *22*(3), 509–526. http://doi.org/10.1093/cercor/bhr114

Freeman, E., Driver, J., Sagi, D., & Zhaoping, L. (2003). Top-Down Modulation of Lateral Interactions in Early Vision. *Current Biology*, *13*(11), 985–989. http://doi.org/10.1016/S0960-9822(03)00333-6

Freeman, E., Sagi, D., & Driver, J. (2001). Lateral interactions between targets and flankers in low-level vision depend on attention to the flankers. *Nature Neuroscience*, *4*(10), 1032–1036. http://doi.org/10.1038/nn728

Fukuda, K., Vogel, E., Mayr, U., & Awh, E. (2010). Quantity, not quality: the relationship between fluid intelligence and working memory capacity. *Psychonomic Bulletin & Review*, *17*(5), 673–679. http://doi.org/10.3758/17.5.673

Funahashi, S., Bruce, C. J., & Goldman-Rakic, P. S. (1989). Mnemonic coding of visual space in the monkey's dorsolateral prefrontal cortex. *Journal of Neurophysiology*, *61*(2), 331–349.

Furman, M., & Wang, X.-J. (2008). Similarity effect and optimal control of multiple-choice decision making. *Neuron*, *60*(6), 1153–1168. http://doi.org/10.1016/j.neuron.2008.12.003

Fuster, J. M., & Alexander, G. E. (1971). Neuron activity related to short-term memory. *Science*.

Fuster, J. M., & Jervey, J. P. (1981). Inferotemporal neurons distinguish and retain

behaviorally relevant features of visual stimuli. *Science*, *212*(4497), 952–955.

Gold, James M, Hahn, B., Zhang, W. W., Robinson, B. M., Kappenman, E. S., Beck, V. M., & Luck, S. J. (2010). Reduced capacity but spared precision and maintenance of working memory representations in schizophrenia. *Archives of General Psychiatry*, *67*(6), 570–577. http://doi.org/10.1001/archgenpsychiatry.2010.65

Goldman-Rakic, P. S. (1995). Cellular basis of working memory. *Neuron*, *14*(3), 477–485.

Gottlieb, J. (2004). Simultaneous Representation of Saccade Targets and Visual Onsets in Monkey Lateral Intraparietal Area. *Cerebral Cortex*, *15*(8), 1198–1206. http://doi.org/10.1093/cercor/bhi002

Hazy, T. E., Frank, M. J., & O'Reilly, R. C. (2006). Banishing the homunculus: Making working memory work. *Neuroscience*, *139*(1), 105–118. http://doi.org/10.1016/j.neuroscience.2005.04.067

Hubel, D. H., & Wiesel, T. N. (1959). Receptive fields of single neurones in the cat's striate cortex. *The Journal of Physiology*, *148*, 574–591. http://doi.org/10.1113/jphysiol.2009.174151

Hubel, D. H., & Wiesel, T. N. (1965). Receptive fields and functional architecture in two nonstriate visual areas (18 and 19) of the cat. *Journal of Neurophysiology*, *28*, 229–289.

Johnson, J. S., Spencer, J. P., Luck, S. J., & Schöner, G. (2009). A Dynamic Neural Field Model of Visual Working Memory and Change Detection. *Psychological Science*, *20*(5), 568–577. http://doi.org/10.1111/j.1467-9280.2009.02329.x

Kilpatrick, Z. P., Ermentrout, B., & Doiron, B. (2013). Optimizing Working Memory

with Heterogeneity of Recurrent Cortical Excitation. *Journal of Neuroscience*, *33*(48), 18999–19011. http://doi.org/10.1523/JNEUROSCI.1641-13.2013

Kiyonaga, A., & Egner, T. (2016). Center-Surround Inhibition in Working Memory. *Current Biology : CB*, *26*(1), 64–68. http://doi.org/10.1016/j.cub.2015.11.013

Kohonen, T. (1982). Self-organized formation of topologically correct feature maps. *Biological Cybernetics*.

Kriete, T., Noelle, D. C., Cohen, J. D., & O'Reilly, R. C. (2013). Indirection and symbol-like processing in the prefrontal cortex and basal ganglia. *Proceedings of the National Academy of Sciences*, *110*(41), 16390–16395. http://doi.org/10.1073/pnas.1303547110

Lara, A. H., & Wallis, J. D. (2014). Executive control processes underlying multi-item working memory. *Nature Publishing Group*, *17*(6), 876–883. http://doi.org/10.1038/nn.3702

Lara, A. H., & Wallis, J. D. (2015). The Role of Prefrontal Cortex in Working Memory: A Mini Review. *Frontiers in Systems Neuroscience*, *9*, 173. http://doi.org/10.3389/fnsys.2015.00173

Lew, T. F., & Vul, E. (2015). Ensemble clustering in visual working memory biases location memories and reduces the Weber noise of relative positions. *Journal of Vision*, *15*(4), 10. http://doi.org/10.1167/15.4.10

Lowe, M. X., Stevenson, R. A., Wilson, K. E., Ouslis, N. E., Barense, M. D., Cant, J. S., & Ferber, S. (2016). Sensory processing patterns predict the integration of information held in visual working memory. *Journal of Experimental Psychology: Human Perception and Performance*, *42*(2), 294–301.

http://doi.org/10.1037/xhp0000131

Luck, S. J., & Vogel, E. K. (2013). Visual working memory capacity: from psychophysics and neurobiology to individual differences. *Trends in Cognitive Sciences*, *17*(8), 391–400. http://doi.org/10.1016/j.tics.2013.06.006

Luria, R., & Vogel, E. K. (2014). Come Together, Right Now: Dynamic Overwriting of an Object's History through Common Fate. *Journal of Cognitive Neuroscience*, 1–11. http://doi.org/10.1038/nature02447

Ma, W. J., Husain, M., & Bays, P. M. (2014). Changing concepts of working memory. *Nature Neuroscience*, *17*(3), 347–356. http://doi.org/10.1038/nn.3655

Matthey, L., Bays, P. M., & Dayan, P. (2015). A Probabilistic Palimpsest Model of Visual Short-term Memory. *PLoS Computational Biology*, *11*(1), e1004003. http://doi.org/10.1371/journal.pcbi.1004003.s001

Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annual Review of Neuroscience*, *24*, 167–202. http://doi.org/10.1146/annurev.neuro.24.1.167

Miller, G. A. (1956). The magical number seven, plus or minus two: Some limits on our capacity for processing information. *Psychological Review*.

Murray, J. D., Anticevic, A., Gancsos, M., Ichinose, M., Corlett, P. R., Krystal, J. H., & Wang, X. J. (2014). Linking Microcircuit Dysfunction to Cognitive Impairment: Effects of Disinhibition Associated with Schizophrenia in a Cortical Working Memory Model. *Cerebral Cortex*, *24*(4), 859–872. http://doi.org/10.1093/cercor/bhs370

O'Reilly, R. C., & Frank, M. J. (2006). Making working memory work: a computational

model of learning in the prefrontal cortex and basal ganglia. *Neural Computation*, *18*(2), 283–328. http://doi.org/10.1162/089976606775093909

Oberauer, K., & Lin, H.-Y. (2017). An interference model of visual working memory. *Psychological Review*, *124*(1), 21–59. http://doi.org/10.1037/rev0000044

Orhan, A. E., & Jacobs, R. A. (2013). A probabilistic clustering theory of the organization of visual short-term memory. *Psychological Review*, *120*(2), 297–328. http://doi.org/10.1037/a0031541

Orhan, A. E., & Jacobs, R. A. (2014). Are performance limitations in visual short-term memory tasks due to capacity limitations or model mismatch? *arXiv.org*.

Pratte, M. S., Park, Y. E., Rademaker, R. L., & Tong, F. (2017). Accounting for stimulus-specific variation in precision reveals a discrete capacity limit in visual working memory. *Journal of Experimental Psychology: Human Perception and Performance*, *43*(1), 6–17. http://doi.org/10.1037/xhp0000302

Rademaker, R. L., Tredway, C. H., & Tong, F. (2012). Introspective judgments predict the precision and likelihood of successful maintenance of visual working memory. *Journal of Vision*, *12*(13), 21. http://doi.org/10.1167/12.13.21

Rouder, J. N., Morey, R. D., Cowan, N., Zwilling, C. E., Morey, C. C., & Pratte, M. S. (2008). An assessment of fixed-capacity models of visual working memory. *Proceedings of the National Academy of Sciences*, *105*(16), 5975–5979. http://doi.org/10.1073/pnas.0711295105

Sims, C. R., Jacobs, R. A., & Knill, D. C. (2012). An ideal observer analysis of visual working memory. *Psychological Review*, *119*(4), 807–830. http://doi.org/10.1037/a0029856

Somers, D. C., Nelson, S. B., & Sur, M. (1995). An emergent model of orientation

selectivity in cat visual cortical simple cells. *The Journal of Neuroscience : the*

Official Journal of the Society for Neuroscience, *15*(8), 5448–5465.

Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J., & Friston, K. J. (2009).

Bayesian model selection for group studies. *NeuroImage*, *46*(4), 1004–1017.

http://doi.org/10.1016/j.neuroimage.2009.03.025

Störmer, V. S., & Alvarez, G. A. (2014). Feature-Based Attention Elicits Surround

Suppression in Feature Space. *Current Biology*, *24*(17), 1985–1988.

http://doi.org/10.1016/j.cub.2014.07.030

Swan, G., & Wyble, B. (2014). The binding pool: A model of shared neural resources

for distinct items in visual working memory. *Attention, Perception &*

Psychophysics, *76*(7), 2136–2157. http://doi.org/10.3758/s13414-014-0633-3

Swan, G., Collins, J., & Wyble, B. (2016). Memory for a single object has differently

variable precisions for relevant and irrelevant features. *Journal of Vision*, *16*(3),

32. http://doi.org/10.1167/16.3.32

van den Berg, R., Awh, E., & Ma, W. J. (2014). Factorial comparison of working

memory models. *Psychological Review*, *121*(1), 124–149.

http://doi.org/10.1037/a0035234

van den Berg, R., Shin, H., Chou, W.-C., George, R., & Ma, W. J. (2012). Variability in

encoding precision accounts for visual short-term memory limitations.

Proceedings of the National Academy of Sciences, *109*(22), 8780–8785.

http://doi.org/10.1073/pnas.1117465109

Vogel, E. K., McCollough, A. W., & Machizawa, M. G. (2005). Neural measures reveal

individual differences in controlling access to working memory. *Nature*,
438(7067), 500–503. http://doi.org/10.1038/nature04171

Voytek, B., & Knight, R. T. (2010). Prefrontal cortex and basal ganglia contributions
to visual working memory. *Proceedings of the National Academy of Sciences*,
107(42), 18167–18172. http://doi.org/10.1073/pnas.1007277107

Wang, X. J. (1999). Synaptic basis of cortical persistent activity: the importance of
NMDA receptors to working memory. *Journal of Neuroscience*, *19*(21), 9587–
9603.

Warden, M. R., & Miller, E. K. (2007). The Representation of Multiple Objects in
Prefrontal Neuronal Delay Activity. *Cerebral Cortex*, *17*(suppl 1), i41–i50.
http://doi.org/10.1093/cercor/bhm070

Wei, Z., Wang, X.-J., & Wang, D.-H. (2012). From distributed resources to limited
slots in multiple-item working memory: a spiking network model with
normalization. *Journal of Neuroscience*, *32*(33), 11228–11240.
http://doi.org/10.1523/JNEUROSCI.0735-12.2012

Wilken, P., & Ma, W. J. (2004). A detection theory account of change detection.
Journal of Vision, *4*(12), 11–11. http://doi.org/10.1167/4.12.11

Xing, J., & Heeger, D. J. (2001). Measurement and modeling of center-surround
suppression and enhancement. *Vision Research*, *41*(5), 571–583.

Zhang, W., & Luck, S. J. (2008). Discrete fixed-resolution representations in visual
working memory. *Nature*, *453*(7192), 233–235.
http://doi.org/10.1038/nature06860

Zhang, W., & Luck, S. J. (2009). Sudden death and gradual decay in visual working

memory. *Psychological Science*, *20*(4), 423–428. http://doi.org/10.1111/j.1467-

9280.2009.02322.x

Zhang, W., & Luck, S. J. (2011). The number and quality of representations in

working memory. *Psychological Science*, *22*(11), 1434–1441.

http://doi.org/10.1177/0956797611417006

Supplementary Information

Figure S1: Uniformly spaced stimulus configurations degrade task performance and confidence in human subjects. Subject performance was assessed in terms of accuracy (percent of trials eliciting positive feedback) and confidence (percent of trials eliciting high post-decision wagers) separately according to precision condition (23 subjects were required to achieve an error of less than $\pi/3$ to elicit positive feedback [low precision], whereas 24 subjects were required to achieve an error of less than $\pi/8$ to elicit positive feedback [high precision]). **A)** Subjects in the low precision condition were more accurate for random spacing, as opposed to fixed spacing, stimulus configurations (orange; t=5.6, p < 10e-4), whereas subjects in the high precision condition attained similar overall performance in both configurations (blue; t=1.5, p = 0.15). Points/lines indicate group mean/SEM. **B)** Subjects in both conditions indicated higher confidence for random-spacing, as opposed to fixed-spacing, stimulus configurations (t = [2.3, 2.0] and p = [0.03, 0.06] for high and low precision conditions, respectively). **C)** Subjects that were most accurate, as assessed online according to a fixed error threshold, also tended to make higher post-decision wagers. Orange and blue points indicate subjects in low and high precision conditions, respectively. **D)** Furthermore, the improvement in accuracy from fixed- to random-spaced arrays was greater for subjects that showed the largest increase in confidence across the same conditions.

Figure S2: Stimulus clustering and recent feedback impact accuracy and confidence after controlling for other confounded factors in a GLM. Effects of color clustering on performance (left) and confidence (right) persist after accounting for potential confounding factors and feedback-dependent performance adjustments. Coefficients from a mixed-effects logistic regression model of binary accuracy and wager are plotted on the abscissa. Circles/lines reflect mean/SEM, and X marks indicate coefficients significantly different from zero ($p < 0.05$). Coefficients for log(WCV), a proxy for stimulus clustering, are highlighted in orange. Coefficients for log(WCV) are significantly lower than

zero, indicating better performance / higher wagering on trials where stimulus colors were more
clustered. This effect is not present in accuracy data simulated from a mixture model that includes
binding errors (center).

Figure S3: Recall is affected by clustering of both probed and non-probed stimuli. To further
examine the source of the recall benefits, subject data were fit with a mixture model that considered
reports to come from a mixture of processes including 1) a uniform "guess" distribution, 2) a
"memory+binding" distribution centered on the color of the probed target, and 3) a "binding error"
distribution including peaks at each non-probed target. Additional terms were included in the model
to allow the recall probability to vary as a logistic function of various descriptive aspects of stimulus
clustering that all factor into the within-cluster variance measurements reported in figure 5. To do
so, the color array from each trial was divided into two (minimal variance) clusters to compute 1) the
variance of the cluster that did not contain the probed item [OCV], 2) the variance of the cluster that
did contain the probed item [ICV], and the number of colors in the cluster that contained the probed
target [CS]. **A)** Mean/SEM coefficients across subjects indicated that these three factors, along with
their interactions, were systematically related to trial-to-trial fluctuations in subject recall rates.
B&C) The predicted recall rates from model fits are plotted as a function of ICV (B) and OCV (C) color
coded according to the number of items in the relevant cluster (the cluster containing the probed
item for B, and the cluster that did not contain the probed item for C). Recall bonuses are evident for
low values of both ICV and OCV, although these benefits scale with the number of colors contained in
the relevant cluster.

Figure S4: Sorting trials according to the nearest neighbor non-probed target color reveals structure in memory reports. A&B: Signed error of memory reports (red points) for all trials completed by two sample subjects (left = subject 1, right = subject 31). Trial errors are sorted by the distance from the probed target to the most similar color in the target array (nearest neighbor distance, NND) and transformed according to the direction of the nearest neighbor target (blue points). Green points reflect the positions of other colors in the target array, relative to the probed color and transformed as described above. Note the asymmetry in error distributions appears to change as a function of the nearest neighbor distance. C&D: Error histograms for the same two example subjects, transformed as described above. Note that in some cases apparent structure in the sorted errors (A) is no longer visible after collapsing across nearest neighbor distances (C).

1
2
Figure S5: Neighboring stimulus features affect fits of mixture model. Subject (left) and
simulated (center = center-surround, right = independent encoding) data were collapsed across all
sessions and binned in sliding windows according to the absolute distance between the probed
target color and the most similar non-probed target color (NN dist; abscissa). Data in each bin were
fit with a mixture model that included free parameters to estimate the proportion of reports
generated from 1) the von Mises "memory distribution" (**A-C**), 2) the uniform "guess distribution"
(**D-F**), or 3)the mixture of von Mises "binding error distribution" (**G-I**). Parameter estimates for
precision and bias terms are reported in the main text (figure 8).
11
12
13
14

95