Stochastic satisficing account of confidence in uncertain value-based decisions

Uri Hertz [1,2]*, Bahador Bahrami[3], Mehdi Keramati[4,5]

[1] Information Systems Department, University of Haifa, Haifa, Israel

[2] School of Political Sciences, University of Haifa, Haifa, Israel

[3] Institute of Cognitive Neuroscience, University College London

[4] The Gatsby Computational Neuroscience Unit, University College London

[5] Max Planck Centre for Computational Psychiatry and Ageing Research, University College London

* Corresponding Author

Email: uhertz@is.haifa.ac.il (UH)

Abstract

Every day we make choices under uncertainty; choosing what route to work or which queue in a supermarket to take, for example. It is unclear how outcome variance, e.g. uncertainty about waiting time in a queue, affects decisions and confidence when outcome is stochastic and continuous. How does one evaluate and choose between an option with unreliable but high expected reward, and an option with more certain but lower expected reward? Here we used an experimental design where two choices' payoffs took continuous values, to examine the effect of outcome variance on decisions and confidence. We found that our participants' probability of choosing the good (high expected reward) option decreased when both good and bad options' payoffs were more variable. Their confidence ratings were affected by outcome variability, but only when choosing the good option. Inspired by the satisficing heuristic, we propose a "stochastic satisficing" (SSAT) model for choosing between options with continuous uncertain outcomes. In this model, options are evaluated by their probability of exceeding an acceptability threshold, and confidence reports scale with the chosen option's thus-defined satisficing probability. Participants' decisions were best explained by an expected reward model, while the SSAT model provided the best prediction of decision confidence. We further tested and verified predictions of this model in a second experiment. Our model and experimental results generalize the models of metacognition from perceptual detection tasks to continuous-value based decisions. Finally, we discuss how the stochastic satisficing account of decision confidence serves psychological and social purposes associated with the evaluation, communication and justification of decision-making.

Author Summary

Every day we make several choices under uncertainty, such as choosing a queue in a supermarket. However, the computational mechanisms underlying such decisions remain unknown. For example, how does one choose between an option with unreliable high expected reward, such as the volatile express queue, and an option with more certain but lower expected reward in the standard queue? Inspired by bounded rationality and the notion of 'satisficing', i.e. settling for a good enough option, we propose that such decisions are made by comparing the likelihood of different actions surpassing an acceptability threshold. When facing uncertain decisions, our participants' confidence ratings were not consistent with the expected outcome's rewards, but instead followed the satisficing heuristic proposed here. Using an acceptability threshold may be especially useful when evaluating and justifying decisions under uncertainty.

Introduction

Every morning most people have to pick a route to work. While the shortest route may be consistently busy, others may be more variable, changing from day to day. The choice of which route to take impacts the commuting time and is ridden with uncertainty. Decision making under uncertainty has been studied extensively using scenarios with uncertain rewards [1–3]. In such scenarios, participants choose between multiple lotteries where each lottery can lead to one of the two (or several) consequences with different probabilities. Standard models like expected utility theory [4] and prospect theory [5] suggest parsimonious formulations for how the statistics of such binomial (or multinomial) distributions of outcomes determine the value (otherwise known as utility) of a lottery. These models, for example, explain the fact that in certain ranges people prefer a small certain reward to bigger more uncertain ones [6,7].

However, the commuting problem described here highlights the pervasive but much less studied relevance of outcome variance to decisions with continuous (rather than binary) outcomes. It is not straightforward how one's choice and evaluation of the route could be decided using the heuristics applicable to binary win/lose outcomes.

Early studies of bounded rationality [8–10] introduced the concept of satisficing according to which, individuals replace the computationally expensive question of "which is my best choice?" with the simpler and most-of-the-times adequately beneficial question "which option is good enough?". More precisely, instead of finding the best solution, decision makers settle for an option that satisfices an acceptability threshold [8]. In the case of commuting, such acceptability threshold could be "the latest time one affords to arrive at work". Here we generalize the satisficing theory to decision-making under uncertainty. Our

"stochastic satisficing" model suggests that when outcomes are uncertain, one could evaluate -with reasonably simple and general assumptions about the probability distributions of outcomes- the available options' *probability* of exceeding an acceptability threshold [11]. Our commuter's stochastic satisficing heuristic could then be expressed as "which route is *more likely* to get me to work before X o'clock?"

The effect of uncertainty on confidence report is commonly studied in perceptual detection tasks where one has to detect a world state from noisy stimuli (e.g. dots moving to the left or right) [12–16]. Sanders and colleagues (2016) argued that confidence reports in perceptual decisions relates to the Bayesian formulation of confidence used in hypothesis testing. In this view, subjective confidence conveys the posterior probability that an uncertain choice is correct, given the agent's prior knowledge and noisy input information. Following this scheme and generalizing it to value-based contexts, our probabilistic satisficing heuristic is naturally fit to account for the computational underpinnings of choice confidence and draws strong predictions about how confidence would vary with outcome variance. In fact, if choices were made by the probabilistic satisficing heuristic described above, confidence in those choices would be directly proportional to the probability that the chosen option exceeded the acceptability threshold. A choice whose probability of exceeding the acceptability threshold is higher should be made more confidently than another that barely passes the criterion, even if they have equal expected values.

Here we asked if, and how, human decision makers learn and factor outcome variance in their evaluation of choices between options with independent continuous returns. We hypothesised that decision makers use a stochastic satisficing heuristic to evaluate their choices and that their confidence conveys the estimated probability of the chosen option's

value to exceed the satisficing criterion. In two experiments, we used a two-armed bandit task in which the expected values and variances associated with outcomes of each arm were systematically manipulated. We tested the stochastic satisficing model against expected reward model [17] and an expected utility model [18] that propose alternative ways of computing choice and confidence as a function of the estimated statistics of options' returns.

Results

Participants performed a two-armed bandit task online where rewards were hidden behind two doors (Fig. 1A) and the reward magnitudes followed different probability distributions (Fig. 1B). On each trial, the participant decided which door to open, and expressed their choice confidence using a combined choice-confidence scale. Choosing the left side of the scale indicated choice of the left door and distance from the midline (ranged between 1: uncertain, to 6: certain) indicated the choice confidence. After the decision, the reward behind the chosen door was revealed and a new trial started. Each experimental condition was devised for a whole block of consecutive trials during which the parameters (mean and variance) governing the reward distribution for each door were held constant. Each block lasted between 27 and 35 trials. Transition from one block to the next happened seamlessly and participants were not informed about the onset of a new block.

Figure 1: Design and results of experiment 1. (A) On each trial participants had to choose between two doors, using a confidence scale. The choice is determined by the side of the scale used by the participant. Upon decision, the chosen door is opened and the reward is revealed. (B) Four different experimental conditions embedded in a continuous two-armed bandit task. In each condition, one door had a low expected reward (Bad option) and the other had a high expected reward (Good option). Expected rewards reward (m_B and m_G)

were constant across conditions. The variances of the two distributions, however, changed across conditions and was either high or low, resulting in a 2x2 design (V_B (Low/High) x V_G (Low/High)). Each condition lasted between 27 to 35 consecutive trials. (C) Stochastic satisficing model suggests that decisions are made based on the probability of each door's outcome exceeding an acceptability threshold (grey dot-dashed line). This probability (area under the curve) is higher for the door with the high mean expected reward (top) than for the door with the low mean (bottom). (D) The frequency of choosing the good option (averaged over 65 participants) in each experimental condition, averaged across trials 10 to 25. (E) Confidence reports (65 subjects) when choosing the good (middle panel) or bad (right panel) option. Reports were averaged between trials 10 to 25 of each experimental block. When choosing the good option, confidence ratings were higher when variance of the good option was low, regardless of the variance of the bad option. Confidence reports were not significantly different across conditions when choosing the bad option. Error bars represent SEM (* $p<0.05$, *** $p<0.0005$)

Experiment 1

Within each condition, the reward behind one door was drawn from a distribution with a higher mean (65, i.e. the "good" option) than the other door (35, i.e. the "bad" option). The variances of the bad and good options could independently be high (H=625) or low (L=100), resulting in a 2x2 design comprising four experimental conditions: 'H-H', 'L-H', 'H-L' and 'L-L' (Fig. 1B). In this notation, the first and the second letters indicate the variances of the bad (low expected value) and good (high expected value) options, respectively. Participants' trial-by-trial probability of choosing the good option, in each condition, started at chance level and increased until it reached a stable level after about 10 trials. To assess the asymptotic level of performance, within each participant, we averaged the probability of choosing the good option between trials 10 to 25 in each experimental condition. Probability of choosing the good option was highest in the 'L-L' and lowest during the 'H-H'

condition (Fig. 1D). A repeated measure ANOVA test with the variances of the good and bad options as within-subject factors was used to evaluate this pattern. The effects of both variance factors were significant (variance of good option: $F(1,194)=22.24$, $p=0.00001$, variance of bad option: $F(1,194)=5.2$, $p=0.026$). This result indicated an asymmetric effect of outcomes' payoff variances on choice: increased variance of the good option reduced the probability of choosing the good option, whereas increased variance of the bad option increased the probability of choosing the bad option. This variance-dependent choice pattern demonstrates that decision-making depended not only on the expected rewards, but also on their variances.

To examine the pattern of confidence reports, we calculated the average confidence reported on trials 10 to 25 in each condition (Fig. 1E). Using a repeated measures ANOVA we found that the main effect of the good, but not the bad, option's variance was significant when choosing the good option (good option variance: $F(1,194)=33.32$, $p<0.00001$, bad option variance: $F(1, 194)=0.02$, $p=0.89$). When choosing the bad option, confidence ratings were generally lower (paired t-test $t(64)=8.3$, $p=9e-12$) and were not significantly different across experimental conditions. Therefore, variance affected confidence reports, but only when choosing the good option.

Fitting models to choice

To examine the use of a probabilistic satisficing heuristic and acceptability threshold in decisions under uncertainty we devised a set of models which employ these heuristics (See Methods). We started with a classical expected reward model ('Reward' model, hereafter) that tracks the expected value of the reward from each door on every time-step [19,17]. Choice is then made according to the expected reward of each option [4]. We also tested an

expected utility model ('Utility' model) which penalized options for their payoff's variance [4,18].

We also added two further models 'Reward–T' and 'Utility-T' to our set of competing models by formalizing the use of acceptability threshold and adding a free parameter 'threshold' to the 'Reward' and 'Utility' models. In these models, on each trial, the unchosen option drifted towards the value of this parameter. This 'threshold' therefore represented the participant's expectations of outcome in the game. When this threshold was very high, the participant would assume that the unchosen option drifted toward this high threshold, making him likely to switch options often. A participant with a low threshold, however, might stick to an option even if it yielded low reward, as he would assume that the unchosen option drifted towards an even lower threshold.

We formalized the probabilistic satisficing heuristic in a stochastic satisficing ('SSAT') model in which the mean and variance of rewards obtained by each of the two doors are tracked in a trial-by-trial manner (see Methods). In this model, decision is made by comparing the probability of each option yielding a reward above an acceptability threshold, i.e. being good enough. In fact, given the estimated probability distribution over the rewarding outcome of a choice, the model computes the total mass under this distribution that is above the acceptability threshold (Fig. 1C). This cumulative quantity is then used to determine the probability of choosing that option. Such mechanism can capture the asymmetric effect of payoff variance on choice, as the good option (i.e. higher than threshold) becomes less likely to exceed the acceptability threshold as its variance increases, while the bad option (below threshold) becomes more likely to exceed the threshold as its variance increases. Upon making the choice and receiving reward feedback

from the environment, the model updates the distribution over the value of the chosen action. We also examined a drift version of the SSAT model in which the value of the unchosen action drifts toward the acceptability threshold ('SSAT-T'), similar to the drifting mechanism described above for 'Reward-T' and 'Utility-T' models.

We fitted all models to all the choices made by participants (240 trials per participant) using Monte-Carlo-Markov-Chain (MCMC) procedure [20]. After correction for the number of parameters using Watanabe-Akaike information criterion (WAIC) [21], we compared posterior likelihood estimates obtained for each participant, for each model (Table 1). The models using drifting thresholds all performed better (lower WAIC score) than those not using it, and the 'Reward-T' model gave the best fit to the choice data.

Examining the individual parameters fitted by the models we observed a high correspondence between the 'Reward-T' and 'SSAT-T' models for both the parameters estimated for acceptability threshold and the parameters estimated for learning rate (Table 2). This correspondence was captured by high correlation between the individual threshold parameters (R^2=0.89) and learning-rate parameters (R^2=0.86) (Figure S1). Such similarity was not found between the 'SSAT-T' and 'Utility-T' models for threshold parameters (R^2=0.38) nor learning-rate parameters (R^2=0.6).

Table 1: Models performance in Experiment 1

Model	Sum WAIC	Mean ± STD WAIC	Mean ± STD Confidence R^2
Reward	14,273	226.55 ± 67.67	0.21 ± 0.22
Utility	14,320	227.29 ± 67.48	0.18 ± 0.18
SSAT	14,047	222.96 ± 67.96	0.21 ± 0.22

Reward-T	**13,518**	214.57 ± 68.79	0.21 ± 0.21
Utility-T	13,813	219.25 ± 64.38	0.17 ± 0.16
SSAT-T	13,695	217.38 ± 67.61	**0.24 ± 0.21**

Table 2: Estimated Models' Parameters for Experiment 1 (Mean ± STD)

Model	Beta	Learning Rate	Acceptability Threshold	Variance Learning Rate	Risk Aversion
Reward	6.84 ± 3.67	0.61 ± 0.21			
Utility	0.71 ± 0.38	0.55 ± 0.23		0.36 ± 0.15	0.91 ± 1.06
SSAT	5.65 ± 3.46	0.64 ± 0.21	0.52 ± 0.13	0.32 ± 0.21	
Reward-T	8.48 ± 3.88	0.56 ± 0.19	0.33 ± 0.13		
Utility-T	0.86 ± 0.45	0.49 ± 0.20	0.41 ± 0.17	0.39 ± 0.13	0.66 ± 0.63
SSAT-T	5.34 ± 2.37	0.58 ± 0.18	0.35 ± 0.13	0.31 ± 0.15	

Model predictions for confidence ratings

We hypothesize that confidence in choice reflects the subjective probability that the value of the chosen option exceeded the acceptability threshold (i.e., the total mass under the value distribution of the chosen option that is more than the acceptability threshold). To test this hypothesis, we compared the predictions of our model for confidence to the empirical confidence reports. We compared the three models that used the acceptability

threshold drift parameter, 'Reward-T', 'SSAT-T' and 'Utility-T', as the addition of this parameter increased models' explanatory power of the choice behaviour. With the free parameters fitted to trial-by-trial choice data for each individual participant, we simulated the models to draw predictions for the confidence reports for the corresponding individual. Following previous studies that examined confidence in value-based decisions [22,23], we defined confidence, for the 'Reward-T' and 'Utility-T' models, as proportional to the estimated decision variable: means of rewards for 'Reward-T' model and expected utilities of options for the 'Utility-T' model. We focused on trials 10-25 of each experimental condition and regressed the models' predictions for these trials from the confidence reports made in these trials by each participant, in order to obtain the individual goodness of fit for each model (R^2) (left column of Table T1, higher is better). We found that the model which gave the best predictions for trial-by-trial confidence reports was the 'SSAT-T' model, which formalized confidence reports as the probability of exceeding an acceptability threshold.

To examine the pattern of confidence reports generated by each model, we calculated the average confidence for each model's simulation when choosing the good option and when choosing the bad option in each condition. All models predicted lower confidence when choosing the bad, as compared to the good, option (Fig. 2), similar to the observed confidence reports. Additionally, all models predicted similar confidence levels across conditions when the bad option was chosen. When choosing the good option, however, the SSAT-T model's predictions were the most consistent with the reports made by participants. Only the SSAT-T model predicted higher confidence when variance of the good option was low (i.e. 'L-L','H-L'). The other models did not predict a variance effect on confidence.

Figure 2: Model predictions for confidence reports in experiment 1 (A) Models' predictions for confidence reports when choosing the good option. Predictions were averaged between trials 10-25 in each block. The average reports made by participants is displayed in grey. SSAT-T model gave the best predictions of confidence reports. (B) models' predictions of confidence reports when choosing the bad option, averaged between trials 10-25 in each block. Error bars represent SEM.

Our model-comparison approach showed that the use of acceptability threshold parameter helped explaining participants' choice behaviour, which was best captured by the 'Reward-T' model. Confidence, on the other hand, followed most closely the 'SSAT-T' model prediction of reporting probability of exceeding the acceptability threshold. A counterintuitive prediction of the model borne out by the behavioural data was the difference between the two conditions involving unequal variances (i.e. L-H and H-L conditions). Stochastic satisficing predicted –and the data confirmed– a difference in confidence (c.f. Fig 2B-C, compare L-H and H-L) despite identical expected values for the chosen (good) option in these two conditions. In Experiment 2, we focused on the choice

between options with unequal variances to further tease apart the cognitive substrates of stochastic satisficing.

Experiment 2

To conduct a more rigorous test of the parsimony and plausibility of the stochastic satisficing heuristic, in Experiment 2, we designed a new payoff structure for the two-arm bandit, focusing on options with unequal variances in all conditions (Fig. 3A). We kept the mean and variance of the bad option constant across conditions (mean=35 and variance=100) while varying the mean and variance of the better option in a 2x2 design. Mean reward of the good option could be low (mL=57; still better than the bad option) or high (mH=72), and its variance could be independently low (vL=5^2=25) or high (vH=20^2=400). Thus, we constructed four experimental conditions all involving options with unequal variances and large or small differences in their expected values.

Figure 3: Experiment 2 design and behavioural results (A) In experiment 2 the rewards' mean and variance of the bad option (black lines) were kept constant across experimental conditions, while the mean and variance of the good option varied. Mean values could be high (mH) or low (mL), and variances could be independently high (vH) or low (vL), resulting in four experimental conditions. (B) Experimental results (33 subjects). Both choices and confidence reports were averaged between trials 10 to 25 of each experimental block. Frequency\ of choosing the good option gradually increased as the mean expected reward increased, and as the variance

decreased. (C) When choosing the good option (middle panel), confidence ratings did not differ between the 'mL-vL' and 'mH-vH' condition. When choosing the bad option (right panel) confidence reports were not significantly different between conditions. Error bars represent SEM. (* p<0.05, *** p<0.0005).

We examined participants' choices and confidence reports in experiment 2 in a new group of subjects (N=33) and compared them to the predictions made by the models. The probability of choosing the good option increased with the mean reward of the good option (repeated measures ANOVA, $F_{(1,89)}=21.25$, p=0.0001) and decreased with its variance ($F_{(1,89)}=15.03$, p=0.0005) (Fig. 3B). Confidence when choosing the bad option did not change significantly across conditions (Fig. 3C). When choosing the good option, confidence was significantly affected by variance ($F_{(1,89)}=35$, p<0.00001) and mean ($F_{(1,89)}=88$, p<0.00001) of the good option's rewards. However, while confidence in the 'mH-vL' was significantly higher than all other conditions ('mH-vL' vs 'mH-vH': $t_{(30)}=4$, p=0.0003), and confidence in the 'mL-vH' was lower than all other conditions ('mL-vH' vs. 'mL-vL': $t_{(30)}=4.9$, p=0.00002), the critical comparison of 'mL-vL' and 'mH-vH' did not show a difference ('mL-vL' vs. 'mH-vH': $t_{(30)}=0.4$, p=0.68).

Model-fitting and Predictions

We fitted all models to the choices made by participants in Experiment 2. Like in Experiment 1, adding the acceptability threshold parameter helped explaining participants' choice behaviour in all models (Table 3). We found again that the best description of the data was given by the 'Reward-T' model. When examining the relationship between individual parameters fitted by the models, we found again a high correspondence between the parameters estimated for Acceptability Threshold and Learning Rates between the 'Reward-T' and 'SSAT-T' model (Table 4), captured by high correlation between the individual

threshold parameters (R^2=0.9) and learning rate parameters (R^2=0.82) (Figure S2). Such similarity was not found between the 'SSAT-T' and 'Utility-T' models for neither threshold parameters (R^2=0.15) nor learning rate parameters (R^2=0.34).

Experiment 2 was explicitly designed to test the models' predictions of choice confidence. We examined whether the models estimated trial-by-trial decision variables (means of rewards for 'Reward-T' model, expected utility for the 'Utility-T' model, and probability of exceeding acceptability threshold for the 'SSAT-T' model). Just like in Experiment 1, we focused on trials 10-25 of each experimental condition, and regressed the models' predictions from these trials from the confidence reports made in these trials for each participant, to obtain the individual goodness of fit for each model (R^2) (right column of Table 3, higher is better). We found that the model which gave the best predictions of trial-by-trial confidence reports in Experiment 2 was the 'SSAT-T' model.

Table 3: Models performance in Experiment 2

Model	Sum WAIC	Mean ± STD WAIC	Mean ± STD Confidence R^2
Reward	3,971	128.09 ± 43.39	0.18 ± 0.15
Utility	3,803	122.69 ± 35.86	0.34 ± 0.19
SSAT	3,957	127.66 ± 44.48	0.21 ± 0.18
Reward-T	**3,629**	117.09 ± 33.31	0.35 ± 0.15
Utility-T	3,770	121.62 ± 35.46	0.31 ± 0.13
SSAT-T	3,703	119.48 ± 33.62	**0.41 ± 0.18**

Table 4: Estimated Models' Parameters for Experiment 2 (Mean ± STD)

Model	Beta	Learning Rate	Acceptability Threshold	Variance Learning Rate	Risk Aversion
Reward	9.20 ± 3.73	0.56 ± 0.20			
Utility	1.05 ± 0.52	0.54 ± 0.19		0.31 ± 0.13	1.00 ± 0.95
SSAT	5.22 ± 2.9	0.61 ± 0.21	0.51 ± 0.79	0.42 ± 0.15	
Reward-T	12.17 ± 3.72	0.54 ± 0.17	0.38 ± 0.11		
Utility-T	1.76 ± 1.4	0.43 ± 0.17	0.51 ± 0.15	0.36 ± 0.15	0.69 ± 0.59
SSAT-T	6.54 ± 2.25	0.51 ± 0.17	0.41 ± 0.09	0.33 ± 0.21	

To demonstrate the pattern of confidence reports generated by each model, we calculated the average confidence for each model's simulation when choosing the good and the bad options in each condition. The most striking qualitative difference between the models was in their predictions of confidence reports when choosing the good option. All models predicted the lowest confidence for choosing the good option with low mean and high variance ('mL-vH') (Fig. 4). Highest confidence was predicted when choosing the good option with high mean and low variance ('mH-vL') by all models. However, 'SSAT-T' model was the only one following the pattern observed in the participants' reported confidence, predicting similar confidence ratings for the low mean, low variance ('mL-vL') and the high mean, high variance ('mH-vH') conditions, as the probability of exceeding the satisficing threshold was the same for these two conditions. Critically, because these two conditions

have different expected rewards, the 'Reward-T' model predicted different confidence levels for these two conditions. Even though 'Utility-T' model penalized options' values according to their variance, it failed to recover the behavioural pattern and predicted lower confidence reports in the 'mL-vL', compared to the 'mH-vH', condition.

Figure 4: Model predictions for confidence reports in experiment 2. (A) Models' predictions for confidence reports when choosing the good option. Predictions were averaged between trials 10-25 in each block. The average reports made by participants is displayed in grey. SSAT-T model gave the best prediction of confidence reports. (B) models' predictions of confidence reports when choosing the bad option, averaged between trials 10-25 in each block. Error bars represent SEM.

Discussion

We set out to examine decision-making and confidence reports in uncertain value-based choices. In a two-armed bandit task played by human subjects, the probability of choosing the good option increased as the variance of either options' outcomes decreased. However,

confidence ratings were associated with variance only when choosing the good (higher mean) option, as items with low variance outcomes were chosen with higher decision confidence. Confidence ratings associated with choosing the bad (i.e. lower mean) option were always low and were independent of the variances of the options' outcomes. We examined how bounded rationality heuristics may account for this pattern of behaviour, first by introducing an acceptability threshold representing an expectation about the outcomes' values, and by proposing a stochastic satisficing model in which decisions are made by comparing the options' probability of exceeding this acceptability threshold. We found that choice behaviour could be accounted for by adding the threshold parameter to a simple TD learning mechanism which tracks the expected reward of each option [19,17]. Confidence reports, however, were best captured by the stochastic satisficing model, as confidence reports scaled with the chosen option's satisficing probability. To directly test a critical prediction of this model, a second experiment involving options with unequal variances and means was simulated first and then empirically performed. As predicted by the 'SSAT-T' model, participants' confidence reports matched the options' probability of exceeding a threshold, and not the options' expected outcome.

In our experiments, models based on utility theory [4,18], aimed at modelling the impact of risk aversion on options' values, were not successful at explaining participants choices or confidence reports. Following utility theory prescription, rewards were transformed using a concave utility function. When applied to continuous outcomes with Gaussian distribution, maximizing expected utility boiled down to penalizing outcomes according to their variance (see Methods). An important feature of this instantiation of risk aversion is that the effect of variance is always in the same direction, reducing the value or utility of both good and bad options. This means that when the variance of the bad option increases, the likelihood of

choosing the good option should increase. This was not the case in our experimental results. Our stochastic satisficing model provides a mechanism by which variance effect is not symmetrical for good and bad option – when the bad option's variance increases, its value (i.e. the probability of surpassing an acceptability threshold) increases.

Our results suggest a divergence between choice and confidence reports. Choices were best explained by the 'Reward-T' model, which does not track outcome's variance, while confidence reports were best explained by the 'SSAT-T' model and were affected by the outcomes' variance. Such separation of actions and evaluation of actions is in line with the second-order framework for self-evaluation of decision performance [16]. In the second-order model suggested by Fleming and Daw, action and confidence stem from parallel processes. Sensory input is assumed to be sampled independently by the action and evaluation processes. In this framework, confidence is first affected by its independent sample, and then by the action chosen by the action process. Our results are in line with such parallel processing. Actions were accounted for by a parallel and correlated process to the confidence generating process, and confidence was conditional on the action selected by the client.

The second-order model [16] and other recent studies [12,15,24,25] have formulized confidence as the probability of having made a correct choice over tracked outcome or evidence distribution. This approach builds on the line of research about the representation of evidence distribution, and suggests that confidence summarizes this probabilistic representation, estimating the probability of being correct. Probability of being correct is more readily defined in perceptual detection tasks where option outcomes are not independent (e.g. the target can be in only one of two locations but not both) and there is

an objective criterion for correctness. When the two options have continuous outcome and are governed by independent distributions, confidence was shown to reflect the difference in values between the two choice items [22,26]. However, in these studies, items' values were predefined, and importantly had no uncertainty associated with them. Our stochastic satisficing model combines these two approaches, expanding observations from value-based decisions to scenarios where outcomes are stochastic. In such scenarios, our theory-based analysis of data suggests, participants use an arbitrary criterion, the acceptability threshold, to evaluate the probability of an outcome to exceed the threshold, analogous to the evaluation of correctness probability in detection tasks. Confidence would then reflect the probability that the chosen option exceeded the "good enough" acceptability threshold. As the likelihood of exceeding the acceptability threshold increases – either by reducing the outcome variance (Experiment 1) or increasing the outcome mean (Experiment 2) – so does decision confidence.

Research in administrative decision making suggests that when faced with elaborate and complex environments, where finding the optimal solution to a problem can prove to be very costly in terms of time, money and cognitive resources, people employ heuristics when making decisions [1,8,11]. In the 1950s Simon introduced the concept of satisficing, by which decision makers settle for an option that satisfies some threshold or criterion instead of finding the optimal solution. The idea is illustrated in the contrast between 'looking for the sharpest needle in the haystack' (optimizing) and 'looking for a needle sharp enough to sew with' (satisficing) (p. 244) [11,27]. This notion of acceptability threshold has been extended to other ambiguous situations [28], for example for setting a limit (i.e. threshold) to the time and resources an organization invests in learning a new capability [11], where suboptimal solution may be balanced with preventing unnecessary cost.

We suggest that our stochastic satisficing serves a similar objective by extending the basic idea of satisficing into stochastic contexts with continuous payoff domains. We found stochastic satisficing to be particularly useful at explaining decisions' confidence, i.e. evaluation of decisions. Bounded rationality was originally developed to explain administrative decision making [10], in which decisions are often evaluated explicitly, and the decision maker is held accountable for the outcome [29]. Stochastic satisficing may therefore serve psychological and social purposes associated with the evaluation, communication and justification of decision-making [30,31]. As it strives to avoid catastrophe, i.e. receiving a reward below acceptability threshold, stochastic satisficing may be useful to minimize regret, similarly to status quo bias [32,33]. Choosing the option less likely to provide unacceptable payoffs can serve as a safe argument for justifying decisions to oneself or others [29], in the spirit of the saying "nobody ever got fired for buying IBM".

Methods

Participants

We recruited participants through Amazon M-Turk online platform [34]. All participants provided an informed consent. Experiments were approved by the local ethics committee. Participants earned a fixed monetary compensation, but also a performance-based bonus if they collected more than 10,000 points. 88 participants were recruited for the first experiment, in order to obtain power of 0.8 with expected effect size of 0.4 for variance effect on confidence. The actual effect size obtained in Experiment 1 was 0.6, and we therefore recruited 33 subjects for the second experiment. 25 participants were excluded from analysis as their performance was at chance level (16 participants) or for using only

one level for confidence reports (9 participants). Data from 96 participants (62 males aged 32±9 (mean±std), and 34 females aged 32±8) were analysed.

Experimental Procedure and Design

On each trial participants chose between two doors, each leading to a reward between 1 and 100 points (Fig. 1A). Each door had a fixed colour-pattern along the task, but the positions (left vs. right) were chosen randomly. Subjects made choices by using a 12-level confidence scale: 1-6 towards one option and 1-6 towards the other, with 6 indicating 'most certain' and 1 indicating 'most uncertain'. Following choice, subjects observed the reward of the chosen door drawn from a normal distribution $N(m_i, S_i^2)$, where i was a or b, indicating one or the other door.

Experiment 1 consisted of 240 trials and included six stable blocks where the mean and variance of each option's reward remained constant. Each block lasted at least 25 trials. The transition from one block to another occurred along 10 trials during which the mean and variance associated with each door changed gradually in a linear fashion, from their current to the new levels corresponding to the upcoming block. Embedded within these six blocks, four blocks followed a 2x2 design where the mean rewards of the two options were 65 (for the good option) and 35 (for the bad option), and their variances could be independently high (H=25^2=625) or low (L=10^2=100) (Fig. 1B). This design creates four conditions: 'L-L','H-L','L-H' and 'H-H', where the first and the second letters indicated the magnitude of the variance of the good and the bad options, respectively.

Experiment 2 consisted of 160 trials and was similarly composed of blocks of fixed reward probability distributions. In all four blocks, the reward of one option always followed a Gaussian distribution with a mean of 35 and a variance of 100 (10^2). The mean of the other

option could take either high (mH=72) or low (mL=57), and its variance could be either high

(vH $=20^2=400$) or low (vL=5^2=25). This produced a 2x2 design, with the four conditions

denoted by 'mL-vL', 'mL-vH', 'mH-vH', 'mL-vL'(Fig. 3A).

Models

Six different models were fitted to the participants' choices. These included models that

track only mean of the rewards from each option, and models that track both mean and

variance.

The 'Reward' model assumes that expected reward of the outcomes govern choices, and it

tracks the means of the rewards using a temporal difference algorithm [19,17].

[1]
$$\begin{cases} Q_a(t+1) = Q_a(t) + a\left(R(t) - Q_a(t)\right) \\ Q_b(t+1) = Q_b(t) \end{cases}$$

Where a and b indicate the chosen and the un-chosen options, respectively. α is the learning

rate. A softmax action-selection rule was used:

[2] $$p(a) = \frac{\exp\left(\beta \cdot Q_a(t)\right)}{\exp\left(\beta \cdot Q_a(t)\right) + \exp\left(\beta \cdot Q_b(t)\right)}$$

Where β is the rate of exploration. Therefore, the 'Reward' model has 2 free parameters: *{α,*

β}.

The 'Utility' model tracks both mean and variance of rewards from the two options. Tracking

the mean of rewards is done in a similar manner to the 'Reward' model (Eq. [1]). Tracking of

variance is done using a similar temporal difference rule:

[3]
$$\begin{cases} V_a(t+1) = V_a(t) + \gamma \cdot \left(\left(R(t) - Q_a(t)\right)^2 - V_a(t)\right) \\ V_b(t+1) = V_b(t) \end{cases}$$

Where γ is the variance learning rate. This model assumes an increasing and concave utility function by which the utility of a reward decreases as the reward increases:

[4] $\quad U(R) = -e^{-\lambda R} \quad \lambda > 0$

λ denotes the risk sensitivity of the participant, the larger λ is, the more risk averse the participant is. When rewards are governed by a Gaussian distribution is it possible to evaluate the expected utility of an option analytically [18].

[5] $\quad EU_a(t) = \dfrac{1}{\sqrt{2\pi V_a(t)}} \displaystyle\int_{-\infty}^{\infty} -e^{\lambda x} e^{-\frac{(x - Q_a(t))}{2V_a(t)}} \, dx$

Using the tracked variance and mean of the rewards, the value to maximize (for option a, for example) is:

[6] $\quad EU_a(t) \propto Q_a(t) - \dfrac{\lambda V_a(t)}{2}$

According to this model choices' expected utility depends on the expected reward, and penalized by the variance of rewards. Again, softmax rule (Eq. [2]) was used for action selection with the expected utilities as the values associated with each option. The 'Utility' model has 4 free parameters: {α, γ , λ, β}.

The Stochastic satisficing (SSAT) model employs a threshold heuristic. It tracks the means (Eq. [1]) and variances (Eq. [3]) associated with the two options. The probability of payoff being higher than the acceptability threshold, *T*, is calculated using a cumulative Gaussian distribution equation:

[7] $\quad SPa(t) = \dfrac{1}{\sqrt{2\pi V_a(t)}} \displaystyle\int_{T}^{\infty} \exp\left(-\dfrac{(x - Q_a(t))^2}{2V_a(t)} \right) dx$

where SP_a indicated the probability of action a being satisficing. A softmax (Eq. [2]) rule is used to calculate choice probabilities according to the options' satisficing probabilities (SP_a and SP_b).

In addition to these three models, we tested a version of all three models in which the unchosen option (in the example below option b was not chosen) drifts towards an acceptability threshold T:

[8]
$$\begin{cases} Q_a(t+1) = Q_a(t) + \alpha \cdot \left(R(t) - Q_a(t)\right) \\ Q_b(t+1) = Q_b(t) + \alpha \cdot \left(T - Q_b(t)\right) \end{cases}$$

This rule was use in the 'Reward-T' and 'Utility-T' models, adding to them an additional free parameter T. This rule was also used in the 'SSAT-T' model, using the threshold parameter T which was already used in the 'SSAT' model.

Model fitting and model comparison

For each model, we used Hamiltonian Monte Carlo sampling implemented in the STAN software package [35] to fit the free parameters of each model to the choice data, in a subject-by-subject fashion, in order to maximize likelihood [36]. The Markov Chain Monte Carlo (MCMC) process used for optimization produces a likelihood distribution over the parameter space of the model, for each subject. For model comparisons, we calculated Watanabe Akaike Information Criterion (WAIC) that uses these likelihood distributions and penalizes for the number of free parameters [21]. We then simulated each model, using the estimated posterior distribution over the individual parameters of that model, in order to produce the model's value estimations associated with each option during the experiment. We used these estimated values to predict the model's confidence ratings for the choices made by participants.

Acknowledgements

UH and BB are supported by the European Research Council (NeuroCoDec 309865). UH is also supported by the John Templeton Foundation. MK is supported by the Gatsby Charitable Foundation.

References

1. Tversky A, Kahneman D. Judgment under Uncertainty: Heuristics and Biases. Science (80-). 1974;185: 1124–1131. doi:10.1126/science.185.4157.1124

2. Glimcher PW. Indeterminacy in brain and behavior. Annu Rev Psychol. 2005;56: 25–56. doi:10.1146/annurev.psych.55.090902.141429

3. Ma WJ, Jazayeri M. Neural coding of uncertainty and probability. Annu Rev Neurosci. 2014;37: 205–220. doi:10.1146/annurev-neuro-071013-014017

4. Camerer CF, Loewenstein G, Rabin M. Advances in behavioral economics. Princeton University Press; 2011.

5. Kahneman D, Tversky A. Prospect Theory: An Analysis of Decision under RisK. Econometrica. 1979;47: 263–292. doi:10.2307/1914185

6. Niv Y, Edlund J a, Dayan P, O'Doherty JP. Neural prediction errors reveal a risk-sensitive reinforcement-learning process in the human brain. J Neurosci. 2012;32: 551–62. doi:10.1523/JNEUROSCI.5498-10.2012

7. Erev I, Barron G. On Adaptation, Maximization, and Reinforcement Learning Among Cognitive Strategies. Psychol Rev. 2005;112: 912–931. doi:10.1037/0033-295X.112.4.912

8.   Simon H a. Rational choice and the structure of the environment. Psychol Rev. 1956;63: 129–138. doi:10.1037/h0042769

9.   Winter S idney G. Satisficing , Selection , and The Innovating Remnant. Q J Econ. 1971;85: 237–261.

10. Simon HA. Administrative behavior; a study of decision-making processes in administrative organization. 4th ed. New York, New York, USA: Simon and Schuster; 1997.

11. Winter SG. The Satisficing Principle in Capability Learning. Strateg Manag J. 2000;21: 981–996.

12. Sanders JI, Hangya B, Kepecs A. Signatures of a Statistical Computation in the Human Sense of Confidence. Neuron. 2016;90: 499–506. doi:10.1016/j.neuron.2016.03.025

13. Fleming SM, Weil RS, Nagy Z, Dolan RJ, Rees G. Relating introspective accuracy to individual differences in brain structure. Science. 2010;329: 1541–3. doi:10.1126/science.1191883

14. Yeung N, Summerfield C. Metacognition in human decision-making: confidence and error monitoring. Philos Trans R Soc Lond B Biol Sci. 2012;367: 1310–21. doi:10.1098/rstb.2011.0416

15. Pouget A, Drugowitsch J, Kepecs A. Confidence and certainty: distinct probabilistic quantities for different goals. Nat Neurosci. 2016;19: 366–374. doi:10.1038/nn.4240

16. Fleming SM, Daw ND. Self-evaluation of decision performance: A general Bayesian framework for metacognitive computation. 2016;123. doi:10.1002/smll.))

17. Sutton RS, Barto AG. Reinforcement learning: An introduction [Internet]. 2nd ed.

Cambridge: MIT press; 2012. doi:10.1109/MED.2013.6608833

18. Sargent TJ. Macroeconomic theory. 1979.

19. Rescorla RA, Wagner AR. A Theory of Pavlovian Conditioning : Variations in the Effectiveness of Reinforcement and Nonreinforcement. In: Black A, Prokasy WF, editors. Classical conditioning II: current research and theory. New York, New York, USA: Appleton-Century-Crofts; 1972. pp. 64–99.

20. Kruschke JK. Bayesian Estimation Supersedes the t Test. J Exp Psychol Gen. 2012;142: 573–603. doi:10.1037/a0029146

21. Watanabe S. Asymptotic Equivalence of Bayes Cross Validation and Widely Applicable Information Criterion in Singular Learning Theory. J Mach Learn Res. 2010;11: 3571–3594. Available: http://www.jmlr.org/papers/volume11/watanabe10a/watanabe10a.pdf

22. De Martino B, Fleming SM, Garrett N, Dolan RJ. Confidence in value-based choice. Nat Neurosci. Nature Publishing Group; 2013;16: 105–10. doi:10.1038/nn.3279

23. Lebreton M, Jorge S, Michel V, Thirion B, Pessiglione M. An Automatic Valuation System in the Human Brain: Evidence from Functional Neuroimaging. Neuron. 2009;64: 431–439. doi:10.1016/j.neuron.2009.09.040

24. Navajas J, Bahrami B, Latham PE. Post-decisional accounts of biases in confidence. Curr Opin Behav Sci. Elsevier Ltd; 2016;11: 55–60. doi:10.1016/j.cobeha.2016.05.005

25. Meyniel F, Schlunegger D, Dehaene S. The Sense of Confidence during Probabilistic Learning: A Normative Account. O'Reilly JX, editor. PLOS Comput Biol. 2015;11: e1004305. doi:10.1371/journal.pcbi.1004305

26. Lebreton M, Abitbol R, Daunizeau J, Pessiglione M. Automatic integration of confidence in the brain valuation signal. Nat Neurosci. 2015;18: 1159–1167. doi:10.1038/nn.4064

27. Simon HA. Models of bounded rationality: Empirically grounded economic reason. MIT press; 1982.

28. Sanborn AN, Chater N. Bayesian Brains without Probabilities. Trends Cogn Sci. Elsevier Ltd; 2016;xx: 1–11. doi:10.1016/j.tics.2016.10.003

29. Lerner JS, Tetlock PE. Accounting for the effects of accountability. Psychol Bull. 1999;125: 255–275. doi:10.1037/0033-2909.125.2.255

30. Shea N, Boldt A, Bang D, Yeung N, Heyes C, Frith CD. Supra-personal cognitive control and metacognition. Trends Cogn Sci. Elsevier Ltd; 2014;18: 186–93. doi:10.1016/j.tics.2014.01.006

31. Bang D, Frith CD. Making better decisions in groups Subject Category : Subject Areas : 2017; doi:http://dx.doi.org/10.1098/rsos.170193

32. Nicolle A, Fleming SM, Bach DR, Driver J, Dolan RJ. A Regret-Induced Status Quo Bias. J Neurosci. 2011;31: 3320–3327. doi:10.1523/JNEUROSCI.5615-10.2011

33. Samuelson W, Zeckhauser R. Status quo bias in decision making. J Risk Uncertain. 1988;1: 7–59. doi:10.1007/BF00055564

34. Crump MJC, McDonnell J V, Gureckis TM. Evaluating Amazon's Mechanical Turk as a tool for experimental behavioral research. PLoS One. 2013;8: e57410. doi:10.1371/journal.pone.0057410

35. Carpenter B, Lee D, Brubaker MA, Riddell A, Gelman A, Goodrich B, et al. Stan: A

Probabilistic Programming Language. J Stat Softw. 2015;

36.   Kruschke J. Doing Bayesian data analysis: A tutorial introduction with R JAGS, and

         Stan. 2nd ed. Igarss 2014. Elsevier; 2015.