The most informative neural code accounts for population heterogeneity

Elizabeth Zavitz[1,2,3], Hsin-Hao Yu[1,2], Marcello GP Rosa[1,2,3], Nicholas SC Price[1,2,3]

(1) Department of Physiology, Monash University, Melbourne, Victoria, Australia
(2) Biomedicine Discovery Institute, Monash University, Melbourne, Victoria, Australia
(3) ARC Centre of Excellence in Integrative Brain Function

Corresponding Author:
Elizabeth Zavitz
elizabeth.zavitz@monash.edu

Competing interests:
The authors have declared that no competing interests exist.

Funding:
This work was funded by Australia's National Health and Medical Research Council, the Human Frontier Science Program, and the Australian Research Council.

Author Contributions:
EZ and NSCP designed the study, EZ, HHY, MGPR, and NSCP ran the experiments, EZ performed the analysis and modelling, EZ and NSCP wrote the paper.

Abstract

Sensory perception depends on the accurate representation of the external world by neuronal populations. Each neuron's contribution to a population code depends on its tuning preferences, but neuronal populations are heterogeneous: their spiking rate, spiking variability and tuning selectivity are all different. To understand how this heterogeneity impacts a neuron's contribution to the population code, we recorded responses to moving stimuli from motion-sensitive neurons in anaesthetized marmosets (*Callithrix jacchus*) and trained linear decoders to discriminate direction using these responses. The relationship between a neuron's preferred direction and the discrimination boundary was the strongest predictor of its decoding weight, and highly direction selective neurons are the most useful in the population code. Millisecond-timescale changes in neuronal responses mean that optimal weights change rapidly; however, perceptual readouts do not have this fine-grained temporal flexibility, and must perform sub-optimal decoding at each point in time.

Author Summary

It is widely understood that perception depends upon interpreting, or decoding, the pattern of activity across a neuronal population. To do this, firing rates from hundreds of sensory neurons must be weighted and combined to accurately represent stimulus properties. Despite the reality of a diverse, heterogeneous population of neurons, all we know is that their weighting is a function of the relationship between their tuning preference, and the decoding decision or perceptual task under consideration. In this manuscript we ask: which neurons in a heterogeneous population are the most informative, can their usefulness can be predicted by their response properties, and to what degree can we expect them to be optimized? We addressed this question using a machine learning approach to learn how to weight each neuron's response in order to perform a range of discrimination tasks, and fit a series of decoding models to show that models based on preferred direction alone are significantly improved if neurons that are more selective are weighted more strongly. These

27   results show that we can perform better decoding without machine learning if we address

28   the false assumption that all members of the neural population are equally informative.

Introduction

Each of our perceptions is not a reflection of the activity of a single neuron, but an

interpretation of the aggregate activity across a population of neurons. Firing rates from

ensembles of hundreds of neurons must be weighted and combined to accurately represent

stimulus properties. We understand some aspects of how a perceptual 'readout' may be

produced from this population activity, such as how neurons with different tuning

preferences can be weighted and evaluated in order to make discriminations (1–3) or to

identify where a stimulus lies on a continuous scale (4,5). Often, the neural population is

idealized as a sequence of identical bell-shaped tuning curves whose peaks are offset from

one another to uniformly tile the stimulus space. In this case it is reasonable for every

neuron to contribute equally to the readout. However, cortical neurons are diverse: within a

single brain area they vary in sharpness of tuning, selectivity, overall firing rates, and trial-to-

trial variability (6). Here we address the problem of optimal coding in a heterogeneous

population by asking which neurons are the most informative, whether their usefulness can

be predicted by their response properties, and to what degree we can expect them to be

optimized.

Within the brain, the firing rate of a given neuron depends on the firing rate of its inputs, and

the relative weighting of each input. This weighting is governed by the strength of synaptic

connections from each input neuron. In the context of sensory decision making, the

magnitude of a neuron's synaptic weight indicates the amount to which it contributes to a

decision. A computational decoder emulating a decision making process thus represents the

activity of readout neurons that receive inputs from a large population of sensory neurons,

and its weights are analogous to synaptic weights (7). To decode neural activity

computationally, each neuron may be assigned multiplicative weights *a priori*, based on

known attributes of the neurons such as preferred direction. This is done often in theoretical

contexts: all neurons are assumed to be identical aside from their tuning preference, and

they are assigned weights based on that preference alone. Alternately, weights may be

derived with machine learning approaches. As expected (8), the weights that individual

neurons are assigned by decoders trained to perform fine discrimination tasks are highest

when the individual tuning curves have the most discriminatory power because their tuning

curves are steep or have relatively low inter-trial variability (1,9). Even after accounting for

this relationship, there is still a significant amount of variability in the weights that neurons in

heterogeneous populations are assigned.

How a decoding model's performance varies over time can provide meaningful insight into

how optimal neural coding may be. When decoders are trained and tested at matching time

points throughout the stimulus response, their weights are optimized to the responses at

each time (9,10). However, spike-rate adaptation following strong stimulus drive is

associated with changes in firing rates and tuning properties. These stimulus-specific

changes in firing rate result in perceptual errors (11). If the weights that neural circuits use to

decode population activity are continuously and rapidly updated, adaptation would not affect

perception because the readout would be continually optimized to produce an accurate

percept. That we observe adaptation-related effects in a multitude of contexts and modalities

suggests that readout weightings are stable over short timescales (12), and thus that coding

is not optimal over the same time scales.

In this paper, we used the responses from heterogeneous populations recorded in area MT

of the non-human primate visual cortex to examine how the direction of moving patterns is

encoded by neural populations. To determine which neurons are most informative, we

derived weights for each neuron using a machine learning model. We compared these

weights against the tuning properties of each neuron in order to predict which neurons will

be useful. We found that direction selectivity both predicted the weight of the recorded

neurons, and enhanced the performance of *a priori* decoding models (in which weights are

pre-defined, rather than learned), independent of the readout decision (identification or

discrimination), and population size. Our results suggest that those neurons that are highly

selective contribute the most to the population code, and that little optimization in weights is

needed for the predicted perceptual errors between trials to equal the degree of error that is

tolerated over time.

Results

The activity across a population of neurons is weighted and interpreted to produce

perceptual experiences. In the context of motion processing, theoretical and empirical

methods have demonstrated that a neuron's utility in a population code depends primarily on

its preferred direction, but how other response characteristics impact population coding is

unknown.

To assess how response properties other than preferred direction influence coding weight,

we recorded extracellular responses from motion-sensitive neurons in the middle temporal

area (MT) of four anaesthetized common marmosets (*Callithrix jacchus*) while we displayed

moving dot patterns. The stimulus dots moved coherently in one of 12 directions for 500 ms

before a 500 ms blank period, and each direction was repeated 120 times. We combined

trial-shuffled responses for 136 single units, then applied a supervised learning algorithm to

decode them based on one of three schemes. Fine and coarse two-alternative

discriminations were decoded based on a binomial generalized linear model (Figure 1A),

and 12-alternative identification was decoded based on a multinomial generalized linear

model (Figure 1B).

Figure 1: Decoding neural population activity. (A) Schematic of the two-alternative bimodal generalized linear model. The spiking responses (*r*) of a population of *n* neurons are integrated in a spike counting window, multiplied by a weight (*w*), summed, transformed, then compared to a criterion. Therefore every pattern of spike counts predicts one of the two possible directions. **(B)** Schematic of the identification multinomial generalized linear model. In this model, spike counts are weighted, integrated and transformed multiple times: once for each possible stimulus direction category. These responses are subsequently combined using a vector average to produce a direction prediction on a continuous scale. Continuous estimates within ±15º of the stimulus were considered 'correct'.

The purpose of the supervised learning process is to choose weights to apply to each

neuron's spike count which maximize decoding performance at each point in time. In both

models, the weights learned for each neuron are representative of synaptic connection

strength, but we use them here as a proxy for how important that neuron is to making each

perceptual decision. More broadly, these models allow us to examine how the importance of

a neuron varies depending on its response properties, the time since stimulus onset, and

which decision is being made.

Decoding weights generalize well, but not perfectly, over time

To see how variable the neural code is over the 500 ms stimulus duration, we can repeat

training and decoding at every time point and measure how weights generalize from one

time point to another. The generalization matrix for the 12-AFC decoder (Figure 2A) shows

decoding performance for every pairing of training and test times, for spikes counted in

sliding 50 ms time windows. In this case, decoding performance peaks at around 40%

correct (chance is 8.3%). Note that we are primarily interested in how changing aspects of

the decoder affects relative decoding performance, rather than trying to maximize absolute

performance. Along the diagonal (solid box), weights are trained and tested on matching

time points. The horizontal boxes show how weights from training early (dotted) and late

(dashed) within a trial after motion onset generalize to all other decoding times.

We resampled our sub-populations in this and subsequent analyses because a neuron's

weight depends on what information is available from other neurons. We could not assume

that the sub-population of 136 neurons we recorded is an accurate reflection of the

population that contributes to each readout in the whole animal. We thus resampled smaller

sub-populations in order to estimate the sample-related variability in performance and

weight.

In both the 12- and two-alternative identification decisions (Figure 2B & C), the performance

of the decoders that were trained only at one time depends on the time during which they

were trained. Training early (dotted line, 200 ms) only performs as well as the decoder

trained at every time point in the earliest part of the response. Training late (dashed line, 400

ms) performs as well as the decoder optimised at every time point through both the mid and

late parts of the response. In both cases, training only once leads to below-chance

performance following stimulus offset (Figure 2 B&C, dashed lines, 550 ms onward). This

reflects transient adaptation effects that only the temporally-matched decoder can take

advantage of (10,13,14).

These results show at least three distinct epochs in decoding performance: an early,

contrast driven code (50-250 ms), a late sustained code (250-550 ms), and an adaptation-

driven code (550 ms onward). The effects of adaptation following stimulus offset mean that

models trained only once produce systematic errors that are consistent with perceptual

aftereffects. Because we have evidence in the form of aftereffects that these coding errors

affect perception, it is unlikely that the brain benefits from decoding weights that are

optimized at each time point after stimulus onset. This implies that whatever weights the

brain uses, they will not be optimized at all time points, so the weaker decoding performance

when the model fails to generalize perfectly may represent a good estimate of how much

error the brain tolerates in a given perceptual code.

Figure 2: Decoding weights generalize well, but not perfectly, over time. (A) Full
generalization matrix for 12-alternative decoding (chance = 8.3%). Percent correct is
indicated by color for each combination of training and testing time. **(B)** Twelve-alternative
decoding performance for three slices of the generalization matrix: train-test same (solid
line), train 200 ms (dotted line), train 400 ms (dashed line). **(C)** as in B for fine and coarse
two-alternative discrimination (chance = 50%).

Population size affects decoding performance, not weight structure

Decoding performance as a measure of encoded information depends on many factors,

including the size of the spike-counting window for each time point (the integration window),

and the size of the neural population (*n*) from which responses are integrated. These factors

affect the structure of the recovered decoding weights, because when decoding is easy

enough that performance is at ceiling, weights cannot be further optimized. In other words,

the weighting that allows a population to solve an easy task perfectly may not extract

enough information from the population to solve a more difficult task, even if the information

is there. To circumvent this, we varied the integration window in order to match different

population sizes for decoding performance, so that the weights could be examined without

the number of neurons contributing to the population confounding our results. For simplicity,

we examined the weights learned at a representative time point (200 ms) after stimulus

onset.

To measure the effect of population size on how the weights were assigned to different

neurons, we first calculated decoding performance for integration windows ranging from the

prohibitively small to slightly longer than the duration of the stimulus (4-512 ms), and for sub-

populations of 20, 40 or 130 neurons (Figure 3A-C). We fit cumulative Gaussian functions to

the decoding performance, and interpolated to find an integration window that produced a

level of performance well above chance (lower dashed lines), but below the saturation points

of any of the functions. This corresponded to 60% correct for the 12-alternative decoder and

80% for the two-alternative decoders (upper dashed lines).

We compared the weight profiles obtained for the different population sizes (Figure 3D-F).

Each data point is the average weight for a neuron across 100 resampled sub-populations.

Furthermore, as we tested twelve directions, each neuron contributes twelve weights per

sub-population, either simultaneously in the 12-alternative condition, or individually for each

direction-pairing in the two-alternative condition. Here, for clarity, we show all the weights

(dots) for the n = 40 population, and rolling averages for the larger and smaller populations.

For all population sizes, the weights are distributed across preferred directions in the same

way. In all cases there are relatively few extreme weights, with most weights close to zero.

Notably, the weight profiles follow the same shape for the fine and coarse discrimination,

unlike previous observations in primate V1 (1). Our simulations (below) suggest that this is

because of the broader tuning curves in area MT.

To examine the stability of a neuron's weight in the context of different population sizes, we

correlated the weights learned for a neuron in the full population against the weights it

received in the 20 and 40-neuron sized subpopulations (Figure 3G-I). For all three decoder

types, there is a strong positive correlation between decoding weights, but the regression

lines for the subpopulations have slopes lower than 1, with scatter most likely to occur in the

bottom left and top right quadrants. This means that while a neuron's precise weight may

vary, that variation is restricted so that it almost never changes sign. This is reasonable,

because a given neuron may contribute more or less to a prediction, but it is unlikely to

switch from providing evidence for a stimulus condition to providing evidence against it.

These results show that, the principles that govern weighting are consistent across

variations in population size when populations are matched for decision difficulty.

Figure 3: Role of population size in decoding performance and optimal weights. (A)
Psychometric functions for a 12 AFC identification decoder for three different population
sizes (20, 40, and 130 neurons). Decision difficulty was parameterized by changing the size
of the integration window for spike counting. Percent correct data were fit with a cumulative
Gaussian function. The upper dashed line indicates the 60% threshold that we used to
choose an integration window that would match the performance across population sizes.
(B) As in A for a coarse discrimination (90°). Here and in C, we used a cutoff of 80% correct
to determine a spike counting window. **(C)** As in B, for a fine 2 AFC discrimination (30°). **(D)**
Weights for each neuron depended on the separation between their preferred direction and

the stimulus class. Decoding was performed at the threshold spike counting window
determined in A. **(E)** As in D, for coarse 2 AFC discrimination relative to the discrimination
boundary. **(F)** As in E, for fine 2 AFC discrimination. **(G-I)** Correlation between weights for
each neuron across population sizes. Weights are strongly correlated, with a tendency for
weaker (closer to zero) weights in the smaller populations. Lines are regression lines for the
two subpopulation sizes. Asterisks indicate p < 0.01.

Decoding weight Is related to the response properties of the neuron

We and others have shown that decoding neural populations requires setting weights that

depend on the relationship between the neuron's preferred direction and the task. However,

in populations that vary in a range of response properties (such as selectivity, firing rate,

trial-to-trial variability, or spontaneous rate), the weights learned across the population are

still difficult to predict based on preferred direction alone. To account for some of this

variability, we explored how the weights correlated with the response properties of the

neurons, specifically for conditions in which the preferred direction of the neuron predicted

that its weight should be at its highest. For example, in a twelve-alternative decision, this

means when its preferred direction is within 15 degrees of the presented class.

The weights have a nonlinear relationship with the preferred direction of the neuron (Figure

3D-F). To account for this, we further examined weights only when the preferred direction

predicted that they should be most informative (colored weights, Figure 4A). In 100

subpopulations of 20 neurons, we measured the partial Spearman's correlation between the

weights and each of selectivity, gain, Fano factor, and bandwidth. The direction selectivity

(Figure 4B), and, to a lesser extent, the gain (Figure 4C) of each neuron correlates positively

with the weight it is assigned across all types of decoding decisions. Fano factor (Figure 4D)

correlates negatively with weight. Low variability, as measured by a low Fano factor,

appears to be necessary but not sufficient: all of those neurons with large weights have low

Fano factors, but many neurons with low Fano factors are not weighted strongly. Bandwidth

of the direction tuning curve (Figure 4E) does not appear to correlate systematically with

weight, which suggests that the correlation between selectivity and bandwidth (r_s = 0.24, p <

0.01) contributes to the strong appearance of a relationship between bandwidth and weight.

These results are consistent across population sizes (Supplementary Table 1).

These results suggest that the best predictor of a neuron's decoding weight, after preferred

direction, is its selectivity. Fano factor, gain, and bandwidth appear to have progressively

weaker and less systematic correlations with decoding weight.

Figure 4: Direction selectivity and Fano factor predict decoding weight. (A) Left:
Weights assigned to neurons in 100 subpopulations trained to perform 12-alternative

identification, plotted against the different between each unit's preferred direction and the class of the weight. We further analyzed weights for those classes within the range of +/- 45º of each unit's preferred direction (colored points). Middle, Right: As in A, for two-alternative, 90º and 30º discriminations. The weights we went on to analyze were those assigned when the preferred direction of the neuron was between 10º and 110º from the discrimination boundary. Black lines show running means. **(B)** Direction selectivity index against the weight of each neuron for an identification decision. For clarity, only weights greater than 0 are shown, but negative weights were still included in correlation analyses. Inset *r*-value is the Spearman partial correlation between direction selectivity and weight (discounting variance shared with gain, Fano factor, and bandwidth), asterisks indicate p < 0.01. **(C-E)** As in B, for gain, Fano factor, and bandwidth.

Weights assigned by optimal decoders are scaled by selectivity

We aim to describe general encoding principles, but we have recorded from a limited

population of cells. Therefore, we generated homogeneous synthetic neural populations that

allowed us to define a weighting function that describes the relationship between the

decision and the preferred direction. Then, to sample a wider variety of populations and fit a

model based on physiological properties, we simulated unique heterogeneous populations of

neurons that conformed to the distributions of tuning properties we observed in our

recordings. In the following sections we:

1) **Define generative models** that can ascribe weights to simulated neurons in
   homogeneous populations based on preferred direction alone.
2) **Extend the generative models** to heterogeneous populations by fitting them to subsets
   of simulated neurons grouped by their Fano factor and direction selectivity.
3) **Define an *a priori* decoding model** that gives a generative model for neurons based on
   their preferred direction, direction selectivity and Fano factor.
4) **Compare the *a priori* decoding performance** to performance achieved by models
   defined through machine learning in heterogeneous populations of recorded neurons.

By using two layers of models, were able to dissect which of a neuron's tuning properties are

generically important for decoding accuracy, regardless of the instantaneous responses of

each neuron.

Defining generative models by simulating and decoding a homogenous population

As shown in this paper and previously, for a given relationship between the preferred

direction and the class or decision boundary, weights in heterogeneous populations are

variable (e.g. Figure 4A). This variability precludes us from fitting a model that describes the

relationship between the preferred direction of the neuron, the class or decision boundary,

and the weight the neuron is assigned in a decoder. To overcome this, we first simulated a

homogeneous population.

The properties of the recorded population (Figure 5A-D) were first characterized using

inverse Gaussian distributions (Fano factor and gain), an exponential function (spontaneous

rates) and a Gaussian distribution (bandwidths). To simulate a homogeneous population, the

tuning properties were fixed to the means of the distributions in Figure 5A-D, and preferred

directions were sampled randomly from a uniform distribution.

Figure 5: In simulated populations the distribution of weights is also predicted by
selectivity. (A) Distribution of the Fano factor for 136 recorded neurons (bars), and the
inverse Gaussian probability density function (PDF) used to generate simulated populations
(line). The mean and standard deviation for the simulated populations are matched to the
recorded population. **(B)** As in A for bandwidth, and a Gaussian PDF. **(C)** As in A, for
spontaneous rate and an exponential PDF. **(D)** as in A for gain and an inverse Gaussian
PDF. **(E)** example of tuning curves generated by the model for a population of 20 neurons,
and the distribution of their measured DSIs. **(F)** A subpopulation of 20 recorded neurons and
their DSIs for comparison. **(G)** Weights learned in a simulated homogeneous population with
the same mean spontaneous rate, gain, and bandwidth as in the recorded population. The
grey dots are the learned weights for each neuron, in each class, for each of 5 randomly
generated populations. Plotted with these weights is the Gaussian model fit to the data (solid

To fit models that can account for the relationship between preferred direction and weight in a homogeneous population, we used the same machine learning approach to weight the simulated neurons for decoding. The weights that the decoders learned for neurons in these populations (Figure 5G-I, circles) were very similar to what would be expected given the tuning curve (dashed line, Figure 5G), or the Fisher information (Figure 5H, I). There is some variability in the weights, even in homogeneous populations, caused by Poisson spiking variability over the limited number of trials used to train each decoder. We defined two generative models based on the homogeneous simulation weights that capture the expected weight given the preferred direction of the neuron: a Gaussian model (Equation 1) for the twelve-alternative condition, and a Gabor model (Equation 2) for the two-alternative conditions (Figure 5G-I, black lines) (see Methods). Both models have two free parameters: amplitude and spread.

Extending the generative models by simulating and decoding a heterogeneous population

Using a homogeneous population allowed us to define models that account for the role of preferred direction in decoding. We expected that the shape of those models (amplitude and spread) would vary for neurons that tended to have higher weights. To fit the amplitude and spread parameters used to predict a neuron's decoding weight, we simulated 150 heterogeneous populations of 20 neurons each (e.g. Figure 5E) with the same population-wide distributions of properties (Figure 5F). Neurons were created with preferred directions sampled randomly from a uniform distribution, and other properties drawn independently from the relevant distribution. An exemplar heterogeneous population shows how the simulated neurons (Figure 5E) closely resembled those we recorded (Figure 5F) – including the wide range of observed selectivities – even though selectivity was never set explicitly.

We learned decoding weights for each neuron then partitioned the weights for the 3000

simulated neurons into evenly spaced bins based on their selectivity (8 bins) and Fano factor

(9 bins), and fit the generative models to the weights in each bin. Figure 5 J-L illustrates how

these models vary with selectivity, for a single Fano factor bin (1.25-1.5). This approach

allows us to examine how neuronal weights are best allocated to neurons with specific

selectivities and spiking variability. Supplementary Figure 1 shows the model parameters

(amplitude and spread) and goodness of fit for all subsets of neurons. Not all combinations

of Fano Factor and selectivity matched neurons in the simulation, so we fit a total of 51

models in the 12-alternative decision, and 38 models in the two-alternative decisions.

Defining the *a priori* model
In the Gaussian model used to describe the optimal weights for a 12-alternative decision, we

found that the amplitude of the model is higher for more direction-selective neurons with

lower Fano factors (Figure 5J, Supplementary Figure 1A, top). Given how well the two-

parameter generative models describe neuronal weightings for bins of neurons with similar

selectivity and Fano factor, we then tried to predict the amplitude and spread parameters of

the weighting functions for any arbitrary neuron, given only its DSI and Fano factor. The

amplitude parameter was well defined by a second-order polynomial regression surface (R^2

= 0.97), however, the relationship between the Gaussian model's spread, Fano factor and

selectivity is more complicated (Supplementary Figure 1B, top). It appears as though the

spread is narrowest for selective neurons with higher Fano factors, but the data are noisy

and the range is small (64º-80º), so for further analysis we fixed this parameter at the

median: 72º.

Likewise, in the Gabor model used to account for weights in the 30 and 90 degree

discriminations, we were able to capture the relationship between model amplitude, Fano

factor, and selectivity with a second-order polynomial (R^2_{90}= 0.94, R^2_{30}= 0.93), but the

surface that described the model spread was too complex to fit with a reasonable number of

parameters. In these cases the ranges were large, but not systematic, and many of the most

extreme values were associated with lower R^2. For further analyses, we used a spread with

the median value: 98º in the 30 degree discrimination and 107º in 90 degree discrimination.

These results show that larger weights are learned for more selective, less variable neurons,

and outline quantitatively what weight is expected for a given preferred direction, selectivity

and Fano factor. This quantitative description allowed us to set weights for our recorded

population of neurons based on these properties alone instead of using a supervised

learning algorithm.

Comparing *a priori* decoding performance

We have shown that weights learned to decode real and simulated populations depend

systematically on direction selectivity, but this does not mean that these weights directly

improves decoding performance – those neurons with high weights may instead facilitate

learning. To address the direct impact of weights on performance, we extended the

generative Gabor and Gaussian models described above to define weights *a priori* and

compared the decoding performance of several different *a priori* decoding models to

decoders trained at each time point. In brief, the learned weights produce the best decoding

for the given set of neurons, and defining weights based on the preferred direction alone

(PD-only) gives the worst performance. We can compare how other *a priori* models including

selectivity (DSI) and Fano factor (FF) perform within this range to give insight into which

neuronal properties affect decoding.

We trained decoders on the responses of 100 subpopulations of 20 neurons each, sampled

with replacement from the 136 neurons we recorded from marmoset MT. For each

subpopulation, we compared performance with the learned weights (Figure 6A) to

performance with weights set according to four different models. The preferred direction only

(PD-only) model (Figure 6B) is the model typically considered in population decoding.

Regardless of any other properties, neurons are weighted based on the relationship

between their preferred direction and the class being decoded.

To determine the potential benefit of accounting for additional response properties, we

modified the weighting function for each neuron based on the fits regression surface. We

added selectivity to this model by setting the amplitude of the Gaussian based on where the

measured selectivity of the neuron fell on the regression surface with Fano factor = 1.5

(Figure 6C), and added Fano factor in the same manner with selectivity = 0.8 (Figure 6D).

High values of Fano factor and selectivity were chosen so that they did not handicap the

cell's potential influence. Precise values did not matter – we tested several variants of fixed

values and the results were unchanged. Finally, we included a model that accounts for

selectivity, Fano factor, and the interaction between them (Figure 6E).

400
Figure 6: Weight models based on machine learning and fits to simulated weights. (A)
Five models of weights used to identify stimulus direction in a 12-alternative decision. From
left, the learned weights model uses those learned for each subpopulation of 20 neurons
(one example population is depicted here). The preferred direction (PD-only) model weights
each neuron based on its preferred direction. The PD+DSI and PD+FF models are scaled
based on each property alone, and the PD+DSI+FF model scales weights based on all three
properties. **(B)** As in A, for a fine (30º) two-alternative discrimination. **(C)** As in A, for a
coarse (90º) discrimination. Color scale shows direction selectivity index (DSI).

We used these weighting functions to decode the stimulus direction as before, and

compared the average performance of each of the *a priori* models to the model with learned

weights at all time points (Figure 7A-C), and then specifically compared the distributions of

performances at a single time point (400 ms) (Figure 7D-F). We found that the *a priori* model

performance was indistinguishable from the learned model performance in the coarse (90º)

two-alternative discrimination for two models: PD+DSI (Figure 7F, dotted) and PD+DSI+FF

(Figure 7F, solid purple) (Wilcoxon Signed Rank Test, p > 0.01, n = 1200). The Learned

model significantly outperformed all other models (Wilcoxon Signed Rank Test, p < 0.01).

417
Figure 7: Weight models that account for preferred direction and selectivity account
for much of learned decoding performance. (A) The performance of the models in Figure
6 over time. The learned weights outperform the modelled weights, but the models including
selectivity and variability perform at least as well as the model that accounts for preferred
direction alone. **(B)** As in A for a fine two-alternative discrimination. **(C)** As in A for a coarse
two-alternative discrimination **(D)** Comparison between models and learned weights for each
of the 100 subpopulations examined 400 ms after stimulus onset (shaded region in A). The
learned performance is subtracted from the model performance so negative values are
subpopulations where the model was worse than the learned weights, and positive values
indicate that the model was better than the learned weights. **(E)** As in D for a fine two-
alternative discrimination. Note that the high number of samples compared to D is because
each subpopulation was decoded multiple times: once for each pair of directions. Thus,
there are 1200 instead of 100 samples. **(F)** As in E for a coarse two-alternative
discrimination.

Amongst the four *a priori* models, there was a significant main effect of model on decoding

performance (Friedman test, p < 0.01). Including Fano factor alone (PD+FF, Figure 7,

dashed) significantly improved performance above PD-only in only the coarse two-

alternative discrimination (Dunn's multiple comparisons, p > 0.01). On the other hand,

including selectivity alone (PD+DSI, Figure 7, dotted), or with variability (PD+DSI+FF, Figure

7, solid color) consistently improved decoding performance for all types of discrimination (p <

0.01). We found no evidence that including variability along with selectivity (PD+DSI+FF)

could improve performance over selectivity alone (PD+DSI) (p > 0.01).

These results show that accounting for direction selectivity improves the representation of

motion in a population code beyond what is attainable by accounting for preferred direction

alone. Furthermore they show that while neurons with a low Fano factor and high direction

selectivity are likely to be weighted strongly by machine learning techniques, incorporating

the influence of Fano factor on weight does not measurably improve performance in most

cases, while accounting for the influence of selectivity on weight does. This may be because

selectivity has a stronger relationship with the optimal weight, or it may be because a low

Fano factor is useful in adjusting weights during learning, but negligible once the optimal

weightings are already known. Because different schemes perform similarly, they also

suggest that the brain has a high tolerance for sub-optimal weighting in even small

populations, particularly in the case of easier perceptual discriminations.

Discussion

Decoding is one way to assess the amount of information contained in the firing rates of a

population of neurons. In its most basic form, decoding applies weights to neurons in a

population vector scheme that depends only on each neuron's tuning preference (2,4). At its

most flexible, decoding uses machine learning to derive the weights for each neuron that

give the best estimates of the stimulus (1,9). This has the advantage of being completely

agnostic about which neurons are most informative, and does not require knowing anything

about each neuron in advance. Here, we have combined these techniques to show that

neurons are not equally informative members of the population. We found that those

neurons that are more selective should be weighted more heavily in order to improve the

population representation of the stimulus.

Although a machine learning approach to assessing population coding is advantageous

overall, it does have limitations. When we use a neuron's learned weight as a proxy for how

informative it is, we are confounding its contributions to learning and its contributions to the

ultimate discrimination. Our *a priori* modeling only partially addresses this confound,

because the absence of a statistically significant effect (i.e. for Fano factor) does not mean

that no effect exists. Further, applying weights multiplicatively means that neurons with very

low firing rates may be weighted strongly because those weights are then multiplied by

values close to zero. Machine learning approaches are also limited by the need for a large

number of trials to train the decoder before it may be tested on held-back trials. Techniques

such as leave-one-out testing (15) help to make the most of the available trials while still

performing cross-validation, but there is no substitute for larger, more varied training and

testing data sets. In particular, while leave-one-out validation approaches cross-validate

each test trial, they are not able to assess the variability that comes from changing the

training corpus. We were able to measure the variability to an extent by resampling both the

subpopulations of neurons and how trials were distributed in an 80-20 training-testing cross-

validation regime, but this approach is still limited by the total number of available trials.

Knowing that with a mismatch between the weighting scheme and a population biased by

adaptation we can predict observed perceptual aftereffects (Zavitz et al., 2016), it is unlikely

that any weighting scheme varies on short timescales. That weights fail to generalize

completely from one time to another implies that the perceptual readout is often sub-optimal,

even setting aside adaptation-induced biases. However, our results suggest that there is

likely some tolerance for sub-optimal weighting schemes. Using the *a priori* models we have

assigned weights that were substantially different from those the models learned, and found

that as long as they accounted for the preferred direction, the models could be used to

discriminate and identify stimulus directions within a median performance drop of less than

4% correct.

The easiest perceptual discrimination we tested (90º two-alternative) was also the least

sensitive to the precise weights applied to each neuron. Performance in this discrimination

dropped by a median of 2% correct with preferred-direction-only model, and was equal to

performance for the learned weights with any model including selectivity. This is interesting,

because performance was not at ceiling with respect to the percent correct, but it may have

been at ceiling given the information available in 50 ms of spiking information from 20

neurons. This can happen if a proportion of trials are 'unsolvable', either by being entirely

ambiguous, or by having firing rates that, on most other trials, represent a different stimulus.

Despite their temporal rigidity, neurons are dynamically re-weighted for different perceptual

tasks in both dramatic (identification vs. discrimination), and subtle (fine vs. coarse

discrimination) ways. This suggests that the relatively flexible readout scheme evident

across perceptual tasks is the result of top-down influences switching between stereotyped

weighting functions, or refining a weighting scheme over much longer timescales than

investigated here. Similarly, perceptual learning can correct for biases in the population

code, so it is likely that over longer time scales errors like those we see in adaptation-related

aftereffects are ultimately corrected.

Previous studies have reported that the pattern of weights learned in fine discrimination

tasks is steeper in the vicinity of the category boundary, which corresponds to a narrower

spread in our model (1). However, these findings were reported for orientation discrimination

with primate V1 neurons, which have a much narrower bandwidth than neurons in MT. A

model that rapidly changes from negative to positive weights near the discrimination

boundary can take advantage of neurons with narrow tuning, but such cells were a minority

in our recorded, and therefore our simulated, populations. Still, there is some evidence that

in our fine discrimination task the most selective cells had weights described by a narrower

model (Figure 5K, Supplementary Figure 1B), and that cells with lower bandwidths tended to

be weighted more heavily (r = -0.15, p < 0.01).

Fisher information determined for a single neuron's tuning curve predicts decoding weights

in two-alternative discrimination tasks for homogeneous populations, and this function can

be extended to describe decoding weights in heterogeneous populations. The relationship

between the Fisher information and the weights depends on the relationship between each

neuron and the discrimination boundary of the task. For example, when discriminating 0º vs

90º, the boundary is 45º. In an identification task there is no single discrimination boundary.

The same can be said for very coarse (i.e. 180˚) discriminations: when the tuning curves

don't overlap, there are many, equally valid, discrimination boundaries. In these cases it is

less informative to know the Fisher information of a single neuron or the population.

We examined only how our neurons might contribute to direction perception, but it is likely

that the same neurons contribute to multiple population codes. In MT alone, it is likely that

the population simultaneously represents motion direction, speed (16–18), eye position (19),

and disparity (20,21). How each neuron's selectivity interacts with the population to code

multiple stimulus properties simultaneously is an open question.

Conclusions

In this work, we found that direction selectivity and Fano factor predicted the weight

assigned to a neuron with a given preferred direction. In some ways, this is not surprising as

neurons with high selectivity and low variability are also going to be the most useful to the

sort of iterative, supervised learning algorithm commonly used to decode neural responses.

We addressed this concern by using the generative models fit to the learned weights in

simulated populations (Figure 5) to produce weights for the recorded neurons based on their

preferred direction, Fano factor, and direction selectivity (Figure 6). These modeled weights

underperform the learned weights but, importantly, models that include selectivity as a factor

outperform models based on preferred direction alone. This suggests that while high

selectivity may improve learning, it also improves a neuron's contribution to a population

code.

Methods

Our electrophysiology experiments were conducted in accordance with the Australian Code

of Practice for the Care and Use of Animals for Scientific Purposes. All procedures were

approved by the Monash University Animal Ethics Experimentation Committee.

Electrophysiology
We performed extracellular recordings in four anesthetized, adult New World monkeys (3

male, 1 female; common marmoset, *Callithrix jacchus*). Our procedures are slightly modified

from the procedure in (22), as described by (23). Briefly, anesthesia was induced with

alfaxalone (Alfaxan, 8 mg/kg), and a tracheotomy and vein cannulation were performed. The

animal was artificially ventilated with a gaseous mixture of nitrous oxide and oxygen (7:3).

Maintenance solution with opiate anesthetic (sufentanil) and paralytic (pancuronium

bromide) was infused intravenously. Atropine and phenylephrine hydrochloride eye drops

were applied; then the cornea was protected, and the eyes were fitted with contact lenses to

bring a monitor at 350 mm into focus. The ipsilateral eye was occluded. A craniotomy and

durotomy were performed over area MT, and a 10x10, 96 channel, "Utah" array (Blackrock

Microsystems) was implanted using a pneumatic insertion tool over area MT (localized using

gross anatomical landmarks, verified postmortem using receptive field maps and histology).

Recordings were collected at 30 kHz using a Cerebus system (Blackrock Microsystems).

The raw voltage signal was high pass filtered at 750 Hz, and spikes were detected based on

threshold crossings. Spikes were manually segregated offline into isolated single units using

custom MATLAB software. Responses from each single unit were trial shuffled, and units

were combined across animals. Non-selective units (direction selectivity index < 0.2 in all 50

ms spike bins) were excluded from further analysis. A total of 136 direction selective single

units from four animals were used throughout the study.

Visual Stimulation
Stimuli were presented on a VIEWPixx 3D (1920x1080 pixels; 520x295 mm; VPixx

Technologies) positioned at a viewing distance of 350 mm. The stimulus filled the display

and consisted of a sheet of white dots on a black background. The field consisted of 0.5 dots

per degree square, and each dot subtended 0.3 degrees of visual angle. Dots moved

coherently with no noise in 1 of 12 directions and at 8, 10, or 20 cycles per degree. Data

were collapsed across stimulus speeds. The stimulus moved in one direction for 500 ms and

was followed by a blank (black) screen before another, random, direction was presented.

Each direction was presented 120 times.

Characterizing neurons
We characterized our recorded neurons by their preferred direction, bandwidth, Fano factor,

gain, and direction selectivity. A raw tuning curve was constructed based on the mean

response to each stimulus direction. Gain was calculated as difference between the

maximum and minimum responses. Preferred direction was calculated as the vector sum of

the tuning curve, and direction selectivity as its vector magnitude. The bandwidth was

computed based on the full width at half height of a Von Mises function fit to the tuning

curve. Fano factor was calculated as the spike count variance divided by the mean across

all directions.

Decoding
The stimulus direction was decoded at multiple time points throughout the 500 ms duration

based on spike counts measured in time windows of 4-512 ms. These spike counts were

weighted, then integrated across neurons and nonlinearly transformed. In the discrimination

model, the sum is compared to a criterion to determine which direction the model reports. In

the identification model, each spike count is weighted multiple times – once for each of the

possible stimulus directions. These weighted spike counts are integrated and transformed as

before, then used to create a direction vector, which the model provides as a continuous

estimate of the stimulus direction.

We used two logistic regression models to decode neuronal responses: a multinomial

generalized linear model (GLM) to make identification decisions, and a binomial GLM to

make discriminations. For optimization, we used the glmnet statistical software package in

Matlab (24,25). The models were trained on 80% of the stimulus trials by refining weights to

optimize performance via penalized maximum likelihood. The performance we report is the

decoding performance on the remaining 20% of trials. Which trials were training trials were

randomly selected each time a decoder was trained. In different experiments we varied the

sizes of the populations and the size of the spike integration window, but unless otherwise

specified we used subpopulations of 20 neurons, and integrated spikes for 30 ms. We

decoded at a temporal resolution of 10 ms.

To perform two-alternative discriminations on a data set collected for 12 stimulus directions,

we selected out only the trials in each possible pairing. For example, in the coarse two-

alternative discrimination, we trained models to decode 0º vs 90º, 30º vs 120º, etc.. This

means that the 12-alternative decoder has 12 times as many trials to train and test on, but

that 12 times more decoders were trained for the two-alternative discriminations (i.e., 100

subpopulations for each decoding task, times 12 different direction pairs). For this reason,

the weights tend to be noisier in the two-alternative decoders, but their performance

distributions are smoother. Note also that the 12-alternative decoder is training a weight for

every class, while the two-alternative decoders train only one weight, so the ratio of

parameters to training data is the same in all cases.

To create *a priori* decoding models, we used the same procedure, except instead of learning

the optimal weights for each neuron and class, we applied the weights predicted by the

relevant model.

In the Gaussian decoding model, for direction identification, the relevant weight is given by

the difference between a neuron's preferred direction and the class of the weight ($\theta_{pref}-\theta_{class}$).

The Gaussian was centered at $\theta_{pref}-\theta_{class} = 0$, and had three free parameters: gain, standard

deviation, and an additive shift. After fitting these parameters to the simulated data, we used

selectivity as the gain parameter, and fixed the standard deviation and shift (1 and -1

respectively), to decode our neuronal populations.

$$w(\theta) = \left(ae^{-\theta^2/2\sigma^2}\right) - a/2 \tag{1}$$

622 The twelve-alternative model was a Gaussian function centered at θ_{pref} - θ_{class} = 0, with free

623 parameters for amplitude and spread. The two-alternative model was a Gabor function that

624 crossed zero at the decision boundary (θ_{pref} - θ_{bound} = 0) between the two possible directions.

625 The amplitude and the spread of the model were free parameters.

$$w(\theta) = ae^{-\theta^2/2\sigma^2} \sin(x(90/\sigma)) \tag{2}$$

In the Gabor decoding model, for direction discrimination, the relevant weight is given by the

difference between a neuron's preferred direction and the discrimination boundary between

the two classes (θ_{pref}-$\theta_{decisionBound}$). The zero-crossing of the Gabor was fixed at θ_{pref}-

$\theta_{decisionBound}$ = 0, and there were two additional free parameters: the gain, and the spread of

the Gabor. The frequency of the sine wave was set as a ratio of the Gaussian's standard

deviation, so that one full cycle fit within the Gaussian envelope. After fitting these

parameters to the simulated data, we used selectivity as the gain parameter, and fixed the

standard deviation at 1 to decode our neuronal populations.

Simulation
Populations of neurons were simulated based on the distributions of gain, bandwidth, Fano

factor, and spontaneous activity that we observed in our recorded populations. A Gaussian

tuning curve was produced with the specified gain, bandwidth and spontaneous level, and

spike counts were generated for a given trial based on the tuning curve, Fano factor, and a

Poisson spike generator. These spike counts were then decoded in the same manner as our

recorded populations of neurons.

Acknowledgements

This work was supported by National Health and Medical Research Council Project Grants

APP1008287, APP1066588 and APP1120667, Human Frontier Science Program Career

Development Award to N.S.C.P., the ARC SRI in Bionic Vision, and the ARC Centre of

Excellence for Integrative Brain Function. We thank Janssen-Cilag Pty Limited for the

donation of sufentanil citrate

References

1.   Graf ABA, Kohn A, Jazayeri M, Movshon JA. Decoding the activity of neuronal
populations in macaque primary visual cortex. Nat Neurosci. 2011 Feb;14(2):239–45.

2.   Seung HS, Sompolinsky H. Simple models for reading neuronal population codes.
PNAS. 1993 Nov 15;90(22):10749–53.

3.   Shamir M. Emerging principles of population coding: in search for the neural code.
Current Opinion in Neurobiology. 2014 Apr;25:140–8.

4.   Georgopoulos AP, Schwartz AB, Kettner RE. Neuronal population coding of movement
direction. Science. 1986 Sep 26;233(4771):1416–9.

5.   Salinas E, Abbott LF. Vector reconstruction from firing rates. J Comput Neurosci. 1994
Jun 1;1(1–2):89–107.

6.   Ecker AS, Berens P, Tolias AS, Bethge M. The Effect of Noise Correlations in
Populations of Diversely Tuned Neurons. J Neurosci. 2011 Oct 5;31(40):14272–83.

7.   Jazayeri M, Movshon JA. Optimal representation of sensory information by neural
populations. Nat Neurosci. 2006 May;9(5):690–6.

8.   Pouget A, Dayan P, Zemel RS. Inference and Computation with Population Codes.
Annual Review of Neuroscience. 2003;26(1):381–410.

9.   Berens P, Ecker AS, Cotton RJ, Ma WJ, Bethge M, Tolias AS. A Fast and Simple
Population Code for Orientation in Primate V1. J Neurosci. 2012 Aug 1;32(31):10618–
26.

10.   Mendoza-Halliday D, Torres S, Martinez-Trujillo JC. Sharp emergence of feature-
selective sustained activity along the dorsal visual pathway. Nat Neurosci [Internet].
2014 Aug 10 [cited 2014 Aug 12];advance online publication. Available from:
http://www.nature.com.ezproxy.lib.monash.edu.au/neuro/journal/vaop/ncurrent/full/nn.3
785.html

11.   Zavitz E, Yu H-H, Rowe EG, Rosa MGP, Price NSC. Rapid Adaptation Induces
Persistent Biases in Population Codes for Visual Motion. J Neurosci. 2016 Apr
20;36(16):4579–90.

12.   Schwartz O, Hsu A, Dayan P. Space and time in visual context. Nat Rev Neurosci.
2007 Jul;8(7):522–35.

13.   Glasser DM, Tsui JMG, Pack CC, Tadin D. Perceptual and neural consequences of
rapid motion adaptation. PNAS. 2011 Nov 8;108(45):E1080–8.

14.   Van Wezel RJAV, Britten KH. Motion Adaptation in Area MT. Journal of
Neurophysiology. 2002 Dec 1;88(6):3469–76.

15.   Chen SC, Morley JW, Solomon SG. Spatial precision of population activity in primate
682   area MT. Journal of Neurophysiology. 2015 Aug 1;114(2):869–78.

683   16.   Krekelberg B, Wezel RJA van, Albright TD. Adaptation in Macaque MT Reduces
684   Perceived Speed and Improves Speed Discrimination. Journal of Neurophysiology.
685   2006 Jan 1;95(1):255–70.

686   17.   Price NSC, Born RT. Adaptation to Speed in Macaque Middle Temporal and Medial
687   Superior Temporal Areas. J Neurosci. 2013 Mar 6;33(10):4359–68.

688   18.   Priebe NJ, Cassanello CR, Lisberger SG. The Neural Representation of Speed in
689   Macaque Area MT/V5. J Neurosci. 2003 Jul 2;23(13):5650–61.

690   19.   Morris AP, Bremmer F, Krekelberg B. Eye-Position Signals in the Dorsal Visual System
691   Are Accurate and Precise on Short Timescales. Journal of Neuroscience.
692   2013;33(30):12395–12406.

693   20.   Maunsell JH, Van Essen DC. Functional properties of neurons in middle temporal
694   visual area of the macaque monkey. II. Binocular interactions and sensitivity to
695   binocular disparity. Journal of Neurophysiology. 1983 May 1;49(5):1148–67.

696   21.   Uka T, DeAngelis GC. Contribution of Middle Temporal Area to Coarse Depth
697   Discrimination: Comparison of Neuronal and Psychophysical Sensitivity. J Neurosci.
698   2003 Apr 15;23(8):3515–30.

699   22.   Bourne JA, Rosa MGP. Preparation for the in vivo recording of neuronal responses in
700   the visual cortex of anaesthetised marmosets (Callithrix jacchus). Brain Res Brain Res
701   Protoc. 2003 Jul;11(3):168–77.

702   23.   Yu H-H, Rosa MGP. Uniformity and diversity of response properties of neurons in the
703   primary visual cortex: selectivity for orientation, direction of motion, and stimulus size
704   from center to far periphery. Vis Neurosci. 2014 Jan;31(1):85–98.

705   24.   Friedman J, Hastie T, Tibshirani R. Regularization Paths for Generalized Linear Models
706   via Coordinate Descent. J Stat Softw. 2010;33(1):1–22.

707   25.   Qian J, Hastie T, Friedman J, Tibshirani R, Simon N. Glmnet for Matlab.
708   http://www.stanford.edu/~hastie/glmnet_matlab/; 2013.

Supplementary Information

	12 AFC	2 AFC 90	2 AFC 30
130			
DSI	0.72	0.12	0.22
Gain	-0.10	0.37	0.12
FF	-0.24	-0.15	-0.11
BW	-0.23	-0.04	-0.14
40			
DSI	0.62	0.32	0.26
Gain	0.27	0.21	0.09

FF	-0.36	-0.21	-0.15
BW	-0.23	-0.13	-0.17
20			
DSI	0.60	0.40	0.31
Gain	0.32	0.12	0.14
FF	-0.37	-0.23	-0.21
BW	-0.10	-0.07	-0.15

Supplementary Table 1: Summary of Spearman's partial correlation coefficients for all decoders and population sizes.

Supplementary Figure 1: Selectivity and Fano factor are reflected in the amplitude of the weighting functions. (A) Left: The amplitude parameter of the Gaussian model (intensity) for neurons with each pairing of Fano factor and selectivity. There is a smooth amplitude gradient with respect to both Fano factor and DSI. Centre: The spread parameter of the Gaussian model. The relationship between spread and the parameters of interest is not as systematic as the amplitude, but there seems to be a narrower spread in conditions where Fano factor and selectivity are both moderate. Areas outside of the pink boundary indicate pairings of properties where there were fewer than thirteen weights (and so only one or no simulated neurons). Right: R^2 for the models from which amplitude and spread were

725   derived. **(B)** As in A for the amplitude and spread of the Gabor model in the 30º two-
726   alternative discrimination. **(C)** As in A for the 90º two-alternative discrimination model. Fits
727   were achieved with a five-parameter second-order surface where $f(x,y) = a + bx + cy + dxy + ey^2$.
728   ey^2. The quadratic term was required for direction selectivity (y), but not for Fano factor.