1

Scalable Multi-Sample Single-Cell Data Analysis by Partition-Assisted Clustering and Multiple
Alignments of Networks

Ye Henry Li[1, ¶], Dangna Li[2, ¶], Nikolay Samusik[3], Xiaowei Wang[4], Leying Guan[4], Garry P.
Nolan[3], Wing Hung Wong[4,5,*]

[1]Structural Biology Department and Public Policy Program, Stanford University, Stanford, USA.

[2]Institute for Computational and Mathematical Engineering, Stanford University, Stanford, USA.

[3]Department of Microbiology and Immunology, Baxter Laboratory, Stanford University,
Stanford, USA

[4]Statistics Department, Stanford University, Stanford, USA.

[5]Department of Biomedical Data Science, Stanford University, Stanford, USA

[*]Corresponding author.

Email: whwong@stanford.edu

[¶]These authors contributed equally to this work.

Abstract

Mass cytometry (CyTOF) has greatly expanded the capability of cytometry. It is now easy to generate multiple CyTOF samples in a single study, with each sample containing single-cell measurement on 50 markers for more than hundreds of thousands of cells. Current methods do not adequately address the issues concerning combining multiple samples for subpopulation discovery, and these issues can be quickly and dramatically amplified with increasing number of samples. To overcome this limitation, we developed Partition-Assisted Clustering and Multiple Alignments of Networks (PAC-MAN) for the fast automatic identification of cell populations in CyTOF data closely matching that of expert manual-discovery, and for alignments between subpopulations across samples to define dataset-level cellular states. PAC-MAN is computationally efficient, allowing the management of very large CyTOF datasets, which are increasingly common in clinical studies and cancer studies that monitor various tissue samples for each subject.

Author Summary

Recently, the cytometry field has experienced rapid advancement in the development of mass cytometry (CyTOF). CyTOF enables a significant increase in the ability to monitor 50 or more cellular markers for millions of cells at the single-cell level. Initial studies with CyTOF focused on few samples, in which expert manual discovery of cell types were acceptable. As the technology matures, it is now feasible to collect more samples, which enables systematic studies of cell types across multiple samples. However, the statistical and computational issues surrounding multi-sample analysis have not been previously examined in detail. Furthermore, it was not clear how the data analysis could be scaled for hundreds of samples, such as those in clinical studies. In this work, we present a scalable analysis pipeline that is grounded in strong statistical foundation. Partition-Assisted Clustering (PAC) offers fast and accurate clustering and Multiple Alignments of Networks (MAN) utilizes network structures learned from each homogeneous cluster to organize the data into data-set level clusters. PAC-MAN thus enables the analysis of a large CyTOF dataset that was previously too large to be analyzed systematically; this pipeline can be extended to the analysis of similarly large or larger datasets.

Introduction

Analyses of CyTOF data rely on many of the tools and ideas from flow cytometry (FC) data analysis, as CyTOF datasets are essentially higher dimensional versions of flow cytometry datasets. Currently, the most widely used method in FC is still human hand-gating, as other methods often fail to extract meaningful subpopulations of cells automatically. In hand-gating, we draw polygons or other enclosures around pockets of cell events on a two-dimensional scatterplot to define subpopulations and cellular states that are observed in the data. This process is painfully time-consuming and requires advance knowledge of the marker panel design, the quality of the staining reagents, and, most importantly, *a priori* what cell subpopulations to expect to occur in the data. When presented with a new set of marker panels and biological system, the researcher would find it difficult to delineate the cell events, especially in high-dimensional and multi-sample datasets.

The inefficient nature of hand-gating in flow cytometry motivated algorithmic development in automatic gating. Perhaps the most popular is flowMeans[1], which is optimized for FC and can learn subpopulations in FC data[2] in an automated manner; however, it has not been successfully applied to CyTOF data analysis. Currently, most data analysis tools created for flow cytometry data analyses are not easily applicable for high-dimensional datasets[3]. An exception is SPADE, which was developed and optimized specifically for the analysis of CyTOF datasets[3]. flowMeans and SPADE constitute the leading computational methods in cytometry, but as shown later in this work, their performance may become sub-optimal when challenged with large and high-dimensional datasets. There are also other recent clustering-based tools that utilize dimensionality reduction and projections of high-dimensional data, however, these tools do not directly learn the subpopulations for all the cell events, and may be too slow to complete data analysis for an increasing amount of samples.

In this study, we address the data analysis challenges in two major steps. First, we propose the partition-assisted clustering (PAC) approach, which produces a partition of the k-dimensional space (k=number of markers) that captures the essential characteristic of the data distribution. This partitioning methodology is grounded in a strong mathematical framework of partition-based high-dimensional density estimation[4–8]. The mathematical framework offers the guarantee that these partitions approximate the underlying empirical data distribution; this step is faster than the recent k-nearest neighbor-based method [9] and is essential to the scalability of our clustering approach to analyze datasets with many samples. The clustering of cells based on recursive partitioning is then refined by a small number of k-means style iterations before a merging step to produce the final clustering.

Secondly, the subpopulations learned separately in multiple different but related datasets can be aligned by marker network structures (multiple alignments of networks, or MAN),

making it possible to characterize the relationships of subpopulations across different samples
automatically. The ability to do so is critical for monitoring changes in a subpopulation across
different conditions. Importantly, in every study, batch effect is present; batch effects shift
subpopulation signals so that the means can be different from experiment to experiment. PAC-
MAN naturally addresses batch effects in finding the alignments of the same or closely related
subpopulations from different samples.

PAC-MAN finds homogeneous clusters efficiently with all data points in a scalable
fashion and enables the matching of these clusters across different samples to discover cluster
relationships in the form of clades.

Results and Discussion

PAC

PAC has two parts: partitioning and post-processing. In the partitioning part of PAC, the
data space is recursively divided into smaller hyper-rectangles based on the number of data
points in the locality (Fig 1a). The partitioning is accomplished by either Bayesian Sequential
Partition (BSP) with limited look-ahead (Fig 1a and 1b) or Discrepancy Sequential Partition
(DSP) (Fig 1a); these are two fast variants of partition-based density estimation methods
previously developed by our group [4–8], with DSP being the fastest. BSP and DSP divide the
sample space into hyper-rectangles with uniform density value in each of them. The subsetting of
cells according to the partitioning provides a principled way of clustering the cells that reflects
the characteristics of the underlying distribution. In particular, each significant mode is captured
by a number of closely located rectangles with high-density values (Fig 1c). Although this
method allows a fast and unbiased localization of the high-density regions of the data space, we
should not use the hyper-rectangles directly to define the final cluster boundaries for two
reasons. First, real clusters are likely to be shaped elliptically, therefore, the data points in the
corners of a hyper-rectangle are likely to be incorrectly clustered. Second, a real cluster is often
split into more than one closely located high-density rectangles. We designed post-processing
steps to overcome these limitations: 1) a small number of k-means iterations is used to round out
the corners of the hyper-rectangles, 2) a merging process is implemented to ameliorate the
splitting problem, which is inspired by the flowMeans algorithm. The details of post-processing
are given in the Materials and Methods. The resulting method is named b-PAC or d-PAC
depending on whether the partition is produced by BSP or DSP.

Fig 1: PAC recursively partitions the data space to obtain rational initialization structure. (a) Partition-based methods estimate data density by cutting the data space into smaller rectangles. Bayesian Sequential Partition (BSP) divides the data space via binary partition in the middle of the bounded region, while that of Discrepancy Sequential Partition (DSP) occur at the location that balances the data point uniformly on both sides of the cut. The numbers denote sequential order of partitions. Since DSP adapts to the data points, it converges on the estimated density faster than BSP. (b) In the (one-step) look-ahead of version of partition, the algorithm cuts the data space for all potential cuts plus one step more (steps 2 and 3), and it finds the optimal future version (after step 3), which determines the actual cut (step 2). (c) The partitioning of simulated data space containing five subpopulations; the hyper-rectangles surround high-density areas, approximating the underlying distribution.

MAN

An approach to analyze multiple related samples of CyTOF data is to pool all samples into a combined sample before detection of subpopulations. This is a natural approach under the assumptions that there are no significant batch effects or systematic shifts in cell subpopulations across the different samples. However, such assumptions may not hold due to one or more of the following reasons:

1) *Dataset size and instruments used*. Large number of samples usually means the samples were collected on different days with different experimental preparations. Many steps can introduce significant shifts in measurement levels.
2) *Staining reagents*. Reagents such as antibodies, purchased from different vendors and batch preparations can affect the overall signal. While saturation of reagents in the protocol could help eliminate the batch effects in the staining procedure, this approach is costly and might not work for all antibodies, especially those with poor specificity.
3) *Normalization beads stock*. While normalization beads[10] help to control for the signal level, especially within one experiment, the age of the beads stock and their preparation could lead to significant batch effects. In addition, there are different types of normalization beads and normalization calculations.
4) *Human work variation*. While many researchers are studying the same system (e.g., immune system), different protocols and implementation by different researchers, who sometimes perform experimental steps slightly differently, can lead to batch effects.
5) *Subpopulation dynamics*. The subpopulation centers can move from sample to sample due to treatments on the cells in treatment-control studies or perturbation studies. General practice is to cluster by phenotypic markers.
6) *Sample background*. If the data came from different cell lines or individuals in a clinical study, the measurement levels and proportions of cell subpopulations would be expected

to change from sample to sample. Without expert scrutiny, it would be difficult to make
sense of the data with current data analysis tools.

Could we extract shared information that allows us to interpret cross-sample similarities
and differences? To ameliorate these difficulties, we have designed an alternative approach that
is effective in the presence of substantial systematic between-sample variation. In this approach,
each sample is analyzed separately (by PAC) to discover within-sample subpopulations. Over-
partitioning in this step is allowed in order not to miss small subpopulations in high dimension
due to lack of prior knowledge. The subpopulations from all samples are then compared to each
other based on a pairwise dissimilarity measure designed to capture the differences in within-
sample distributions (among the markers) across two subpopulations. Using this dissimilarity, we
perform bottom-up hierarchical clustering of the subpopulations to represent the relationship
among the subpopulations. The resulting tree of subpopulations is then used to guide the merging
of subpopulations from the same sample, and to establish linkage of related subpopulations from
different samples. We note that the design of a dissimilarity measure (Materials and Methods)
that is not sensitive to systematic sample-to-sample variation is a novel aspect of our approach.
The merging of subpopulations from the same sample is also important, as it offers a way to
consolidate any over-partitioning that may have occurred during the initial PAC analysis of each
sample. We emphasize that, as with the usage of all statistical methods, the user must utilize
samples or datasets that are considered as good as possible; interpretation of the analysis results
rely on the researchers to collect data with validated reagents for all samples.

Rational initialization for PAC increases clustering effectiveness

Appropriate initialization of clustering is very important for eventually finding the
optimal clustering labels; PAC works well because the implicit density estimation procedure
yields rational centers to learn the modes of sample subpopulations. When tested on the hand-
gated CyTOF data on the bone marrow sample in (14), compared to k-means alone, PAC gives
lower total sums of squares and higher F-measures in the subpopulations (Fig 2a and 2b). This
process also helps PAC to converge in 50 iterations (Fig 3) in post-processing, whereas k-means
performs very poorly even after 5000 iterations (Fig 4). Through the lens of t-sne plots (Fig 4),
the PAC results are more similar to the hand-gating results, while the k-means, flowMeans, and
SPADE clustering results perform poorly. In flowMeans, several large subpopulations are
merged. SPADE's separation of points is inconsistent and highly heterogeneous, probably due to
its down-sampling nature. On the other hand, by inspection, PAC obtains similar separation for
both the major and minor subpopulations as the hand-gating results.

Fig 2. Rational initialization is better than random initialization. The hand-gated CyTOF data (see S1 Fig) is used for illustration. In this case, (a) the overall sum of squares error is lower and (b) the F-measure is higher for PAC.

Fig 3. Rational initialization and minimal kmeans post-processing iterations give fast convergence. The convergence of PAC toward the hand-gated results, or ground truth, is fast. It takes less than 50 downstream post-processing kmeans iterations for the PAC to achieve convergence.

Fig 4. Visualization and comparison of clustering results by t-sne plots. Each t-sne plot contains the same 10,000 cell events from the hand-gated CyTOF data with different set of colored labels drawn. Note that the colors are informative only within each panel. These labels are from kmeans, SPADE, flowMeans, b-PAC, and d-PAC. The subpopulation numbers for all methods were set to be the same as that of hand-gated results. PAC methods achieve a significantly better convergence to the hand-gate labels than alternative methods.

PAC is consistently better than flowMeans and SPADE for simulated datasets and hand-gated cytometry datasets

In the systematic simulation study, we challenged the methods with different datasets with varying number of dimensions, number of subpopulations, and separation between the subpopulations. The F-measure and p-measures for the PAC methods are consistently equal or higher than that of flowMeans and SPADE (Table 1 and S2a Fig). In addition, we observe that flowMeans gives inconsistent F-measures for similar datasets (Table 1), which may be due to the convergence of k-means to a local minimum without a rational initialization.

Table 1. F-measure Comparisons of Methods on Simulated and Hand-gated Cytometry Datasets.

Data	Analysis Methods			
	flowMeans	SPADE	d-PAC	b-PAC
5_10_40_100k*	0.79	0.64	0.94	0.94
5_20_40_100k	0.9	0.73	0.94	0.94
10_5_30_100k	0.74	0.93	0.93	0.97
10_10_30_100k	0.967	0.88	0.98	0.98
10_10_40_100k	0.92	0.95	0.98	0.98

10_20_30_100k	0.88	0.76	0.9	0.91
10_20_40_100k	0.94	0.93	0.95	0.95
10_40_30_100k	0.42	0.55	0.7	0.7
20_5_20_100k	0.75	0.71	0.91	0.9
20_5_30_100k	0.76	0.98	0.99	0.99
20_5_40_100k	0.72	0.85	1.00**	1.00**
20_10_40_100k	0.25	0.96	0.97	0.97
20_20_40_100k	0.93	0.91	0.92	0.93
35_5_40_200k	0.96	0.89	0.99	0.99
35_10_40_200k	0.93	0.79	0.96	0.96
Stem Cell (6 dimensions, 5 subpopulations)	0.98	0.41	0.98	0.91
NDD (12 dimensions, 8 subpopulations)	0.8	0.77	0.79	0.8
CyTOF (39 dimensions, 24 subpopulations)	0.59	0.53	0.84	0.82

F-measure is calculated using the original hand-gate labels and the estimated labels generated by each analysis method. The true-positives are found if the methods assign the same labels to points belonging to the same subpopulation in the hand-gated data. The more true-positives found, the higher the F-measure, which ranges from 0 to 1, with 1 being the highest. Partition-based methods perform consistently well on data ranging from 5 to 39 dimensions. In the simulations, d-PAC and b-PAC perform just as well or better than flowMeans and SPADE. flowMeans gives drastically different F-measures for the cases 20_10_40_100k and 20_20_40_100k : 0.25386 vs. 0.92518; this large difference is likely due to the random initiation of cluster centers. In the hand-gated datasets, SPADE has the worst performance. Ultimately, the performance of flowMeans and SPADE deteriorate for the 39-dimensional real CyTOF data, while d-PAC and b-PAC perform consistently well.

*Simulated data have the following convention: a_b_c_d, where a denotes the number of dimensions/markers, b denotes the number of subpopulations, c denotes the size of the hypercube for data generation, and d denotes the number of cells.

**from rounding up, not originally 1.00

Next, we tested the methods based on published hand-gated cytometry datasets to see how similar the estimated subpopulations are to those obtained by human experts. We applied

the methods on the hematopoietic stem cell transplant and Normal Donors datasets from the
FlowCAP challenges[2] and on the subset of gated mouse bone marrow CyTOF dataset (Dataset
5) recently published[11]. The gating strategy of the CyTOF dataset is provided in Fig S1. The
dataset and expert gating strategy are the same as described earlier[12]. Note that in the flow
cytometry data, the computed F-measures are slightly lower than that reported in FlowCAP; this
is due to the difference in the definition of F-measures. Overall, the PAC outperforms
flowMeans and SPADE by consistently obtaining higher F-measures (Table 1). In particular, in
the CyTOF data example, PAC generated significantly higher F-measures (greater than 0.82)
than flowMeans and SPADE (0.59 and 0.53, respectively). In addition, PAC gives higher overall
subpopulation-specific purities (S2b Fig and S1 Table). These results indicate that PAC gives
consistently good results for both low and high-dimensional datasets. Furthermore, PAC results
match human hand-gating results very well. The consistency between PAC-MAN results and
hand-gating results in this large data set confirms the practical utility of the methodology.

Separate-then-combine outperforms pool approach when batch effect is present

It is natural to analyze samples separately then combine the subpopulation features for
downstream analysis in the multiple samples setting. However, we need to resolve the batch
effects. Two distinct subpopulations could overlap in the combined/pooled sample, such as in the
case when the data came from two generations of CyTOF instruments (newer instrument
elevates the signals). On the other hand, in cases with changing means, two subpopulations can
evolve together such that their means change slightly, but enough to shadow each other when
samples are merged prior to clustering.

We introduce Multiple Alignments of Networks to resolve the management issue
surrounding the organization of homogeneous clusters found in the PAC step (Fig 5). First, we
consider the overlapping scenario (Fig 6a). When viewed together in the merged sample, the
right subpopulation from sample 1 overlaps with the left subpopulation in sample 2 (Fig 6b left
panel). There is no way to use expression level alone to delineate the two overlapping
subpopulations (Fig 6b right panel). By learning more subpopulations using PAC, there are some
hints that multiple subpopulations are present (Fig 6c). Despite these hints, it would not be
possible to say whether the shadowed subpopulations relate in any way to other distinct
subpopulations.

Fig 5. Schematic analogy of MAN. Consider a deck of networks (in analogy to cards), with
each "suit" representing a sample and each "rank" representing a unique network structure. The
networks are aligned by similarity and organized on a dendrogram. The tree is cut (red line) at
the user-specified level to output the desired k clades. Within each clade, the network structures

are similar or the same. If the same sample has multiple networks in the same clade, then these
networks are merged (black box around same cards).

Fig 6. Simple Batch Effect Scenario. (a) Simulated data samples with two of the same
subpopulations. The means shifted due to measurement batch effect. (b) When the samples are
combined, as in the case of analyzing all samples together, two different subpopulations overlap
(left panel). The overlapped subpopulations cannot be distinguished by clustering (right panel).
(c) PAC could be used to discover more subpopulations, however, the hints of the present of
another subpopulation do not help to resolve the batch effect.

PAC-MAN resolves the overlapping issue by analyzing the samples separately (Fig 7). In
the case in which we do not know *a priori* the number of true subpopulations, we learn three
subpopulations per sample (Fig 7a). The network structures of the subpopulations discovered are
presented in Fig 7b-c and we see that the third subpopulations from the two samples share the
same network structures, while the first subpopulations of the two samples differ by only one
edge; these respective networks are clustered together in the dendrogram (Fig 8a right panel). By
utilizing the networks, the clades that represent the same and/or similar subpopulations of cells
can be established. Clustering by network structures alone resolves the majority of points in the
data (Fig 8a, left panel). Furthermore, as discussed next, by incorporating marker levels into the
alignment process, all the subpopulations can be resolved (Fig 8b).

Fig. 7. Calculation of sample clusters and their underlying network structures. (a) PAC was
used to discover several subpopulations per sample without advanced knowledge of the exact
number of subpopulations. (b-c) The networks of the subpopulations in both samples discovered
in (a). Networks can be grouped by similarities to organize the subpopulations across samples;
the alignment is based on Jaccard dissimilarity network structure characterization matrix;
dendrogram of the hierarchical clustering results.

Fig 8. Resolution of batch effects for simple batch effect scenario. (a) Resolution of batch
effect by networks of all subpopulations discovered. (b) Resolution of batch effect first by
network structures of larger subpopulations and then by merging smaller subpopulations into the
aligned clades.

Next we consider the case with dynamic evolution of subpopulations that models the
treatment-control and perturbation studies. The interesting information is in tracking how
subpopulations change over the course of the experiment. In the simulation, we have generated
two subpopulations that nearly converge in mean expression profile over the time course (Fig 9).
The researcher could lose the dynamic information if they were to combine the samples for
clustering analysis. As in the previous case, we could use PAC to learn several subpopulations
per sample (Fig 10). Then, with the assumption that there are two evolving clusters from data
exploration, we align the subpopulations to construct clades of same and/or similar
subpopulations (Fig 11 left panel) based on the network structural information (S3 Fig). With
network and expression level information in the alignment process, the two subpopulations or
clades can be resolved naturally (Fig 11 right panel).

Fig 9. Ground truth of simulated dynamic batch effect samples. Two subpopulations, in blue
color, almost converge in time by mean shifts.

Fig 10. PAC on dynamic batch effect scenario. PAC discovers several subpopulations per
sample without advanced knowledge of the number of subpopulations present.

Fig 11. PAC-MAN results for dynamic batch effect scenario. Comparison of PAC-MAN
results between representative clades (number of clades set to 2). Using network structures (left
panel) or expression information (middle panel) alone does not resolve the dynamic information.
On the other hand, the dynamic information is resolved first by alignments of networks of larger
subpopulations and then by merging smaller subpopulations into the aligned clades (right panel).

Network and expression alignment is better than network or expression alignment alone

With networks in hand, we could further characterize the relationships between
subpopulations across samples. However, the alignment process needs to work well for true
linkage to be established. We could align by network alone, by expression (or marker) means, or
both. Figs 8 and 11 present these alternatives in comparison. By using all the subpopulation
networks, the results still contain subsets of misplaced cells (Figs 8a and 11 left panel). This is
because small clusters of cells have noisy underlying covariance structure; therefore, the
networks cannot be accurately inferred. These structural inaccuracies negatively impact the
network clustering. The (mean) marker level approach also does not work well (Fig 11 center
panel) due to the subpopulation mean shifts across samples. On the other hand, the sequential
approach works well (Figs 8b and 11 right panel). In the sequential approach, larger (>1500 in

batch effect case; >1000 in dynamic case) subpopulations' networks are utilized for the initial
alignment process. Next, the smaller subpopulations, which have noisy covariance, are merged
with the closest larger, aligned subpopulations. Thus, more subpopulations could be discovered
upstream (in PAC), and the network alignment would work similarly as the smaller
subpopulations, which could be fragments of a distribution, do not impact the alignment process
(S4a Fig and S4b Fig). Moreover, in the network inference step, unimportant edges can
negatively impact the alignment process (S4c Fig) in the network-alone case. Biologically, this
means that edges that do not constrain or define the cellular state should not be utilized in the
alignment of cellular states. Effectively, the threshold placed on the number of edges in the
network inference controls for the importance of the edges. Thus, the combined alignment
approach works well and allows moderate over-saturation of cellular states to be discovered in
the PAC step so that no advance knowledge of the exact number of subpopulations is necessary.

PAC-MAN efficiently outputs meaningful data-level subpopulations for mouse tissue
dataset

We use the recently published mouse tissue dataset[11] to illustrate the multi-sample data
analysis pipeline. The processed dataset contains a total of more than 13 million cell events in 10
different tissue samples, and 39 markers per event (S2 Table). The original research results
centered on subpopulations discovered from hand-gating the bone marrow tissue data to find
'landmark' subpopulations; the rest of the data points were clustered to the most similar
landmark subpopulations. While this enables the exploration of the overall landscape from the
perspective of bone marrow cell types within an acceptable time frame, a significant amount of
useful information from the data remains hidden; a larger dataset would make it infeasible to
analyze by manual gating and existing computational tools to learn the relationships of the
cellular states among all samples. In addition, a natural question is how well do the bone marrow
cell types represent the whole immune system?

In contrast to the one-sample perspective, using d-PAC-MAN, the fastest approach by
our comparison results, we can perform subpopulation discovery for each sample automatically
and then align the subpopulations across samples to establish dataset-level cellular states. On a
standard Core i7-44880 3.40GHz PC computer, the single-thread data analysis process with all
data points takes about one hour to complete, which is much faster than alternative methods.
With multi-threading and parallel processing, the data analysis procedure can be completed very
quickly. As mentioned earlier, PAC results for the bone marrow subsetted data from this dataset
matches closely to that of the hand-gated results. This accuracy provides confidence for applying
PAC to the rest of the dataset.

Figs 11-12 show the t-sne plots for subpopulation discovered (top panel of each sample)
and the representative subpopulation established (bottom panel of each sample) for the entire

dataset. In the PAC discovery step, we learn 35 subpopulations per sample without advance knowledge of how many subpopulations are present. This moderate over-partitioning of the data samples leads to a moderate heterogeneity in the t-sne plots. Next, the networks are inferred for the larger subpopulations (with number of cell events greater than 1000), and the networks are aligned for all the tissue samples. We output 80 representative subpopulations or clades for the entire dataset to account for the traditional immunological cellular states and sample-specific cellular states present. Within samples, the subpopulations that cluster together by network structure are aggregated. The smaller subpopulations (not involved in network alignment) are either merged to the closest larger subpopulation or establish their own sample-specific subpopulation by expression alignment; small subpopulations were clamped with larger clades by grouping the subpopulations into 5 clusters per sample based on the means (of marker signal). The representative subpopulations (90 total) follow the approximate distribution of the cell events on the t-sne plots and the aggregating effect cleans up the heterogeneities due to over-partitioning in the PAC step.

Fig 12. Visualization of PAC-MAN results for Blood, Bone Marrow, Colon, Inguinal Lymph Node, and Liver samples. Each t-sne plot was generated using 10,000 randomly drawn cell events from each mouse tissue sample. The results from PAC (top panel) and MAN (bottom panel) steps are presented as a pair. Initial PAC discovery was set to 35 subpopulations without advanced knowledge of the number of subpopulations in each sample. In MAN, 80 network clades were outputted, and the cellular states are defined by expression (marker signal), network structure, and dataset-level variation. This composite definition naturally aggregates the initial 35 subpopulations to yield smaller number of subpopulations in less variable samples.

Fig 13. Visualization of PAC-MAN results for Lung, Mesenteric Lymph Node, Spleen, Thymus, and Small Intestine samples. The settings and descriptions are the same as those in Fig 12. Continuation of visualization of PAC-MAN results for the mouse tissue data.

The cell type clades are the representative subpopulations for the entire dataset, and they could either be present across samples or in one sample alone. Their distribution is visualized by a heatmap (Fig 14). While the bone marrow sample contains many cell types, only a subset of them are directly aligned to cell types in other samples, which means using the bone marrow data as the reference point leaves much information unlocked in the dataset. Therefore, the data suggests that the bone marrow cell types are not adequate in representing all cell types in the immune system. The cell types in the blood and spleen samples have more alignments with cell types in other samples. The lymph node samples share many clades; the small intestine and colon

samples also share many clades, probably due to closeness in biological function. The thymus
sample has few clades shared with other samples, which may be due to its functional specificity.

Fig 14: Heatmap of clade proportions across the tissue samples. Sample-specific clades have
a value of 1, while shared clades have proportions spread across different samples.
Physiologically similar samples share more clades.

PAC-MAN style analysis can be applied to align the tissue subpopulations by their means
instead of network similarities (S5 Fig). As done previously, representative clades (88 total) were
outputted. The same aggregating effect is observed (S5a Fig), and this is due to the organization
from dataset-level variation in the means. Comparing to the network alignment, the means
linkage approach has slightly more subpopulations per sample; the subpopulation proportion
heatmap (S5b Fig) shows more linking. Although the bone marrow sample subpopulations co-
occur in the same clades slightly more with other sample subpopulations, this sample does not
co-occur with many clades in the dataset. Thus, a PAC-MAN style analysis with means linkage
also harvests additional information from the entire dataset.

To compare the network and means approaches with PAC-MAN, we study the F-measure
and p-measure results with 88 total clades from each approach. The overall F-measure with all
cell events is 0.7969 and the overall F-measure with clades assignments of PAC-discovered
subpopulations is 0.3143. The two F-measure values suggest that the assignment of PAC-
discovered subpopulations is more consistent for larger subpopulations.

To illustrate the assignment purities, the p-measures are computed for the following two
cases. 1) Network clade assignment is the basis (network-justified), similar to the ground truth in
the clustering comparisons previously; or 2) means clade assignment is the basis (means-
justified) (S4 Table). P-measure cutoff is set at 0.3 (to remove unreliable comparisons) to obtain
purer clade assignments. In the network-justified case, PAC subpopulations with more than 0.3
in p-measure constitute 93.44 % of all cell events. In the means-justified case, PAC
subpopulations with more than 0.3 in p-measure constitute 92.67 % of all cell events.
Furthermore, if the p-measure cutoff were to increase to 0.5, the percentages of cells left for the
network-justified and mean-justified cases are 6.25% and 75.16%, respectively. The network-
justified case yields drastically lower numbers of cell events in the purer PAC subpopulations
because the means approach has more heterogeneity in the linkages (defined as PAC-
subpopulation participants in each shared clade with size of at least 2). In fact, the network
approach has 100 linkages while the means approach has 209 linkages. Therefore, the extra
linkages in the means approach would yield greater impurities in the network-justified case. The
linkage plot (S6a Fig) shows that the low linkages occur slightly more frequently for the network
approach. One consequence is that the network approach aggregates PAC subpopulations within

sample more frequently; for instance, in the thymus sample, the network approach yields 14 clades while the means approach yields 21 clades.

After aggregating, the clade sizes (with unique participants per sample) are plotted (S6b Fig). The network approach tends to find fewer linkages, as more clades have sizes of less than 4, while the means approach has more clades than the network approach with clade sizes greater than 4. The network approach is more conservative due to the additional constraints from network structures. Conventionally, in the cytometry field, only the means are considered in the definition of cellular states. Assuming the absence of batch and dynamic effects, the researcher could view the purer shared clade assignments in the network-justified case (general agreement between constrained network approach and means approach) as more reliable candidates of cross-sample relationships to investigate in future experiments (S6c Fig).

Hence, the network alignment approach is in agreement that of the means approach, with network alignment being more stringent in the establishment of linkages. The network PAC-MAN approach defines cellular states with the additional information from network structures, and it has the effect of constraining the number of linkages between samples while finding linkages for subpopulations that are distant in their means.

Network hubs provide natural annotations

To further characterize the cell types, we annotate the clades within each sample using the top network hub markers, which constrain the cellular states. The full annotation, along with mean average expression profiles, is presented in S3 Table. The clade information is presented in the ClusterID column. The annotations for cells across different samples but within the same clades share hub markers. For example, in clade 1 for the blood and bone marrow samples, the cells share the hub markers Ly6C and CD11b. In the bone marrow sample, one important set of subpopulations is the hematopoietic stem cell subpopulations. One such subpopulation is present as clade 18 with the annotation CD34-CD27-cKit-Sca1 and is about 1.87 percent in the bone marrow sample. Clade 18 is only present in the bone marrow sample, indicating that the PAC-MAN pipeline defines this as a sample-specific and coherent subpopulation using dataset-level variation. The thymus contains a large subpopulation (84.07 percent) that is characterized as CD5-CD4-CD43-CD3, suggesting it to be the maturing T-cell subpopulation.

Conclusion

We have presented the PAC-MAN data analysis pipeline. This pipeline was designed to remove major roadblocks in the utilization of existing and future CyTOF datasets. First, we established a quick and accurate clustering method that closely matches expert gating results; second, we demonstrated the management of multiple samples by handling mean shifts and batch effects across samples. The alignment allows researchers to find relationships between cells across samples without resorting to pooling of all data points. PAC-MAN allows the cytometry field to harvest information from the increasing amount of CyTOF data available. It is important to standardize multi-sample data analysis with automation so that discoveries based on multi-sample CyTOF datasets from different laboratories do not depend on the experts' manual gating strategies and the grouping of subpopulations that is constrained by non-systematic computations. Furthermore, due to PAC-MAN's generality, this pipeline can be utilized to analyze large datasets of high-dimension beyond the cytometry field.

Materials and Methods

Partition-assisted clustering has two parts

1) Partitioning: a partition method (BSP[5] or DSP[7]) is used to learn N initial cluster centers from the original data.

2) Post-processing: A small number (m) of k-mean iterations is applied to the rectangle-based clusters from the partitioning, where m is a user-specified number. We used m=50 in our examples. After this k-means refinement, we merge the N clusters hierarchically until the desired number of clusters (this number is user-specified) is reached. The merging is based on a given distance metric for clusters. In the current implementation, we use the same distant metric as in flowMeans[1]. That is, for two clusters X and Y, their distance $D(X, Y)$ is defined as:

$$D(X, Y) = \min\left\{(\bar{x} - \bar{y})^T S_x^{-1}(\bar{x} - \bar{y}), (\bar{x} - \bar{y})^T S_y^{-1}(\bar{x} - \bar{y})\right\} \qquad (1)$$

where $\bar{x}, \bar{y}$ are the sample mean of cluster X and Y, respectively. S_x^{-1} is the inverse of the sample covariance matrix of cluster X. S_y^{-1} is defined similarly. In each step of the merging process, the two clusters having the smallest pairwise distance will be merged together into one cluster.

Partition Methods

There are two partition methods implemented in the comparison study: d-PAC and b-
PAC. The results are similar, with d-PAC being the faster algorithm. Fig 1a illustrates this
recursive process.

d-PAC is based on the discrepancy density estimation (DSP)[7]. Discrepancy, which is
widely used in the analysis of Quasi-Monte Carlo methods, is a metric for the uniformity of
points within a rectangle. DSP partitions the density space recursively until the uniformity of
points within each rectangle is higher than some pre-specified threshold. The dimension and the
cut point of each partition are chosen to approximately maximize the gap in uniformity of two
adjacent rectangles.

BSP + LL is an approximation inference algorithm for Bayesian sequential partitioning density
estimation (BSP)[5]. It borrows ideas from Limited-Look-ahead Optional Pólya Tree (LL-OPT),
an approximate inference algorithm for Optional Pólya Tree[8]. The original inference algorithm
for BSP looks at one level ahead (i.e. looking at the possible cut points one level deeper) when
computing the sampling probability for the next partition. It then uses resampling to prune away
bad samples. Instead of looking at one level ahead, BSP + LL looks at h levels ahead (h > 1)
when computing the sampling probabilities for the next partition and does not do resampling (Fig
1b). In other words, it compensates the loss from not performing resampling with more accurate
sampling probabilities. For simplicity, 'BSP + LL' is shortened to 'BSP' in the rest of the article.

F-measure

We use the F-measure for comparison of clustering results to ground truth (known in
simulated data, or provided by hand-gating in real data). This measure is computed by regarding
a clustering result as a series of decisions, one for each pair of data points. A true positive
decision assigns two points that are in the same class (i.e. same class according to ground truth)
to the same cluster, while a true negative decision assigns two points in different classes to
different clusters. The F-measure is defined as the harmonic mean of the precision and
recall. Precision P and recall R are defined as:

559
$$P = \frac{TP}{TP+FP} \tag{2}$$

560
$$R = \frac{TP}{TP+FN} \tag{3}$$

where TP is the total number of true positives, FP is the total number of false positives and FN is
the total number of false negatives.

F-measure ranges from 0 to 1. The higher the measure, the more similar the estimated
cluster result is to the ground truth. This definition of F-measure is different than that of
FlowCAP challenge[2]. The use of co-assignment of labels in this definition is a more accurate
way to compute the true positives and negatives.

Purity-measure (p-measure)

Most of the existing measurements for clustering accuracy aim at measuring the overall
accuracy of the entire datasets, i.e. comparing with the ground truth over all clusters. However,
we are also interested in analyzing how well a clustering result matches the ground truth within a
certain class. Specifically, consider a dataset D with K classes: $\{C_1, C_2, ..., C_K\}$ and a given
ground truth cluster labels g, we construct an index called the purity measure, or p-measure for
short, to measure how well our clustering result matches g for each class C_i. This index is
computed as follows:

1) For each class C_k, look for the cluster that has the maximum number of overlapping points
with this class, denoted by L_{i_k}.

2) Define

$$S_1 = \frac{|C_k \cap L_{i_k}|}{|L_{i_k}|}, S_2 = \frac{|C_k \cap L_{i_k}|}{|C_k|} \tag{4}$$

580 where $|\cdot|$ denotes the number of points in a set.

581 3) The final P-index for class C_k is given by

$$P = \frac{2S_1 S_2}{S_1 + S_2} \tag{5}$$

583 If we were to match a big cluster with a small class, even though the overlapping may be
584 large, S_1 would still be low since we have divided the score by the size of the cluster in S_1. In
585 addition, we are interested in knowing how many points in C_k are clustered together by L_{i_k},
586 which is measured by S_2.

Network construction and comparison

After PAC, the discovered subpopulations typically have enough cells for the estimation
of mutual information. This enables the construction of networks as the basis for cell type
characterization. Computationally, it is not good to directly use the mutual information networks
constructed this way to organize the subpopulations downstream. The distance measure used to
characterize the networks could potentially give the same score for different network structures.

Thus, it is necessary to threshold the network edges based on the strength of mutual information
to filter out the noisy and miscellaneous edges. In this work, these subpopulation-specific
networks are constructed using the MRNET network inference algorithm in the Parmigene [13]
R package. The algorithm is based on mutual information ranking, and outputs significant edges
connecting the markers. The top *d* edges (*d* is set to be 1x the number of markers in all examples)
are used to define a network for the subpopulation. This process enables a careful calculation of
the distance measure.

For each pair of subpopulation networks, we calculate a network distance, which is
defined as follows. If G_1 and G_2 are two networks, let S be the set of shared edges and A be
union of the of the edges in the two networks, then we define

$$604 \quad \text{Similarity}(G_1, G_2) = \frac{|S|}{|A|} \quad\quad\quad (6)$$

where $|\cdot|$ denotes the size of a set.

This is known as the Jaccard coefficient of the two graphs. The Jaccard distance, or 1-
Jaccard coefficient, is then obtained. This is a representation of the dissimilarity between each
pair of networks; the Jaccard dissimilarity is the measure used for the downstream hierarchical
clustering.

Cross-sample linkage of subpopulations

We perform agglomerative clustering of the pool of subpopulations from all samples.
This clustering procedure greedily links networks that are the closest in Jaccard dissimilarity, and
yields a dendrogram describing the distance relationship between all the subpopulations. We cut
the dendrogram to obtain the *k* clades of subpopulations. Subpopulations from the same sample
and falling into the same clade are then merged into a single subpopulation (Fig 5). This merging
step has the effect of consolidating the over-partitioning in the PAC step. No merging is
performed for subpopulations from different samples sharing the same clade. In this way, we
obtain *k* clades of subpopulations, with each clade containing no more than one subpopulation
from each sample. We regard the subpopulations within each clade as being linked across
samples.

In the above computation, only subpopulations with enough cells to define a stable
covariance are used for network alignment via the Jaccard distance; the rest of the cell events
from very small subpopulations are then merged with the closet clade by marker profile via
distance of mean marker signals. If the small subpopulations are distant from the defined clades,
then a new sample-specific clade is created for these small subpopulations.

Annotation of Subpopulations

To annotate the cellular states, we first apply PAC-MAN to learn the dataset-level
subpopulation/clade labels. Next, these labels are used to learn the representative/clade networks.
The top hubs (i.e. the most connected nodes) in these networks are used for annotation. This
approach has biological significance in that important markers in a cellular state are often central
to the underlying marker network, which is analogous to important genes in gene regulatory
networks; these important markers have many connections with other markers. If the connections
were broken, the cell would be perturbed and potentially driven to other states.

Running Published Methods

To run t-SNE [14] a dimensionality reduction visualization tool, we utilized the scripts
published here (https://lvdmaaten.github.io/tsne/). Default settings were used.

To run SPADE, we first converted the simulated data to fcs format using Broad
Institute's   free   CSVtoFCS   online   tool   in   GenePattern[15]
(http://www.broadinstitute.org/cancer/software/genepattern#).

Next, we carried out the tests using the SPADE package in Bioconductor R[16]
(https://bioconductor.org/packages/release/bioc/html/spade.html).

To run flowMeans, we carried out the tests using the flowMeans package in
Bioconductor R[1] (https://bioconductor.org/packages/release/bioc/html/flowMeans.html).

In the comparisons, we selected only cases that work for all methods to make the tests as
fair as possible.

To calculate the mutual information of the subpopulations, we use the infotheo R package
(https://cran.r-project.org/web/packages/infotheo/index.html).

To run network inference, we use the mrnet algorithm in the parmigne R package [13].
(https://cran.r-project.org/web/packages/parmigene/index.html).

Code Availability

655 The PAC R package can be accessed at: https://cran.r-project.org/web/packages/PAC/index.html

Simulated Data for Clustering Analysis

To compare the clustering methods, we generated simulated data from Gaussian Mixture Model varying dimension, the number of mixture components, mean, and covariance. The dimensions range from 5 to 39. The number of mixture components is varied along each dimension. The mean of each component was generated uniformly from a d-dimensional hypercube; we generated datasets using hypercube of different sizes, but kept all the other attributes the same. The covariance matrices were generated as AA^T, where A is a random matrix whose elements were independently drawn from the standard normal distribution. The sizes of the simulated dataset range from 100k to 200k.

The simulated data are provided as (Datasets 1-6). Datasets 1-4 are for the PAC part. Dataset 1 contains data with 5 dimensions; Dataset 2 contains data with 10 dimensions; Datasets 3a and 3b contain data with 20 dimensions; and Datasets 4a and 4b contain data with 35 dimensions. The ground truth labels are included as separate sheets in each dataset.

When applying flowMeans, SPADE, and the PAC to the data, we preset the desired number of subpopulations to that in the data to allow for direct comparisons.

Gated Flow Cytometry Data

Two data files were downloaded from the FlowCAP challenges[2]. One data file is from the Hematopoietic stem cell transplant (HSCT) data set; it has 9,936 cell events with 6 markers, and human gating found 5 subpopulations. Another data file is from the Normal Donors (ND) data set; it has 60,418 cell events with 12 markers, and human gating found 8 subpopulations. The files are the first ('001') of each dataset. These data files were all 1) compensated, meaning that the spectral overlap is accounted for, 2) transformed into linear space, and 3) pre-gated to remove irrelevant events. We used the data files without any further transformation and filtering. When applying flowMeans, SPADE, and the PAC to the data, we preset the desired number of subpopulations to that in the data to allow for direct comparisons.

Gated Mass Cytometry Data

Human gated mass cytometry data was obtained by gating for the conventional immunology cell types using the mouse bone marrow data recently published[11]. The expert gating strategy is provided as Fig S1. The gated sample subset contains 64,639 cell events with 39 markers and 24 subpopulations and it is provided as Dataset 7.

To test the performance of different analysis methods, the data was first transformed using the asinh(x/5) function, which is the transformation used prior to hand-gating analysis; For

692 SPADE analysis, we utilize the asinh(x/5) option in the SPADE commands. The post-clustering
693 results from flowMeans, SPADE, b-PAC, and d-PAC were then subsetted using the indexes of
694 gated cell events. These subsetted results are compared to the hand-gated results.

Simulated Data for MAN Analysis

To test the linking of subpopulations, we generated simulated data from multivariate
Gaussian with preset signal levels and randomly generated positive definite covariance matrices.
There are two cases, batch effect and dynamic. Each simulated sample file has five dimensions,
with two of these varying in levels; these are the dimensions that are visualized. Dataset 5
contains the data for general batch effects case and Dataset 6 contains the data for dynamic
effects case. The ground truth labels are included as separate sheets in each dataset.

General batch scenario. Sample 1 represents data from an old instrument (instrument 1) while
sample 2 represents data from a new instrument (instrument 2). There are two subpopulations per
sample. These two subpopulations are the same, but their mean marker levels shifted higher up
in sample 2 due to higher sensitivity of instrument 2 (Fig 6a). The subpopulations have different
underlying relationships between the markers. In this simulated experiment, five markers were
measured. Out of the five markers, two markers show significant shift, and we focus on these
two dimensions by 2-dimensional scatterplots. In Fig 6a, the left subpopulation in sample 1 is the
same as the left subpopulation in sample 2; the same with the right subpopulation. The same
subpopulations were generated from multivariate Gaussian distributions with changing means
with fixed covariance structure.

Dynamic scenario. Dynamic scenario models the treatment-control and perturbation studies. In
the simulation, we have generated two subpopulations that nearly converge over the time course
(Fig 9). The researcher could lose the dynamic information if they were to combine the samples
for clustering analysis. The related subpopulations were generated from multivariate Gaussian
distributions with changing means with fixed covariance structure.

Raw CyTOF Data Processing

The researcher preprocesses the data to 1) normalize the values to normalization bead
signals, 2) de-barcode the samples if multiple barcoded samples were stained and ran together,
and 3) pre-gate to remove irrelevant cells and debris to clean up the data[10,17]. Gene
expressions look like log-normal distributions[18]; given the lognormal nature of the values, the
hyperbolic arcsine transform is applied to the data matrix to bring the measured marker levels
(estimation of expression values) close to normality, while preserving all data points. Often,

researchers use the asinh(x/5) transformation, and we use the same transformation for the
CyTOF datasets analyzed in this study.

Mouse Tissue Data

In the Spitzer et al., 2015 dataset[11], three mouse strains were grown, and cells were
collected from different tissues: thymus, spleen, small intestine, mesenteric lymph node, lung,
liver, inguinal lymph node, colon, bone marrow, and blood. In each experiment, 39 expression
markers were monitored. The authors used the C57BL6 mouse strain as the reference[11]; the
data was downloaded from Cytobank, and we performed our analysis on the reference strain.

First, all individual samples were filtered by taking the top 95% of cells based on DNA
content and then the top 95% of cells based on cisplatin: DNA content allows the extraction of
good-quality cells and cisplatin level (low) allows the extraction of live cells. Overall, the top
90% of cell events were extracted. The filtered samples were then transformed by the hyperbolic
arcsine (x/5) function, and merged as a single file, which contains 13,236,927 cell events and 39
markers per event (S2 Table).

Using PAC-MAN, we obtained 35 subpopulations in each sample then 80 clades for the
entire dataset. The 80 clades account for the traditional immune subpopulations and sample-
specific subpopulations. Small subpopulations not used in alignment are later merged into the
closest clades; this is done by performing hierarchical clustering with the marker signals to
obtain 5 "expression" subclades per sample. Subsequently, any clade with less than 100 cells is
discarded. Subpopulation proportion heatmap was plotted to visualize the subpopulation-
specificities and relationships across the samples. Finally, annotation was performed using the
hub markers of each representative subpopulation in each sample.

Acknowledgements

We thank the members of Wong Lab, in particular Tung-yu Wu, Chen-yu Tseng and Kun
Yang, for critical feedback.

References

1. Aghaeepour N, Nikolic R, Hoos HH, Brinkman RR. Rapid cell population identification in flow cytometry data. Cytometry A. 2011 Jan 1;79A(1):6–13.

2. Aghaeepour N, Finak G, Consortium TF, Consortium TD, Hoos H, Mosmann TR, et al. Critical assessment of automated flow cytometry data analysis techniques. Nat Methods. 2013 Mar;10(3):228–38.

3. Qiu P, Simonds EF, Bendall SC, Gibbs Jr KD, Bruggner RV, Linderman MD, et al. Extracting a cellular hierarchy from high-dimensional cytometry data with SPADE. Nat Biotechnol. 2011 Oct;29(10):886–91.

4. Wong WH, Ma L. Optional Pólya tree and Bayesian inference. Ann Stat. 2010 Jun;38(3):1433–59.

5. Lu L, Jiang H, Wong WH. Multivariate Density Estimation by Bayesian Sequential Partitioning. J Am Stat Assoc. 2013 Dec 1;108(504):1402–10.

6. Yang K, Wong WH. Discovering and Visualizing Hierarchy in the Data. ArXiv14034370 Stat [Internet]. 2014 Mar 18 [cited 2015 Nov 27]; Available from: http://arxiv.org/abs/1403.4370

7. Yang K, Wong WH. Density Estimation via Adaptive Partition and Discrepancy Control. ArXiv14041425 Stat [Internet]. 2014 Apr 4 [cited 2015 Nov 27]; Available from: http://arxiv.org/abs/1404.1425

8. Jiang H, Mu JC, Yang K, Du C, Lu L, Wong WH. Computational Aspects of Optional Pólya Tree. J Comput Graph Stat. 2015 Feb 13;0(ja):00–00.

9. Samusik N, Good Z, Spitzer MH, Davis KL, Nolan GP. Automated mapping of phenotype space with single-cell data. Nat Methods. 2016 Jun;13(6):493–6.

10. Finck R, Simonds EF, Jager A, Krishnaswamy S, Sachs K, Fantl W, et al. Normalization of mass cytometry data with bead standards. Cytometry A. 2013 May 1;83A(5):483–94.

11. Spitzer MH, Gherardini PF, Fragiadakis GK, Bhattacharya N, Yuan RT, Hotson AN, et al. An interactive reference framework for modeling a dynamic immune system. Science. 2015 Jul 10;349(6244):1259425.

12. Samusik N, Good Z, Spitzer MH, Davis KL, Nolan GP. Automated mapping of phenotype space with single-cell data. Nat Methods. 2016 Jun;13(6):493–6.

13. Sales G, Romualdi C. parmigene—a parallel R package for mutual information estimation and gene network reconstruction. Bioinformatics. 2011 Jul 1;27(13):1876–7.

792   14.   Maaten L van der, Hinton G. Visualizing Data using t-SNE. J Mach Learn Res.
793   2008;9(Nov):2579–605.

794   15.   Reich M, Liefeld T, Gould J, Lerner J, Tamayo P, Mesirov JP. GenePattern 2.0. Nat Genet.
795   2006 May;38(5):500–1.

796   16.   Linderman MD, Bjornson Z, Simonds EF, Qiu P, Bruggner RV, Sheode K, et al.
797   CytoSPADE: high-performance analysis and visualization of high-dimensional cytometry
798   data. Bioinformatics. 2012 Sep 15;28(18):2400–1.

799   17.   Zunder ER, Finck R, Behbehani GK, Amir ED, Krishnaswamy S, Gonzalez VD, et al.
800   Palladium-based mass tag cell barcoding with a doublet-filtering scheme and single-cell
801   deconvolution algorithm. Nat Protoc. 2015 Feb;10(2):316–33.

802   18.   Bengtsson M, Ståhlberg A, Rorsman P, Kubista M. Gene expression profiling in single cells
803   from the pancreatic islets of Langerhans reveals lognormal distribution of mRNA levels.
804   Genome Res. 2005 Oct 1;15(10):1388–92.

Supporting Information

S1 Fig. Gating strategy of CyTOF data for methods comparison. Biaxial gating hierarchy for the mouse bone marrow CyTOF dataset. Gating strategy that was used to find 24 reference populations in the mouse bone marrow CyTOF data. Pre-gating step involved removal of doublets, dead cells, erythrocytes and neutrophils. Non-neutrophils population was either subject to cluster analysis by computational tools or subsequent gating. Dotted boxes represent 24 terminal gates that were selected as reference populations for the comparison analysis.

S2 Fig. Subpopulation purity of simulated and real CyTOF data. (a) Subpopulation-specific purity plot of 35-dimensional simulated data with 10 subpopulations. The blue points denote the differences between the p-measures of the partition-based method (either d-PAC or b-PAC) and flowMeans, while the red points denote the p-measure differences between the partition methods and SPADE. The horizontal line at 0 means no difference between the methods. Most of the blue and red points are above 0, indicating that the PAC generates purer subpopulations compared to the ground truth. The two subplots are very similar, which means that d-PAC and b-PAC give very similar p-measures. More precisely, the sum of differences between d-PAC and flowMeans and d-PAC and SPADE are 0.85 and 1.09, respectively; and the overall difference between b-PAC and flowMeans and b-PAC and SPADE are 0.84 and 1.08, respectively.

(b) Subpopulation-specific purity plot of the hand-gated CyTOF data. The same convention is used as in (S2a Fig). Again, more blue and red points are above 0, indicating that the partition-based methods generate purer subpopulations compared to the ground truth. There is a cluster of points below 0 occurring in the middle of the plot, suggesting that flowMeans and SPADE capture the mid-size subpopulations more similar to hand-gating than the partition-based methods. More specifically, flowMeans does better (p-measure difference of 0.1 or better; difference of less 0.1 is considered practically no difference) with finding subpopulations of GMP, CD8 T cells, MEP, CD4 T cells (compared to d-PAC), and Plasma cells, while SPADE does better with CD19+IgM- B cells, NK cells (compared to d-PAC), CD8 T cells, NKT cells, Basophils, Short-Term HSC, and Plasma cells. However, overall, PAC has a much better performance, as the absolute sum of points above 0 is higher than that of points below 0. More precisely, the sum of differences between d-PAC and flowMeans and d-PAC and SPADE are 1.21 and 1.45, respectively; and the overall difference between b-PAC and flowMeans and b-PAC and SPADE are 2.06 and 2.31, respectively. The difference table is provided in S1 Table.

S3 Fig. Networks inferred from subpopulations in the dynamic example simulated dataset. Fig 9 introduced the dynamic example in which five samples each having 2 true subpopulations captures the almost-convergence of means. Here the underlying network structures for the PAC discovered subpopulations (three per sample) are presented.

S4 Fig. Comparison between aligning cross-sample subpopulations by network, expression profile, or both. (a) PAC can be used to discover more subpopulations, with the effect of more partitions from the true clusters. (b) When over-partitioning is present, network or expression profile alone cannot resolve the dynamic (or batch) effects due to noisy covariance for small fragments of distributions. However, first aligning the larger subpopulations with more stable covariance, and thus network structures, and then merge in the smaller subpopulations by expression profile resolves the effects. (c) If more irrelevant edges were introduced, network alignment would fail due to the negative impact of the miscellaneous edges; however, eliminating small subpopulations from the alignment step alleviates the increased edge count problem.

S5 Fig. PAC-MAN style linkage by means. (a) t-sne plots of mouse tissue samples colored by representative subpopulations labels from linkage by means. (b) Subpopulation proportion heatmap of clades of samples from linkage by means.

S6 Fig. Comparison between network and means PAC-MAN. (a) PAC-discovered subpopulations are aggregated by MAN into clades; the number of PAC subpopulations/clades for the network and means PAC-MAN approaches are plotted. (b) After aggregating shared clades within samples, the number of shared clades for the entire dataset is plotted for the two PAC-MAN approaches. c) Using the network approach results as basis, the clades with strong agreement (high p-measures) with the means PAC-MAN approach are given. The shared clades (present in more than one sample) are reliable candidates for future experiment to find cross-sample relationships.

S1 Table. Purity (p) Measure Differences in CyTOF Comparison. p-measure differences in gated CyTOF data analysis comparison. The differences are shown for all the annotated cell subpopulations, which are ordered by their sizes. Overall, the PAC methods give more positive p-measures.

S2 Table. Sample Sizes in Mouse Tissue CyTOF Dataset. The numbers of cells in the samples of Spitzer et al., 2015 CyTOF dataset. The data is from the C57BL6 mouse strain and a total of ten tissue samples are present. The raw column shows the number of cells prior to filtering by DNA and cisplatin values. The final cell counts are shown in the filtered file (3^{rd}) column.

S3 Table. PAC-MAN Subpopulation Characterization Output for Mouse Tissue CyTOF Dataset. The full set of annotated results, along with mean expressions, subpopulation proportion and counts, are reported.

S4 Table. Network-justified and means-justified p-measures for Alignments of PAC-discovered Subpopulations. The PAC-discovered subpopulations were mapped as clades in both the network and means PAC-MAN approaches. The p-measures were calculated for the cases 1) network approach mapping as the basis and 2) means approach mapping as the basis. The comparison is the same in principle to the comparison of labels for clustering methods. The results are ordered by p-measures.

a

BSP   DSP

b

VS.

c

Partitioned Data Space

V2

V1

a

Comparision of Different Initializations: Total Sum of Squares

b

Comparision of Different Initializations: F-measure

a

All Samples, Rep Clades by Networks

Clade Size
● 8124
● 11876

Cluster Dendrogram

b

All Samples, Rep Clades by GeneExp and Networks

Clade Size
● 10005
● 9995

Cluster Dendrogram