Transformation from independent to integrative coding of multi-object arrangements

in human visual cortex

Daniel Kaiser[1,2,*], Marius V. Peelen[1]

[1]*Center for Mind/Brain Sciences, University of Trento, 38068 Rovereto (TN), Italy*

[2]*Institute of Psychology, Freie Universität Berlin, 14195 Berlin-Dahlem, Germany*

[*]Correspondence to:

Daniel Kaiser

Institute of Psychology, Freie Universität Berlin

Habelschwerdter Allee 45, 14195 Berlin-Dahlem, Germany

danielkaiser.net@gmail.com

Abstract

The human visual system has adapted to process cluttered scenes containing dozens of regularly arranged objects. The regularity among objects critically contributes to the efficiency of naturalistic vision. Recent studies investigating multiple object perception have demonstrated that visual cortex responses to multi-object displays can be accurately modeled by a linear combination of responses to individual objects, revealing independent processing of simultaneously presented objects. Here we use fMRI to show that this independence partly breaks down when objects are positioned according to frequently experienced configurations. Participants viewed pairs of objects that formed minimalistic two-object scenes (e.g., a "living room" consisting of a sofa and television) presented in their regularly experienced spatial arrangement or in an irregular arrangement (with interchanged positions). Additionally, single objects were presented centrally and in isolation. Multi-voxel activity patterns evoked by the object pairs were modeled as the average of the response patterns evoked by the two single objects forming the pair. In two experiments, this approximation in object-selective cortex (OSC) was significantly less accurate for the regularly than the irregularly positioned pairs, indicating integration of individual object representations. More detailed analysis revealed a transition from independent to integrative coding along the posterior-anterior axis of the visual cortex, with the independent component (but not the integrative component) being almost perfectly predicted by object selectivity across the visual hierarchy. These results reveal a transitional stage between individual object and multi-object coding in visual cortex, providing a possible neural correlate of efficient processing of regularly positioned objects in natural scenes.

Introduction

Our everyday environments are cluttered, consisting of a large number of separable objects. It is therefore of fundamental importance to understand how the visual system processes the multitude of objects contained in real-world scenes in an efficient way.

However, much of our knowledge about the neural mechanisms of object perception comes from neuroimaging studies using single objects as stimuli. These studies have linked object perception to activity in object-selective cortex (OSC), a region which preferentially responds to objects compared to scrambled objects (Grill-Spector, 2003; Malach et al., 1995) and exhibits reliably discriminable response patterns for different types of objects (Eger et al., 2008; Haxby et al., 2001; Kriegeskorte et al., 2008). Further neuroimaging work has demonstrated that OSC responses show some degree of size- and location-invariance (Cichy et al., 2011; Vuilleumier et al., 2002) and party reflect perceived rather than physical object properties (Haushofer et al., 2008; Kourtzi and Kanwisher, 2001), suggesting that OSC activation can be linked to behavioral performance in object recognition (Grill-Spector et al., 2000; Williams et al., 2007).

Recently, studies have moved towards more naturalistic conditions, measuring OSC responses when multiple objects are presented simultaneously. These studies have demonstrated that OSC codes multiple objects in an independent, linearly additive way: Responses to pairs of objects could be modeled as a linear combination (e.g., the average) of the responses to their constituent single objects (Agam et al., 2010; Baeck et al., 2013; Kaiser et al., 2014b; Kubilius et al., 2015; MacEvoy and Epstein, 2009; Reddy et al., 2009; Zoccolan et al., 2005), even when the objects were embedded in complex natural scenes (MacEvoy and Epstein, 2011).

Importantly, however, individual objects in natural scenes usually adhere to

typical and recurring positional structures: constrained by their function, their

relationship with other objects, and physical properties of the world, objects appear in

predictable locations relative to each other (e.g., sofas facing TV sets, or cars stopping in

front of traffic lights). Previous research has demonstrated that such inter-object

regularities facilitate behavioral performance in capacity-limited tasks (Bar, 2004; Chun,

2000; Kaiser et al., 2014a; Oliva and Torralba, 2007; Wolfe et al., 2011), suggesting that

regularly positioned object arrangements are more efficiently processed at a neural level.

In the current study, we provide evidence that the visual system integrates

representations of regularly positioned objects, revealing a transformation from

independent to integrative coding of multiple objects along the posterior-anterior axis of

the visual processing hierarchy.

In two fMRI experiments, participants viewed pairs of objects that formed

minimalistic versions of scenes (e.g., a "living room", consisting of a sofa and a TV; Fig. 1,

A). These pairs could be arranged in a regular, typically encountered way (e.g., the sofa

facing the TV) or in an irregular way (with the two objects exchanged). Additionally, each

single object was presented centrally and in isolation. The multi-voxel response pattern

evoked by each pair was then modeled by the average of the patterns evoked by its

constituent objects. Replicating previous observations (Kaiser et al., 2014b; Kubilius et al.,

2015; MacEvoy and Epstein, 2009, 2011), we find that OSC response patterns evoked by a

pair can be accurately predicted by the average response patterns evoked by its

constituent objects. Crucially, however, this linear approximation of the pair response

depended on the relative position of the objects: Pair approximation in OSC was less

accurate for regularly positioned pairs than for irregularly positioned pairs, showing that

the independence of multiple object processing breaks down when objects are

positioned regularly. More detailed analyses revealed a transformation from

independent to integrative representations of regularly positioned object pairs along the

posterior-anterior axis of the visual cortex. The integrative component of multi-object

processing reflects an emerging tuning to positional structures in real-world scenes.

Materials and Methods

Participants

Fifteen healthy adults (6 male; mean age 24.6 years, SD=3.3) took part in

Experiment 1, and 16 healthy adults took part in Experiment 2 (8 male; mean age 24.7

years, SD=3.0). All participants had normal or corrected-to-normal visual acuity. All

procedures were carried out in accordance with the Declaration of Helsinki and were

approved by the ethical committee of the University of Trento. Due to excessive head

movement, one participant was excluded from Experiment 1. Two participants were

excluded from Experiment 2, one due to excessive head movement, and one due to bad

functional localizer data, not allowing for a reliable definition of object-selective voxels.

Stimuli

The stimulus set comprised four pairs of objects, which each depicted a

minimalistic version of a scene (Fig. 1, **A**). The four scenes were bathroom (toilet and

sink), living room (sofa and television), street crossing (car and traffic lights), and

playground (seesaw and slide). The stimuli were created by cutting the stimuli directly

from a complete scene images, leaving the size and position the same as in the original

scene ("regular" condition). For each scene, a second version was created where the

object positions were swapped ("irregular" condition). These irregular versions

contained the same objects, but the arrangement did not follow the typical arrangement

normally experienced in scenes. For each pair, a total of eleven different stimuli were

used. In addition to the pair stimuli we also showed the eight single objects centrally, and

in isolation. For Experiment 2, additionally a set of 22 scenes (11 indoor rooms, 11 outdoor

street scenes) was used; none of these scenes contained any of the objects that

constituted the pairs. All stimuli were surrounded by a black frame, which subtended a

visual angle of 10° X 7.5°. Stimulus presentation was controlled using MATLAB and

Psychtoolbox (Brainard, 1997). The stimulation was back-projected onto a translucent

screen placed at the end of the scanner bore. Participants viewed the screen through a

tilted mirror mounted to the head coil.

Experiment 1 procedure

The experiment consisted of multiple runs of 5 minutes each. Half of the runs

were object pair runs, and half of the runs were single object runs. During object pair

runs, the four different pair types (bathroom, living room, street crossing, playground)

were shown in each of the two conditions (regular and irregular). During single object

runs, all constituent single objects were shown. Each run consisted of 18 blocks. Within

each block, twelve stimuli were presented, with each stimulus being an exemplar of the

same condition (e.g., a bathroom/irregular block would contain only bathroom pairs in

irregular configuration). Each block contained all eleven pairs (i.e., exemplars) of a

specific condition, and one-back image-level repetition of a specific pair (i.e., exemplar).

Each stimulus was shown for 400ms, with an inter-stimulus-interval of 900ms (Fig. 1, **B**);

each block thus lasted 15.6s. The first nine blocks of each run consisted of eight

stimulation blocks and one block of fixation baseline (in randomized order). The second

nine blocks of a run were the same blocks in mirror-reversed order. The experiment

comprised ten runs (two participants only completed eight runs), always starting with a

pair run and then alternating between single object and pair runs. Participants had to

report one-back image repetitions by pressing a button.

Fig. 1. Stimuli and paradigm. **A**, For Experiment 1, four pairs of objects were collected by

directly cropping them from scenes of four types (bathroom, living room, street crossing,

playground). Object pairs could be positioned in a regular way (as they appeared in the

scenes) or in an irregular way (with their positions exchanged). In Experiment 2, only the

living room and street crossing pairs were used and, in separate blocks, participants saw

images of natural scene images (indoor room versus outdoor street scenes). **B**, Stimuli

were presented for 400ms, separated by inter-stimulus intervals of 900ms. In each

stimulation block, only pairs from one category and one regularity condition appeared

(e.g., regularly positioned cars and traffic lights). Participants responded to one-back

image-level repetitions. Similarly, the single objects belonging to the pairs were

presented in separate runs, using the same block design and task.

Experiment 2 procedure

The procedure in Experiment 2 was identical to experiment 2 unless otherwise

noted. In Experiment 2, only two of the object pairs were used (living room and street

crossing). Additionally, in separate runs, the natural scene stimuli were presented (Fig. 1,

A). These runs had an identical structure to the pair and single object runs. In alternating

order, only indoor rooms or outdoor street scenes appeared in a single block. In total,

Experiment 2 consisted of 9 runs (3 pair runs, 3 single object runs, 3 scene runs), always

starting with a pair run, followed by a single object run and by a scene run (this order was

repeated three times).

Functional localizer

In both experiments, participants additionally completed two functional localizer

runs of five minutes each. Participants performed a one-back task while viewing images

of faces, houses, everyday objects, and phase-scrambled versions of these objects. Each

stimulus category included 36 individual exemplars. Within each run, there were four

blocks of each stimulus category and four blocks of fixation baseline, with all blocks

lasting 16s. Block order was randomized for the first ten blocks and then mirror-reversed

for the remaining ten blocks. Each non-fixation block included two one-back stimulus

repetitions.

fMRI data acquisition and preprocessing

MR imaging was conducted using a Bruker BioSpin MedSpec 4T head scanner

(Bruker BioSpin, Rheinstetten, Germany), equipped with an eight-channel head coil.

During the experimental runs, T2*-weighted gradient-echo echo-planar images (EPI)

were collected (repetition time TR=2.0s, echo time TE=33ms, 73° flip angle, 3 x 3 x 3mm

voxel size, 1mm gap, 34 slices, 192mm field of view, 64×64 matrix size). Additionally, a T1-

weighted image (MPRAGE; 1 x 1 x 1mm voxel size) was obtained as a high-resolution

anatomical reference. All resulting data were preprocessed using MATLAB and SPM8. EPI

volumes were realigned and coregistered to the structural image. Functional volumes

collected during the functional localizer runs were additionally smoothed with a 6mm

full-width-half-maximum Gaussian kernel.

Region on interest definition

The BOLD-signal of each voxel in each participant in the localizer runs was

modeled using one regressor for each stimulus category, and six regressors for the

movement parameters obtained from the realignment procedure. Object-selective

cortex (OSC) (Malach et al., 1995) was localized using an object>scrambled contrast.

Regions for both hemispheres were concatenated to form a bilateral ROI (Experiment 1:

mean ROI size 1000 voxels, SE=35; Experiment 2: mean ROI size 1036 voxels, SE=45).

Additionally, an early visual cortex (EVC) ROI was defined by inverse-normalizing an

anatomical mask into individual-subject space (Experiment 1: mean ROI size 996 voxels,

SE=8; Experiment 2: mean ROI size 969 voxels, SE=9). For both ROIs, an additional voxel

selection criterion was adopted: as we expected that optimally pair-selective voxels

allow for better approximation of the pair patterns by single-object patterns (Baeck et

al., 2013; MacEvoy and Epstein, 2009), the OSC and EVC ROIs were intersected with

voxels that could optimally discriminate between the different pairs. These voxels were

selected from a whole-brain searchlight classification analysis (see below). A-priori, a

voxel count of the 100 most pair-selective voxels was set for all analyses; to rule out that

the results were specific to this particular number of selected voxels, the analysis was

repeated with different voxel counts ranging from 20 to 500 (see Supplementary

Information). For results obtained with a different selection method and for the results in

scene-selective regions see the Supplementary Information.

Univariate Analysis

The BOLD-signal of each voxel in each participant was modeled using one

regressor for each stimulus type, and six regressors for the movement parameters

obtained from the realignment procedure. Activation differences were computed by

averaging beta-weight estimates across voxels for each ROI. Significant differences

between the regularly and irregularly positioned pairs were assessed using t-tests.

Multi-voxel pattern analysis

Multivariate pattern analysis (MVPA) was carried out on a TR-based level using

the CoSMoMVPA toolbox (Oosterhof et al., 2016). For each voxel belonging to a specific

ROI, TRs corresponding to the conditions of interest were selected by shifting the voxel-

wise time-course of activation by three TRs (to account for the hemodynamic delay).

Subsequently, for each run separately, activation values were extracted from the EPI-

volumes for each TR coinciding with the onset of a specific condition; the activation

values were then normalized by z-scoring the values for each voxel. For the decoding

analyses, linear discriminant analysis (LDA) classifiers were trained on all but one runs,

and tested on the remaining run; this procedure was repeated so that every run was left

out once. Pair classification was also computed in a searchlight decoding analysis (which

was used for guiding ROI definition): for this analysis, a spherical neighborhood of 100

voxels was used to identify voxels in visual cortex that could optimally discriminate the

different object pairs, irrespective of the regularity condition. Significant decoding was

assessed by comparing classifier accuracy to chance performance, using t-tests. For the

pair combination analysis, response patterns were averaged across all TRs belonging to a

specific condition, resulting in a single response pattern for every condition. Single-object

230 response patterns for the two objects belonging to a specific pair (e.g., car and traffic

231 light or sofa and TV) were averaged. Thus, for each pair three response patterns were

232 available: (1) the response pattern evoked by the pair presented in the regular

233 arrangement, (2) the response pattern evoked by the pair presented in the irregular

234 arrangement, and (3) the average response pattern evoked by the two constituent

235 objects. To assess pair approximation quality in the regular and irregular conditions

236 separately, the average single object patterns were correlated to their corresponding

237 pair response patterns (within-correlation) and to the pair patterns evoked by the non-

238 corresponding pairs (between-correlation) (Fig. 2). For the scene approximation analysis

239 in Experiment 2, pair response patterns were correlated with the corresponding scene

240 response patterns (e.g., sofa/TV and indoor room scene; within-correlation) and the non-

241 corresponding scene patterns (e.g., sofa/TV and outdoor street scene; between-

242 correlation), separately for regular and irregular pairs. The difference between these

243 within- and between-correlations was used as a measure of pair approximation quality.

244 Approximation quality was then compared for the regular and irregular pairs by using

245 paired t-tests. All correlations were Fisher-transformed prior to statistical analysis.

Fig. 2. Schematic illustration of the pair approximation analysis. For each ROI, the

response pattern across hemispheres was extracted both for the single object and pair

conditions. The single object patterns corresponding to each pair were then averaged

and correlated with the pair-evoked pattern. The difference between the correlations

with corresponding pairs (within-correlation) and non-corresponding pairs (between-

correlation) was taken as a measure of approximation quality. This analysis was done

separately for the regular and irregular pairs.

Combined searchlight analysis

To characterize the emergence of the regularity effect along the visual processing

hierarchy, we performed a searchlight analysis, where we systematically moved a spatial

voxel neighborhood along the anterior-posterior axis. For this analysis, the data from

both experiments was combined. First, the occipitotemporal cortex (defined based on an

anatomical mask) was divided into 40 slices. Each slice spanned 10mm in the anterior-

posterior (Y) direction, with an inter-slice distance of 2mm (thus, individual slices were

overlapping). X and Z coordinates of the occipitotemporal region were fully covered,

with the exception that the medial parts of occipital cortex were masked out to avoid

sampling of EVC voxels. The 40 slices were then inverse-normalized to individual-

participant space. Separately for each participant, within each slice the 100 voxels that

allowed the most accurate pair decoding in a searchlight analysis were selected (similarly

to the OSC analyses, see above). Subsequently, the pair approximation analysis (see

above) was performed for these 100 voxels within each slice. To assess the general

object-selectivity of the voxels in each slice, we computed the difference between the

GLM beta weights for intact and scrambled object in the functional localizer runs (see

above). To identify slices yielding significant effects, we used a threshold-free cluster-

enhancement procedure (Smith and Nichols, 2009) with default parameters, using

multiple-comparison correction based on a sign-permutation test (with null distributions

created from 10,000 bootstrapping iterations) as implemented in CoSMoMVPA

(Oosterhof et al., 2016). The resulting Z-values were thresholded at $Z > 1.96$ (i.e., $p < 0.05$)

to reveal significant decoding performance.

Results

Experiment 1

To investigate whether positional regularities impact neural responses in object-

selective visual cortex (OSC), we presented participants with pairs of objects that

commonly appear together in real world scenes, such as in a bathroom (toilet and sink),

in a living room (sofa and TV), on a street crossing (car and traffic lights), or at a

playground (seesaw and slide). These objects were directly cut from natural scene

images and presented on a blank background ("regular" condition; Fig. 1, **A**). To

investigate whether the way in which these object typically co-occur in the real world

influences neural responses, we added a condition where we reversed the object

locations ("irregular" condition, Fig. 1, **A**), keeping everything else identical. Additionally,

the single objects belonging to the pairs were presented centrally (Fig. 1, **B**).

Functional MRI analyses primarily focused on two regions of interest: functionally

defined object-selective cortex (OSC) and anatomically defined early-visual cortex (EVC)

(see below for data from scene-selective ROIs). While we expected an effect of regularity

on the representation of object pairs in OSC, no effect was expected in EVC, where more

basic visual analysis takes place. Based on previous work (Baeck et al., 2013; MacEvoy &

Epstein, 2009), we expected stronger effects in areas of OSC that preferentially

represent information about the object pairs. To define voxels that contribute most to

the coding of the object pairs, a whole-brain searchlight analysis was performed (see

Materials and Methods), where linear classifiers were used to discriminate the four

object pairs, regardless of their positioning (i.e., collapsed across the regular and

irregular pairs). Based on this searchlight analysis, within OSC and EVC the 100 voxels

(see Supplementary Information for results with different voxel counts) that contributed

most to the classification of the four pairs were selected (Fig. 3, **A**).

First, we tested whether the four object pairs were reliably discriminable in both

OSC and EVC. Separately for regular and irregular pairs, a multivariate classification

analysis of response patterns across voxels was performed. In a leave-one-run-out

fashion, linear discriminant analysis (LDA) classifiers were used to classify response

patterns to the four different pairs (see Materials and Methods). In both OSC and EVC,

these classifiers performed highly above chance level (OSC: 42%; EVC: 40%). For both

regions, no reliable difference in decoding accuracy was found when comparing the

regular and irregular conditions directly (OSC: $t[13]=0.8$, $p=0.41$; EVC: $t[13]=1.2$, $p=0.25$).

Similarly, no difference in univariate activation values between the two conditions was

observed (OSC: $t[13]=0.7$, $p=0.48$; EVC: $t[13]=1.1$, $p=0.29$). This pattern of results argues

against overall differences in signal quality, for example due to differences in attentional

engagement for the two conditions: such an effect would be expected to result in a

univariate and/or classification difference between the regular and irregular conditions.

Next, we tested whether the average of the response patterns evoked by the

single objects could more accurately approximate the pattern evoked by the

corresponding pairs than the pattern evoked by the non-corresponding pairs: for

example, is the average of the response patterns for cars and traffic lights more similar

to the response pattern for the car and traffic light pair than to the other pairs (e.g., to a

TV and a sofa)? This analysis was performed separately for regular and irregular pairs (Fig.

2). Correlations between the response patterns evoked by object pairs and the average

patterns coming from the corresponding single objects (within-correlations) or from non-

corresponding single objects (between-correlations) were computed (see Materials and

Methods). For both regular and irregular pairs separately, the difference between within-

and between-correlations was taken as a measure of pair approximation quality.

In OSC, both regular and irregular pairs were discriminable using the average

single object patterns (regular: t[13]=6.33, p<0.001; irregular: t[13]=11.2, p<0.001; Fig. 3,

B). Despite the position change of the objects, also EVC patterns allowed for reliably

discriminating between the four pairs (regular: t[13]=6.1, p<0.001; irregular: t[13]=4.7,

p<0.001). Next, to investigate whether regularly positioned pairs were processed

differently from irregularly positioned pairs, discriminability was compared directly for

regular and irregular pairs. Crucially, in OSC the average single object patterns more

closely resembled the response patterns evoked by irregular pairs than by regular pairs

(t[13]=2.5, p=0.02). By contrast, no such difference was found in EVC (t[13]=1.0, p=0.32;

interaction with region: t[13]=2.9, p=0.01). These findings suggest that object processing

in OSC is sensitive to typical real-world positioning.

Fig. 3. Pair approximation results. **A**, Object selective cortex (OSC) and early visual cortex

(EVC) maps depicting voxel-wise overlap between participants: Regions were defined on

a single-subject level by selecting the 100 voxels that best discriminated the four pairs

across the regularity conditions (see Materials and Methods) within either a functional

OSC mask or an anatomical EVC mask. For illustration purposes, the regions were

normalized into standard space and overlaid on a brain template using MRIcron (Rorden

and Brett, 2000). **B,** The pair approximation analysis for Experiment 1 revealed a more

accurate approximation of the irregularly positioned pairs than of the regularly

positioned pairs in OSC, while no effect was found in EVC. **C,** In Experiment 2, this pattern

of results was replicated, demonstrating sensitivity for object regularity structure in OSC,

but not EVC. All error bars reflect standard errors of pairwise differences. (*p<0.05,

**p<0.01)

Experiment 2

In a second fMRI experiment we aimed to replicate the pattern of results. The

structure of the experiment was largely identical to Experiment 1 (see Materials and

Methods) and participants viewed images from two of the pairs also used in Experiment

1 (sofa and TV; car and traffic lights).

First, as in Experiment 1, discriminability of the response patterns for the regular

and irregular pairs was assessed using a two-way linear classification analysis in OSC and

EVC. In both regions, classifiers performed highly above chance level (OSC: 69%; EVC:

64%) and no difference in decoding accuracy was found when comparing the regular and

irregular conditions directly (OSC: $t[13]=0.02$, $p=0.99$; EVC: $t[13]=0.7$, $p=0.51$). Additionally,

no difference was observed in univariate activation values for the two conditions (OSC:

$t[13]=0.01$, $p=0.99$; EVC: $t[13]=1.0$, $p=0.32$).

Second, separately for regular and irregular pairs, constituent single-object

response patterns were averaged for each pair to test how well these average response

patterns could approximate the two pairs. As in Experiment 1, in OSC the average of the

response patterns evoked by the single objects was more similar to the pattern evoked

by the corresponding than by the non-corresponding pairs, both for the regular pairs

(t[13]=11.1, p<0.001) and the irregular pairs (t[13]=11.7, p<0.001; Fig. 3, **C**). By contrast (and

unlike Experiment 1), the average single object patterns did not accurately approximate

the pair patterns in EVC (regular pairs: t[13]=0.8, p=0.44; irregular pairs: t[13]=0.2,

p=0.87). Most importantly, Experiment 2 replicated the key finding of Experiment 1: a

difference between the approximation of regular and irregular pairs in OSC (t[13]=3.4,

p=0.004), with no such difference in EVC (t[13]=0.77, p=0.46; interaction across regions:

t[13]=3.3, p=0.006). These results closely resemble the pattern of results obtained in

Experiment 1, providing further evidence for an influence of positional regularities on

multi-object coding in OSC.

Experiment 2 was additionally designed to test a possible explanation for the

regularity effect: perhaps regularly positioned object pairs more strongly induced a

mental representation of the corresponding scene, thereby distorting the representation

of the individual objects. To test this account, participants viewed images of room scenes

and street scenes during separate blocks of Experiment 2 (Fig. 1, **A**). None of these

scenes contained any of the objects belonging to the pairs. OSC response patterns to

these scenes were reliably discriminable in a two-way classification analysis (mean

accuracy: 64%; t[13]=9.1, p<0.001). To determine whether the relatively inaccurate pair

approximation for regularly positioned pairs in OSC reflected the activation of the

corresponding scene representations (e.g., living room for sofa-TV pairs), we correlated

the activation patterns evoked by the pair stimuli to the activation patterns of the scene

stimuli. Separately for the regular and irregular conditions, this correlation was

computed within scene type (i.e., sofa/TV and indoor room scene, and car/lights and

outdoor street scene) and between scene type (i.e., sofa/TV and outdoor street scene,

and car/lights and indoor room scene). The difference of these within- and between-

correlations was taken as a measure of scene approximation quality. In OSC, this scene

approximation was not significantly different from chance, both for regularly (t[13]=0.4,

p=0.69) and irregularly (t[13]=0.2, p=0.87) positioned pairs and no difference was found

when directly comparing discriminability for regular and irregular pairs (t[13]=0.7,

p=0.50). Similar results were obtained in scene-selective regions of visual cortex (see

Supplementary Information). These results suggest that the differential coding of regular

and irregular pairs in OSC does not reflect a difference in the degree to which they

activate scene representations.

Transformation from independent to integrative coding

The results from Experiments 1 and 2 demonstrate that a linear combination of

single object response patterns accurately predicts the response patterns evoked by

both regularly and irregularly positioned pairs. However, a relative disruption of this

approximation was observed in the regular condition. This pattern of results suggests

that responses to regularly positioned pairs reflect both an independent processing

component and an integrative component that disrupts this independent processing to

some degree. To reveal the transformation from independent to integrative processing

at finer anatomical resolution we tracked the overall approximation quality (reflecting

the independent component of multi-object representations) and the regularity effect

(reflecting the relative disruption of independent coding in the regular condition) along

the visual hierarchy. Combining the data from both experiments, we performed a

searchlight analysis along the posterior-anterior axis of the occipitotemporal cortex (see

Materials and Methods). In brief, anatomically defined occipitotemporal cortex was

divided into slices (width: 10mm) varying along the y-coordinate (in MNI space) in steps

of 2mm (see Fig. 4, **A**). For each of these slices, comparably to the OSC analyses for

Experiments 1 and 2, the 100 best pair-representing voxels were selected based on

individual-participant searchlight maps. Then, for each slice separately, the pair

approximation analysis was repeated, leading to a pair approximation value (within-

correlation vs. between-correlation) and a regularity effect for each slice (Fig. 4, **B**).

Generally, approximation quality across the two regularity conditions (i.e., the mean of

the two conditions) was very robust and significantly above chance for all slices centered

between Y=-100 and Y=-34 (Fig 4, **C**). To detect regularity effects, the difference of the

linear approximation quality in the regular and irregular conditions was compared to

zero. This analysis revealed an effect that emerged between Y=-80 and Y=-84, and later

between Y=-64 and Y=-38 (Fig 4, **D**). This pattern of results shows that highly accurate

linear approximation can be observed at earlier processing stages than the relative

breakdown of this approximation in the regular condition, suggesting that the

integrative multi-object coding for regularly positioned objects is preceded by an

independent representational stage.

To assess how the overall approximation quality and the regularity effect relate to

object selectivity, the difference of the intact and scrambled object conditions in the

functional localizer was computed for each slice (see Materials and Methods). All slices

between Y=-98 and Y=-30 exhibited significant object-selectivity (Fig. 4, **C/D**).

Interestingly, across slices object-selectivity almost perfectly predicted overall

approximation quality (r=0.97, p<0.001). By contrast, object-selectivity did not

significantly predict the regularity effect across slices (r=-0.05, p=0.75). These results

suggest that the independent component of multi-object processing is tightly linked to

the degree of object-selectivity, while the encoding of object regularity emerges later in

the visual hierarchy. In sum, this analysis shows that overall linear approximation

(reflecting the independent component of multi-object processing) and its relative

breakdown (reflecting an effect of positional structure) can be anatomically dissociated,

revealing a transformation from independent to integrative coding of multi-object

displays along the visual processing hierarchy.

Fig. 4. Combined searchlight analysis. **A,** Searchlight analysis was performed for slices of

occipitotemporal cortex (10mm width) with varying y-coordinate, in steps of 2mm. Slices

were defined in standard space (based on MNI coordinates) and back-projected into

individual subject space. Subsequently, within each slice, the 100 best pair-representing

voxels were selected on an individual-participant level. **B,** Pair approximation (expressed

as the difference between within- and between correlations) for regular and irregular

pairs in slices along the y-coordinate. **C,** Overall approximation (i.e., the mean of the

regular and irregular conditions) was generally very accurate throughout the visual

hierarchy, and showed a striking correspondence with the degree of object-selectivity. **D,**

Differences between the regular and irregular conditions emerged starting from Y=-80.

In contrast to the overall approximation, the regularity effects along the hierarchy did

not correspond well with the degree of object-selectivity. (*p<0.05, corrected for

multiple comparisons)

Discussion

In two fMRI experiments, we demonstrate non-independence in the visual cortex representation of multi-object displays, revealing a transformation from independent to integrative representations along the visual processing hierarchy. Response patterns in OSC evoked by regularly positioned object pairs were less accurately modeled by the response patterns evoked by their constituent objects. The relative breakdown of this linear response approximation reflects a disruption of independent multi-object coding when objects adhere to their typical real-world positions. The regularity effect was significant in functionally localized OSC (but not EVC and scene-selective regions; see Supplementary Information). However, further analyses revealed that object selectivity was closely related, along the posterior-anterior axis, to independent object coding rather than integrative object coding, which emerged later in the visual hierarchy.

The searchlight analysis along the posterior-anterior axis of the occipitotemporal cortex suggests that the coding of multiple, regularly positioned objects is reflecting two dissociable components: an independent processing component and an integrative component. Independent processing can be observed starting at early stages of the visual object processing hierarchy, and is tightly linked to object selectivity. The striking correspondence between object-selectivity and pair approximation suggests that the same neural mechanisms support single-object coding and (independent) multi-object coding. By contrast, at later stages of the processing hierarchy, pair approximation quality diverges for regular and irregular pairs, reflecting additional, integrative processing for regularly positioned pairs that (partly) disrupts independent coding. Interestingly, this relative disruption cannot be explained by differences in object-selectivity along the visual hierarchy. We speculate that the independent and integrative

components of multi-object coding are reflecting activity in different sub-regions of

object-selective cortex, with a more posterior sub-region – possibly reflecting LO1

(Larsson and Heeger, 2006) (Y=-90, SE=5) – primarily reflecting independent coding and a

more anterior sub-region – possibly reflecting LO2 (Larsson and Heeger, 2006) (Y=-83,

SE=6) – containing also an integrative component. This assumption is consistent with a

previously reported difference in spatial summation along the posterior-anterior axis,

with a higher rate of information compression in the more anterior LO2 (Kay et al., 2013).

However, further studies employing retinotopic mapping techniques are needed to test

whether the effect can indeed be pinpointed to a specific sub-region of object-selective

occipitotemporal cortex.

The disruption of independent coding observed here is unlikely to reflect

differential semantic associations between objects. Previous electrophysiological studies

have demonstrated that learned associations between objects can alter neural tuning

properties in visual cortex: The associative pairing of two objects can shape neural

responses in a way that neurons become selective to both of the individual objects

(Messinger et al., 2001; Sakai et al., 1991). However, in our study the objects were equally

related in their semantic content in both the regular and irregular conditions – the crucial

difference was the positional structure. Thus, our results are more aptly explained by

visual group representations that are shaped by co-occurrence structure of objects in

real-world environments. Such group representations have been described in the cortical

representation of people, where information from the face and body is integrated into a

person representation, which is sensitive to the correct relative positioning of both parts

(Bernstein et al., 2014; Harry et al., 2016; Schmalzl et al., 2012; but see Kaiser et al., 2014b).

Similarly, regularly positioned objects may be grouped in visual cortex, giving rise to

different response patterns to the whole than the sum of the parts. Further studies are required to probe the nature of these representations at a finer grained level.

A number of previous studies have explored relational coding of objects in the context of action relationships. Some of these studies have reported univariate activation differences between objects positioned correctly or incorrectly for performing a specific action (Kim and Biederman, 2011; Kim et al., 2011; Roberts and Humphreys, 2010). Others have used similar methods as the current study to demonstrate that action relationships alter combination rules in the processing of multiple objects (Baeck et al., 2013; Baldassano et al., 2016). Notably, the regularity effects observed in these studies have been attributed to processing asymmetries favoring the "active" object (e.g., a hammer) over the "passive" object (e.g., a nail) in a pair (Baeck et al., 2013; Riddoch et al., 2003). By contrast, our approach focused on real-world object structure more generally, avoiding such direct functional interactions of the two objects. Furthermore, in our study the positional structure of the object pairs was solely manipulated by exchanging the position of the single objects, without introducing changes of low-level visual characteristics (like physically connecting the objects differently; see Kim and Biederman, 2011; Baldassano et al., 2016). Therefore, the relative disruption of independent coding in the regular condition observed in our data cannot be explained by low-level visual interactions between the two stimuli. Our results thus provide strong evidence for sensitivity for positional structure in visual cortex, which is not attributable to a shift of weights in favor of one of the objects and is independent of low-level visual content.

How does this sensitivity for positional regularities arise from the typical relative positioning of objects? In the present study, we interchanged the position of the object

pairs to disrupt positional structure while keeping the individual objects identical. In the

irregular displays, positional structure was disrupted on multiple levels: The objects did

not adhere to their typical relative viewpoints and sizes, the laws of physics were partly

violated, and the typical functional relationships between the objects were disrupted. All

these factors constitute properties of positional object structures in real-world scenes, so

that all of them potentially contribute to the effects observed here. Thus, while our study

provides clear evidence for a role of positional structure in multi-object representations,

further studies are needed to disentangle the relative contributions of the different

aspects our manipulation entailed.

The sensitivity for positional structure observed here may reflect the grouping (or

integration) of multiple, regularly positioned objects. Such grouping may provide an

efficient way to deal with the large number of objects contained in natural scenes (Kaiser

et al., 2014a). As a result of limitations in visual capacity, parallel processing of objects is

associated with competition for representation between individual stimuli: When

multiple objects need to be processed at the same time, neural processing becomes less

efficient and behavioral performance decreases (Desimone and Duncan, 1995; Franconeri

et al., 2013; Kastner and Ungerleider, 2001). Processing objects in meaningful chunks

might help to reduce the complexity of a scene by reducing the number of competing

objects. Behavioral evidence suggests that regularly positioned objects can be more

efficiently processed in a number of visual tasks (Gronau and Shachar, 2014, 2015; Kaiser

et al., 2014a, 2015; Stein et al., 2015). These behavioral benefits have been linked to a

reduction in competitive interactions in visual cortex when objects follow positional

regularities (Kaiser et al., 2014a). Our current results provide an explanation for this

reduction of neural competition: Regularly positioned arrangements of objects are not

recruiting independent and competing object representations, but are to some degree

integrated into group representations at higher stages of visual cortex. Such group

representations may constitute an integral step in the visual processing hierarchy,

bridging the gap between individual object coding and the representation of complex

visual scenes.

Acknowledgements

The research was supported by the Autonomous Province of Trento, Call "Grandi

Progetti 2012", project "Characterizing and improving brain mechanisms of attention –

ATTEND".

References

Agam Y, Liu H, Papanastassiou A, Buia C, Golby AJ, Madsen JR, Kreiman G (2010) Robust

selectivity to two-object images in human visual cortex. Curr Biol 20:1-8.

Baeck A, Wagemans J, Op de Beeck HP (2013) The distributed representation of random

and meaningful object pairs in human occipitotemporal cortex: the weighted

average as a general rule. Neuroimage 70:37-47.

Baldassano C, Beck DM, Fei-Fei L (2016) Human-object interactions are more than the

sum of their parts. Cereb Cortex, DOI: 10.1093/cercor/bhw077.

Bar M (2004) Visual objects in context. Nat Rev Neurosci 5:617-629.

Bar M, Aminoff EM (2003) Cortical analysis of visual context. Neuron 38:347-358.

Bernstein M, Oron J, Sadeh B, Yovel G (2014) An integrated face-body representation in

the fusiform gyrus but not the lateral occipital cortex. J Cogn Neurosci 26:2469-

2478.

Brainard DH (1997) The psychophysics toolbox. Spat Vis 10:433-436.

Chun MM (2000) Contextual cueing of visual attention. Trends Cogn Sci 4:170-178.

Cichy RM, Chen Y, Haynes JD (2011) Encoding the identity and location of objects in

human LOC. Neuroimage 54:2297-2307.

Desimone R, Duncan J (1995) Neural mechanisms of selective visual attention. Annu Rev

Neurosci 18:193-222.

Eger E, Ashburner J, Haynes JD, Dolan RJ, Rees G (2008) fMRI activity patterns in human

LOC carry information about object exemplars within category. J Cogn Neurosci

20:356-370.

Epstein RA, Kanwisher N (1998) A cortical representation of the local visual environment.

Nature 392:598-601.

Franconeri SL, Alvarez GA, Cavanagh P (2013) Flexible cognitive resources: competitive

content maps for attention and memory. Trends Cogn Sci 17:134-141.

Grill-Spector K (2003) The neural basis of object perception. Curr Opin Neurobiol 13:159-

166.

Grill-Spector K, Kushnir T, Hendler T, Malach R (2000) The dynamics of object-selective

activation correlate with recognition performance in humans. Nat Neurosci 3:837-

843.

Gronau N, Shachar M (2014) Contextual integration of visual objects necessitates

attention. Atten Percept Psychophys 76:695-714.

Gronau N, Shachar M (2015) Contextual consistency facilitates long-term memory of

perceptual detail in barely seen images. J Exp Psychol Hum Percept Perform

41:1095-1111.

Harry BB, Umla-Runge K, Lawrence AD, Graham KS, Downing PE (2016) Evidence for

integrated visual face and body representations in the anterior temporal lobes. J

Cogn Neurosci 28:1178-1193.

Hasson U, Levy I, Behrmann M, Hendler T, Malach R (2002) Eccentricity bias as an

organizing principle for human high-order object areas. Neuron 34:479-490.

Haushofer J, Livingstone MS, Kanwisher N (2008) Multivariate patterns in object-

selective cortex dissociate perceptual and physical shape similarity. PLoS Biol

6:e187.

Haxby JV, Gobbini MI, Furey ML, Ishai A, Schouten JL, Pietrini P (2001) Distributed and

overlapping representations of faces and objects in ventral temporal cortex.

Science 293:2425-2430.

Kaiser D, Stein T, Peelen MV (2014a) Object grouping based on real-world regularities

facilitates perception by reducing competitive interactions in visual cortex. Proc

Natl Acad Sci USA 111:11217-11222.

Kaiser D, Stein T, Peelen MV (2015) Real-world spatial regularities affect visual working

memory for objects. Psychon Bull Rev 22:1784-1790.

Kaiser D, Strnad L, Seidl KN, Kastner S, Peelen MV (2014b) Whole-person evoked fMRI

activity patterns in human fusiform gyrus are accurately modeled by a linear

combination of face- and body-evoked activity patterns. J Neurophysiol 111:82-90.

Kastner S, Ungerleider LG (2001) The neural basis of biased competition in the human

visual cortex. Neuropsychologia 39:1263-1276.

Kay KN, Winawer J, Mezer A, Wandell BA (2013) Compressive spatial summation in

human visual cortex. J Neurophysiol 110:481-494.

Kim JG, Biederman I (2011) Where do objects become scenes? Cereb Cortex 21:1738-1746.

Kim JG, Biederman I, Juan CH (2011) The benefit of object interactions arises in the lateral

occipital cortex independent of attentional modulation from the intraparietal

sulcus: A TMS study. J Neurosci 31:8320-8324.

Kourtzi Z, Kanwisher N (2001) Representation of perceived object shape by the human

lateral occipital complex. Science 293:1506-1509.

Kriegeskorte N, Mur M, Ruff DA, Kiani R, Bodurka J, Esteky H, Tanaka K, Bandettini PA

(2008) Matching categorical object representations in inferior temporal cortex of

man and monkey. Neuron 60:1126-1141.

Kubilius J, Baeck A, Wagemans J, Op de Beeck HP (2015) Brain-decoding fMRI reveals

how wholes relate to the sum of parts. Cortex 72:5-14.

640 Larsson J, Heeger DJ (2006) Two retinotopic visual areas in human lateral occipital

641   cortex. J Neurosci 26:13128-13142.

642 MacEvoy SP, Epstein RA (2009) Decoding the representation of multiple simultaneous

643   objects in human occipitotemporal cortex. Curr Biol 19:943-947.

644 MacEvoy SP, Epstein RA (2011) Constructing scenes from objects in human

645   occipitotemporal cortex. Nat Neurosci 14:1323-1329.

646 Malach R, Reppas JB, Benson RR, Kwong KK, Jiang H, Kennedy WA, Ledden JP, Brady TJ,

647   Rosen BR, Tootell RB (1995) Object-related activity revealed by functional

648   magnetic resonance imaging in human occipital cortex. Proc Natl Acad Sci USA

649   92:8135-8139.

650 Messinger A, Squire LR, Zola SM, Albright TD (2001) Neural representations of stimulus

651   associations develop in the temporal lobe during learning. Proc Natl Acad Sci USA

652   98:12239-12244.

653 Oliva A, Torralba A (2007) The role of context in object recognition. Trends Cogn Sci

654   11:520-527.

655 Oosterhof NN, Connolly AC, Haxby JV (2016) CoSMoMVPA: multi-modal multivariate

656   pattern analysis of neuroimaging data in Matlab / GNU Octave. Front Neuroinform

657   10:20.

658 Reddy L, Kanwisher NG, VanRullen R (2009) Attention and biased competition in multi-

659   voxel object representations. Proc Natl Acad Sci USA 106:21447-21452.

660 Riddoch MJ, Humphreys GW, Edwards S, Baker T, Willson K (2003) Seeing the action:

661   neuropsychological evidence for action-based effects on object selection. Nat

662   Neurosci 6:82-89.

Roberts KL, Humphreys GW (2010) Action relationships concatenate representations of

separate objects in the ventral visual system. Neuroimage 52:1541–1548.

Rorden C, Brett M (2000) Stereotaxic display of brain lesions. Behav Neurol 12:191-200.

Sakai K, Miyashita Y (1991) Neural organization for the long-term memory of paired

associates. Nature 354:152-155.

Schmalzl L, Zopf R, Williams MA (2012) From head to toe: evidence for selective brain

activation reflecting visual perception of whole individuals. Front Hum Neurosci

6:108.

Smith SM, Nichols TE (2009) Threshold-free cluster enhancement: Addressing problems

of smoothing, threshold dependence and localisation in cluster inference.

Neuroimage 44:83-98.

Stein T, Kaiser D, Peelen MV (2015) Interobject grouping facilitates visual awareness. J Vis

15:10.

Vuilleumier P, Henson RN, Driver J, Dolan RJ (2002) Multiple levels of visual object

constancy revealed by event-related fMRI of repetition priming. Nat Neurosci

5:491-499.

Williams MA, Dang S, Kanwisher NG (2007) Only some spatial patterns of fMRI response

are read out in task performance. Nat Neurosci 10:685-686.

Wolfe JM, Võ ML-H, Evans KK, Greene MR (2011) Visual search in scenes involves selective

and nonselective pathways. Trends Cogn Sci 15:77-84.

Zoccolan D, Cox DD, DiCarlo JJ (2005) Multiple object normalization in monkey

inferotemporal cortex. J Neurosci 25:8150-8164.

685