Transformation from independent to integrative coding of multi-object arrangements

in human visual cortex

Daniel Kaiser[1,2,*], Marius V. Peelen[1,3]

[1]*Center for Mind/Brain Sciences, University of Trento, 38068 Rovereto (TN), Italy*

[2]*Department of Education and Psychology, Freie Universität Berlin, 14195 Berlin-Dahlem,*

Germany

[3]*Donders Institute for Brain, Cognition and Behaviour, Radboud University, Nijmegen, The*

Netherlands

[*]Correspondence to:

Daniel Kaiser

Department of Education and Psychology, Freie Universität Berlin

Habelschwerdter Allee 45, 14195 Berlin-Dahlem, Germany

danielkaiser.net@gmail.com

Abstract

To optimize processing, the human visual system utilizes regularities present in naturalistic visual input. One of these regularities is the relative position of objects in a scene (e.g., a sofa in front of a television), with behavioral research showing that regularly positioned objects are easier to perceive and to remember. Here we use fMRI to test how positional regularities are encoded in the visual system. Participants viewed pairs of objects that formed minimalistic two-object scenes (e.g., a "living room" consisting of a sofa and television) presented in their regularly experienced spatial arrangement or in an irregular arrangement (with interchanged positions). Additionally, single objects were presented centrally and in isolation. Multi-voxel activity patterns evoked by the object pairs were modeled as the average of the response patterns evoked by the two single objects forming the pair. In two experiments, this approximation in object-selective cortex was significantly less accurate for the regularly than the irregularly positioned pairs, indicating integration of individual object representations. More detailed analysis revealed a transition from independent to integrative coding along the posterior-anterior axis of the visual cortex, with the independent component (but not the integrative component) being almost perfectly predicted by object selectivity across the visual hierarchy. These results reveal a transitional stage between individual object and multi-object coding in visual cortex, providing a possible neural correlate of efficient processing of regularly positioned objects in natural scenes.

1 Introduction

Our everyday environments are cluttered, consisting of a large number of separable objects. How does the visual system efficiently process such complex input?

Much of our knowledge about the neural mechanisms of object perception comes from neuroimaging studies using single objects as stimuli. These studies have linked object perception to activity in object-selective cortex (OSC), a region which preferentially responds to objects compared to scrambled objects (Grill-Spector, 2003; Malach et al., 1995) and exhibits reliably discriminable response patterns for different types of objects (Eger et al., 2008; Haxby et al., 2001; Kriegeskorte et al., 2008). Further neuroimaging work has demonstrated that OSC responses show some degree of size- and location-invariance (Cichy et al., 2011; Vuilleumier et al., 2002), partly reflect perceived rather than physical object properties (Haushofer et al., 2008; Kourtzi and Kanwisher, 2001), and are linked to behavioral performance in object recognition (Grill-Spector et al., 2000; Williams et al., 2007).

Recently, studies have moved towards more naturalistic conditions, measuring OSC responses when multiple objects are presented simultaneously. These studies have demonstrated that OSC codes multiple objects in an independent, linearly additive way: Responses to pairs of objects could be modeled as a linear combination (e.g., the average) of the responses to their constituent single objects (Agam et al., 2010; Baeck et al., 2013; Kaiser et al., 2014b; Kubilius et al., 2015; MacEvoy and Epstein, 2009; Reddy et al., 2009; Zoccolan et al., 2005), even when the objects were embedded in complex natural scenes (MacEvoy and Epstein, 2011). Other studies have shown that the optimal combination rules for approximating the multi-object pattern can be shifted away from a

simple average when objects are correctly positioned for an action between the objects

(Baeck et al., 2013) or between an object and a human actor (Baldassano et al., 2017).

Importantly, most objects in natural scenes adhere to meaningful and recurring

positional structures: constrained by their function, their relationship with other objects,

and physical properties of the world, objects appear in predictable locations, viewpoints,

and sizes relative to each other (e.g., sofas facing TV sets, or cars stopping in front of

traffic lights). Previous research has demonstrated that the presence of such inter-object

regularities facilitates behavioral performance in capacity-limited tasks (Bar, 2004; Chun,

2000; Kaiser et al., 2014a; Oliva and Torralba, 2007; Wolfe et al., 2011), raising the question

of how regularly positioned object arrangements are processed in the brain. In the

current study, we provide evidence that the visual system integrates representations of

regularly positioned objects.

In two fMRI experiments, participants viewed pairs of objects that formed

minimalistic versions of scenes (e.g., a "living room", consisting of a sofa and a TV; Fig. 1,

A). These pairs could be arranged in a regular, typically encountered way (e.g., the sofa

facing the TV) or in an irregular way (with the two objects exchanged). Additionally, each

single object was presented centrally and in isolation. The multi-voxel response pattern

evoked by each pair was then modeled by the average of the patterns evoked by its

constituent objects. Replicating previous observations (Kaiser et al., 2014b; MacEvoy and

Epstein, 2009, 2011), we find that OSC response patterns evoked by a pair can be

accurately predicted by the average response patterns evoked by its constituent objects.

Crucially, however, this linear approximation of the pair response depended on the

relative position of the objects: Pair approximation in OSC was less accurate for regularly

positioned pairs than for irregularly positioned pairs, showing that the independence of

multiple object processing breaks down when objects are positioned regularly. More

detailed analyses revealed a transformation from independent to integrative

representations of regularly positioned object pairs along the posterior-anterior axis of

the visual cortex. We interpret this integrative component of multi-object processing as

reflecting an emerging tuning to positional structures in real-world scenes.

2 Materials and Methods

2.1 Participants

Fifteen healthy adults (6 male; mean age 24.6 years, SD=3.3) took part in Experiment 1, and 16 healthy adults took part in Experiment 2 (8 male; mean age 24.7 years, SD=3.0). All participants had normal or corrected-to-normal visual acuity. All procedures were carried out in accordance with the Declaration of Helsinki and were approved by the ethical committee of the University of Trento. Due to excessive head movement, one participant was excluded from Experiment 1. Two participants were excluded from Experiment 2, one due to excessive head movement, and one due to bad functional localizer data, not allowing for a reliable definition of object-selective voxels.

2.2 Stimuli

The stimulus set comprised four pairs of objects, which each depicted a minimalistic version of a scene (Fig. 1, **A**). The four scenes were bathroom (toilet and sink), living room (sofa and television), street crossing (car and traffic lights), and playground (seesaw and slide). The stimuli were created by cutting the objects directly from complete scene images, leaving the size and position the same as in the original scene ("regular" condition). For each scene, a second version was created where the object positions were swapped ("irregular" condition). These irregular versions contained the same objects, but the arrangement did not follow the typical arrangement normally experienced in scenes. For each pair, a total of eleven different stimuli were used. In addition to the pair stimuli we also showed the eight single objects centrally, and in isolation. For Experiment 2, additionally a set of 22 scenes (11 indoor rooms, 11 outdoor street scenes) was used; none of these scenes contained any of the objects that

constituted the pairs. All stimuli were surrounded by a black frame, which subtended a

visual angle of 10° X 7.5°. Stimulus presentation was controlled using MATLAB and

Psychtoolbox (Brainard, 1997). The stimulation was back-projected onto a translucent

screen placed at the end of the scanner bore. Participants viewed the screen through a

tilted mirror mounted to the head coil.

2.3 Experiment 1 procedure

The experiment consisted of multiple runs of 5 minutes each. Half of the runs

were object pair runs, and half of the runs were single object runs. During object pair

runs, the four different pair types (bathroom, living room, street crossing, playground)

were shown in each of the two conditions (regular and irregular). During single object

runs, all constituent single objects were shown. As a previous study has shown that an

approximation of multi-object patterns by single-object patterns is also possible when

the positions of the objects do not match (MacEvoy and Epstein, 2011), the single objects

were presented centrally. Each run consisted of 18 blocks. Within each block, twelve

stimuli were presented, with each stimulus being an exemplar of the same condition

(e.g., a bathroom/irregular block would contain only bathroom pairs in irregular

configuration). Each block contained all eleven pairs (i.e., exemplars) of a specific

condition, and one-back image-level repetition of a specific pair (i.e., exemplar). Each

stimulus was shown for 400ms, with an inter-stimulus-interval of 900ms (Fig. 1, **B**); each

block thus lasted 15.6s. The first nine blocks of each run consisted of eight stimulation

blocks and one block of fixation baseline (in randomized order). The second nine blocks

of a run were the same blocks in mirror-reversed order. The experiment comprised ten

runs (two participants only completed eight runs), always starting with a pair run and

then alternating between single object and pair runs. Participants had to report one-back

image repetitions by pressing a button.

Fig. 1. Stimuli and paradigm. **A**, For Experiment 1, four pairs of objects were collected by

directly cropping them from scenes of four types (bathroom, living room, street crossing,

playground). Object pairs could be positioned in a regular way (as they appeared in the

scenes) or in an irregular way (with their positions exchanged). In Experiment 2, only the

living room and street crossing pairs were used and, in separate blocks, participants saw

images of natural scene images (indoor room versus outdoor street scenes). **B**, Stimuli

were presented for 400ms, separated by inter-stimulus intervals of 900ms. In each

stimulation block, only pairs from one category and one regularity condition appeared

(e.g., regularly positioned cars and traffic lights). Participants responded to one-back

image-level repetitions. Similarly, the single objects belonging to the pairs were

presented in separate runs, using the same block design and task.

2.4 Experiment 2 procedure

The procedure in Experiment 2 was identical to that of Experiment 1 unless

otherwise noted. In Experiment 2, only two of the object pairs were used in the pair runs

(living room and street crossing), and only their four constituent objects were used in the

single object runs. Additionally, in separate runs, the natural scene stimuli were

presented (Fig. 1, **A**). These runs had an identical structure to the pair and single object

runs. In alternating order, only indoor rooms or outdoor street scenes appeared in a

single block. In total, Experiment 2 consisted of 9 runs (3 pair runs, 3 single object runs, 3

scene runs), always starting with a pair run, followed by a single object run and by a

scene run (this order was repeated three times).

2.5 Functional localizer

In both experiments, participants additionally completed two functional localizer

runs of five minutes each. Participants performed a one-back task while viewing images

of faces, houses, everyday objects, and phase-scrambled versions of these objects. Each

stimulus category included 36 individual exemplars. Within each run, there were four

blocks of each stimulus category and four blocks of fixation baseline, with all blocks

lasting 16s. Block order was randomized for the first ten blocks and then mirror-reversed

for the remaining ten blocks. Each non-fixation block included two one-back stimulus

repetitions.

2.6 fMRI data acquisition and preprocessing

MR imaging was conducted using a Bruker BioSpin MedSpec 4T scanner (Bruker

BioSpin, Rheinstetten, Germany), equipped with an eight-channel head coil. During the

experimental runs, T2*-weighted gradient-echo echo-planar images (EPI) were collected

(repetition time TR=2.0s, echo time TE=33ms, 73° flip angle, 3 x 3 x 3mm voxel size, 1mm

gap, 34 slices, 192mm field of view, 64×64 matrix size). Additionally, a T1-weighted image

(MPRAGE; 1 x 1 x 1mm voxel size) was obtained as a high-resolution anatomical reference.

All resulting data were preprocessed using MATLAB and SPM8. EPI volumes were

realigned and coregistered to the structural image. Functional volumes collected during

the functional localizer runs were additionally smoothed with a 6mm full-width-half-

maximum Gaussian kernel.

2.7 Region of interest definition

The BOLD-signal of each voxel in each participant in the localizer runs was

modeled using one regressor for each stimulus category, and six regressors for the

movement parameters obtained from the realignment procedure. Object-selective

cortex (OSC) (Malach et al., 1995) was localized using an object>scrambled contrast,

thresholded at p<0.001 (uncorrected). Regions for both hemispheres were concatenated

to form a bilateral ROI (Experiment 1: mean ROI size 1000 voxels, SE=35; Experiment 2:

mean ROI size 1036 voxels, SE=45). Additionally, an early visual cortex (EVC) ROI was

defined by inverse-normalizing an anatomical mask (BA17/18; created from WFUpickatlas

for SPM) into individual-subject space (Experiment 1: mean ROI size 996 voxels, SE=8;

Experiment 2: mean ROI size 969 voxels, SE=9). For both ROIs, an additional voxel

selection criterion was adopted: as we expected that optimally pair-selective voxels

allow for better approximation of the pair patterns by single-object patterns (Baeck et

al., 2013; MacEvoy and Epstein, 2009), the OSC and EVC ROIs were intersected with

voxels that could optimally discriminate between the different pairs (irrespective of

regularity condition). These voxels were selected from a whole-brain searchlight

classification analysis (see below). A-priori, a voxel count of the 100 most pair-selective

voxels was set for all analyses; to rule out that the results were specific to this particular

number of selected voxels, the analysis was repeated with different voxel counts ranging

from 20 to 500 (see Supplementary Information). For results obtained with a different

selection method and for results in scene-selective regions see Supplementary

Information.

2.8 Univariate Analysis

The BOLD-signal of each voxel in each participant was modeled using one

regressor for each stimulus type, and six regressors for the movement parameters

obtained from the realignment procedure. Activation differences were computed by

averaging beta-weight estimates across voxels for each ROI. Significant differences

between the regularly and irregularly positioned pairs were assessed using t-tests.

2.9 Multivariate pattern analysis

Multivariate pattern analysis (MVPA) was carried out on a TR-based level using

the CoSMoMVPA toolbox (Oosterhof et al., 2016). For each voxel belonging to a specific

ROI, TRs corresponding to the conditions of interest were selected by shifting the voxel-

wise time-course of activation by three TRs (to account for the hemodynamic delay).

Subsequently, for each run separately, activation values were extracted from the EPI-

volumes for each TR coinciding with the onset of a specific condition; the activation

values were then normalized by z-scoring the values for each voxel. For the decoding

analyses, linear discriminant analysis (LDA) classifiers were trained to discriminate the

object pairs on all but one runs, and tested on the remaining run; this procedure was

repeated so that every run was left out once. Pair classification was also computed in a

searchlight decoding analysis (which was used for guiding ROI definition): for this

analysis, a spherical neighborhood of 100 voxels was used to identify voxels in visual

cortex that could optimally discriminate the different object pairs, irrespective of the

regularity condition. Significant decoding was assessed by comparing classifier accuracy

to chance performance, using t-tests.

For the pair combination analysis, response patterns were averaged across all TRs

belonging to a specific condition, resulting in a single response pattern for every

condition. Single-object response patterns for the two objects belonging to a specific

pair (e.g., car and traffic light or sofa and TV) were averaged. Thus, for each pair three

response patterns were available: (1) the response pattern evoked by the pair presented

in the regular arrangement, (2) the response pattern evoked by the pair presented in the

irregular arrangement, and (3) the average response pattern evoked by the two

constituent objects. To assess pair approximation quality in the regular and irregular

conditions separately, the average single object patterns were correlated to their

corresponding pair response patterns (within-correlation) and to the pair patterns

evoked by the non-corresponding pairs (between-correlation, average of 3 correlations)

(Fig. 2).

For the scene approximation analysis in Experiment 2, pair response patterns

were correlated with the corresponding scene response patterns (e.g., sofa/TV and

indoor room scene; within-correlation) and the non-corresponding scene patterns (e.g.,

sofa/TV and outdoor street scene; between-correlation), separately for regular and

irregular pairs. The difference between these within- and between-correlations was used

as a measure of pair approximation quality. Approximation quality was then compared

for the regular and irregular pairs by using paired t-tests. All raw correlations were Fisher-

transformed prior to statistical analysis.

Fig. 2. Schematic illustration of the pair approximation analysis. For each ROI, the

response pattern across hemispheres was extracted both for the single object and pair

conditions. The single object patterns corresponding to each pair were then averaged

and correlated with the pair-evoked pattern. The difference between the correlations

with corresponding pairs (within-correlation) and non-corresponding pairs (between-

correlation) was taken as a measure of approximation quality. This analysis was done

separately for the regular and irregular pairs.

2.10 Combined searchlight analysis

To characterize the emergence of the regularity effect along the visual processing

hierarchy, we performed a searchlight analysis, where we systematically moved a spatial

voxel neighborhood along the anterior-posterior axis. For this analysis, the data from

both experiments was combined. First, the occipitotemporal cortex (defined based on an

anatomical mask) was divided into 40 slices. Each slice spanned 10mm in the anterior-

posterior (Y) direction, with an inter-slice distance of 2mm (thus, individual slices were

overlapping). X and Z coordinates of the occipitotemporal region were fully covered,

with the exception that the medial parts of occipital cortex were masked out to avoid

sampling of EVC voxels. The 40 slices were then inverse-normalized to individual-

participant space. Separately for each participant, within each slice the 100 voxels that

allowed the most accurate pair decoding in a searchlight analysis were selected (similarly

to the OSC analyses, see above). Subsequently, the pair approximation analysis (see

above) was performed for these 100 voxels within each slice. To assess the general

object-selectivity of the voxels in each slice, we computed the difference between the

GLM beta weights for intact and scrambled object in the functional localizer runs (see

above). To identify slices yielding significant effects, we used a threshold-free cluster-

enhancement procedure (Smith and Nichols, 2009) with default parameters, using

multiple-comparison correction based on a sign-permutation test (with null distributions

created from 10,000 bootstrapping iterations) as implemented in CoSMoMVPA

(Oosterhof et al., 2016). The resulting Z-values were thresholded at $Z > 1.96$ (i.e., $p < 0.05$).

3 Results

3.1 Experiment 1

To investigate whether positional regularities impact neural responses in object-selective visual cortex (OSC), we presented participants with pairs of objects that commonly appear together in real world scenes, such as in a bathroom (toilet and sink), in a living room (sofa and TV), on a street crossing (car and traffic lights), or at a playground (seesaw and slide). These objects were directly cut from natural scene images and presented on a blank background ("regular" condition; Fig. 1, **A**). To investigate whether the way in which these objects typically co-occur in the real world influences neural responses, we added a condition where we reversed the object locations ("irregular" condition, Fig. 1, **A**), keeping everything else identical. Additionally, the single objects belonging to the pairs were presented centrally (Fig. 1, **B**).

Functional MRI analyses primarily focused on two regions of interest: functionally defined object-selective cortex (OSC) and anatomically defined early-visual cortex (EVC) (see Supplementary Information for results in scene-selective ROIs). Based on previous work (Baeck et al., 2013; MacEvoy and Epstein, 2009), we expected stronger effects in areas of OSC that preferentially represent information about the object pairs. To define voxels that contribute most to the coding of the object pairs, a whole-brain searchlight analysis was performed (see Materials and Methods), where linear classifiers were used to discriminate the four object pairs, regardless of their positioning (i.e., collapsed across the regular and irregular pairs). Based on this searchlight analysis, within OSC and EVC the 100 voxels that contributed most to the classification of the four pairs were selected (Fig. 3, **A**). Other voxel counts and voxel selection methods gave similar results (see Supplementary Information).

First, we wanted to confirm that the four object pairs were reliably discriminable

in both OSC and EVC. Separately for regular and irregular pairs, a multivariate

classification analysis of response patterns across voxels was performed. In a leave-one-

run-out fashion, linear discriminant analysis (LDA) classifiers were used to classify

response patterns to the four different pairs (see Materials and Methods). In both OSC

and EVC, these classifiers performed highly above chance level (OSC: 42%; EVC: 40%), as

expected based on the voxel selection method. For both regions, no reliable difference

in decoding accuracy was found when comparing the regular and irregular conditions

directly (OSC: $t[13]=0.8$, $p=0.41$; EVC: $t[13]=1.2$, $p=0.25$). Similarly, no difference in

univariate activation values between the two conditions was observed (OSC: $t[13]=0.7$,

$p=0.48$; EVC: $t[13]=1.1$, $p=0.29$). This pattern of results argues against overall differences

in signal quality, for example due to differences in attentional engagement for the two

conditions: such an effect would be expected to result in a univariate and/or classification

difference between the regular and irregular conditions.

Next, we tested whether the average of the response patterns evoked by the

single objects could more accurately approximate the pattern evoked by the

corresponding pairs than the pattern evoked by the non-corresponding pairs: for

example, is the average of the response patterns for cars and traffic lights more similar

to the response pattern for the car and traffic light pair than to the other pairs (e.g., to a

TV and a sofa)? Two types of correlations were computed: within-correlations, of the

average single object response patterns and the corresponding pair response patterns;

and between-correlations, of the average single object response patterns and the other,

non-corresponding pair response patterns (see Materials and Methods; Fig. 2). For both

regular and irregular pairs separately, the difference between these within- and between-

correlations was taken as a measure of pair approximation quality.

In OSC, within-correlations were significantly higher than between-correlations,

both for regular and irregular pairs, indicating that the mean of the constituent object

responses offered a reliable approximation of the pair responses (regular: t[13]=6.33,

p<0.001; irregular: t[13]=11.2, p<0.001; Fig. 3, **B**). Similar effects were observed in EVC

(regular: t[13]=6.1, p<0.001; irregular: t[13]=4.7, p<0.001). Next, to investigate whether

positional regularity affected this approximation, we directly compared regular and

irregular pair approximation. Crucially, pair approximation was better for irregular pairs

than for regular pairs (t[13]=2.5, p=0.02). By contrast, no such difference was found in

EVC (t[13]=1.0, p=0.32; interaction with region: t[13]=2.9, p=0.01). These findings indicate

that multiple object processing in OSC is sensitive to typical real-world positioning.

Fig. 3. Pair approximation results. **A**, Object selective cortex (OSC) and early visual cortex

(EVC) maps depicting voxel-wise overlap between participants: Regions were defined on

a single-subject level by selecting the 100 voxels that best discriminated the four pairs

across the regularity conditions (see Materials and Methods) within either a functional

OSC mask or an anatomical EVC mask. For illustration purposes, the regions were

normalized into standard space and overlaid on a brain template using MRIcron (Rorden

and Brett, 2000). **B,** The pair approximation analysis for Experiment 1 revealed a more

accurate approximation of the irregularly positioned pairs than of the regularly

positioned pairs in OSC, while no effect was found in EVC. **C,** In Experiment 2, this pattern

of results was replicated, demonstrating sensitivity for object regularity structure in OSC,

but not EVC. All error bars reflect standard errors of pairwise differences. (*p<0.05,

**p<0.01)

3.2 Experiment 2

In a second fMRI experiment we aimed to replicate the pattern of results. The

structure of the experiment was largely identical to Experiment 1 (see Materials and

Methods) and participants viewed images from two of the pairs also used in Experiment

1 (sofa and TV; car and traffic lights).

First, as in Experiment 1, discriminability of the response patterns for the regular

and irregular pairs was assessed using a two-way linear classification analysis in OSC and

EVC. In both regions, classifiers performed highly above chance level (OSC: 69%; EVC:

64%) and no difference in decoding accuracy was found when comparing the regular and

irregular conditions directly (OSC: $t[13]=0.02$, $p=0.99$; EVC: $t[13]=0.7$, $p=0.51$). Additionally,

no difference was observed in univariate activation values for the two conditions (OSC:

$t[13]=0.01$, $p=0.99$; EVC: $t[13]=1.0$, $p=0.32$).

Second, separately for regular and irregular pairs, constituent single-object

response patterns were averaged for each pair to test how well these average response

patterns could approximate the two pairs. As in Experiment 1, in OSC the average of the

response patterns evoked by the single objects was more similar to the pattern evoked

by the corresponding than by the non-corresponding pairs, both for the regular pairs

(t[13]=11.1, p<0.001) and the irregular pairs (t[13]=11.7, p<0.001; Fig. 3, **C**). By contrast (and

unlike Experiment 1), the average single object patterns did not accurately approximate

the pair patterns in EVC (regular pairs: t[13]=0.8, p=0.44; irregular pairs: t[13]=0.2,

p=0.87). Most importantly, Experiment 2 replicated the key finding of Experiment 1: a

difference between the approximation of regular and irregular pairs in OSC (t[13]=3.4,

p=0.004), with no such difference in EVC (t[13]=0.8, p=0.46; interaction across regions:

t[13]=3.3, p=0.006). These results closely resemble the pattern of results obtained in

Experiment 1, providing further evidence for an influence of positional regularities on

multi-object coding in OSC.

Experiment 2 was additionally designed to test a possible explanation for the

regularity effect: perhaps regularly positioned object pairs more strongly induced a

mental representation of the corresponding scene (e.g., the spatial layout of the scene),

thereby distorting the representation of the individual objects. To test this account,

participants viewed images of room scenes and street scenes during separate blocks of

Experiment 2 (Fig. 1, **A**). None of these scenes contained any of the objects belonging to

the pairs. OSC response patterns to these scenes were reliably discriminable in a two-way

classification analysis (mean accuracy: 64%; t[13]=9.1, p<0.001). To determine whether the

relatively inaccurate pair approximation for regularly positioned pairs in OSC reflected

the activation of the corresponding scene representations (e.g., living room for sofa-TV

pairs), we correlated the activation patterns evoked by the pair stimuli to the activation

patterns of the scene stimuli. Separately for the regular and irregular conditions, this

correlation was computed within scene type (i.e., sofa/TV and indoor room scene, and

car/lights and outdoor street scene) and between scene type (i.e., sofa/TV and outdoor

street scene, and car/lights and indoor room scene). The difference of these within- and

between-correlations was taken as a measure of scene approximation quality. In OSC,

this scene approximation was not significantly different from zero, both for regularly

(t[13]=0.4, p=0.69) and irregularly (t[13]=0.2, p=0.87) positioned pairs and no difference

was found when directly comparing discriminability for regular and irregular pairs

(t[13]=0.7, p=0.50). Similar results were obtained in scene-selective regions of visual

cortex (see Supplementary Information). These results suggest that the differential

coding of regular and irregular pairs in OSC does not reflect a difference in the degree to

which they activate scene category response patterns.

3.3 Transformation from independent to integrative coding

The results from Experiments 1 and 2 demonstrate that a linear combination of

single object response patterns accurately predicts the response patterns evoked by

both regularly and irregularly positioned pairs. However, a relative disruption of this

approximation was observed in the regular condition. This pattern of results suggests

that responses to regularly positioned pairs reflect both an independent processing

component and an integrative component that disrupts this independent processing to

some degree. As our region of interest analysis only focused on two larger portions of

the visual cortex (EVC versus OSC), it could not reveal which parts of OSC are housing the

independent and integrative components of multi-object processing. To reveal the

transformation from independent to integrative processing at finer anatomical

resolution we tracked the overall approximation quality (reflecting the independent

component of multi-object representations) and the regularity effect (reflecting the

relative disruption of independent coding in the regular condition) along the visual

hierarchy. Combining the data from both experiments, we performed a searchlight

analysis along the posterior-anterior axis of the occipitotemporal cortex (see Materials

and Methods). In brief, anatomically defined occipitotemporal cortex was divided into

slices (width: 10mm) varying along the y-coordinate (in MNI space) in steps of 2mm (see

Fig. 4, **A**). For each of these slices, comparably to the OSC analyses for Experiments 1 and

2, the 100 best pair-representing voxels were selected based on individual-participant

searchlight maps. Then, for each slice separately, the pair approximation analysis was

performed (as illustrated in Fig 2), leading to a pair approximation value (within-

correlation vs. between-correlation) and a regularity effect for each slice (Fig. 4, **B**).

Generally, approximation quality across the two regularity conditions (i.e., the mean of

the two conditions) was very robust and significantly above chance for all slices centered

between Y=-100 and Y=-34 (Fig 4, **C**). To detect regularity effects, the difference of the

linear approximation quality in the regular and irregular conditions was compared to

zero. This analysis revealed an effect that emerged between Y=-80 and Y=-84, and later

between Y=-64 and Y=-38 (Fig 4, **D**). This pattern of results shows that highly accurate

linear approximation can be observed at earlier processing stages than the relative

breakdown of this approximation in the regular condition, suggesting that the

integrative multi-object coding for regularly positioned objects is preceded by an

independent representational stage.

To assess how the overall approximation quality and the regularity effect relate to

object selectivity, the difference of the intact and scrambled object conditions in the

functional localizer was computed for each slice (see Materials and Methods). All slices

between Y=-98 and Y=-30 exhibited significant object-selectivity (Fig. 4, **C/D**).

Interestingly, across slices object-selectivity almost perfectly predicted overall

approximation quality (r=0.97, p<0.001). By contrast, object-selectivity did not

significantly predict the regularity effect across slices (r=-0.05, p=0.75). These results

suggest that the independent component of multi-object processing is tightly linked to

the degree of object-selectivity, while the influence of object regularity emerges later in

the visual hierarchy. In sum, this analysis shows that overall linear approximation

(reflecting the independent component of multi-object processing) and its relative

breakdown (reflecting an effect of positional structure) can be anatomically dissociated,

revealing a transformation from independent to integrative coding of multi-object

displays along the visual processing hierarchy.

Fig. 4. Combined searchlight analysis. **A**, Searchlight analysis was performed for slices of

occipitotemporal cortex (10mm width) with varying y-coordinate, in steps of 2mm. Slices

were defined in standard space (based on MNI coordinates) and back-projected into

individual subject space. Subsequently, within each slice, the 100 best pair-representing

voxels were selected on an individual-participant level. **B**, Pair approximation (expressed

as the difference between within- and between correlations) for regular and irregular

pairs in slices along the y-coordinate. **C**, Overall approximation (i.e., the mean of the

regular and irregular conditions) was generally very accurate throughout the visual

hierarchy, and showed a striking correspondence with the degree of object-selectivity. **D**,

Differences between the regular and irregular conditions emerged starting from Y=-80.

In contrast to the overall approximation, the regularity effects along the hierarchy did

not correspond well with the degree of object-selectivity. (*p<0.05, corrected for

multiple comparisons). The transition from independent to integrative coding might

occur between object-selective regions LO1 and LO2 (**A**, region maps taken from Wang et

al., 2015), with independent coding in LO1 and additional integrative coding in LO2 (see

Discussion).

4 Discussion

In two fMRI experiments, we demonstrate non-independence in the visual cortex representation of multi-object displays, revealing a transformation from independent to integrative representations along the visual processing hierarchy. Response patterns in OSC evoked by regularly positioned object pairs were less accurately modeled by the response patterns evoked by their constituent objects. The relative breakdown of this linear response approximation reflects a disruption of independent multi-object coding when objects adhere to their typical real-world positions. The regularity effect was significant in functionally localized OSC, but not in EVC. (Mixed results were obtained in scene-selective regions; see Supplementary Information.) However, further analyses revealed that object selectivity was closely related, along the posterior-anterior axis, to independent object coding rather than integrative object coding, which emerged later in the visual hierarchy.

The searchlight analysis along the posterior-anterior axis of the occipitotemporal cortex suggests that the coding of multiple, regularly positioned objects reflects two dissociable components: an independent processing component and an integrative component. Independent processing can be observed starting at early stages of the visual object processing hierarchy, and is tightly linked to object selectivity. The striking correspondence between object-selectivity and pair approximation suggests that the same neural mechanisms support single-object coding and (independent) multi-object coding. By contrast, at later stages of the processing hierarchy, pair approximation quality diverges for regular and irregular pairs, reflecting additional, integrative processing for regularly positioned pairs that (partly) disrupts independent coding.

Interestingly, this relative disruption cannot be explained by differences in object-

selectivity along the visual hierarchy.

We speculate that the independent and integrative components of multi-object

coding reflect activity in different sub-regions of object-selective cortex, with a more

posterior sub-region – possibly LO1 (Larsson and Heeger, 2006) (Y=-90, SE=5) – primarily

reflecting independent coding and a more anterior sub-region – possibly LO2 (Larsson

and Heeger, 2006) (Y=-83, SE=6) – also containing an integrative component. This

proposal is supported in our current data: Repeating the main pair approximation

analysis using probabilistic LO1/LO2 group masks[1] (Wang et al., 2015; Fig. 4, **A**), we found

that pair approximation was disrupted in LO2 ($t[27]=2.0$, $p=0.05$), but not in LO1

($t[27]=0.7$, $p=0.47$; interaction across regions: $t[27]=2.3$, $p=0.03$). This difference in

integrative object processing is consistent with a previously reported difference in spatial

summation along the posterior-anterior axis, with a higher rate of information

compression in the more anterior LO2 (Kay et al., 2013). However, further studies

employing retinotopic mapping techniques are needed to more precisely pinpoint the

effects to specific sub-regions of object-selective occipitotemporal cortex.

The disruption of independent coding observed here is unlikely to reflect

differential semantic associations between objects (e.g., that car and traffic light are

semantically related). Previous electrophysiological studies have demonstrated that such

associations between objects can alter neural tuning properties in visual cortex: The

associative pairing of two objects can shape neural responses in a way that neurons

---

[1] ROIs were generated by inverse-normalizing the group masks into individual-subject space. To ensure sufficient voxel counts for the analysis, all voxels exceeding a probability of 25% of belonging to either region were selected. Overlapping voxels were grouped into the higher-probability region.

become selective to both of the individual objects (Messinger et al., 2001; Sakai et al.,

1991). However, in our study the objects were equally related in their semantic content in

the regular and irregular conditions – the crucial difference was the positional structure.

An alternative explanation is that our results reflect the activation of object group

representations that are shaped by the co-occurrence structure of objects in real-world

environments. Such group representations have been proposed for the cortical

representation of people, where information from the face and body is integrated into a

person representation (Bernstein et al., 2014; Harry et al., 2016; Schmalzl et al., 2012; but

see Kaiser et al., 2014b). The additional recruitment of group representations would

disrupt the linear approximation of multi-object patterns: if neurons mediating the group

representation are distributed differently across voxels from neurons mediating the

individual object representations, the pair patterns suffers a distortion (relative to the

average of the individual object patterns). Further studies are required to probe the

nature of these group representations at a finer grained level.

A number of previous studies have explored relational coding of objects in the

context of action relationships. Some of these studies have reported univariate

activation differences between objects positioned correctly or incorrectly for performing

a specific action (Kim and Biederman, 2011; Kim et al., 2011; Roberts and Humphreys,

2010). Others have used similar methods as the current study to demonstrate that action

relationships alter combination rules in the processing of multiple objects (Baeck et al.,

2013; Baldassano et al., 2017). Notably, the regularity effects observed in these studies

have been attributed to processing asymmetries favoring the "active" object (e.g., a

hammer) over the "passive" object (e.g., a nail) in a pair (Baeck et al., 2013; Riddoch et

al., 2003). By contrast, our approach focused on real-world object structure more

generally, avoiding such direct functional interactions of the two objects. Furthermore, in

our study the positional structure of the object pairs was solely manipulated by

exchanging the position of the single objects, without introducing changes of low-level

visual characteristics (like physically connecting the objects differently; see Kim and

Biederman, 2011; Baldassano et al., 2017). Therefore, the relative disruption of

independent coding in the regular condition observed in our data cannot be explained by

low-level visual interactions between the two stimuli. Our results thus provide strong

evidence for sensitivity for positional structure in visual cortex, which is not attributable

to a shift of weights in favor of one of the objects and is not due to low-level grouping.

Previous studies using similar paradigms have often shown single objects and

multiple objects in identical, peripheral locations (Baeck et al., 2013; Kaiser et al., 2014b;

MacEvoy and Epstein, 2009). By contrast, our study employed a design where the single

objects were presented centrally and thus in different retinotopic locations as within the

pairs (MacEvoy and Epstein, 2011). In this case, the successful approximation of the pair

responses – and thus the breaking down of this approximation – must emerge from

neural populations with sufficiently large receptive fields and sufficient location

tolerance (this also becomes apparent in the higher pair approximation quality in OSC, as

compared to EVC). In natural environments, this location tolerance might be a crucial

property of multiple object representations: In the real world, objects frequently change

retinotopic position but their relative position is more stable. Object group

representations may thus help to maintain a coherent and stable representation of a

scene.

How does the neural sensitivity for positional regularities arise from the typical

relative positioning of objects? In the present study, we interchanged the position of the

object pairs to disrupt positional structure while keeping the individual objects identical.

In the irregular displays, positional structure was disrupted in multiple ways: The objects

did not adhere to their typical relative viewpoints and sizes, the laws of physics were

partly violated, and the typical functional relationships between the objects were

disrupted. All these factors constitute properties of positional object structures in real-

world scenes, so that all of them potentially contribute to the effects observed here.

Thus, while our study provides clear evidence for a role of positional structure in multi-

object representations, further studies are needed to disentangle the contributions of

the different aspects our manipulation entailed.

The sensitivity for positional structure observed here may reflect the grouping (or

integration) of multiple, regularly positioned objects. Such grouping may provide an

efficient way to deal with the large number of objects contained in natural scenes (Kaiser

et al., 2014a). As a result of limitations in visual capacity, parallel processing of objects is

associated with competition for representation between individual stimuli: When

multiple objects need to be processed at the same time, neural processing becomes less

efficient and behavioral performance decreases (Desimone and Duncan, 1995; Franconeri

et al., 2013; Kastner and Ungerleider, 2001). Processing objects in meaningful chunks

might help to reduce the complexity of a scene by reducing the number of competing

objects. Behavioral evidence suggests that regularly positioned objects can be more

efficiently processed, as measured in various visual tasks (Gronau and Shachar, 2014,

2015; Kaiser et al., 2014a, 2015; Stein et al., 2015). These behavioral benefits have been

linked to a reduction in competitive interactions in visual cortex when objects follow

positional regularities (Kaiser et al., 2014a). Our current results provide an explanation for

this reduction of neural competition: Regularly positioned arrangements of objects are

not recruiting independent and competing object representations, but are to some

degree integrated into group representations at higher stages of visual cortex. Such

group representations may constitute an integral step in the visual processing hierarchy,

bridging the gap between individual object coding and the representation of whole

scenes.

Acknowledgements

The research was supported by the Autonomous Province of Trento, Call "Grandi

Progetti 2012", project "Characterizing and improving brain mechanisms of attention –

ATTEND". This project has received funding from the European Research Council (ERC)

under the European Union's Horizon 2020 research and innovation programme (grant

agreement No 725970).

References

Agam Y, Liu H, Papanastassiou A, Buia C, Golby AJ, Madsen JR, Kreiman G (2010) Robust selectivity to two-object images in human visual cortex. Curr Biol 20:1-8.

Baeck A, Wagemans J, Op de Beeck HP (2013) The distributed representation of random and meaningful object pairs in human occipitotemporal cortex: the weighted average as a general rule. Neuroimage 70:37-47.

Baldassano C, Beck DM, Fei-Fei L (2017) Human-object interactions are more than the sum of their parts. Cereb Cortex, 27:2276-2288.

Bar M (2004) Visual objects in context. Nat Rev Neurosci 5:617-629.

Bar M, Aminoff EM (2003) Cortical analysis of visual context. Neuron 38:347-358.

Bernstein M, Oron J, Sadeh B, Yovel G (2014) An integrated face-body representation in the fusiform gyrus but not the lateral occipital cortex. J Cogn Neurosci 26:2469-2478.

Brainard DH (1997) The psychophysics toolbox. Spat Vis 10:433-436.

Chun MM (2000) Contextual cueing of visual attention. Trends Cogn Sci 4:170-178.

Cichy RM, Chen Y, Haynes JD (2011) Encoding the identity and location of objects in human LOC. Neuroimage 54:2297-2307.

Desimone R, Duncan J (1995) Neural mechanisms of selective visual attention. Annu Rev Neurosci 18:193-222.

Eger E, Ashburner J, Haynes JD, Dolan RJ, Rees G (2008) fMRI activity patterns in human LOC carry information about object exemplars within category. J Cogn Neurosci 20:356-370.

Epstein RA, Kanwisher N (1998) A cortical representation of the local visual environment. Nature 392:598-601.

Franconeri SL, Alvarez GA, Cavanagh P (2013) Flexible cognitive resources: competitive

content maps for attention and memory. Trends Cogn Sci 17:134-141.

Grill-Spector K (2003) The neural basis of object perception. Curr Opin Neurobiol 13:159-

166.

Grill-Spector K, Kushnir T, Hendler T, Malach R (2000) The dynamics of object-selective

activation correlate with recognition performance in humans. Nat Neurosci 3:837-

843.

Gronau N, Shachar M (2014) Contextual integration of visual objects necessitates

attention. Atten Percept Psychophys 76:695-714.

Gronau N, Shachar M (2015) Contextual consistency facilitates long-term memory of

perceptual detail in barely seen images. J Exp Psychol Hum Percept Perform

41:1095-1111.

Harry BB, Umla-Runge K, Lawrence AD, Graham KS, Downing PE (2016) Evidence for

integrated visual face and body representations in the anterior temporal lobes. J

Cogn Neurosci 28:1178-1193.

Hasson U, Levy I, Behrmann M, Hendler T, Malach R (2002) Eccentricity bias as an

organizing principle for human high-order object areas. Neuron 34:479-490.

Haushofer J, Livingstone MS, Kanwisher N (2008) Multivariate patterns in object-

selective cortex dissociate perceptual and physical shape similarity. PLoS Biol

6:e187.

Haxby JV, Gobbini MI, Furey ML, Ishai A, Schouten JL, Pietrini P (2001) Distributed and

overlapping representations of faces and objects in ventral temporal cortex.

Science 293:2425-2430.

Kaiser D, Stein T, Peelen MV (2014a) Object grouping based on real-world regularities

facilitates perception by reducing competitive interactions in visual cortex. Proc

Natl Acad Sci USA 111:11217-11222.

Kaiser D, Stein T, Peelen MV (2015) Real-world spatial regularities affect visual working

memory for objects. Psychon Bull Rev 22:1784-1790.

Kaiser D, Strnad L, Seidl KN, Kastner S, Peelen MV (2014b) Whole-person evoked fMRI

activity patterns in human fusiform gyrus are accurately modeled by a linear

combination of face- and body-evoked activity patterns. J Neurophysiol 111:82-90.

Kastner S, Ungerleider LG (2001) The neural basis of biased competition in the human

visual cortex. Neuropsychologia 39:1263-1276.

Kay KN, Winawer J, Mezer A, Wandell BA (2013) Compressive spatial summation in

human visual cortex. J Neurophysiol 110:481-494.

Kim JG, Biederman I (2011) Where do objects become scenes? Cereb Cortex 21:1738-1746.

Kim JG, Biederman I, Juan CH (2011) The benefit of object interactions arises in the lateral

occipital cortex independent of attentional modulation from the intraparietal

sulcus: A TMS study. J Neurosci 31:8320-8324.

Kourtzi Z, Kanwisher N (2001) Representation of perceived object shape by the human

lateral occipital complex. Science 293:1506-1509.

Kriegeskorte N, Mur M, Ruff DA, Kiani R, Bodurka J, Esteky H, Tanaka K, Bandettini PA

(2008) Matching categorical object representations in inferior temporal cortex of

man and monkey. Neuron 60:1126-1141.

Kubilius J, Baeck A, Wagemans J, Op de Beeck HP (2015) Brain-decoding fMRI reveals

how wholes relate to the sum of parts. Cortex 72:5-14.

Larsson J, Heeger DJ (2006) Two retinotopic visual areas in human lateral occipital

cortex. J Neurosci 26:13128-13142.

MacEvoy SP, Epstein RA (2009) Decoding the representation of multiple simultaneous

objects in human occipitotemporal cortex. Curr Biol 19:943-947.

MacEvoy SP, Epstein RA (2011) Constructing scenes from objects in human

occipitotemporal cortex. Nat Neurosci 14:1323-1329.

Malach R, Reppas JB, Benson RR, Kwong KK, Jiang H, Kennedy WA, Ledden JP, Brady TJ,

Rosen BR, Tootell RB (1995) Object-related activity revealed by functional

magnetic resonance imaging in human occipital cortex. Proc Natl Acad Sci USA

92:8135-8139.

Messinger A, Squire LR, Zola SM, Albright TD (2001) Neural representations of stimulus

associations develop in the temporal lobe during learning. Proc Natl Acad Sci USA

98:12239-12244.

Oliva A, Torralba A (2007) The role of context in object recognition. Trends Cogn Sci

11:520-527.

Oosterhof NN, Connolly AC, Haxby JV (2016) CoSMoMVPA: multi-modal multivariate

pattern analysis of neuroimaging data in Matlab / GNU Octave. Front Neuroinform

10:20.

Reddy L, Kanwisher NG, VanRullen R (2009) Attention and biased competition in multi-

voxel object representations. Proc Natl Acad Sci USA 106:21447-21452.

Riddoch MJ, Humphreys GW, Edwards S, Baker T, Willson K (2003) Seeing the action:

neuropsychological evidence for action-based effects on object selection. Nat

Neurosci 6:82-89.

Roberts KL, Humphreys GW (2010) Action relationships concatenate representations of

separate objects in the ventral visual system. Neuroimage 52:1541–1548.

Rorden C, Brett M (2000) Stereotaxic display of brain lesions. Behav Neurol 12:191-200.

Sakai K, Miyashita Y (1991) Neural organization for the long-term memory of paired

associates. Nature 354:152-155.

Schmalzl L, Zopf R, Williams MA (2012) From head to toe: evidence for selective brain

activation reflecting visual perception of whole individuals. Front Hum Neurosci

6:108.

Smith SM, Nichols TE (2009) Threshold-free cluster enhancement: Addressing problems

of smoothing, threshold dependence and localisation in cluster inference.

Neuroimage 44:83-98.

Stein T, Kaiser D, Peelen MV (2015) Interobject grouping facilitates visual awareness. J Vis

15:10.

Vuilleumier P, Henson RN, Driver J, Dolan RJ (2002) Multiple levels of visual object

constancy revealed by event-related fMRI of repetition priming. Nat Neurosci

5:491-499.

Wang L, Mruczek RE, Arcaro MJ, Kastner S (2015) Probabilistic maps of visual topography

in human cortex. Cereb Cortex 25:3911-3931.

Williams MA, Dang S, Kanwisher NG (2007) Only some spatial patterns of fMRI response

are read out in task performance. Nat Neurosci 10:685-686.

Wolfe JM, Võ ML-H, Evans KK, Greene MR (2011) Visual search in scenes involves selective

and nonselective pathways. Trends Cogn Sci 15:77-84.

Zoccolan D, Cox DD, DiCarlo JJ (2005) Multiple object normalization in monkey

inferotemporal cortex. J Neurosci 25:8150-8164.