Drug Target Ontology to Classify and Integrate Drug Discovery Data

Yu Lin[¶,1], Saurabh Mehta[¶,1,3], Hande Küçük-McGinty[¶,1,2], John Paul Turner[5], Dusica Vidovic[1,5], Michele Forlin[1,5], Amar Koleti[1], Dac-Trung Nguyen[7], Lars Juhl Jensen[6], Rajarshi Guha[7], Stephen L. Mathias[4], Oleg Ursu[4], Vasileios Stathias[5], Jianbin Duan[1,2], Nooshin Nabizadeh[1], Caty Chung[1], Christopher Mader[1], Ubbo Visser[2], Jeremy J. Yang[4], Cristian G. Bologa[4], Tudor Oprea[*,4], Stephan C. Schürer[*,1,5]

1. Center for Computational Science, University of Miami, Coral Gables, FL, USA

2. Department of Computer Science, University of Miami, Coral Gables, FL, USA

3. Department of Applied Chemistry, Delhi Technological University, Delhi, India

4. Translational Informatics Division, Department of Internal Medicine, University of New Mexico School of Medicine, Albuquerque, NM, USA

5. Department of Molecular and Cellular Pharmacology, Miller School of Medicine, University of Miami, FL, USA

6. Novo Nordisk Foundation Center for Protein Research, Faculty of Health and Medical Sciences, University of Copenhagen, Copenhagen, Denmark.

7. National Center for Advancing Translational Science, Rockville, MD, USA

[¶] Authors contributed equally.

* Corresponding author:

Stephan Schürer, email: sschurer@miami.edu

Tudor Oprea, email: toprea@salud.unm.edu

Abstract

Background: One of the most successful approaches to develop new small molecule therapeutics has been to start from a validated druggable protein target. However, only a small subset of potentially druggable targets has attracted significant research and development resources. The Illuminating the Druggable Genome (IDG) project develops resources to catalyze the development of likely targetable, yet currently understudied prospective drug targets. A central component of the IDG program is a comprehensive knowledge resource of the druggable genome.

Results: As part of that effort, we have been developing a framework to integrate, navigate, and analyze drug discovery data based on formalized and standardized classifications and annotations of druggable protein targets, the Drug Target Ontology (DTO). DTO was constructed by extensive curation and consolidation of various resources. DTO classifies the four major drug target protein families, GPCRs, kinases, ion channels and nuclear receptors, based on phylogenecity, function, target development level, disease association, tissue expression, chemical ligand and substrate characteristics, and target-family specific characteristics. The formal ontology was built using a new software tool to auto-generate most axioms from a database while also supporting manual knowledge acquisition. A modular, hierarchical implementation facilitates development and maintenance and makes use of various external ontologies, thus integrating the DTO into the ecosystem of biomedical ontologies. As a formal OWL-DL ontology, DTO contains asserted and inferred axioms. Modeling data from the Library of Integrated Network-based Cellular Signatures (LINCS) program illustrates the potential of DTO for contextual data integration and nuanced definition of important drug target

characteristics. DTO has been implemented in the IDG user interface Portal, Pharos and the

TIN-X explorer of protein target disease relationships.

Conclusions: DTO was built based on the need for a formal semantic model for druggable

targets including various related information such as protein, gene, protein domain, protein

structure, binding site, small molecule drug, mechanism of action, protein tissue localization,

disease association, and many other types of information. DTO will further facilitate the

otherwise challenging integration and formal linking to biological assays, phenotypes, disease

models, drug poly-pharmacology, binding kinetics and many other processes, functions and

qualities that are at the core of drug discovery. The first version of DTO is publically available

via   the   website   http://drugtargetontology.org/,   Github

(https://github.com/DrugTargetOntology/DTO),   and   the   NCBO   Bioportal

(https://bioportal.bioontology.org/ontologies/DTO). The long-term goal of DTO is to provide

such an integrative framework and to populate the ontology with this information as a

community resource.

1 INTRODUCTION

The development and approval of novel small molecule therapeutics (drugs) is highly complex and exceedingly resource intensive, being estimated at over one billion dollars for a new FDA approved drug. The primary reason for attrition in clinical trials is the lack of efficacy, which has been associated with poor or biased target selection [1]. Although the drug target mechanism of action is not required for FDA approval, a target-based mechanistic understanding of diseases and drug action is highly desirable and a preferred approach of drug development in the pharmaceutical industry. Following the advent of the Human Genome, several research groups in academia as well as industry have focused on "the druggable genome" *i.e.* the subsets of genes in the human genome that express proteins which have the ability to bind drug-like small molecules [2]. The researchers have estimated the number of druggable targets ranging from few hundred to several thousands [3]. Furthermore, it has been suggested by several analyses that only a small fraction of likely relevant druggable targets are extensively studied, leaving a potentially huge treasure trove of promising, yet understudied ("dark") drug targets to be explored by pharmaceutical companies and academic drug discovery researchers. Not only is there ambiguity about the number of the druggable targets, but there is also a need of systematic characterization and annotation of the druggable genome. A few research groups have made efforts to address these issues and have indeed developed several useful resources, *e.g.* IUPHAR/BPS Guide to PHARMACOLOGY (GtoPdb/IUPHAR) [4], PANTHER [5], Therapeutic Target Database (TTD) [6], Potential Drug Target Database (PDTD) [7], covering important aspects of the drug targets. However, to the best of our knowledge, a publically available structured knowledge resource of drug target classifications and relevant annotations for the most important protein families, one that facilitates querying, data integration, re-use, and

analysis does not currently exist. Content in the above-mentioned databases is scattered and in

some cases inconsistent and duplicated, complicating data integration and analysis.

The Illuminating the Druggable Genome (IDG) project (http://targetcentral.ws/) has the goal to

identify and prioritize new prospective drug targets among likely targetable, yet currently poorly

or not at all annotated proteins; and by doing so to catalyze the development of novel drugs with

new mechanism of action. Data compiled and analyzed by the IDG Knowledge Management

Center (IDG-KMC) shows that the globally marketed drugs stem from only 3% of the human

proteome. These results also suggest that the substantial knowledge deficit for understudied drug

targets may be due to an uneven distribution of information and resources [8].

In the context of the IDG program we have been developing the Drug Target Ontology (DTO).

Formal ontologies have been quite useful to facilitate harmonization, integration, and analysis of

diverse data in the biomedical and other domains. DTO integrates and harmonizes knowledge of

the most important druggable protein families: kinases, GPCRs, ion channels and nuclear

hormone receptors. DTO content was curated from many information sources and the literature

and includes detailed hierarchical classifications of proteins and genes, tissue localization,

disease association, drug target development level, protein domain information, ligands,

substrates, and other types of relevant information. The covered resources were chosen by

domain experts based on relevance coverage and completeness of the information available

through them. Most resources had been peer reviewed (references are included at appropriate

places), published and were therefore considered reliable. DTO is aimed towards the drug

discovery and clinical communities and was built to align with other ontologies including

BioAssay Ontology (BAO) [9-11]and GPCR Ontology [12].   By providing a semantic

framework of diverse information related to druggable proteins, DTO facilitates the otherwise

challenging integration and formal linking of heterogeneous and diverse data important for drug

discovery. DTO is particularly relevant for big data, systems-level models of diseases and drug

action as well as precision medicine. The long-term goal of DTO is to provide such an

integrative framework and to populate the ontology with this information as a community

resource. Here we describe the development, content, architecture, modeling and use of the

DTO. DTO has already been implemented in end-user software tools to facilitate the browsing

[11] and navigation of drug target data [13].

116 2 Methods

118 2.1   Drug Target data curation and classification

DTO places special emphasis on the four protein families that are central to the NIH IDG

initiative: non-olfactory GPCRs (oGPCRs), Kinases, Ion Channels and Nuclear Receptors. The

classifications and annotations of these four protein families were extracted, aggregated,

harmonized, and manually curated from various resources as described below, and further

enriched using the recent research literature. Proteins and their classification and annotations

were aligned with the Target Central Resource Databases (TCRD) database [11] developed by the

IDG project (http://targetcentral.ws/ProteinFam). In particular, the Target Development Level

(TDL) classification was obtained from the TCRD database.

Kinase classification: Kinases have been classified primarily into protein and non-protein

kinases. Protein kinases have been further classified into several groups, families, subfamilies.

Non-protein kinases have been classified in several groups, based on the type of substrates (lipid,

carbohydrate, nucleoside, other small molecule, *etc*.). Classification information has been

extracted and curated from various resources *e.g.* UniProt, ChEMBL, PhosphoSitePlus® (PSP)

[14], Sugen Kinase website (http://www.kinase.com/web/current/), and the literature, and was

organized manually, consolidated and checked for consistency. Kinase substrates were manually

curated from UniProt and the literature. Pseudokinases, which lack key functional residues and

are (to current knowledge) not catalytically active, were annotated based on the Sugen kinase

domain sequences and the literature.

Ion-channel classification: Ion channels have been classified primarily into family, subfamily,

sub-subfamily. Most of the information has been taken from the Transporter Classification

Database (http://www.tcdb.org/) [15], UniProt and several linked databases therein. The

classification is based on both the phylogenetic and functional information. Additional

information regarding the gating mechanism (voltage gated, ligand gated, etc.), transported ions,

protein structural and topological information has also been captured and included as separate

annotations. Moreover, the transported ions, such as chloride, sodium, etc. have been mapped to

the "Chemical entity" of the ChEBI reference database [16].

GPCR classification: GPCRs have been classified based on phylogenetic, functional and the

endogenous ligand information. The primary classification included class, group, family, and

subfamily. Most of the information has been taken from the GPCR.org classification and had

been updated using various sources *e.g*. IUPHAR [4], ChEMBL, UniProt and also from our

earlier GPCR ontology [12]. Furthermore, the information for the specific endogenous ligands

for each protein has been extracted from IUPHAR and has been integrated with the classification.

The information about the GPCR ligand and ligand type (lipid, peptide, *etc.*) has also been

included and has been mapped manually to the "Chemical entity" of the ChEBI reference

database.

Nuclear receptor classification: This information has been adopted directly from IUPHAR.

External DTO modules and mapping: Proteins mapped to UniProt. Genes were classified

identical to proteins (above) and mapped to Entrez gene. The external modules incorporated into

DTO were extracted from the Disease Ontology (DOID) [17], BRENDA Tissue Ontology (BTO)

[18], UBERON [19], the ontology of Chemical Entities of Biological Interest (ChEBI) [20], and

Protein Ontology (PRO) [21]. Data about over 1000 cell lines from the LINCS project [22] were

integrated and mapped to diseases and tissues. Gene/protein–disease [23] and protein–tissue

associations [24] were obtained from the JensenLab at Novo Nordisk Foundation Center for

Protein Research. Mapping between UBERON and BRENDA to integrate the tissue

associations of cell lines and proteins was retrieved from the NCBO BioPortal [25, 26] and

manually cross-checked. Target Development Level (TDL) were obtained from TCRD and

included as separate annotation for all protein families.

2.2   Drug Target Ontology (DTO) development

Ontology modeling: While curators stored all classification and annotation data into various

spreadsheets, ontologists created the ontological model to link the metadata obtained from those

spreadsheets, and to create the descriptive logic axioms to define ontology classes using a semi-

automated workflow. Finalizing and optimizing the ontology model or design pattern required

iterative processes of intensive discussions, modeling refinement, voting, and approval among

domain experts, data curators, IT developers, and ontologists. Once ontologists proposed a

conceptual ontology model, the selection of the most robust ontology model was guided by

simple criteria: correct representation of domain content, minimize the number of relations to link

all metadata, avoid contradiction with existing domain knowledge representation ontologies, such

as the OBO ontologies. For example, in our conceptual model, the relations among organ, tissue,

cell lines and anatomical entity were adopted and refined from the UBERON and CLO

ontologies. Some relations such as the shortcut relations between protein and associated disease

or tissue were created specifically for DTO, which was a compromise for accommodating the

large amount of data in DTO. Approval process of accepting a model proposal was driven by our

domain experts with contributing data curators, IT developers, and ontologists. The voting process

was rather informal; however, the model had to be agreed by all the parties involved in the

ontology development: domain experts, data curators, IT developers, and ontologists. Once the

most fit ontology model was chosen, this piece of modeling was used as template for a java tool

(described below) to generate all the OWL files by using above mentioned data annotation

spreadsheets as input.

Modularization approach: DTO was built with an extended modular architecture based on the

modular architecture designed and implemented for BAO [9]. The modularization strategy

developed previously was a layered architecture and used the modeling primitives, vocabularies,

modules and axioms. Most significantly, DTO's modular architecture includes an additional layer

to the modularization process by automating the creation of basic subsumption hierarchies and

select axioms such as the axioms for disease and tissue associations. Three types of files are used

in the modular architecture: vocabulary files, module files, and combined files, such as DTO_core

and DTO_complete. Vocabularies only contain concepts (classes with subsumption only).

Module layers enable combining vocabularies in flexible ways to create desired ontology

structures or subsets. Finally, in the combined files axioms are added to the vocabularies to

formally define the various concepts to allow logical inferences. Classes and relationships are

imported (directly or indirectly) from module and/or vocabulary files [9]. The external third party

ontologies were extracted using the OWL API or OntoFox [27].

OntoJOG tool: To streamline the building process, a Java tool (OntoJOG) was developed to

automatically create the OWL module files, vocabulary files as components of the whole

ontology. OntoJOG takes a flat CSV or TSV data file and loads it as a table either into a

temporary SQLite database or a permanent MySQL database. This table is then used as a

reference for creating and generating the OWL files as well as several relationship tables. The

relationship tables and the final OWL files are generated based on a CSV mapping file that

generates the commands for the OntoJOG to perform and the various options for those

commands. The commands from the mapping file are read in two passes to ensure everything is

added correctly. In the first pass all classes and their annotations are inserted into the relationship

tables and are assigned IDs as necessary, and in the second pass all axioms and relationships

between classes are created. After this process is completed an optional reparenting phase is

executed before each module of the ontology is generated into its own OWL vocabulary files with

an accompanying module file containing the relationships for the given vocabulary files.

Finally, the ontology was thoroughly reviewed, tested and validated by developers, domain

experts, and users in the IDG-KMC.

2.3   DTO Visualization

Data visualization is important, especially with the increasing complexity of the data. Ontology

visualization, correspondingly, has an appealing potential to help to browse and comprehend the

structures of ontologies. A number of ontology visualization tools have been developed and

applied as information retrieval aids, such as OntoGraf, OWLViz as part of the Ontology

development tool Protégé, and OntoSphere3D [28] among others. Further, studies and reviews

on different visualization tools, e.g. [29, 30] and [31], have been published by comparing each

tool's performances. Preference of visualization models depends on the type and query context

of the visualized network, also on users' needs.

Data-Drive Document (D3) is a relatively novel representation-transparent and dynamic

approach to visualize data on the web. It is a modern interactive visualization tool available as a

JavaScript library [29]. By selectively binding input data to arbitrary document elements, D3.js

enables direct inspection and manipulation of a native representation. The D3.js JavaScript

library gained popularity as a generic framework based on widely accepted web standards such

as SVG, JavaScript, HTML5 and CSS.

Consequently, we use the D3.js library for the interactive visualization of our DTO as part of the

Neo4J graphical database solution.

2.4   DTO and BAO integration to model LINCS data

The Library of Network-Based Cellular Signatures (LINCS) program has been generating a

reference "library" of molecular signatures, such as changes in gene expression and other cellular

phenotypes that occur when cells are exposed to a variety of perturbing agents. One of the LINCS

screening assays is a biochemical kinase profiling assay that measures drug binding using a panel

of ~440 recombinant purified kinases, namely, KINOMEscan assay. The HMS LINCS Center has

collected 165 KINOMEscan datasets in order to analyze the drug-target interaction. All these

LINCS KINOMEscan data were originally retrieved from Harvard Medical School (HMS)

LINCS DB (http://lincs.hms.harvard.edu/db/). KINOMEscan data was curated by domain experts

to map to both Pfam domains, and corresponding Kinases. Unique KINOMEscan domains and

annotations, including domain descriptions, IDs, names, gene symbols, phosphorylation status,

and mutations were curated from different sources, including the HMS LINCS DB, DiscoverX

KINOMEscan® assay list [32], Pfam (http://pfam.xfam.org/), and our previous modeling efforts

of the entire human Kinome (publication in preparation). The kinase domain classification into

group, family, *etc.* was the same as described above (kinase classification). Gatekeeper and hinge

residues were assigned based on structural alignment of existing kinase domain crystal structures

and structural models of the human kinome and sequence alignment with the full kinase protein

referenced by UniProt accession in the DTO. Pfam accession number and names were obtained

from Pfam [33]. The protocol and the KINOMEscan curated target metadata table were analyzed

by ontologists to create kinase domain drug target ontology model.

2.5   Ontology source access and license

The official DTO website is publicly available at http://drugtargetontology.org/, where it can be

visualized and searched. The DTO is an open source project, and released under a Creative

Commons 3.0 License. The source code including the development and release versions are freely

available at the URL: http://github.com/DrugTargetOntology/DTO . DTO is also published at the

NCBO BioPortal (https://bioportal.bioontology.org/ontologies/DTO).

3 Results

271 In what follows, the *italic* font represents terms, classes, relations, or axioms used in the

272 ontology.

3.1   Drug Targets definition and classification

Different communities have been using the term "drug target" ambiguously with no formal

generally accepted definition.   The DTO project develops a formal semantic model for drug

targets including various related information such as protein, gene, protein domain, protein

structure, binding site, small molecule drug, mechanism of action, protein tissue localization,

disease associations, and many other types of information.

The IDG project defines 'drug target' as "a native (gene product) protein or protein complex that

physically interacts with a therapeutic drug (with some binding affinity) and where this physical

interaction is (at least partially) the cause of a (detectable) clinical effect". DTO defined a DTO

specific term "*drug target role*". The text definition of "*drug target role*" is "a role played by a

material entity, such as native (gene product) protein, protein complex, microorganism, DNA,

etc., that physically interacts with a therapeutic or prophylactic drug (with some binding affinity)

and where this physical interaction is (at least partially) the cause of a (detectable) clinical effect."

At the current phase, DTO focuses on protein targets. DTO provides various asserted and

inferred hierarchies to classify drug targets. Below we describe the most relevant ones.

3.1.1 Target Development Level (TDL)

The IDG classified proteins into four levels with respect to the depth of investigation from a

clinical, biological and chemical standpoint (http://targetcentral.ws/) [8]:

1) T_{clin} are proteins targeted by approved drugs as they exert their mode of action [3]. The Tclin

proteins are designated drug targets under the context of IDG.

2) T_{chem} are proteins that can specifically be manipulated with small molecules better than

bioactivity cutoff values (30 nM for kinases, 100 nM for GPCRs and NRs, 10 uM for ICs, and 1

uM for other target classes), which lack approved small molecule or biologic drugs. In some

cases, targets have been manually migrated to Tchem through human curation, based on small

molecule activities from sources other than ChEMBL or Drug Central.

3) T_{bio} are proteins that do not satisfy the T_{clin} or T_{chem} criteria, which are annotated with a Gene

Ontology Molecular Function or Biological Process with an Experimental Evidence code, or

targets with confirmed OMIM phenotype(s), or do not satisfy the Tdark criteria detailed in 4).

4) T_{dark} refers to proteins that have been described at the sequence level and have very few

associated studies. They do not have any known drug or small molecule activities that satisfy the

activity thresholds detailed in 2), lack OMIM and GO terms that would match Tbio criteria, and

meet at least two of the following conditions:

•   A PubMed text-mining score < 5 [23]
•   <= 3 Gene RIFs [34]
•   <= 50 Antibodies available per Antibodypedia (http://antibodypedia.com)

3.1.2 Functional and phylogenetic classification

DTO proteins have been classified into various categories based on their structural

(sequence/domains) or functional similarity. A high-level summary of the classifications for

Kinases Ion Channels, GPCRs and Nuclear Receptors is shown in Figure 1. It should be noted

that, as indicated above, the classification information has been extracted from various database

and literature resources. The classification is subject to continuous updating for greater accuracy,

and enriching the DTO using the most recent information as it becomes available. The present

classification of the four protein families is briefly discussed below:

320
321 Most of the 578 kinases covered in the current version of DTO are protein kinases. These 514

322 PKs are categorized in 10 groups that are further sub-categorized in 131 families and 82

323 subfamilies. A representative classification hierarchy for MAPK1 is:

324 *Kinase > Protein Kinase > CMGC group > MAPK family > ERK subfamily > Mitogen-*
325 *activated Protein Kinase 1*
326

The 62 non-protein kinases are categorized in 5 groups depending upon the substrate that are

phosphorylated by these proteins. These 5 groups are further sub-categorized in 25 families and

7 subfamilies. There are two kinases that haven't been categorized yet in any of the above types

or groups.

The 334 Ion channel proteins (out of 342 covered in the current version of DTO) are categorized

in 46 families, 111 subfamilies, and 107 sub-subfamilies.

Similarly, the 827 GPCRs covered in the current version of DTO are categorized in 6 classes, 61

families and 14 subfamilies. The additional information whether any receptor has a known

endogenous ligand or is currently "orphan" is mapped with the individual proteins. Finally, the

48 nuclear hormone receptors are categorized in 19 NR families.

Figure 1. Summary of protein classification hierarchies for Kinase, Ion Channel, GPCR, and NR protein families.
Note that several other relevant target annotations have been incorporated into DTO.
340

3.1.3 Disease- and tissue-based classification

Target-disease associations and tissue expressions were obtained from the DISEASES [23]and

TISSUES [24] databases (see Methods). Examples of such classifications are available as

inferences in DTO (see below section 3.3.2).

3.1.4 Additional annotations and classifications

In addition to the phylogenetic classification of the proteins, there are several relevant properties

associated with them as additional annotations. For example, there are 46 PKs that have been

annotated as pseudokinases [35]. For ion channels, important properties, like transporter protein

type, transported ion(s), gating mechanism, etc. have been associated with the individual proteins.

The gating mechanism refers to the information regarding the factors that control the opening

and closing of the ion channels. The important mechanisms include voltage-gated, ligand-gated,

temperature-gated, mechanically-gated, etc. Similarly, for the GPCRs, the additional information

whether any receptor has a known endogenous ligand or is currently "orphan" is mapped with

the individual proteins. Current version of DTO has approximately 255 receptors that have

information available regarding the endogenous ligands.

The analysis of Drug target protein classification along with such relevant information associated

through separate annotations may lead to interesting inferences.

3.1.5 Chemical classifications

Known GPCR ligands and IC transported ions were categorized by chemical properties and

mapped to ChEBI (see methods). For example, depending upon their chemical structure and

properties, these known endogenous ligands for GPCRs have been categorized in seven types,

namely, amine, amino acid, carboxylic acid, lipid, peptide, nucleoside and nucleotide. Similarly,

the ions transported by the ion channel proteins and ion types (anion/cation) have been mapped

to ChEBI. These annotations together with mappings of substrates and ligands to the proteins

enable inferred classification of the proteins based on their chemical properties (see below).

3.2   DTO ontology implementation and modeling

3.2.1 Drug discovery target knowledge model of the DTO

The first version of the DTO includes detailed target classification and annotations for the four

IDG protein families. Each protein is related to four types of entities: gene, related disease,

related tissue or organ, and target development level. The conceptual model of DTO is

illustrated as a linked diagram with nodes and edges. Nodes represent the classes in the DTO,

and edges represent the ontological relations between classes. As shown in Figure 2, GPCRs,

kinases, ICs and NRs are types of proteins. GPCR binds GPCR ligands, and IC transports ions.

Most GPCR ligands and ion are types of chemical entity from ChEBI. Each protein has a target

development level (TDL), i.e., T_{clin}, T_{chem}, T_{bio} and T_{dark}. The protein is linked to gene by 'has

gene template' relation. The gene is associated with disease based on evidence from the

DISEASES database. The protein is also associated with some organ, tissue, or cell line using

some evidence from TISSUES database. The full DTO contains many more annotations and

classifications, and it is available at http://drugtargetontology.org/

DTO is implemented in OWL2-DL to enable further classification by inference reasoning and

SPARQL queries. The current version of DTO contains > 13,000 classes and > 220,000 axioms.

The DTO contains 827 GPCRs, 572 kinase, 342 ion channels (ICs), and 48 NRs.

Figure 2. Conceptual high-level model of main DTO entities

3.2.2 Modular implementation of the DTO combining auto-generated and expert axioms

In DTO, each of the four drug target families has two vocabulary files of gene and protein, respectively; other DTO-native categories were created as separate vocabulary files. Additional vocabulary files include quality, role, properties, and cell line classes and subclasses. A vocabulary file contains entities of a class, which only contains "is-a" hierarchies. For example, the GPCR gene vocabulary contains only GPCR gene list and its curated classification. DTO core imports all the DTO vocabulary files of four families, including genes and proteins, and necessary axioms were added. Finally, DTO core was imported into the DTO complete file, which includes other vocabulary files and external files. External ontologies used in DTO include: BTO, CHEBI, DOID, UBERON, Cell Line Ontology (CLO), Protein Ontology (PRO), Relations Ontology (RO) and Basic Formal Ontology (BFO). The DTO core and DTO external are imported into the DTO module with auto-generated axioms, which links entities from different vocabulary files. Besides the programmatically generated vocabularies and modules, DTO also contains manually generated vocabularies and modules, as shown in Figure 3.

Figure 3. DTO architecture

This approach significantly simplifies the maintenance of the ontology contents, especially when

the ontology is large in size. If the gene or protein list changes, only the vocabulary file and the

specific module file need to be updated instead of the whole ontology. In addition, external and

internal resources are maintained separately. This modularization approach facilitates automated

content updates from external resources including axioms generated using the above-mentioned

Java tool OntoJOG without the need to re-generate manually axiomized domain knowledge,

which can be very resource intensive, by simply separating them into two layers.

3.3   DTO to infer biologically and chemically relevant target classes

3.3.1 Chemically relevant target classes inferred by DTO

In addition to detailed asserted target classifications, DTO incorporates various other annotations

including GPCR endogenous ligands for GPCRs, transported ions for ICs, gating mechanism for

ICs, or pseudokinases. Endogenous GPCR ligands were manually mapped to ChEBI and

classified by chemical category such as amine, lipid, peptide, etc. As ligands relate to receptor

properties, GPCRs are typically classified based on their ligands; however, the ligand-based

classification is orthogonal to the classification based on class A, B, C, adhesion, etc. and it

changes as new ligands are deorphanized.

In DTO we therefore infer the ligand-based receptor, for example *aminergic GPCR*, *lipidergic*

GPCR, *peptidic GPCR*, and *orphan GPCR*, which are of particular interest, by defining their

logical equivalent as follows:

aminergic GPCR ≡ GPCR and ('binds molecular entity' some amine);

lipidergic GPCR ≡ GPCR and ('binds molecular entity' some lipid);

peptidic GPCR ≡ GPCR and ('binds molecular entity' some peptide);

orphan GPCR ≡ GPCR and (not ('binds molecular entity' some 'GPCR ligand')).

An example for 5-hydroxytryptamine receptor is shown in Figure 4; the receptor is inferred as

aminergic receptor based on its endogenous ligand.

Figure 4. Inferred classifications in DTO:
A) 5-hydroxytryptamine receptor as aminergic receptor based in its endogenous ligand,
B) mevalonate kinase as putative metabolic drug target.

DTO has classified 39 *aminergic GPCR*, 37 *lipidergic GPCR*, 119 *peptide GPCR* and 582

orphan GPCR.

3.3.2 Disease relevant target classes inferred by DTO

In a similar way, we categorized important disease targets by inference based on the protein -

disease association, which were modeled as 'strong', 'at least some', or 'at least weak' evidence

using subsumption. For example, DTO uses the following hierarchical relations to declare the

relation between a protein and the associated disease extracted from the DISEASES database.

has associated disease with at least weak evidence from DISEASES

-   *has associated disease with at least some evidence from DISEASES*

-   *has associated disease with strong evidence from DISEASES*

In the DISEASES database, the associated disease and protein are measured by a Z-Score [23].

In DTO, the "at least weak evidence" is translated as a Z-Score between zero and 2.4; the "some

evidence" is translated as a Z-Score between 2.5 and 3.5; and the "strong evidence" is translated

as a Z-Score between 3.6 and 5.

This allows querying or inferring proteins for a disease of interest by evidence. Diseases related

targets were defined using following axioms (as illustrative as examples):

Putative infectious disease targets ≡ Protein and ('has associated disease with strong evidence
from DISEASES' some 'disease of metabolism');
457
458 *Putative infectious disease targets ≡ Protein and ('has associated disease with strong evidence*
459 *from DISEASES' some 'disease by infectious agent');*
460
461 *Putative mental health disease targets ≡ Protein and ('has associated disease with strong*
462 *evidence from DISEASES' some 'developmental disorder of mental health')*
463
464 We created such inference examples in DTO, including 29 *metabolic disease targets*, 36 *mental*

465 *health disease targets*, and 1 *infectious disease targets*.

3.4 Modeling and integration of Kinase data from the LINCS project

The Library of Network-Based Cellular Signatures (LINCS, http://lincsproject.org/) program has

a systems biology focus. This project has been generating a reference "library" of molecular

signatures, such as changes in gene expression and other cellular phenotypes that occur when

cells are exposed to a variety of perturbing agents. The project also builds computational tools

for data integration, access, and analysis. Dimensions of LINCS signatures include the biological

model system (cell type), the perturbation (e.g. small molecules) and the assays that generate

diverse phenotypic profiles. LINCS aims to create a full data matrix by coordinating cell types

and perturbations as well as informatics and analytics tools. We have processed various LINCS

datasets, which are available at the LINCS Data Portal (http://lincsportal.ccs.miami.edu/).

LINCS data standards [22]are the foundation of LINCS data integration and analysis. We have

previously illustrated how integrated LINCS data can be used to characterize drug action [36];

among those, KINOME-wide drug profiling datasets.

We have annotated the KINOMEscan domains data generated from HMS LINCS KINOMEscan

dataset. The annotation includes domains descriptions, names, gene symbols, phosphorylation

status, and mutations. To integrate this information into DTO, we built a kinase domain module

following the modularization approach described in section 2.2.

We started with an example scenario given by domain expert shown below:

    - ABL1 is a tyrosine-protein kinase with UNIPROT ID P00519 (human). The sequence

    itself is 1131 AA long.

    - The KINOMEscan domain named "ABL1" is a part of the protein (AA Start/Stop

    S229/K512) containing the "Pkinase-Tyr" domain (pFam accession PF07714.14, AA

    Start/Stop   I242/F493)

490    - The KINOMEscan domain named "ABL1(F317I)-nonphosphorylated" is the same part

491    of the protein (AA Start/Stop S229/K512) with a mutation at position 317. pFam, anyway

492    identifies the same domain (accession PF07714.14)

493    - The KINOMEscan domain named "ABL1(F317I)-phosphorylated" is the same part of

494    the protein (AA Start/Stop S229/K512) with a mutation at position 317. pFam, anyway

495    identifies the same domain (accession PF07714.14)

496 In this scenario, there are four major ontological considerations or relations need to be

497 considered when building an ontology module (Figure 5).

499 **Figure 5.** Relations between protein, kinase domain, mutated kinase domain, phosphorylated kinase domain, and pfam domains in DTO.
500

3.4.1 Kinase domain and kinase protein

502 DTO use "*has part*" relation to link the kinase protein and kinase domain, which reflects the

503 biological reality that kinase domain is a partial protein.

3.4.2 Kinase domain variations: mutated kinase domain and phosphorylated kinase domain

Mutated kinase domain relates to its wild type kinase domain by simply using "*is mutated form*

of" relation. Both, phosphorylated and nonphosphorylated forms of a kinase domain are child of

a kinase domain from which they were modified to current phosphorylation variation forms.

Since the KINOMEscan assay cannot provide the specific phosphorylation position information,

the definition of a phosphorylated form of a kinase domain, either mutated or wild-type, is

generally constituted using an ad-hoc axiom: *has part some "phosphorylated residue"*. Note

that "*phosphorylated residue*" (MOD_00696) is an external class imported from Protein

Modification Ontology (MOD).

3.4.3 Pfam domain mapping to kinase domain and its variations

DTO data curators / domain experts have mapped all the kinase domains (including their

variations) to Pfam families using sequence level data. This information was captured by using

"*map to pfam domain*" relation, which links a kinase domain to a pfam domain.

Figure 5 shows how in DTO the above scenario is modeled by connecting *ABL1 Kinase domain*

with *ABL1 protein* using relation *is part of*, as well as how kinase domain relates to Pfam domain

using *map to pfam domain* relation. In this scenario, all the variations of ABL1 kinase domain

are mapped to the same Pfam domain.

3.4.4 Kinase gatekeeper and mutated amino acid residues

The kinase gatekeeper position is an important recognition and selectivity element for small

molecule binding. One of the mechanisms by which cancers evade kinase drug therapy is by

mutation of key amino acids in the kinase domain. Often the gatekeeper is mutated. Located in

the ATP binding pocket of protein kinases, the gatekeeper residue has been shown to influence

selectivity and sensitivity to a wide range of small molecule inhibitors. Kinases that possess a

small side chain at this position (Thr, Ala, or Gly) are readily targeted by structurally diverse

classes of inhibitors, whereas kinases that possess a larger residue at this position are broadly

resistant [37].

DTO defines a "*gatekeeper role*" to capture any residue that is annotated as a gatekeeper. In the

case of ABL1 kinase domain, the THR74 within the ABL1 kinase domain is identified as a

gatekeeper by the data curator / domain expert. This gatekeeper residue is further mapped to the

315th residue located in the whole ABL1 kinase amino acid sequence. DTO defines a term:

THR315 in ABL1 kinase domain with an axiom of "*has role some gatekeeper role*". With an

equivalence definition of term "*gatekeeper residue*" as anything that satisfied the condition of

"*has role some gatekeeper role*", DTO can group all the gatekeeper residues in this

KINOMEscan dataset (Figure 6).

542

543 **Figure 6.** Protégé screen shot shows the inferred subclasses of gatekeeper residue.
544

3.5 DTO shines light on Tdark proteins

With integrated information about drug targets available in DTO, it is possible, for example to

query information for Tdark kinases for which data in LINCS is available. Kinases in the LINCS

KINOMEscan assay were annotated by their (kinase) domain, phosphorylation status, gatekeeper

residue and mutations as explained above. To illustrate this integration, we conducted a simple

SPARQL query to identify Tdark (kinase) proteins that have a gatekeeper annotation in DTO.

The SPARQL query we use to search DTO are as following:

```
552  PREFIX rdfs: <http://www.w3.org/2000/01/rdf-schema#>
553  PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
554  PREFIX owl: <http://www.w3.org/2002/07/owl#>
555  PREFIX dto: <http://www.drugtargetontology.org/dto/>
556
557  select ?subject ?subject_label ?p_label ?tdl_label
558  Where {
559     ?subject rdfs:subClassOf ?s1 .
560         ?s1 owl:onProperty <http://purl.obolibrary.org/obo/RO_0000087>; owl:someValuesFrom
561  dto:DTO_00000002 .
562         ?subject rdfs:label ?subject_label .
563         ?subject owl:equivalentClass ?s2 .
564         ?s2 owl:intersectionOf ?list .
565         ?list rdf:rest*/rdf:first ?l .
566         ?l owl:onProperty dto:DTO_90000020; owl:allValuesFrom ?k .
567         ?k rdfs:subClassOf* dto:DTO_61000000 .
568         ?k rdfs:subClassOf ?s3 .
569         ?s3 owl:onProperty dto:DTO_90000020; owl:someValuesFrom ?p .
570         ?p rdfs:subClassOf* <http://purl.obolibrary.org/obo/PR_000000001> .
571         ?p rdfs:label ?p_label .
572         ?p rdfs:subClassOf ?s4 .
573         ?s4           owl:onProperty<http://www.drugtargetontology.org/dto/DTO_91000020>;
574  owl:someValuesFrom ?TDL .
575         ?TDL rdfs:label ?tdl_label
576  }
577
```

We found in total 378 (kinase) protein containing gatekeeper residue annotations. Of those 378

proteins, (Serine/threonine-protein kinase NEK10) is a Tdark protein, two (Mitogen-activated

protein kinase 4 and Serine/threonine-protein kinase WNK1) are Tbio proteins, 320 are Tchem

proteins, and 54 are Tclin proteins (Supplementary table 1). We then could look for the

associated disease and tissue expression information in DTO. For example, the Serine/threonine-

protein kinase NEK10 (Tdark) contains a gatekeeper residue, Thr301, which is associated with

breast cancer by "weak evidence", and expressed in liver, testis, trachea with "strong evidence".

This way, DTO provides rich information to prioritize proteins for further study, linked directly

to KINOMEscan results via the LINCS Data Portal.

3.6 Integration of DTO in software applications

3.6.1 DTO Visualization

The drug target ontology consists of > 13,000 classes and > 122,000 links. Our visualization has

two options: a) a static pure ontology viewer starting with the top-level concepts featured by a

collapsible tree layout (mainly for browsing concepts) and b) a dynamic search and view page

where a search-by-class user interface is combined with a collapsible force layout for a deeper

exploration. Figure 7 shows an excerpt of an interactive visualization of the DTO. Users can

search for classes, alter the visualization by showing siblings, zoom in/out, and alter the figure by

moving classes within the graph for better visualization.

Figure 7. An excerpt of an interactive visualization of the DTO. The viewer is available at http://drugtargetontology.org

3.6.2 Pharos: The IDG Web Portal

- 27 -

Pharos is the front-end Web Portal of the IDG project (https://pharos.nih.gov). Pharos was

designed and built to encourage "serendipitous browsing" of a wide range of protein drug target

information curated and aggregated from a multitude of resources [11]. Via a variety of user

interface elements to search, browse and visualize drug target information, Pharos can help

researchers to identify and prioritize drug targets based a variety of criteria. The DTO is an

integral part of Pharos; it's user interface has been designed to integrate DTO at multiple levels

of detail. At the highest level, the user can get a bird's-eye view of the target landscape in terms

of the development level through the interactive DTO circle packing visualization

(https://pharos.nih.gov/dto); see Figure 8. For any suitable set of targets (e.g., as a result of

searching and/or filtering), Pharos also provides an interactive sunbrust visualization of the DTO

as a convenient way to help the user navigate the target hierarchy. At the most specific level,

each appropriate target record is annotated with the full DTO path in the form of a breadcrumb.

This not only gives the user context but also allows the user to easily navigate up and down the

target hierarchy with minimal effort.

Figure 8. visualization of the drug target ontology using the circle packing layout available in the D3 visualization framework.
617

3.6.3 Tin-X: Target Importance and Novelty Explorer

TIN-X is a specialized, user-friendly Web-based tool to explore the relationship between

proteins and diseases (http://newdrugtargets.org/) extracted from the scientific literature [13].

TIN-X supports searching and browsing across proteins and disease based on ontological

classifications. DTO is used to organize proteins and content can be explored using the DTO

hierarchy.

4 CONCLUSION AND DISCUSSION

The IDG program is a systematic effort to prioritize understudied, yet likely druggable protein

targets for the development of chemical probes and drug discovery entry points [3]. DTO covers

proteins as prospective druggable targets. Druggability can be considered from a structural point

of view, i.e. proteins to which small molecules can bind. This structural druggability is implicit

in the selection of the IDG target families, GPCRs, kinases, ion channels and nuclear receptors

for which there exist a large number of small molecule binders. Another aspect of druggability

is the ability to induce a therapeutic benefit by modulating the biological function of the protein

that the drug binds to. Establishing and prioritizing this functional druggability is one the main

goals of the IDG project. DTO includes knowledge of protein disease association and the target

development level for all proteins as a foundation to formally describes drug mechanisms of

actions. DTO provides a framework and formal classification based on function and

phylogenetics, rich annotations of (protein) drug targets along with other chemical, biological,

and clinical classifications and relations to diseases and tissue expression. This may facilitate the

rational and systematic development of novel small molecule drugs by integrating mechanism of

action (drug targets) with disease models, mechanisms, and phenotypes. DTO is already used in

the Target Central Resource Database (TCRD - http://juniper.health.unm.edu/tcrd), the IDG

main portal Pharos (https://pharos.nih.gov/) and the Target Importance and Novelty eXplorer

(TIN-X - http://newdrugtargets.org/) to prioritize drugs by novelty and importance. The search

and visualization uses the inferred DTO model, including the inferred classes described in this

report.

We have illustrated how DTO and other ontologies are used to annotate, categorize and integrate

knowledge about kinases, including nuanced target information of profiling data generated in the

LINCS project. By doing so, DTO facilitates contextual data integration, for example

considering the kinase domain or the full protein, phosphorylation status or even information

important for small molecule binding, such as gatekeeper residues and point mutations. As we

develop DTO and other resources, we will facilitate the otherwise challenging integration and

formal linking of biochemical and cell-based assays, phenotypes, disease models, omics data,

drug targets and drug poly-pharmacology, binding sites, kinetics and many other processes,

functions and qualities that are at the core of drug discovery. In the era of big data, systems-level

models for diseases and drug action, and personalized medicine, it is a critical requirement to

harmonize and integrate these various sources of information. DTO is designed to be easily

extensible and integrative to other recourses, especially applying the modularization approach.

The modularization approach makes it easy for developers to create, modify, expand and

maintain the ontology, especially for the big scale ontologies. Several drug target-related

resources have been developed, such as the ChEMBL Drug Target Slim [38], where GO

annotations are available for drug targets in ChEMBL. Protein Ontology recently enhanced the

protein annotation with pathway information and phosphorylation sites information [39].

Comprehensive FDA proved drug and target information is available in [3]. As a similar and

complementary resource, Open Targets project (https://www.opentargets.org/) is developed by

partnership between pharmaceutical companies and EBI. DTO aims to incorporate these newly

developed resources, and support an integrative drug discovery data portal as a community

resource for academics use.

List of Abbreviations:

BFO Basic Formal Ontology; **BTO** BRENDA Tissue Ontology; **ChEBI** Chemical Entities of

Biological Interest; **CLO** Cell Line Ontology; **DOID** Disease Ontology; **DTO** Drug Target

Ontology; **GPCRs** G-protein-coupled receptors; **IC** Ion Channel; **IDG** Illuminating the

Druggable Genome; **IDG-KMC** IDG Knowledge Management Center; **IUPHAR** International

Union of Basic and Clinical Pharmacology; **LINCS** The Library of Network-Based Cellular

Signatures; **NR** Nuclear Receptor; **PRO** Protein Ontology; **RO** Relations Ontology; **TCRD**

Target Central Resource Databases; **TDL** Target Development Level; **UBERON** Uber Anatomy

Ontology

Competing interests

681   The authors declare that they have no competing interests.

Authors' contributions

YL: ontology development and implementation; SM: content curation and annotation; HKM:

ontology modularization and implementation; JPT: software and database tools to build the

ontology; DV: kinase domain annotation, DTO curation; MF: kinase domain module, integration

with LINCS data; AK: database schema and software tools to build ontology; DTN:

implementation of DTO in Pharos, UI design and implementation; LJJ: integration of

DISEASES and TISSUES into DTO; RG: Pharos UI design and DTO implementation; SLM:

IDG database and synchronization to DTO ; OU: development and implementation of DTL; VS:

LINCS data processing and annotation; JD: DTO visualizer, web-interface and backend ; NN:

DTO database and software tools; CC: DTO website and processes; CM: software design; UV:

ontology modeling and visualization; JJY: implementation of DTO in TIN-X, UI design; CGB:

TDL development, TIN-X DTO integration; TO: DTL classification and annotation, UI design,

content curation, project coordination; SCS: envisioned DTO, ontology development and

implementation, content curation, database and software design, project coordination.

YL, SM and SCS wrote the manuscript; HKM, DTN, RG, UV, TO contributed to writing the

manuscript; all co-authors approve the manuscript,

Acknowledgements

This work was supported by grants U54CA189205 (Illuminating the Druggable Genome

Knowledge Management Center, IDG-KMC) and U54HL127624 (BD2K LINCS Data

Coordination and Integration Center, DCIC). The IDG-KMC (http://targetcentral.ws/) is a

component of the Illuminating the Druggable Genome (IDG) project

(https://commonfund.nih.gov/idg) awarded by the NCI. The BD2K LINC DCIC is awarded by

the National Heart, Lung, and Blood Institute through funds provided by the trans-NIH Library

of Integrated Network-based Cellular Signatures (LINCS) Program (http://www.lincsproject.org/)

and the trans-NIH Big Da-ta to Knowledge (BD2K) initiative (https://datascience.nih.gov/bd2k).

Both IDG and LINCS are NIH Common Fund projects. We also acknowledge resources from

the Center for Computational Science (CCS) at the University of Miami.

References

1.   Jones LH, Bunnage ME: **Applications of chemogenomic library screening in drug discovery**. *Nat Rev Drug Discov* 2017.

2.   Russ AP, Lampel S: **The druggable genome: an update**. *Drug Discov Today* 2005, **10**(23-24):1607-1610.

3.   Santos R, Ursu O, Gaulton A, Bento AP, Donadi RS, Bologa CG, Karlsson A, Al-Lazikani B, Hersey A, Oprea TI *et al*: **A comprehensive map of molecular drug targets**. *Nat Rev Drug Discov* 2017, **16**(1):19-34.

4.   Southan C, Sharman JL, Benson HE, Faccenda E, Pawson AJ, Alexander SP, Buneman OP, Davenport AP, McGrath JC, Peters JA *et al*: **The IUPHAR/BPS Guide to PHARMACOLOGY in 2016: towards curated quantitative interactions between 1300 protein targets and 6000 ligands**. *Nucleic Acids Res* 2016, **44**(D1):D1054-1068.

5.   Mi H, Poudel S, Muruganujan A, Casagrande JT, Thomas PD: **PANTHER version 10: expanded protein families and functions, and analysis tools**. *Nucleic Acids Res* 2016, **44**(D1):D336-342.

6.   Qin C, Zhang C, Zhu F, Xu F, Chen SY, Zhang P, Li YH, Yang SY, Wei YQ, Tao L *et al*: **Therapeutic target database update 2014: a resource for targeted therapeutics**. *Nucleic Acids Res* 2014, **42**(Database issue):D1118-1123.

7.   Gao Z, Li H, Zhang H, Liu X, Kang L, Luo X, Zhu W, Chen K, Wang X, Jiang H: **PDTD: a web-accessible protein database for drug target identification**. *BMC Bioinformatics* 2008, **9**:104.

8.   **Unexplored opportunities in the druggable human genome** [http://www.nature.com/nrd/posters/druggablegenome/index.html]

9.   Abeyruwan S, Vempati UD, Kucuk-McGinty H, Visser U, Koleti A, Mir A, Sakurai K, Chung C, Bittker JA, Clemons PA *et al*: **Evolving BioAssay Ontology (BAO): modularization, integration and applications**. *J Biomed Semantics* 2014, **5**(Suppl 1 Proceedings of the Bio-Ontologies Spec Interest G):S5.

10.   Vempati UD, Przydzial MJ, Chung C, Abeyruwan S, Mir A, Sakurai K, Visser U, Lemmon VP, Schurer SC: **Formalization, annotation and analysis of diverse drug and probe screening assay datasets using the BioAssay Ontology (BAO)**. *PLoS One* 2012, **7**(11):e49198.

11.   Nguyen DT, Mathias S, Bologa C, Brunak S, Fernandez N, Gaulton A, Hersey A, Holmes J, Jensen LJ, Karlsson A *et al*: **Pharos: Collating protein information to shed light on the druggable genome**. *Nucleic Acids Res* 2017, **45**(D1):D995-D1002.

12.   Przydzial MJ, Bhhatarai B, Koleti A, Vempati U, Schurer SC: **GPCR ontology: development and application of a G protein-coupled receptor pharmacology knowledge framework**. *Bioinformatics* 2013, **29**(24):3211-3219.

13.   Cannon DC, Yang JJ, Mathias SL, Ursu O, Mani S, Waller A, Schurer SC, Jensen LJ, Sklar LA, Bologa CG *et al*: **TIN-X: Target Importance and Novelty Explorer**. *Bioinformatics* 2017.

14.   Hornbeck PV, Zhang B, Murray B, Kornhauser JM, Latham V, Skrzypek E: **PhosphoSitePlus, 2014: mutations, PTMs and recalibrations**. *Nucleic Acids Res* 2015, **43**(Database issue):D512-520.

15.   Saier MH, Jr., Reddy VS, Tsu BV, Ahmed MS, Li C, Moreno-Hagelsieb G: **The**
Transporter Classification Database (TCDB): recent advances. *Nucleic Acids Res*
2016, **44**(D1):D372-379.

16.   Hastings J, de Matos P, Dekker A, Ennis M, Harsha B, Kale N, Muthukrishnan V, Owen
G, Turner S, Williams M *et al*: **The ChEBI reference database and ontology for**
biologically relevant chemistry: enhancements for 2013. *Nucleic Acids Res* 2013,
41(Database issue):D456-463.

17.   Kibbe WA, Arze C, Felix V, Mitraka E, Bolton E, Fu G, Mungall CJ, Binder JX, Malone
J, Vasant D *et al*: **Disease Ontology 2015 update: an expanded and updated database**
of human diseases for linking biomedical knowledge through disease data. *Nucleic*
Acids Res 2015, **43**(Database issue):D1071-1078.

18.   Gremse M, Chang A, Schomburg I, Grote A, Scheer M, Ebeling C, Schomburg D: **The**
BRENDA Tissue Ontology (BTO): the first all-integrating ontology of all organisms
for enzyme sources. *Nucleic Acids Res* 2011, **39**(Database issue):D507-513.

19.   Haendel MA, Balhoff JP, Bastian FB, Blackburn DC, Blake JA, Bradford Y, Comte A,
Dahdul WM, Dececchi TA, Druzinsky RE *et al*: **Unification of multi-species vertebrate**
anatomy ontologies for comparative biology in Uberon. *J Biomed Semantics* 2014,
5:21.

20.   Hastings J, Owen G, Dekker A, Ennis M, Kale N, Muthukrishnan V, Turner S, Swainston
N, Mendes P, Steinbeck C: **ChEBI in 2016: Improved services and an expanding**
collection of metabolites. *Nucleic Acids Res* 2016, **44**(D1):D1214-1219.

21.   Natale DA, Arighi CN, Blake JA, Bult CJ, Christie KR, Cowart J, D'Eustachio P, Diehl
AD, Drabkin HJ, Helfer O *et al*: **Protein Ontology: a controlled structured network of**
protein entities. *Nucleic Acids Res* 2014, **42**(Database issue):D415-421.

22.   Vempati UD, Chung C, Mader C, Koleti A, Datar N, Vidovic D, Wrobel D, Erickson S,
Muhlich JL, Berriz G *et al*: **Metadata Standard and Data Exchange Specifications to**
Describe, Model, and Integrate Complex and Diverse High-Throughput Screening
Data from the Library of Integrated Network-based Cellular Signatures (LINCS). *J*
Biomol Screen 2014, **19**(5):803-816.

23.   Pletscher-Frankild S, Palleja A, Tsafou K, Binder JX, Jensen LJ: **DISEASES: text**
mining and data integration of disease-gene associations. *Methods* 2015, **74**:83-89.

24.   Santos A, Tsafou K, Stolte C, Pletscher-Frankild S, O'Donoghue SI, Jensen LJ:
Comprehensive comparison of large-scale tissue expression datasets. *PeerJ* 2015,
3:e1054.

25.   Salvadores M, Alexander PR, Musen MA, Noy NF: **BioPortal as a Dataset of Linked**
Biomedical Ontologies and Terminologies in RDF. *Semant Web* 2013, **4**(3):277-284.

26.   Whetzel PL, Noy NF, Shah NH, Alexander PR, Nyulas C, Tudorache T, Musen MA:
BioPortal: enhanced functionality via new Web services from the National Center
for Biomedical Ontology to access and use ontologies in software applications.
Nucleic Acids Res 2011, **39**(Web Server issue):W541-545.

27.   Xiang Z, Courtot M, Brinkman RR, Ruttenberg A, He Y: **OntoFox: web-based support**
for ontology reuse. *BMC Res Notes* 2010, **3**:175.

28.   Bosca A, Bonino D: **OntoSphere3D: A Multidimensional Visualization Tool for**
Ontologies. In: *17th International Workshop on Database and Expert Systems*
Applications (DEXA'06): 4-8 Sept. 2006 2006; 2006: 339-343.

29.   Bostock M, Ogievetsky V, Heer J: **D³ Data-Driven Documents**. *IEEE*
Transactions on Visualization and Computer Graphics 2011, **17**(12):2301-2309.
30.   Ramakrishnan S, Vijayan A: **A study on development of cognitive support features in**
recent ontology visualization tools. *Artif Intell Rev* 2014, **41**(4):595-623.
31.   Sivakumar R, Arivoli PV, Sri AVVM: **Ontology Visualization Protégé Tools – a**
Review. In*: 2011*; 2011.
32.   .
33.   Coggill P, Finn RD, Bateman A: **Identifying protein domains with the Pfam database**.
Curr Protoc Bioinformatics 2008, **Chapter 2**:Unit 2 5.
34.   Mitchell JA, Aronson AR, Mork JG, Folk LC, Humphrey SM, Ward JM: **Gene indexing:**
characterization and analysis of NLM's GeneRIFs. *AMIA Annu Symp Proc* 2003:460-
464.
35.   Fabbro D, Cowan-Jacob SW, Moebitz H: **Ten things you should know about protein**
kinases: IUPHAR Review 14. *Br J Pharmacol* 2015, **172**(11):2675-2700.
36.   Vidovic D, Koleti A, Schurer SC: **Large-scale integration of small molecule-induced**
genome-wide transcriptional responses, Kinome-wide binding affinities and cell-
growth inhibition profiles reveal global trends characterizing systems-level drug
action. *Front Genet* 2014, **5**:342.
37.   Gibbons DL, Pricl S, Kantarjian H, Cortes J, Quintas-Cardama A: **The rise and fall of**
gatekeeper mutations? The BCR-ABL1 T315I paradigm. *Cancer* 2012, **118**(2):293-
299.
38.   Mutowo P, Bento AP, Dedman N, Gaulton A, Hersey A, Lomax J, Overington JP: **A**
drug target slim: using gene ontology and gene ontology annotations to navigate
protein-ligand target space in ChEMBL. *J Biomed Semantics* 2016, **7**(1):59.
39.   Natale DA, Arighi CN, Blake JA, Bona J, Chen C, Chen SC, Christie KR, Cowart J,
D'Eustachio P, Diehl AD *et al*: **Protein Ontology (PRO): enhancing and scaling up the**
representation of protein entities. *Nucleic Acids Res* 2017, **45**(D1):D339-D346.
825