Compressed timeline of recent experience in monkey lPFC

Zoran Tiganj
Center for Memory and Brain
Department of Psychological and Brain Sciences
Boston University
Boston, MA 02215

Jason A. Cromer, Jefferson E. Roy, Earl K. Miller
The Picower Institute for Learning and Memory
Department of Brain and Cognitive Sciences
Massachusetts Institute of Technology
Cambridge, MA 02139

Marc W. Howard
Center for Memory and Brain
Department of Psychological and Brain Sciences
Boston University
Boston, MA 02215

Abstract

Cognitive theories suggest that working memory maintains not only the identity of recently-presented stimuli but also a sense of the elapsed time since the stimuli presentation. Previous studies of the neural underpinnings of working memory have focused on sustained firing, which can account for maintenance of the stimulus identity, but not for representation of the elapsed time. We analyzed single-unit recordings from the macaque lateral prefrontal cortex (lPFC) during performance of a delayed-match-to-category task. The sample stimulus triggered a consistent sequence of neurons, each neuron in the sequence firing during a circumscribed period of time. The sequences initiated by different sample stimuli were distinct but overlapping, with the degree of overlap reflecting the visual similarity of the stimuli that caused the sequences. These sequences of neurons encoded both stimulus identity and the elapsed time. The temporal code became less precise as the sample stimulus receded into the past. These findings suggest that working memory is maintained as a compressed timeline, consistent with longstanding cognitive theories of human memory.

Introduction

Theories of human memory have long suggested that memory depends on a representation of the recent past in which events are organized on a compressed timeline (James, 1890; Crowder, 1976; Brown, Neath, & Chater, 2007; Howard, Shankar, Aue, & Criss, 2015). This implies that memory provides access to what happened when; a neural representation supporting a timeline should enable reconstruction of the chronological order of previous stimuli as well as their identity. If the timeline is compressed, then as stimuli recede into the past, their time of occurrence and identity is represented with less and less accuracy.

The neural underpinnings of working memory are studied using tasks which require maintenance of a small amount of information across a (typically brief) delay interval. Most neural models assume that working memory maintenance relies on sustained firing of neurons (Goldman-Rakic, 1995; Goldman, 2009; Egorov, Hamam, Fransén, Hasselmo, & Alonso, 2002). According to this model, when a to-be-remembered stimulus is presented, it activates a specific population of neurons that remain firing at an elevated rate for as long as necessary until the information is no longer required. A great deal of work in computational neuroscience has developed mechanisms for sustained stimulus-specific firing at the level of circuits, channels, and LFPs (Amit & Brunel, 1997; Compte, Brunel, Goldman-Rakic, & Wang, 2000; Durstewitz, Seamans, & Sejnowski, 2000; Chaudhuri & Fiete, 2016; Lundqvist, Herman, & Lansner, 2011; Mongillo, Barak, & Tsodyks, 2008; Sandberg, Tegnér, & Lansner, 2003). However, if the firing rate is constant while the stimulus is maintained in working memory, then information about the passage of time is lost. Thus a memory representation based on sustained firing would not constitute a timeline as predicted by the cognitive theories.

Time cells, neurons that fire sequentially, each for a circumscribed period of time, during the delay interval of a memory task (Pastalkova, Itskov, Amarasingham, & Buzsaki, 2008; MacDonald, Lepage, Eden, & Eichenbaum, 2011), provide a neural representation of elapsed time. By examining which time cell is firing at a particular moment, one can reconstruct how far in the past the delay began. Behavioral work on timing shows that the accuracy in estimating the elapsed time decreases with the amount of time to be estimated (e.g., Rakitin et al., 1998; Lewis & Miall, 2009). Two properties of time cells are consistent with an analogous decrease in temporal accuracy. First, time fields later in the sequence should be more broad (i.e., less precise). Second, there should be more neurons with time fields early in the delay and fewer neurons representing times further in the past. Both of these properties have been observed, primarily in rodent work, for time cells in the hippocampus (Howard et al., 2014; Salz et al., 2016), entorhinal cortex (Kraus et al., 2015), medial prefrontal cortex (mPFC) (Tiganj, Kim, Jung, & Howard, 2016), and striatum (Jin, Fujii, & Graybiel, 2009; Mello, Soares, & Paton, 2015; Akhlaghpour et al., 2016).

The cognitive models for a compressed timeline predict that distinct sequences of time cells should be triggered by distinct stimuli. In this way, one could directly read off not only what stimulus occurred in the past, but also how far in the past that stimulus was presented. Thus far there has been little evidence for conjunctive "what and when" information in populations of time cells. Earlier studies of time cells have not observed stimulus-specific time cell firing (e.g., Akhlaghpour et al., 2016 but see MacDonald, Carrow, Place, & Eichenbaum, 2013) leading some theorists to hypothesize that what and when

information are maintained separately (Friston & Buzsáki, 2016) in much the same way that what and where information are presumably segregated in the visual system.

Results

In this study we analyzed recordings from 500 units in lateral prefrontal cortex (lPFC) of two macaque monkeys during performance of a delayed match to category working memory task initially reported in Cromer, Roy, and Miller (2010). The method is summarized in Figure 1. Neurons in lateral PFC (lPFC) are known to maintain stimulus information during the delay. Here we focus on the units that showed temporal modulation, with special attention to the existence of stimulus-specific time cells, as predicted by cognitive models of working memory (Howard et al., 2015). In order to facilitate comparison of the neural phenomena to theoretical models, we also include simulations of a computational model for a compressed neural timeline (Shankar & Howard, 2012, 2013; Howard et al., 2014).

Units carrying temporal information

Out of 500 analyzed units 229 were classified as time cells. Several examples of firing activity of those units are shown in Figure 2. The time cells activated sequentially, spanning the entire interval. The temporal profiles of all 229 time cells averaged across trials are shown on Figure 3A. The cells are sorted by the peak time of the estimated Gaussian shaped time fields (μ_t).

Temporal information was coded with decreasing accuracy as the trial elapsed

There are two ways that a population of time cells would show decreasing temporal accuracy. First, the width of time fields should increase as the trial elapses. Second, the number of units with time fields earlier in the delay should be larger than the number later in the delay. Both of these properties were observed.

First, the width of the central ridge in Figure 3A increases from the left of the plot to the right of the plot, suggesting that units that fire earlier in the trial tend to have narrower time fields than the units that fire later. This impression was confirmed by analyses of the across-units relationship between the peak time (μ_t) and the standard deviation (σ_t) of the estimated Gaussian shaped time fields (Figure 4A). The correlation between the peak time and the width was significant (Pearson's correlation 0.50, $p < 10^{-15}$). A linear regression model linking the peak time (independent variable) and the width (dependent variable) gave an intercept of 0.10 ± 0.01 (mean $\pm$ SE), $p < 10^{-13}$, and a slope of 0.16 ± 0.02, $p < 10^{-15}$. To the extent the relationship is linear, it confirms a key quantitative prediction of a scale-invariant timeline; the dashed green line in Figure 4A is the prediction derived from the theoretical model (see methods for details).

Second, the number of time fields later in the trial was smaller than the number of time fields earlier in the interval. This can be seen from the fact that the central ridge in Figure 3A does not follow a straight line, as would have been the case if it followed a uniform distribution. Rather, the curve flattens as the interval proceeds. To quantify this, we examined the distribution of the peak times across time cells (Figure 4B). The KS test rejected the hypothesis that the distribution of the peak times is uniform, $D(229) = 0.17$, $p < 0.005$. The dashed green line in Figure 4B is the cumulative that would be expected if

A

B

Figure 1. **Behavioral Task. A.** Stimuli were divided into two category sets, ANIMALS and CARS; each category set consisted of two categories. The ANIMAL category set consisted of CATS and DOGS and the CAR category set consisted of SPORTS CARS and SEDANS. Stimuli were morphed combinations of prototypes within a given category set. **B.** Two monkeys performed a delayed match to category task. On each trial, the monkey was required to respond to whether a test stimulus matched the category of the sample stimulus. To perform the task correctly the animal had to maintain a memory representation of the stimulus category throughout the sample and delay periods. Reproduced from Cromer et al. (2010).

Figure 2. **Representative examples of units classified as time cells.** Each of the five columns shows activity of single unit. For each unit, the plot in the top row shows a raster of spikes across trials irrespective of the stimulus category. The bottom row shows the averaged trial activity (solid green line), the model fit with only a constant term (dotted blue line) and the model fit with a constant term and a Gaussian-shaped time field (dashed red line). See methods for details. The units were chosen such that the estimated peak time (μ_t) increases progressively from the first unit to the fifth unit.

Figure 3. **lPFC time fields show decreasing temporal accuracy for events further in the past. A.** Activity of all 229 units classified as time cells during the 1.6 s interval. Each row on the heatplot corresponds to a single unit and displays the firing rate (normalized to 1) averaged across all trials. Red corresponds to high firing rate; blue corresponds to low firing rate. The units are sorted with respect to the peak time estimated for their time field. There are two features related to temporal accuracy that can be seen from examination of this plot. First, time fields later in the delay are more broad than time fields earlier in the delay. This can be seen as the widening of the central ridge as the peak moves to the right. In addition the peak times of the time cells were not evenly distributed across the delay, with later time periods represented by fewer cells than early time periods. This can be seen in the curvature of the central ridge; a uniform distribution of time fields would manifest as a straight line. **B.** Ensemble similarity of all 229 time cells given through a cosine of the angle between normalized firing rate population vectors. The angle is computed at all pairs of time points during the observed interval. The bins along the diagonal are necessarily equal to 1 (warmest color). The similarity spreads out indicating that the representation changes more slowly later in the observed interval than it does earlier in the observed interval.

Figure 4. **As the trial elapses, time cells in lPFC show broader and less frequent time fields. A.** Width of the time fields increases with the peak time. Each dot represents the best-fitting parameters for a single unit classified as a time cell. There is no apparent difference between category/category set specific time cells (red) and the non-specific time cells (blue). The solid black line shows the results of linear regression (only the slope is shown, without the intercept term). The dashed green line is the relationship between the width and the peak time of time cells generated with the computational model with parameter $k = 15$. **B.** Peak times of the time fields are non-uniformly distributed along the delay interval. The cumulative density function for the parameter describing the peak firing of each time cell is shown as the solid black line. A uniform distribution is represented with a dotted red line. More time cells had time fields earlier in the delay interval and fewer had time fields later in the delay interval. The dashed green line shows the a power law distribution with exponent -1 with values chosen between 100 ms and 1500 ms. The correspondence between the empirical results and this scale-invariant distribution is striking.

the distribution was a power law with exponent -1 with values between 100 ms and 1500 ms. The correspondence of the observed results and this theoretical distribution suggests that the timeline is compressed logarithmically.

The observation that temporal information was coded with decreasing accuracy as the trial elapsed was further supported by changes in the ensemble similarity across time. The ensemble similarity (Figure 3B) was computed for the population of time cells as a cosine of the normalized firing rate vectors between all pairs of time points during the observed 1.6 s long time interval.

The population coding for time conjunctively carried information about stimulus identity

Out of 229 units classified as time cells, 169 also distinguished the identity of the category of the to-be-remembered stimulus using the criteria described in the methods. Figure 5 shows several examples of such cells. These units were classified as time cells because they fired preferentially at circumscribed periods of time during the trial. However, the magnitude of their firing also depended dramatically on what category of stimulus was presented on the trial.

Figure 5. **Representative time cells that were modulated by the category of the sample stimulus.** A significant proportion of units classified as time cells distinguished the categories from one another. The activity of three category-specific time cells is shown (rows) with rasters corresponding to all the trials (left) as well as to each of the four stimulus categories (subsequent four columns). Category 1 and 2 are trials in which the sample stimulus was chosen from the DOG or CAT category respectively; Category 3 and 4 are SPORTS CAR and SEDAN trials. Averaged trial activity is shown as a solid green line, the model fit with only a constant term is given by the dotted blue line and the best-fitting model—with different coefficients for each category—as a dashed red line.

Time cells respected category-set structure

The two category sets (ANIMAL *vs* CAR) differ in their visual similarity. That is CAT and DOG stimuli are more visually similar to one another than they are to stimuli from the CAR category set. In order to determine whether stimulus-specific time cells respected this visual similarity structure, we noted that 43 out of 229 time cells met the definition for category-set specific time cells (see methods for details). Figure 6 shows several examples of representative units that were classified as category-set specific time cells.

As a control we computed the number of cells that had similar coefficients for artificial category sets. The number of category-set specific units significantly exceeded the number of cells specific for artificial category sets: 8 units distinguished DOG and SPORTS CAR stimuli from CAT and SEDAN stimuli. 14 units distinguished DOG and SEDAN stimuli from CAT and SPORTS CAR stimuli. Both of these proportions (8 and 14 out of 169) is reliably different than the 43/169 that distinguished the true category sets (ANIMAL vs CAR), $\chi^2 = 25.51$, $p < 10^{-6}$ and $\chi^2 = 16.5$, $p < 10^{-4}$.

The results for conjunctive coding of what and when information can be read off directly from the heatmaps in Figure 7, which shows the temporal profiles of all 169 stimulus specific time cells. The first heatmap Figure 7 shows the temporal profile for each unit in

Figure 6. **Representative time cells that were modulated by the category-set of the sample stimulus**. As in Fig. 5, each row is a cell. The left-most column shows data for all trials; the next four columns show data for trials in which the sample stimulus was chosen from each of the four categories. Category 1 and 2 correspond to the ANIMAL category set; Category 3 and 4 correspond to the CAR category set. The lines below each raster show averaged trial activity as a solid green line, the model fit with only a constant term as a dotted blue line and the best-fitting model—with distinct coefficients for each of the category sets—as a dashed red line.

response to the category that caused the unit to fire at the highest rate. The middle heatmap shows the temporal profile for the same sorting of units for stimuli for the other category from the same category set. For instance, if a particular unit responded most to DOG stimuli, that temporal profile would be in the left heatmap and its response to CAT stimuli would be in the middle heatmap. The heatmap on the right shows the temporal profile for each unit in response to stimuli from the category set that did not include the unit's best category. For instance, if a unit responded best to DOG stimuli, its profile in the right heatmap gives its response to stimuli from the CAR category set, including trials with sample stimuli from both the SPORTS CAR and SEDAN categories.

The sensitivity of the stimulus-specific time cells to category set can be noted from observing the difference between the heatmap in the second column and the heatmap in the third column. Although a difference between the first and second heatmaps could simply be a selection artifact, the difference between the second and the third indicates that time cells in this experiment respected the structure of the category sets.

Computational model for compressed memory representation

Previous work in computational neuroscience (Shankar & Howard, 2012; Howard et al., 2014) and cognitive psychology (Shankar & Howard, 2012; Howard et al., 2015) has developed a quantitative model for how a compressed timeline could be constructed. This

Figure 7. **Sequentially activated time cells in lPFC encode time conjunctively with stimulus identity.** The three heatmaps each show the response of every unit classified as a time cell. The heatmap on the left ("Best category") shows the response of each unit to the category that caused the highest response for that unit, sorted according to the units estimated time of peak activity. The second column ("Same category set") shows the heatmap for the same units, but for the other category from the same category set as that unit's "Best category." For instance, if a unit responded the most on trials in which the sample stimulus was chosen from the CAT category, then that units response to CAT trials would go in the first column and its response to DOG trials would go in the second column. The third column shows the response of each unit to trials on which the sample stimulus was from the other category set. Continuing with our example, a unit whose best category was CAT would have its response to CAR trials in the third column. The scale of the colormap is the same for all three plots and it is normalized for each unit such that red represents the unit's highest average firing rate and blue represents its lowest average firing rate across time bins.

method (described in more detail in the methods) makes a strong commitment to scale-invariance of the temporal representation inspired by robust behavioral results from timing and memory experiments (Rakitin et al., 1998; Howard, Youker, & Venkatadass, 2008). Consistent with these behavioral findings, and the logarithmic compression of receptive fields in the visual system (Schwartz, 1977; Van Essen, Newsome, & Maunsell, 1984), theoretical considerations (Shankar & Howard, 2013; Howard & Shankar, submitted) strongly suggest that time fields should also be logarithmically compressed. This quantitative argument makes two clear predictions. First, the width of time fields should go up linearly with the time of their peak. Second, the number of time fields centered on a time τ should go down like τ^{-1}.

This model can be understood as a two-layer feedforward network. However, because it can be well-described mathematically, analytic results can be readily obtained (see methods for details). Figure 4 provides a means to evaluate whether these quantitative predictions are consistent with the empirical data. The straight line relating spread of the time fields to their center (dashed green line in Figure 4A) is a qualitative prediction of the model; the slope of the line is controlled by a single parameter k (see methods for details). The distribution of time fields given by the model is given by the distribution $N(\tau) \simeq \tau^{-1}$; the dashed green line in Figure 4B shows this distribution with two parameters controlling the smallest and largest possible values of the center of the time field (set to 100 ms and 1500 ms respectively). The agreement of the empirical data with the predictions of a

Figure 8. **Sequentially activated time cells generated with the computational model.**
The three plots on the figure resemble the results shown on Figure 7. Analogous to the heatmaps
in Figure 7, each row corresponds to a single model unit and displays its normalized activity across
time. The cells are sorted with respect to the peak time. The two features observed in Figure 7 are
fully captured by the model: the time fields later in the delay were more broad than the time fields
earlier in the delay and the density of time fields decreased as a function of time. This illustrates
that the model can indeed account for the firing dynamics of the sequentially activated time cells
that form a compressed representation of time. In addition, the model predicts that the stimulus
selectivity observed in the data. This is because every time a stimulus is presented, it activates not
only its own memory representation, but also the memory representation of other stimuli to the
degree they are similar to the presented stimulus. The response to stimuli from the same category
set is on average more similar the response to stimuli from different category sets.

scale-invariant timeline is very strong.

In order to further evaluate the comparison between the model and the empirical
results, we also generated heatmaps as in Figure 7. By causing different units in the
timeline to respond to differentially to stimuli from different categories, we were able to
generate a strong agreement with the empirical results, as shown in Figure 8 (see methods
for details). Because these are analytic results, there is no noise in the time fields across
trials.

Discussion

During performance of a working memory task, some neurons in lPFC fired in se-
quences while information needed to be maintained in working memory. The sequences
exhibited coding of temporal information—the time since the sample stimulus was pre-
sented (Fig. 3)—conjunctively with information about the identity of the category of the
sample stimulus (Fig. 7). The temporal information decreased in accuracy as time elapsed
(Fig. 4). This decrease in accuracy aligned well with predictions of a scale-invariant timeline
taken from cognitive models of memory.

Temporal information throughout the brain

The present findings provide robust evidence of conjunctive coding of what and when
information in the lPFC. Although to our knowledge this is the first report of robust
stimulus-specific time cells, many recent papers have shown evidence for sequentially acti-

vated time cells in a broad range of brain regions and multiple species. Previous studies in rodents have found time cells with similar properties in hippocampus (MacDonald et al., 2011; Kraus, Robinson, White, Eichenbaum, & Hasselmo, 2013; Salz et al., 2016), medial prefrontal cortex (Tiganj et al., 2016), and striatum (Akhlaghpour et al., 2016; Mello et al., 2015). A monkey study has previously observed sequentially-activated time cells in dlPFC and striatum (Jin et al., 2009). In some of those previous studies showing time cell activity, the experimental procedure would not enable measurement of conjunctive what and when information (Jin et al., 2009; Tiganj et al., 2016; Mello et al., 2015; Kraus et al., 2013). In some other studies it would have been possible in principle to measure robust conjunctive what and when information (Akhlaghpour et al., 2016; MacDonald et al., 2011; Salz et al., 2016), but it was not observed.[1] Systematic study will be necessary to determine which of the many methodological differences between that study and this one is responsible for the discrepancy.

The presence of sequentially-activated time cells, regardless of whether or not they also code for stimulus identity, in so many brain regions with such similar functional properties is striking. This may point to a fundamental role for a compressed timeline in many different forms of memory. Our conventional understanding of the cognitive neuroscience of memory describes memory as composed of a number of separable systems associated predominantly with various brain regions (Squire, 2004; Eichenbaum, 2012; Jenkins & Ranganath, 2016). Although there are ongoing disputes about how exactly to specify the systems, there is broad consensus that the hippocampus is associated with the declarative memory system, the striatum is associated with a non-declarative implicit memory system and the PFC is associated with a working memory system, etc. The fact that such similar temporal representations are observed in regions associated with so many distinct memory systems suggests that these memory systems rely on a common form of temporal representation. Perhaps different memory systems perform different operations on a common representation (Howard et al., 2015; Aronov, Nevers, & Tank, 2017).

Why time cells are important

Previous studies have reported that it is possible to extract temporal or stimulus identity information by applying different decoding techniques on the activity of neural populations (Stokes et al., 2013; Kim, Ghim, Lee, & Jung, 2013; Pesaran, Pezaris, Sahani, Mitra, & Andersen, 2002; Baeg et al., 2003; Hung, Kreiman, Poggio, & DiCarlo, 2005). Neural models of timing rely on gradually changing firing rate throughout a delay period rather than temporal receptive fields (Kim et al., 2013; Gavornik & Shouval, 2011; Simen, Balci, de Souza, Cohen, & Holmes, 2011). Similarly, recurrent neural networks, including liquid state machines (Buonomano & Merzenich, 1995; Maass, Natschläger, & Markram, 2002; Buonomano & Maass, 2009; White, Lee, & Sompolinsky, 2004) can be shown to maintain information about preceding stimuli, but the decoder necessary to extract that information into a useful form can be quite complex.

Fusi, Miller, and Rigotti (2016) have argued that the brain expends significant resources representing features conjunctively using mixed selectivity to enable linear decoding

---

[1]MacDonald et al. (2011) observed some evidence for conjunctive what and when coding in the rodent hippocampus, but it was not as reliable as the present study. See also MacDonald et al. (2013).

(Rigotti et al., 2013). For coding of continuous dimensions, mixed selectivity manifests as receptive fields. To make a concrete example, the hippocampal place code might have consisted of as few as two neurons that fire proportionally to the x or y position of the animal. Although this code would require few neurons to represent position, learning an association between a location in the middle of an arena and reward would be a significant computational challenge. Instead, the hippocampal place code uses many neurons, each with a place field; the set of all place fields tile the enclosure. Although this coding scheme uses many more neurons it is computationally straightforward to learn an association between a circumscribed spatial position (represented by the currently-active place cells) and some behaviorally relevant outcome. Although sequentially activated stimulus-specific time cells seem to require a great many neurons, conjunctive coding of what and when information (Fig. 7) enables direct readout of the elapsed time and the stimulus identity.

Computational model of working memory

Computational neuroscience studies of working memory have predominantly focused on maintaining information about the identity of presented stimuli, either through sustained (Goldman-Rakic, 1995; Curtis & D'Esposito, 2003; Wang, 2001) or through time-varying firing dynamics (Durstewitz & Seamans, 2006; Stokes, 2015; Lundqvist et al., 2011; Murray et al., 2016; Sreekumar, Dennis, Doxas, Zhuang, & Belkin, 2014). Even though very useful, such models do not readily account for the temporal aspect of memory. Other computational models (e.g., Goldman, 2009; Grossberg & Merrill, 1992; Itskov, Curto, Pastalkova, & Buzsáki, 2011) can also account for sequentially-active firing that can be used to read off temporal information.

The computational model used here differs from previous work in that it makes a strong commitment to a logarithmically-compressed timeline and is mathematically tractable, enabling straightforward derivation of behavioral predictions (Shankar & Howard, 2012, 2013). The biological plausibility of the key components of the model has been studied closely. The major objection, that the method requires neurons with slow functional time constants, has been addressed by showing that a single-cell model based on known properties of persistently-firing neurons (Egorov et al., 2002; Fransén, Tahvildari, Egorov, Hasselmo, & Alonso, 2006) can be readily adapted to generate a broad range of slow functional time constants (Tiganj, Hasselmo, & Howard, 2015; Tiganj, Shankar, & Howard, 2013). The other major assumption of the model is a feedforward projection that is functionally equivalent to a set of on-center/off-surround receptive fields placed in series. The logarithmic compression of temporal receptive fields parallels the logarithmic compression of visual receptive fields, which has been known for decades (Hubel & Wiesel, 1974; Van Essen et al., 1984). Moreover the mathematics of this model can be readily adapted to provide a description not only of time cells, but a variety of findings from the place cell literature and even sustained firing (Howard et al., 2014).

Conclusions

We analyzed single-unit data from the lPFC of macaques during performance of a delayed-match-to-category task. Presentation of a sample image induced a conjunctive sequential activation during the sample and the delay period. This activation was constituting

a memory representations conveying readily available information about stimulus identity and time since the stimulus presentation. In addition, consistently with previous reports of sequential time cells activations, the memory was compressed and exhibited gradually decaying accuracy. This was manifested in that neurons that fired later in the sequence showed broader temporal receptive fields and were less prevalent than neurons that fired earlier in the sequence. The existence of a compressed, conjunctive memory timeline is consistent with longstanding cognitive theories of human memory. In addition, we described a computational model based on recent theoretical work that describes a specific neural mechanism that could give rise to the conjunctive coding on a compressed timeline observed in the data.

Acknowledgments

The authors gratefully acknowledge support from ONR MURI N00014-16-1-2832, NIBIB R01EB022864, NIMH R01MH112169, and NIMH R37MH087027.

References

Akhlaghpour, H., Wiskerke, J., Choi, J. Y., Taliaferro, J. P., Au, J., & Witten, I. (2016). Dissociated sequential activity and stimulus encoding in the dorsomedial striatum during spatial working memory. *eLife*, *5*, e19507.

Amit, D. J., & Brunel, N. (1997). Model of global spontaneous activity and local structured activity during delay periods in the cerebral cortex. *Cerebral cortex*, *7*(3), 237–252.

Aronov, D., Nevers, R., & Tank, D. W. (2017). Mapping of a non-spatial dimension by the hippocampal–entorhinal circuit. *Nature*, *543*(7647), 719–722.

Baeg, E., Kim, Y., Huh, K., Mook-Jung, I., Kim, H., & Jung, M. (2003). Dynamics of population code for working memory in the prefrontal cortex. *Neuron*, *40*(1), 177–188.

Brown, G. D. A., Neath, I., & Chater, N. (2007). A temporal ratio model of memory. *Psychological Review*, *114*(3), 539-76.

Buonomano, D. V., & Maass, W. (2009). State-dependent computations: spatiotemporal processing in cortical networks. *Nature Reviews Neuroscience*, *10*(2), 113-25. doi: 10.1038/nrn2558

Buonomano, D. V., & Merzenich, M. M. (1995). Temporal information transformed into a spatial code by a neural network with realistic properties. *Science*, *267*(5200), 1028.

Chaudhuri, R., & Fiete, I. (2016). Computational principles of memory. *Nature Neuroscience*, *19*(3), 394–403.

Compte, A., Brunel, N., Goldman-Rakic, P. S., & Wang, X. J. (2000, Sep). Synaptic mechanisms and network dynamics underlying spatial working memory in a cortical network model. *Cerebral Cortex*, *10*(9), 910-23.

Cromer, J. A., Roy, J. E., & Miller, E. K. (2010). Representation of multiple, independent categories in the primate prefrontal cortex. *Neuron*, *66*(5), 796-807. doi: 10.1016/j.neuron.2010.05.005

Crowder, R. G. (1976). *Principles of learning and memory.* Hillsdale, NJ: Erlbaum.

Curtis, C. E., & D'Esposito, M. (2003). Persistent activity in the prefrontal cortex during working memory. *Trends in cognitive sciences*, *7*(9), 415–423.

Durstewitz, D., & Seamans, J. K. (2006). Beyond bistability: biophysics and temporal dynamics of working memory. *Neuroscience*, *139*(1), 119-33.

Durstewitz, D., Seamans, J. K., & Sejnowski, T. J. (2000). Neurocomputational models of working memory. *Nature Neuroscience*, *3*, 1184-91.

Egorov, A. V., Hamam, B. N., Fransén, E., Hasselmo, M. E., & Alonso, A. A. (2002). Graded persistent activity in entorhinal cortex neurons. *Nature*, *420*(6912), 173-8.

Eichenbaum, H. (2012). *The cognitive neuroscience of memory: An introduction* (2nd ed.). New York, NY: Oxford University Press.

Fransén, E., Tahvildari, B., Egorov, A. V., Hasselmo, M. E., & Alonso, A. A. (2006). Mechanism of graded persistent cellular activity of entorhinal cortex layer V neurons. *Neuron*, *49*(5), 735-46.

Friston, K., & Buzsáki, G. (2016). The functional anatomy of time: What and when in the brain. *Trends in Cognitive Sciences*.

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition. *Current opinion in neurobiology*, *37*, 66–74.

Gavornik, J. P., & Shouval, H. Z. (2011). A network of spiking neurons that can represent interval timing: mean field analysis. *Journal of Computational Neuroscience*, *30*(2), 501-13. doi: 10.1007/s10827-010-0275-y

Goldman, M. S. (2009). Memory without feedback in a neural network. *Neuron*, *61*(4), 621–634.

Goldman-Rakic, P. (1995). Cellular basis of working memory. *Neuron*, *14*, 477-85.

Grossberg, S., & Merrill, J. (1992). A neural network model of adaptively timed reinforcement learning and hippocampal dynamics. *Cognitive Brain Research*, *1*, 3-38.

Howard, M. W., MacDonald, C. J., Tiganj, Z., Shankar, K. H., Du, Q., Hasselmo, M. E., & Eichenbaum, H. (2014). A unified mathematical framework for coding time, space, and sequences in the hippocampal region. *Journal of Neuroscience*, *34*(13), 4692-707. doi: 10.1523/JNEUROSCI.5808-12.2014

Howard, M. W., & Shankar, K. H. (submitted). *Neural scaling laws for an uncertain world.* (arXiv:1607.04886)

Howard, M. W., Shankar, K. H., Aue, W., & Criss, A. H. (2015). A distributed representation of internal time. *Psychological Review*, *122*(1), 24–53. doi: 10.1037/a0037840

Howard, M. W., Youker, T. E., & Venkatadass, V. (2008). The persistence of memory: Contiguity effects across several minutes. *Psychonomic Bulletin & Review*, *15*(PMC2493616), 58-63.

Hubel, D. H., & Wiesel, T. N. (1974). Uniformity of monkey striate cortex: a parallel relationship between field size, scatter, and magnification factor. *Journal of Comparative Neurology*, *158*(3), 295-305. doi: 10.1002/cne.901580305

Hung, C. P., Kreiman, G., Poggio, T., & DiCarlo, J. J. (2005). Fast readout of object identity from macaque inferior temporal cortex. *Science*, *310*(5749), 863–866.

Itskov, V., Curto, C., Pastalkova, E., & Buzsáki, G. (2011). Cell assembly sequences arising from spike threshold adaptation keep track of time in the hippocampus. *Journal of Neuroscience*, *31*(8), 2828-34.

James, W. (1890). *The principles of psychology.* New York: Holt.

Jenkins, L. J., & Ranganath, C. (2016). Distinct neural mechanisms for remembering when an event occurred. *Hippocampus*, *26*, 554-559.

Jin, D. Z., Fujii, N., & Graybiel, A. M. (2009). Neural representation of time in cortico-basal ganglia circuits. *Proceedings of the National Academy of Sciences*, *106*(45), 19156–19161.

Kim, J., Ghim, J.-W., Lee, J. H., & Jung, M. W. (2013). Neural correlates of interval timing in rodent prefrontal cortex. *Journal of Neuroscience*, *33*(34), 13834-47. doi: 10.1523/JNEUROSCI.1443-13.2013

Kraus, B. J., Brandon, M. P., Robinson, R. J., Connerney, M. A., Hasselmo, M. E., & Eichenbaum, H. (2015). During running in place, grid cells integrate elapsed time and distance run. *Neuron*, *88*(3), 578–589.

Kraus, B. J., Robinson, R. J., 2nd, White, J. A., Eichenbaum, H., & Hasselmo, M. E. (2013). Hippocampal "time cells": time versus path integration. *Neuron*, *78*(6), 1090-101. doi: 10.1016/j.neuron.2013.04.015

Lewis, P. A., & Miall, R. C. (2009). The precision of temporal judgement: milliseconds, many minutes, and beyond. *Philosophical Transcripts of the Royal Society London B: Biological Sciences*, *364*(1525), 1897-905. doi: 10.1098/rstb.2009.0020

Lundqvist, M., Herman, P., & Lansner, A. (2011). Theta and gamma power increases and alpha/beta power decreases with memory load in an attractor network model. *Journal of cognitive neuroscience*, *23*(10), 3008–3020.

Maass, W., Natschläger, T., & Markram, H. (2002). Real-time computing without stable states: a new framework for neural computation based on perturbations. *Neural Computation*, *14*(11), 2531-60. doi: 10.1162/089976602760407955

MacDonald, C. J., Carrow, S., Place, R., & Eichenbaum, H. (2013). Distinct hippocampal time cell sequences represent odor memories immobilized rats. *Journal of Neuroscience*, *33*(36), 14607–14616.

MacDonald, C. J., Lepage, K. Q., Eden, U. T., & Eichenbaum, H. (2011). Hippocampal "time cells" bridge the gap in memory for discontiguous events. *Neuron*, *71*, 737-749.

Mello, G. B. M., Soares, S., & Paton, J. J. (2015). A Scalable Population Code for Time in the Striatum. *Current Biology*, *25*(9), 1113–1122.

Mongillo, G., Barak, O., & Tsodyks, M. (2008). Synaptic theory of working memory. *Science*, *319*(5869), 1543–1546.

Murray, J. D., Bernacchia, A., Roy, N. A., Constantinidis, C., Romo, R., & Wang, X.-J. (2016). Stable population coding for working memory coexists with heterogeneous neural dynamics in prefrontal cortex. *Proceedings of the National Academy of Sciences*, 201619449.

Pastalkova, E., Itskov, V., Amarasingham, A., & Buzsaki, G. (2008). Internally generated cell assembly sequences in the rat hippocampus. *Science*, *321*(5894), 1322-7.

Pesaran, B., Pezaris, J. S., Sahani, M., Mitra, P. P., & Andersen, R. A. (2002). Temporal structure in neuronal activity during working memory in macaque parietal cortex. *Nature neuroscience.*, *5*(8), 805-11.

Post, E. (1930). Generalized differentiation. *Transactions of the American Mathematical Society*, *32*, 723-781.

Rakitin, B. C., Gibbon, J., Penny, T. B., Malapani, C., Hinton, S. C., & Meck, W. H. (1998). Scalar expectancy theory and peak-interval timing in humans. *Journal of Experimental Psychology: Animal Behavior Processes*, *24*, 15-33.

Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., & Fusi,

S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*, *497*(7451), 585-90. doi: 10.1038/nature12160

Salz, D. M., Tiganj, Z., Khasnabish, S., Kohley, A., Sheehan, D., Howard, M. W., & Eichenbaum, H. (2016). Time cells in hippocampal area ca3. *The Journal of Neuroscience*, *36*(28), 7476–7484.

Sandberg, A., Tegnér, J., & Lansner, A. (2003). A working memory model based on fast hebbian learning. *Network: Computation in Neural Systems*, *14*(4), 789–802.

Schwartz, E. L. (1977). Spatial mapping in the primate sensory projection: analytic structure and relevance to perception. *Biological Cybernetics*, *25*(4), 181-94.

Shankar, K. H., & Howard, M. W. (2012). A scale-invariant representation of time. *Neural Computation*, *24*, 134-193.

Shankar, K. H., & Howard, M. W. (2013). Optimally fuzzy scale-free memory. *Journal of Machine Learning Research*, *14*, 3753-3780.

Simen, P., Balci, F., de Souza, L., Cohen, J. D., & Holmes, P. (2011). A model of interval timing by neural integration. *Journal of Neuroscience*, *31*(25), 9238-53. doi: 10.1523/JNEUROSCI.3121-10.2011

Squire, L. R. (2004). Memory systems of the brain: a brief history and current perspective. *Neurobiology of learning and memory*, *82*(3), 171-7.

Sreekumar, V., Dennis, S., Doxas, I., Zhuang, Y., & Belkin, M. (2014). The geometry and dynamics of lifelogs: discovering the organizational principles of human experience. *PLoS One*, *9*(5), e97166. doi: 10.1371/journal.pone.0097166

Stokes, M. G. (2015). 'activity-silent' working memory in prefrontal cortex: a dynamic coding framework. *Trends in Cognitive Sciences*, *19*(7), 394–405.

Stokes, M. G., Kusunoki, M., Sigala, N., Nili, H., Gaffan, D., & Duncan, J. (2013). Dynamic coding for cognitive control in prefrontal cortex. *Neuron*, *78*(2), 364–375.

Tiganj, Z., Hasselmo, M. E., & Howard, M. W. (2015). A simple biophysically plausible model for long time constants in single neurons. *Hippocampus*, *25*(1), 27-37.

Tiganj, Z., Kim, J., Jung, M. W., & Howard, M. W. (2016). Sequential firing codes for time in rodent mPFC. *Cerebral Cortex*(1-9). doi: 10.1093/cercor/bhw336

Tiganj, Z., Shankar, K. H., & Howard, M. W. (2013). Encoding the Laplace transform of stimulus history using mechanisms for persistent firing. *BMC Neuroscience*, *14*(Suppl 1), P356.

Van Essen, D. C., Newsome, W. T., & Maunsell, J. H. (1984). The visual field representation in striate cortex of the macaque monkey: asymmetries, anisotropies, and individual variability. *Vision Research*, *24*(5), 429-48.

Wang, X. (2001). Synaptic reverberation underlying mnemonic persistent activity. *Trends in Neurosciences*, *24*(8), 455–463.

White, O. L., Lee, D. D., & Sompolinsky, H. (2004). Short-term memory in orthogonal neural networks. *Physical Review Letters*, *92*(14), 148102.

Methods

This paper reports reanalysis of data initially described in Cromer et al. (2010). More detailed descriptions of the behavioral and recording methods can be found in that paper.

Behavioral task

Two macaque monkeys performed a delayed match to category task. The stimuli were chosen from one of two independent category sets; each category set consisted of two categories. One category set was ANIMALS, which consisted of the categories DOGS and CATS. The other category set was CARS, which consisted of the categories SPORTS CARS and SEDANS. Stimuli were constructed as morphed images, composed from a mixture of two prototype images each taken from a different category within the same category set (Figure 1A-B). The test stimulus was always chosen to be from the same category set as the sample stimulus, but it could come from either the same or from a different category within that category set.

Each trial was initiated by the monkey grabbing a response bar. The trials started with a 1000 ms fixation period, during which a white cross was presented in the middle on the screen. The monkey was required to fixate on it. The fixation period was followed by a 600 ms sample stimulus presentations and then by a 1000 ms delay interval during which the monkey had to maintain a memory of the stimulus category in order to be able to successfully complete the task and obtain a reward. The delay period was followed by a test stimulus presentation lasting for another 600 ms.

On match trials, when the test stimulus was from the same category as the sample stimulus, the monkey had to release the response bar within 600 ms of the test stimulus presentation. On nonmatch trials, the monkey had to continue holding the bar during the test stimulus presentation and during a subsequent 600 ms delay interval followed by a second test image. The second test image was always a category match to the sample image (see Figure 1C for a block diagram showing the behavioral protocol). The performance of each monkey was correct in more than 80% of trials.

Electrophysiological Recordings

Neural recordings were made using up to 16 individual, epoxy-coated tungsten electrodes (FHC Inc., Bowdoin, ME) positioned over the lPFC. Spike sorting was performed on digitalized waveforms using principal components analysis (Offline Sorter, Plexon Inc., Dallas, TX). A total of 500 isolated units was recorded from the two animals. Recordings of 455 out of these 500 units were already used for the analysis published in (Cromer et al., 2010). Eye movements were recorded using an infrared eye tracking system (Iscan, Burlington, MA).

Analysis methods

We used a maximum likelihood approach to evaluate whether time and/or stimulus identity were encoded in the firing of the recorded cells. These methods build on analysis methods used to identify time cells in rodent hippocampus and mPFC (Salz et al., 2016; Tiganj et al., 2016). Here we expanded the approach to include the identify of the stimulus in the modeled firing rates. This enables the method to identify conjunctive, stimulus-specific time cells.

In each trial we only analyzed the 1600 ms starting from presentation of the sample and terminating at the presentation of the next stimulus. This interval includes the 600 ms presentation of the sample stimulus and a 1000 ms blank delay interval. The spike trains

of each cell were fitted with models that included different variables, such as time and stimulus identity. The parameter space of these models was systematically explored in order to compute the maximum likelihood fit. To find the best-fitting model the parameter space was iteratively searched using a combination of particle swarming and the Quasi-Newton method. Particle swarming was performed first (with the swarm size equal to 50) and its output was used to initialize the Quasi-Newton method which was performed second (the number of maximum function evaluations was set to 10000). The computations were implemented in Matlab 2016a. To avoid solutions that converged to a local minimum, the fitting procedure was repeated until the algorithm did not result with better likelihood for at least five consecutive runs. As a preprocessing step, spike trains were downsampled to 1 ms temporal resolution such that if a spike was observed in a particular 1 ms time bin, the corresponding data point was set to 1, otherwise it was set to 0. The maximum likelihood was computed for each recorded cell using all available trials.

We first identified cells that whose firing was modulated by the passage of time. This was done by comparing the maximum likelihood of the fits from two different models, one containing a Gaussian-shaped time field and the other containing only a constant term. The model with Gaussian-shaped time fields had a set of parameters Θ, which consisted of a constant term a_0, the amplitude of the time fields a_1, the mean μ_t and standard deviation σ_t of the Gaussian time field. With this model the probability of a spike at any given time point t was given as:

$$p(t; \Theta) = a_0 + a_1 T(t; \sigma_t, \mu_t), \tag{1}$$

where the Gaussian-shaped time field $T(t; \sigma_t, \mu_t)$ was defined as:

$$T(t; \sigma_t, \mu_t) = e^{\frac{-(t-\mu_t)^2}{2\sigma_t^2}}. \tag{2}$$

We refer to cells that were better fit by Eq. 1 than by a constant term (just a_0) as *time cells*, subject to several constraints described in detail below.

The mean of the time term μ_t was allowed to vary between -100 ms and 1700 ms and the standard deviation σ_t varied between 0 and 5 s. In order to ensure that $p(t; \Theta)$ can be considered as a probability we had to ensure that its values are bounded between 0 and 1. Therefore, the coefficients were bounded such that $a_0 + a_1 \leq 1$. The likelihood of the fit was defined as a product of these probabilities across all 1600 time bins within each trial and across all trials. We expressed the likelihood in terms of the negative log-likelihood (nLL), therefore instead of a product, a sum of the probabilities was computed:

$$\underset{\Theta}{\arg\min} \, \text{nLL} = -\sum_{trial} \sum_{t} [f_t \, \log(p_t) + (1 - f_t) \log(1 - p_t)], \tag{3}$$

where f_t is the spike train.

In order to quantify whether the contribution of the terms that contained time was significant, the maximum log-likelihood was computed again, but this time with the time term set to zero $(a_1 = 0)$, such that the likelihood was affected only by the constant term a_0. Since the models with and without time are nested, the likelihood-ratio test was used to assess the probability that adding the time term significantly improved the fit. The test is based on the ratio of the likelihoods of two different models and expresses how many

times the data are more likely under one model than the other and it takes into account the difference in the number of parameters. To ensure that a unit will not be classified as a time cell only due to its activity in a single trial, the analysis was done separately on even and odd trials. For a unit to be classified as a time cell it was required that the likelihood-ratio test was significant ($p < 0.01$) for both even and odd trials. In order to eliminate units with ramping or decaying firing rate during a delay interval, μ_t was required to be within the delay interval and at least one σ_t away from either the beginning or the end of the interval. Also, to eliminate units with overly flat firing rate from classification as a time cell, σ_t was required to be at most equal to the length of the delay interval.

The subset of units that passed the above criteria were classified as time cells. We then tested whether these units were also modulated by the category of stimulus on each trial (i.e., cats, dogs, sports cars, sedans) or for category sets (i.e., animals/cars). Category specificity was tested with a model that allowed four parameters, rather than one as above, to modulate the Gaussian-shaped time field, determined by the identity of the stimulus category on each trial. The probability of a spike at time point t was given as:

$$p\left(t;\Theta\right) = a_0 + \sum_{i=1}^{4} a_i c_i T(t; \sigma_t, \mu_t), \tag{4}$$

where a_0 to a_4 are the parameters to be estimated, while μ_t and σ_t are those estimated from the previous fit with a single time field eq. (1). The factor c_i was equal to 1 for trials when a stimulus from i-th category was presented and 0 otherwise. For instance, $c_1 = 1$ for trials which started with a sample stimulus from the DOG category and $c_1 = 0$ for trials where the sample stimulus was a CAT, SPORTS CAR or SEDAN). The model that includes category specificity eq. (4) and the model with a single time field eq. (1) are nested. Therefore, we use the likelihood-ratio test to assess the probability that adding the category specificity significantly improves the fit. When the outcome of the likelihood ratio test was significant ($p < 0.01$), a time cell was classified as category specific.

The category set specificity of the time cells was tested in analogous way to the category specificity, but using two time fields instead of four. Each of the two time fields corresponded to a particular category set. Thus the probability of a spike at time point t was given as:

$$p\left(t;\Theta\right) = a_0 + \sum_{i=1}^{2} a_i c_i T(t; \sigma_t, \mu_t). \tag{5}$$

The factor c_i was equal to 1 for all the data points at trials when a stimulus from i-th category set was presented and 0 otherwise. For instance, $c_1 = 1$ for trials which started with a sample stimulus from the DOG or CAT categories, and $c_1 = 0$ for trials which started with a stimulus from the SPORTS CAR or SEDAN category. As in the case of the category specific cells, μ_t and σ_t were used as estimated from the fit with a single time field eq. (1). The likelihood-ratio test was used again to assess whether adding the category set specificity (eq. (5)) provided a better fit ($p < 0.01$) than the model with four time fields.

As an additional control to evaluate whether category set specificity was meaningful, we evaluated whether the number of category set specific time cells was more than one would expect from artificial pairings of categories. This was done by comparing the number of time cells that distinguished between animal and car category sets to the number of time cells

that distinguished between artificial (not meaningful) mixtures of categories. One control model estimated the number of units that distinguished DOG and SPORTS CAR stimuli from CAT and SEDAN CAR stimuli. The other estimated the number of units that distinguished DOG and SEDAN CAR stimuli from CAT and SPORTS CAR stimuli. Because these artificial "category sets" are not meaningful, if the actual number of units coding for the true category sets—ANIMAL *vs* CAR—exceeds the number for the artificial category sets, we can conclude that the population contains information about the organization of the stimuli into category sets.

Computational model

The computational model used here is based on a previously-published method for computing a scale-invariant neural timeline (Shankar & Howard, 2012, 2013). The model can be understood as a two-layer feedforward network. The first layer implements an approximation of the Laplace transform of the input to the network (keeping only the real part of the coefficients). The second layer approximates an inversion of the transform using the Post approximation formula (Post, 1930). Here we assume that the input function is a transient that captures information about the identity of the sample stimulus at the time it is presented. After the input is presented, the first layer codes the Laplace transform of the input function. As the delay progresses, this input function contains the identity of the sample stimulus further and further in the past. The Laplace transform contains this information and the second layer approximates a reconstruction of this function, with different units supporting different parts of the time axis. We compare the properties of units in the second layer of the network to experimentally-observed stimulus-specific time cells. These units estimate the time of the sample stimulus with decreasing accuracy as it recedes into the past, resulting in broader time fields and fewer units with time fields as the sample stimulus becomes more temporally remote.

To make this more concrete, in the present experiment with four distinct categories of stimuli, it is sufficient to consider an input vector $\mathbf{f}(t)$ consisting of 4 elements. At each moment $\mathbf{f}(t)$ gives the vector-valued category of the stimulus currently presented. When a stimulus from a particular category A is presented, the component f_A is set equal to 1 for a brief moment (i.e., a delta function input) and 0 at other times during the delay.

For simplicity, let us first consider the activity of units that receive input only from one component of $\mathbf{f}(t)$, say $f_A(t)$, with the understanding that in general units will receive some mixture of inputs from all four categories. Units in the first layer receiving input from $f_A(t)$, which we denote as $F_A(t, \overset{*}{\tau})$, act as leaky integrators (first order low-pass filters):

$$\frac{F_A(t, \overset{*}{\tau})}{dt} = -\frac{k}{\overset{*}{\tau}} F_A(t, \overset{*}{\tau}) + f_A(t). \tag{6}$$

Each unit is characterized by a time constant $\overset{*}{\tau}/k$, where k is positive integer that is common across all units. We assume that the probability of observing a unit with time constant $\overset{*}{\tau}$ goes down like $\overset{*}{\tau}^{-1}$ (Shankar & Howard, 2013; Howard et al., 2015; Howard & Shankar, submitted). After receiving an input, units participating in F_A decay exponentially with a time constant that depends on their value of $\overset{*}{\tau}$ (Figure 9,middle).

Figure 9. Constructing a scale-invariant compressed memory representation through an integral transform and its inverse. A transient input stimulus $f(t)$ feeds into a layer of leaky integrators $F(t, \overset{*}{\tau})$ with a spectrum of time constants $\overset{*}{\tau}$ constituting a discrete approximation of an integral transform. The transform is denoted as **L** since it is equivalent to the real part of the Laplace transform. Only three nodes in $F(t, \overset{*}{\tau})$ are shown. Each leaky integrator is characterized with its time constant, $\overset{*}{\tau}$. F projects onto $\tilde{f}(t, \overset{*}{\tau})$ through a set of weights defined with the operator denoted as $\mathbf{L}_k^{-1}$ which implements an approximation of the inverse of the Laplace transform. Nodes in $\tilde{f}(t, \overset{*}{\tau})$ activate sequentially following the stimulus presentation creating a memory representation. The width of the activation of each node scales with the peak time determined by the corresponding $\overset{*}{\tau}$, making the memory scale-invariant. Logarithmic spacing of the $\overset{*}{\tau}$ makes the memory representation is compressed.

Let us denote the activity of units in the second layer receiving input from $F_A(t)$ as $\tilde{f}_A(t, \overset{*}{\tau})$. These units are also indexed by their value of $\overset{*}{\tau}$ and combine inputs from nearby values of $\overset{*}{\tau}$ in F_A, computing a k^{th} order derivative with respect to $k/\overset{*}{\tau}$:

$$\tilde{f}_A(t, \overset{*}{\tau}) = C_k \left(\frac{k}{\overset{*}{\tau}}\right)^{k+1} F_A^{(k)}(t, \overset{*}{\tau}), \tag{7}$$

where C_k is a constant that depends only on k. Post (1930) proved that in the limit as k goes to infinity, $\tilde{\mathbf{f}}(\overset{*}{\tau})$ approximates $\mathbf{f}(t' < t)$.

When the input is a delta function at time zero, the activity of units in $\tilde{f}_A(t, \overset{*}{\tau})$ obey

$$\tilde{f}_A(t, \overset{*}{\tau}) = C_k \frac{1}{\overset{*}{\tau}} \left(\frac{t}{\overset{*}{\tau}}\right)^k e^{-k\frac{t}{\overset{*}{\tau}}}, \tag{8}$$

where C_k here is another constant that depends only on k. This expression is the product of an increasing power term $\left(\frac{t}{\overset{*}{\tau}}\right)^k$ and a decreasing exponential term $e^{-k\frac{t}{\overset{*}{\tau}}}$. Consequently, the activity of each node in $\tilde{f}_A(t, \overset{*}{\tau})$ peaks at its value of $\overset{*}{\tau}$ (Figure 9,bottom).

It turns out (Shankar & Howard, 2012) that the width of each unit's activity as a function of time depends linearly on its value of $\overset{*}{\tau}$ with a Weber fraction that is determined by the value of k. We found a good correspondence to the empirical data with $k = 15$. The

values of $\overset{*}{\tau}$ were logarithmically spaced between 100 ms and 1500 ms. Logarithmic spacing implements Weber-Fechner scaling.

To mimic stimulus-specificity we assumed that units in $\tilde{\mathbf{f}}$ received a mixture of inputs from stimuli from the four categories. For each unit, we picked one category as its preferred category and weighted its response by one (eq. 8) for that category. For the other categories, we picked coefficients randomly to weight the same temporal response. When a stimulus did not belong to the preferred category, but was from the same category set as the preferred category, we weighted the impulse response by a value taken from a normal distribution with mean 0.6 and standard deviation 0.3. When the stimulus was from the other category set, the temporal response was weighted by a value taken from a normal distribution with mean 0.3 and standard deviation 0.3. In addition, all of the coefficients were bounded between 0 and 1. These values were chosen informally to provide rough agreement with the empirical data.