StateHub-StatePaintR: rules-based chromatin state annotations.

Simon G. Coetzee[1], Zachary Ramjan[3,4], Huy Q. Dinh[1], Benjamin P. Berman[1,2], Dennis J. Hazelett[1,2,*],

1 The Center for Bioinformatics and Functional Genomics, Department of Biomedical Sciences, Cedars-Sinai Medical Center, Los Angeles CA
2 Sammuel Oschin Comprehensive Cancer Institute
3 Zaxxis LLC
4 Van Andel Research Institute, Grand Rapids MI
* Dennis.Hazelett@csmc.edu

Abstract

Genome annotation is critical to understand the function of disease variants, especially for clinical applications. To meet this need there are segmentations available from public consortia reflecting varying unsupervised approaches to functional annotation based on epigenetics data, but there remains a need for transparent, reproducible, and easily interpreted genomic maps of the functional biology of chromatin. We introduce here methods for defining chromatin state with a combinatorial epigenomic model using an annotation tool, *StatePaintR* and a website database, *StateHub*. Annotations are fully documented with change history and versioning, authorship information, and original source files. The tool calculates quantitative state scores based on genome-wide ranking, allowing prioritization and enrichment testing, facilitating quantitative analysis. *StateHub* hosts annotation tracks for major public consortia as a resource, and allows users to submit their own alternative models.

Introduction 1

Chromatin segmentations are increasingly important for a broad area of research that includes regulatory genomics, genetic epidemiology, precision health, and molecular genetics. There is a need for consistent, unbiased resolution of chromatin states to interpret the epigenome and predict function across different tissues and cell types.

Complex, overlapping patterns of post-translational modifications (PTM) to histone subunits[Rando, 2013, Gardner et al., 2011], signify differing states of chromatin activity. These modifications consist of mono-, di-, or tri-methylation and acetylation of histone 3 lysines 4, 9, 27, and 36[Rothbart and Strahl, 2014]. Direct assays for histone PTMs with next-generation sequencing (NGS) using chromatin immunoprecipitation (ChIP-seq) result in a set of genomic intervals with evidence for enrichment over background (input chromatin), using signal intensity.

In addition to ChIP-seq of histone PTMs, there are also NGS methods for histone displacement, including DNase I hypersensitivity[Boyle et al., 2008] (DNase-seq or DHS), Formaldehyde Assisted Isolation of Regulatory Elements[Simon et al., 2012] (FAIRE-seq), Assay for Transposase Accessible Chromatin[Buenrostro et al., 2013] (ATAC-seq) and Nucleosome Occupancy and Methylome sequencing (NOMe-seq)[Gal-Yam et al., 2006]. Histone displacement, nucleosome positioning and DNA methylation are also detected

in genomewide assays (*e.g.* whole genome bisulfite sequencing[Cokus et al., 2008]). ₁₉
Histone displacement is associated with transcription factor binding and transcriptional ₂₀
activity[Thurman et al., 2012]. In addition, direct binding of transcription factors is ₂₁
measured in ChIP-seq experiments with an antibody directed against a transcription ₂₂
factor or an epitope-tagged version. ₂₃

All these data are compatible with data represented as genomic intervals (in bed ₂₄
format), including CpG islands, annotated transcription start sites, repeat elements, 3′ ₂₅
UTRs). The input and final (output) processed data format are both as browser extensible ₂₆
data (.bed), a flexible standard for different peak calling methods (*e.g.* "narrowPeak" ₂₇
and "broadPeak" are types of .bed files). ₂₈

Several machine-learning approaches integrate NGS experiments into annotation ₂₉
tracks[Li et al., 2015]. The goal is to discover epigenomic states and aid in understanding ₃₀
"non-coding" genomic elements (they do not encode protein sequence) in an unbiased ₃₁
but biologically meaningful way. Newly discovered states are likely an amalgam of true ₃₂
functional categories reflected in chromatin biology. The most popular and widely used of ₃₃
these machine learning methods is ChromHMM[Ernst and Kellis, 2012]. Other machine- ₃₄
learning approaches include spectral-based learning[Song and Chen, 2015], inference based ₃₅
on read counts[Mammana and Chung, 2015], dynamic bayesian networks[Hoffman et al., ₃₆
2012], probabilistic approaches[Hon et al., 2008], supervised enhancer detection[Santoni, ₃₇
2012], and other hidden markov methods[Zacher et al., 2014, Sohn et al., 2015, Biesinger ₃₈
et al., 2013]. However, a software framework for expert or rule-based segmentations ₃₉
is lacking. Such methodology is needed for integrating different experimental data ₄₀
(including non-NGS data) in a reproducible way, reflecting both the novel insights gained ₄₁
from the machine learning methods and our current understanding of genome biology. ₄₂

Here we introduce *StateHub* and *StatePaintR* for generating and documenting models ₄₃
in a transparent and reproducible fashion. *StateHub* is a public resource for storing ₄₄
annotation models, state definitions and associated data in a shareable, referenceable ₄₅
form. The *StatePaintR* package implements these models and state definitions to produce ₄₆
annotation tracks. We show that *StatePaintR* can be used to rapidly annotate large ₄₇
collections of public data for summarizing epigenomics data or annotation of variants. ₄₈
We show how annotations gracefully degrade, in that cell types or tissues with missing ₄₉
data types are annotated appropriately based upon available information. We show ₅₀
some use cases, and describe how *StatePaintR* uses ChIP-seq data to rank within states, ₅₁
making quantitative analysis possible. ₅₂

Results ₅₃

A framework for rules-based annotation ₅₄

In order to assign chromatin states, it is necessary to account for the complex interplay ₅₅
of input from genomic annotations and cell-type-specific experimental data sources ₅₆
that define and demarcate functional regions of the genome[Rando, 2013]. We could ₅₇
implement such a model from a simple decision tree. From such a tree it is possible to ₅₈
produce a satisfactory annotation, from any set of marks. However, it would be complex ₅₉
to implement, to maintain and to update. Some marks are indicative of regulatory ₆₀
status in one context, but have quite different properties depending on which other ₆₁
marks are available. For example, H3K4me1 is generally consistent with enhancers, ₆₂
but is not sufficient on its own to designate a regulatory element as active, poised, ₆₃
primed or bivalent. Consequently, in order to capture meaning there are different trees ₆₄
to make for different combinations of available data. Computationally they have to ₆₅
be put in the right order to avoid erroneous overwriting of information-rich categories ₆₆
with information-poor ones. Thus, decision trees are not general enough to cover most ₆₇

situations. Furthermore, they would have to be completely re-written in a labor-intensive ₆₈
process when new information comes to light. To avoid this problem, we generalized our ₆₉
models as a decision matrix, which has the advantage of separating model specification ₇₀
from software, enabling complete re-design of the annotation software without computer ₇₁
programming expertise. ₇₂

We created a searchable website, *StateHub*, to host a permanent repository of models, ₇₃
to document model objects and make them available as a resource to the community. ₇₄
The *StatePaintR* package retrieves models from *StateHub* and performs annotations on ₇₅
local data. Thus, *StateHub-StatePaintR* is a framework to document models and apply ₇₆
them to annotate genomic data. The models in *StateHub* consist of an abstraction ₇₇
layer, defining the relationships between data sources and functional categories. These ₇₈
categories are integrated to produce annotations (left hand column, "Chromatin States") ₇₉
via a decision matrix (figure 1). Within the model each state has associated descriptions ₈₀
of arbitrary length which may contain key words or other relevant details (bottom right). ₈₁

Each cell of the decision matrix relates functional category to chromatin state in a ₈₂
3 bit code representing the answers to two TRUE/FALSE questions. Is the functional ₈₃
category required in order to call the state? And, is overlap consistent with the state? For ₈₄
example, in our focused poised promoter model, the cell of the decision matrix defining ₈₅
the relationship between the state "PPR" and the functional category "PolycombNarrow" ₈₆
is 3, representing the binary value 11_2. In order to call the PPR state, PolycombNarrow ₈₇
data is required be present, and second, it must also overlap with a peak. A score of 2 ₈₈
representing the binary value 10_2, as in the category "Active" and state PPR, indicates ₈₉
that data relating to the active mark must be present to call PPR, but must not overlap. ₉₀
A score of 0 representing the binary value 00_2, as in the cell for category "Core" and ₉₁
PPR, indicates that it is not necessary for data consistent with Core marks to be present. ₉₂
If the data is present and overlapping a segment, the state is excluded. The category ₉₃
"Translation marks" does not affect PPR in this model, even if it overlaps. Marks that ₉₄
are essentially irrelevant to PPR such as this one are assigned 1 representing binary 01_2. ₉₅

Each row has a unique combination of requirements, and the rows are ordered by the ₉₆
software by increasing information content. *StatePaintR* attempts to match each row ₉₇
from top to bottom. When more than one match is found, the last (highest information) ₉₈
state is assigned. This is how model degeneracy is acheived, and how *StatePaintR* is able ₉₉
to annotate incomplete datasets sensibly. A complete model therefore specifies every ₁₀₀
imaginable combination of factors or histone marks. ₁₀₁

Segmentation of public datasets ₁₀₂

We generated annotations of 119 ENCODE cell lines[Dunham et al., 2012], 128 Roadmap ₁₀₃
tissues[Roadmap Epigenomics et al., 2015], 26 cell lines and tissues from CEEHRC (peak ₁₀₄
calls obtained from the IHEC website http://epigenomesportal.ca/ihec/index.html), and ₁₀₅
23 blood cell types from Blueprint (download at statehub.org). On a desktop PC it ₁₀₆
takes approximately 12-15 seconds to produce an annotation from a typical cell line, ₁₀₇
depending on the number of datasets and intervals (see S1 Figure). *StatePaintR* produces ₁₀₈
genome-browser compatible BED files with color-coded state annotations (specified in ₁₀₉
StateHub model). Figure 2 shows a representative region around the *POLR2A* gene ₁₁₀
from a subset of 77 high-quality(at least 15m reads) tissue samples and cell lines with ₁₁₁
H3K27Ac data from Roadmap. A complete manifest for processing these data is included ₁₁₂
as additional files 1. ₁₁₃

Annotation of genomewide association studies ₁₁₄

A common use of genome annotation is to assign putative function to genetic loci ₁₁₅
identified by genome-wide association studies (GWAS), particularly for non-coding ₁₁₆

Figure 1. Mapping datasets to functional significance annotations. Experimental data and external database annotations are combined into abstraction layers (columns), integrated to produce chromatin states (rows) from the decision matrix. *StatePaintR* produces state assignments by iteratively comparing the marks that are present in each segment with each row of data in the table. The values of color-coded squares signify relationship between data and state: 0 (light red) the feature/data type negates the state but is not required to be present, 1 (light green) feature is consistent with the state but not required, 2 (red) if the feature is required to be available and negates the state, and 3 (green) it is both required and consistent with the state. Information content (sum of row values) of states increases from top to bottom. For the example, red dotted arrows indicate non-matching rows, and green arrows indicate matching rows. The state call corresponds to the last matched row.

regions. We previously used a custom annotation of Roadmap tissues based on the approach described in this manuscript to identify locus-specific tissue enrichment in

Figure 2. Annotation of public epigenomics data sets. Annotations of 77 cell types from the Roadmap Epigenomics consortium, including some Roadmap-processed ENCODE data, selected for their high quality with default model. Roadmap tissues are clustered and color coded at left according to the same color scheme used in Roadmap publications[Roadmap Epigenomics et al., 2015].

	hg19	hg38	mm10
Blueprint (IHEC)	630	548	0
CEEHRC (IHEC)	158	0	2
DEEP (IHEC)	22	0	6
ENCODE	84	109	98
Roadmap	127	0	0

Table 1. Annotation of public datasets. Data from the indicated public consortia were downloaded and processed in *StatePaintR*. The resulting annotation files and browser sessions are available from the StateHub web page under each model page.

variants associated with Parkinson's disease[Coetzee et al., 2016]. In that study we displayed locus-by-tissue enrichment as a heat-map. Here we present a similar analysis using our new *StateHub* model as the basis for an alternative visualization. Since we showed that Parkinson's disease variants are primarily associated with enhancers and promoters[Coetzee et al., 2016], we plotted the 95% range of credible values for enrichment in enhancers and promoters vs background SNPs (matched for GC content & minor allele frequency). Each locus (row) is plotted against a selection of tissues in Roadmap (figure 3).

Figure 3. Locus- and tissue-specific enrichment of Parkinson's GWAS variants GWAS data and LD proxies ≥ 0.8. Bars: 95% credible range for enrichment in active states vs SNPs in the region with similar minor allele frequency and LD < 0.8, for each of 4 independent genetic loci. Significant enrichment profiles for roadmap tissues are displayed in color (REMC lineage-specific colors); non-significant are gray.

Evaluation of two models with respect to cancer methylation

Our "default" model proposes a class of enhancers and promoters in a poised state (EPR and PPR). These features have H3K4me1 or H3K4me3 and lack H3K27Ac. This model also classifies H3K27me3 as silenced/polycomb repressed (SCR). To investigate functional enrichment of methylation variants, we looked at how differentially methylated regions (DMR) in ovarian cancer tumors partition between chromatin states as defined in this model (figure 1).

From previous work CpG islands containing temporarily silenced (poised) genes by polycomb repressive complex in normal tissues may acquire DNA methylation during cancer formation resulting in permanent silencing[Gal-Yam et al., 2008, Teschendorff et al., 2016]. While the segments called EPR and PPR were associated with hypermethylated probes in ovarian cancer across tissues, the magnitude of enrichment was not great (see figure 4, "Model 1"), and it remained possible that our state definitions were too broad.

One hypothesis is that poised promoters are distinguishable by the presence or absence of focussed H3K27me3, in particular the narrowPeak calls (as opposed to broad, low-level enrichment from broadPeak files used in model 1). To address this hypothesis, we repeated the analysis in figure 4 for an alternative model (model 2; "focused poised promoter") in which H3K27me3 is called as both broadPeak and narrowPeaks. We use the H3K27me3 broadPeak file as in the previous model to identify repressed regions, and H3K27me3 narrowPeaks to identify poised states (EPR and PPR). Enhancers lacking H3K27Ac and H3K27me3 were classified as weak enhancers and promoters (EWR and PWR, not shown in figure 4). Regulatory elements with these properties have been also been called "primed"[Calo and Wysocka, 2013].

We found greater enrichment when we defined poised states in this way (compare model 2 (focused poised promoter) with model 1 (default) in figure 4). The hypermethylated ovarian cancer CpGs were more enriched in EPR, PPR, and SCR states as defined in the focused poised promoter model relative to the default model, and hypomethylated probes were enriched only in HET and SCR states (not shown). The odds ratio of enrichment for hypermethylated CpGs in EPR and PPR from the default model fell in the a range from between 0 and 5. However, the enrichment of the hypermethylated probes in our focused poised promoter model was > 5 in PPR and > 10 in EPR (figure 4,

Figure 4. Example of model comparisons. Enrichment as in figure 3 using either of two different state models (model 1 and model 2) from StateHub, "Default" and "Focused Poised Promoter", which differ in the treatment of poised promoters. Y-axis range is the same for both plots. Both models distinguish hypermethylated probes in the poised state but model 2 is more selective than model 1. In this model (2) enhancers with H3K4me1 and promoters with H3K4me3 overlapping narrow regions of H3K27me3 are poised (EPR and PPR), but those without H3K27me3 are called weak (EWR and PWR). Model 1, by contrast, assigns promoters lacking active marks to the poised state.

model 2). Thus, ovarian hypermethylated probes are enriched across roadmap tissues in H3K27me3+ enhancers and promoters, and we concluded that H3K27me3 narrowPeaks are an important distinguishing feature for this class.

Enrichment of functional annotation

Next, we characterized the distribution of states in our focused poised promoter model relative to Gencode v37 gene annotations and also to enhancers from Ensembl[Zerbino et al., 2015]. Figure 5 shows the relative enrichment of Human mammary epithelial cell (HMEC) chromatin states in each of these features. We found enrichment in Ensembl enhancers for three states: Active enhancer (EAR), Active regions (AR) and Weak enhancer (EWR). The definition of "active enhancer" in the Ensembl build is cumulative across cell types[Zerbino et al., 2015] and therefore includes many cell-type specific enhancers that would be predicted to be weak (having exclusively H3K4me1) in a particular cell line such as HMEC. These three states were not enriched in any other category of genomic annotations. Likewise we found enrichment of the inactive enhancers in Transcribed (TRS) and Silenced/Polycomb (SCR). TRS was most enriched in gene body annotations, particularly internal exons and introns. SCR and Heterochromatin (HET) were depleted across all categories. Lastly, the 5′, first exon and first intron regions were enriched in active and weak promoters, consistent with the role of these regions in transcription initiation.

Figure 5. Enrichment in genomic annotations. Relative enrichment of called states genomewide from HMEC in annotations from Ensembl and Gencode. Genegraph (top) visualisation of the regions indicated for each column. Enrichment is log_2 observed over random. Positive enrichment is indicated with mustard color vs relative depletion in purple.

Enhancer predictions

To use ChIP-seq data for quantitative analysis, we ranked within each state by peak score from Macs2 output (generic peak height). We programmed *StatePaintR* to rank each state by normalizing on a scale of 1-1000, 1000 being the highest rank. *StatePaintR* ranks the required dataset(s) for each state (*i.e.* assigned "3" in the decision matrix). To evaluate the ranking function, we measured area under the precision-recall-gain curve (AUPRG) using the set of experimentally validated human and mouse noncoding fragments with

gene enhancer activity as assessed in transgenic mice (VISTA enhancer browser and [Visel et al., 2006]). We randomly sampled 100 enhancers from 7 VISTA tissues to evaluate different aspects of our models (training), and then used the remainder of the data to test our enhancer predictions against previously published predictions using the same data sets.

Some states, including the ones that are germane for enhancer prediction, reference more than one required (matrix value 3) dataset, and therefore it was necessary to optimize the best method for ranking based on > 1 ChIP-seq experiment. We computed the average, median and ceiling functions of ranks across multiple ChIP-seq tracks. The three methods were comparable, but median and average produced the best results (S2 Figure).

There are three required marks for active enhancers in our model, but if one of them is not informative for active enhancer prediction, using the ceiling "max" method would produce false positives when this mark has the highest peak rank. Therefore we interrogated which marks are informative using a leave-one-out approach. We found that leaving out H3K4me1 significantly improved our predictions, whereas leaving out the other marks did not (S3 Figure).

Next we assessed AUPRG of different state calls *vs* VISTA enhancers and found that predictive power descends in order AR + EAR > EAR > AR > RPS > EPRC > etc (S4 Figure). When we tried combinations of states the highest precision recall gain was observed for EAR, EARC, AR and ARC added together (S4 Figure), and this was greater than other combinations and than any of the state calls individually, suggesting that H3K27Ac is the most informative predictor of enhancers.

Since H3K4me1 does not improve predictions and is the only thing that distinguishes between AR and EAR (by its presence or absence), an improved model would consolidate AR and EAR into a single state and reassign "1" to H3K4me1 instead of "3", leaving this mark exclusively to define weak (or primed) promoters.

To validate our method of enhancer prediction, we compared our predictions with ENCODE Encyclopedia, Version 3 (hrefhttp://zlab-annotations.umassmed.edu/enhancers/methodszlab-annotations.umassmed.edu/enhancers/methods), EnhancerFinder[Erwin et al., 2014], RFECS[Rajagopal et al., 2013], DELTA[Lu et al., 2015], CSIANN[Firpi et al., 2010], and REPTILE[He et al., 2017] for held-out data using AUPRG (S5 Figure)[Flach and Kull, 2015].

source	neural tube	midbrain	hindbrain	limb	heart	average auprg	average rank
ENCODE	0.82	0.82	0.80	0.85	0.88	0.83	3.4
EnhancerFinder	NA	0.59	0.63	0.67	0.82	0.54	6.8
REPTILE	0.86	0.87	0.76	0.89	0.92	0.86	2.0
DELTA	0.81	0.84	0.76	0.84	0.93	0.84	3.6
RFECS	0.79	0.85	0.78	0.85	0.92	0.84	3.0
CSIANN	0.72	0.68	0.62	0.69	0.84	0.71	6.2
StatePaintR	0.84	0.84	0.79	0.85	0.88	0.84	3.0

Table 2. Relative performance of *StatePaintR* enhancer ranking *vs.* VISTA enhancers[Visel et al., 2006].

Our predictions are comparable to the Encode model which uses H3K27Ac overlapping with distal DHS, RFECS and REPTILE, which had the lowest average rank across tissues (table 2, S5 Figure). Our predictions compared favorably to EnhancerFinder and CSIANN which had an average rank > 6 across the different tissues; heart, midbrain, hindbrain, neural tube and limb. Predictions are only available for these tissues. Thus,

StatePaintR ranking is useful for drawing quantitative comparisons between different ²²³
models, making predictions, or prioritizing regions for functional evidence. ²²⁴

Discussion ²²⁵

We created a platform for hosting, browsing, and generating new genome annotation ²²⁶
models called *StateHub*. The *StateHub* framework makes it possible to specify combina- ²²⁷
tions of genomic data as they relate to regions of functional significance in epigenetically ²²⁸
marked chromatin. In addition we created a software package, *StatePaintR*, that facili- ²²⁹
tates the use of *StateHub* models to generate browser tracks for bioinformatic analyses. ²³⁰
We showed how *StatePaintR* can be used as part of a workflow with uniformly processed ²³¹
data to generate reproducible annotations from public and private data. ²³²
Our framework does not replace current machine learning methods, the aim of ²³³
which is to discover states. But these methods suffer from certain drawbacks that we ²³⁴
have addressed with a rules-based approach that provides greater transparency and ²³⁵
reproducibility. For example, it is often the case with machine-learning methods that ²³⁶
more states are discovered than immediately understood, and there have been different ²³⁷
solutions proposed. During discovery, one could iteratively reduce the number of states, ²³⁸
minimizing the number of similar or redundant combinations of histone marks. Then ²³⁹
the number of discovered states would depend on the number of unique data types ²⁴⁰
used for learning and their distribution around known features. This brittleness makes ²⁴¹
replication in different settings (with different labs or types of experiments) impractical. ²⁴²
Our method avoids these issues, allowing users to specify a model of the epigenome ²⁴³
in a matrix (as in figure 1) that accounts for all known possibilities. Thus, we built a ²⁴⁴
comprehensive framework for a rules-based annotation, reflecting current hypotheses (or ²⁴⁵
models) of the epigenome. ²⁴⁶
A significant drawback of our approach is that some unusual combinations of marks ²⁴⁷
that may have biological function will be ignored. This has much to do with the fact that ²⁴⁸
StatePaintR is not for discovering novel states, but rather for annotating the genome ²⁴⁹
according to a specific, existing model. Nonetheless, the label assignment step of other ²⁵⁰
chromatin state discovery tools **also** suffers the same limitations; states are aggregated or ²⁵¹
optimized in an iterative fashion based on prior knowledge and assumptions. ENCODE ²⁵²
for example has published tracks for both ChromHMM and Segway that include multiple ²⁵³
states with similar names (*e.g.* "Tss" vs. "TssF" from ChromHMM, and "EnhF1" vs. ²⁵⁴
"EnhF3" from Segway[Hoffman et al., 2013]). To resolve discrepancies between the two ²⁵⁵
methods, the authors of those studies proposed a combined analysis to simplify the ²⁵⁶
number of state labels and summarize discovery using a rule-based metric not unlike ²⁵⁷
a *StateHub* model. Thus, they classified regions into 7 types "emphasizing biologically ²⁵⁸
meaningful differences"[Hoffman et al., 2013]. In direct comparisons we found that our ²⁵⁹
own annotations exhibited greater similarity to the combined analysis than to either ²⁶⁰
of the Segway or ChromHMM tracks separately (not shown). Whatever the protocol, ²⁶¹
the basic problem persists; machine-learning is able to provide insight into what the ²⁶²
categories are, but not how many categories there should be. Currently this remains the ²⁶³
exclusive province of the biologist. ²⁶⁴
One of the additional challenges is compatibility between data sets. In order for two or ²⁶⁵
more cell types to be annotated according to the same model, it is necessary to combine ²⁶⁶
each of the cell types for the training. One solution is concatenation of genomes[Hoffman ²⁶⁷
et al., 2013]. Another approach is to jointly model epigenomes in parallel, as proposed ²⁶⁸
in Integrative and Descriminative Epigenome Annotation System (IDEAS)[Zhang et al., ²⁶⁹
2016]. This approach has the distinctive advantage of also modeling segment boundaries. ²⁷⁰
Our approach does not model boundaries, but does offer some advantages. One is ²⁷¹
reproducibility: *StatePaintR* always produces the same annotation independently for ²⁷²

each cell type from the same model. Secondly, even samples with different types of data or missing data result in compatible annotations because they come from the same model. Third, the models, composed of a 2D matrix with a range of 4 values, are relatively easy to understand and author. Every file produced in *StatePaintR* contains a record of the model ID, genome version and all the source files. Clinicians working with human genetics will value consistency and reproducibility across datasets. We produced annotations for REMC, ENCODE, IHEC and blueprint and made these available on the *StateHub* website for the two models described in this paper. The website also has links to browser sessions where they can be explored and used to create figures. A fourth advantage is speed: samples can be processed in parallel and there is no computationally expensive learning step.

A final feature that is very useful is the ranking by peak score (figure S5 Figure). Using this scheme, we investigated what states contribute most to true enhancers (S2 Figure-S4 Figure). We found that H3K27Ac defined the best predictive subset of annotations for VISTA enhancers. We also investigated different approaches for handling multiple peak calls for a state and found the median to be optimal (S2 Figure), and incorporated this method as the default behavior of *StatePaintR*. When we compared our predictions to held-out data, they were comparable to the best enhancer predictions[He et al., 2017, Rajagopal et al., 2013] and ENCODE enhancers[Dunham et al., 2012] and on the web (unpublished).

We demonstrated a workflow wherein new models generate annotations, which are used to test predictions against experimental data, and then in turn to make improvements to old models. We anticipate that this will be valuable in testing new ideas and hypotheses generated from unsupervised methods. The ability to rank features also aids in prioritizing variants for GWAS and studies of somatic mutations. Knowing which variants overlap features in the epigenomic landscape of a particular cell type is key. In the future, other methods may become available for incorporation into *StatePaintR* but the models described in *StateHub* will remain stable.

Conclusions

We introduced two new computational resources, an online database of chromatin state models and processed genome segmentations called *StateHub*, and an R/Bioconductor tool called *StatePaintR* which translates epigenomics files into segmentations using these models. One may annotate incomplete datasets rapidly and sensibly according to a single model specification that gracefully degrades to lesser annotations with missing data. Annotations have header documentation with genome version, *StateHub* model, and the names of source files and their mappings. These tools document segmentations and state labels precisely as they are used in individual studies and to allow comparisons between evolving models of epigenomic states as they relate to NGS experiments. They also enable mixing of epigenomic states with other types of data, such as 3D looping assays, transcription factors, primary sequence features such as position weight matrices, or disease variants.

Materials and Methods

StateHub models

The main text makes reference to two models in *StateHub* (www.statehub.org). The unique identifiers of these models are as follows: "Default" (model ID: 581ff9f246e0fb06b4b6b178) and "Focused Poised promoter" (model ID:

5813b67f46e0fb06b493ceb0). In each of the two models presented and discussed in this paper we chose a naming convention for our states reflecting biological function.

Annotation of public datasets

Preprocessed peak calls were obtained from the IHEC and ENCODE websites (see Table 1) for hg19, and where possible hg38. Where possible we used IDR (Irreproducible discovery rate) processed narrowPeak calls for DHS and broadPeaks for broad marks (H3K27Ac, H3K4me1, H3K27me3, H3K36me3) unless otherwise specified in the model. A complete manifest with filenames, plus all annotation tracks are available on the *StateHub* website.

Analysis of methylation data

To select methylation variants, we analyzed the Infinium HM450 data of 114 ovarian tumor samples[Patch et al., 2015] and 216 control normal Fallopian tube samples[Teschendorff et al., 2016]. The differentially methylated probes were called (FDR-corrected p-value < 0.01) and divided into hyper- and hypo-methylated probes (difference $\beta \geq 0.3$ cancer *vs.* normal).

Enrichment calculations

Parkinson's GWAS variants. A conjugate beta-binomial distribution was used for estimating the 95% highest density interval (HDI) for the credible differences of the enrichment of single SNPs with Parkinson's at each locus for observed vs. random SNPs, matched for both GC content and minor allele frequency. Matching random SNPs were generated using the webtool SNPsnap[Pers et al., 2015]. *Comparison of models with demethylated regions.* Enrichment calculations were done as in figure 4, using either of two different state models from StateHub, default and focused poised promoter, which differ in the treatment of poised promoters.*Enrichment in genomic annotations.* Analyses and graphics were produced using the SegTools package[Buske et al., 2011].

Code for figures and tables

All code used to generate figures, tables, and this manuscript is included as additional file 1.

Supporting Information ₃₄₈

The following are additional files containing manifests to run *StatePaintR* with current ₃₄₉
releases of all public datasets listed in Table 1, links to segmentation tracks, and all code ₃₅₀
used for analysis and generation figures in this manuscript. ₃₅₁

Additional file 1 — Rnotebook ₃₅₂

Complete code generated from R markdown (Rnotebooks/html format) for generating ₃₅₃
all analyses, figures and tables. ₃₅₄

S1 Figure

Figure S1. Relationship between data and runtime

StatePaintR takes only a few seconds to run. The exact time depends on the number number of unique segments (lines of data) created by overlapping genomic intervals of all input files, cumulative. Thus, 128 Roadmap tissues can be run in $10s \times 128 \approx 1,280s$ $(21m)$.

S2 Figure

Figure S2. Predictions with multiple marks.
Ranked ChIP-seq peak scores for multiple marks were used to rank active enhancers
(H3K4me1 + H3K27Ac + DHS) by 3 methods (median, mean, ceiling) and compared to
a sample ($n = 100$) of experimentally validated enhancers. The average or median of
three marks was a better predictor than ceiling. The choice of function is subservient to
choice of data for ranking–if one of the three is less informative, it will produce false
positives when using the max method–therefore it is better to eliminate uninformative
marks. See also S4 Figure.

S3 Figure

Supplementary Figure 3 – Scoring Features

Figure S3. Ranking enhancers with subsets of marks.
Combinations of marks were used to predict active enhancers by the max ranking method
(as in S2 Figure) and compared to enhancer score. "All" includes regulatory (H3K4me1),
active (H3K27Ac), and core (DHS). We also tried a leave-one-out strategy for each
of these categories in succession. Leaving out H3K4me1 ("no regulatory") produced
superior predictions, suggesting that its inclusion made the predictions less specific.

S4 Figure

Supplementary Figure 4 – Scoring Segments

Figure S4. Chromatin states as predictors of true enhancers.
We tested different chromatin states for their ability to predict true enhancers under
the poised focused promoter model. Active enhancers exhibited the greatest predictive
power under the precision recall gain curve.

S5 Figure

Figure S5. Performance of enhancer predictions.
Area under precision-recall-gain curves reflect the accuracy of three models of enhancer prediction. True positive enhancers are those validated in the VISTA enhancer browser. The ENCODE method (in blue) and the *StatePaintR* method (in red) show similar accuracy in retrieving VISTA enhancers showing tissue specific enhancer activity, while EnhancerFinder (in green) is less accurate.

Acknowledgments

The study was funded by NIH UO1CA184826 (BPB), startup funds to BPB, and RO1CA190182 (DJH).

References

J. Biesinger, J. Wang, and X. Xie. Discovering and mapping chromatin states using a tree hidden markov model. *BMC Bioinformatics*, 14 Suppl 5, 2013. ISSN S4. doi: 10.1186/1471-2105-14-S5-S4.

Alan P. Boyle, Sean Davis, Hennady P. Shulha, Elliott H. Margulies, Zhiping Weng, and Terrence S. Furey. High-resolution mapping and characterization of open chromatin across the genome. *Cell*, 132:311–322, January 2008. ISSN 2. doi: 10.1016/j.cell.2007. 12.014.

Jason D. Buenrostro, Paul G. Giresi, Lisa C. Zaba, Howard Y. Chang, and William J. Greenleaf. Transposition of native chromatin for fast and sensitive epigenomic profiling of open chromatin, DNA-binding proteins and nucleosome position. *Nature methods*, 10:1213–1218, October 2013. doi: 10.1038/nmeth.2688.

O. J. Buske, M. M. Hoffman, N. Ponts, K. G. Le Roch, and W. S. Noble. Exploratory analysis of genomic segmentations with segtools. 12:415, 2011. doi: doi:10.1186/ 1471-2105-12-415.

Eliezer Calo and Joanna Wysocka. Modification of enhancer chromatin: what, how and why? *Molecular Cell*, 49(5):825–837, 2013. doi: 10.1016/j.molcel.2013.01.038.

Simon G Coetzee, Steven Pierce, Patrik Brundin, Lena Brundin, Dennis J Hazelett, and Gerhard A Coetzee. Enrichment of risk SNPs in regulatory regions implicate diverse tissues in parkinson's disease etiology. *Scientific Reports*, 6:30509, July 2016.

Shawn J. Cokus, Suhua Feng, Xiaoyu Zhang, Zugen Chen, Barry Merriman, Christian D. Haudenschild, Sriharsa Pradhan, Stanley F. Nelson, Matteo Pellegrini, and Steven E. Jacobsen. Shotgun bisulphite sequencing of the *Arabidopsis* genome reveals DNA methylation patterning. *Nature*, 452:215–219, March 2008. doi: 10.1038/nature06745.

Ian Dunham, Anshul Kundaje, Shelley F. Aldred, Patrick J. Collins, Carrie A. Davis, Francis Doyle, et al. An integrated encyclopedia of DNA elements in the human genome. *Nature*, 489(7414):57–74, September 2012. ISSN 0028-0836, 1476-4687. doi: 10.1038/nature11247.

Jason Ernst and Manolis Kellis. ChromHMM: automating chromatin-state discovery and characterization. *Nature Methods*, 9:215–216, February 2012.

Genevieve D. Erwin, Nir Oksenberg, Rebecca M. Truty, Dennis Kostka, Karl K. Murphy, Nadav Ahituv, Katherine S. Pollard, and John A. Capra. Integrating diverse datasets improves developmental enhancer prediction. *PLOS Computational Biology*, 10(6): 1–20, 06 2014. doi: 10.1371/journal.pcbi.1003677. URL http://dx.doi.org/10. 1371%2Fjournal.pcbi.1003677.

Hiram A Firpi, Duygu Ucar, and Kai Tan. Discover regulatory DNA elements using chromatin signatures and artificial neural network. *Bioinformatics*, 26(13):1579–1586, jul 2010. ISSN 1367-4803. URL http://dx.doi.org/10.1093/bioinformatics/ btq248.

Peter Flach and Meelis Kull. Precision-recall-gain curves: Pr analysis done right. In C. Cortes, N. D. Lawrence, D. D. Lee, M. Sugiyama, and R. Garnett, editors, *Advances in Neural Information Processing Systems 28*, pages 838–846. Curran Associates, Inc., 2015. URL http://papers.nips.cc/paper/5867-precision-recall-gain-curves-pr-analysis-done-right.pdf.

Einav Nili Gal-Yam, Shinwu Jeong, Amos Tanay, Gerda Egger, Amy S. Lee, and Peter A. Jones. Constitutive nucleosome depletion and ordered factor assembly at the GRP78 promoter revealed by single molecule footprinting. *PLOS Genetics*, September 2006. doi: 10.1371/journal.pgen.0020160.

Einav Nili Gal-Yam, Gerda Egger, Leo Iniguez, Heather Holster, Steingrímur Einarsson, Xinmin Zhang, Joy C Lin, Gangning Liang, Peter A Jones, and Amos Tanay. Frequent switching of Polycomb repressive marks and DNA hypermethylation in the PC3 prostate cancer cell line. *Proceedings of the National Academy of Sciences*, 105(35): 12979–12984, sep 2008. ISSN 0027-8424. doi: 10.1073/pnas.0806437105.

Kathryn E. Gardner, C. David Allis, and Brian D. Strahl. OPERating ON chromatin, a colorful language where context matters. *Journal of Molecular Biology*, 409:36–46, May 2011. ISSN 1. doi: 10.1016/j.jmb.2011.01.040.

Yupeng He, David U Gorkin, Diane E Dickel, Joseph R Nery, Rosa G Castanon, Ah Young Lee, Yin Shen, Axel Visel, Len A Pennacchio, Bing Ren, and Joseph R Ecker. Improved regulatory element prediction based on tissue-specific local epigenomic signatures. *Proceedings of the National Academy of Sciences*, page 201618353, feb 2017. ISSN 0027-8424. doi: 10.1073/pnas.1618353114. URL http://www.pnas.org/content/early/2017/02/07/1618353114.abstracthttp://www.pnas.org/lookup/doi/10.1073/pnas.1618353114.

Michael M. Hoffman, Orion J. Buske, Jie Wang, Zhiping Weng, Jeff A. Bilmes, and William Stafford Noble. Unsupervised pattern discovery in human chromatin structure through genomic segmentation. *Nature Methods*, 9(5):473–476, March 2012.

Michael M. Hoffman, Jason Ernst, Steven P. Wilder, Anshul Kundaje, Robert S. Harris, Max Libbrecht, Belinda Giardine, Paul M. Ellenbogen, Jeffrey A. Bilmes, Ewan Birney, Ross C. Hardison, Ian Dunham, Manolis Kellis, and William Stafford Noble. Integrative annotation of chromatin elements from encode data. *Nucleic Acids Research*, 41(2): 827–841, jan 2013. doi: 10.1093/nar/gks1284.

Gary Hon, Bing Ren, and Wei Wang. ChromaSig: a probabilistic approach to finding common chromatin signatures in the human genome. *PLOS Computational Biology*, 4 (10):e1000201, 2008. doi: doi:10.1371/journal.pcbi.1000201.

Yifeng Li, Chih-yu Chen, Alice M. Kaye, and Wyeth W. Wasserman. The identification of cis-regulatory elements: A review from a machine learning perspective. *BioSystems*, 138:6–17, October 2015. doi: 10.1016/j.biosystems.2015.10.002.

Yiming Lu, Wubin Qu, Guangyu Shan, and Chenggang Zhang. DELTA: A Distal Enhancer Locating Tool Based on AdaBoost Algorithm and Shape Features of Chromatin Modifications. *PLOS ONE*, 10(6):e0130622, jun 2015. URL http://dx.doi.org/10.1371{%}2Fjournal.pone.0130622.

Alessandro Mammana and Ho-Ryun Chung. Chromatin segmentation based on a probabilistic model for read counts explains a large portion of the epigenome. *Genome Biology*, 16(151):12 pages, July 2015. doi: 10.1186/s13059-015-0708-z.

A. M. Patch, E. L. Christie, D. Etemadmoghadam, D. W. Garsed, J. George, S. Fereday, et al. Whole-genome characterization of chemoresistant ovarian cancer. *Nature*, 521 (7553):489–494, May 2015. doi: 10.1038/nature14410.

Tune H. Pers, Pascal Timshel, and Joel N. Hirschhorn. SNPsnap: a Web-based tool for identification and annotation of matched SNPs. *Bioinformatics*, 31:418–420, 2015. ISSN 3. doi: 10.1093/bioinformatics/btu655.

Nisha Rajagopal, Wei Xie, Yan Li, Uli Wagner, Wei Wang, John Stamatoyannopoulos, Jason Ernst, Manolis Kellis, and Bing Ren. RFECS: A Random-Forest Based Algorithm for Enhancer Identification from Chromatin State. *PLOS Computational Biology*, 9(3):e1002968, mar 2013. URL http://dx.doi.org/10.1371{%}2Fjournal.pcbi.1002968.

Oliver J. Rando. Combinatorial complexity in chromatin structure and function: revisiting the histone code. *Current Opinion in Genetics and Development*, 22:148–155, April 2013. ISSN 2. doi: 10.1016/j.gde.2012.02.013.

Consortium Roadmap Epigenomics et al. Integrative analysis of 111 reference human epigenomes. *Nature*, 518:317–330, feb 2015.

Scott E. Rothbart and Brian D. Strahl. Interpreting the language of histone and dna modifications. *Biochemica et Biophysica Acta*, 1839:627–643, August 2014. ISSN 8. doi: 10.1016/j.bbagrm.2014.03.001.

Federico Andrea Santoni. EMdeCODE: a novel algorithm capable of reading words of epigenetic code to predict enhancers and retroviral integration sites and to identify h3r2me1 as a distinctive mark of coding versus non-coding genes. *Nucleic Acids Research*, 41:e48, December 2012.

Jeremy M. Simon, Paul G. Giresi, Ian J. Davis, and Jason D. Lieb. Using formaldehyde-assisted isolation of regulatory elements (FAIRE) to isolate active regulatory DNA. *Nature protocols*, 7:256–267, January 2012. doi: 10.1038/nprot.2011.444.

K. A. Sohn, J. W. Ho, Djordjevic D., H. H. Jeong, P. J. Park, and J. H. Kim. hiHMM: Bayesian non-parametric joint inference of chromatin state maps. *Bioinformatics*, 31, July 2015. ISSN 13. doi: 10.1093/bioinformatics/btv117.

Jimin Song and Kevin C. Chen. Spectacle: fast chromatin state annotation using spectral learning. *Genome Biology*, 16(33):18 pages, February 2015. doi: 10.1186/s13059-015-0598-0.

Andrew E. Teschendorff, Yang Gao, Allison Jones, Matthias Ruebner, Matthias W. Beckmann, David L. Wachter, Peter A. Fasching, and Martin Widschwendter. DNA methylation outliers in normal breast tissue identify field defects that are enriched in cancer. *Nature Communications*, 7(10478), January 2016. doi: 10.1038/ncomms10478.

Robert E. Thurman, Eric Rynes, Richard Humbert, Jeff Vierstra, Matthew T. Maurano, Eric Haugen, et al. The accessible chromatin landscape of the human genome. *Nature*, 489(7414):75–82, September 2012. ISSN 0028-0836, 1476-4687. doi: 10.1038/nature11232. URL http://www.nature.com/doifinder/10.1038/nature11232.

Axel Visel, Simon Minovitsky, Inna Dubchak, and Len A. Pennacchio. Vista enhancer browser—a database of tissue-specific human enhancers. *Nucleic Acids Research*, 35:D88, 2006. doi: 10.1093/nar/gkl822. URL http://dx.doi.org/10.1093/nar/gkl822.

Benedikt Zacher, Michael Lidschreiber, Patrick Cramer, Julien Gagneur, and Achim Tresch. Annotation of genomics data using bidirectional hidden Markov models unveils variations in Pol II transcription cycle. *Molecular Systems Biology*, 10(12):768, December 2014. doi: 10.15252/msb.20145654.

Daniel R. Zerbino, Steven P. Wilder, Nathan Johnson, Thomas Juettemann, and Paul R. Flicek. The Ensembl regulatory build. *Genome Biology*, 16(56), mar 2015. doi: 10.1186/s13059-015-0621-5.

Yu Zhang, Lin An, Feng Yue, and Ross C. Hardison. Jointly characterizing epigenetic dynamics across multiple human cell types. *Nucleic Acids Research*, 44(14):6721–6731, April 2016.