TITLE

Model-based fMRI Reveals Dissimilarity Processes Underlying Base Rate Neglect

AUTHORS

Sean R. O'Bryan*[a], Darrell A. Worthy[b], Evan J. Livesey[c], Tyler Davis[a]

AFFILIATIONS

a Department of Psychological Sciences, Texas Tech University, Lubbock, TX, 79409
b Department of Psychology, Texas A&M University, College Station, TX, 77843
c School of Psychology, University of Sydney, Sydney, New South Wales, Australia

CONTACT

Correspondence to:

Sean R. O'Bryan
Texas Tech University
Department of Psychological Sciences
MS 2051
Lubbock, TX 79409

sean.r.obryan@ttu.edu; 806.500.1183

Abstract

Extensive evidence suggests that people use base rate information inconsistently in decision making. A classic example is the inverse base rate effect (IBRE), whereby participants classify ambiguous stimuli sharing features of both common and rare categories as members of the rare category. Computational models of the IBRE have either posited that it arises from associative similarity-based mechanisms or dissimilarity-based processes that may depend upon higher-level inference. Here we develop a hybrid model, which posits that similarity- and dissimilarity-based evidence both contribute to the IBRE, and test it using functional magnetic resonance imaging data collected from human subjects completing an IBRE task. Consistent with our model, multivoxel pattern analysis reveals that activation patterns on ambiguous test trials contain information consistent with dissimilarity-based processing. Further, trial-by-trial activation in left rostrolateral prefrontal cortex tracks model-based predictions for dissimilarity-based processing, consistent with theories positing a role for higher-level symbolic processing in the IBRE.

Keywords: Categorization; fMRI; base rates; multivoxel analysis, rostrolateral prefrontal cortex; exemplar model

1   **Introduction**

2   Does this patient have influenza or Ebola virus? Categorization is a fundamental

3   process that underlies many important decisions. Categories, such as viruses,

4   often have different relative frequencies or base rates. Influenza, for example, is

5   very common and infects millions of people worldwide each year, whereas Ebola

6   virus tends to have infection rates that are orders of magnitude lower.

7   One critical question is how people use such base rate information when

making categorization decisions. Research so far has suggested that people

tend to be, at best, inconsistent in their use of base rate information. Both in

realistic studies with medical professionals and artificial categorization tasks in

the lab, when confronted with examples that share characteristics with both rare

and common categories, people show a tendency to predict the rare category

much more often than the base rates would suggest (Tversky & Kahneman,

1974; Casscells, Schoenberger & Graboy, 1978; Bravata, 2000). In an extreme

case, known as the inverse base rate effect (IBRE), people may even predict

rare categories as more likely than common ones (Medin & Edelson, 1988). For

example, in an IBRE context, a patient presenting with cough (a characteristic

feature of influenza) and unexplained bleeding (a characteristic feature of Ebola),

may be more likely to be diagnosed with Ebola than influenza.

20   The mechanisms that lead to base rate neglect are currently

undetermined at both the cognitive and neural levels. Computationally, according

to influential work with similarity-based categorization models (Medin & Edelson,

1988; Kruschke, 1996, 2001), the IBRE arises from differential selective attention

to features for common and rare categories. Specifically, participants learn to

attend more strongly to features of rare categories, making ambiguous cases

seem more similar to rare categories and thus more likely to be rare category

members. In terms of the flu example, participants may attend more to the

unexplained bleeding feature of the rarer Ebola virus category, and thus predict

Ebola when confronted with a patient with both features.

Similarity-based category learning models have strong support in the

neurobiological category learning literature. Model-based predictions for how

similar items are to stored category representations have been shown to

correlate with activation in the medial temporal lobes (MTL; Davis, Love &

Preston, 2012a; 2012b). Moreover, at a finer-grained level, multivoxel activation

patterns in the MTL have been shown to contain information associated with

higher-order similarity relationships between category members anticipated by

similarity-based models (Davis & Poldrack, 2014), including those predicted by

differences in selective attention (Mack, Love & Preston, 2016). The dorsolateral

prefrontal cortex (dlPFC) tends to track predictions of choice uncertainty from

similarity-based models, whereas ventromedial PFC (vmPFC) tends to track

estimates of high choice accuracy or model-confidence (Davis, Goldwater &

Giron, 2017).

Despite the strong cognitive and neural evidence for similarity-based

models, it remains an open question whether they provide a complete account of

IBRE-like phenomena. One alternative that has been proposed is that people's

choice of rare categories when confronted with conflicting information may stem

from the reliance on dissimilarity processes, either on their own, or in addition to

similarity-based processes. According to theories that focus on dissimilarity-

based processes, people build strong expectations of the common category; thus

they view items containing features inconsistent with these expectations as more

likely to be members of the rare category (Juslin, Wennerholm & Winman, 2001;

Winman et al., 2005). For example, a doctor may have seen thousands of cases

of flu, none with unexplained bleeding, and thus rule out influenza and choose

Ebola virus based on these expectations. In these cases, it is *dissimilarity* to

members of the common category that drives choice, rather than the similarity to

rare category members per se.

Formal models positing dissimilarity processes have so far been explicitly

dual-process oriented. For example, ELMO, a computational model that

incorporates a choice elimination decision based on dissimilarity argues that

such elimination depends on explicit reasoning processes that are separate from

similarity-based processes that arise on other trials (Juslin, Wennerholm &

Winman, 2001). In the present study, we propose a new account based on a

recently proposed dissimilarity-based extension of the generalized context

model, the dissGCM (Stewart & Morin, 2007). This account uses the exact same

basic similarity computations as standard similarity-based models (e.g.,

Nosofsky, 1986), but allows similarities and dissimilarities to stored exemplars to

be used as evidence for a category. In terms of the above example, dissimilarity

to influenza can be used as evidence for Ebola (and vice versa).

As specified computationally, the dissGCM is agnostic about whether

dissimilarity-based evidence constitutes a different cognitive or neurobiological

mechanism from similarity-based evidence. On one hand, the dissGCM has no

fundamentally different computations from a basic similarity process; as detailed

below, dissimilarity is a simple transformation of similarity. On the other hand, it is

possible that dissimilarity processes require manipulating similarity relationships

between category representations in a more symbolic or abstract manner, as

anticipated by previous dissimilarity theories.

Higher-level cognitive control mechanisms are thought to depend upon a

hierarchy of abstraction in the lateral PFC along the rostral-caudal axis (Badre &

D'Esposito, 2007, 2009). At the apex of this hierarchy is the rostrolateral PFC

(rlPFC), a region often implicated in tasks that require people to generalize

across abstract, symbolic representations. For example, relational reasoning

tasks like Raven's progressive matrices and rule-based tasks involving abstract

relations are thought to depend on left rlPFC (Christroff et al., 2001; Bunge et al.,

2005, 2009; Davis, Goldwater, & Giron, 2017). In addition to its role in

generalizing abstract, relational rules, we have recently found left rlPFC to be

involved in rule evaluation and novel generalization processes for simpler

feature-based rules in categorization tasks (Paniukov & Davis, 2018). In the

present study, dissimilarity-based generalization to novel feature pairings may

depend on rule evaluation processes in the rlPFC more so than simple similarity-

based processing, if studies anticipating that dissimilarity-based processes

depend more upon higher-level symbolic rules are correct (Juslin, Wennerholm,

& Winman, 2001; Winman et al., 2005).

Here we test the dissGCM by incorporating its predictions into an analysis

of fMRI data collected from participants completing a standard IBRE task (Medin

& Edelson, 1988; Kruschke, 1996). We first examine whether activation patterns

elicited during conflicting trials in the IBRE task are consistent with participants

thinking more about the rare category, as predicted by pure similarity-based

accounts, or thinking more about (dissimilarity to) the common category, as

predicted by the dissGCM. To this end, we use representational similarity

analysis (RSA; Kriegeskorte et al., 2008) to decode which features of the stimuli

are most strongly activated while participants are categorizing the conflicting

items. This analysis is based on recent work in the broader memory literature

establishing that it is possible to decode whether participants are thinking about

or retrieving particular object categories from memory based on their activation

patterns in ventral temporal cortex (Rissman & Wagner, 2012; Haxby, Connolly,

& Guntupalli, 2014). Here we use the real world visual categories faces, scenes,

and objects as stimulus features. These visual categories have a well-defined

representational topography across the cortex (Haxby et al., 2001; Grill-Spector

& Weiner, 2014), allowing us to predict whether participants are thinking about a

particular stimulus feature (faces, scenes, or objects) by computing similarities

between activation patterns elicited for the key IBRE trials and feature-specific

patterns from an independent localizer scan. By crossing the visual stimulus

features with our category structure (Figure 1), we create situations where a rare

category is associated with one feature type (e.g., a scene) whereas a common

category is associated with another feature type (e.g., an object). The extent to

which each type of information is active can then be compared to determine

whether participants are thinking more about common or rare categories on a

trial, and thus answer whether their neural activation patterns are more

consistent with pure similarity or dissGCM's combined dissimilarity and similarity

processes.

Figure 1. Abstract task design and an example trial. In the headings, I = imperfect predictor, PC =

common perfect predictor, PR = rare perfect predictor. The second row refers to the visual

category used for each stimulus feature: F = face, S = scene, O = object. Each following row

corresponds to a learning trial, with a "1" indicating the presence of the feature and "0" indicating

its absence.

In addition to our multivoxel analysis, we also test whether the

dissimilarity-based evidence may tap distinct brain regions, such as the rlPFC,

beyond those involved with similarity-based evidence. To this end, we take trial-

by-trial predictions for how much similarity- and dissimilarity-based evidence

contribute to the winning category choice and use these predictions as

regressors in fMRI analysis. We anticipated that the MTL and vmPFC would be

positively associated with similarity-based evidence, whereas dlPFC would be

negatively associated with similarity-based evidence. Contrastingly, we expected

rlPFC to track estimates of dissimilarity-based evidence.

138   **Model**

The dissimilarity generalized context model (dissGCM) is based off of the original

generalized context model (Nosofsky, 1986), but allows for dissimilarity to be

used as evidence for a decision (Stewart & Morin, 2007). The model posits that

people represent stimuli as points in a multidimensional feature space.

Categorization judgments are based off of distances between probe stimuli Si

and stored exemplars Sj along each dimension k:

$$d_{ij} = \left(\sum_{k=1}^{K} w_k |S_{ik} - S_{jk}|^r \right)^{1/r}, \qquad (1)$$

146   where r defines the metric of the space, here assumed to be one (city-block). The

147   w_k indicates dimensional attention weights, which have the function of stretching

148   the distance along strongly attended dimensions, and are constrained to sum to

149   one.

150   Distances are converted to similarities via an exponential transform:

151
$$sim_{ij} = e^{-cd_{ij}}, \qquad\qquad (2)$$
152

where c is a specificity parameter that controls the rate at which similarity decays

as a function of distance.

Like the standard GCM, similarities to all exemplars of each category are

summed into evidence for each category. However, in the dissGCM, evidence

that an item is dissimilar to other categories is also used as evidence for a

category. For example, evidence for Disease 1 includes not only an item's

similarity to members of Disease 1, but also its dissimilarity to other diseases.

The overall evidence, v, for a category C_A, given stimulus S_i is:

$$v_{iA} = s \sum_{S_j \in C_A} t_j sim_{ij} + (1 - s) \sum_{S_j \in \neg C_A} t_j (1 - sim_{ij}), \qquad (3)$$

where s is a free parameter that determines how much the model weights

similarity versus dissimilarity. The parameter t_j reflects exemplar-specific memory

strength, which we fix at each exemplar's true base rate during learning (1 for

rare category exemplars, 3 for common category exemplars). Here, we also

make the assumption that exemplars only contribute evidence (similarity or

dissimilarity) if they have at least one positive feature match with a probe

stimulus.

The model makes a prediction for how likely an item is to be classified as

a member of a given category C_A by:

$$pr(resp = C_A|S_i) = \frac{v_{iA} + b}{\sum v_{iC} + 4b}, \qquad (4)$$

where b is a free parameter that reflects the baseline level of similarity for a

category that has zero positive feature matches. More generally, this parameter

ensures that no predicted probabilities are zero or one, which interferes with the

maximum likelihood-based model fits.

The model was fit to the group response frequencies for each option by

minimizing the -2 * Log Likelihood (G^2) using a differential evolution function

optimizer. The overall fit was 4,314.588. The best fitting parameters for each of

the dimension weights were w_1 (face 1) = 0.277, w_2 (common scene) = 0.665, w_3

(rare object) = 0.887, w_4 (face 2) = 0.170, w_5 (common object) = 0.712, and w_6

(rare scene) = 0.879); c = 9.05; s = 0.946; b = 0.023.

For the model-based neuroimaging analysis, we break the evidence v for

the winning (most probable) category into separate measures indicating the

similarity-based evidence (the summed similarity to the winning category) and

dissimilarity-based evidence (summed dissimilarity to other categories). Likewise,

for the multivoxel analysis we examine how much each category's exemplars

(common and rare) contribute to the rare response for ambiguous items to

predict how strongly participants should be activating information associated with

each category.

191   **Results**

Behavioral Results

Learning curves over the 12 learning blocks for common and rare disease item

pairs are shown in Figure 2. All subjects reached greater than 90% accuracy

over the last 4 blocks (M = 98.1%, SD = 2.4%, range = 93.5 – 100%). Mean

choice performance in the first block was above chance (25%) for both common

(M = 63.6%) and rare (M = 43.2%) feature pairs. Consistent with previous IBRE

studies, a mixed effects ANOVA revealed a significant block by feature type

interaction, F (1, 21) = 9.87, p = .005: the common diseases were learned more

quickly than the rare diseases, with prediction accuracy for the common and rare

feature pairs becoming comparable by the fifth learning block.

Figure 2. Learning curves. Points depict proportions correct for common and rare disease predictions over the 12 blocks of the training phase (mean ± SEM).

Choice probabilities and dissGCM-derived predictions for each of the test

items are summarized in Table 1. Consistent with an inverse base-rate effect,

participants were numerically more likely to classify ambiguous test stimuli

(combinations of rare and common features) as members of the relevant rare

category (M = 47.6%) than the relevant common category (M = 43.4%). A one-

sample t-test revealed that the percentage of rare responding on ambiguous

trials was significantly higher than the 1/4 base rate for the rare category, t (21) =

8.11, p < .001.

Test Item	Behavior				DissGCM			
	D1	D2	D3	D4	D1	D2	D3	D4
F1+S1	.972	.018	.008	.003	.971	.014	.008	.008
F1+O1	.031	.962	.008	0.	.063	.901	.018	.018
F2+O2	.005	0.	.987	.008	.008	.008	.972	.013
F2+S2	.023	.008	.069	.901	.018	.018	.059	.905
F1	.667	.295	.023	.015	.667	.283	.025	.025
F2	.107	.038	.550	.305	.027	.027	.640	.307
S1	.848	.061	.008	.083	.955	.015	.015	.015
O1	.008	.908	.069	.015	.040	.880	.040	.040
O2	.008	.069	.908	.015	.012	.012	.965	.012
S2	.023	.053	.008	.916	.032	.032	.032	.904
S1+O1	*.414*	*.487*	*.073*	*.027*	*.419*	*.496*	*.042*	*.042*
O2+S2	*.035*	*.047*	*.453*	*.465*	*.038*	*.038*	*.460*	*.464*
F1+O2	.131	.238	.631	0.	.156	.174	.658	.013
F1+S2	.264	.062	.008	.667	.178	.237	.023	.563
F2+S1	.608	.031	.138	.223	.657	.013	.155	.175
F2+O1	.008	.674	.302	.016	.024	.567	.170	.239
O1+O2	.008	.514	.475	.004	.040	.444	.477	.040
S1+S2	.397	.065	.011	.527	.400	.040	.040	.520

Table 1. Observed and dissGCM-predicted response probabilities for the test phase. The

feature combinations presented at test are listed in the leftmost column: F = face, S = scene,

O = object. In the headings, D1 – D4 correspond to the four possible category responses

(diseases). Bold, italicized values indicate results for the key ambigous stimuli in which a

scene was paired with an object.

Multivoxel Results

Test Phase. The primary goal of the multivoxel analysis was to decode, for the

ambiguous stimuli, whether participants were thinking more about the common or

rare category when they make the choice to classify the stimulus as rare.

Specifically, for the bold italicized stimuli listed in Table 1, we tested whether

participants' activation patterns were more similar to localizer activation patterns

associated with scenes when a scene was the common feature (and object was

rare) and more similar to those of objects when an object was the common

feature (and scene was rare).

The prediction that information associated with the common category

should be more active on ambiguous trials is derived from the dissGCM. The

model posits that the higher probability for a rare response is based on the

contribution that dissimilarity to the common category makes to the evidence for

the rare category. Indeed, in the fitted version of the model, the evidence for rare

contributed by similarity to the rare category exemplar was nearly half the

evidence contributed by dissimilarity to the common category exemplar (rare =

0.088; common = 0.153, in the dissGCM's attention weighted similarity units).

Neural similarities to both visual stimulus categories on the ambiguous

test trials are depicted in Figure 3. Consistent with the dissGCM's predictions, a

linear mixed effects model revealed that when participants made a rare choice,

their activation patterns were most similar to whichever visual stimulus category

(scenes or objects) was associated with the common category, t (21) = 2.78, p =

.011. Interestingly, there was no significant difference between pattern similarity

for rare and common features when participants made a common response, t

(21) = 0.45, p =.653. This pattern, whereby participants tended to only

differentially activate patterns associated with common features when they made

a rare response, manifested in a significant interaction, t (42) = -2.22, p = .032.

Figure 3. Neural similarity to visual stimulus categories for ambiguous trials in which

participants made common (left) and rare (right) responses (mean ± SEM). The white

squares indicate similarity for trials in which an object or scene was the common category

feature. Black squares indicate similarity for trials in which an object or scene was the

rare category feature.

Learning Phase. Beyond our primary questions about test phase activation,

multivoxel analysis of the learning phase can provide additional information about

how participants were processing stimuli in the present task. Generally, both

similarity-based models and dissimilarity-based models like the dissGCM predict

that features which are most informative about the correct category will contribute

more to categorization decisions during learning. With respect to multivoxel

predictions, this means that activation patterns elicited during learning should

contain more information about the predictive features (objects or scenes) than

non-predictive features (faces), and both of these types of information should be

activated more strongly than non-present features. Figure 4 depicts mean pattern

similarities for predictive, non-predictive, and non-present visual stimulus

categories during the learning phase for both common and rare disease trials. As

anticipated, a one-way within-subjects ANOVA collapsed across trial type

revealed that neural similarity to the visual category was the strongest for

perfectly predictive features (M = .065), followed by the non-predictive but

present features (M = -.050) and the non-present features (M = -.145), F (2, 42) =

41.0, p < .001. This finding, whereby activation patterns elicited for stimuli during

learning are most similar to predictive features, is consistent with recent studies

using MVPA to measure dimensional selective attention in categorization and

reinforcement learning (Mack et al., 2013; 2016; Leong et al., 2017; O'Bryan et

al., 2018).

275   Although the greater contribution of predictive features to multivoxel

activation patterns during learning is a straightforward prediction that is

consistent with any model, a further question is how such activation patterns

during learning contribute to later test performance. As with the test phase,

dissimilarity-based theories make the somewhat counterintuitive prediction that it

is specifically what people learn about the common category that is driving later

choices of the rare category. One way to test this using activation patterns

elicited during learning is to examine how the activation of rare and common

information patterns is associated with the extent to which individual participants

exhibit the inverse base rate effect later during the test phase. Consistent with

dissimilarity-based accounts, we found that greater activation of neural patterns

associated with the common features during learning was correlated with a

higher proportion of rare choices on the ambiguous test trials, $r = .550$, $t(20) =$

2.95, $p = .008$. Alternatively, we found no relationship between activation of

neural patterns associated with the rare features during learning and choice

proportions on IBRE trials, $r = .158$, $t(20) = .713$, $p = .483$. Figure 5 depicts the

associations between neural similarity to common and rare features during

learning and base-rate neglect.

Figure 4. Multivoxel pattern similarity to each feature type during the learning phase (mean ± SEM). The left panel is for trials predictive of a common disease, and the right for trials predictive of a rare disease. Red points represent perfect predictors, purple points represent imperfect predictors (faces), and blue points represent non-present features.

Figure 5. Associations between multivoxel pattern similarity to common (left) and rare

(right) features during the learning phase and individual differences in base-rate neglect.

The y-axis represents the proportion of rare responses made by each subject on

ambiguous test trials. '**' = $p < 0.01$.

Model-based Univariate Results

By revealing a link between activation of common feature patterns and the IBRE,

our multivoxel results suggest that dissimilarity-based evidence contributes to

choice behavior in the present task. However, it remains an open question

whether such dissimilarity processes involve distinct neural or cognitive

mechanisms beyond those thought to underlie basic similarity processes.

To test whether similarity- and dissimilarity-based evidence rely on

different brain regions, we modeled univariate voxel-wise activation using trial-

by-trial estimates of similarity- and dissimilarity-based evidence derived from the

dissGCM (Figure 6). We found activation in the MTL and vmPFC that was

positively correlated with similarity-based evidence, whereas the dlPFC and

posterior parietal cortex were negatively correlated with similarity-based

evidence. These results are consistent with findings from other model-based

fMRI studies suggesting that the MTL is involved in similarity-based retrieval

(Davis, Love & Preston, 2012a, 2012b), and that the vmPFC and dlPFC track

higher-confidence or higher-uncertainty categorization decisions, respectively

(DeGutis & D'Esposito, 2007; Seger et al., 2015; Davis, Goldwater & Giron,

2017; O'Bryan et al., 2018). Contrastingly, dissimilarity-based evidence was

positively correlated with activation in the left rlPFC, consistent with our

hypothesis that this type of evidence might encourage more symbolic processes

believed to underlie the rlPFC's contribution to category learning (Davis,

Goldwater & Giron, 2017; Paniukov & Davis, 2018). No clusters were

significantly negatively associated with dissimilarity-based evidence.

Figure 6. Results from the model-based univariate analysis. A) Depicts activation that tracks similarity-based contributions to choice. Red depicts activation positively correlated with similarity-based contributions whereas blue depicts negatively correlated activation. B) Depicts brain regions that are positively correlated with dissimilarity-based contributions to choice.

334   **Table 2.** Activated clusters and peaks for the fMRI results in Figure 6.

Contrast	Regions	Peak t-value	Peak MNI Coordinates (x,y,z)	Number of voxels	Cluster p
Similarity > 0					
	Rostral and ventral medial prefrontal cortex	7.76	0, 54, -2	2268	p < .001
	Middle temporal gyrus	5.74	64, -6, -14	1050	p = .016
	Precentral gyrus	7.65	42, -16, 62	1031	p < .001
	Precentral gyrus	4.81	0, -30, 58	463	p = .008
	Middle temporal gyrus	4.98	-62, -2, -16	322	p = .016
	Parietal operculum cortex	5.74	-34, -30, 18	282	p = .027
	Hippocampus	5.25	-22, -18, -16	271	p = .019
	Lateral occipital cortex (inferior)	4.68	50, -72, 12	157	p = .039
Similarity < 0					
	Superior Parietal & Lateral occipital cortex (superior)	8.43	-44, -46, 58	5123	p < .001
	Middle frontal gyrus	7.01	-52, 12, 36	2491	p < .001
	Dorsal medial PFC	9.00	-2, 18, 46	917	p < .001
	Cerebellum	6.11	28, -64, -28	769	p = .002
	Middle frontal gyrus	6.23	32, 2, 62	730	p = .002
	Middle frontal gyrus	5.89	44, 36, 30	391	p = .009
	Inferior temporal gyrus	6.09	-54, -52, -12	375	p = .009
	Inferior temporal gyrus	6.53	60, -52, -10	271	p = .016
	Cerebellum	6.08	-28, -60, -32	186	p = .031
	Thalamus	4.88	-10, -18, 10	175	p = .038
Dissimilarity > 0					
	Occipital cortex	7.55	12, -78, 12	1372	p < .001
	Fusiform and Lateral occipital cortex (inferior)	6.82	42, -60, -18	865	p = .002
	Fusiform and Lateral occipital cortex (inferior)	5.97	-36, -52, -18	575	p = .003
	Middle frontal gyrus	5.00	54, 16, 34	255	p = .020
	Frontal Pole (rostrolateral PFC)	5.93	-42, 52, -6	130	p = .047

Discussion

The present study employed model-based fMRI to test how similarity and

dissimilarity contribute to the inverse base rate effect (IBRE) and how these

types of evidence relate to neural mechanisms that support category learning.

The dominant theory behind the IBRE suggests that it arises from attentional

processes that make ambiguous items containing features of rare and common

categories seem more similar to members of the rare category. Here we find

support for the hypothesis that dissimilarity-based evidence also contributes to

the IBRE: people may categorize the ambiguous stimuli as members of the rare

category not only because of their similarity to the rare category, but also

because of their dissimilarity to members of the common category.

The dissGCM, an extension of the GCM that allows for the use of

dissimilarity-based evidence in categorization behavior, predicted two novel

observations in the neuroimaging data. First, as predicted by the dissGCM's

relative contribution of similarity- and dissimilarity-based evidence during the

ambiguous trials, multivoxel analysis suggested stronger activation of patterns

associated with features of the common category when participants classified

ambiguous stimuli as rare. Second, model-based univariate analysis revealed

that measures of similarity- and dissimilarity-based evidence had unique neural

topographies. Similarity-based evidence was positively correlated with regions of

the hippocampus and vmPFC and negatively correlated with dlPFC. Dissimilarity-

based evidence was positively correlated with the left rlPFC.

The present results raise several important questions about the cognitive

and neural mechanisms underlying people's use of base rate information.

Previous theories arguing for dissimilarity-like processes as explanations of IBRE

have argued that they arise from mechanisms rooted in higher-level propositional

logic that fundamentally differ from the similarity-based mechanisms posited by

dominant theories (Juslin, Wennerholm & Winman, 2001). As illustrated by the

dissGCM, such dissimilarity-based processes can be viewed as simple

extensions of similarity-based processing and need not depend on the existence

of a functionally separate categorization system. At the same time, our

neuroimaging results suggest dissimilarity, but not similarity-based evidence may

arise from processing in rlPFC regions that are known to be involved with higher-

level reasoning and problem solving (Christoff et al., 2001; Bunge et al., 2005,

2009). One possibility for reconciling these theories is that the dissimilarity-based

evidence involves more abstract or symbolic feature processing than pure

similarity processes, and this additional processing taps rlPFC regions. This is

consistent with our recent model-based fMRI results which demonstrate that

rlPFC tracks measures of relational encoding in category learning, but otherwise

this type of category learning may rely on the same basic similarity-based

mechanisms as simpler feature-based learning (Davis, Goldwater, & Giron,

2017).

By establishing that the rlPFC is engaged when participants incorporate

dissimilarity-based evidence into categorization decisions, our research adds to a

growing literature aiming to pinpoint a domain-general computational role for this

region. A common thread among tasks shown to engage the rlPFC is that they

tend to involve combining across disparate representations to form the basis for

a decision – whether those representations are comprised of confidence

estimates and subjective value (De Martino et al., 2013), visual features and their

relations (Bunge et al., 2004, 2009; Davis, Goldwater, & Giron, 2017), or

expected rewards and their relative uncertainties (Boorman et al., 2009; Badre et

al., 2012). Likewise, in the case of the current study, the evidence that an

ambiguous stimulus is similar to a given category must be combined with the

evidence that the stimulus is dissimilar to the other possible categories. Although

the dissGCM instantiates dissimilarity as a simple transformation of similarity, the

involvement of rlPFC when participants place more reliance on dissimilarity-

based evidence may be attributable to increasing demands for integrating

evidence across several abstract representations. A decision based on pure

similarity-based evidence would require no such integration. This hypothesis

accords with recent findings implicating the rlPFC in evaluative processes for

categorization tasks that require candidate rules to be weighed over the course

of several trials, relative to matching tasks where a rule can be known with

certainty following a single correct trial (Paniukov & Davis, 2018).

One question that has arisen repeatedly in the literature on the IBRE is

whether it reflects an inherent irrationality in decision making. When viewed

through the lens of basic similarity-based attentional processes (e.g., Medin &

Edelson, 1988; Kruschke, 1996, 2001), the IBRE appears to arise from very

simple learning mechanisms that are not particularly tied to higher-level

rationality, and rare choices seem to indicate a lack of knowledge of the base

rates. Indeed, in a separate model fit, we attempted to fit the standard similarity-

based GCM to the key pattern on the ambiguous trials. However, the standard

GCM was only able to predict a greater proportion of rare choices if accurate

knowledge of the exemplar base-rates was eliminated (all values of $t_j = 1$ or fit as

free parameters). In contrast, accurate knowledge of the category base rates

directly contributes to the greater dissimilarity-based evidence against the

common category. Thus from the dissGCM perspective, participants are perfectly

knowledgeable about the base rates in the present task, but they use this

knowledge in a way not anticipated by pure similarity-based models. However,

whether this use of dissimilarity-based evidence constitutes irrationality is a

deeper question that cannot be answered based purely on the present results.

416   The IBRE exemplifies a case in cognitive neuroscience where

independent models that predict essentially the same behavioral patterns make

very different assumptions about the cognitive processes, and accordingly, brain

states, involved in producing the behavior. Our findings from the test phase

represent a critical step forward in an emerging area of research using

multivariate fMRI to reveal that qualitatively distinct brain states may reflect the

use of multiple response strategies in the face of identical stimuli (e.g., Mack et

al., 2013). Consistent with past research using MVPA to decode learned

selective attention (Mack et al., 2013, 2016; Leong et al., 2017; O'Bryan et al.,

2018), multivoxel patterns associated with predictive features were more strongly

activated than imperfectly predictive features during the learning phase. Using

the same approach to decode which information participants were focusing on

during ambiguous test trials, we found stronger activation of patterns associated

with common compared to rare stimulus features, but importantly, this pattern

only emerged in cases where participants chose the rare category. Although

these results are consistent with a dissimilarity-based process where activating

knowledge of the common feature provides contrastive evidence against the

well-established common category, understanding the precise cognitive

mechanisms that contribute to these response-dependent activation patterns

remains a direction for future research. One possibility is that common choices

stem from habitual response patterns that involve feature matching and require

little active deliberation, and hence less activation of featural information in the

associated multivoxel activation patterns, whereas more actively weighing the

evidence for each category engages a "strategic guessing" process that involves

ruling out the most unlikely option (Juslin, Wennerholm, & Winman, 2001).

Interestingly, while our findings argue against the prediction from

similarity-based models that the IBRE arises because rare features become

more similar to their associated category, the observed parameters from the

model fits are consistent with a key part of similarity theory – that there is greater

selective attention allocated to the rare feature dimension. Indeed, the rare

feature dimensions outweighed the common features for both sets of categories

in our data. However, these larger attention weights did not seem to drive greater

neural similarity to the rare feature dimension in our multivoxel results.

Accordingly, it is possible that our multivoxel results are not driven directly by

simple feature-based attention, but instead indicate some combination of

attention and memory-based retrieval of the category exemplars. This hypothesis

coincides with findings from the memory literature, which have found that

memory-based retrieval of non-present, associated stimuli can be detectable in

activation patterns (e.g., Zeithamova, Dominick & Preston, 2012; for review, see

Rissman & Wagner, 2012). Future studies may wish to combine multivoxel

pattern analysis with eye-tracking (e.g., Leong et al., 2017) to better understand

the unique contributions that attention and memory make to the present results.

458   In conclusion, using model-based fMRI analysis, we found evidence that

extreme cases of base rate neglect such as the IBRE may arise from a

combination of similarity- and dissimilarity-based processes. Accordingly,

measures of neural activation suggest that people may be more strongly relying

on evidence about how dissimilar an item is to common categories when faced

with ambiguous stimuli. Further, dissimilarity processes have a unique cortical

topography that includes the rostrolateral PFC, a region believed to be involved

with more symbolic feature processing.

467   **Materials and Methods**

Twenty-four healthy right-handed volunteers (age range 18 – 58; 13 women)

participated in the study for $35. All protocols were approved by the Texas Tech

University IRB. Two participants were excluded, one for falling asleep and the

other for excessive head motion.

Behavioral Protocol

The study consisted of three phases, localizer, learning, and test. The localizer

phase consisted of two scanning runs in which participants classified images

based on whether they contained a face, an object, or a scene. Each image was

presented for 2.5 s during which participants were asked to respond "Scene (1),

Face (2), or Object (3)?" Each trial was separated with random fixation drawn

from a truncated exponential distribution with mean = 3 s. Over the duration of

the localizer phase, subjects categorized 38 examples of each stimulus type. The

face, object, and scene images used were black-and-white squares presented on

a white background with black text. The stimuli used during the localizer runs

were presented in a random order, and did not include any of the images used

for the experimental task.

In the learning phase, participants learned a classic IBRE category

structure based on Medin and Edelson (1988; See Figure 1). The features used

for the stimuli included examples of faces, objects, and scenes not shown in the

localizer phase. Participants were given an epidemiological cover story asking

them to predict whether hypothetical patients would contract a disease based on

the people they have been in contact with (faces), the objects they have used

(objects), and the places they have been (scenes). On each trial of the learning

phase, participants would see a stimulus for 3 s and were asked to answer

"Disease 1, 2, 3, or 4?" This was followed by random fixation, feedback (1.75 s)

in which they were told whether they were right or wrong and the correct answer,

and additional fixation. The same distribution was used to generate fixations as in

the localizer phase. Faces were always assigned to the imperfectly predictive

feature dimensions, whereas objects and scenes were perfectly predictive and

associated with only one disease (Figure 1). To ensure that no visual stimulus

category differed in overall frequency, one common disease always was

associated with objects and the other scenes, and likewise for rare diseases.

Participants were randomly assigned to one of two conditions to balance which

images were presented together during learning and test, and disease labels

were randomized across participants. Within-pair stimulus position (left or right)

was randomized on each trial, and the presentation order of feature pairs was

randomized within each block for every participant. The learning phase was

spread over three scanning runs, and four blocks of the stimulus set were

presented per run, resulting in a total of12 blocks and 96 trials for the learning

phase. The progression of a learning trial is depicted in the bottom panel of

Figure 1.

During the test phase, participants completed trials with both new and old

exemplars and classified them as "Disease 1, 2, 3, or 4?", but no longer received

feedback. New items included all possible single and two-feature combinations of

the perfectly predictive features (see Table 1, Results). Trials were 3 s and

separated by random fixation as described above. Like the learning phase, the

test phase occurred over three consecutive scanning runs. Presentation order of

the test items was randomized for each of the three runs, with participants rating

two test sets per run, resulting in a total of 156 test trials.

Image Acquisition

Imaging data were acquired on a 3.0 T Siemens Skyra MRI scanner at the Texas

Tech Neuroimaging Institute. Structural images were acquired in the sagittal

plane using MPRAGE whole-brain anatomical scans (TR = 1.9 s; TE = 2.44 ms;

θ = 9°; FOV = 250 x 250 mm; matrix = 256 x 256 mm; slice thickness = 1.0 mm,

slices = 192). Functional images were acquired using a single-shot T2*-weighted

gradient echo EPI sequence (TR = 2.5 s; TE = 25 ms; θ = 75°; FOV= 192 x 192

mm; matrix = 64 x 64; slice thickness = 3 mm).

fMRI Analysis and Preprocessing

Functional data were preprocessed and analyzed using FSL

(www.fmrib.ox.ac.uk/fsl). Anatomical images were preprocessed using

Freesurfer (autorecon1). Functional images were skull stripped, motion

corrected, prewhitened, and high-pass filtered (cutoff: 60 s). For the model-

based univariate analysis, functional images were spatially smoothed using a 6

mm FWHM Gaussian kernel. No smoothing was performed on functional data

used for the multivoxel analysis. First-level statistical maps were registered to

the Montreal Neurological Institute (MNI)-152 template using 6-DOF boundary-

based registration to align the functional image to the Freesurfer-processed

high-resolution anatomical image, and 12-DOF affine registration to the MNI-152

brain.

540   The model-based univariate analysis employed a standard three-level

mixed effects model carried out in FSL's FEAT program. The first-level model

included an EV for stimulus presentation and two model-based parametric

modulators: Similarity- and Dissimilarity-based evidence, computed from the

dissGCM. Both parametric modulators were centered and scaled (z-scored)

within run. Calculation of these regressors is described in the Model section.

Additional explanatory variables (EVs) of no interest included motion parameters,

their temporal derivatives, EVs to censor volumes exceeding a framewise

displacement of 0.9mm (Siegel et al., 2014), and an EV to account for trials in

which participants failed to make a behavioral response. Final statistical maps

were corrected for multiple comparisons using a non-parametric cluster-mass-

based correction with a cluster-forming threshold of t (21) = 3.52 (p < .001, one-

tailed).

RSA was conducted using the PyMVPA toolbox (Hanke et al., 2009) and

custom Python routines. In this analysis, we measured how much participants

were activating scene, object, and face information on individual test phase trials

by calculating mean correlation distance (1 – Pearson's r) between activation

patterns on each test trial and those elicited for each visual category during the

localizer phase. For interpretative ease, the distances were converted to

similarities using exp(- distance), and then standardized (z-scored) within

participants. Activation patterns were estimated for each trial using a Least

Squares All procedure (Mumford et al., 2012), and anatomically restricted to two

ventral temporal ROIs that were maximally responsive to scene and object

information in the localizer data. Specifically, pattern estimates were spatially

localized in visual stimulus category-specific ROIs by creating 6-mm spheres

around subjects' peak activation within anatomically defined regions in the

Harvard-Oxford Atlas associated with category selectivity (objects: left inferior

posterior temporal gyrus; scenes: bilateral parahippocampal gyrus; Ishai et al.,

1999; Lewis-Peacock & Postle, 2008; Lewis-Peacock et al., 2012; Grill-Spector &

Weiner, 2014). The last trial of each run was automatically discarded from the

multivoxel analysis to ensure stable estimation of the activation patterns for all

trials. Additional explanatory variables (EVs) of no interest included motion

parameters, their temporal derivatives, and EVs to censor volumes exceeding a

framewise displacement of 0.9mm. Source data and scripts used to create all

figures and tables (e.g., R code, PyMVPA scripts, statistical maps for the model-

based fMRI analysis) are freely available online at https://osf.io/atbz7/.

Acknowledgements

This work was supported by start-up funds to TD from Texas Tech University.

The authors declare no conflicts of interest.

References

Badre, D., & D'Esposito, M. (2007). Functional magnetic resonance imaging

evidence for a hierarchical organization of the prefrontal cortex. *Journal of*

Cognitive Neuroscience, *19*, 2082–2099.

Badre, D., & D'Esposito, M. (2009). Is the rostro-caudal axis of the frontal lobe

hierarchical? *Nature Reviews Neuroscience*, *10*, 659–669.

Badre, D., Doll, B.B., Long, N.M., & Frank, M.J. (2012). Rostrolateral prefrontal

588   cortex and individual differences in uncertainty-driven exploration. *Neuron*,

589   *73*, 595–607.

590   Boorman, E.D., Behrens, T.E.J., Woolrich, M.W., & Rushworth, M.F.S. (2009).

591   How green is the grass on the other side? Frontopolar cortex and the

592   evidence in favor of alternative courses of action. *Neuron*, *62*, 733–743.

593   Bravata DM (2000). Making medical decisions under uncertainty. *Seminars in*

594   *Medical Practice*, *3*, 6-13.

595   Bunge, S.A., Wendelken, C., Badre, D., & Wagner, A.D. (2005). Analogical

596   reasoning and prefrontal cortex: evidence for separable retrieval and

597   integration mechanisms. *Cerebral Cortex*, *15*, 239–249.

598   Bunge, S.A., Helskog, E.H., & Wendelken, C. (2009). Left, but not right,

599   rostrolateral prefrontal cortex meets a stringent test of the relational

600   integration hypothesis. *NeuroImage*, *46*, 338–342.

601   Casscells, W., Schoenberger, A., & Graboys, T. B. (1978). Interpretation by

602   physicians of clinical laboratory results. *New England Journal of Medicine,*

603   *299*, 999-1001.

604   Christoff, K., Prabhakaran, V., Dorfman, J., Zhao, Z., Kroger, J. K., Holyoak, K.

605   J., & Gabrieli, J. D. (2001). Rostrolateral prefrontal cortex involvement in

606   relational integration during reasoning. *NeuroImage, 14*, 1136-1149.

607   Davis, T., Love, B. C., & Preston, A.R. (2012a). Learning the exception to the

608   rule: Model-based fMRI reveals specialized representations for surprising

609   category members. *Cerebral Cortex, 22,* 260-273.

Davis, T., Love, B. C., & Preston, A.R. (2012b). Striatal and hippocampal

entropy and recognition signals in category learning: simultaneous

processes revealed by model-based fMRI. *Journal of Experimental*

Psychology: Learning, Memory, and Cognition, *38*, 821-839

Davis, T., & Poldrack, R. A. (2013). Quantifying the internal structure of

categories using a neural typicality measure. *Cerebral Cortex, 24,* 1720-

1737.

Davis, T., Goldwater, M.B., Giron, J. (2017). From concrete examples to abstract

relations: The rostrolateral prefrontal cortex integrates novel examples into

relational categories. *Cerebral Cortex, 27*, 2652-2670.

DeGutis, J., D'Esposito, M. (2007). Distinct mechanisms in visual category

learning. *Cognitive Affective and Behavioral Neuroscience, 7*, 251-259.

De Martino, B., Fleming, S.M., Garrett, N., & Dolan, R., (2013). Confidence in

value-based choice. *Nature Neuroscience*, *16*, 105–110.

Grill-Spector, K., & Weiner, K.S. (2014). The functional architechture of ventral

temporal cortex and its role in categorization. *Nature Reviews*

Neuroscience, *15*, 536-548.

Hanke, M., Halchenko, Y.O., Sederberg, P.B., Hanson, S.J., Haxby, J.V., &

Pollmann, S. (2009). PyMVPA: A Python toolbox for multivariate pattern

analysis of fMRI data. *Neuroinformatics*, *7*, 37-53.

Haxby, J.V., Gobbini, M.I., Furey, M.L., Ishai, A., Schouten, J.L., & Pietrini, P.

(2001). Distributed and overlapping representations of faces and objects

in ventral temporal cortex. *Science* 293: 2425–2430.

Haxby, J.V., Connolly, A.C., & Guntupalli, J.S. (2014). Decoding neural

representational spaces using multivariate pattern analysis. *Annual*

Review of Neuroscience, *37*, 435-456.

Ishai, A., Ungerleider, L.G., Martin, A., Schouten, J.L., & Haxby, J.V. (1999).

Distributed representation of objects in the human ventral visual pathway.

Proceedings of the National Academy of Sciences, *96*, 9379.

Juslin, P., Wennerholm, P., & Winman, A. (2001). High-level reasoning and

base-rate use: Do we need cue- competition to explain the inverse base-

rate effect? *Journal of Experimental Psychology: Learning, Memory, and*

Cognition, 27, 849-871.

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational similarity

analysis— connecting the branches of systems neuroscience. *Frontiers in*

Systems Neuroscience, *2*, 4.

Kruschke, J.K. (1996). Base rates in category learning. *Journal of Experimental*

Psychology: Learning, Memory, and Cognition, 22, 3-26.

Kruschke, J.K. (2001). Toward a unified model of attention in associative

learning. *Journal of Mathematical Psychology, 45*, 812-863.

Leong, Y.C., Radelescu, A., Daniel, R., & Niv, Y. (2017). Dynamic interaction

between reinforcement learning and attention in multidimensional

environments. *Neuron*, *93*, 451-463.

Lewis-Peacock, J.A., & Postle, B.R. (2008). Temporary activation of long-term

memory supports working memory. *The Journal of Neuroscience, 28*,

8765–8771.

Lewis-Peacock, J.A., Drysdale, A.T., Oberauer, K., & Postle, B.R. (2012). Neural

evidence for a distinction between short-term memory and the focus of

attention. *Journal of Cognitive Neuroscience*, *24*, 61-79.

Mack, M.L., Preston, A.R., & Love, B.C. (2013). Decoding the brain's algorithm

for categorization from its neural implementation. *Current Biology*, *23*, 1-5.

Mack, M. L., Love, B. C., & Preston, A. R. (2016). Dynamic updating of

hippocampal object representations reflects new conceptual knowledge.

Proceedings of the National Academy of Sciences, 113, 13203-13208.

Medin, D. L., & Edelson, S. M. (1988). Problem structure and the use of base-

rate information from experience. *Journal of Experimental Psychology:*

General, 117, 68-85.

Mumford, J. A., Turner, B. O., Ashby, F. G., & Poldrack, R. A. (2012).

Deconvolving BOLD activation in event-related designs for multivoxel

pattern classification analyses. *NeuroImage, 59,* 2636-2643.

Nosofsky, R. M. (1986). Attention, similarity, and the identification–categorization

relationship. *Journal of Experimental Psychology: General, 115,* 39-57.

O'Bryan, S.R., Walden, E., Serra, M.J., & Davis, T. (2018). Rule activation and

ventromedial prefrontal engagement support accurate stopping in self-

paced learning. *NeuroImage*, *172*, 415-426.

Paniukov, D., & Davis, T. (2018). The evaluative role of rostrolateral prefrontal

cortex in rule-based category learning. *NeuroImage, 166,* 19-31.

Rissman, J., & Wagner, A. D. (2012). Distributed representations in memory:

insights from functional brain imaging. *Annual Review of Psychology, 63,*

101-128.

Seger, C.A., Braunlich, K., Wehe, H.S., & Liu, Z. (2015). Generalization in

category learning: The roles of representational and decisional

uncertainty. *The Journal of Neuroscience*, *35*, 8802-8812.

Siegel, J.S., Power, J.D., Dubis, J.W., Vogel, A.C., Church, J.A., Schlaggar, B.L.,

& Petersen, S.E. (2014). Statistical improvements in functional magnetic

resonance imaging analyses produced by censoring high-motion data

points. *Human Brain Mapping*, *35*, 1981–1996.

Stewart, N., & Morin, C. (2007). Dissimilarity is used as evidence of category

membership in multidimensional perceptual categorization: A test of the

similarity– dissimilarity generalized context model. *Quarterly Journal of*

Experimental Psychology, 60, 1337-1346.

Tversky, A., & Kahneman, D. (1974). Judgment under uncertainty: Heuristics and

biases. *Science, 185,* 1124- 1131.

Winman, A., Wennerholm, P., Juslin, P., & Shanks, D.R. (2005). Evidence for

rule-based processes in the inverse base-rate effect. *Quarterly Journal of*

Experimental Psychology, *58A,* 789-815.

Zeithamova, D., Dominick, A.L., & Preston, A.R. (2012). Hippocampal and

ventral medial prefrontal activation during retrieval-mediated learning

supports novel inference. *Neuron, 75,* 168-179.

699