Title: Policies or Knowledge: Priors differ between perceptual and sensorimotor

tasks

Abbreviated title: Perceptual and sensorimotor priors are different

Claire Chambers

Hugo Fernandes

Konrad Paul Kording

Department of Bioengineering and Department of Neuroscience, University of

Pennsylvania, Philadelphia, 19104, USA

Corresponding author: Claire Chambers, clairenc@seas.upenn.edu

Contributions

HF and KPK designed experiments. CC and HF collected data. CC analyzed the data,

with contributions from HF. CC and KPK wrote the manuscript, with contributions

from HF. KPK initiated the research.

ABSTRACT

If the brain abstractly represents probability distributions as knowledge, then the modality of a decision, e.g. movement vs perception, should not matter. If on the other hand, learned representations are policies, they may be specific to the task where learning takes place. Here, we test this by asking if a learned spatial prior generalizes from a sensorimotor estimation task to a two-alternative-forced choice (2-Afc) perceptual comparison task. A model and simulation-based analysis revealed that while participants learn the experimentally-imposed prior distribution in the sensorimotor estimation task, measured priors are consistently broader than expected in the 2-Afc task. That the prior does not fully generalize suggests that sensorimotor priors strongly resemble policies. In disagreement with standard Bayesian thought, the modality of the decision has a strong influence on the implied prior distribution.

NEW AND NOTEWORTHY

We do not know if the brain represents abstract and generalizable knowledge or task-specific policies that map internal states to actions. We find that learning in a sensorimotor task does not generalize strongly to a perceptual task, suggesting that humans learned policies and did not truly acquire knowledge. Priors differ across tasks, thus casting doubt on the central tenet of may Bayesian models, that the brain's representation of the world is built on generalizable knowledge.

KEYWORDS

Generalization, Bayesian, Sensorimotor, Knowledge, Policies.

INTRODUCTION

The acquisition of knowledge is thought to be at the core of the brain's function (Tenenbaum et al. 2006, 2011; Battaglia et al. 2013). A behavioral signature of knowledge-use is strong generalization across situations. For instance, when a child learns a new word they can use it in many new situations, not just the sentence where the word was learned (Xu and Tenenbaum 2007; Perfors et al. 2011). However, the framing of learned representations as generalizable knowledge may not apply to all of the brain's functions equally. For example, generalization from movements of one arm to those of the other is not always complete (Criscimagna-hemminger et al. 2003; Shadmehr 2004). Indeed, the reinforcement learning literature (Sutton and Barto

1998) defines an alternative way of learning. Within this framework, learning is

framed as policy-acquisition, i.e. mappings from states to actions (Daw and Doya

2006; Haith and Krakauer 2013). This definition implies that learning of policies is

specific to the action for which it was learned and thus suggests limited generalization

across tasks. We want to know if humans are policy animals, knowledge carriers, or

something in between.

In sensorimotor estimation tasks, humans weigh prior knowledge with sensory

information in a near-optimal way (Körding and Wolpert 2004; Tassinari et al. 2006;

Berniker et al. 2010; Vilares et al. 2012) and generalize learned prior statistics to new

conditions (Fernandes et al. 2014). Thus, there is evidence for learning of

sensorimotor priors. However, little is known about whether sensorimotor learning

generalizes when the read-out modality of the decision changes. Therefore, we do not

know if sensorimotor priors should be described as knowledge or policies. This is

important because it has consequences for how neural representations should be

conceptualized.

Here, we investigate if priors are the same across modalities by examining

whether priors generalize across two simple tasks. The experiment was designed so

that tasks were equivalent in terms of how probabilistic information should be

combined to achieve optimal performance. Participants learned a spatial prior in a

sensorimotor estimation task, and we asked if they transferred the learned prior to a

two-alternative-forced-choice (2-Afc) task, where participants made a binary decision

about object location. We inferred the standard deviation of the learned prior and

found that the learned sensorimotor prior does not generalize fully to the 2-Afc task.

The prior standard deviation measured from 2-Afc decisions was higher than the

standard deviation measured from sensorimotor estimates. This shows that a learned

prior does not generalize fully across sensorimotor and decisional modalities and

suggests that sensorimotor priors are represented as policies.

METHODS

The results presented here use data from previous work (Acuna et al. 2015),

augmented with newly collected data on the same paradigm. A complete description

of the methods is given in previous work and will be described here. Participants were

six males and two females (age: M = 29.87, SD = 7.27). Participants gave written

informed consent before taking part. Ethical approval was provided by the NU IRB
#20142500001072 (Northwestern University, USA).

We required tasks that were equivalent in how probabilistic information
should be combined across sources and that allowed us to infer priors used by
participants. We used a "coin-catching" task (Berniker et al. 2010; Vilares et al. 2012;
Acuna et al. 2015), where on each trial, participants guessed the location of a hidden
stimulus ("coin") on the screen based on an uncertain visual cue ("splash") and a prior
learned through feedback on stimulus location. Varying the prior and likelihood width
allowed us to assess whether participants weighed prior and likelihood information
according to their relative uncertainties during sensorimotor estimation and decision
making.

Before starting the experiment, participants were presented with the
instructions that on each trial, someone was throwing two coins, one after another,
into a pond represented by the screen; and that their aim was to guess where the coin
stimuli landed. They were told that there was no relationship between where the two
coins landed (Fig. 1). On each trial, they were presented with "splash" stimuli and
were told that it was caused by a hidden coin stimulus. On estimation trials,
participants provided an estimate of the second stimulus's location on the horizontal
axis by placing a vertical bar where they thought that the stimulus landed. On 2-Afc
trials, participants compared the locations of the inferred stimulus locations and
indicated which stimulus was further to the right. Participants were paid based on
their performance on the estimation task, as quantified using the distance between
their estimates and the true stimulus location.

Figure 1. Experimental protocol. Participants were shown two splashes (likelihoods) in
succession, created by hidden coins (stimuli) falling into a pond (screen), which were
interleaved with white noise masks. Participants were then presented with one of two possible
tasks. In the estimation task, participants were prompted to place a net where the second
hidden stimulus fell. In the 2-Afc task, participants reported which hidden stimulus landed
farther to the right.
133

Eight participants performed the experiment, including the seven participants

from an existing data set (Acuna et al. 2015) and one additional participant to increase

the power of group statistics (statistical results were the same with and without this

participant). The experiment lasted 10,000 trials over 5 days. On each day, they were

seated in front of a computer monitor (52 cm wide, 32.5 cm high) in a quiet room.

Stimuli were generated by sampling visual stimuli from a Gaussian prior distribution

defined over spatial location, with a mean at the center of the screen and standard

deviation of .04 or .2 in units of screen width. The stimulus was hidden from view.

Instead, they were presented with a visual cue with experimentally-controlled

uncertainty (splash stimulus). The splash consisted of four dots sampled from a

Gaussian likelihood distribution centered on the stimulus location. The likelihood

distribution could have a standard deviation of .025 or .1 in units of the screen. In all

trials, two consecutive splashes were displayed for .025 s, each followed by a visual

mask for .5 s. The standard deviation of the likelihood was either the same across

presentations within a trial (both at .025 or both at .1) or varied within trial (.025 and

.1) and presented in randomized order. We refer to the broader likelihood as the

reference and the narrower likelihood as the probe.

On each trial, participants performed one of two tasks, as defined by the

question displayed at the end of the trial. On estimation trials, participants were asked

"Where was the coin located?" and they indicated where they thought the second coin

stimulus was using a vertical bar ("net"), which was 2% screen width and extended

from the top to the bottom of the screen. On 2-Afc trials, participants were asked

"Which coin was further to the right?" and using a key-press they indicated if they

thought the first or second coin stimulus was further to the right. Trials in both tasks

were identical until the end of the trial, until the question was displayed on screen. At

the end of estimation trials only, feedback was provided on the exact location of the

stimulus, but not on 2-Afc trials, allowing us to ask if the prior learned in the

estimation task generalizes to the 2-Afc task.

Experimental Design

There were four conditions in the estimation task: Narrow Prior, Narrow

Likelihood; Narrow Prior, Wide Likelihood; Wide Prior, Narrow Likelihood; Wide

Prior, Wide Likelihood. In the 2-Afc trials, conditions were defined by the width of

the prior (Narrow Prior and Wide Prior) and whether likelihoods were equal within

trial, Equal Likelihoods (both narrow or both wide) or Unequal Likelihoods (one

narrow and one wide). We only used Unequal Likelihood trials in the present study.

Therefore in our analysis, there were two conditions for the 2-Afc trials: Narrow Prior

and Wide Prior.

On each day of the experiment participants performed two 1,000-trial blocks.

The prior over stimulus location switched from block to block (e.g., from wide to

narrow on one day, from narrow to wide on the subsequent day, and so on). Each

block contained 500 estimation trials and 500 2-Afc trials in a random order all

generated from the same prior. In order to aid with learning the prior, estimation trials

made up the first half of each block (375 estimation trials and 125 2-Afc trials), and 2-

Afc trials made up the second half of each block (125 estimation trials and 375 2-Afc

trials).

Data Analysis and simulations

We asked whether the use of prior information differed between

psychophysical tasks. To answer this question, we examined whether the prior

parameters fit to one of the two tasks could predict behavior well in the other task. As

a baseline comparison, we examined whether the prior standard deviation fit to one

half of the data predicted behavior on the other half of the data, within task. To

examine how each participant's prior related to the veridical prior used in the

experiment, we estimated the prior parameters from each task. To ensure that the data

analysis produced unbiased results, we performed the same analysis on data simulated

from an ideal Bayesian model.

Quantifying the Estimation slope and PSE slope from behavioral data

In order to examine the use of probabilistic information during the estimation

task, we examined how much participants relied on likelihood or prior information. In

the estimation task, participants gave a continuous estimate of stimulus location. We

wanted to quantify how much participants relied on the learned stimulus location

(prior) or visual information (likelihood). To do so, we computed the relationship

between the likelihood's center and participants' estimates, which we termed the

Estimation slope. If someone were to rely only on likelihood information to judge

stimulus location, on average, estimates should correspond to the center of the

likelihood (*Estimation slope* =1). If someone were to ignore the likelihood entirely

and rely only on their prior to judge stimulus location, there should be no relationship

between the likelihood's center and estimates (*Estimation slope* = 0). The Bayesian

optimal strategy is to weigh the prior and likelihood according to their relative

precision, as in Equation 1.

$$\text{Estimation slope} = \sigma_s^2/(\sigma_s^2 + \sigma_l^2/n) \quad (1)$$

In the 2-Afc task, participants were given probabilistic information on

stimulus location exactly as in the estimation task. On each trial, they compared the

locations of two stimuli with different uncertainties, a probe stimulus with Narrow

Likelihood and a reference stimulus with Wide Likelihood. Uncertainty should

influence the judgment of stimulus location in the same way as in the estimation task.

A Bayesian observer judges the more uncertain stimulus to be shifted further to the

prior mean than the more certain stimulus. This, in turn, influences decisions about

relative stimulus location. Therefore, use of the prior can be inferred from

participants' 2-Afc data.

Consider the psychometric function that describes the comparison of stimuli

with unequal widths. The psychometric function is the probability that the probe

stimulus is reported to the right, *P(Decision=1)*, as a function of difference between

the likelihood stimuli (*Discrepancy*), and the *Reference location*. The participant's

prior influences the *Discrepancy* at which the stimuli are perceived as equal (point of

subjective equality, *PSE*). For a Bayesian observer, the *PSE* arises when the reference

is more distant from the prior's center than the probe. The *PSE* further deviates from

zero as the distance between the prior and the reference increases. Importantly, the

slope of this linear relationship, the *PSE slope*, is related to the width of the

participant's prior – a *PSE slope* of 0 shows that participants relied only on visual

information from the likelihood; and the more negative the *PSE slope*, the narrower

the participant's prior. The optimal *PSE slope* is given by Equation 2.

$$\text{PSE slope} = (\sigma_{l1}^2/n - \sigma_{l2}^2/n)/(\sigma_{l2}^2/n + \sigma_s^2) \quad (2)$$

We fit psychometric functions (the cumulative Gaussian function) to each

participant's decision data. The *PSE slope* (m_{PSE}) estimated from this function

provides an indicator of the variance of the participant's prior. We model the

probability of a decision as:

$$230 \qquad P(\text{Decision} = 1) = \left(\frac{1}{2} \left[1 + \text{erf} \left(\frac{\delta - s_{l2} \times m_{PSE}}{\sqrt{2}\,\sigma} \right) \right] \right) \quad (3)$$

where δ is the discrepancy between stimuli, s_{l2} is the location of the reference

stimulus with broader likelihood, σ describes the deviation of the function (Acuna et

al. 2015). We find the values of m_{PSE} and σ using a maximum-likelihood estimation

algorithm.

Analysis of priors during Estimation and 2-Afc decision making

If priors are the same, then priors used in one task should predict behavior in

the other task well. A cross-validation error computed across tasks should not exceed

the error computed within tasks. To test this, we performed 2-fold cross-validation by

estimating priors from one task and computing the Mean Squared Error (MSE) on the

held-out task (Across-task MSE). We compared the Across-task MSE with the

within-task MSE, computed by performing 2-fold cross-validation using the data of

one task, then summing the MSE across tasks. If priors are the same, we expect that

the Across-task MSE should not exceed the Within-task MSE. This analysis allowed

us to examine if priors were the same or different across tasks.

To quantify the prior width in the estimation task and the 2-Afc task, we used

the *Estimation slope* and the *PSE slope* respectively. Using a maximum-likelihood

estimation algorithm, we estimated prior standard deviation parameters from the

slopes of one task by minimizing the MSE between the slope values and the slopes

given by Equations 1 and 2. To compute the Across-task MSE, we predicted the

slopes of the held-out task from the fitted parameters and compared the predicted

slope with that computed from the data using the MSE. To compute the Within-task

MSE, we estimated the prior standard deviation parameters from 50% data of one

task, then predicted the slope for the same task, and compared the predicted slope to

the slope computed from the held-out data.

To ensure that our analysis led to unbiased results, we simulated 1000

Bayesian observers who combined prior and likelihood information optimally and

used the veridical prior parameters in both tasks. Simulated observers should not

show systematic differences between the Across-task and Within-task MSE.

In order to examine how the priors used by participants differed from the

veridical priors, we estimated the prior standard deviation using Equations 1 and 2

and a maximum likelihood estimation algorithm. We ensured that this procedure did

not lead to biased results using simulations. We simulated Bayesian observers who

combined prior and likelihood information optimally. Simulated participants used the

veridical prior standard deviation in the estimation task and used a prior standard

deviation in the 2-Afc task which related to the veridical value by a factor of .5, 1, or

2. We performed 1000 simulations per condition. Inferring the prior width from the

behavioral data allowed us to examine generalization of the prior.

RESULTS

We asked if a learned prior distribution generalizes across tasks and thus

consists of knowledge. To do so, we first had participants learn a prior in a

sensorimotor estimation task where participants gave a continuous estimate of

stimulus location under uncertainty. We then quantified use of the prior in a 2-Afc

task where instead participants compared the locations of two hidden stimuli (Fig. 1).

We used data from previous work (Acuna et al. 2015). We examined whether the data

was consistent with use of the same or different priors across tasks and estimated the

prior standard deviation parameters from the data of each task.

In our tasks, participants judged the location of visual stimuli on screen.

Stimuli were samples from a Gaussian prior distribution, $N(\mu, \sigma_s^2)$, which were

hidden from view. Instead, participants were shown an uncertain visual cue in the

form of *n* samples (*n*=4) from a Gaussian likelihood distribution, distributed around

stimulus location, $N(s, \sigma_l^2)$. When judging stimulus location, the Bayesian optimal

strategy is to combine the likelihood and the learned prior according to their relative

precision. Therefore, to examine participants' use of probabilistic information, we

manipulated the standard deviations of the prior and likelihood, σ_s^2 and σ_l^2 and

quantified how much participants rely on the likelihood or prior to reach a decision

(see Methods, Fig. 2). Our paradigm allowed us to examine integration of

probabilistic information and to infer participants' learned priors in the estimation and

2-Afc tasks.

Figure 2. Estimation and 2-Afc data. (**A**) Estimation data overlaid with linear fit for a representative participant. The net position as a function of the centroid of the likelihood is shown for each trial (black points). Each panel displays estimation data for one condition, with overlaid fitted (blue line) and optimal (red line) functions. An *Estimation slope* of 1 indicates complete reliance on the likelihood and an *Estimation slope* of 0 indicates complete reliance on the prior. (**B**) 2-Afc data for the representative participant in (**A**) with one panel per condition. Raw binary decision data (dark gray points, Decision=0, probe stimulus to the left; light gray points, Decision=1, probe stimulus to the right). The best fitting PSE (blue line) and optimal PSE (red line) are shown. The more negative the *PSE slope*, the narrower the prior.

To examine use of probabilistic information in producing estimates, we first examined influence of the prior width and likelihood width on participants' reliance on the likelihood or prior (*Estimation slope*, see Fig. 2 and Methods for details). We found that both prior width and likelihood width influence the *Estimation slope* (Repeated-measures ANOVA: main effect of prior width: $p<.0001$, $F(1, 7) = 320.74$; main effect of likelihood width, $p<.0001$, $F(1, 7) = 140.67$). Therefore, participants use the prior and likelihood widths to judge stimulus location. Therefore, it makes sense to describe participants' sensorimotor estimates as Bayesian and to quantify the prior used during the task.

We then examined use of probabilistic information in the 2-Afc task, with a measure of reliance on prior or likelihood in decision data, which we termed the *PSE slope* (see Fig. 2 and Methods for details). It was important to establish that participants could incorporate a prior into 2-Afc decisions, as shown by a negative *PSE slope*. We thus compared PSE slopes with 0 (Narrow prior: $p < .05$, one-sample, 2-sided t-test, $t(7) = 3.60$, Wide prior: $p < .05$, one-sample, 2-sided t-test, $t(7) = 3.28$, Bonferroni-corrected p-values). As is shown by the significantly negative PSE slope

in both conditions, participants incorporate priors into 2-Afc decisions. There was a

significant effect of prior width on *PSE slope* (p < .0001, paired, 2-sided t-test, t(14) =

7.59). Thus, participants are influenced by the prior in their decisions and have a

greater reliance on the prior in the Narrow-Prior condition. This is consistent with

Bayesian computation, making it appropriate to quantify the prior used during the

task.

324
325 Figure 3. *Estimation slope* and *PSE slope*. (**A**) The median *Estimation slop*e is shown as a
326 function of Prior width and Likelihood width. Error bars display bootstrapped 95%
327 confidence intervals (CI). The optimal slope values for each condition are shown by red
328 diamonds. (**B**) The median *PSE slope* is shown as a function of Prior width. Error bars display
329 95% CI. The optimal slope values for each condition are shown by red diamonds.
330

Behavior in the two tasks is in accordance with the use of probabilistic

information. This was shown by an influence of the uncertainty of the prior and

likelihood on judgments in both tasks. However, it is possible that the priors used in

the estimation and 2-Afc tasks are different. Such a difference would be in violation

of standard Bayesian thought where the prior representation is considered as

knowledge and hence, domain general and fully available for use across tasks.

We then asked if the data supports task-dependent prior representations. If

participants use the same prior to perform both tasks, prior width parameters

estimated from one task's data should predict the other task's data well. The cross-

validated error between slopes across tasks (Across-task MSE, see Methods) should

not exceed the cross-validated error within tasks (Within-task MSE). We found that

the Across-task MSE exceeded the MSE computed within each task (p<.01,

t(7)=3.35, Fig 4A). Simulations show that this analysis is unbiased and does not favor

this result (Fig 4A). This result suggests that participants use different priors in the

different tasks.

346
Figure 4. Comparison of priors in the Estimation and 2-Afc tasks (**A**) The MSE computed
within tasks is shown as a function of the MSE computed across tasks. For each participant,
the MSE across tasks exceeds the MSE within tasks. Therefore, the data is not consistent with
use of the same prior. MSE for 1000 simulated participants (distribution in purple, color bar
displays kernel density estimate) show that this analysis gives unbiased results. (**B**) For each
participant, prior standard deviation inferred from the 2-Afc task data is shown as a function
of the prior standard deviation inferred from the estimation task data. The median bootstrap is
shown (error bar=95% CI). The dotted line shows the diagonal, for which prior width in the
tasks are equal. (**C**) Prior parameters estimated from the data of 1000 simulated Bayesian
observers in the Narrow-Prior condition (upper panel) and Wide-Prior condition (lower
panel). Simulated participants use the theoretical prior in the estimation task and either the
same prior standard deviation in the 2-Afc task (simulated prior ratio=1, the prior ratio being
the ratio of the standard deviations in the 2-Afc and estimation tasks) or a different prior
standard deviation in the 2-Afc task (simulated prior ratio= .5, or 2. The median inferred prior
standard deviation is shown for the estimation task (orange) and the 2-Afc tasks (purple),
shaded area= 2.5th-97.5th percentile. Broken red lines show the veridical prior standard
deviations.
364
Having found that priors were different across tasks, we wanted to know how

they were different. We, therefore, inferred the prior width (standard deviation) from

the estimation and 2-Afc data from the *Estimation slope* and the *PSE slope* using

bootstrapped parameter estimation. For each individual participant, the prior in the 2-

Afc task is wider than the prior in the estimation task in both the Narrow and Wide

prior conditions (95% CI consistently above the diagonal in Fig. 4B). We show that

our estimation of prior width is unbiased and that we can successfully infer prior

width from simulated estimation and 2-Afc data (Fig. 4C). Regarding our hypothesis

on the generalization of the learned prior from the estimation task to the 2-Afc task,

this shows that the prior does not generalize fully. Therefore, our analysis supports

policy representation rather than knowledge representation.

DISCUSSION

We examined if a prior distribution learned during a sensorimotor estimation
task generalized to a computationally-equivalent 2-Afc decision task. We showed that
there was a difference in priors across tasks. The finding of a wider prior in the 2-Afc
task shows that the prior did not generalize fully from the situation where participants
provided a continuous estimate of location to different task where participants
compared two object locations. This shows that sensorimotor priors are not
knowledge, in the sense that they do not generalize fully across modalities.

A caveat is that we assume that the brain uses maximum a-posteriori (MAP) to
compute decisions. MAP is widely-used in the decision-making literature and is a
plausible choice of mechanism since it maximizes reward in simple cases (Maloney
2002; Mamassian et al. 2002). Other decision-making mechanisms include sampling
from probability distributions and have been explored in previous work (Vul et al.
2014; Acuna et al. 2015). While the choice of MAP may be reasonable in the case of
unimodal Gaussian posterior distributions as in the current study, MAP is less adapted
to cases of multimodal or broadly-distributed posteriors. Further work is needed to
explore the decision rules that the brain uses.

One implication of our finding is that priors cannot be assumed to generalize
even when the difference between learning and testing conditions or tasks is subtle.
For example, previous work investigating decision-making mechanisms quantifies the
prior in an estimation task and measures the influence of the subjective prior in a 2-
Afc task (Acuna et al. 2015). The findings of this previous work therefore rest on the
assumption that the prior is the same across tasks and the conclusions of this paper
and others with the same assumption should be revisited.

Why are the priors different? The tasks may engage distinct neural systems,
with the estimation task having a stronger sensorimotor component ('Where is the
object in relation to me?'), whereas the 2-Afc task is a perceptual task and concerns
relationships between objects in the outside world ('Where is one object in relation to
another?'). Therefore, partly independent neural representations may lead to
incomplete generalization across tasks (Aglioti et al. 1995; Knill 2005). In this view,
partial generalization comes from partly distinct neural systems.

Importantly, our finding is inconsistent with the view that the brain acquires
fully generalizable knowledge, in the form of priors that can automatically be
incorporated into behavior regardless of the task. While high-level conceptual
representations may fit the definition of knowledge (Perfors et al. 2011; Tenenbaum

et al. 2011; Battaglia et al. 2013), our findings show that learning in a sensorimotor

task has a strong policy component, with a prior being partly confined to the task

where it was learned. In naturalistic situations, the use of policies may be functionally

beneficial, allowing for learning to be optimized for the task at hand.

Knowledge and policies are often evoked to explain behavior (Tenenbaum et

al. 2011; Haith and Krakauer 2013). However, they are seldom pitted against each

other as they originate from distinct theoretical frameworks. A more common

dichotomy is that of procedural and declarative knowledge, which describes

knowledge of how to perform some action and knowledge of concepts, respectively,

or 'knowing how and knowing that' (Ryle 1945; Winograd 1975; Squire

2004). While these resemble the concepts of knowledge and policy, the declarative-

procedural dichotomy does not have the same implications for generalization.

Declarative knowledge is by definition generalizable, while procedural knowledge

can generalize strongly or not, that is, can be consistent with knowledge or policy.

Therefore, these dichotomies do not completely overlap with one another. A second

common dichotomy is that of model-based and model-free behavior (Sutton and Barto

1998; Daw and Doya 2006; Doll et al. 2012). Model-based behavior leverages a

model of a situation to attain a goal, while model-free behavior involves repetition of

previously successful actions. When applied to our paradigm, one could conclude that

the more optimal prior use in the estimation task is based on a better model of how

stimuli were generated and that deviations from this in the 2-Afc task imply weaker

use of a model. Our findings, however, do not support pure model-based or model-

free behavior in either task and our experiment and findings are more amenable to a

probabilistic treatment and quantification of priors. Discussion of findings in light of

different approaches and frameworks is helpful and will be necessary to build a more

unified theory of the brain's function.

These results are compatible with a learning framework, rather than a high-

level Bayesian view of the brain's computations, where one set of priors (knowledge)

is used for different output behaviors. Multi-layer neural networks provide a flexible

way of modeling diverse kinds of behavior based on function optimization (LeCun et

al. 2015; Marblestone et al. 2016). Within a broader network, sub-networks that

implement specialized learning could produce patterns of generalization or non-

generalization across conditions and tasks. Importantly, a system that learns by

gradient descent will approximate Bayesian behavior without explicitly implementing

Bayesian computations (Weisswange et al. 2011; Mandt et al. 2017), simply because

it is the optimal strategy for estimation under uncertainty. Our finding thus casts

doubt on the view that Bayesian computation is at the core of the neural code (Zemel

et al. 1998; Ma et al. 2008).

GRANTS

This work was funded by grant by NIH grant 5R01NS063399-08, awarded to KPK.

REFERENCES

Acuna DE, **Berniker M**, **Fernandes HL**, **Kording KP**. Using psychophysics to ask

if the brain samples or maximizes. *J Vis* 15: 7, 2015.

Aglioti S, **DeSouza JFX**, **Goodale MA**. Size-contrast illusions deceive the eye but

not the hand. *Curr Biol* 5: 679–685, 1995.

Battaglia PW, **Hamrick JB**, **Tenenbaum JB**. Simulation as an engine of physical

scene understanding. *Proc Natl Acad Sci U S A* 110: 18327–32, 2013.

Berniker M, **Voss M**, **Kording K**. Learning priors for bayesian computations in the

nervous system. *PLoS One* 5: 1–9, 2010.

Criscimagna-hemminger SE, **Donchin O**, **Gazzaniga MS**, **Shadmehr R**, **Sarah E**,

Donchin O, **Michael S**. Learned Dynamics of Reaching Movements Generalize From

Dominant to Nondominant Arm. *J Neurophysiol* 89: 168–176, 2003.

Daw ND, **Doya K**. The computational neurobiology of learning and reward. *Curr*

Opin Neurobiol 16: 199–204, 2006.

Doll BB, **Simon DA**, **Daw ND**. The ubiquity of model-based reinforcement learning.

Curr Opin Neurobiol 22: 1075–1081, 2012.

Fernandes HL, **Stevenson IH**, **Vilares I**, **Kording KP**. The generalization of prior

uncertainty during reaching. *J Neurosci* 34: 11470–84, 2014.

Haith AM, **Krakauer JW**. Theoretical models of motor control and motor learning.

In: *Routledge handbook of motor control and motor learning*. London: Routledge,

2013, p. 7–28.

Knill D. Reaching for visual cues to depth: the brain combines depth cues differently

for motor control and perception. *J Vis* 5: 103–115, 2005.

Körding KP, **Wolpert DM**. Bayesian integration in sensorimotor learning. *Nature*
427: 244–247, 2004.

LeCun Y, **Yoshua B**, **Geoffrey H**. Deep learning. *Nature* 521: 436–444, 2015.

Ma WJ, **Beck JM**, **Pouget A**. Spiking networks for Bayesian inference and choice.
Curr Opin Neurobiol 18: 217–222, 2008.

Maloney LT. Statistical decision theory and biological vision. In: *Perception and the*
physical world, edited by D H, R M. New York: Wiley, 2002, p. 145–189.

Mamassian P, **Landy M**, **Maloney LT**. Bayesian Modelling of Visual Perception.
In: *Probabilistic models of the brain: Perception and neural function*, edited by Rao
N, Olhausen B, Lewicki M. Cambridge, MA: MIT Press, 2002, p. 13–36.

Mandt S, **Hoffman MD**, **Blei DM**. Stochastic Gradient Descent as Approximate
Bayesian Inference. *arXiv* : 1–30, 2017.

Marblestone AH, **Wayne G**, **Kording KP**. Toward an Integration of Deep Learning
and Neuroscience. *Front Comput Neurosci* 10: 94, 2016.

Perfors A, **Tenenbaum JB**, **Regier T**. The learnability of abstract syntactic
principles. *Cognition* 118: 306–338, 2011.

Ryle G. Knowing How and Knowing That : The Presidential Address. *Proc Aristot*
Soc 46: 1–16, 1945.

Shadmehr R. Generalization as a behavioral window to the neural mechanisms of
learning internal models. *Hum Mov Sci* 23: 543–568, 2004.

Squire LR. Memory systems of the brain: A brief history and current perspective.
Neurobiol Learn Mem 82: 171–177, 2004.

Sutton RS, **Barto AG**. *Reinforcement learning: An introduction*. Cambridge, MA:
MIT press, 1998.

Tassinari H, **Hudson TE**, **Landy MS**. Combining priors and noisy visual cues in a
rapid pointing task. *J Neurosci* 26: 10154–63, 2006.

Tenenbaum JB, **Griffiths TL**, **Kemp C**. Theory-based Bayesian models of inductive
learning and reasoning. *Trends Cogn Sci* 10: 309–318, 2006.

Tenenbaum JB, **Kemp C**, **Griffiths TL**, **Goodman ND**. How to grow a mind:

statistics, structure, and abstraction. *Science* 331: 1279–1285, 2011.

Vilares I, **Howard JD**, **Fernandes HL**, **Gottfried JA**, **Kording KP**. Differential

representations of prior and likelihood uncertainty in the human brain. *Curr Biol* 22:

1641–1648, 2012.

Vul E, **Goodman N**, **Griffiths TL**, **Tenenbaum JB**. One and done? Optimal

decisions from very few samples. *Cogn Sci* 38: 599–637, 2014.

Weisswange TH, **Rothkopf CA**, **Rodemann T**, **Triesch J**. Bayesian Cue Integration

as a Developmental Outcome of Reward Mediated Learning. 6, 2011.

Winograd T. Frame representations and the declarative/procedural controversy. In:

Representation and understanding: Studies in cognitive science, edited by Bobrow J.

Elsevier, p. 185–210.

Xu F, **Tenenbaum JB**. Word Learning as Bayesian Inference. *Psychol Rev* 114: 245–

250, 2007.

Zemel RS, **Dayan P**, **Pouget A**. Probabilistic interpretation of population codes.

Neural Comput 10: 403–430, 1998.

520