Interpreting Temporal Fluctuations in Resting-State Functional Connectivity MRI

Raphaël Liégeois[a,1], Timothy O. Laumann[b], Abraham Z. Snyder[b,c], Helen J. Zhou[d], B.T. Thomas Yeo[a,d,e]

[a]*Department of Electrical and Computer Engineering, ASTAR-NUS Clinical Imaging Research Centre, Singapore Institute for Neurotechnology and Memory Networks Program, National University of Singapore, Singapore*
[b]*Department of Neurology, Washington University School of Medicine, St. Louis, MO, USA*
[c]*Department of Radiology, Washington University School of Medicine, St. Louis, MO, USA*
[d]*Centre for Cognitive Neuroscience, Duke-NUS Medical School, Singapore*
[e]*Martinos Center for Biomedical Imaging, Massachusetts General Hospital, Charlestown, MA, USA*

Abstract

Resting-state functional connectivity is a powerful tool for studying human functional brain networks. Temporal fluctuations in functional connectivity, i.e., *dynamic* functional connectivity (dFC), are thought to reflect dynamic changes in brain organization and *non-stationary* switching of discrete brain states. However, recent studies have suggested that dFC might be attributed to sampling variability of static FC. Despite this controversy, a detailed exposition of stationarity and statistical testing of dFC is lacking in the literature. This article seeks an in-depth exploration of these statistical issues at a level appealing to both neuroscientists and statisticians.

We first review the statistical notion of stationarity, emphasizing its reliance on ensemble statistics, which contrasts with the fact that all FC measures depend on sample statistics. One implication is that stationarity does not imply the absence of brain states. We then expound the assumptions underlying two frameworks - phase randomization (PR) and autoregressive randomization (ARR) - widely used to generate null data for statistical testing of dFC. It turns out that both PR and ARR rely on assumptions of stationarity, linearity and Gaussianity. Therefore statistical rejection does not necessarily imply non-stationarity, but can also be due to nonlinearity or non-Gaussianity. We further show that a common form of ARR (bivariate ARR) is susceptible to false positives compared with PR and an adapted version of ARR (multivariate ARR).

Application of PR and multivariate ARR to Human Connectome Project data suggests that the stationary, linear, Gaussian null hypothesis cannot be rejected for most participants. However, failure to reject the null hypothesis does not imply that static FC can fully explain dFC. After all, AR models are dynamical FC models in the sense that they encode linear dynamic interactions beyond static FC. We find that AR models could explain temporal FC fluctuations significantly better than static FC models. We also find that AR models explain temporal FC fluctuations significantly better than a popular model assuming discrete brain states, suggesting the lack of discrete states (as measured by resting-state fMRI). Overall, our results suggest that AR models are not only useful as a means for generating null data, but may be a powerful tool for exploring the dynamical properties of resting-state functional connectivity. We also discuss how apparent contradictions in the growing dFC literature might be reconciled.

Keywords: stationarity, linear dynamical systems, brain states, dynamic FC, surrogate data

1. Introduction

The human brain exhibits complex spatiotemporal patterns of activity fluctuations even during the resting-state (Greicius et al., 2003; Damoiseaux et al., 2006; Smith et al., 2013b). Characterizing the structure of these fluctuations is commonly done via functional connectivity (FC) analyses of resting-state fMRI (rs-fMRI) data (Van Den Heuvel and Pol, 2010; Buckner et al., 2013). The most common FC measure is the Pearson correlation between brain regional time courses (Biswal et al., 1995; Vincent et al., 2006; Dosenbach et al., 2007; Buckner et al., 2009; Zalesky et al., 2010; Power et al., 2011; Yeo et al., 2011,

2014; Margulies et al., 2016), although other measures, such as partial correlation (Fransson and Marrelec, 2008; Spreng et al., 2013) or mutual information (Tsai et al., 1999; Tedeschi et al., 2005; Chai et al., 2009) have been utilized. These FC measures are *static* in the sense that they are invariant to temporal re-ordering of fMRI time points, thus ignoring temporal information that might be present in fMRI

In contrast, recent work on *dynamic* functional connectivity (dFC) suggests that there might be important information beyond static FC, e.g., in the temporal fluctuations of FC or in models taking into account the temporal ordering of fMRI time series (see Hutchison et al. (2013a); Calhoun et al. (2014); Preti et al. (2016) for recent re-

---

[1]*Contact:* `R.Liegeois@nus.edu.sg` (Raphaël Liégeois)

views). To interrogate dFC, sliding window correlations (SWC) is by far the most common method (Sakoğlu et al., 2010; Handwerker et al., 2012; Hutchison et al., 2013b; Allen et al., 2014; Leonardi et al., 2014; Liégeois et al., 2016; Wang et al., 2016), although many alternative approaches have been proposed (Majeed et al., 2011; Smith et al., 2012; Lindquist et al., 2014; Karahanoğlu and Van De Ville, 2015; Shine et al., 2015).

To assess the statistical significance of dFC, randomization frameworks are typically used to generate null data. Null hypothesis testing can then be performed by comparing statistics from the original data against those from the null data. The two most popular randomization frameworks are autoregressive randomization (ARR) (Chang and Glover, 2010; Zalesky et al., 2014) and phase randomization (PR) (Handwerker et al., 2012; Allen et al., 2014; Hindriks et al., 2016). While most papers reported the rejection of the null model (Chang and Glover, 2010; Handwerker et al., 2012; Zalesky et al., 2014), recent studies have suggested difficulties in rejecting the null model, especially in single subject data (Hindriks et al., 2016; Laumann et al., 2016).

The observed dFC have also been interpreted by many authors as evidence of non-stationary switching of discrete brain states (Allen et al., 2014; Hansen et al., 2015). These states have been associated with mental disorders (Damaraju et al., 2014; Rashid et al., 2014; Su et al., 2016; Du et al., 2016), as well as variation in intra-individual and inter-individual differences in vigilance, consciousness and executive function (Barttfeld et al., 2015; Nomi et al., 2017; Shine et al., 2016; Wang et al., 2016). In contrast, some have suggested that the brain (as measured by rs-fMRI) might not be undergoing sharp transition between discrete states (Leonardi et al., 2014) or that dFC fluctuations might largely reflect sampling variability (Laumann et al., 2016).

Contributing to the possible confusion in the literature is the loose use of the term "stationarity" (e.g., Hutchison et al., 2013a; Allen et al., 2014; Zalesky and Breakspear, 2015; Preti et al., 2016). For example, Hutchison and colleagues Hutchison et al. (2013a) equated static FC and dFC analyses with assumptions of stationarity and non-stationarity respectively. However, the very same review cautioned that a stationary process can exhibit temporal fluctuations in an FC metric, such as SWC (Hutchison et al., 2013a). Since null data generation frameworks (e.g., PR and ARR) were developed based on strict statistical definitions of stationarity (Tucker et al., 1984; Efron and Tibshirani, 1986), the loose usage of statistical terminologies impedes our understanding of dFC. To the best of our knowledge, issues of stationarity and assumptions of null data generation frameworks (PR and ARR) are often briefly mentioned, but not discussed in detail in the literature. By exploring these issues in-depth, this commentary leads to several surprising conclusions.

The commentary begins by reviewing random processes, weak-sense stationarity and how fMRI can be conceptualized as a random process (Section 2). We then show that a two-state hidden Markov model (HMM) process is actually stationary, suggesting that stationarity does not imply the absence of brain states (Section 3). In the following section, assumptions behind PR and ARR are discussed, revealing that both PR and AR generate null data that are linear, stationary and Gaussian. Therefore rejection of the PR and ARR null models does not imply non-stationarity. Importantly, AR models encode dynamical interactions between brain regions, above and beyond static FC (Section 4). Experiments on the Human Connectome Project data suggests that the PR and ARR null models cannot be rejected for most low motion participants, and that bivariate ARR (a common variant of ARR) can yield false positives (Section 5). Furthermore, multivariate AR models replicate the rich dynamics of SWC significantly better than just models of static FC, as well as commonly used HMM-type models that explicitly encode discrete brain states (Section 6). We conclude with a discussion of how these results can be reconciled with the growing literature on dFC (Section 7).

While our experiments focused on SWC, almost all the issues we discuss apply to other dFC methods. In addition, it is worth distinguishing dFC (second order statistics) from dynamic fMRI activity level (first order statistics). From the earliest days of resting-state fMRI, the question of dynamic fMRI activity level during resting-state and its relationship with behavior has been of great interest (Fox et al., 2006, 2007; Kucyi et al., 2016). Many of the issues that we raised in this commentary also apply to the study of dynamic activity level. Therefore we will point out relevant lessons to dynamic activity level as and when they arise.

2. Interpreting fMRI as a random process

In this section, we first review random variables, random processes and weak-sense stationarity (WSS). We then distinguish between sample statistics and ensemble statistics. Finally, we formalize fMRI as a random process and explain why testing dFC within a formal statistical framework is non-trivial.

2.1. Random variables

A random variable is a quantity that is uncertain (Prince, 2012). It may be the outcome of an experiment (e.g., tossing a coin) or real world measurement (e.g., measuring the temperature of a room). If we observe a random variable multiple times, we will get different values. Some values occur more frequently than others; this variation in frequencies is encoded by the probability distribution of the random variable. Multiple observations of a random variable are referred to as *realizations* (or samples) of the random variable.

The mean or expectation of a random variable X is denoted as $E(X)$. We can think of $E(X)$ as the average

value of X over many (infinite) realizations of X. Similarly, the variance of a random variable X is denoted as $Var(X) = E[(X - E(X))^2]$. We can think of $Var(X)$ as the average square deviation of X from its mean over many (infinite) realizations of X.

In the case of two random variables X and Y, we can characterize their linear relationship with the covariance $Cov(X, Y) = E[(X - E(X))(Y - E(Y))]$. We can think of $Cov(X, Y)$ as averaging $(X - E(X))(Y - E(Y))$ over many (infinite) realizations of X and Y. The covariance measures how much X and Y co-vary across their respective means. If the covariance is positive, then for a particular realization of X and Y, if X is higher than its mean, then Y tends to be higher than its mean. If the covariance is negative, then for a particular realization of X and Y, if X is higher than its mean, then Y tends to be lower than its mean. We note that $Cov(X, X) = Var(X)$.

2.2. Random processes and weak-sense stationarity (WSS)

A random process is an infinite collection of random variables, and is especially useful for the analysis of time-series. For example, suppose we randomly pick a thermometer from a store (with many thermometers) to measure the temperature of a particular room. Let U_t be the thermometer measurement at time t. Then U_t is a random process. Figure 1A illustrates three *realizations* of the random process, where each realization (blue, red or green) corresponds to a different thermometer. Here we assume that the room temperature is constant at $20°C$, and that each thermometer is identical and incurs an independent (zero-mean unit-variance Gaussian) measurement noise at each time, i.e., $p(U_t) \sim \mathcal{N}(20, 1)$.

The expectation of a random process X_t at time t is denoted as $E(X_t)$. We can think of $E(X_t)$ as averaging X_t across infinite realizations of the random process at time t. For the toy example U_t (Figure 1A), averaging the temperature measurements across many thermometers at a particular time t converges to the true temperature of the room, and so $E(U_t) = 20$ for all time t. Similarly, we can think of $Var(X_t) = E[(X_t - E(X_t))^2]$ as averaging the square deviation of X_t at time t from its mean $E(X_t)$ over infinite realizations of the random process. For the toy example U_t (Figure 1A), $Var(U_t) = 1$ for all time t.

Finally, the auto-covariance $Cov(X_n, X_m) = E[(X_n - E(X_n))(X_m - E(X_m))]$ measures the co-variation of X_n and X_m about their respective means at times n and m. For example, if the auto-covariance is positive, then for a particular realization of X_t, if X_n is higher than its mean $E(X_n)$, then X_m tends to be higher than its mean $E(X_m)$. Conversely, if the auto-covariance is negative, then for a particular realization of X_t, if X_n is higher than its mean $E(X_n)$, then X_m tends to be lower than its mean $E(X_m)$. We note that $Cov(X_n, X_n) = Var(X_n)$. For the toy example U_t (Figure 1A), $Cov(X_n, X_m) = 0$ for two different time points n and m since we assume the thermometer noise is independent at each time point.

We can now define WSS as follows (Papoulis, 2002):

A random process X_t is WSS if its mean $E(X_t)$ is constant for all time t and its auto-covariance $Cov(X_n, X_m)$ depends only on the time interval $\tau = n - m$, i.e., $Cov(X_n, X_m) = R(n - m) = R(\tau)$.

Since $Var(X_n) = Cov(X_n, X_n)$, this implies that $Var(X_n) = R(0)$ for a WSS process. In other words, the variance $Var(X_t)$ of a WSS process is constant over time. While there are other forms of stationarity (e.g., strict-sense stationarity), we will only focus on WSS in this paper and will use the phrase "stationarity" and "WSS" interchangeably.

The toy example U_t (Figure 1A) is WSS because $E(U_t) = 20$ is a constant, and $Cov(X_n, X_m)$ can be written as $R(n - m)$, where $R(0) = 1$ (when $n = m$) and $R(n - m)$ is equal to 0 for $n - m \neq 0$. In contrast, suppose the thermostat of the room was changed at time t_0, so that the room temperature increased from $20°C$ to $23°C$ (Figure 1B). Then the resulting random process V_t is non-stationary because $E(V_t) = 20$ for $t < t_0$ and $E(V_t) = 23$ for $t > t_0$.

2.3. Ensemble statistics versus sample statistics

It is worth emphasizing that the mean $E(X_t)$, variance $Var(X_t)$ and auto-covariance $Cov(X_n, X_m)$ of a random process are defined *across* an infinite number of realizations, rather than within a *single* realization. To illustrate this point, suppose at time points t_1 and t_2, we average across multiple realizations of the random process U_t resulting in $M_U(t_1)$ and $M_U(t_2)$ (Figure 1A). We can think of $M_U(t_1)$ and $M_U(t_2)$ as estimates of $E(U_{t_1})$ and $E(U_{t_2})$. Indeed, as the number of realizations increases, $M_U(t_1)$ and $M_U(t_2)$ will converge to $E(U_{t_1})$ and $E(U_{t_2})$ respectively. This convergence holds not just for WSS processes, but all random processes. In the toy example V_t (Figure 1B), $M_V(t_1)$ converges to $E(V_{t_1}) = 20$, while $M_V(t_2)$ converges to $E(V_{t_2}) = 23$. We refer to the computation of statistics across realizations as *ensemble* statistics.

In contrast, *sample* statistics are computed within a single realization. For example, we can average each realization of the random process U_t resulting in $M(U^1)$, $M(U^2)$ and $M(U^3)$ (blue, green and red in Figure 1A). In the case of the random process U_t (Figure 1A), as the number of time points for each realization increases, the sample statistics converge to the ensemble statistics. More specifically, $M(U^1)$, $M(U^2)$ and $M(U^3)$ converge to $E(U_t) = 20$. However, sample statistics do not converge to ensemble statistics for non-stationarity processes. In the toy example V_t (Figure 1B), the sample statistics $M(V^1)$, $M(V^2)$ and $M(V^3)$ (blue, green and red in Figure 1B) converge to 21.5.

Therefore ensemble statistics are generally not equivalent to sample statistics in the case of non-stationary processes. Based on the toy example U_t (Figure 1A), one might be tempted to conclude that ensemble and sample statistics are equivalent in WSS processes. However, this turns out not to be true. To illustrate this, let's again assume the room temperature is constant at $20°C$.

Figure 1: Three examples of random processes U_t (left), V_t (middle) and W_t (right) and three realizations in each case illustrating the distinction between ensemble and sample statistics. Ensemble statistics are computed across realizations, while sample statistics are computed within a single realization. The random process U_t is weak-sense stationary (WSS) because ensemble statistics (e.g., mean and variance) do not depend on time, i.e., $M_U(t_1) = M_U(t_2)$. U_t is also ergodic because ensemble statistics are equal to sample statistics, i.e., $M_U(t_1) = M(U^1) = M(U^2) = M(U^3)$. Random process V_t is not WSS because the ensemble mean is not constant in time, i.e., $M_V(t_1) \neq M_V(t_2)$. It is also not ergodic, i.e., $M_V(t_1) \neq M(V^1)$. Random process W_t is WSS, i.e., $M_W(t_1) \neq M_W(t_2)$. However, W_t is not ergodic because ensemble statistics are constant in time but sample mean is not the same for different realizations, i.e., $M_W(t_1) \neq M(W^1) \neq M(W^2) \neq M(W^3)$.

However, each thermometer now incurs an independent non-zero-mean unit-variance Gaussian noise at each time $p(W_t) \sim \mathcal{N}(20 + b, 1)$, where the bias $b \sim \mathcal{N}(0, 1)$ is different for each thermometer (but held constant within a realization). Three realizations of random process W_t is illustrated in Figure 1C. The random process W_t is WSS with $E(W_t) = 20$ (because the bias b is zero-mean), $Var(W_t)$ is constant over time, and $Cov(W_n, W_m) = 0$ for $n \neq m$. The ensemble mean $M_W(t_1)$ and $M_W(t_2)$ still converge to $E(W_t) = 20$. However, the sample means $M(W^1)$, $M(W^2)$ and $M(W^3)$ now converge to 17, 20 and 23 respectively because we have assumed $b = -3, 0, 3$ for the blue, green and red realizations in Figure 1C. We now define ergodicity as follows (Papoulis, 2002):

> A random process X_t is ergodic if its ensemble statistics and sample statistics converge to the same values. An ergodic process is WSS.

The distinction between ensemble statistics and sample statistics becomes important as we conceptualize fMRI as a random process in the next section.

2.4. Interpreting fMRI as a random process

In the previous examples of random processes (Figure 1), each realization consisted of one uncertain quantity (temperature) at each time point. However, a random process X_t can also be *multivariate*, i.e., each realization consists of a vector at each time point. fMRI data typically consists of N time series, where N is the number of voxels or regions of interest (ROIs). Therefore the fMRI data can be thought of as a multivariate random process with a $N \times 1$ vector of measurements at each time point (i.e., TR).

For a multivariate random process, $E(X_t)$ is now an $N \times 1$ vector equivalent to averaging X_t across infinite realizations of the random process at time t. The $N \times N$ auto-covariance matrix $Cov(X_n, X_m) = E[(X_n - E(X_n))(X_m - E(X_m))^T]$ measures the co-variation of X_n and X_m about their respective vectorial means at times n and m. For example, if the i-th row and j-column of the auto-covariance matrix is positive, then for a particular realization of X_t, if the i-th element of X_n is higher than its mean (the i-th element of $E(X_n)$), then the j-th element of X_m tends to be higher than its mean (the j-th element of $E(X_m)$). For a WSS process, the auto-covariance $Cov(X_n, X_n) = E[(X_n - E(X_n))(X_n - E(X_n))^T]$ is constant over time.

In the case of fMRI, one could potentially interpret $Cov(X_n, X_n)$ as the *ensemble* $N \times N$ (un-normalized) functional connectivity matrix among all brain regions at time n and might therefore be relevant for the topic of dFC. However, difficulties arise because the auto-covariance and WSS are based on ensemble statistics, and therefore require multiple realizations of a random process to estimate. While most researchers can probably agree that the fMRI data of a single subject can be considered a single realization of a random process, what constitutes multiple realizations is more ambiguous. Most neuroscientists would probably balk at conceptualizing the fMRI data of each subject (of a multi-subject dataset) as a single real-

ization of the *same* random process. Therefore in most dFC papers (Chang and Glover, 2010; Handwerker et al., 2012; Zalesky et al., 2014; Hindriks et al., 2016), the fMRI data of different subjects are treated as single realizations of *different* random processes. As such, both ensemble statistics and hypothesis testing only have access to a single realization of a random process (i.e., relying on sample statistics). Yet, for sample statistics to converge to ensemble statistics (previous section), fMRI must be ergodic, which in turn implies WSS. This creates conceptual and practical issues for dFC analysis that will be the focus for the remainder of this paper.

3. Stationarity does not imply the absence of brain states

The previous section suggests the existence of conceptual and practical issues when studying dFC. This section focuses on the conceptual issue of whether non-WSS and dFC are equivalent. In the literature, it is often implicitly assumed that WSS implies the lack of fluctuations in FC (e.g., as measured by SWC) or FC states (e.g. Allen et al., 2014). However, we now show that WSS does not imply the lack of FC fluctuations or FC states.

Consider a toy "brain" with two regions whose signals correspond to a bivariate random process X_t containing two brain states S_1 and S_2. If the brain is in state S_1 at time t, then $X_t \sim \mathcal{N}\left(\begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 1 & 0.9 \\ 0.9 & 1 \end{bmatrix} \right)$, i.e., the two brain regions are functionally connected with $r = 0.9$. If the brain is in state S_2 at time t, then $X_t \sim \mathcal{N}\left(\begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 1 & -0.2 \\ -0.2 & 1 \end{bmatrix} \right)$, i.e., the two regions are anti-correlated with $r = -0.2$. Finally, let the probability of transitioning between the two brain states be given by the following transition probability matrix: $\begin{bmatrix} 0.99 & 0.01 \\ 0.01 & 0.99 \end{bmatrix}$, i.e., from time t to $t+1$, there is a 0.99 probability of remaining in the same state and a 0.01 probability of switching state. This random process is known as a hidden Markov process (HMM) (Baum and Petrie, 1966).

Three realizations of this process are shown in Figure 2. The blue and green time courses correspond to the signals of the two brain regions. The sliding window correlations (SWC) between the two regions (red lines in Figure 2) exhibit huge fluctuations with correlations close to 0.9 and -0.2 in states S_1 and S_2 respectively.

Most neuroscientists would probably agree that this toy brain exhibits brain states and dFC. However, this toy brain is also WSS because the ensemble mean $E(X_t)$ is constant over time, and the ensemble auto-covariance $Cov(X_n, X_m)$ is only a function of the interval $n - m$. More importantly, the ensemble (unnormalized) functional connectivity matrix $Cov(X_n, X_n)$ in this toy brain is constant over time, despite the presence of brain states and dFC (Figure 2). This situation arises because dFC and brain states exist within a single realization, where the FC

Figure 2: Three realizations of the Hidden Markov Model (HMM) process with two brain regions and two states. Time series of the two brain regions are shown in blue and light green (scale on the left vertical axis). The sliding window correlation (SWC) between the two time series (number of frames $T = 1200$, window size $w = 30$ frames) is shown in red (scale on the right vertical axis). The HMM process is stationary, yet exhibits abrupt transitions in SWC corresponding to the switching between brain states.

at a given time depends on the underlying brain state, which can change over time in a single realization. However, these dynamics are averaged out (across realizations) when considering ensemble notions like WSS. Therefore WSS does not imply the absence of brain states or fluctuations in FC.

It is also worth noting that non-WSS does not necessarily imply the presence of dFC either. If the (unnormalized) functional connectivity matrix $Cov(X_n, X_n)$ varies as a function of time, then fMRI is non-WSS and the brain exhibits true fluctuations in FC. However, non-WSS can arise from just a non-stationary mean $E(X_t)$. In other words, the first order statistics (mean) can be non-stationary, while the second order statistics (variance and covariance) remains stationary. For example, the random process V_t (Figure 1A) is non-stationary because its mean $E(V_t)$ is non-constant over time, but its variance $Var(V_t)$ is actually constant over time. Therefore, even if fMRI is shown to be non-WSS, this might be due to non-stationary spontaneous activity level and/or non-stationary FC. In other words, non-WSS does not necessarily imply real fluctuations in FC.

While we focus on dFC (second order statistics) in this paper, many of the same issues also apply to the study of dynamic activity level (first order statistics). For example, one could modify the previous HMM example (Figure 2) so that the two states have different ensemble means, but the same ensemble covariance matrix. In this case, the resulting toy brain will be WSS, while still exhibiting real dynamic spontaneous activity (but not dFC)[1].

---

[1]One could also modify the HMM so that the toy brain will be

Despite the caveat that non-WSS does not necessarily imply real fluctuations in FC, establishing non-stationarity of fMRI is still a useful step towards establishing dFC. Therefore in the next section, we leave behind the conceptual issues raised in this section, and dive into the statistical testing of non-stationarity when only a single realization of the random process is available.

4. Stationarity cannot be tested alone

Statistical testing of FC non-stationarity is difficult for two reasons. First, observed dFC values (e.g., using SWC) are only estimates of true values (Hindriks et al., 2016; Laumann et al., 2016). As such, observed dFC fluctuations might simply correspond to sampling variability or measurement noise. Second, as explained in previous sections, the notion of stationarity is based on ensemble statistics defined across infinite realizations of a random process. Therefore observing fluctuations in a single realization of fMRI cannot be directly interpreted as evidence for non-stationarity but requires further statistical testing.

This section seeks to provide insights into common approaches for statistical testing of FC stationarity. A statistical test for non-stationarity requires defining a test statistic and a procedure to generate null data preserving certain properties of the single fMRI realization. The test statistic computed from real data is then compared against the null distribution of test statistics computed from the null data. A significant deviation of the real test statistic from the null distribution of test statistics would result in the rejection of the null hypothesis.

The test statistic should ideally reflect the null hypothesis being tested. For example, if one is interested in whether there are "real" fluctuations in FC between two brain regions, then an intuitive test statistic might be the variance of the SWC (Hindriks et al., 2016):

$$\kappa = \frac{1}{T-1} \sum_{t=1}^{T} [\mathrm{SWC}(t) - \mu]^2, \qquad (1)$$

where $\mathrm{SWC}(t)$ is the SWC between the two brain regions at time t and μ is the mean of the SWC time series. A higher κ (relative to a properly generated null distribution) indicates stronger evidence of dFC.

While there have been a wide variety of test statistics and dFC measures proposed in the literature (Sakoğlu et al., 2010; Chang and Glover, 2010; Zalesky et al., 2014; Hindriks et al., 2016), there has been significantly less discussion about the assumptions behind procedures for generating null data. Such assumptions are highly important because if one manages to generate WSS null data that also preserve all other properties (e.g., possible nonlinearity or non-Gaussianity) of the original data, then a rejection of

the null hypothesis would imply non-WSS. However, as will be seen, the two main approaches – autoregressive randomization (ARR) and phase randomization (PR) – actually generate linear, WSS, Gaussian data. Therefore a rejection of the null hypothesis only implies that the signal is non-linear, non-WSS, non-Gaussian or any combination of the above (Schreiber and Schmitz, 2000).

We begin by discussing properties of the fMRI time series we hope to preserve in the null data, followed by explaining how ARR and PR preserve these properties, and the relationships between the two approaches. Finally, we illustrate with examples of how the null hypothesis can be rejected even though the underlying data is WSS.

4.1. Properties to preserve in null data

To test if observed fluctuations in FC (e.g., SWC) can be completely explained by static FC (e.g., Pearson correlation), the null data should retain the static FC observed in real data. To preserve static FC, we could simply generate null data by permuting the temporal ordering of fMRI time courses. However, this procedure destroys the autocorrelational structure inherent in fMRI, and therefore the null hypothesis will be easily rejected. In other words, procedures for generating null data should also preserve the auto-correlational structure of fMRI data in addition to static FC.

Let us define these auto-correlations more precisely. Suppose we observe fMRI time courses from N ROIs (or voxels) of length T. Let x_t be the $N \times 1$ vector of fMRI data at time t after each time course has been demeaned. We define the auto-covariance sequence to be the following $N \times N$ matrices:

$$R_l = \frac{1}{T-l} \sum_{t=1}^{T-l} x_t x'_{t+l} \text{ for } 0 \le l \le T-1 , \qquad (2)$$

where $'$ denotes transpose. We note that the diagonal elements of R_l encode the *auto*-covariance of individual time courses, while the off-diagonal terms of R_l encode what is usually referred to as the *cross*-covariance between pairs of time courses.

The auto-covariance sequence $\{R_l\}$ measures the covariance of fMRI data l time points apart. Since the auto-covariances are computed from a single realization of fMRI data, the $\{R_l\}$ are considered sample statistics. R_0 is the (un-normalized) functional connectivity matrix typically computed in the literature. If fMRI data is ergodic (and hence WSS), then R_0 would be equal to the *ensemble* (un-normalized) functional connectivity matrix among all brain regions (for sufficiently large T). As will be seen, R_0 encodes static properties of fMRI, while the higher order auto-covariances $R_1, \cdots, R_{T-1}$ encode the dynamic properties of fMRI. We will now examine two frameworks for generating null data that preserve auto-covariances of the original data.

WSS, but exhibiting real dynamic spontaneous activity *and* dynamic FC.

4.2. Autoregressive randomization (ARR)

The ARR framework has been utilized by the statistics and physics community for decades (Efron and Tibshirani, 1986) and adopted by seminal papers in the dFC literature (Chang and Glover, 2010; Zalesky et al., 2014). Suppose we have fMRI time courses from N brain regions (or voxels). Each fMRI time course is assumed to be demeaned[2]. ARR assumes that the fMRI data at time t is a linear combination of the fMRI data from the previous p time points:

$$x_t = \sum_{l=1}^{p} A_l x_{t-l} + \epsilon_t, \qquad (3)$$

where $p \geq 1$, x_t is the $N \times 1$ vector of fMRI data at time t, $\epsilon_t \sim \mathcal{N}(0, \Sigma)$ corresponds to independent zero-mean gaussian noise[3], and A_l is a $N \times N$ matrix encoding the linear dependencies between time t and time $t-l$. Eq. (3) is known as a p-th order Gaussian autoregressive (AR) model.

ARR proceeds by first estimating the AR model parameters $(\Sigma, A_1, \cdots, A_p)$ from the fMRI data (details in Appendix A1). Each null fMRI timeseries is initialized by randomly selecting p consecutive time points of the original data, and then repeatedly applying the AR model (Eq. (3)) until null data of length T are generated.

Suppose the estimated AR model is stable. Then the AR model corresponds to a linear WSS Gaussian process whose auto-covariance sequence $R_0, \cdots R_p$ matches those of the original data.

The preservation of the first $p+1$ auto-covariances of the original data is a consequence of the Yule-Walker equations (Yule, 1927; Walker, 1931). Further details are found in Appendix A2. One consequence of the above result is the need to verify that the estimated AR model parameters correspond to a stable AR model (see Appendix A2).

Furthermore, any Gaussian linear process can be approximated arbitrarily well by an AR model[4] (El-Shaarawi and Piegorsch, 2013). Therefore, significant deviation from ARR null data (i.e., null hypothesis rejected) might be due to the fMRI data being non-linear, non-Gaussian, non-WSS or any of the above.

The matching of the higher order auto-covariances $R_1, \cdots, R_p$ arise from the linear dynamical interactions between brain regions (A_l in Eq. (3)). Therefore the higher order auto-covariances encode the dynamic properties of functional connectivity beyond the static FC encoded by R_0.

4.3. Phase randomization (PR)

The PR framework for generating null data has been utilized in the physics community for decades (Tucker et al., 1984; Osborne et al., 1986; Theiler et al., 1992; Prichard and Theiler, 1994). It has been applied to fMRI in several important dFC papers (Allen et al., 2014; Hindriks et al., 2016). We again assume without loss of generality that each fMRI time courses has been demeaned. The PR procedure generates null data by performing Discrete Fourier Transform (DFT) of each time course, adding a uniformly distributed random phase to each frequency, and then performing the inverse DFT. Importantly, the random phases are generated independently for each frequency, but are the *same* across brain regions. Details of this procedure is found in Appendix A3.

PR generates data corresponding to a linear WSS Gaussian process whose auto-covariance sequence $R_0, \cdots, R_{T-1}$ matches those of the original data.

Proof of WSS is found in Appendix A4. The preservation of all auto-covariances of the original data is a consequence of the Wiener-Khintchine theorem (Wiener, 1930; Khintchine, 1934; Prichard and Theiler, 1994; Weisstein, 2016); see further elaborations in Appendix A5. An important consequence of the above result is that a rejection of the null hypothesis could be due to the fMRI data being non-linear, non-Gaussian, non-WSS or any of the above.

Figure 3: Properties of original data preserved in autoregressive randomized (ARR) and phase randomized (PR) null data. By preserving the power spectral density of the original data, the Wiener-Khintchine theorem (Appendix A4) ensures that PR null data preserve the full original auto-covariance sequence $R_0, R_1, \ldots, R_{T-1}$ (Eq. (2)), where T is the number of time points. On the other hand, ARR null data generated from an AR(p) model (Eq. (3)) preserve the first $p+1$ terms of the auto-covariance sequence via the Yule-Walker equations (Appendix A2).

The relationship between ARR and PR is summarized in Figure 3. ARR preserves the first $p+1$ auto-covariances of the original data, while PR preserves the entire auto-covariance sequence. Therefore, if the original data is not

---

[2]The mean can always be added back to the null data hence there is no loss of generality to assume the original time courses were demeaned.

[3]Σ might not be a diagonal matrix, i.e., the noise does not need to be independent across brain regions.

[4]In statistical parlance, AR processes are dense in the class of linear Gaussian processes.

auto-correlated beyond p time points (i.e., $R_l = 0$ for l greater than p), then a p-th order ARR would be theoretically equivalent to PR, except for implementation details. Differences arising from implementation details should not be downplayed. For example, estimating the parameters of a p-th order AR model requires the original data to be at least of length $T = p \cdot (N + 1)$, where N is the number of brain regions. The implication is that a $(T - 1)$-th order ARR cannot be performed even if it is theoretically equivalent to PR. Another difference is that PR null data is only Gaussian for sufficiently long T (Tucker et al., 1984), while ARR does not have the constraint. On the other hand, ARR preserves the auto-covariance sequence for sufficiently long T, while PR preserves the entire auto-covariance sequence for any T. Yet another difference is that PR can only generate null data of the same length as the original data, while ARR can generate null data of arbitrary length, although in the case of dFC, we are typically interested in generating null data of the same length as the original data. As will be seen in the next sections, both approaches appear to yield similar conclusions in dFC analyses despite the practical differences.

4.4. WSS data can be rejected by ARR and PR

To demonstrate that rejection of the null hypothesis with ARR and PR null data does not imply non-stationarity, we consider the toy brain in the previous section (Figure. 2). Recall that the toy brain is a HMM with two brain regions and two brain states, but is WSS.

Figure 4 shows a single realization of this toy brain (Figure 4A), and corresponding first order ARR (Figure 4B) and PR (Figure 4C) null data. The blue and green time courses correspond to the signals of the two brain regions. The PR and ARR null data successfully replicate the auto-covariance sequence of the original time series. For example, the static functional connectivity (Pearson correlation) between the time courses of the two brain regions is equal to 0.35 in the original, ARR and PR data.

On the other hand, the SWC between the two regions in the original data (red line in Figure 4A) exhibit huge fluctuations with correlations close to 0.9 and -0.2 in states $S1$ and $S2$ respectively. However, there is little variation in SWC correlations for the null data (red lines in Figures 4A and 4B). Using the κ statistic (Eq. (1)), the null hypothesis is easily rejected.

This result is indeed good news because the implication is that using current methodologies, the null hypothesis can be rejected for a WSS brain with states assuming sufficient statistical power (e.g., the states have sufficiently distinct connectivity patterns and the sliding window is shorter than the average dwell time of a brain state, etc). However, the bad news is that a rejection of the null hypothesis does not imply the existence of brain states because the rejection might simply be due to a non-Gaussian process with no brain states. These considerations are unfortunately moot because experiments with real data (next section) suggest that the stationary linear Gaussian model

Figure 4: Examples of ARR and PR null time series generated from one realization of the two-state Hidden Markov Model (HMM) process with two brain regions. Time series of the two brain regions are shown in blue and light green (scale on the left vertical axis). The sliding window correlation (SWC) between the two time series (number of frames $T = 1200$, window size $w = 30$ frames) is shown in red (scale on the right vertical axis). (A) The original data exhibits sharp transitions in SWC. (B, C) The null data do not exhibit sharp transitions in SWC.

cannot be rejected for most low motion Human Connectome Project (HCP) participants.

5. Stationary linear Gaussian model cannot be rejected for most low motion subjects

In this section, we show that for most low-motion Human Connectome Project (HCP) participants, the stationary linear Gaussian model cannot be rejected. In addition, we show that one form of ARR used in the literature might result in false positives and should be utilized with care.

5.1. HCP data and SWC computation

We considered ICA-FIX fMRI data from the HCP S900 data release in fsLR surface space (Glasser et al., 2013; Smith et al., 2013a; Van Essen et al., 2013). Since motion can potentially introduce false positives in dFC (Laumann et al., 2016), our analyses were restricted to participants whose maximum framewise root mean square (FRMS) motion[5] was less than 0.2mm and maximum DVARS was smaller than 75. Among the four fMRI runs available for each HCP participant, the second run (REST1_RL) yielded the most participants (116) who survived these criteria and was therefore considered (the remaining runs were ignored). Of the 116 remaining participants (or runs), the top 100 participants with the smallest average FRMS were selected. Among these 100 low motion participants,

---

[5]Values were obtained from Movement_RelativeRMS.txt provided by HCP.

average FRMS of the second run ranged from 0.051mm to 0.073mm.

For each participant, the fMRI signal was averaged within each of 114 cortical ROIs (Yeo et al., 2011, 2015; Krienen et al., 2016) resulting in an 114×1200 matrix of fMRI data per participant. Following Zalesky et al. (2014), SWC was computed using a window size of 83 frames (59.76s), consistent with window sizes recommended in the literature (Leonardi and Van De Ville, 2015; Liégeois et al., 2016).

5.2. PR, multivariate ARR and bivariate ARR

For each participant, null fMRI data was generated using ARR (section 4.2) and PR (section 4.3). For the ARR procedure, the most common variant in the literature (Chang and Glover, 2010; Zalesky et al., 2014) involves estimating for each pair of brain regions, a 2×2 A_l matrix (Eq. (3)) for each temporal lag l (even though there are 114 ROIs). In other words, the resulting null time courses are generated for each pair of brain regions separately. We refer to this procedure as bivariate ARR. In contrast, multivariate ARR estimates a single 114×114 A_l matrix (Eq. (3)) for each lag l. For both multivariate ARR and bivariate ARR, an AR order of $p = 1$ was utilized. A larger order p did not affect our conclusions (see additional control analyses in section 5.6). For each procedure and each participant, 1999 null datasets were generated[6].

5.3. Most pairs of brain regions exhibit stationary, linear and Gaussian dynamics

We first tested if there exists "dynamic" connections in the human brain, defined as ROI pairs exhibiting greater SWC variance (Eq. (1)) than those from null data. To this end, for each participant and ROI pair, the observed SWC variance (computed from real data) was compared against the null distribution of SWC variance generated from the 1999 null datasets, resulting in one p value for each ROI pair[7]. Within each participant, multiple comparisons were corrected by applying a false discovery rate (FDR) of $q < 0.05$ to the 6441 p values.

Figure 5 illustrates the number of significant ROI pairs across the 100 participants. For both multivariate ARR and PR, 57% of the participants have 0 significant edges. On average (across 100 participants), 36.8 and 34.2 edges were significant with multivariate ARR and PR respectively. Therefore a stationary linear Gaussian model was able to reproduce the SWC fluctuations of more than 99.4% of ROI pairs.

Figure 5: Number of edges in each participant exhibiting significantly greater SWC variance than (i) phase randomized (PR) null data, (ii) multivariate ARR null data and (iii) bivariate ARR null data. On average (across 100 participants), less than 40 (out of 6441) edges were statistically significant for PR and multivariate ARR. For bivariate ARR, 306.7 edges were statistically significant on average (across 100 participants).

On the other hand, for bivariate ARR, 21% of the participants have 0 significant edges. On average (across 100 participants), 306.7 edges were significant. In other words, bivariate ARR tends to be less strict in terms of rejecting the null hypothesis. We will return to this point in Section 5.5.

5.4. For almost all low-motion HCP subjects, coherent brain dynamics are stationary, linear and Gaussian

Existence of *coherent* SWC fluctuations was tested using the approach of the pioneering dFC paper (Zalesky et al., 2014). More specifically, this approach involves computing the SWC time series for all ROI pairs and then selecting the top 100 most dynamic SWC time series as measured by the SWC variance (Eq. (1)). The percentage variance explained by the top principal component of these 100 SWC time series was utilized as a test statistic (Zalesky et al., 2014). A high percentage variance would imply the existence of coherent SWC fluctuations across the 100 pairs of brain regions. The percentage variance computed from real data was compared against the null distribution from 1999 null datasets, resulting in one p value for each participant. Multiple comparisons across participants were corrected using a FDR of $q < 0.05$.

Figure 6 illustrates data from a representative HCP subject, as well as one single representative null data from PR, first order multivariate ARR and eleventh order bivariate ARR. The order of the bivariate ARR was chosen to match Zalesky et al. (2014). The top 100 most dynamic SWC time series (blue lines in Figure 6) exhibited massive fluctuations in the representative participant (Figure 6A) and corresponding null data (Figure 6B-6D). In the representative participant (Figure 6A), PR (Figure 6B), multivariate ARR (Figure 6C) and bivariate ARR (Figure

---

[6] There were 1999 (and not 2000) null datasets because the real data is also counted as a dataset when computing p values, so that a p value of 0 is impossible.

[7] Since there were 114 ROIs, each null dataset generated 6441 $(= 114(114 - 1)/2)$ null values, which were pooled across the cortex into a single, highly-resolved null distribution (Zalesky et al., 2014). In other words, for a given participant, all the ROI pairs shared the same null distribution.

Figure 6: Sliding window correlations (SWC) of a representative low motion HCP subject (left) and example null data from phase randomization (PR - middle left), multivariate ARR (middle right) and bivariate ARR (right). The 100 most dynamic SWC time series are shown in blue, while their first principal component is shown in red. The percentage variance explained by the first principal component measures the coherence of brain dynamics. For the representative subject shown here, the percentage variance of the original data, PR, multivariate ARR and bivariate AR were 62%, 58%, 66% and 11% respectively. Therefore the coherence of brain dynamics was statistically indistinguishable among real data, PR and multivariate ARR, while bivariate ARR null data exhibited significantly less coherent brain dynamics.

6D), the first principal component of the 100 SWC time series (red line in Figure 6) accounted for 62%, 58%, 66% and 11% of the variance respectively.

On average (across 100 participants), the first principal component explained 49%, 46%, 45% and 10% variance in real data, PR, multivariate ARR and bivariate ARR respectively (Figure S1). For PR and multivariate ARR null data, the null hypothesis was rejected for only one participant. Therefore the stationary linear Gaussian model reproduces *coherent* SWC fluctuations for 99% of the low motion HCP participants. For bivariate ARR, the null hypothesis was rejected for all the participants. This discrepancy is discussed in the following section.

5.5. Why bivariate ARR might generate false positives

The previous two sections suggest that bivariate ARR commonly used in the literature (Chang and Glover, 2010; Zalesky et al., 2014) might be susceptible to false positives. To understand why this might occur, let us consider the toy example illustrated in Figure 7. In this toy example, there are three brain regions X, Y and Z, whose signals follow a first order AR model (Figure 7A). With the multivariate ARR procedure, the AR parameters were estimated using the time series from all three brain regions. The estimated AR parameters (Figure 7B) were the same as the true parameters (Figure 7A). As illustrated in Figure 7B, there is no arrow directly connecting brain regions Y and Z. In other words, brain regions Y and Z only influence each other via brain region X.

On the other hand, the bivariate ARR procedure estimates AR parameters separately for brain regions X and Y, brain regions X and Z, and brain regions Y and Z. The estimated parameters (Figure 7C) are generally different from the true AR parameters (Figure 7A). More specifically, brain regions Y and Z exert direct influence on each other (which is non-existent under the true model).

When generating null data using multivariate ARR, the time course at brain region X is generated by taking into account the influence of both brain regions Y and Z (Figure 7B). However, in the bivariate ARR procedure, the time course at brain region X is generated by taking into account the influence of only brain region Y (left panel of

A   True AR model

$$\begin{pmatrix} X_t \\ Y_t \\ Z_t \end{pmatrix} = \begin{pmatrix} 0.3 & 0.4 & -0.5 \\ 0.4 & 0.3 & 0 \\ -0.5 & 0 & 0.3 \end{pmatrix} \cdot \begin{pmatrix} X_{t-1} \\ Y_{t-1} \\ Z_{t-1} \end{pmatrix} + \epsilon(t)$$

B   Multivariate ARR parameter estimates

C   Bivariate ARR parameter estimates

Figure 7: (A) Example AR model with three regions X, Y and Z. (B) AR model parameters estimated by considering the data from all three regions jointly (i.e., multivariate ARR). True AR parameters were recovered. (C) AR model parameters estimated for each pair of regions (i.e., bivariate ARR). Wrong AR parameters were recovered. In particular, direct interactions between regions Y and Z (red in figure) were found, which were non-existent in the true model.

Figure 7C) or brain region Z (center panel of Figure 7C), but not both. Therefore bivariate ARR neglects influence among all brain regions, thus resulting in null data that are less "dynamic".

Furthermore, since bivariate ARR estimates the AR parameters for each pair of brain regions separately, any coherence among pairs of brain regions is destroyed. Consequently, the false positive situation appeared more severe when evaluating the existence of coherent brain dynamics (section 5.4) than when evaluating the existence of "dynamic" connections (section 5.3).

5.6. Control analyses

To ensure the results are robust to the particular choice of parameters, the sliding window size was varied from 20

frames to 100 frames, and the AR model order p was varied from 1 to 8. When evaluating coherence of whole brain dynamics, the number of most dynamic connections was also varied from 20 to 200. Since thresholding by DVARS might artificially exclude "real" dynamics, we also considered all the HCP subjects, rather than just the top 100 participants with least motion and DVARS. None of these changes significantly affected the results. Surprisingly, AR models of orders ranging from 1 to 8 explained similar variations in SWC fluctuations (Figure S2). However, AR model of order 0 (i.e., only preserving R_0 or static FC) could not explain SWC fluctuations (Figure S2). Since our results might be sensitive to the choice of test statistic, the nonlinear statistic utilized in Zalesky et al. (2014) was also considered. We found that it was even more difficult to reject the null hypothesis using this nonlinear statistic.

Finally, some authors have suggested that regressing mean grayordinate signal (akin to global signal regression) in addition to ICA-FIX might be necessary to remove global noise artifacts (Burgess et al., 2016; Siegel et al., 2016). When mean grayordinate signal was regressed, the SWC fluctuations were even less statistically significant. For example, when evaluating the existence of coherent brain dynamics, the null hypothesis was not rejected for all 100 participants (Figure S3).

6. Stationary linear Gaussian models explain SWC fluctuations better than HMM

Section 5 suggests that distinguishing the linear stationary Gaussian model from real fMRI data is difficult (at least for the statistics tested). However, failure to reject the null hypothesis could be due to a lack of statistical power, rather than the null hypothesis being true. It is entirely possible that HMM-type models (Allen et al., 2014; Wang et al., 2016) might generate null data that fit observed fluctuations in SWC better than the linear stationary Gaussian model.

To test this possibility, Figure 8A shows the $T \times T$ functional connectivity dynamics (FCD) matrix of a representative HCP participant, where the i-th row and j-th column of the FCD matrix corresponds to the correlation between the SWC of time points i and j (Hansen et al., 2015). The presence of relatively large off-diagonal entries (yellow in Figure 8A) suggest the presence of recurring SWC patterns.

The PR (Figure 8B) and first-order multivariate ARR (Figure 8C) null data were able to replicate the rich dynamics of the empirical FCD matrix (Figure 8A), while first-order bivariate ARR null data (Figure 8D) exhibited significantly weaker recurring SWC patterns. By contrast, the 3-state HMM null data[8] (Figure 8E) exhibited recur-

ring SWC patterns with much sharper transitions than real data (Figure 8A).

To quantify these differences, the FCD matrices of the four null data generation approaches (Figure 8B-E) were compared with the empirical FCD matrix (Figure 8A) using the Kolmogorov-Smirnov statistic (Figure S4). Both the PR null data and (first-order) multivariate ARR null data fitted the empirical FCD matrix better than the HMM null data (two-sample t-test $p < 1e$-32 and $p < 1e$-30 respectively).

11 states were necessary for the HMM model to perform as well as first-order multivariate ARR (Figure S4). However, visual inspection of the FCD matrix (Figure S5A) suggests that the 11-state HMM still generated SWC patterns with sharper transitions than real data. The results were replicated (Figure S6) in the one subject for whom the stationary, linear, Gaussian null hypothesis was rejected in Section 5.4. For completeness, Figures S4 and S5B show the FCD results replicated with the Laumann null data generation approach (Laumann et al., 2016).

7. Discussion

In this commentary, we seek to improve our understanding of observed fluctuations in resting-state FC (e.g., SWC) widely reported in the literature. These fluctuations have often been interpreted as dynamic changes in inter-regional functional interactions, and non-stationary switching of discrete brain states (e.g. Allen et al., 2014). However, several recent papers have questioned these interpretations, especially in the case of single subject fMRI data (Hindriks et al., 2016; Laumann et al., 2016).

7.1. Linking Stationarity, dFC and brain states

By reviewing the conceptualization of fMRI as a random process (Section 2), we highlight that many statistical notions, such as *ensemble* auto-covariance and WSS, are reliant on ensemble statistics. Ensemble statistics are defined by taking into account an infinite number of realizations of a random process. However, the fMRI data of multiple participants are often considered as single realizations of different random processes. Therefore all FC measures in the literature are actually based on sample statistics (i.e., statistics based on one realization), but not ensemble statistics. It is possible that in the case of fMRI, ensemble statistics are equal to sample statistics. However, in this scenario, fMRI would be ergodic, which would in turn imply that fMRI is WSS.

---

[8]Following popular approaches (Allen et al., 2014; Wang et al., 2016), SWC of the representative participant were clustered into two states using kmeans. Probability of transitioning between states were

estimated based on the state assignment by kmeans. Timepoints assigned to the same state was utilized to estimate the mean and covariance matrix of a multivariate Gaussian distribution using maximum likelihood. The estimated model parameters were then used to generate null data. It is worth noting that the 3-state HMM has roughly the same number of parameters as a first-order multivariate AR model.

Figure 8: PR and multivariate ARR can replicate rich SWC dynamics of real data. Each plot is a $T \times T$ functional connectivity dynamics (FCD) matrix, where the i-th row and j-th column of the matrix corresponds to the correlation between the SWC of time points i and j matrix. (A) Representative HCP subject, (B) PR null data, and (C) first-order multivariate ARR null data exhibit recurring SWC patterns. (D) Bivariate ARR null data exhibits weak recurring SWC patterns. (E) 3-state HMM null data exhibits sharp SWC transitions not present in original data. Here the FCD matrices were computed based on a parcellation into 114 ROIs (Yeo et al., 2011, 2015).

Because the definition of WSS involves ensemble statistics, it is possible to come up with a toy brain with discrete brain states (i.e., HMM process) that is both WSS and ergodic (Section 3). Given that a WSS process can exhibit sharp transitions in SWC (Figure 2), this suggests that observed fluctuations in functional connectivity are not necessarily evidence of a non-stationary system.

The loose use of the term "non-stationarity" in the literature is not merely a linguistic issue, but can lead to potential confusion because current dFC statistical testing approaches rely on frameworks from the physics and statistics communities utilizing strict statistical notions, including stationarity (e.g. Schreiber and Schmitz, 2000). This motivates our detailed exploration of the assumptions behind the popular ARR and PR frameworks for generating null data for hypothesis testing of dFC.

It is possible that the dFC community might not be referring to "non-stationarity" in the statistical sense. However, the widely used null hypothesis testing frameworks (ARR and PR) do rely on traditional statistical notions of stationarity. Therefore it is important for the community to articulate the exact statistical notions (e.g., piecewise stationarity; Nason (2013)) that might encode the intuitive notion of "non-stationarity" mentioned in the dFC literature. Having the exact statistical notions will lead to better null hypothesis testing frameworks.

7.2. Preserving auto-covariance beyond static FC

Our review of ARR and PR frameworks (Section 4) shows that both approaches retain the 0-th sample auto-covariance (R_0 in Eq (2)) of the original fMRI data. R_0 can be interpreted as *static* FC (being an unnormalized variant of Pearson's correlation). Therefore R_0 is an important quantity to preserve in null data since the dFC researcher is presumably interested in showing that dFC cannot be completely explained by static FC.

Preserving R_0 (static FC) can be easily achieved by permuting the temporal ordering of fMRI time points. However, such a procedure ignores well-known autocorrelation in the original fMRI data, which will lead to false

positives in null hypothesis testing. Both PR and ARR seek to preserve auto-correlations in addition to R_0. More specifically, PR preserves the entire *sample* auto-covariance sequence ($R_0, \cdots R_{T-1}$ in Eq (2)) of the original fMRI data, while ARR of order p preserves only the first $p + 1$ terms of the auto-covariance sequence ($R_0, \cdots R_p$). For example, ARR of order 1 preserves R_0 and R_1.

Since PR preserves higher order auto-covariances than ARR, it might be theoretically advantageous. However, in our experiments, PR and multivariate ARR of order 1 were able to explain observed SWC in real fMRI data equally well (Figures 5, 6 and 8). On the other hand, ARR of order 0 (i.e., only R_0 or static FC is preserved) does not explain SWC fluctuations at all (Figure S2). The implication is that fluctuations in SWC can largely be explained by taking into account auto-covariances of lag 0 (i.e., static FC or R_0) and lag 1 (i.e., R_1) from the original fMRI data.

7.3. Null data generation in the literature

Understanding why ARR and PR are able to preserve sample auto-covariances of the original data (Figure 3) is useful for interpreting other null data generation approaches in the literature. For example, Allen et al. (2014) applies the PR framework directly on the sliding window FC time series, and not on the fMRI time series. Therefore in the case where the same random phase sequence was added to all dFC phase spectra (i.e., SR1 in Allen et al., 2014), the null dFC time series have the same auto-covariance sequence as the original dFC time courses, but not the auto-covariance of the original fMRI time courses. Therefore the tested null hypothesis is similar, but not the same as other papers that applied PR to the fMRI time series (Handwerker et al., 2012; Hindriks et al., 2016).

More recently, Laumann et al. (2016) proposed a procedure to generate null data that matches the static FC (R_0) and the power spectral density of the original fMRI data (averaged across ROIs). Given the deep relationship between the auto-covariance sequence and cross-spectral density of the original fMRI data (Appendix A5), preserving the average power spectral density retain some (but

not all) information of the original fMRI auto-covariance structure *beyond* static FC. The advantage of the Laumann (and PR) approaches over multivariate ARR is that the number of fitted parameters does not increase quadratically with the number of ROIs. This allows the generation of null data with large number of ROIs for which multivariate AR model parameters cannot be estimated (see Appendix A2). However, because the Laumann approach preserved fewer properties of the original data than PR or multivariate ARR, one might expect the Laumann null data to be less close to real data than PR or multivariate ARR. Indeed, this expectation is empirically confirmed in Figures S4 and S5B. On the other hand, these results also suggest that compared with bivariate ARR, the Laumann procedure generated null data that were more similar to real data.

ARR have also been widely used in neuroimaging applications, mostly following the bivariate variant proposed by Chang and Glover (2010). Our results suggest that bivariate ARR neglects higher-order interactions (Figure 7), resulting in wrongly estimated AR model parameters, potentially leading to false positives. The issue with wrongly estimated AR model parameters is reminiscent of Friston's criticism of functional connectivity (Friston, 2011), where two regions A and B might be functionally connected because of mutual effective connectivity with an intermediary region C. However, it should be noted that AR models are not effective connectivity models because of the lack of hemodynamic modeling (Friston, 2009).

The false positive rate associated with bivariate ARR is less serious when investigating the existence of individual "dynamic" edges (Figure 5), but extreme when investigating the coherence of SWC across dynamic pairs of brain regions. More specifically, when investigating SWC coherence, the null hypotheses for all participants were rejected using bivariate ARR, compared with only one participant for multivariate ARR or PR (Figures 6 and S1).

7.4. The stationary, linearity, Gaussian null hypothesis

Our review suggests that PR and ARR generate null data that are linear, WSS and Gaussian (Section 4). Conversely, any linear Gaussian process can be arbitrarily well approximated by an AR model of sufficiently large order p. Together, this implies that if the original time series significantly differ from ARR or PR null data, then the original data is non-Gaussian or nonlinear or non-stationary. For example, the null hypothesis was easily rejected for the WSS two-state toy brain (Figure 4) due to nonlinearity and non-Gaussianity, rather than non-stationarity.

Nevertheless, this ambiguity is less of an issue because our results also suggest that the stationary linear Gaussian null hypothesis cannot be rejected for most low-motion HCP participants (Section 5). On average (across participants), the stationary linear Gaussian null hypothesis can only be rejected for 0.6% of brain region pairs (Figure 5) when using PR and multivariate ARR. When studying dFC coherence, the stationary linear Gaussian null

hypothesis was only rejected for 1% of the participants (Figures 6, S1 and S2).

The difficulty in rejecting the null hypothesis is somewhat surprising given that the brain is a complex organ possessing nonlinear neuronal dynamics (e.g., Hodgkin and Huxley, 1952; Valdes et al., 1999; Deco et al., 2008; Stephan et al., 2008; Deco et al., 2011). However, our results are consistent with previous literature reporting difficulties to reject the null model, especially in single subject fMRI data (Hindriks et al., 2016; Laumann et al., 2016). A close look at the dFC literature suggests similar difficulties in seminal dFC papers. For example, dFC states were found using null data generated by adding the same random phase sequence to all dFC phase spectra during PR (i.e., SR1 in Allen et al., 2014). Similarly, Zalesky and colleagues (Zalesky et al., 2014) reported that on average across subjects, the null hypothesis was rejected for only 4% of edges when using bivariate ARR, which is highly consistent with our bivariate ARR results, where 5% of edges were rejected. Therefore, the dFC literature is consistent in finding only small deviations from the stationary, lineary, Gaussian null hypothesis. Much of the controversy might be due to differences in the interpretation, i.e., viewing the glass as half-full or half-empty.

For the small minority of edges or participants whose null hypothesis is rejected, it is unclear whether this deviation is due to non-stationarity, non-linearity or non-Gaussianity. It is also unclear whether these deviations are due to artifacts (e.g., respiration; Laumann et al., 2016; Power et al., 2017) or biologically meaningful. One approach of demonstrating biological relevance is by association with behavior or disease. While there are many studies linking dFC measures (e.g., SWC, dwell time of brain states, etc) with behavior and diseases (Damaraju et al., 2014; Barttfeld et al., 2015; Su et al., 2016; Du et al., 2016; Nomi et al., 2017; Shine et al., 2016; Wang et al., 2016), there are far fewer studies explicitly demonstrating that dFC measures are able to explain behavioral measures or disease status above and beyond static FC (e.g. Rashid et al., 2014). Moreover, to the best of our knowledge, we are unaware of any studies showing dFC-behavioral associations above and beyond the stationary, linear and Gaussian model. Therefore, for studies demonstrating that their dFC measures are more strongly associated with behavior than static FC (e.g. Rashid et al., 2014), the improvement might potentially be explained by the AR model, which encodes both static FC (R_0) and linear dynamical interactions between brain regions (R_1, etc)

7.5. Does dynamic functional connectivity exist?

Does stationarity, linearity and gaussianity of fMRI time series imply that dFC is spurious? Obviously, if dFC is strictly defined as non-WSS (Section 2.2), then stationarity does imply the lack of dFC. However, Section 3 suggests that such a definition of dFC would exclude a class of signals (e.g., HMM) that most neuroscientists would think

of as encoding dFC. Therefore alternative definitions of dFC should be considered.

If dFC is thought of as corresponding to the brain sharply switching between discrete states with distinct FC patterns, then our results suggest a lack of evidence in resting-state fMRI. The presence of HMM-type states could potentially lead to the rejection of the stationary linear Gaussian null hypothesis (Section 3). However, the null hypothesis was not rejected for most low motion HCP participants (Section 5). This non-rejection could be due to a lack of statistical power. Therefore we tested whether an HMM-type model explicitly encoding the presence of states would fit SWC fluctuations better than AR (or PR) models. We found that ARR and PR reproduced the gentle fluctuations of recurring SWC patterns in real data, whereas sharp transitions were observed in the HMM (Figure 8). This result was replicated (Figure S6) in the one subject for whom the stationary linear Gaussian model was rejected (Section 5.4). Altogether, this suggests the lack of discrete brain states, which is consistent with some proposals that SWC might be better explained by a mixture of states (Leonardi et al., 2014).

If dFC is thought of as the existence of FC information beyond static FC, then our results do support the existence of dFC because multivariate AR models explained SWC fluctuations significantly better than just static FC (Figure S2). Indeed, AR models are often considered models of linear dynamical systems (e.g. Casti, 1986; Gajic, 2003). By encoding linear dynamical interactions between brain regions (A_1 in Eq. (3)), the first order AR model captures both static FC (i.e., R_0 in Eq. (2)) and temporal FC structure (i.e., R_1 in Eq. (2)). It is worth reminding the readers that the diagonal elements of R_1 encode the auto-correlation within individual brain regions, while the off-diagonal terms encode lagged cross-covariance between brain regions. Since the Laumann null data generation approach (Laumann et al., 2016) explicitly preserves static FC and temporal autocorrelation, but did not explain SWC as well as first order AR models (Figure S5), this suggests the importance of the off-diagonal entries of R_1, i.e., lagged cross-covariance between brain regions. The importance of such resting-state lagged cross-covariances has been described in humans (Mitra et al., 2014; Raatikainen et al., 2017) using fMRI and in animals using a variety of electrophysiological techniques (Mohajerani et al., 2013; Stroh et al., 2013; Matsui et al., 2016); for review, see Mitra and Raichle (2016).

Finally, if dFC refers to the presence of biological information in FC fluctuations, then recent evidence suggests that FC fluctuations within a single fMRI session can be linked to varying level of vigilance (Wang et al., 2016). Others have shown that fluctuation in activity level fluctuations might also be associated with arousal (Chang et al., 2016) or attention (Kucyi et al., 2016). However, it is currently unclear whether behavioral fluctuations might be more readily explained by fluctuating activity level (first order statistics) or fluctuating FC (second order statis-

tics). To see that stationary, linear, Gaussian fMRI does not necessarily contradict the previously mentioned studies, consider the following toy example. Suppose Alice and Bob plays a game, where Alice tosses a fair coin at each round of the game. Every time the coin toss results in a head, Alice pays Bob a dollar. Every time the coin toss results in a tail, Bob pays Alice a dollar. We can see that the coin tosses do not possess any interesting dynamics: the coin tossing is a stationary process and temporally independent. However, the outcomes of the coin toss are still financially (behaviorally) relevant.

7.6. Future directions

Rather than arguing about the existence of dFC, it might be more useful to re-frame this debate in terms of adequate models of fMRI time series: (i) what kind of model reproduces properties of fMRI (and dFC) time series and (ii) what types of FC fluctuations (shapes, timescales) are expected in these models? This framing sidesteps the question of whether dFC exists, but instead relies on mathematical models, from which principled predictions and interpretations might provide further insights into human brain organization.

Given the ability of AR (and PR) models to generate realistic SWC, rather than treating them as just null models, AR models could themselves be utilized to provide insights into the brain. Since more complex models are harder to interpret, they should not be preferred unless existing models could not fit some important aspect of fMRI data. For example, since models of static FC cannot explain SWC dynamics very well (Figure S4), it is clear that first order multivariate AR model is preferable for a researcher interested in dFC. The next step would be to show that the additional dynamics modeled by AR model (above and beyond static FC) is functionally meaningful, such as by association with behavior or disease.

Since this commentary only focuses on SWC and several statistics (Sections 5.3, 5.4 and 6), it is possible that stationary linear gaussian models are unable to explain other unexamined aspects of fMRI dynamics captured by other statistics (Maiwald et al., 2008; Griffa et al., 2017). In these cases, more complex generative models, such as those involving mixture of states (Leonardi et al., 2014) or wavelets (Breakspear et al., 2004; Van De Ville et al., 2004), might be necessary. However, more complex and biophysically realistic models might not necessarily explain fMRI dynamics better. For example, the use of the FCD matrices (Figure 8) to visualize the rich SWC dynamics was pioneered by Hansen et al. (2015), who demonstrated that nonlinear biophysical (neural mass) models could replicate some of the rich SWC dynamics, while a linear stochastic model was not able to. The linear stochastic model utilized by Hansen and colleagues is essentially the same as the first order AR model utilized here. However, the linear stochastic model was utilized to model neural dynamics, rather than fMRI data directly. The "output"

of the linear neural model was then fed into a biophysical hemodynamic response model to generate fMRI data. Importantly, the interactions between brain regions were set to be the diffusion connectivity matrix, rather than fitted to real fMRI data. Consequently, the linear stochastic model (Hansen et al., 2015) did not exhibit the rich dynamics observed in this commentary (Figure 8). Because of the difficulties in estimating the parameters of the nonlinear neural mass models, it is unclear whether an optimized neural mass model might be able to explain FC fluctuations better than a first order multivariate AR model.

A recurring criticism of AR modeling of fMRI time series is that the model parameters cannot be interpreted as effective connectivity because spatial variability of the hemodynamic response function is usually not taken into account (e.g. Friston, 2009). Hence other generative models such as dynamic causal modelling should be preferred if one wants to study effective connectivity (Friston et al., 2003). However, this does not preclude the use of AR models as a diagnostic tool encoding functional connectivity information beyond static FC (Rogers et al., 2010). An obvious challenge will then be to extract the most relevant information from these models (Liégeois et al., 2015; Ting et al., 2016).

8. Conclusion

In this commentary, we explore statistical notions relevant to the study of dynamic functional connectivity. We demonstrate the existence of a stationary process exhibiting discrete states, suggesting that stationarity does not imply the absence of brain states. Our review of two popular null data generation frameworks (PR and ARR) suggests that rejection of the null hypothesis indicates non-stationarity or nonlinearity or non-Gaussianity. We show that most HCP participants possess stationary, linear and Gaussian fMRI during the resting-state. Furthermore, AR models explain real fMRI data better than just static FC, and a popular approach that explicitly models brain states. Overall, the results suggest a lack of evidence for discrete brain states (as measured by fMRI SWC), as well as the existence of FC information beyond static FC. Therefore dFC is not necessarily spurious because AR models are themselves linear dynamical models, encoding temporal auto-covariance above and beyond static FC. Given the ability of AR models to generate realistic fMRI data, AR models might be well suited for exploring the dynamical properties of fMRI. Finally, our results do not contradict recent studies showing that temporal fluctuations in functional connectivity or activity level can be behaviorally meaningful. The code used for this work are available at GITHUB_LINK_TO_BE_ADDED.

Acknowledgements

The authors thank Andrew Zalesky for important perspectives and feedback on this work. This work was supported by Singapore MOE Tier 2 (MOE2014-T2-2-016), NUS Strategic Research (DPRT/944/09/14), NUS SOM Aspiration Fund (R185000271720), Singapore NMRC (CB RG/0088/2015), NUS YIA, and Singapore NRF fellowship (NRF-NRFF2017-06). RL is also supported by a Wallonie-Bruxelles International-WORLD Excellence Fellowship. Data were provided by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University.

References

Allen, E. A., E. Damaraju, S. M. Plis, E. B. Erhardt, T. Eichele, and V. D. Calhoun
2014. Tracking whole-brain connectivity dynamics in the resting state. *Cerebral cortex*, 24(3):663–676.

Barttfeld, P., L. Uhrig, J. D. Sitt, M. Sigman, B. Jarraya, and S. Dehaene
2015. Signature of consciousness in the dynamics of resting-state brain activity. *Proceedings of the National Academy of Sciences*, 112(3):887–892.

Baum, L. E. and T. Petrie
1966. Statistical inference for probabilistic functions of finite state markov chains. *The annals of mathematical statistics*, 37(6):1554–1563.

Biswal, B., F. Z. Yetkin, V. M. Haughton, and J. S. Hyde
1995. Functional connectivity in the motor cortex of resting human brain using echo-planar mri. *Magnetic resonance in medicine*, 34:537–541.

Breakspear, M., M. J. Brammer, E. T. Bullmore, P. Das, and L. M. Williams
2004. Spatiotemporal wavelet resampling for functional neuroimaging data. *Human brain mapping*, 23(1):1–25.

Buckner, R. L., F. M. Krienen, and B. T. Yeo
2013. Opportunities and limitations of intrinsic functional connectivity mri. *Nature neuroscience*, 16(7):832–837.

Buckner, R. L., J. Sepulcre, T. Talukdar, F. M. Krienen, H. Liu, T. Hedden, J. R. Andrews-Hanna, R. A. Sperling, and K. A. Johnson
2009. Cortical hubs revealed by intrinsic functional connectivity: mapping, assessment of stability, and relation to alzheimer's disease. *The Journal of neuroscience : the official journal of the Society for Neuroscience*, 29:1860–1873.

Burgess, G. C., S. Kandala, D. Nolan, T. O. Laumann, J. D. Power, B. Adeyemo, M. P. Harms, S. E. Petersen, and D. M. Barch
2016. Evaluation of denoising strategies to address motion-correlated artifacts in resting-state functional magnetic resonance imaging data from the human connectome project. *Brain connectivity*, 6(9):669–680.

Calhoun, V. D., R. Miller, G. Pearson, and T. Adalı
2014. The chronnectome: time-varying connectivity networks as the next frontier in fmri data discovery. *Neuron*, 84(2):262–274.

Casti, J. L.
1986. *Linear dynamical systems*. Academic Press Professional, Inc.

Chai, B., D. Walther, D. Beck, and L. Fei-Fei
2009. Exploring functional connectivities of the human brain using multivariate information analysis. In *Advances in neural information processing systems*, Pp. 270–278.

Chang, C. and G. H. Glover
2010. Time–frequency dynamics of resting-state brain connectivity measured with fmri. *Neuroimage*, 50(1):81–98.

Chang, C., D. A. Leopold, M. L. Schölvinck, H. Mandelkow, D. Picchioni, X. Liu, F. Q. Ye, J. N. Turchi, and J. H. Duyn
2016. Tracking brain arousal fluctuations with fmri. *Proceedings of the National Academy of Sciences of the United States of America*, 113(16):4518–4523.

Damaraju, E., E. Allen, A. Belger, J. Ford, S. McEwen, D. Mathalon, B. Mueller, G. Pearson, S. Potkin, A. Preda, et al.
2014. Dynamic functional connectivity analysis reveals transient states of dysconnectivity in schizophrenia. *NeuroImage: Clinical*, 5:298–308.

Damoiseaux, J., S. Rombouts, F. Barkhof, P. Scheltens, C. Stam, S. M. Smith, and C. Beckmann
2006. Consistent resting-state networks across healthy subjects. *Proceedings of the national academy of sciences*, 103(37):13848–13853.

Deco, G., V. K. Jirsa, and A. R. McIntosh
2011. Emerging concepts for the dynamical organization of resting-state activity in the brain. *Nature Reviews Neuroscience*, 12(1):43–56.

Deco, G., V. K. Jirsa, P. A. Robinson, M. Breakspear, and K. Friston
2008. The dynamic brain: from spiking neurons to neural masses and cortical fields. *PLoS Comput Biol*, 4(8):e1000092.

Dosenbach, N. U., D. A. Fair, F. M. Miezin, A. L. Cohen, K. K. Wenger, R. A. Dosenbach, M. D. Fox, A. Z. Snyder, J. L. Vincent, M. E. Raichle, et al.
2007. Distinct brain networks for adaptive and stable task control in humans. *Proceedings of the National Academy of Sciences*, 104(26):11073–11078.

Du, Y., G. D. Pearson, Q. Yu, H. He, D. Lin, J. Sui, L. Wu, and V. D. Calhoun
2016. Interaction among subsystems within default mode network diminished in schizophrenia patients: A dynamic connectivity approach. *Schizophrenia research*, 170(1):55–65.

Efron, B. and R. Tibshirani
1986. Bootstrap methods for standard errors, confidence intervals, and other measures of statistical accuracy. *Statistical science*, Pp. 54–75.

El-Shaarawi, A. H. and W. W. Piegorsch
2013. Encyclopedia of environmetrics.

Fox, M. D., A. Z. Snyder, J. L. Vincent, and M. E. Raichle
2007. Intrinsic fluctuations within cortical systems account for intertrial variability in human behavior. *Neuron*, 56(1):171–184.

Fox, M. D., A. Z. Snyder, J. M. Zacks, and M. E. Raichle
2006. Coherent spontaneous activity accounts for trial-to-trial variability in human evoked brain responses. *Nature neuroscience*, 9(1):23–25.

Fransson, P. and G. Marrelec
2008. The precuneus/posterior cingulate cortex plays a pivotal role in the default mode network: Evidence from a partial correlation network analysis. *Neuroimage*, 42(3):1178–1184.

Friston, K.
2009. Causal modelling and brain connectivity in functional magnetic resonance imaging. *PLoS biol*, 7(2):e1000033.

Friston, K. J.
2011. Functional and effective connectivity: a review. *Brain connectivity*, 1(1):13–36.

Friston, K. J., L. Harrison, and W. Penny
2003. Dynamic causal modelling. *Neuroimage*, 19(4):1273–1302.

Gajic, Z.
2003. *Linear dynamic systems and signals*. Prentice Hall – Pearson Education.

Glasser, M. F., S. N. Sotiropoulos, J. A. Wilson, T. S. Coalson, B. Fischl, J. L. Andersson, J. Xu, S. Jbabdi, M. Webster, J. R. Polimeni, et al.
2013. The minimal preprocessing pipelines for the human connectome project. *Neuroimage*, 80:105–124.

Greicius, M. D., B. Krasnow, A. L. Reiss, and V. Menon
2003. Functional connectivity in the resting brain: a network analysis of the default mode hypothesis. *Proceedings of the National Academy of Sciences*, 100(1):253–258.

Griffa, A., B. Ricaud, K. Benzi, X. Bresson, A. Daducci, P. Vandergheynst, J.-P. Thiran, and P. Hagmann
2017. Transient networks of spatio-temporal connectivity map communication pathways in brain functional systems. *NeuroImage – In Press*.

Handwerker, D. A., V. Roopchansingh, J. Gonzalez-Castillo, and P. A. Bandettini
2012. Periodic changes in fmri connectivity. *Neuroimage*, 63(3):1712–1719.

Hansen, E. C., D. Battaglia, A. Spiegler, G. Deco, and V. K. Jirsa
2015. Functional connectivity dynamics: modeling the switching behavior of the resting state. *Neuroimage*, 105:525–535.

Hindriks, R., M. H. Adhikari, Y. Murayama, M. Ganzetti, D. Mantini, N. K. Logothetis, and G. Deco
2016. Can sliding-window correlations reveal dynamic functional connectivity in resting-state fmri? *Neuroimage*, 127:242–256.

Hodgkin, A. L. and A. F. Huxley
1952. A quantitative description of membrane current and its application to conduction and excitation in nerve. *The Journal of physiology*, 117(4):500.

Hutchison, R. M., T. Womelsdorf, E. A. Allen, P. A. Bandettini, V. D. Calhoun, M. Corbetta, S. Della Penna, J. H. Duyn, G. H. Glover, J. Gonzalez-Castillo, et al.
2013a. Dynamic functional connectivity: promise, issues, and interpretations. *Neuroimage*, 80:360–378.

Hutchison, R. M., T. Womelsdorf, J. S. Gati, S. Everling, and R. S. Menon
2013b. Resting-state networks show dynamic functional connectivity in awake humans and anesthetized macaques. *Human brain mapping*, 34(9):2154–2177.

Karahanoğlu, F. I. and D. Van De Ville
2015. Transient brain activity disentangles fmri resting-state dynamics in terms of spatially and temporally overlapping networks. *Nature communications*, 6.

Khintchine, A.
1934. Korrelationstheorie der stationaryren stochastischen prozesse. *Mathematische Annalen*, 109(1):604–615.

Krienen, F. M., B. T. Yeo, T. Ge, R. L. Buckner, and C. C. Sherwood
2016. Transcriptional profiles of supragranular-enriched genes associate with corticocortical network architecture in the human brain. *Proceedings of the National Academy of Sciences*, 113(4):E469–E478.

Kucyi, A., M. J. Hove, M. Esterman, R. M. Hutchison, and E. M. Valera
2016. Dynamic brain network correlates of spontaneous fluctuations in attention. *Cerebral Cortex*, 27(3):1831 – 1840.

Laumann, T. O., A. Z. Snyder, A. Mitra, E. M. Gordon, C. Gratton, B. Adeyemo, A. W. Gilmore, S. M. Nelson, J. J. Berg, D. J. Greene, J. E. McCarthy, E. Tagliazucchi, H. Laufs, B. L. Schlaggar, N. U. F. Dosenbach, and S. E. Petersen
2016. On the stability of bold fmri correlations. *Cerebral Cortex – In Press.*

Leonardi, N., W. R. Shirer, M. D. Greicius, and D. Van De Ville
2014. Disentangling dynamic networks: Separated and joint expressions of functional connectivity patterns in time. *Human brain mapping*, 35(12):5984–5995.

Leonardi, N. and D. Van De Ville
2015. On spurious and real fluctuations of dynamic functional connectivity during rest. *Neuroimage*, 104:430–436.

Liégeois, R., B. Mishra, M. Zorzi, and R. Sepulchre
2015. Sparse plus low-rank autoregressive identification in neuroimaging time series. In *Proc. 54th IEEE Conf. Decision and Control (CDC)*, Pp. 3965–3970.

Liégeois, R., E. Ziegler, C. Phillips, P. Geurts, F. Gómez, M. A. Bahri, B. T. T. Yeo, A. Soddu, A. Vanhaudenhuyse, S. Laureys, and R. Sepulchre
2016. Cerebral functional connectivity periodically (de)synchronizes with anatomical constraints. *Brain structure and function*, 221:2985–2997.

Lindquist, M. A., Y. Xu, M. B. Nebel, and B. S. Caffo
2014. Evaluating dynamic bivariate correlations in resting-state fmri: A comparison study and a new approach. *Neuroimage*, 101:531–546.

Lutkepohl, H.
2005. New introduction to multiple time series analysis. *Econometric theory*, 22(5):961–967.

Maiwald, T., E. Mammen, S. Nandi, and J. Timmer
2008. *Surrogate Data — A Qualitative and Quantitative Analysis*, Pp. 41–74. Berlin, Heidelberg: Springer Berlin Heidelberg.

Majeed, W., M. Magnuson, W. Hasenkamp, H. Schwarb, E. H. Schumacher, L. Barsalou, and S. D. Keilholz
2011. Spatiotemporal dynamics of low frequency bold fluctuations in rats and humans. *Neuroimage*, 54(2):1140–1150.

Margulies, D. S., S. S. Ghosh, A. Goulas, M. Falkiewicz, J. M. Huntenburg, G. Langs, G. Bezgin, S. B. Eickhoff, F. X. Castellanos, M. Petrides, et al.
2016. Situating the default-mode network along a principal gradient of macroscale cortical organization. *Proceedings of the National Academy of Sciences*, 113(44):12574–12579.

Matsui, T., T. Murakami, and K. Ohki

2016. Transient neuronal coactivations embedded in globally propagating waves underlie resting-state functional connectivity. *Proceedings of the National Academy of Sciences*, 113(23):6556–6561.

Mitra, A. and M. E. Raichle
2016. How networks communicate: propagation patterns in spontaneous brain activity. *Phil. Trans. R. Soc. B*, 371(1705):20150546.

Mitra, A., A. Z. Snyder, C. D. Hacker, and M. E. Raichle
2014. Lag structure in resting-state fmri. *Journal of neurophysiology*, 111(11):2374–2391.

Mohajerani, M. H., A. W. Chan, M. Mohsenvand, J. LeDue, R. Liu, D. A. McVea, J. D. Boyd, Y. T. Wang, M. Reimers, and T. H. Murphy
2013. Spontaneous cortical activity alternates between motifs defined by regional axonal projections. *Nature neuroscience*, 16(10):1426–1435.

Nason, G.
2013. A test for second-order stationarity and approximate confidence intervals for localized autocovariances for locally stationary time series. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 75(5):879–904.

Nomi, J. S., S. G. Vij, D. R. Dajani, R. Steimke, E. Damaraju, S. Rachakonda, V. D. Calhoun, and L. Q. Uddin
2017. Chronnectomic patterns and neural flexibility underlie executive function. *NeuroImage*, 147:861–871.

Osborne, A., A. Kirwan, A. Provenzale, and L. Bergamasco
1986. A search for chaotic behavior in large and mesoscale motions in the pacific ocean. *Physica D: Nonlinear Phenomena*, 23(1):75–83.

Papoulis, A.
2002. *Probability, Random Variables and Stochastic Processes.* Mc Graw Hill.

Pfaff, B.
2008. *Analysis of integrated and cointegrated time series with R.* Springer Science & Business Media.

Pollock, D.
2011. *Econometric Theory.* University of Leicester.

Power, J. D., A. L. Cohen, S. M. Nelson, G. S. Wig, K. A. Barnes, J. A. Church, A. C. Vogel, T. O. Laumann, F. M. Miezin, B. L. Schlaggar, and S. E. Petersen
2011. Functional network organization of the human brain. *Neuron*, 72(4):665–678.

Power, J. D., M. Plitt, T. O. Laumann, and A. Martin
2017. Sources and implications of whole-brain fmri signals in humans. *Neuroimage*, 146:609–625.

Preti, M. G., T. A. Bolton, and D. Van De Ville
2016. The dynamic functional connectome: State-of-the-art and perspectives. *NeuroImage – In Press.*

Prichard, D. and J. Theiler
1994. Generating surrogate data for time series with several simultaneously measured variables. *Physical Review Letters*, 73(7):951–954.

Prince, S. J.
2012. *Computer vision: models, learning, and inference.* Cambridge University Press.

Raatikainen, V., N. Huotari, V. Korhonen, A. Rasila, J. Kananen, L. Raitamaa, T. Keinänen, J. Kantola, O. Tervonen, and V. Kiviniemi
2017. Combined spatiotemporal ica (stica) for continuous and dynamic lag structure analysis of mreg data. *NeuroImage.*

Rashid, B., E. Damaraju, G. D. Pearlson, and V. D. Calhoun
2014. Dynamic connectivity states estimated from resting fmri identify differences among schizophrenia, bipolar disorder, and healthy control subjects. *Frontiers in human neuroscience*, 8:897.

Rogers, B. P., S. B. Katwal, V. L. Morgan, C. L. Asplund, and J. C. Gore
2010. Functional mri and multivariate autoregressive models. *Magnetic resonance imaging*, 28(8):1058–1065.

Sakoğlu, Ü., G. D. Pearlson, K. A. Kiehl, Y. M. Wang, A. M. Michael, and V. D. Calhoun
2010. A method for evaluating dynamic functional network con-

nectivity and task-modulation: application to schizophrenia. *Magnetic Resonance Materials in Physics, Biology and Medicine*, 23(5-6):351–366.

Schreiber, T. and A. Schmitz
2000. Surrogate time series. *Physica D: Nonlinear Phenomena*, 142(3):346–382.

Shine, J. M., O. Koyejo, P. T. Bell, K. J. Gorgolewski, M. Gilat, and R. A. Poldrack
2015. Estimation of dynamic functional connectivity using multiplication of temporal derivatives. *NeuroImage*, 122:399–407.

Shine, J. M., O. Koyejo, and R. A. Poldrack
2016. Temporal metastates are associated with differential patterns of time-resolved connectivity, network topology, and attention. *Proceedings of the National Academy of Sciences*, 113(35):9888–9891.

Siegel, J. S., A. Mitra, T. O. Laumann, B. A. Seitzman, M. Raichle, M. Corbetta, and A. Z. Snyder
2016. Data quality influences observed links between functional connectivity and behavior. *Cerebral Cortex – In Press.*

Smith, S. M., C. F. Beckmann, J. Andersson, E. J. Auerbach, J. Bijsterbosch, G. Douaud, E. Duff, D. A. Feinberg, L. Griffanti, M. P. Harms, M. Kelly, T. Laumann, K. L. Miller, S. Moeller, S. Petersen, J. Power, G. Salimi-Khorshidi, A. Z. Snyder, A. T. Vu, M. W. Woolrich, J. Xu, E. Yacoub, K. Ugurbil, D. C. V. Essen, and M. F. Glasser
2013a. Resting-state fmri in the human connectome project. *NeuroImage*, 80:144 – 168.

Smith, S. M., K. L. Miller, S. Moeller, J. Xu, E. J. Auerbach, M. W. Woolrich, C. F. Beckmann, M. Jenkinson, J. Andersson, M. F. Glasser, et al.
2012. Temporally-independent functional modes of spontaneous brain activity. *Proceedings of the National Academy of Sciences*, 109(8):3131–3136.

Smith, S. M., D. Vidaurre, C. F. Beckmann, M. F. Glasser, M. Jenkinson, K. L. Miller, T. E. Nichols, E. C. Robinson, G. Salimi-Khorshidi, M. W. Woolrich, et al.
2013b. Functional connectomics from resting-state fmri. *Trends in cognitive sciences*, 17(12):666–682.

Spreng, R. N., J. Sepulcre, G. R. Turner, W. D. Stevens, and D. L. Schacter
2013. Intrinsic architecture underlying the relations among the default, dorsal attention, and frontoparietal control networks of the human brain. *Journal of cognitive neuroscience*, 25(1):74–86.

Stephan, K. E., L. Kasper, L. M. Harrison, J. Daunizeau, H. E. den Ouden, M. Breakspear, and K. J. Friston
2008. Nonlinear dynamic causal models for fmri. *Neuroimage*, 42(2):649–662.

Stoica, P. and R. L. Moses
2005. *Spectral analysis of signals.* Pearson/Prentice Hall Upper Saddle River, NJ.

Stoica, P. and A. Nehorai
1987. On stability and root location of linear prediction models. *IEEE Transactions on Acoustics, Speech, and Signal Processing*, 35(4):582–584.

Stroh, A., H. Adelsberger, A. Groh, C. Rühlmann, S. Fischer, A. Schierloh, K. Deisseroth, and A. Konnerth
2013. Making waves: initiation and propagation of corticothalamic ca 2+ waves in vivo. *Neuron*, 77(6):1136–1150.

Su, J., H. Shen, L.-L. Zeng, J. Qin, Z. Liu, and D. Hu
2016. Heredity characteristics of schizophrenia shown by dynamic functional connectivity analysis of resting-state functional mri scans of unaffected siblings. *NeuroReport*, 27(11):843–848.

Tedeschi, W., H.-P. Müller, D. de Araujo, A. Santos, U. Neves, S. Ernè, and O. Baffa
2005. Generalized mutual information tests applied to fmri analysis. *Physica A: Statistical Mechanics and its Applications*, 352(2):629–644.

Theiler, J., S. Eubank, A. Longtin, B. Galdrikian, and J. D. Farmer
1992. Testing for nonlinearity in time series: the method of surrogate data. *Physica D: Nonlinear Phenomena*, 58(1):77–94.

Ting, C.-M., A.-K. Seghouane, and S.-H. Salleh

2016. Estimation of high-dimensional connectivity in fmri data via subspace autoregressive models. In *Statistical Signal Processing Workshop (SSP), 2016 IEEE*, Pp. 1–5. IEEE.

Tsai, A., J. W. Fisher III, C. Wible, W. M. Wells III, J. Kim, and A. S. Willsky
1999. Analysis of functional mri data using mutual information. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, Pp. 473–480.

Tucker, M., P. G. Challenor, and D. Carter
1984. Numerical simulation of a random sea: a common error and its effect upon wave group statistics. *Applied ocean research*, 6(2):118–122.

Valdes, P., J. C. Jiménez, J. Riera, R. Biscay, and T. Ozaki
1999. Nonlinear eeg analysis based on a neural mass model. *Biological cybernetics*, 81(5):415–424.

Van De Ville, D., T. Blu, and M. Unser
2004. Integrated wavelet processing and spatial statistical testing of fmri data. *NeuroImage*, 23(4):1472–1485.

Van Den Heuvel, M. P. and H. E. H. Pol
2010. Exploring the brain network: a review on resting-state fmri functional connectivity. *European neuropsychopharmacology*, 20(8):519–534.

Van Essen, D. C., S. M. Smith, D. M. Barch, T. E. Behrens, E. Yacoub, K. Ugurbil, W.-M. H. Consortium, et al.
2013. The wu-minn human connectome project: an overview. *Neuroimage*, 80:62–79.

Vincent, J. L., A. Z. Snyder, M. D. Fox, B. J. Shannon, J. R. Andrews, M. E. Raichle, and R. L. Buckner
2006. Coherent spontaneous activity identifies a hippocampal-parietal memory network. *Journal of neurophysiology*, 96(6):3517–3531.

Walker, G.
1931. On periodicity in series of related terms. *Proceedings of the Royal Society of London. Series A, Containing Papers of a Mathematical and Physical Character*, 131(818):518–532.

Wang, C., J. L. Ong, A. Patanaik, J. Zhou, and M. W. Chee
2016. Spontaneous eyelid closures link vigilance fluctuation with fmri dynamic connectivity states. *Proceedings of the National Academy of Sciences*, 113(34):9653–9658.

Weisstein, E.
2016. "cross-correlation theorem." from mathworld–a wolfram web resource.

Wiener, N.
1930. Generalized harmonic analysis. *Acta Mathematica*, 55:117–258.

Yeo, B. T., F. M. Krienen, M. W. Chee, and R. L. Buckner
2014. Estimates of segregation and overlap of functional connectivity networks in the human cerebral cortex. *Neuroimage*, 88:212–227.

Yeo, B. T. T., F. M. Krienen, J. Sepulcre, M. R. Sabuncu, D. Lashkari, M. Hollinshead, J. L. Roffman, J. W. Smoller, L. Zöllei, J. R. Polimeni, B. Fischl, H. Liu, and R. L. Buckner
2011. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of neurophysiology*, 106:1125–1165.

Yeo, B. T. T., J. Tandi, and M. W. L. Chee
2015. Functional connectivity during rested wakefulness predicts vulnerability to sleep deprivation. *NeuroImage*, 111:147–158.

Yule, G. U.
1927. On a method of investigating periodicities in disturbed series, with special reference to wolfer's sunspot numbers. *Philosophical Transactions of the Royal Society of London. Series A, Containing Papers of a Mathematical or Physical Character*, 226:267–298.

Zalesky, A. and M. Breakspear
2015. Towards a statistical test for functional connectivity dynamics. *NeuroImage*, 114:466–470.

Zalesky, A., A. Fornito, and E. T. Bullmore
2010. Network-based statistic: identifying differences in brain networks. *Neuroimage*, 53(4):1197–1207.

Zalesky, A., A. Fornito, L. Cocchi, L. L. Gollo, and M. Breakspear

2014. Time-resolved resting-state brain networks. *Proceedings of the National Academy of Sciences*, 111(28):10341–10346.

Zivot, E. and J. Wang
2006. Vector autoregressive models for multivariate time series. *Modeling Financial Time Series with S-PLUS*, Pp. 385–429.

Appendix

A1. Details of ARR procedure and linear Gaussianity

Let x_t be the $N \times 1$ vector of fMRI data at time t after each time course has been demeaned. There are many approaches to estimate the p-th order AR model parameters $(\Sigma, A_1, \cdots, A_p)$ from the data x_t. A common approach is as follows

1. Estimate $A_1, \cdots, A_p$ using the following least-squares cost function:

$$\left\| \sum_{t=p+1}^{T} \left(x_t - \sum_{l=1}^{p} A_l x_{t-l} \right) \right\|^2, \qquad (A1)$$

where T is the number of time points. Let $A = [A_1, \cdots A_p]$ (i.e., A is a $N \times Np$ matrix). Then the optimum to the above criterion corresponds to

$$\hat{A} = XZ'(ZZ')^{-1}, \qquad (A2)$$

where $'$ indicates transpose, X is a $N \times (T-p)$ matrix

$$X = [x_{p+1}, \cdots, x_T], \qquad (A3)$$

and Z is a $Np \times (T-p)$ matrix

$$Z = \begin{bmatrix} x_p & x_{p+1} & \ldots & x_{T-1} \\ x_{p-1} & x_p & \ldots & x_{T-2} \\ \vdots & \vdots & \ddots & \vdots \\ x_1 & x_2 & \ldots & x_{T-p} \end{bmatrix}. \qquad (A4)$$

The estimation procedure therefore requires ZZ' (in Eq. (A2)) to be full rank, which implies that $T \geq (N+1)p$. For example, if one utilized a parcellation with 400 ROIs, then one would need at least $401 \times 3 = 1203$ time points for a 3rd order AR model.

2. After estimating $\hat{A} = [\hat{A}_1, \cdots, \hat{A}_p]$, the residual (error) is defined as follows

$$\delta_t = x_t - \sum_{l=1}^{p} \hat{A}_l x_{t-l} \quad \text{for } t = p+1, \cdots, T \quad (A5)$$

The covariance matrix Σ can then be estimated via the empirical covariance matrix:

$$\hat{\Sigma} = \frac{1}{T-p} \sum_{t=p+1}^{T} \delta_t \delta_t' \qquad (A6)$$

Once $(\Sigma, A_1, \cdots, A_p)$ are estimated, each ARR null data is initialized by randomly selecting p consecutive time points of the original data, and then repeatedly applying the AR model (Eq. (3)) until null data of length T are generated. By virtue of the AR model (Eq. (3)), the resulting null data is linear Gaussian if the resulting system is stable (see Appendix A2).

In the fMRI literature, it is common to generate null data where ϵ_t in Eq. (3)) are not generated using a Gaussian distribution, but obtained by sampling from the residuals δ_t of the identified AR model (Chang and Glover, 2010). In practice, the residuals might not follow a Gaussian distribution (Lutkepohl, 2005), and so the resulting ARR null data would only be linear but not Gaussian. However, in our experiments (not shown), this difference does not have any practical effect on our conclusions.

A2. WSS, stability and auto-covariance of ARR null data

The AR random process (Eq. (3)) is WSS if and only if the AR model is stable (Lutkepohl, 2005; Zivot and Wang, 2006; Pfaff, 2008). Stability can be assessed by ensuring that the matrix

$$\mathbb{A} = \begin{bmatrix} A_1 & A_2 & \ldots & A_{p-1} & A_p \\ \mathbb{I} & 0 & \ldots & 0 & 0 \\ 0 & \mathbb{I} & \ldots & 0 & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & \ldots & \mathbb{I} & 0 \end{bmatrix} \qquad (A7)$$

has eigenvalues with magnitude strictly smaller than one.

Therefore ARR null data is WSS assuming that the estimated AR parameters correspond to that of a stable AR model. This stability condition should therefore be checked when estimating the AR model parameters (Eq. (A1)). Since the original fMRI data is stable (i.e., the fMRI measurements do not diverge to infinity), the estimated AR model should be stable as long as the estimation procedure is reliable. In our experience with fMRI data, this is indeed the case if the AR order p is not too close to its maximal value of $p_{max} = \frac{T}{N+1}$ (Appendix A1). If the order p is too close to p_{max}, then the estimation procedure (Eq. (A1)) might require the inversion of an almost singular matrix, which might lead to an unstable AR model.

We now turn our attention to the relationship between the AR model parameters $(\Sigma, A_1, \cdots, A_p)$ (Eq. (3)) and auto-covariance sequence $R_0, \cdots, R_p$ (Eq. (2)), which is governed by the Yule-Walker equations (Yule, 1927; Walker, 1931) assuming infinitely long time courses:

$$\begin{bmatrix} R_0 & R_1' & \ldots & R_p' \\ R_1 & R_0 & \ldots & R_{p-1}' \\ \vdots & \vdots & \ddots & \vdots \\ R_p & R_{p-1} & \ldots & R_0 \end{bmatrix} \begin{bmatrix} 1 \\ A_1 \\ \vdots \\ A_p \end{bmatrix} = \begin{bmatrix} \Sigma \\ 0 \\ \vdots \\ 0 \end{bmatrix}. \qquad (A8)$$

Eq. (A8) is invertible for sufficiently large T, and so the AR model parameters are completely determined by the auto-covariance sequence of the original data (Stoica and Moses, 2005) and vice versa (e.g., Pollock, 2011, Chapter 13). Consequently, the AR null data generated by this framework share the first $p + 1$ auto-covariances (Eq. (2)) computed from the original data.

It is also worth noting that for sufficiently large T, the AR parameters obtained by inverting Eq. (A8) are mathematically and practically equivalent to those obtained from Appendix A1. For small T, AR model parameters estimated from Eq. (A8) are guaranteed to correspond to a stable system, while AR model parameters estimated from Eq. (A2) are not (Stoica and Nehorai, 1987). Therefore one should always check the stability of the AR system when using the least squares approach (Appendix A1).

A3. Details of the PR procedure

This appendix elaborates the PR procedure. Let x^n denote the time course of the n-th brain region, while x_t^n denote the t-th time point of the n-th brain region (where the first time point corresponds to $t = 0$). Without loss of generality, we assume that the time courses have been demeaned. PR proceeds as follows:

1. The Discrete Fourier Transform (DFT) for each time course x^n is computed:

$$y_k^n = \mathcal{F}(x^n) = \sum_{t=0}^{T-1} x_t^n \exp\left(-i2\pi k \frac{t}{T}\right)$$
$$= Q_k^n \, \exp(i\Phi_k^n) \quad \text{for } k = 0, \cdots, T-1, \quad \text{(A9)}$$

   where k indexes frequency, and Q_k^n and Φ_k^n are the amplitude and phase of the k-th frequency component of the DFT. Since the input signal is real, $Q_k^n = Q_{T-k}^n$ and $\Phi_k^n = -\Phi_{T-k}^n$. Because the signal has been demeaned, therefore $Q_0^n = 0$.

2. A random phase ϕ_k is then added to the DFT coefficients for each brain region n:

$$\tilde{y}_k^n = Q_k^n \, \exp(i(\Phi_k^n + \phi_k)) \quad \text{for } k = 0, \cdots, T-1, \quad \text{(A10)}$$

   where ϕ_k is drawn from a uniform distribution on the $[0, 2\pi]$ interval. Importantly, ϕ_k is the same for all brain regions and independently sampled for frequencies $k = 0, \cdots, \lceil T/2 \rceil$ (although we note that ϕ_0 is useless because $Q_0^n = 0$). For $k > \lceil T/2 \rceil$ ($\lceil \cdot \rceil$ denote the ceiling function), $\phi_k = -\phi_{T-k}$ because of the need to ensure the null data remains real (rather than complex-valued).

3. The inverse DFT is then performed for each brain

region n resulting in the PR null data:

$$\tilde{x}_t^n = \mathcal{F}^{-1}(\tilde{y}^n) \quad \text{(A11)}$$
$$= \frac{1}{T} \sum_{k=0}^{T-1} \tilde{y}_k^n \exp\left(i2\pi k \frac{t}{T}\right) \quad \text{for } t = 0, \cdots, T-1, \quad \text{(A12)}$$

Because $Q_k^n = Q_{T-k}^n$, $\Phi_k^n = -\Phi_{T-k}^n$, $Q_0^n = 0$, and $\phi_k = -\phi_{T-k}$ for $k > \lceil T/2 \rceil$, the null data (Eq. (A12)) can be written in the following form:

$$\tilde{x}_t^n = 2 \sum_{k=1}^{\lceil T/2 \rceil} Q_k^n \cos(2\pi k \frac{t}{T} + \Phi_k^n + \phi_k). \quad \text{(A13)}$$

A4. PR null data are WSS

To show that the PR null data is WSS, we show that the ensemble mean and ensemble auto-covariance do not depend on the time t.

First, by applying "expectation" to Eq. (A13) and via the linearity of expectation, the ensemble mean is equal to:

$$\mathbb{E}[\tilde{x}_t^n] = 2 \sum_{k=1}^{T/2} Q_k^n \mathbb{E}\left[\cos\left(2\pi k \frac{t}{T} + \Phi_k^n + \phi_k\right)\right]$$
$$= 2 \sum_{k=1}^{T/2} Q_k^n \int_0^{2\pi} \frac{1}{2\pi} \cos\left(2\pi k \frac{t}{T} + \Phi_k^n + \phi_k\right) d\phi_k$$
$$= 0, \quad \text{(A14)}$$

where the second equality arises $\phi_k \sim \mathbb{U}[0, 2\pi]$. Therefore the ensemble mean does not depend on the time t.

Let $Cov(x_t^n, x_{t-l}^m)$ be the ensemble auto-covariance between the signal of brain region n at time t and the signal of brain region m at time $t-l$. Because the ensemble mean is equal to 0 for all time points, therefore

$$Cov(x_t^n, x_{t-l}^m) = \mathbb{E}[\tilde{x}_t^n \tilde{x}_{t-l}^m]$$
$$= 4\mathbb{E}\left[\sum_{k_1=1}^{T/2} Q_{k_1}^n \cos\left(2\pi k_1 \frac{t}{T} + \Phi_{k_1}^n + \phi_{k_1}\right)\right.$$
$$\left. \sum_{k_2=1}^{T/2} Q_{k_2}^m \cos\left(2\pi k_2 \frac{t-l}{T} + \Phi_{k_2}^m + \phi_{k_2}\right)\right]$$
$$= 4(A + B), \quad \text{(A15)}$$

where A corresponds to the products of cosines with different frequencies and B corresponds to the products of

cosines with the same frequencies. More specifically,

$$
A = \mathbb{E}\left[\sum_{k_1=1}^{T/2}\sum_{k_2 \neq k_1} Q_{k_1}^n Q_{k_2}^m \cos\left(2\pi k_1 \frac{t}{T} + \Phi_{k_1}^j + \phi_{k_1}\right)\right.
$$
$$
\left.\cos\left(2\pi k_2 \frac{t-l}{T} + \Phi_{k_2}^h + \phi_{k_2}\right)\right] \tag{A16}
$$

$$
= \sum_{k_1=1}^{T/2}\sum_{k_2 \neq k_1} Q_{k_1}^n Q_{k_2}^m \mathbb{E}\left[\cos\left(2\pi k_1 \frac{t}{T} + \Phi_{k_1}^j + \phi_{k_1}\right)\right]
$$
$$
\mathbb{E}\left[\cos\left(2\pi k_2 \frac{t-l}{T} + \Phi_{k_2}^h + \phi_{k_2}\right)\right] \tag{A17}
$$

$$
= 0 \tag{A18}
$$

where the second equality is true due to the fact that the random phases ϕ_{k_1} and ϕ_{k_2} are independently sampled, and the third equality is obtained from straightforward integration (just like the ensemble mean). On the other hand,

$$
B = \mathbb{E}\left[\sum_{k=1}^{T/2} Q_k^n Q_k^m \cos\left(2\pi k \frac{t}{T} + \Phi_k^n + \phi_k\right)\right.
$$
$$
\left.\cos\left(2\pi k \frac{t-l}{T} + \Phi_k^m + \phi_k\right)\right] \tag{A19}
$$

$$
= \frac{1}{2}\mathbb{E}\left[\sum_{k=1}^{T/2} Q_k^n Q_k^m \left(\cos\left(4\pi k \frac{2t-l}{T} + \Phi_k^n + \Phi_k^m + 2\phi_k\right)\right.\right.
$$
$$
\left.\left.+ \cos\left(2\pi k \frac{l}{T} + \Phi_k^n - \Phi_k^m\right)\right)\right] \tag{A20}
$$

$$
= \frac{1}{2}\sum_{k=1}^{T/2} Q_k^n Q_k^m \cos\left(2\pi k \frac{l}{T} + \Phi_k^n - \Phi_k^m\right) \tag{A21}
$$

Therefore

$$
Cov(x_t^n, x_{t-l}^m) = \frac{1}{2}\sum_{k=1}^{T/2} Q_k^n Q_k^m \cos\left(2\pi k \frac{l}{T} + \Phi_k^n - \Phi_k^m\right), \tag{A22}
$$

which does not depend on time t and only depends on the interval l between the two time points t and $t-l$. Therefore PR null data are WSS. Furthermore, one can also verify that the sample mean is equal to 0 and the sample autocovariance sequence R_l are equal to the ensemble autocovariances (Eq. (A22)). Therefore PR null data are also ergodic.

A5. PR null data preserve auto-covariance sequences

In this appendix, we explain why PR null data preserve auto-covariance sequences (Eq. (2)) of the original data. This property arises from the Wiener-Khintchine theorem, first formulated in the univariate case by Wiener

(1930) and Khintchine (1934), and then reported in the multivariate case as an extension of the Wiener-Khintchine theorem (Prichard and Theiler, 1994), or cross-correlation theorem (Weisstein, 2016).

Given two time courses x_t^n and x_t^m from brain regions n and m, their (sample) cross spectral density (CSD) is defined as $\Psi_k^{n,m} = \mathcal{F}(x_t^n)\mathcal{F}^*(x_t^m)$, where $\mathcal{F}(\cdot)$ is the DFT, k indexes frequency, and $*$ is the complex conjugate. Let $R_l^{n,m}$ corresponds to the n-th row and m-column of the autocovariance matrix R_l defined in Eq. (2). Then according to the multivariate Wiener-Khintchine theorem:

$$
R_l^{n,m} = \mathcal{F}(\Psi_k^{n,m}), \quad \Psi_k^{n,m} = \mathcal{F}^{-1}(R_l^{n,m}). \tag{A23}
$$

In other words, the (sample) CSD and the autocovariance sequence of a multivariate random process encode the same information about the data.

Let the PR null time courses for brain regions n and m be denoted as $\tilde{x}_t^n$ and $\tilde{x}_t^m$. Their sample CSD corresponds to

$$
\tilde{\Psi}_k^{n,m} = \mathcal{F}(\tilde{x}_t^n)\mathcal{F}^*(\tilde{x}_t^m) \tag{A24}
$$
$$
= Q_k^n \exp(i(\Phi_k^n + \phi_k))Q_k^m \exp(-i(\Phi_k^m + \phi_k)) \tag{A25}
$$
$$
= Q_k^n \exp(i\Phi_k^n)Q_k^m \exp(-i\Phi_k^m) \tag{A26}
$$
$$
= \Psi_k^{n,m}, \tag{A27}
$$

where the second equality is obtained by plugging in Equation (A10), and the random phase ϕ_k is the same for all brain regions and therefore cancels out in the third equality. Since the sample CSD is the same between brain regions n and m in the PR null data, then their autocovariance sequence is also the same according to Wiener-Khintchine theorem (Eq. (A23)).

Supplementary material

S1. Coherence of SWC dynamics

Figure S1: Distribution of percentage variance of first principal component across 100 participants in original, phase randomized (PR), multivariate ARR and bivariate ARR null data. For 99% of the subjects, the stationary linear gaussian null-model cannot be rejected using a false discovery rate of $q < 0.05$. (12 subjects had an uncorrected p value of less than 0.05).

S2. Impact of ARR order p

Statistics in original and multivariate ARR null data with different orders

Figure S2: Impact of AR model order p. AR model of order 0 (static model) does not capture fluctuations in coherent brain dynamics (as measured by percentage variance of first principal component) present in the original (OR) data. AR models of orders 1 to 8 capture similar fluctuations in coherent brain dynamics.

S3. Impact of mean grayordinate regression (MGR)

Figure S3: Impact of mean grayordinate regression (MGR). (Left) ICA-FIX original data. (Middle) ICA-FIX data with mean grayordinate regression (MGR). (Right) Phase randomization (PR) of ICA-FIX mean grayordinate regressed data. Mean grayordinate regression reduces the percentage variance of the first principal component. PR of ICA-FIX mean grayordinate regressed data is not distinguishable from original (ICA-FIX + MGR) data.

S4. Comparing Stationary Linear Gaussian Model and Hidden Markov Model

Figure S4: Distribution of Kolmogorov-Smirnov (KS) statistics between the functional connectivity dynamics (FCD) matrices of the original data and 100 null data from PR, multivariate ARR, bivariate ARR, 3-state hidden Markov model (HMM), 11-state HMM, and Laumann et al. (2016). A smaller KS statistic implies a better match between original data and null data as the KS statistics measures the maximum distance between two distributions.

S5. FCD matrices computed with other surrogates

Figure S5: FCD matrices of (A) 11-state hidden Markov model (HMM) and (B) Laumann et al. (2016)

S6. FCD matrices for the most "dynamic" HCP subject

Figure S6: FCD matrices for (A) the one HCP subject for whom the stationary, linear, Gaussian null hypothesis was rejected in Section 5.4, (B) PR, (C) first-order multivariate ARR, (D) bivariate ARR, and (E) 3-state HMM. Note the slight difference in scale as compared to Figures 8 and S5.