The neural representation of personally familiar and unfamiliar faces in the distributed system for face perception

Matteo Visconti di Oleggio Castello[1,+,*], Yaroslav O. Halchenko[1,+,*], J. Swaroop Guntupalli[1], Jason D. Gors[1], M. Ida Gobbini[1,2,*]

1: Department of Psychological and Brain Sciences, Dartmouth College, Hanover, NH 03755, USA

2: Dipartimento di Medicina Specialistica, Diagnostica e Sperimentale (DIMES), Medical School, University of Bologna, Bologna, Italy

+: these authors contributed equally to the work

*: corresponding authors

M. Ida Gobbini: mariaida.gobbini@unibo.it

Matteo Visconti di Oleggio Castello: mvdoc.gr@dartmouth.edu

Yaroslav O. Halchenko: yoh@dartmouth.edu

Abstract

Personally familiar faces are processed more robustly and efficiently than unfamiliar faces. The human face processing system comprises a core system that analyzes the visual appearance of faces and an extended system for the retrieval of person-knowledge and other nonvisual information. We applied multivariate pattern analysis to fMRI data to investigate aspects of familiarity that are shared by all familiar identities and information that distinguishes specific face identities from each other. Both identity-independent familiarity information and face identity could be decoded in an overlapping set of areas in the core and extended systems. Representational similarity analysis revealed a clear distinction between the two systems and a subdivision of the core system into ventral, dorsal and anterior components. This study provides evidence that activity in the extended system carries information about both individual identities and personal familiarity, while clarifying and extending the organization of the core system for face perception.

Keywords: personally familiar faces; mvpa; decoding; brain networks; core and extended systems; representational similarity analysis.

Introduction

A wide and distributed network of brain areas underlies face processing. The model by Haxby and colleagues[1–3] posited a division between a core system involved in the processing the visual appearance of faces—comprising the Occipital Face Area (OFA), the Fusiform Face Area (FFA), and the posterior Superior Temporal Sulcus (pSTS)—and an extended system, comprising parietal, frontal, and subcortical areas, involved in inferring socially relevant information from faces, such as direction of attention, intentions, emotions, and retrieval of person knowledge[1–4].

The definition of the core system has been extended to include areas in the anterior fusiform gyrus (the anterior temporal face area, ATFA[5,6]), the anterior superior temporal sulcus (aSTS-FA[7–9]), and the inferior frontal gyrus (IFG-FA[7,10–12]). For example, in a recent fMRI neural decoding study with visually familiar faces[11], we showed that the representation of face identity is progressively disentangled from image-specific features along the ventral visual pathway. While early visual cortex and the OFA represented head view independently of the identity of the face, we recorded an intermediate level of representation in the FFA in which identity was emerging but was still entangled with head view. The human face processing pathway culminated in the right ATFA and IFG-FA where we recorded a view-invariant representation of face identity.

While both unfamiliar and familiar faces effectively activate the core system[7,8,11,13,14], familiar faces activate the extended system more strongly than unfamiliar faces[2,13,15–17]. Personally familiar faces recruit Theory of Mind (ToM) areas such as the medial prefrontal cortex (MPFC) and the temporo-parietal junction (TPJ), because they are more strongly associated with person knowledge[2,16,18]; they activate the precuneus and the anterior temporal cortices, suggesting retrieval of long-term episodic memories; they modulate the activity in the amygdala and insula, suggesting an increased emotion processing[2,13,18]. Because the core and extended systems have been mostly studied separately, we lack a clear understanding of how personal familiarity, consolidated through repeated interactions, affects the representations in the core system, and how core and extended systems interact to create the known

behavioral advantages for personally familiar faces.

The behavioral literature on face processing[19–25] suggests that, despite the subjective

impression of efficient or "expert" perception of natural faces[26], only familiar faces are

detected and recognized more robustly and efficiently, in stark contrast with the

surprisingly inefficient identification of unfamiliar faces. Recognition of personally

familiar faces is highly accurate even when images are severely degraded, while

recognition of unfamiliar faces is markedly impaired by variation in head position or

lighting, even with good image quality[24,25,27–29]. Detection of personally familiar faces is

facilitated even in conditions of reduced attentional resources and without

awareness[19].

The representations of familiar and unfamiliar faces may differ in multiple ways.

Familiar identities could have more robust, individually-specific representations, which

are learned and consolidated over the course of personal interactions. Alternatively,

familiar face representations could be enhanced with attributes that are similar across

many personally familiar faces. For example, personally familiar faces (especially those

used in the present and our previous experiments that are faces of close relatives of

personal friends) are associated with person-knowledge and emotional attachment

that lead to social interactions that are different from the interactions with strangers,

and these attributes may be shared across many familiar—one may be more open

and unguarded with family and personal friends[18].

Here we applied multivariate pattern analyses (MVPA[30,31], including MVP classification

(MVPC) and representational similarity analysis (RSA[32] with two goals in mind. First,

we wanted to dissociate familiarity information from identity information in the core

and extended systems. Second, we wanted to investigate the relationships among

core and extended face processing areas by examining the similarities of their

representational spaces using second-order representational geometry[32–34].

We first derived independent neural measures of identification and familiarity. To

prevent any effect of familiarity information in identity decoding, we performed identity

classification separately for familiar and unfamiliar faces. To control for the effect of

identity-specific visual information in familiarity decoding, we trained classifiers to

distinguish familiar from unfamiliar faces, and tested them on left-out identities. The

results replicated the distinction between the representations of personally familiar

and unfamiliar faces in the extended system that was previously revealed only with

univariate analysis[2], showing that this effect captured factors that were common

across familiar faces and invariant across identities.

To unravel the representational structure of the face processing network, we

investigated the relationships among the areas of the core and extended system

uncovered by the classification analyses. Using the approach used by Guntupalli and

colleagues[34] (see also Kriegeskorte and colleagues[33]), we studied the similarities

between representational geometries[32] in different face-processing areas (second-

order representational geometry). This analysis revealed clear distinctions between the

core system and the extended system, supporting the model by Haxby and

colleagues[1–3]. In addition, the results support the extension of the core system to more

anterior areas, such as the ATFA, the aSTS-FA and IFG-FA[5–7,11,35], and reveal a finer

subdivision of this system into ventral, dorsal, and anterior components.

Results

In this experiment, we investigated the face processing network while participants

performed an oddball-detection task with faces of friends and strangers (see Figure 1).

We first investigated which areas responded more strongly to familiar faces than

unfamiliar ones with a standard GLM analysis. Because familiarity information

(whether a face is a familiar one) is necessarily confounded with identity information

(who that person is), we next used MVPC to dissociate which areas of the core and

extended system encode identity-independent familiarity information (familiar vs.

unfamiliar classification across identities), and which parts of the network encode

identity information. We performed two classification analyses using different cross-

validation schemes to control for the effect of identity on the representation of general

familiarity and to control for the effect of familiarity on the representation of identity.

For the familiarity classification, we employed a leave-two-identities-out cross-

validation scheme, where the classifier was trained on six faces (three familiar, three

unfamiliar) to distinguish between familiar and unfamiliar faces, and tested on two left-
out identities. This cross-validation scheme reduced the effect of identity information
(see Figure 4B and Supplementary Figures 1 and 2). For the identity classification, we
decoded the four familiar faces and the four unfamiliar faces separately to eliminate
the effect of familiarity information in the classification of identity information. Finally,
we investigated the network structure derived from the similarities of representations
to investigate relationships among areas in the core and extended system.
131

Figure 1: Slow event-related fMRI design. During each trial, images were presented in sequences of three pictures of the same identity (normal trial) or two different identities (oddball trials) in front-view or 30-degree profile views. Subjects engaged in an oddball-detection task to ensure that they paid attention to each stimulus.

Univariate analyses

In the univariate analysis contrasting Familiar > Unfamiliar we found significant activation in bilateral MTG/STS extending along the full length of the right STS. Additionally, we found significant clusters in the bilateral precuneus and bilateral MPFC, as well as in the right IFG. Familiar faces also evoked stronger responses in the left mid fusiform gyrus and the right anterior fusiform gyrus near the locations of the FFA[36,37] and ATFA[5]. For the contrast Unfamiliar > Familiar we found only one significant cluster in the right inferior parietal lobule encroaching on the TPJ. Figure 2 shows the resulting statistical maps projected on the surface.

Figure 2. Cluster-corrected (p < .05) z-values for the univariate contrast Familiar > Unfamiliar. Abbreviations: IPL: inferior parietal lobule; mFus: middle fusiform gyrus; aFus: anterior fusiform gyrus; TPJ: temporo-parietal junction; MTG/STS: middle temporal gyrus/superior temporal sulcus; Precun: precuneus; MPFC: medial prefrontal cortex; IFG: inferior frontal gyrus.

Multivariate analyses

Familiarity Classification

The results of searchlight MVPC of identity-independent familiarity largely overlapped with the univariate maps, showing significant classification in the bilateral MTG/STS, mid and anterior right fusiform gyrus, right IFG, TPJ, precuneus, and MPFC (Figure 3). Surprisingly, small patches of cortex in early visual cortex also showed significant MVPC of identity-independent familiarity. We further investigated MVPC in early visual cortex with additional analyses on probabilistic ROI masks[38], and found statistically significant decoding performance in V2 and V3 (see Supplementary Methods and Supplementary Figure 7). Since testing was performed on left-out familiar and unfamiliar identities, and all pictures were taken with the same equipment and settings, it is unlikely that this result was due simply to low-level features that distinguished familiar from unfamiliar faces. To test this further, we extracted features from the layers C1 and C2 of the HMAX model[39,40] and performed the same classification analysis, and found that decoding performance was not statistically significant (accuracy with C1 features 52%, p = 0.67; accuracy with C2 features 49%, p = 0.96; see Supplementary Methods and Supplementary Figure 8).

The results from the familiarity classification showed some correspondence with the univariate analysis, but the two maps were not completely overlapping. The scatterplot between the voxel-wise z-values for univariate GLM and the familiarity decoding MVPA results (Figure 4A) shows large spread, highlighting that the multivariate classification leveraged additional information other than magnitude differences between the two conditions. In addition, as can be seen in Figure 4B, the leave-two-identities-out cross-validation scheme effectively controlled for visual identity information in early visual cortex, which was necessarily conflated in the univariate contrast.

Figure 3. Searchlight maps for the Familiarity classification projected onto the surface. Maps were thresholded at a z-TFCE score of 1.65, corresponding to p < 0.05 one-tailed (corrected for multiple comparisons). Abbreviations: mFus: middle fusiform gyrus; aFus: anterior fusiform gyrus; TPJ: temporo-parietal junction; MTG/STS: middle temporal gyrus/superior temporal sulcus; Precun: precuneus; MPFC: medial prefrontal cortex; IFG: inferior frontal gyrus.

Figure 4. A) Comparison of the univariate analysis of familiarity with the MVPA familiarity decoding. The x-axis shows z-values from the univariate contrast Familiar > Unfamiliar. The y-axis shows the z-values of the Familiarity classification across identities. Colors depict voxel position in Posterior-to-Anterior (Blue-to-Red) direction. Some but not complete correspondence exists between the two maps, showing that the multivariate analyses leveraged additional information other than magnitude differences. **B) Comparison of cross-validation schemes for the familiarity decoding.** The x-axis shows z-values from the familiarity classification using the leave-2-identities-out scheme, as reported in the main manuscript. The y-axis shows the same classification using a common leave-one-run-out scheme. The leave-two-identities-out scheme successfully controls for identity visual information, as can be seen by the overall lower z-values for voxels belonging to the occipital cortex.

Identity Classification

The identity classification analysis showed that identity could be decoded in many of

the same areas as identity-independent familiarity (Figure 4). Significant classification

was found in the MPFC and precuneus, and in the bilateral MTG/STS, TPJ, and IFG.

The area in the precuneus with significant identity classification, however, was quite

dorsal, whereas that for significant familiarity classification was ventral and included

the posterior cingulate. Identity classification was significant in bilateral visual cortex

starting in EV and extending to occipital, posterior, and mid fusiform cortices.

Although MVPC of familiar identities showed a weak trend towards higher accuracies

than for unfamiliar identities in the IFG and MTG/STS (Supplementary Figures 4, 5,

and 6), these differences were not significant despite the large number of subjects.

Figure 5. Searchlight maps for the Identity classification. The classification was run separately for familiar and unfamiliar identities (4-way), and the resulting maps were averaged. Maps were thresholded at a z-TFCE score of 1.65, corresponding to p < 0.05 one-tailed (corrected for multiple comparisons). Abbreviations: OccFus: occipital fusiform gyrus; pFus:

posterior fusiform gyrus; mFus: middle fusiform gyrus; TPJ: temporo-parietal Junction; MTG/STS: middle temporal gyrus/superior temporal sulcus; dPrecun: dorsal precuneus; MPFC: medial prefrontal cortex; IFG: inferior frontal gyrus.

ROI Analysis and Second-order Representational Geometry

We investigated the relationships among the areas uncovered by the classification
analysis as a second-order, inter-areal representational geometry. We selected 30
spherical ROIs (see Methods for how they were selected, Figure 5 for their location,
and Supplementary Table 1 for their MNI coordinates) and computed a cross-
validated representational dissimilarity matrix[41] in each ROI. We then constructed a
distance matrix quantifying the similarity of these RDMs between all pairs of ROIs.
Then, we computed an MDS solution to visualize the geometry of this inter-ROI
matrix. Figure 6 shows the results of the projection of a 3D MDS plot on the first two
dimensions. Supplementary Figure 10 shows the distance matrices, Supplementary
Figures 11, 12, and Supplementary Videos 1, 2 show the full MDS solution.

Figure 6. Spherical ROIs used to analyze the similarity of representational geometries. Top row shows left sagittal slices; middle row shows right sagittal slices; bottom row shows axial slices. Regions are color coded according to the system they belong to. Grey dotted lines between ROIs indicates that they were contiguous but not overlapping (see Methods for details).

The first two dimensions of the MDS solution captured relationships among areas in

the ventral portion of the core system in the first dimension, and relationships among

areas in the dorsal and anterior parts of the core system and areas in the extended

system in the second dimension. The first dimension showed a progression from EV

areas to the posterior, mid, and anterior fusiform areas. Extended system areas were

all at the distant end of the first dimension, as were the areas in the dorsal part of the

core system (MTG/STS) and the IFG. The second dimension captured distinctions among these extended and core system areas, with the precuneus areas clustered together at one end, the MPFC and TPJ in the middle, and the dorsal and anterior core system areas at the other end.

We replicated this second-order RSA on an independent fMRI dataset collected while different subjects watched a full-length audiovisual movie, *Raiders of the Lost Ark*[34,42] This naturalistic stimulus contained a rich variety of dynamic faces that rapidly became familiar while the plot unfolded. The inter-ROI similarity matrix and MDS plot replicated the results based on representational geometry for the eight faces in the experiment (Figure 6). The results tend to be more clearly defined for the movie data, probably due to the the dynamic videos, the larger data set, and hyperalignment of the data. Contributions from scene context, language, music, and narrative structure might also play a role[43,44]. The first two dimensions of the MDS solution cleanly captured distinctions in the ventral core system in the first dimension and in the extended, dorsal core, and anterior core systems in the second dimension, with remarkably similar placement of ROIs on each of these dimensions between task data and movie data; the distance matrices obtained from the two datasets were very similar (RV-coefficient[45,46] = 0.755 [0.7254, 0.7612]; Spearman r = 0.48 [0.34, 0.49]; see Supplementary Methods and Figures 12, 13).

We quantified the similarity of the within-system RDMs by running a linear mixed-effect model on the correlation values and contrasting within-systems correlations with between-systems correlations. We found a clear distinction between the core and extended systems in terms of similarity of representational geometries. For the task data, the correlations within the extended system were significantly higher than the between-system correlations (estimate of the contrast "Within Extended > Between" 0.0993 [0.0875, 0.1111] 95% confidence interval, t-value = 16.36), while the correlations within the core system were not significantly different from the between-system correlations (estimate of the contrast "Within Core > Between" 0.0044 [-0.0043, 0.0130], t-value = 1.00). For the movie data, both contrasts were significant: within-core vs. between 0.0678 [0.0619, 0.0738], t-value = 22.47; and within-extended vs. between 0.1479 [0.1398, 0.1565], t-value = 35.07. Supplementary Tables 2 and 3

235   show the full parameter estimates for both models, while Supplementary Tables 4 and

236   5 report additional statistics on the subsystems.

Figure 7. Similarity of neural representations in ROIs derived from familiarity and identity decoding. Top panel and middle panel show the first two dimensions of 3D MDS solutions based on the task data (A) and the hyperaligned movie data[34,42] (B) (see Methods section for more details). The color of the labels indicates the system to which the ROI belongs to (see Figure 5 for their location and Supplementary Table 1 for the MNI coordinates). With both datasets the MDS solution shows the hierarchy from early visual cortex to ventral core system (first dimension, x-axis), as well as a segregation between the precuneus, theory of mind areas, and areas of the anterior and dorsal core system (second dimension, y-axis). Panel (C) shows the proposed division of the core system into dorsal, ventral, and anterior portions. This division builds upon existing models of face processing[1,7], which suggest a progression from early visual areas to separate dorsal and ventral streams, while extending these models with the finding that both streams converge to the IFG. Representation of identity and gaze in the anterior core areas are disentangled from variations in head view[11,47].

Discussion

In this experiment we investigated how familiar and unfamiliar faces are represented in the distributed neural system for face perception. We distinguished between familiarity information, abstracted from the visual appearance of the faces, and the identification of individual faces, controlling for the added information of personal familiarity. These analyses revealed an extensive network of areas that carry information about face familiarity and identity, replicating with a larger sample size previous studies that used univariate analyses, and also providing more details about the type of information present in those areas. We then analyzed the second-order representational geometry of this extensive network, revealing a clear distinction between the core and the extended systems for face perception and a new subdivision of the areas in the core system.

The results from the second-order representational analysis suggest that the core system for face perception can be separated into ventral, dorsal, and anterior subsystems, extending the existing neural models of face perception[1,2,7]. The ventral core system consists of fusiform areas extending from the occipital lobe to the anterior ventral temporal lobe. The dorsal system extends from the posterior MTG/STS to anterior lateral temporal cortex. The representations in the dorsal core system did not appear to have strong similarities with those in the ventral core system, consistent with the functional distinction between dorsal and ventral areas suggested by others[48, 8]. Based on the results reported here, we propose that the anterior areas in the fusiform gyrus, the anterior MTG/STS, and the IFG may be the convergence of the ventral and dorsal pathways in which representations of faces become invariant to facial attributes such as head position[9,11] and perhaps other social attributes. For example, the right anterior STS plays a role in the representation of the dangerousness of animals[49] and may play a role in the representation of social impressions, such as trustworthiness and aggressiveness[50]. The hierarchy of areas proposed in this work provides a testable model for future studies aimed at further characterizing the transformations operating on the representation of faces, from retinotopic input to higher order areas.

Using MVPC, we teased apart neural responses due to factors that are shared by
familiar faces from factors that are specific to familiar and unfamiliar identities. While
standard univariate analyses necessarily conflate identity information with familiarity
information, we used different cross-validation schemes in the MVPC to separate
familiarity information from identity information. To separate identity-independent
familiarity information from identity-specific visual information, we used a cross-
validation scheme in MVPC of face familiarity in which we tested the classifier on
identities that were not included in the training data. To investigate identity-specific
information that was independent of familiarity, we tested MVPC of familiar and
unfamiliar identities separately.

We found reliable decoding of identity-independent familiarity in extended system
areas that showed stronger responses to familiar faces in univariate analyses, such as
theory of mind areas (precuneus, TPJ, and MPFC), consistent with previous reports[2,13].
Univariate and multivariate analyses were complementary in that they tested different
properties of the BOLD response (differences in mean activations vs. patterns): the
two resulting maps showed some but not complete correspondence, highlighting that
multivariate analyses leveraged additional information other than magnitude
differences. In addition, MVPC of familiarity was designed to test for a familiarity effect
that was not specific to familiar individuals, revealing that this network does carry
such identity-independent information about the familiarity of faces. Both the
univariate and MVPC results expand the areas reported previously to include
additional areas that are components of the dorsal and anterior core system for face
perception in the MTG/STS, anterior fusiform cortex, and IFG. We suspect that our
relatively large sample size made it possible to identify this more extensive network.

In this experiment subjects had to perform an oddball-detection task to ensure that
they paid attention to the stimuli. It is possible that some of the decoding results for
familiarity might be attributed to differences in attentional demands between
personally familiar and unfamiliar faces, but it is hard to predict the direction of an
effect of attention. Behavioral evidence suggests that personally familiar faces are
processed faster[20–23,51], and require fewer attentional resources[19]. On the other hand,
we also have shown that familiar faces, relative to unfamiliar faces, slow down shifts

of attention away from the face, suggesting they hold attention[52]. We found reduced

BOLD activation to personally familiar faces only in the IPL[53,54], while areas of the core

and extended systems showed stronger responses. If the stronger response to

familiar faces in core and extended system areas were due to spontaneous attention,

one would also expect a stronger response in the IPL and other attention-related

cortical areas, which we did not find.

Unexpectedly, we found significant decoding of familiarity information in early visual

cortex while controlling for identity information. Additional ROI decoding analyses in

early visual areas[38] revealed that familiarity information could be decoded in V2 and V3

(see Supplementary Material). Low-level image differences did not seem to explain

this finding: familiar and unfamiliar faces were indistinguishable using features

extracted from the HMAX model[39,40]. Recent studies have shown that feedback

information from higher-order visual areas to early visual cortex carries fine-grained

information about the category of the stimuli being observed[55,56], suggesting that

feedback processes might have contributed to the significant familiarity decoding in

early visual areas. However, future studies with paradigms designed to address the

nature of these feedback processes are needed to further test this possibility.

In addition to identity-independent familiarity, the same network carries information

about specific identities. We tested for this type of information with separate MVPC

analyses of four familiar identities and four unfamiliar identities. By not including

familiar and unfamiliar identities in the same analysis, we could test for identity-

specific neural patterns that were not dependent on familiarity. Again, this network

was more extensive than that reported in previous studies[11,57–63] (most probably due to

the larger number of subjects and, perhaps, the inclusion of personally familiar faces).

Importantly, this network included the IFG, consistent with previous work[11,12], and

extended into the MTG/STS, TPJ, precuneus, and MPFC.

Identity decoding was also found in early visual cortex and the posterior ventral core

system, likely reflecting to some extent image-specific information. In a recent

experiment[11] we showed that view-dependent representation of faces was the

dominant factor in early visual cortex and the OFA. We did not find a significant

difference in MVPC of familiar identities as compared to MVPC of unfamiliar identities,
despite the large number of subjects in this study. There was a nonsignificant trend
towards higher MVPC accuracies for familiar identities in the IFG and MTG/STS, but
more work explicitly designed to investigate view-invariant representations of identity
is needed to establish whether these trends are real.

Conclusions

Our results revealed new structure in the distributed system for face perception,
suggesting that the core system can be subdivided into ventral, dorsal, and anterior
components based on differences of representations. The anterior portion of the core
system may be the point at which the ventral and dorsal pathways converge to
generate view-independent representations of identity and of socially-relevant visual
information, such as direction of attention. Identity-independent information about
familiarity could be decoded in extended system areas such as the TPJ, precuneus,
and MPFC, as well as in dorsal and anterior core system areas such as the MTG/STS,
anterior fusiform cortex, and IFG. In sum, these results reveal new information about
how face perception, one of the most highly developed and socially relevant visual
functions, is realized in an extensive distributed system involving cortical fields in
occipital, temporal, parietal, and prefrontal cortices.

Materials and Methods

Participants

Thirty-three young adults participated in the experiment (mean age 23 y.o. +/- 3.33
SD, 13 males). They were recruited from the Dartmouth College community and all
had normal or corrected-to-normal vision. Prior to the imaging study we took pictures
of four friends for each participant to use as familiar stimuli. Some of these friends
also were study participants (pictures of 76 individuals were taken as familiar stimuli).
Photos of unfamiliar individuals were collected at the University of Vermont
(Burlington) using the same camera and lighting conditions. All individuals signed
written informed consent to use their pictures for research and in publications. Prior to

participation in the fMRI study, subjects were screened for MRI compliance and
provided informed consent. The study was approved by the Committee for the
Protection of Human Subjects at Dartmouth College and was conducted according to
the principles of the Declaration of Helsinki. Participants received monetary
compensation for their time.

362 Stimuli

The stimuli for the fMRI experiment were pictures portraying different familiar and
unfamiliar identities: four friends' faces, four unknown faces, and the subject's own
face. For each identity we used three images with different head orientations: frontal
view and 30-degree profiles to the left and right with gaze towards the camera. All
photos on both sites (Dartmouth College and University of Vermont) were taken using
the same consumer-grade digital camera in a dedicated photo-studio room with black
background and uniform lighting.

Each familiar face was matched with an unfamiliar individual face, similar in age,
gender and ethnicity. Twenty-seven images (9 individuals, 3 head positions) were
used in the experimental design per each subject. Stimuli were presented to the
subjects in the MRI scanner using a projection screen positioned at the rear of the
scanner and viewed through a mirror mounted on the head coil.

The original high-resolution digital images were cropped to include the face from the
top of the head to the neck visible under the chin, centered on the face. Images were
scaled to 400x400 pixels. Images subtended approximately 10x10 degrees of visual
angle.

379 Procedure

The stimuli were presented using a slow event-related design while subjects were
engaged in a simple oddball task (Figure 1). A typical trial consisted of three different
images of the same individual, each presented for 500 ms with no gap. On catch
trials, one of the three images was of a different individual. The order of head
orientations within trials was randomized. The task was included to make sure that
subjects paid attention to the identity of the faces. Before entering the scanner,

subjects had a short practice session with each condition (one trial for each of 9

identities, one blank trial, and one catch trial) to be familiarized with the design and the

stimuli.

The order of the events was pseudo-randomized to approximate a first-order

counterbalancing of conditions[64]. A functional run comprised 48 trials: four trials for

each of the nine individuals (four familiar, four unfamiliar and self), four blank trials,

four oddball and four buffer trials (three at the beginning and one at the end). The

buffer trials were added to optimize the trial order and were discarded from the

analysis. Each run had 10 seconds of fixation at the beginning (to stabilize the

hemodynamic response) and at the end (to collect the response to the last trials).

Each session consisted of 11 functional runs, resulting in 396 non-oddball trials (44 for

each of the nine identities).

Image acquisition

Brain images were acquired using a 3T Philips Achieva Intera scanner with a 32-

channel head coil. Functional imaging used gradient-echo echo-planar-imaging with

SENSE reduction factor of 2. The MR parameters were TE/TR = 35/2000 ms, Flip

angle = 90°, in-plane resolution = 3×3 mm, matrix size of 80×80 and FOV = 240×240

mm. 35 axial slices were acquired with no gap covering the entire brain except the

most dorsal portion (Supplementary Figure 9). Slices were acquired in the Philips-

specific interleaved order (slice step of 6, i.e., ceiled square root of total number of

slices). Each of the 11 functional runs included 154 dynamic scans with 4 dummy

scans for a total time of 316 seconds per run. After the functional runs a single high-

resolution T1-weighted (TE/TR = 3.7/8.2 ms) anatomical scan was acquired with a 3D-

TFE sequence. The voxel resolution was 0.938×0.938×1.0 mm with a bounding box

matrix of 256×256×160 (FOV = 240×240×160 mm).

Image preprocessing

All preprocessing steps were run using a Nipype workflow (version 0.11.0; FSL version

5.0.9)[65,66], which also used functions from SciPy[67] and NumPy[68]. We modified the

preprocessing pipeline *fmri_ants_openfmri.py* and adapted it for our analyses. The

modified version is available at https://www.github.com/mvdoc/famface. All the
preprocessing analyses were run on a computing cluster running Debian Jessie with
tools provided by the NeuroDebian repository[69].

Preprocessing Steps

We used a standard FSL preprocessing pipeline (FEAT) as implemented in Nipype
(*nipype.preprocess.create_featreg_preproc*), using a FWHM smoothing of 6 mm, a
highpass filter at 60 s cutoff, and the first volume of the first run as a reference for EPI
alignment. After motion correction, the BOLD time-series were masked with a dilated
gray-matter mask, smoothed, and then high-pass filtered. The preprocessed data
were then used for a GLM and MVPA analysis, with additional preprocessing steps as
described in the following sections.

Template Registration

Each subject's data (functional or second-level betas) were resliced into the MNI
template with 2 mm isotropic voxel size. First, a reference volume was created by
computing a median temporal SNR volume across functional runs. Then, we
computed an affine transformation registering this median tSNR volume to the
subject's anatomical scan using FSL's FLIRT tool[70], and the transformation was
improved using the BBR cost function. A second non-linear transformation registering
the subject's anatomical image to the MNI template was computed using ANTs[71] with
default parameters. The affine and nonlinear transformations were then combined to
reslice the reference volume and all the functional volumes and second-level betas
into the MNI template. Results from this registration pipeline were visually inspected
for each subject.

MVPA Preprocessing

First, we resliced the bold time-series into the MNI template using a combination of
linear and nonlinear transformations (see Template Registration section). Then, we
extracted beta parameters associated with each condition for each run using
PyMVPA's *fit_event_hrf_model* [72] function based on NiPy's functionality[73]. Additional
nuisance regressors comprised motion estimates, artifacts (volumes were marked as

artifact if their intensity exceeded three standard deviations of the normalized
intensity), and noise estimates. To obtain noise estimates we used the CompCor
method[74]. In brief, we performed a GLM on the BOLD timeseries in the voxels
belonging to each subject's white-matter mask projected in MNI space. The
regressors of this GLM were the motion estimates and volumes marked as artifacts.
We then performed PCA on the residuals, and took the first 5 components as noise
estimates.

451 Univariate analyses

The first-level and second-level analyses (fixed effect) for each subject were
performed in the subject's individual space, and the results were then projected into a
standard template (FSL's MNI152, 2 mm isotropic, see details in the Template
Registration section). These analyses followed a standard FSL pipeline as
implemented in Nipype (*nipype.estimate.create_modelfit_workflow* and
nipype.estimate.create_fixed_effects_flow). A standard GLM analysis was performed
separately for each run to extract beta values associated with each condition and the
planned contrasts. Additional nuisance regressors comprised motion estimates,
artifacts (volumes were marked as artifact if their intensity exceeded three standard
deviations of the normalized intensity), and first-order derivatives. A second-level
analysis was performed to obtain per-subject statistical maps associated with each
condition and contrast using FSL's *FLAMEO* (fixed-effect model). The statistical maps
were then resliced into the MNI152 template (see details above), and a third-level
analysis was performed across subjects using FSL's *FLAMEO* (mixed-effect model).
The resulting z-stat maps were then corrected for multiple comparisons using FSL's
cluster routine, with a voxel z-threshold set at 2.3, and cluster p-value of p = .05. The
Nipype pipeline we used for third-level analysis can be found at
https://www.github.com/mvdoc/famface[1].

---

[1] We thank Satrajit Ghosh and Anne Park for sharing the original pipeline.

Multivariate analyses

Classification methods

MVPC was implemented in Python using PyMVPA[72] http://www.pymvpa.org). GLM betas were estimated within each run for each condition (see MVPA Preprocessing section). For all analyses we kept only the betas for the four familiar and the four unfamiliar identities, discarding trials where subjects saw their own face, or responded to an oddball presentation. The betas were then z-scored within each run (separately for each voxel) and used as features for classification. We used Linear C-SVM as a classifier, as implemented in LIBSVM[75]. The C parameter was set to the PyMVPA default, which scales it according to the mean norm of the training data.

Cross-validation

We used a leave-one-out (LOO) scheme for cross-validation. The splitting unit was dependent on the type of classification (familiarity or identity). For familiarity classification, we cross-validated across pairs of identities. We trained the classifier on three familiar and three unfamiliar identities, and tested on the left-out identities. This resulted in 16 cross-validation splits that allowed us to control for identity information (see Supplementary Figures 1 and 2 for a comparison of leave-one-run-out and leave-two-identities-out cross-validation schemes). For identity classification, we cross-validated across runs, resulting in a leave-one-run-out scheme (11 splits). To remove the effect of familiarity on classification of face identity, we performed identity classification independently for familiar and unfamiliar identities, and averaged the resulting accuracy maps.

Searchlight

We used sphere searchlights[76] to extract local features for classification. We selected a 5-voxel radius (10 mm), and moved the searchlight sphere across the voxels belonging to a union mask in which at least 26 subjects (~80%, arbitrarily chosen) had fMRI coverage (see Supplementary Figure 9), as well as selecting only gray- and white-matter voxels in the cerebrum. For each center voxel in this mask, we selected

498 nearby voxels contained in a sphere, and used them as features for classification. The
499 classifier's accuracy was stored in the central voxel, and the process was repeated for
500 every voxel.

Statistical assessment

To determine statistical significance for the MVPC analyses, we performed
permutation testing[77] coupled with Threshold-Free Cluster Enhancement (TFCE)[78], as
implemented in CoSMoMVPA[79]. For each subject and each classification analysis, we
computed a null distribution by randomly permuting the labels and performing
classification. For identity classification analysis, we randomly shuffled the identity
labels within each run, and performed classification. This procedure was repeated 20
times for each subject. For familiarity analysis, we randomly permuted the familiarity
labels across the entire experiment. This was repeated exhaustively, resulting in 35
permutations (see Supplementary Materials for a short proof that only 35 unique
permutations are possible in this case). To create a null distribution of TFCE values for
each voxel, permutation maps were randomly sampled and averaged across subjects,
and this process was repeated 10,000 times. Note that we selected a smaller number
of permutations than suggested[77] (100 per subject) because of the large number of
subjects we had: with 33 subjects, the number of possible average maps for identity
classification was 20^{33} and for familiarity classification was 35^{33}.

Similarity of neural representations within ROIs

Second-order Representational Similarity Analysis

We defined ROIs based on the searchlight results for both the familiarity and identity
classification. Thirty spherical ROIs were centered on voxels selected manually at or
near peak values, with a 10 mm radius (five voxels). Voxels belonging to more than
one ROI were assigned to the ROI with the closest center (Euclidean distance),
resulting in some contiguous but not overlapping ROIs (see Figure 5). On average,
ROIs contained 412 voxels at a 2 mm isotropic resolution (SD: 73 voxels).

For each ROI we computed a cross-validated representational dissimilarity matrix
(RDM)[41] between the eight identities (four familiar faces, four unfamiliar faces). First,

we z-scored the beta estimates within each run, which were computed as described

in the MVPA Preprocessing section. Then, we divided all runs into two partitions of six

and five runs, and averaged the beta values within each partition. The data between

these two partitions were correlated (Pearson correlation) to obtain an 8x8 matrix of

dissimilarities between pairs of identities. Note that because correlations were

computed between data from two different partitions, the diagonal could be different

from one. This process was repeated for every possible combination of runs, yielding

462 RDMs that were averaged to obtain a final RDM for each ROI and each subject.

The final RDMs were made symmetrical by averaging them with their transpose. All

averaging operations were performed on Fisher-transformed (r-to-z) correlation

values, then mapped back to correlation using the inverse transformation.

We used these final RDMs to compute pairwise distances between ROIs for each

subject individually using correlation distance. The resulting 33 distance matrices (one

for each subject) were averaged to obtain a group-level distance matrix. This distance

matrix was used to compute a three-dimensional MDS solution, using classical MDS

as implemented in R (*cmdscale*) interfaced in Python using *rpy2*[80].

Comparison with movie data

To investigate the reproducibility of the network formed by the ROIs defined above,

we computed between-subject correlation distances across these ROIs using

hyperaligned data from a different study, in which eleven participants watched

"Raiders of the Lost Ark"[34,42]. Since data were functionally aligned with

hyperalignment[34,42], we performed a between-subject analysis instead of a within-

subject analysis, where distances between pairwise ROIs were computed across

subjects, replicating the approach in Guntupalli et al.[34]. Additional details on the

experimental paradigm and scanning parameters can be found in the Supplementary

Material.

Because data were in two different resolutions of the same template (task: MNI 2 mm;

movie: MNI 3 mm), center coordinates of the spherical ROIs were recalculated

assigning the closest voxel in MNI 3 mm using Euclidean distance. The median

displacement was 1.41 mm (min: 1 mm, max: 1.73 mm). As described above,

spherical ROIs were drawn around these center voxels using a radius of 9 mm (3

voxels) to account for the different voxel size. Overlapping voxels were assigned to

the ROI with the closest center, resulting in possibly contiguous but not overlapping

ROIs. On average ROIs contained 100 voxels (SD: 20 voxels).

The movie data were masked selecting only white- and gray-matter voxels, and

divided into two parts for cross-validation. For each of the two parts, whole-brain

searchlight hyperalignment parameters were derived from one part of the movie, and

the second part was projected into the common model space in functional alignment

[34,42]. The aligned data were z-scored, and timepoint-by-timepoint RDMs were

computed in each ROI for each subject individually, yielding a 1322 x 1322 RDM

within each ROI (1336 x 1336 for the second fold of hyperalignment). Following the

analysis in (Guntupalli et al., 2016) we estimated a distance matrix between ROIs while

cross-validating across subjects. For each pair of ROIs, the correlation between their

RDMs was computed for all 55 pairs of subjects, and averaged to compute the cross-

validated correlation between those ROIs. This process resulted in two 30x30 cross-

validated distance matrices (one for each hyperalignment fold), which were made

symmetrical by averaging them with their transpose, and finally averaged together to

obtain one final 30x30 matrix. All averaging operations were computed on Fisher-

transformed (r-to-z) correlation values, then mapped back to correlation using the

inverse transformation. Finally, a dissimilarity index (D) was computed for each pair of

ROIs to normalize the correlation according to the maximum possible correlation

within each ROI[33]:

$$D_{ROI1 \cdot ROI2} = 1 - \frac{r_{ROI1 \cdot ROI2}}{\sqrt{r_{ROI1} \cdot r_{ROI2}}}$$

580   The final matrix containing dissimilarity indices was then used to compute an MDS

581   solution as described previously.

Differences between core and extended system representational geometries

583   In order to quantify differences in representational geometries between areas of the

584   core and extended systems, we divided the pairwise distances between ROIs in the

upper triangular RDM into within-system and between-system cells, and converted them back to correlations (by subtracting them from 1). Then, we ran a Linear Mixed-Effect Model on the correlations using *lme4*[54], fitting a linear model of the form

$$r_{i,j} = \beta_0 + \beta_1 C_{i,j} + \beta_2 E_{i,j} + z_i ,$$

where $i = 1 \dots N$ indicates either the subjects for task data ($N = 33$) or the pairwise subjects for hyperaligned movie data ($N = 55$); $j = 1 \dots 465$ indicates the index of the pairwise correlations between ROIs, $C_{i,j}$ and $E_{i,j}$ indicate whether $r_{i,j}$ is a within-system correlation for the core or extended system respectively, $\beta_0, \beta_1, \beta_2$ are fixed-effects parameters, and z_i are the subject-level random effects. Using this model, β_1 corresponds to the contrast "Within Core > Between", and β_2 to the contrast "Within Extended > Between". After fitting, we performed parametric bootstrapping to obtain 95% bootstrapped confidence intervals on the model parameters.

Visualization

Volumetric results were visualized using Nilearn [82], and projected on template surfaces using AFNI and SUMA [83,84].

Data and code availability

Non-thresholded statistical maps can be found on neurovault.org [85] at the following URL: http://neurovault.org/collections/NEUNABLT. All data can be found at http://datasets.datalad.org/?dir=/labs/gobbini/famface/data. The code used for the analyses is available at the following github repository: https://www.github.com/mvdoc/famface.

Acknowledgments

The authors would like to thank Jim Haxby, Brad Duchaine, the members of the GobbiniLab and HaxbyLab for helpful comments and discussions on this work, and Courtney Rogers for invaluable help with subject recruitment.

References

1. Haxby, J. V., Hoffman, E. A. & Gobbini, M. I. The distributed human neural system

for face perception. *Trends Cogn. Sci.* **4,** 223–233 (2000).

2. Gobbini, M. I. & Haxby, J. V. Neural systems for recognition of familiar faces.

Neuropsychologia **45,** 32–41 (2007).

3. Haxby, J. V. & Gobbini, M. I. Distributed neural systems for face perception. in

Oxford Handbook of Face Perception (eds. Calder, A., Rhodes, G., Johnson, M. &

Haxby, J.) (OUP Oxford, 2011).

4. Gobbini, M. I. Distributed process for retrieval of person knowledge. *Social*

neuroscience: Toward understanding the underpinnings of the social mind 40–53

(2010).

5. Collins, J. A. & Olson, I. R. Beyond the FFA_ The role of the ventral anterior

temporal lobes in face processing. *Neuropsychologia* **61,** 65–79 (2014).

6. Rajimehr, R., Young, J. C. & Tootell, R. B. H. An anterior temporal face patch in

human cortex, predicted by macaque maps. *Proc. Natl. Acad. Sci. U. S. A.* **106,**

1995–2000 (2009).

7. Duchaine, B. & Yovel, G. A Revised Neural Framework for Face Processing.

Annual Review of Vision Science **1,** 393–416 (2015).

8. Pitcher, D., Dilks, D. D., Saxe, R. R., Triantafyllou, C. & Kanwisher, N. Differential

selectivity for dynamic versus static information in face-selective cortical regions.

Neuroimage **56,** 2356–2363 (2011).

9. Carlin, J. D., Calder, A. J., Kriegeskorte, N., Nili, H. & Rowe, J. B. A head view-

invariant representation of gaze direction in anterior superior temporal sulcus.

Curr. Biol. **21,** 1817–1821 (2011).

10. Haxby, J. V. *et al.* The functional organization of human extrastriate cortex: a PET-

rCBF study of selective attention to faces and locations. *J. Neurosci.* **14,** 6336–

6353 (1994).

11. Guntupalli, J. S., Wheeler, K. G. & Gobbini, M. I. Disentangling the Representation

of Identity from Head View Along the Human Face Processing Pathway. *Cereb.*

Cortex (2017). doi:10.1093/cercor/bhw344

12. Axelrod, V. On the domain-specificity of the visual and non-visual face-selective

regions. *Eur. J. Neurosci.* **44,** 2049–2063 (2016).

13. Natu, V. & O'Toole, A. J. The neural processing of familiar and unfamiliar faces: A

review and synopsis. *Br. J. Psychol.* **102,** 726–747 (2011).

14. Gobbini, M. I. & Haxby, J. V. Neural response to the visual familiarity of faces.

Brain Res. Bull. **71,** 76–82 (2006).

15. Taylor, M. J. *et al.* Neural correlates of personally familiar faces: parents, partner

and own faces. *Hum. Brain Mapp.* **30,** 2008–2020 (2009).

16. Cloutier, J., Kelley, W. M. & Heatherton, T. F. The influence of perceptual and

knowledge-based familiarity on the neural substrates of face perception. *Soc.*

Neurosci. **6,** 63–75 (2011).

17. Bobes, M. A., Lage Castellanos, A., Quiñones, I., García, L. & Valdes-Sosa, M.

Timing and tuning for familiarity of cortical responses to faces. *PLoS One* **8,**

e76100 (2013).

18. Ida Gobbini, M., Leibenluft, E., Santiago, N. & Haxby, J. V. Social and emotional

attachment in the neural representation of faces. *Neuroimage* **22,** 1628–1635

(2004).

19. Gobbini, M. I. *et al.* Prioritized Detection of Personally Familiar Faces. *PLoS One*

8, e66620 (2013).

20. Visconti di Oleggio Castello, M. & Gobbini, M. I. Familiar Face Detection in

180ms. *PLoS One* **10,** e0136548 (2015).

21. Visconti di Oleggio Castello, M., Guntupalli, J. S., Yang, H. & Gobbini, M. I.

Facilitated detection of social cues conveyed by familiar faces. 1–11 (2014).

22. Visconti di Oleggio Castello, M., di Oleggio Castello, M. V., Wheeler, K. G., Cipolli,

C. & Gobbini, M. I. Familiarity Facilitates Feature-based Face Processing. (2016).

doi:10.1101/058537

23. Ramon, M., Vizioli, L., Liu-Shuang, J. & Rossion, B. Neural microgenesis of

personally familiar face recognition. *Proc. Natl. Acad. Sci. U. S. A.* **112,** E4835–

E4844 (2015).

24. Burton, A. M., Wilson, S., Cowan, M. & Bruce, V. Face Recognition in Poor-

Quality Video: Evidence From Security Surveillance. *Psychol. Sci.* **10,** 243–248

(1999).

25. Bruce, V., Henderson, Z., Newman, C. & Burton, A. M. Matching identities of

familiar and unfamiliar faces caught on CCTV images. *J. Exp. Psychol. Appl.* **7,**

207 (2001).

26. Diamond, R. & Carey, S. Why faces are and are not special: An effect of

expertise. *J. Exp. Psychol. Gen.* **115,** 107 (1986).

27. Hancock, P., Bruce, V. & Burton, A. M. Recognition of unfamiliar faces. *Trends*

Cogn. Sci. (2000).

28. Jenkins, R. & Burton, A. M. Stable face representations. *Philos. Trans. R. Soc.*

Lond. B Biol. Sci. **366,** 1671–1683 (2011).

29. Burton, A. M., Jenkins, R. & Schweinberger, S. R. Mental representations of

familiar faces. *Br. J. Psychol.* **102,** 943–958 (2011).

30. Haxby, J. V. *et al.* Distributed and overlapping representations of faces and

objects in ventral temporal cortex. *Science* **293,** 2425–2430 (2001).

31. Haxby, J. V., Connolly, A. C. & Guntupalli, J. S. Decoding Neural Representational

Spaces Using Multivariate Pattern Analysis. *Annu. Rev. Neurosci.* **37,** 435–456

(2014).

32. Kriegeskorte, N. & Kievit, R. A. Representational geometry: integrating cognition,

computation, and the brain. *Trends Cogn. Sci.* **17,** 401–412 (2013).

33. Kriegeskorte, N., Mur, M. & Bandettini, P. Representational similarity analysis -

connecting the branches of systems neuroscience. *Front. Syst. Neurosci.* **2,** 4

(2008).

34. Guntupalli, J. S. *et al.* A Model of Representational Spaces in Human Cortex.

Cereb. Cortex bhw068 (2016).

35. Fairhall, S. L. & Ishai, A. Effective Connectivity within the Distributed Cortical

Network for Face Perception. *Cereb. Cortex* **17,** 2400–2406 (2007).

36. Weiner, K. S. *et al.* The mid-fusiform sulcus: A landmark identifying both

cytoarchitectonic and functional divisions of human ventral temporal cortex.

Neuroimage 1–13 (2013).

37. Grill-Spector, K. & Weiner, K. S. The functional architecture of the ventral

temporal cortex and its role in categorization. *Nat. Rev. Neurosci.* **15,** 536–548

(2014).

38. Wang, L., Mruczek, R. E. B., Arcaro, M. J. & Kastner, S. Probabilistic Maps of

Visual Topography in Human Cortex. *Cereb. Cortex* **25,** 3911–3931 (2015).

39. Riesenhuber, M. & Poggio, T. Hierarchical models of object recognition in cortex.

Nat. Neurosci. **2,** 1019–1025 (1999).

40. Serre, T., Wolf, L., Bileschi, S., Riesenhuber, M. & Poggio, T. Robust object

recognition with cortex-like mechanisms. *IEEE Trans. Pattern Anal. Mach. Intell.*

29, 411–426 (2007).

41. Henriksson, L., Khaligh-Razavi, S.-M., Kay, K. & Kriegeskorte, N. Visual

representations are dominated by intrinsic fluctuations correlated between areas.

Neuroimage 1–48 (2015).

42. Haxby, J. V. *et al.* A Common, High-Dimensional Model of the Representational

Space in Human Ventral Temporal Cortex. *Neuron* **72,** 404–416 (2011).

43. Simony, E. *et al.* Dynamic reconfiguration of the default mode network during

narrative comprehension. *Nat. Commun.* **7,** 12141 (2016).

44. Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E. & Gallant, J. L.

Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature*

532, 453–458 (2016).

45. Abdi, H. Congruence: Congruence coefficient, RV coefficient, and mantel

coefficient. *Encyclopedia of research design* 222–229 (2010).

46. Abdi, H. RV coefficient and congruence coefficient. *Encyclopedia of measurement*

and statistics 849–853 (2007).

47. Carlin, J. D., Rowe, J. B., Kriegeskorte, N., Thompson, R. & Calder, A. J.

Direction-sensitive codes for observed head turns in human superior temporal

sulcus. *Cereb. Cortex* **22,** 735–744 (2012).

48. O'Toole, A. J., Roark, D. A. & Abdi, H. Recognizing moving faces: a psychological

and neural synthesis. *Trends Cogn. Sci.* **6,** 261–266 (2002).

49. Connolly, A. C. *et al.* How the Human Brain Represents Perceived Dangerousness

or 'Predacity' of Animals. *J. Neurosci.* **36,** 5373–5384 (2016).

50. Todorov, A., Gobbini, M. I., Evans, K. K. & Haxby, J. V. Spontaneous retrieval of

affective person knowledge in face perception. *Neuropsychologia* **45,** 163–173

(2007).

51. Ramon, M., Caharel, S. & Rossion, B. The speed of recognition of personally

familiar faces. *Perception* **40,** 437–449 (2011).

52. Chauhan, V., Visconti di Oleggio Castello, M., Soltani, A. & Gobbini, M. I. Social

Saliency of the Cue Slows Attention Shifts. *Front. Psychol.* **8,** 738 (2017).

53. Corbetta, M. & Shulman, G. L. Control of goal-directed and stimulus-driven

attention in the brain. *Nat. Rev. Neurosci.* **3,** 201–215 (2002).

54. Singh-Curry, V. & Husain, M. The functional role of the inferior parietal lobe in the

dorsal and ventral stream dichotomy. *Neuropsychologia* **47,** 1434–1448 (2009).

55. Muckli, L. *et al.* Contextual Feedback to Superficial Layers of V1. *Curr. Biol.* **25,**

2690–2695 (2015).

56. Morgan, A. T., Petro, L. S. & Muckli, L. Cortical feedback to V1 and V2 contains

unique information about high-level scene structure. *bioRxiv* 041186 (2016).

doi:10.1101/041186

57. Nestor, A., Plaut, D. C. & Behrmann, M. Unraveling the distributed neural code of

facial identity through spatiotemporal pattern analysis. *Proc. Natl. Acad. Sci. U. S.*

A. **108,** 9998–10003 (2011).

58. Natu, V. S. *et al.* Dissociable neural patterns of facial identity across changes in

viewpoint. *J. Cogn. Neurosci.* **22,** 1570–1582 (2010).

59. Anzellotti, S., Fairhall, S. L. & Caramazza, A. Decoding Representations of Face

Identity That are Tolerant to Rotation. *Cereb. Cortex* (2013).

60. Kriegeskorte, N., Formisano, E., Sorger, B. & Goebel, R. Individual faces elicit

distinct response patterns in human anterior temporal cortex. *Proc. Natl. Acad.*

Sci. U. S. A. **104,** 20600–20605 (2007).

61. Verosky, S. C., Todorov, A. & Turk-Browne, N. B. Representations of individuals

in ventral temporal cortex defined by faces and biographies. *Neuropsychologia*

51, 2100–2108 (2013).

62. Axelrod, V. & Yovel, G. Successful decoding of famous faces in the fusiform face

area. *PLoS One* **10,** e0117126 (2015).

63. Goesaert, E. & Op de Beeck, H. P. Representations of facial identity information in

the ventral visual stream investigated with multivoxel pattern analyses. *J.*

Neurosci. **33,** 8549–8558 (2013).

64. Aguirre, G. K. Continuous carry-over designs for fMRI. *Neuroimage* **35,** 1480–

1494 (2007).

65. Jenkinson, M., Beckmann, C. F., Behrens, T. E. J., Woolrich, M. W. & Smith, S. M.

FSL. *Neuroimage* **62,** 782–790 (2012).

66. Gorgolewski, K., Burns, C. D., Madison, C. & Clark, D. Nipype: a flexible,

lightweight and extensible neuroimaging data processing framework in python.

Front … (2011).

67. Jones, E., Oliphant, T. & Peterson, P. SciPy: Open source scientific tools for

Python. (2001). Available at: http://www.scipy.org/.

68. van der Walt, S., Colbert, S. C. & Varoquaux, G. The NumPy Array: A Structure for

Efficient Numerical Computation. *Comput. Sci. Eng.* **13,** 22–30 (2011).

69. Halchenko, Y. O. & Hanke, M. Open is Not Enough. Let's Take the Next Step: An

Integrated, Community-Driven Computing Platform for Neuroscience. *Front.*

Neuroinform. **6,** 22 (2012).

70. Jenkinson, M., Bannister, P., Brady, M. & Smith, S. Improved optimization for the

robust and accurate linear registration and motion correction of brain images.

Neuroimage **17,** 825–841 (2002).

71. Avants, B. B., Tustison, N. & Song, G. Advanced normalization tools (ANTS).

Insight J. **2,** 1–35 (2009).

72. Hanke, M. *et al.* PyMVPA: a Python Toolbox for Multivariate Pattern Analysis of

fMRI Data. *Neuroinformatics* **7,** 37–53 (2009).

73. Millman, K. J. & Brett, M. Analysis of Functional Magnetic Resonance Imaging in

Python. *Computing in Science Engineering* **9,** 52–55 (2007).

74. Behzadi, Y., Restom, K., Liau, J. & Liu, T. T. A component based noise correction

method (CompCor) for BOLD and perfusion based fMRI. *Neuroimage* **37,** 90–101

(2007).

75. Chang, C.-C. & Lin, C.-J. LIBSVM: A library for support vector machines. *ACM*

Trans. Intell. Syst. Technol. **2,** 1–27 (2011).

76. Kriegeskorte, N., Goebel, R. & Bandettini, P. Information-based functional brain

mapping. *Proceedings of the National Academy of Sciences* **103,** 3863–3868

(2006).

77. Stelzer, J., Chen, Y. & Turner, R. Statistical inference and multiple testing

correction in classification-based multi-voxel pattern analysis (MVPA): Random

permutations and cluster size control. *Neuroimage* **65,** 69–82 (2013).

78. Smith, S. M. & Nichols, T. E. Threshold-free cluster enhancement: addressing

problems of smoothing, threshold dependence and localisation in cluster

inference. *Neuroimage* **44,** 83–98 (2009).

79. Oosterhof, N. N., Connolly, A. C. & Haxby, J. V. CoSMoMVPA: Multi-Modal

Multivariate Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave. *Front.*

Neuroinform. **10,** 27 (2016).

80. Gautier, L. rpy2: A Simple and Efficient Access to R from Python. *URL http://rpy.*

sourceforge. net/rpy2. html (2008).

81. Bates, D., Maechler, M., Bolker, B. & Walker, S. Package 'lme4'. *R Foundation for*

… (2014).

82. Abraham, A. *et al.* Machine learning for neuroimaging with scikit-learn. *Front.*

Neuroinform. **8,** 14 (2014).

83. Cox, R. W. AFNI: software for analysis and visualization of functional magnetic

resonance neuroimages. *Comput. Biomed. Res.* **29,** 162–173 (1996).

84. Saad, Z. S., Reynolds, R. C., Argall, B., Japee, S. & Cox, R. W. SUMA: an

interface for surface-based intra- and inter-subject analysis with AFNI. in *2004*

2nd IEEE International Symposium on Biomedical Imaging: Nano to Macro (IEEE

Cat No. 04EX821) 1510–1513 Vol. 2 (2004).

85. Gorgolewski, K. J. *et al.* NeuroVault.org: a web-based repository for collecting

and sharing unthresholded statistical maps of the human brain. *Front.*

Neuroinform. **9,** 8 (2015).

822
823

Author contribution

825 MIG designed the experiment. JDG, JSG, and YOH conducted the experiment.

826 MVdOC, YOH, and JSG analyzed the data. JSG provided analytic tools and critical

827 input to the manuscript. MVdOC, YOH, and MIG wrote the manuscript.

Additional information

Competing financial interests

830 The authors declare no competing financial interests.