1

3   **Bystro: rapid online variant annotation and natural-language filtering at whole-genome**

4   **scale**

5   Alex V. Kotlar[1], Cristina E. Trevino[1], Michael E. Zwick[1], David J. Cutler[1], and Thomas S.

6   Wingo[1,2,3,*]

[1]Department of Human Genetics, Emory University School of Medicine

[2]Division of Neurology, Atlanta VA Medical Center.

[3]Department of Neurology, Emory University School of Medicine.

*Corresponding author:

Thomas S. Wingo

505K Whitehead Building

615 Michael Street NE

Atlanta, GA 30322-1047

404-727-4905 (office)

404-727-3728 (fax)

thomas.wingo@emory.edu

19
20

Abstract

Accurately selecting relevant alleles in large sequencing experiments remains

technically challenging. Bystro (*https://bystro.io/*) is the first online, cloud-based application that

makes variant annotation and filtering accessible to all researchers for terabyte-sized whole-

genome experiments containing thousands of samples. Its key innovation is a general-purpose,

natural-language search engine that enables users to identify and export alleles and samples of

interest in milliseconds. The search engine dramatically simplifies complex filtering tasks that

previously required programming experience or specialty command-line programs. Critically,

Bystro's annotation and filtering capabilities are orders of magnitude faster than previous

solutions, saving weeks of processing time for large experiments.

Keywords

Natural-language search, genomics, bioinformatics, annotation, filtering, web, online,

cloud, big data

Background

While genome-wide association studies (GWAS) and whole-exome sequencing (WES)

remain important components of human disease research, the future lies in whole-genome

sequencing (WGS), as it inarguably provides more complete data. The central challenge posed

by WGS is one of scale. Genetic disease studies require thousands of samples to obtain

adequate power, and the resulting WGS datasets are hundreds of gigabytes in size and contain

tens of millions of variants. Manipulating data at this scale is difficult. To find the alleles that

contribute to traits of interest, two steps must occur. First, the variants identified in a sequencing

experiment need to be described in a process called annotation, and second, the relevant

alleles need to be selected based on those descriptions in a procedure called variant filtering.

Annotating and filtering large numbers of variant alleles requires specialty software.

Existing annotators, such as ANNOVAR[1], SeqAnt[2], VEP[3], and GEMINI[4] have played an

important research role, and are sufficient for small to medium experiments (e.g.,10s to 100s of

WES samples). However, they require significant computer science training to use in offline,

distributed computing environments, and have substantial restrictions in terms of performance

and the maximum size of the data they will annotate online. Existing variant filtering solutions

are even more limited, with most analyses requiring researchers to program custom scripts,

which can result in errors that impact reproducibility[5]. Therefore, annotation and filtering are

not readily accessible to most scientists, and even bioinformaticians face challenges of

performance, cost and complexity.

Here we introduce an application called Bystro that significantly simplifies variant

annotation and filtering, while also improving performance by orders of magnitude and saving

weeks of processing time on large data sets. It is the first program capable of handling

sequencing experiments on the scale of thousands of whole-genome samples and tens of

millions of variants online in a web browser, and integrates the first, to our knowledge, publicly-

available, online natural-language search engine for filtering variants and samples from these

experiments. The search engine enables real-time (sub-second), nuanced variant filtering, both

across all samples and per sample, using simple phrases and interactive, web-based filters.

Bystro makes it possible to efficiently find alleles of interest in any sequencing experiment

without computer science training, improving reproducibility while reducing annotation and

filtering costs.

Results

To compare Bystro's capabilities with other recent programs, we submitted 1000

Genomes[6] Phase 1 and Phase 3 VCF files for annotation and filtering (Figure 1). Phase 1

contains 39.4 million variants from 1,092 WGS samples, while Phase 3 includes 84.9 million

alleles from 2,504 WGS samples. We first evaluated the online capabilities of the web-based

versions of Bystro, wANNOVAR[7], VEP, and GEMINI (running on the Galaxy[8] platform).

Bystro was the only program able to complete either 1000 Genomes Phase 1 or Phase 3 online,

and was also the only application to handle a $6x10^6$ variant subset of Phase 3, a size

representative of modest whole-genome experiments. When tested with $5x10^4 – 1x10^6$ variant

subsets of 1000 Genomes Phase 3, Bystro was approximately 144 – 212x faster than

GEMINI/Galaxy in generating a downloadable annotation and searchable result database, and

was significantly easier to use, as it did not require a separate annotation step (Figure 2). When

tested on a small trio data set, Bystro was able to identify *de novo* variants without any

additional software, and was 45x faster than GEMINI's de_novo tool (Additional file 1: Table

S1). Bystro and GEMINI/Galaxy produced similarly detailed outputs, with Bystro offering fewer,

but more complete and recent sources, as well as more detailed annotations for some classes

of data (Additional file 1: Table S2 ; Additional file 2). Notably GEMINI was found to work only

with the hg19 human genome assembly, whereas Bystro supports hg19, hg38, and a variety of

model organisms.

Figure 1 | **Using Bystro online to find alleles of interest in sequencing experiments. A**)

After logging in (*https://bystro.io/*), users upload one of more VCF or SNP-format files -

containing alleles from a sequencing experiment - from a computer or a connected Amazon

S3 bucket. Datasets of over 890GB, containing thousands of samples and tens of millions of

variants are supported. The data is rapidly annotated in the cloud, using descriptions from

public sources (e.g. RefSeq, dbSNP, Clinvar, and others). The annotated results can be

filtered using Bystro's natural-language search engine, and any search results can be saved

as new annotations. Annotated experiments and saved results can be viewed online,

downloaded as tab-delimited text, or uploaded back to linked Amazon S3 buckets. **B**) An

example of using Bystro's natural-language search engine to filter 1000 Genomes Phase 3

(*https://bystro.io/public*). To do so, users may type natural phrases, specific terms, numerical

ranges, or apply filters on any annotated field. Queries are flexible, allowing misspelled terms

such as "earl-onset" to accurately match. Complex tasks, such as identifying *de novo*

variants can be achieved by using Boolean operators (AND, OR, NOT, +, -), exact-match

filters, and user-defined terms. For instance, after labeling the "proband" and their "parents",

the user could simply search *proband –parents*, or combine with additional parameters for

more refined queries, i.e. *proband –parents missingness < .1 gnomad.exomes.af_nfe < .001.*

Figure 2 | **Online performance comparison of Bystro, VEP, wANNOVAR, and GEMINI**. Bystro, wANNOVAR, VEP, and GEMINI (running on Galaxy) we run under similar conditions. Total processing time was recorded for 1000 Genomes Phase 3 WGS VCF files, containing either the full data set (2,504 samples, 8.49×10^7 variant sites), or subsets (2,504 samples and 5×10^4, 3×10^5, 1×10^6, and 6×10^6 variants). Only Bystro successfully processed more than 1×10^6 variants online: wANNOVAR (not shown) could not complete the smallest 5×10^4 variant subset; VEP could not complete more than 5×10^4 variants; and GEMINI/Galaxy could not complete more than 1×10^6 variants. Online, VEP outputted a restricted subset of annotation data compared to its offline version. GEMINI and Bystro (but not VEP) outputted whole-genome CADD scores, while only Bystro also returned whole-genome PhyloP and PhastCons conservation scores. Bystro was faster than GEMINI/Galaxy by 144x-212x across all time points.

We next tested offline performance on identical servers to gauge performance in the

absence of web-related file-size and networking limitations. Bystro was 113x faster than

ANNOVAR and up to 790x faster than VEP, annotating all 8.5×10^7 variants and 2,504 samples

from Phase 3 in less than 3 hours (Table 1). Furthermore, ANNOVAR was unable to finish

either Phase 1 or Phase 3 annotations due to memory requirements (exceeding 60GB of RAM),

and VEP annotated Phase 3 at a rate of 10 variants per second, indicating that it would need at

least 98 days to complete. Critically, Bystro's run time grew linearly with the number of

submitted genotypes, suggesting that it could handle even hundreds of thousands of samples

within days.

While offering significantly faster performance, Bystro also provided 3.5x the number of

annotation output fields as ANNOVAR and 5.6x that of VEP (Additional file 3**).** Notably, unlike

ANNOVAR or VEP, Bystro annotated each sample relative to its genotype, reporting

homozygosity, heterozygosity, missingness, sample minor allele frequency, and labeling each

sample as homozygous, heterozygous, or missing. In contrast, ANNOVAR provided only

sample minor allele frequency, while VEP reported no sample-level data. We note that VEP is

capable of providing per-sample annotations (heterozygosity/homozygosity status), but we were

unable to use this feature for performance reasons. A detailed comparison of the exact settings

used is given (Additional file 2 ; Additional file 3).

To investigate annotation accuracy, we next compared Bystro with ANNOVAR and VEP

on a previously-analyzed synthetic dataset[9]. Overall, excellent concordance between all

methods was noted (Additional files 4, 5, and 6). For instance, in comparison with ANNOVAR,

allele position (>98%), allele identity (100%), and variant effects (>99%) were highly consistent

across all classes of variation, for sites that Bystro did not exclude for quality reasons

(Additional file 4).

In cases where the annotators disagreed, Bystro gave the more correct interpretations.

For instance, Bystro and VEP excluded reference sites (ALT: "."), while ANNOVAR annotated

such loci as "synonymous SNV"; it is of course incorrect to call reference sites variant

(Additional file 4 ; Additional file 5). In cases of insertions and deletions, which are often

ambgiuously represented in VCF files due to the format's padding requirements, Bystro always

provided the parsimonious left-shifted representation, while ANNOVAR and VEP occasionally

right-shifted variants (Additional file 4 ; Additional file 5). This is evident at

chr15:42680000CA>CAA, where both ANNOVAR and VEP called the insertion as occuring after

the first "A", with 2 bases of padding, rather than the simpler option after the first base, "C", with

1 base of padding (Additional file 1: Table S3). Similar results were found at multiallelic loci with

complex indels (Additional file 1: Table S4).

Similarly, in cases where Bystro and ANNOVAR or VEP disagreed on variant

consequences, Bystro always appeared correct relative to the underlying transcript set. For

example, in the case of the simple insertion chr19:41123094G>GG, Bystro correctly identified

all three overlapping transcripts (NM_003573;NM_001042544;NM_001042545), and noted the

variant as coding (exonic) relative to all three. In contrast, ANNOVAR called the allele as

disrupting a splice site, despite the fact that the nerest intron, and therefore splice site, was

37bp downstream (Additional file 1: Figure S1).

Additionally, Bystro's strict VCF quality control measures substantially improved

annotation accuracy.This is evident in the case of gnomAD, a VCF-format dataset that

represents the largest experiment on human genetic variation. While Bystro and ANNOVAR

provided identical gnomAD data for 93.7% of tested alleles, the remaining 6.3% were low-

quality gnomAD results that were included in ANNOVAR and excluded from Bystro (Additional

file 4). For instance, in the case of chr16:2103394C>T, ANNOVAR reported rs760688660,

which failed gnomAD's random forest qc step. We note that a 6.3% false-positive rate is similar

to the frequency of common variation, and significantly larger than the frequency of rare

variants, making ANNOVAR's gnomAD annotations a potentially unreliable source of data for

both common and rare variant filtering.

Software	Dataset	Samples	Variants	Variants/s	Bystro vs
Table 1 | **Bystro, VEP, ANNOVAR offline command-line performance**.					
Bystro	1000G Phase 3 chr1	2504	1×10^6	8156 ± 195	-
	1000G Phase 3 chr1	2504	2×10^6	8484 ± 67.9	-
	1000G Phase 3 chr1	2504	4×10^6	8516 ± 57.2	-
	1000G Phase 3 chr1	2504	6.5×10^6	7779 ± 21.8	-
	1000G Phase 1	1092	3.9×10^7	5417 ± 76.8	
	1000G Phase 3	2504	8.5×10^7	7904 ± 15.9	-
VEP	1000G Phase 1	1092	3.9×10^7	18.67 ± 0.58	290x
	1000G Phase 3	2504	8.5×10^7	10.00 ± 0.00	790x
ANNOVAR	1000G Phase 3 chr1	2504	1×10^6	74.67 ± 0.21	109x
	1000G Phase 3 chr1	2504	2×10^6	75.32 ± 0.06	113x
	1000G Phase 3 chr1	2504	4×10^6	75.15 ± 0.39	113x
	1000G Phase 3 chr1	2504	6.5×10^6	NA	NA
	1000G Phase 1	1092	3.9×10^7	NA	NA
	1000G Phase 3	2504	8.5×10^7	NA	NA

Bystro, VEP, and ANNOVAR were similarly configured with 8 threads on Amazon i3.2xlarge servers. "Dataset" refers to the VCF file used. "Variants/s" is the average of three trials. VEP performance was recorded after 2×10^5 sites in consideration of time. In runs of 1×10^6 or more annotated sites, VEP performance did not deviate from the 2×10^5 value. ANNOVAR could not complete the full Phase 1, Phase 3, or Phase 3 chromosome 1 datasets due to memory limitations. Thus, ANNOVAR was compared to Bystro on subsets of 1000 Genomes Phase 3 chromosome 1. Bystro run times included time taken to compress outputs. 1000 Genomes Phase 1 performance reflects IO limitations.

Next, we explored the Bystro search engine's ability to filter the 84.9 million annotated

Phase 3 variants. Bystro's search engine was unique in its natural-language capabilities, and no

other tested online program could handle the full Phase 3 dataset, or subsets as large as 6×10^6

variants (Figure 2). First, we used Bystro's search engine to find all alleles in exonic regions by

entering the term "exonic" (933,343 alleles, 0.030 ± .001 seconds, Table 2). The search engine

calculated a transition to transversion ratio of 2.96 for the query, consistent with previously

observed values in coding regions. To refine results to rare, predicted deleterious alleles, we

queried "cadd > 20 maf < .001 pathogenic expert review missense" (65 alleles, 0.029 ± 0.025s,

Table 2). This search query could be written using partial words ("pathogen"), possessive nouns

("expert's"), different tenses ("reviews"), and synonyms ("nonsynonymous") without changing

the results.

Table 2 | **Online comparison of Bystro and recent programs in filtering 8.49x10^7 variants from 1000 Genomes**

Group	Search query	Time (s)	Variants	Tr:Tv
1	exonic	0.030 ± 0.030	993,343	2.96
2 (a)	cadd > 20 maf < .001 pathogenic expert review missense	0.029 ± 0.009	65	1.71
2 (b)	cadd > 20 maf < .001 pathogenic **expert's** review **non-synonymous**	0.036 ± 0.019	65	1.71
2 (c)	cadd > 20 maf < .001 **pathogen** expert-**reviewed nonsynonymous**	0.044 ± 0.025	65	1.71
3 (a)	early onset breast cancer	0.046 ± 0.029	4,335	2.51
3 (b)	**early-onset** breast cancer	0.037 ± 0.020	4,335	2.51
3 (c)	**Early onset** breast **cancers**	0.033 ± 0.015	4,335	2.51
4 (a)	Pathogenic nonsense Ehlers-Danlos	0.038 ± 0.027	1	NA
4 (b)	**pathogenic** nonsense **E.D.S**	0.078 ± 0.087	1	NA
4 (c)	**pathogenic stopgain eds**	0.040 ± 0.022	1	NA

The full 1000 Genomes Phase 3 VCF file (853GB, 8.49x10^7 variants, 2,504 samples) was filtered in the publicly-available Bystro web application using the Bystro natural-language search engine. VEP, GEMINI, and wANNOVAR (not shown) were also tested, but were unable to annotate this data set or filter it. Bystro's search engine uses a natural language parser that allows for unstructured queries: queries in groups 2, 3, and 4 show phrasing variations that did not affect results returned, as would be expected for a search engine that could handle normal language variation. "Tr:Tv" is the transition to transversion ratio automatically calculated for each query by the search engine. The transition to transversion ratio of 2.96 for the "exonic" query is close to the ~2.8-3.0 ratio expected in coding regions, suggesting that the search engine accurately identified exonic (coding) variants.

To test the search engine's ability to accurately match variants from full-text disease

queries, we first searched "early-onset breast cancer", returning the expected alleles in *BRCA1*

and *BRCA2* (4,335 variants, .037 ± .020s, Table 2). Notably, the queried phrase "early-onset

breast cancer" did not exist within the annotation, and instead matched closely-related RefSeq

transcript names, such as "Homo sapiens breast cancer 2, early onset (BRCA2), mRNA." We

next explored Bystro's ability to handle synonyms and acronyms. To test the hypothesis that

Bystro could interpret common ontologies, we queried "pathogenic nonsense E.D.S", where

"nonsense" is a common synonym for "stopGain" (a term annotated by the Bystro annotation

engine), and "E.D.S" is an acronym for "Ehlers-Danlos Syndrome". Bystro successfully parsed

this query, returning a single *PLOD1* variant found in 1000 Genomes Phase 3 that introduces an

early stop codon in all three of its overlapping transcripts, and which has been reported in

Clinvar as "pathogenic" for "Ehlers-Danlos syndrome, type 4" (1 variant, .038s ± .027s, Table 2).

Since no other tested program could load or filter the 1000 Genomes Phase 3 VCF file

online, we next compared Bystro to GEMINI (running on the Galaxy platform) on subsets of

1000 Genomes Phase 3. In contrast with GEMINI's structured SQL queries, Bystro enabled

shorter and more flexible searches. For instance, to return all missense, rare variants with

CADD Phred scores larger than 15, GEMINI required a 162 character SQL query, while Bystro

needed only 36 characters. Bystro also demonstrated synonym support, returning identical

results for "missense" and "nonsynonymous" queries. Critically, Bystro's search engine enabled

real-time (sub-second) filtering, performing approximately four orders of magnitude faster than

GEMINI on Galaxy while searching and returning similar volumes of data (Table 3).

To test the accuracy of Bystro's search engine relative to the underlying annotation, we

first compared Bystro's natural-language queries with Bystro's "Filters", which provide a

complimentary, exact-match filtering option. All results were identical between the two methods

(Additional file 1: Table S5). To control for the possibility that Bystro's "Filters" were biased, we

created separate Perl filtering scripts that searched for exact matches within the underlying tab-

delimited text annotation. Again, results were completely concordant (Additional file 1: Table

S5). Finally, to control for the possibility that both Bystro's "Filters" and the Perl scripts were

biased due to the programmer, we compared Bystro's natural-language queries with Excel

filters on a smaller dataset that could be manually examined. The queries were found

completely specific in this comparison as well (Additional file 1: Table S6; Additional file 7).

#	Program	Query	Time (s)	Variants	Ts/Tv
1	**Bystro**	**cadd > 15 alt:(a || c || t || g)**	**.004 ± 0**	**28,099**	**2.512**
1	GEMINI	SELECT * FROM variants JOIN variant_impacts ON variants.variant_id = variant_impacts.variant_id WHERE cadd_scaled > 15	442 ± 87	22,063	NA
2	**Bystro**	**gnomad.exomes.af < .001 cadd > 15 missense**	**.007 ± .003**	**6,840**	**3.083**
2	GEMINI	SELECT * FROM variants JOIN variant_impacts ON variants.variant_id = variant_impacts.variant_id WHERE cadd_scaled > 15 AND aaf_exac_all < .001 AND variant_impacts.impact = 'missense_variant'	77.6 ± 18.6	5,160	NA
3	**Bystro**	**gnomad.exomes.af < .001 cadd > 15 nonsynonymous**	**.006 ± .001**	**6,840**	**3.083**
3	GEMINI	SELECT * FROM variants JOIN variant_impacts ON variants.variant_id = variant_impacts.variant_id WHERE cadd_scaled > 15 AND aaf_exac_all < .001 AND variant_impacts.impact = '**nonsynonymous_variant**'	NA	0	NA

Table 3 | Online comparison of Bystro and GEMINI/Galaxy in filtering 1x10^6 variants

Bystro was compared to the latest hosted version of GEMINI (v0.8.1, on the Galaxy platform) in filtering the 1x10^6 variant subset of 1000 Genomes Phase 3, which was the largest tested file that GEMINI/Galaxy could process. GEMINI requires structured SQL queries, while Bystro allows for shorter, unstructured search. In query #1, Bystro searched for CADD scores only within single-nucleotide polymorphisms (using alt:(a || c || t || g), or equivalently the regex query alt:/[actg]/), to normalize results with GEMINI, which provides no CADD data for insertions and deletions. In queries #2 and #3, Bystro's search engine returned identical results for the synonymous terms "missense" and "nonsynonymous", despite annotating such sites only as "nonsynonymous". In contrast, GEMINI required the specific term 'missense_variant'. GEMINI/Galaxy and Bystro returned different results because the latest version of GEMINI on Galaxy (0.8.1) uses outdated annotation sources. Comparisons between Bystro and GEMINI/Galaxy are further limited as GEMINI doesn't provide a natural-language parser, annotation field filters, an interactive result browser, per-query statistics, or the ability to filter saved search results. Notably, Bystro also performed substantially faster, returning all results in less than 1 second.

Discussion

The Bystro annotation and filtering capabilities are primarily exposed through a public

web application (*https://bystro.io/*), and are also available for custom, offline installation. To

ensure data safety, Bystro follows industry recommendations for password management, in-

transit data security, and at-rest data security. Input and output files are encrypted at rest on

Amazon EFS file systems, using AES 256-bit encryption, and every request for annotation or

search data is authenticated by the web server using short-lived identity tokens. To further

protect user data, annotation and search services are not directly open to the Internet, but

require routing and authentication through the web server. Furthermore, all web traffic is

encrypted using TLS (HTTPS), and password hashing follows the National Institute of

Standards and Technology (NIST) recommended PBKDF2-HMAC-SHA512 strategy.

Creating an annotation online is as simple as selecting the genome and assembly used

to make the variant call format (VCF)[10] or SNP[11] format files, and uploading these files from

a computer or Amazon S3 bucket, which can be easily linked to the web application. Annotation

occurs in the cloud, where distributed instances of the Bystro annotation engine process the

data and send the results back to the web application for storage and display (Figure 1).

The Bystro annotation engine is open source, and supports diverse model organisms

including *Homo sapiens* (hg19, hg38), *M. musculus* (mm9, mm10), *R. macaque* (rheMac8), *R.*

norvegicus (rn6), *D. melanogaster* (dm6), *C. elegans* (ce11), *S. cerevisiae* (sacCer3). To

annotate, it rapidly matches alleles from users' submitted files to descriptions from RefSeq[12],

dbSNP[13], PhyloP[14], PhastCons[14], Combined Annotation-Dependent Depletion (CADD),

Clinvar[15], and gnomAD[16]. For custom installations, Bystro supports Ensembl, RefSeq, or

UCSC Known Genes transcript sets, and can be flexibly configured include annotations from

any files in genePredExt, wigFix, BED, or VCF formats.

The annotation engine is aware of alternate splicing, and annotates all variants relative

to each alternate transcript. When provided sample information, Bystro also annotates all

variants relative to all sample genotypes. In such cases, at every site it labels each sample as

homozygous, heterozygous, or missing, and also calculates the heterozygosity, homozogosity,

missingness, and sample minor allele frequency. Furthermore, in contrast with current programs

that require substantial VCF file pre-processing, Bystro automatically removing low-quality sites,

normalizes variant representations, splits multi-allelic variants, and checks the reference allele

against the genome assembly. Critically, Bystro's algorithm guarantees parsimonious (left-

shifted) variant representations, even for multi-allelic sites containing complex insertions and

deletions.

The Bystro annotation engine is designed to scale to any size experiment, offering the

speed of distributed computing solutions such as Hail[17], but with less complexity. Current well-

performing annotators - such as ANNOVAR and SeqAnt - load significant amounts of data into

memory to improve performance. However, when these programs use multiple threads to take

advantage of multicore CPUs they may exceed available memory (in some cases over 60GB),

resulting in a sharp drop in performance or system crash. To solve this, Bystro annotates

directly from an efficient memory-mapped database (LMDB), using only a few megabytes per

thread, and because memory-mapped databases naturally lend themselves to the caching

frequently accessed data, Bystro achieves most of the benefits of in-memory solutions, but

without the per-thread penalties. This approach allows Bystro to take excellent advantage of

multicore CPUs, while also enabling it to perform well on inexpensive, low-memory machines.

Critically, when multiple files are submitted to it simultaneously, the Bystro annotation engine

can automatically distribute the work throughout the cloud (or a user-configured computer

cluster), gaining additional performance by processing the files on multiple computers (Figure

1). Furthermore, in reflection of the large sizes of both input sequencing experiments and the

corresponding annotation outputs - on the order of terabytes for modern whole-genome

experiments - Bystro accepts compressed input files, and directly writes compressed outputs.

This ability to directly write compressed annotations with no uncompressed intermediate is

critical given the rapid growth in sequencing experiment size.

When the web application receives a completed annotation, it saves the data and

creates a permanent results page. Detailed information about the annotation, such as the

database version used for the annotation is stored in a log file that the user may download.

Users may then explore several quality control metrics, including the transition to transversion

ratio on a per-sample or per-experiment basis. They may also download the results as tab-

delimited text to their computer, or upload them to any connected Amazon S3 bucket. In parallel

with the completion of an annotation, the Bystro search engine automatically begins indexing

the results. Once finished, a search bar is revealed in the results page, allowing users to filter

their variants using the search engine (Figure 1).

Unlike existing filtering solutions, Bystro's Elasticsearch-based natural-language search

engine accepts unstructured, "full-text" queries, and relies on a sophisticated language parser to

match annotated variants. This allows it to offer the flexibility of modern search engines like

Google and Bing, while remaining specific enough for the precise identification of alleles

relevant to the research question. The Bystro search engine matches terms regardless of

capitalization, punctuation, or word tense, and accurately finds partial terms within long

annotation values. Like the annotation engine, the search engine is also exceptionally fast,

automatically distributing indexed annotations throughout the cloud, enabling users to sift

through millions of variants from large whole-genome sequencing experiments in milliseconds.

In order to provide flexible, but specific matches without relying on structured SQL

queries, the search engine identifies the data type of every value in the annotation. Text

undergoes stemming and lemmatization, which reduces the influence of grammatical variation,

and is then tokenized into left-edge n-grams, which allows for flexible matching. Numerical data

is stored in the smallest integer or float format that can accommodate it, allowing for rapid and

accurate range queries. For complex queries, the search engine supports Boolean operators

(AND, OR), regular expressions, and Levenshtein-edit distance fuzzy matches. It also has a

built-in dictionary of synonyms, for instance equating "stopgain" and "nonsense".

In some cases, text will match accurately, but not specifically; this most often happens

with short, generic terms. For instance, querying "intergenic" alone may match the word

"intergenic" in "long intergenic non-protein coding RNA" in refSeq's description field, as well as

"intergenic" in the refSeq's siteType field. To help improve accuracy in such cases, Bystro

provides three, closely related features: 1) "Aggregations" allows users to see the top 200

values for any text field, or equivalently the min, max, mean, standard deviation (and other

similar statistics) for any numerical field. This allows users to quickly and precisely understand

the composition of search results, as well as to generate summary statistics. 2) "Filters" allows

users to refine queries, by forcing the inclusion or exclusion of any values found in any field. For

instance, rather than query "intergenic", it may be easier and more precise to simply click on the

"refSeq.siteType" filter, and select the "intergenic" value. Any number of "Filters" may be

combined with any natural-language query, containing up to 1 million words. 3) Bystro allows

field names within a natural-language query for added specificity. For example, rather than

searching for "intergenic", the user could type "refSeq.siteType:intergenic", to indicate that they

wished to match "intergenic" specifically in the refSeq.siteType annotation field.

Bystro's search engine also includes several features to increase flexibility beyond the

contents of the annotation: 1) "Custom Synonyms" allows users to define their own terms and

annotations. Among other uses, this make it is possible to label trios, which can be used to

easily identify *de novo* variants and test allele transmission models. 2) "Search Tools" are small

programs, accessible by a single mouse click, that dynamically modify any query to generate

complex result summaries. Some of their functions include identifying compound heterozygotes.

3) "Statistical Filters" dynamically perform statistical tests on the variants returned from any

query. For instance, the "HWE" filter allows users to exclude variants out of Hardy-Weinberg

Equilibrium. This is an often-needed quality control step.

Most importantly, there is no limit to the number of query terms and "Filters" that can be

combined, and users can save and download the results of any search query, which enables

recursive filtering on a single dataset. The saved results are indexed for search, and hyperlinked

to the annotations that they were generated from, forming permanent records that can be used

to reproduce complex analyses. This multi-step filtering provides functionality similar to custom

command-line filtering script pipelines, but is significantly faster, less error prone, and

accessible to researchers without programming experience.

While Bystro's annotation and filtering performance is currently unparalleled by any other

approach, other software (such as Hail[17]) could achieve similar performance by implementing

distributed computing algorithms like MapReduce[18], and spreading annotation workloads

across many servers. Bystro demonstrates that these workarounds are unnecessary to achieve

reasonable run-times for large datasets online or offline. Additionally, while Bystro's natural-

language search engine significantly reduces the difficulty of variant filtering, it does not handle

language idiosyncrasies as robustly as more mature solutions like Google's, and may return

unexpected results when search queries are very short and non-specific, since such queries

may have multiple correct matches. This is easily avoided by using longer phrases, by using

"Custom Synonyms" to define more specific terms, by examining the composition of results

using "Aggregations", or by applying "Filters" to precisely filter results. Such considerations and

options are well-documented in Bystro's online user guide (*https://bystrio.io/help*).

Conclusions

To date, identifying alleles of interest in sequencing experiments has been time-

consuming and technically challenging, especially for whole-genome sequencing experiments.

Bystro increases performance by orders of magnitude and improves ease of use through three

key innovations: 1) a low-memory, high-performance, multithreaded variant annotator that

automatically distributes work in cloud or clustered environments; 2) an online architecture that

handles significantly larger sequencing experiments than previous solutions; and 3) the first

publicly-available, general-purpose, natural-language search engine for variant filtering in

individual research experiments. Bystro annotates large experiments in minutes, and its search

engine is capable of matching variants within whole-genome datasets in milliseconds, enabling

real-time data analysis. Bystro's features enable practically any researcher – regardless of their

computational experience - to analyze large sequencing experiments (e.g. thousands of whole-

genome samples) within less than a day, and small ones (e.g. hundreds of whole-exome

samples) in seconds. As genome sequencing continues the march toward ever-larger datasets

and becomes more frequently used in diverse research settings, Bystro's combination of

performance and ease of use will prove invaluable for reproducible, rapid research.

Methods

Accessing Bystro

For most users, we recommend the Bystro web application (*https://bystro.io*), as it gives

full functionality, supports arbitrarily large datasets, and provides a convenient interface to the

natural-language search engine. Users with computational experience can download the Bystro

open-source package (*https://github.com/akotlar/bystro*). Using the provided installation script or

Amazon AMI image, Bystro can be easily deployed on an individual computer, computational

cluster, or any Amazon Web Services (AWS) EC2 instance. Bystro has very low memory and

CPU requirements, but benefits from fast SSD drives. As such we recommend at AWS

instances with provisioned I/O EBS drives, RAID 0 non-provisioned EBS, or i2/i3-class EC2

instances.

340   Detailed documentation on Bystro's use, as well as example search queries can be

341 found at *https://bystro.io/help*.

343 **Bystro comparisons with ANNOVAR, wANNOVAR, VEP, and GEMINI/Galaxy**

345 **Bystro Database**

346   Bystro databases were created using the open-source package

347 (*https://github.com/akotlar/bystro*). The hg19 and hg38 databases contains RefSeq, dbSNP,

348 PhyloP, PhastCons, Combined Annotation-Dependent Depletion (CADD), and Clinvar fields, as

349 well as custom annotations (Additional file 8). A complete listing of the original source data is

350 enumerated in the Git repository (*https://github.com/akotlar/bystro/tree/master/config*). Other

351 organism databases contain a subset of these sources, based on availability. Pre-built, up-to-

352 date versions of these databases are publicly available (*https://github.com/akotlar/bystro*).

354 **WGS Datasets**

355   Phase 1 and Phase 3 autosome and chromosome X VCF files were downloaded from

356 *http://www.internationalgenome.org/data/*. Phase 1 files were concatenated using bcftools[19]

357 "concat" function. Phase 3 files were concatenated using a custom Perl script

358 (*https://github.com/wingolab-org/GenPro/blob/master/bin/mergeSnpFiles*). The Phase 1 VCF file

359 was 895GB (139GB compressed), and the Phase 3 data was 853GB (15.6GB compressed).

360 The larger size of Phase 1 can be attributed to the inclusion of extra genotype information (the

361 genotype likelihood). The full Phase 3 chromosome 1 VCF file (6.4×10^6 variants, 1.2GB

362 compressed), and 5×10^4-4×10^6 variant allele subsets (8-655MB compressed) were also tested.

363 All Phase 1 and Phase 3 data correspond to the GRCh37/hg19 human genome assembly. All

364 data used are available (Additional file 9).

Online annotation comparisons

367  For online comparisons, the latest online versions offered at time of writing were used.

Bystro beta10 (September 2017), wANNOVAR (April 2017), VEP (April 2017), and GEMINI

(Galaxy version 0.8.1, released February 2016, latest as of October 2017) were tested online

with the full 1000 Genomes Phase 1 and Phase 3 VCF files, unless they were unable to upload

the files due to file size restrictions (Additional file 2). Bystro was found to be the only program

capable of uploading and processing the full Phase 1 and Phase 3 data sets, or subsets of

Phase 3 larger than 1×10^{6} variants.

375  To conduct Bystro online annotations, a new user was registered within the public Bystro

376 web application (*https://bystro.io/*). Phase 1 and Phase 3 files were submitted in triplicate, one

377 replicate at a time, using the default database configuration (Additional file 2). Indexing was

378 automatically performed by Bystro upon completion of each annotation. The Phase 3 annotation

379 is publicly available to be tested (*https://bistro.io/public*).

381  The public Bystro server was configured on an Amazon i3.2xlarge EC2 instance. The

382 server supported 8 simultaneous users. Throughout the duration of each experiment, multiple

383 users had concurrent access to this server, increasing experiment variance, and limiting

384 observed performance.

386  Online Variant Effect Predictor (VEP) submissions were done using the VEP web

application (*http://www.ensembl.org/info/docs/tools/vep/index.html*). VEP has a 50MB

(compressed) file size limit. Due to gateway timeout issues and this file size limit, data sets

larger than 5×10^{4} variants failed to complete (Additional file 2).

Online ANNOVAR submissions were handled using the wANNOVAR web application.

wANNOVAR could not accept the smallest tested file, the $5x10^4$ variant subset of Phase 3

chromosome 1 (8MB compressed) due to file size restrictions (Additional file 2).

Galaxy submission was made using the public Galaxy servers. Galaxy provides

ANNOVAR, but its version of this software failed to complete any annotations, with the error

"unknown option: vcfinput". Annotations on Galaxy were therefore performed using GEMINI,

which provides annotations similar to Bystro's. Galaxy has a total storage allocation of 250GB

(after requisite decompression), and both Phase 1 and Phase 3 exceed this size. Galaxy was

therefore tested with the full $6.4x10^6$ variant Phase 3 chromosome 1 VCF file. Galaxy's FTP

server was able to upload the file; however, Galaxy was unable to load the data into GEMINI,

terminating after running for 36 hours, with the message "This job was terminated because it ran

longer than the maximum allowed job run time" (Additional file 2). Subsets of Phase 3

chromosome 1 containing $5x10^4$, $3x10^5$, and $1x10^6$ variants were therefore tested. Three

repetitions of the $5x10^4$ variant submission were made. In consideration of the duration of

execution, two repetitions were made of the $3x10^5$ and $1x10^6$ variants submissions. Since

Galaxy does not record completion time, QuickTime was used to record each submission.

Bystro, VEP, and GEMINI online annotation times included the time to generate both a user-

readable tab-delimited text annotation and a searchable database. GEMINI required an extra

step to do so, using the query SELECT * FROM variants JOIN variant_impacts ON

variants.name = variant_impacts.name.

Variant filtering comparisons

After Bystro completed each annotation, it automatically indexed the results for search.

The time taken to index this data was recorded. Once this was completed, the Bystro web

application's search bar was used to filter the annotated sequencing experiments. The query

time, as well as the number of results and the transition to transversion ratio for each query,

were automatically generated by the search engine and recorded. Query time did not take into

account network latency between the search server and the web server. All queries were run six

times and averaged. The public search engine, which processed all queries, was hosted on a

single Amazon i3.2xlarge EC2 instance.

Since VEP, wANNOVAR, and Galaxy/GEMINI could not complete Phase 1 or Phase 3

annotations, variant filtering on these data sets could not be attempted. For small experiments

VEP and GEMINI can filter based on exact matches, while wANNOVAR provides only pre-

configured phenotype and disease model filters. VEP could annotate and filter at most only

5×10^4 variants and was therefore excluded from query comparisons.

Galaxy/GEMINI was tested with subsets of 1000 Genomes Phase 3 of 1×10^6 variants

(the largest tested data set that Galaxy could handle), with the described settings (Additional file

2). In all GEMINI queries a JOIN operation on the variant_impacts table was used to return all

variant consequences, and all affected transcripts, as Bystro does by default. Similarly, Bystro's

CADD query was restricted to single nucleotide polymorphisms (using alt:(A || C || T || G)), as its

behavior diverges from GEMINI's at insertions and deletions: Bystro returns all possible CADD

Phred scores at such sites, whereas GEMINI returns a missing value. Bystro returns all values

to give users added flexibility: its search engine can accurately search within arrays (lists) of

data. Furthermore, as GEMINI on Galaxy only provided the Ensembl transcript set, for all query

comparisons with GEMINI, Bystro was configured to use Ensembl 90, which was the latest

version available at time of revision. It is important to note that the latest version of GEMINI on

Galaxy (0.8.1) dates to February 2016, and its databases are several years older: CADD (v1.0,

2014), Ensembl (v75, February 2014), ExAc (v0.3, October 2014), whereas Bystro uses up-to-

date resources. As a result of searching more up to date Ensembl (v90), population allele

frequency (gnomAD 2.0.1, the successor to ExAc 1.0), and CADD (v1.3) data, Bystro's queries

returned more data.

Since Galaxy does not report run times, QuickTime software was used to record each

run, and the query time was calculated as the difference between the time the search

submission entered the Galaxy queue, to the time that it was marked completed.

Galaxy/GEMINI queries were each run more than 6 times. Because run times varied by more

than 17x, the fastest consecutive 6 runs were averaged to minimize the influence of Galaxy

server load.

All comparisons with the Bystro search engine are limited, because no other existing

method provides natural-language parsing, and either rely on built-in scripts or require the user

to learn a specific language (SQL).

Filtering accuracy comparison

The latest version of Bystro (beta 10, September 2017) was used. For the 1000

Genomes query accuracy checks, the same underlying Ensembl-based Bystro annotation and

search index was used as in the Bystro/GEMINI filtering comparison. Direct comparison to

GEMINI were not made, in reflection of the age of the latest GEMINI Galaxy version (v0.8.1,

with database sources dating to 2014). All Bystro queries from that comparison were saved,

downloaded, and compared with Bystro "Filters", which are exact-match alternatives to Bystro's

natural-language queries, as well as custom Perl filtering scripts that also require exact

matches. A second query accuracy step was conducted, on the Yen et al 2017[9] VCF file. This

file was annotated using the standard RefSeq Bystro database. The same queries used in the

Bystro/GEMINI comparison were re-created on this smaller annotation, saved, downloaded, and

compared with Bystro "Filters" and Excel filters. Excel filters were created in Excel 2016 (Mac),

and required exact matches. All Excel-filtered and all Bystro query results were manually

inspected for concordance (Additional file 7). All scripts generated and used in the comparison

may be found at *https://github.com/akotlar/bystro-paper.*

Offline annotation comparisons

To generate offline performance data, the latest versions of each program available at

time of writing were used. Bystro beta10 (September 2017), VEP 86 (March 2017), and

ANNOVAR (March 2017) were each run on separate, dedicated Amazon i3.2xlarge EC2

instances (Additional file 3). All programs' databases were updated to the latest versions

available as of March 2017 (VEP, ANNOVAR), or September 2017 (Bystro). All programs were

configured to use the RefSeq transcript set.

Each instance contained 4 CPU cores (8 threads), 60GB RAM, and a 1920GB NVMe

SSD. Each instance was identically configured. All programs were configured to as closely

match Bystro's output as possible, although Bystro output more total annotation fields

(Additional file 3). Each data set tested was run 3 times. The annotation time for each run was

recorded, and averaged to generate the mean variant per second (variant/s) performance.

Submissions were recorded using the terminal recorder asciinema, and both memory and cpu

usage were recorded using the **free** and **top** commands set to a 30 second timeout.

VEP was configured to use 8 threads and to run in "offline" mode to maximize

performance, as recommended[3]. In each of three recorded trials, VEP was set to annotate

from RefSeq and CADD, and to check the reference assembly (Additional file 3). Based on

VEP's observed performance, adding PhastCons annotations was not attempted. VEP's

performance was measured by reading the program's log, which records variant/second

performance every $5x10^3$ annotated sites. In consideration of time, VEP was stopped after at

least $2x10^5$ variants were completed, and the $2x10^5$ variants performance was recorded.

ANNOVAR was configured to annotate RefSeq, CADD, PhastCons 100way, PhyloP

100way, Clinvar, avSNP, and ExAc version 0.3 (Additional file 3). ANNOVAR's avSNP database

was used in place of dbSNP, as recommended. We configured ANNOVAR to report allele

frequencies from ExAc, because it does not do so from either avSNP or dbSNP databases.

When annotating Phase 1, Phase 3, or Phase 3 chromosome 1, ANNOVAR crashed by

exceeding the available 60GB of memory. It was therefore tested with the subsets of Phase 3

chromosome 1 that contained $1 \times 10^6 - 4 \times 10^6$ variants.

Bystro was configured to annotate descriptions from RefSeq, dbSNP 147, CADD,

PhastCons 100way, PhyloP 100way, Clinvar, and to check the reference for each submitted

genomic position (Additional file 3).

Annotation accuracy comparison

The latest version of Bystro (beta 10, September 2017), ANNOVAR (July 2017), and

VEP (version 90) at the time of revision submission were used. All programs' databases were

updated to the latest version available. RefSeq-based databases were downloaded using each

program's database builder. All programs were compared on the Yen et al 2017 VCF file [9] for

position, variant call, and variant effects, based on each programs' respective RefSeq database.

The Yen et al VCF file *fileformat* header line was modified to "VCFv4.1" to allow programs to

recognize it as a valid VCF file. This modified file is available: https://github.com/akotlar/bystro-

paper. For the SnpEff comparison, annotations were adapted from Additional File 1 of Yen et al

2017[9]. ANNOVAR was additionally configured with gnomAD genomes, gnomAD exomes, and

CADD 1.3, and compared to Bystro on the corresponding values.

Additional Files

Additional file 1: This file contains 1) a feature comparison of tested programs, 2) investigation

of annotation concordance between tested programs, 3) investigation of Bystro query accuracy

(.docx, 1.4MB)

Additional file 2: Description of online comparison settings (.xlsx, 859KB)

Additional file 3: Description of online comparison settings (.xlsx, 40KB)

Additional file 4: Bystro vs ANNOVAR annotation comparison details (.xslx, 87KB)

Additional file 5: Bystro vs VEP annotation comparison details (.xslx, 701KB)

Additional file 6: Bystro vs SnpEff annotation comparison details (.xslx, 63KB)

Additional file 7: Bystro queries vs Excel filters concordance details (.xslx, 166KB)

Additional file 8: Species supported at time of writing, and their configurations (.xslx, 36KB)

Additional file 9: URLs of 1000 Genomes Phase 1, 1000 Genomes Phase 3, and Yen et al 2017

VCF files used (.xslx, 47KB)

Declarations

Availability of data and materials

The Bystro web application is freely accessible at *https://bystro.io/*, and features detailed

interface documentation (*https://bystro.io/help*). The Bystro annotator, search indexer,

distributed queue servers, and database builder source code is freely available on GitHub

(*https://github.com/akotlar/bystro)* and Zenodo (doi: *10.5281/zenodo.1012417*), under the

Apache 2 open-source license [20]. The software is written in Perl and Go programming

languages and runs on Linux and Mac operating systems. Detailed documentation for Bystro

software is provided at *https://github.com/akotlar/bystro/blob/master/README.md*. The datasets

generated during and/or analyzed during the current study are available in the GitHub

repository, *https://github.com/akotlar/bystro-paper* [6],[9].

Author contributions

A.V.K designed, wrote, and tested Bystro and performed experiments. C.E.T wrote

Bystro documentation and performed quality control. M.E.Z and D.J.C. contributed to the design

of Bystro and experiments. T.S.W. designed and wrote Bystro and designed and performed

experiments. A.V.K. and T.S.W. wrote the manuscript with contributions from all authors.

Acknowledgements

We thank Kelly Shaw and Katherine Squires for beta testing and design suggestions. We thank

Viren Patel and the Emory Integrated Genomics Core (EIGC) for technical support.

Funding

This work was supported by the AWS Cloud Credits for Research program**,** the Molecules to

Mankind program (a project of the Burroughs Wellcome Fund and the Laney Graduate School

at Emory University), Veterans Health Administration (BX001820), and the National Institutes of

Health (AG025688, MH101720, NS091859).

Competing interests

The authors have no competing interests to declare.

Ethics approval and consent to participate

Not applicable

References

1.   Wang K, Li M, Hakonarson H: **ANNOVAR: functional annotation of genetic variants**
from high-throughput sequencing data. *Nucleic Acids Res* 2010, **38:**e164.

2.   Shetty AC, Athri P, Mondal K, Horner VL, Steinberg KM, Patel V, Caspary T, Cutler DJ,

570   Zwick ME: **SeqAnt: a web service to rapidly identify and annotate DNA sequence**

571   **variations.** *BMC Bioinformatics* 2010, **11:**471.

572   3.   McLaren W, Gil L, Hunt SE, Riat HS, Ritchie GR, Thormann A, Flicek P, Cunningham F:

573   **The Ensembl Variant Effect Predictor.** *Genome Biol* 2016, **17:**122.

574   4.   DeFreitas T, Saddiki H, Flaherty P: **GEMINI: a computationally-efficient search**

575   **engine for large gene expression datasets.** *BMC Bioinformatics* 2016, **17:**102.

576   5.   Sandve GK, Nekrutenko A, Taylor J, Hovig E: **Ten simple rules for reproducible**

577   **computational research.** *PLoS Comput Biol* 2013, **9:**e1003285.

578   6.   Genomes Project C, Auton A, Brooks LD, Durbin RM, Garrison EP, Kang HM, Korbel

579   JO, Marchini JL, McCarthy S, McVean GA, Abecasis GR: **A global reference for**

580   **human genetic variation.** *Nature* 2015, **526:**68-74.

581   *http://dx.doi.org/10.1038/nature15393*

582   7.   Chang X, Wang K: **wANNOVAR: annotating genetic variants for personal genomes**

583   **via the web.** *J Med Genet* 2012, **49:**433-436.

584   8.   Goecks J, Nekrutenko A, Taylor J, Galaxy T: **Galaxy: a comprehensive approach for**

585   **supporting accessible, reproducible, and transparent computational research in**

586   **the life sciences.** *Genome Biol* 2010, **11:**R86.

587   9.   Yen JL, Garcia S, Montana A, Harris J, Chervitz S, Morra M, West J, Chen R, Church

588   DM: **A variant by any name: quantifying annotation discordance across tools and**

589   **clinical databases.** *Genome Med* 2017, **9:**7. *http://dx.doi.org/10.1186/s13073-016-*

590   *0396-7*

591   10.   Danecek P, Auton A, Abecasis G, Albers CA, Banks E, DePristo MA, Handsaker RE,

592   Lunter G, Marth GT, Sherry ST, et al: **The variant call format and VCFtools.**

593   *Bioinformatics* 2011, **27:**2156-2158.

594   11.   Johnston HR, Chopra P, Wingo TS, Patel V, International Consortium on B, Behavior in

595   22q11.2 Deletion S, Epstein MP, Mulle JG, Warren ST, Zwick ME, Cutler DJ: **PEMapper**

596   **and PECaller provide a simplified approach to whole-genome sequencing.** *Proc*

597   *Natl Acad Sci U S A* 2017.

598   12.   O'Leary NA, Wright MW, Brister JR, Ciufo S, Haddad D, McVeigh R, Rajput B,

599   Robbertse B, Smith-White B, Ako-Adjei D, et al: **Reference sequence (RefSeq)**

600   **database at NCBI: current status, taxonomic expansion, and functional**

601   **annotation.** *Nucleic Acids Res* 2016, **44:**D733-745.

602   13.   Sherry ST, Ward MH, Kholodov M, Baker J, Phan L, Smigielski EM, Sirotkin K: **dbSNP:**

603   **the NCBI database of genetic variation.** *Nucleic Acids Res* 2001, **29:**308-311.

604   14.   Pollard KS, Hubisz MJ, Rosenbloom KR, Siepel A: **Detection of nonneutral**

605   **substitution rates on mammalian phylogenies.** *Genome Res* 2010, **20:**110-121.

606   15.   Landrum MJ, Lee JM, Benson M, Brown G, Chao C, Chitipiralla S, Gu B, Hart J,

607   Hoffman D, Hoover J, et al: **ClinVar: public archive of interpretations of clinically**

608   **relevant variants.** *Nucleic Acids Res* 2016, **44:**D862-868.

609   16.   Lek M, Karczewski KJ, Minikel EV, Samocha KE, Banks E, Fennell T, O'Donnell-Luria

610   AH, Ware JS, Hill AJ, Cummings BB, et al: **Analysis of protein-coding genetic**

611   **variation in 60,706 humans.** *Nature* 2016, **536:**285-291.

612   17.   Ganna A, Genovese G, Howrigan DP, Byrnes A, Kurki MI, Zekavat SM, Whelan CW,

613   Kals M, Nivard MG, Bloemendal A, et al: **Ultra-rare disruptive and damaging**

614   **mutations influence educational attainment in the general population.** *Nat Neurosci*

615   2016, **19:**1563-1565.

616   18.   Taylor RC: **An overview of the Hadoop/MapReduce/HBase framework and its**

617   **current applications in bioinformatics.** *BMC Bioinformatics* 2010, **11 Suppl 12:**S1.

618   19.   Li H: **A statistical framework for SNP calling, mutation discovery, association**

619   **mapping and population genetical parameter estimation from sequencing data.**

620   *Bioinformatics* 2011, **27:**2987-2993.

621   20.   Kotlar A, Trevino C, Zwick M, Cutler D.J, Wingo T.S. **Bystro: rapid online variant**

622   **annotation and natural-language filtering at whole-genome scale**. Zenodo. 2017.

623   *http://dx.doi.org/10.5281/zenodo.834960*

Figure 1

A)

1000 Genomes Phase 3 Online Processing Time