1
2
3
4
5 **Inferotemporal cortex multiplexes behaviorally-relevant target match**
6 **signals and visual representations in a manner that minimizes their**
7 **interference**
8

10 Noam Roth and Nicole C. Rust*
11
12 Department of Psychology, University of Pennsylvania, Philadelphia, PA 19104
13
14 * Corresponding author
15 Email: nrust@psych.upenn.edu
16
17
18

19
20 Short title: Inferotemporal cortex during invariant object search
21
22
23

Abstract:

Finding a sought visual target object requires combining visual information about a scene with a remembered representation of the target to create a "target match" signal that indicates when a target is in view. Target match signals have been reported to exist within high-level visual brain areas including inferotemporal cortex (IT), where they are mixed with representations of image and object identity. However, these signals are not well understood, particularly in the context of the real-world challenge that the objects we search for typically appear at different positions, sizes, and within different background contexts. To investigate these signals, we recorded neural responses in IT as two rhesus monkeys performed a delayed-match-to-sample object search task in which target objects could appear at a variety of identity-preserving transformations. Consistent with the existence of behaviorally-relevant target match signals in IT, we found that IT contained a linearly separable target match representation that reflected behavioral confusions on trials in which the monkeys made errors. Additionally, target match signals were highly distributed across the IT population, and while a small fraction of units reflected target match signals as target match suppression, most units reflected target match signals as target match enhancement. Finally, we found that the potentially detrimental impact of target match signals on visual representations was mitigated by target match modulation that was approximately (albeit imperfectly) multiplicative. Together, these results support the existence of a robust, behaviorally-relevant target match representation in IT that is configured to minimally interfere with IT visual representations.

Introduction:

Finding a sought visual target object requires combining incoming visual information about the identities of the objects in view with a remembered representation of a sought target object to create a "target match" signal that indicates when a target has been found. During visual target search, target match signals have been reported to emerge in the brain as early as visual areas V4 (Bichot et al., 2005; Chelazzi et al., 2001; Haenny et al., 1988; Kosai et al., 2014; Maunsell et al., 1991) and IT (Chelazzi et al., 1998; Chelazzi et al., 1993; Eskandar et al., 1992; Gibson and Maunsell, 1997; Leuschow et al., 1994; Mruczek and Sheinberg, 2007; Pagan et al., 2013; Woloszyn and Sheinberg, 2009). However, we understand very little about the nature of target match signals, their behavioral relevance, and how these signals are mixed with visual representations.

The nature of the target match signal has been investigated most extensively with traditional versions of the delayed-match-to-sample (DMS) paradigm, which involves the presentation of a cue image indicating a target's identity, followed by the presentation of a random number of distractors and then a target match (e.g. Haenny et al., 1988; Miller and Desimone, 1994; Pagan et al., 2013). During classic DMS tasks in which the cue is presented at the beginning of each trial (and the match is thus a repeat later on), IT has been reported to reflect target match information with approximately equal numbers of neurons preferring target matches versus

those preferring distractors (i.e. "target match enhancement" and "target match suppression", respectively; Miller and Desimone, 1994; Pagan et al., 2013). Upon observing that target match suppression also follows from the repetition of distractor images within a trial, and thus cannot account for a signal that corresponds to a "target match" behavioral report, some have speculated that target match enhancement alone reflects the signal used to make behavioral judgments about whether a target match is present (Miller and Desimone, 1994). Others have proposed that the responses of both target match enhanced and suppressed subpopulations are incorporated to make behavioral judgments, particularly when a task requires disambiguating changes in firing rate due to the presence of a target match from other factors that impact overall firing rate, such as stimulus contrast (Engel and Wang, 2011). Notably, no study to date has produced compelling evidence that either IT target match enhancement or suppression accounts for (or correlates with) behavioral reports (e.g. on error trials).

Another limitation of the traditional DMS paradigm is that the cue image tends to be an exact copy of the target match, whereas real-world object search involves searching for an object that can appear at different positions, sizes and background contexts. One DMS study examined IT neural responses during this type of object variation and reported the existence of target match signals under these conditions (Leuschow et al., 1994). However, we still do not understand how IT target match signals are intermingled with IT invariant object representations of the currently-viewed scene. One intriguing proposal (Fig 1) suggests how visual and target match signals might be multiplexed to minimize the interference between them. That is, insofar as visual representations of different images are reflected as distinct patterns of spikes across the IT population (reviewed by DiCarlo et al., 2012), this translates into a population representation in which visual information is reflected by the population vector angle (Fig 1, 'Visual modulation'). If the introduction of target match modulation also changes population vector angles in IT, this could result in perceptual confusions about the visual scene. However, if target match modulation amounts to multiplicative rescaling of population response vector lengths, this would minimize interference when superimposing visual memories and target match representations within the same network (Fig 1, 'Target match modulation'). The degree to which the target match signal acts in this way remains unknown.

Figure 1. *Multiplexing visual and target match representations*. Shown are the hypothetical population responses to two images, each viewed (at different times) as target matches versus as distractors, plotted as the spike count response of neuron 1 versus neuron 2. In this scenario, visual information (e.g. image or object identity) is reflected by the population response pattern, or equivalently, the angle that each population response vector points. In contrast, target match information is reflected by changes in population vector length (e.g. multiplicative rescaling). Because target match information does not impact vector angle in this hypothetical scenario, superimposing target match information in this way would mitigate the impact of intermingling target match signals within underlying perceptual representations.

To investigate the nature of the IT target match signal, its behavioral relevance, and how it intermingles with IT visual representations, we recorded neural signals in IT as monkeys performed a modified delayed-match-to-sample task in which they were rewarded for indicating when a target object appeared across changes in the objects' position, size and background context.

Results:

The invariant delayed-match-to-sample task (IDMS)

To investigate the target match signal, we trained two monkeys to perform an "invariant delayed-match-to-sample" (IDMS) task that required them to report when target objects appeared across variation in the objects' positions, sizes and background contexts. In this task, the target object was held fixed for short blocks of trials (~3 minutes on average) and each block began with a cue trial indicating the target for that block (Fig 2a, "Cue trial"). Subsequent test trials always began with the presentation of a distractor and on most trials this was followed by additional distractors and then an image containing the target match (Fig 2a, "Test trial"). The monkeys' task required them to fixate during the presentation of distractors and make a saccade to a response dot on the screen following target match onset to receive a reward. In cases where the target match was presented for 400 ms and the monkey had still not broken fixation, a distractor stimulus was immediately presented. To minimize the predictability of the match appearing as a trial progressed, on a small subset of the trials the match did not appear and the monkey was rewarded for maintaining fixation. Our experimental design differs from other classic DMS tasks (e.g. Miller and Desimone, 1994; Pagan et al., 2013) in that it does not incorporate a cue at the beginning of each test trial, to better mimic real-world object search conditions in which target matches are not repeats of the same image presented shortly before.

Figure 2. *The invariant delayed-match-to-sample task.* a) Each block began with a cue trial indicating the target object for that block. On subsequent trials, no cue was presented and monkeys were required to maintain fixation throughout the presentation of distractors and make a saccade to a response dot following the onset of the target match to receive a reward. **b)** The experiment included 4 objects presented at each of 5 identity-preserving transformations ("up", "left", "right", "big", "small"), for 20 images in total. In any given block, 5 of the images were presented as target matches and 15 were distractors. **c)** The complete experimental design included looking "at" each of 4 objects, each presented at 5 identity-preserving transformations (for 20 images in total), viewed in the context of looking "for" each object as a target. In this design, target matches (highlighted in gray) fall along the diagonal of each "looking at" / "looking for" transformation slice. **d)** Percent correct for each monkey, calculated based on both misses and false alarms (but disregarding fixation breaks). Mean percent correct is plotted as a function of the position of the target match in the trial. Error bars (SEM) reflect variation across the 20 experimental sessions. **e)** Histograms of reaction times during correct trials (ms after stimulus onset) during the IDMS task for each monkey, with means indicated by arrows and labeled.

Our experiment included a fixed set of 20 images, including 4 objects presented at each of 5 transformations (Fig 2b). Our goal in selecting these specific images was to make the task of classifying object identity challenging for the IT population and these specific transformations were built on findings from our previous work (Rust and DiCarlo, 2010). In any given block (e.g. a squirrel target block), a subset of 5 of the images would be considered target matches and the remaining 15 would be distractors (Fig 2b). Our full experimental design amounted to 20 images (4 objects presented at 5 identity-preserving transformations), all viewed in the context of each

of the 4 objects as a target, resulting in 80 experimental conditions (Fig 2c). In this design,
"target matches" fall along the diagonals of each looking at / looking for matrix slice (where
"slice" refers to a fixed transformation; Fig 2c, gray). For each condition, we collected at least 20
repeats on correct trials. Monkeys generally performed well on this task (Fig 2d; mean percent
correct monkey 1 = 96%; monkey 2 = 87%). Their mean reaction times (computed as the time
their eyes left the fixation window relative to the target match stimulus onset) were 332 ms and
364 ms (Fig 2e).
170
As two monkeys performed this task, we recorded neural activity in IT using 24-channel probes.
We performed two types of analyses on these data. The first type of analysis was performed on
the data recorded simultaneously across units within a single recording session (n=20 sessions,
including 10 sessions from each monkey). The second type of analysis was performed on data
that was concatenated across different sessions to create a pseudopopulation after screening
for units based on their stability, isolation, and task modulation (see Methods; n=204 units in
total, including 108 units from monkey 1 and 96 units from monkey 2; S1 Dataset). For all but
four of our analyses (Fig 4b, 4d, 8, 9), we counted spikes in a window that started 80 ms
following stimulus onset (to allow stimulus-evoked responses time to reach IT) and ended at 250
ms, which was always before the monkeys' reaction times on these trials. For all but two of our
analyses (Fig 6, 7d), the data are extracted from trials with correct responses.
188   ***Target match signals were reflected in IT during the IDMS task***
189
Distributions of stimulus-evoked firing rates for the 204 units recorded in our experiment are
shown in Figure 3. As is typical of IT and other high-level brain areas, we encountered a
heterogeneous diversity of units with regard to their tuning to different aspects of the IDMS task.
Figure 4a depicts the responses of four example units, plotted as five slices through our
experimental design matrix (Fig 2c), where each slice corresponds to viewing each of the four
objects at a fixed transformation ('Looking AT') in the context of searching for each of the four
objects as a target ('Looking FOR'). Different types of task modulation produce distinct structure
in these response matrices. Visual modulation translates to vertical structure, (e.g. looking at the
same image while looking for different things) whereas target modulation translates to horizontal
structure (e.g. looking for the same object while looking at different things). In contrast, target
match modulation is reflected as a differential response to the same images presented as target
matches (which fall along the diagonal of each slice) versus distractors (which fall off the
diagonal), and thus manifests as diagonal structure in each slice.
203
Figure 3. *Firing rate distributions.* The firing rate response to each stimulus was calculated as
the mean across 20 trials in a window 80 - 250 ms following stimulus onset. **a)** Grand mean
firing rate across all 80 conditions. **b)** Maximum firing rates across the 80 conditions. Arrows
indicate the means (n=204 units).
Figure 4. *Quantifying modulation in IT during the IDMS task.* **a)** The response matrices
corresponding to four example IT units, plotted as the average response to five slices through
the experimental design, where each slice (a 4x4 matrix) corresponds to viewing each of four

objects ('Looking AT') in the context of each of four objects as a target ('Looking FOR'), at one
transformation ('Big', 'Left', 'Right', 'Small', 'Up'). To compute these responses, spikes were
counted in a window 80 –250 ms following stimulus onset, averaged across 20 repeated trials,
and rescaled from the minimum (black) to maximum (white) response across all 80 conditions.
b) Firing rate modulations were parsed into constituent types, where modulation was quantified
in units of standard deviation around each unit's grand mean spike count (see Results). The
evolution of average modulation magnitudes (across all the units for each animal; monkey 1: n =
108, monkey 2: n = 96), shown as a function of time relative to stimulus onset. The shaded area
indicates the spike count window used for subsequent analyses. **c)** Average modulation
magnitudes computed using the spike count window depicted in panel b. **d)** The average
temporal evolution of visual modulation plotted against the average temporal evolution of target
match modulation for groups of units organized into quantiles. Units with either target match or
visual modulation (n=203 of 204 units) were sorted by their ratios of target match over visual
modulation, computed in a window 80-250 ms following stimulus onset. The temporal evolution
of the mean across the population (black dotted line) is plotted among the temporal evolution of
each 25% quartile of the data, as well as the 95-100% quantile (labeled). Start times of each
trajectory (0 ms after stimulus onset) are indicated by a blue dot whereas end times of each
trajectory (250 ms after stimulus onset) are indicated by a red dot.

The first example unit (Fig 4a, 'visual, selective') only responded to one image (object 3
presented in the "big" transformation) and was unaffected by target identity. In contrast, the
second example unit ('Fig 4a, 'visual, invariant') responded fairly exclusively to one object, but
did so across four of the five transformations (all but "up"). This unit also had modest target
match modulation, reflected as a larger response to its preferred object (object 1) when it was a
distractor (i.e. when searching for targets 2-4) as compared to when it was a target (i.e. when
searching for target 1). In other words, this unit exhibited target match suppression. The third
example unit ("Fig 4a, 'one-object target match detector') consistently responded with a high
firing rate to object 3 presented as a target match across all transformations, but not to other
objects presented as target matches. This unit thus exhibited a form of target match
enhancement that was selective for object identity. The fourth example unit ("Fig 4a, 'four-object
target match detector') responded in a compelling way with a higher firing rate response to
nearly any image (any object at any transformation) presented as a target match as compared
to as a distractor, or equivalently target match enhancement that was invariant to object identity.
Given that the IDMS task requires an eye movement in response to images presented as target
matches and fixation to the same images presented as distractors, this unit reflects something
akin to the solution to the monkeys' task.

To quantify the amounts of these different types of modulations across the IT population, we
applied a procedure that quantified different types of modulation in terms of the number of
standard deviations around each unit's grand mean spike count (Pagan and Rust, 2014b). Our
procedure includes a bias-correction to ensure that modulations are not over-estimated by trial
variability and it is similar to a multi-way ANOVA, with important extensions (see Methods).
Modulation magnitudes were computed for the types described above, including visual, target
identity, and target match modulation, as well as "residual" modulations that are reflected as
nonlinear interactions between the visual stimulus and the target identity that are not captured
by target match modulation (e.g. specific distractor conditions). Notably, this analysis defines
target match modulation as a differential response to the same images presented as target
matches versus distractors, or equivalently, diagonal structure in the transformation slices

presented in Fig 4a. Consequently, units both like the "one-object target match detector" as well
as the "four-object target match detector" reflect target match modulation, as both units have a
diagonal component to their responses. What differentiates these two units is that the "one-
object target match detector" also reflects selectivity for image and target identity, reflected in
this analysis as a mixture of target match, visual, and target identity modulation.

Figure 4b illustrates these modulations computed in a sliding window relative to stimulus onset
and averaged across all units recorded in each monkey. As expected from a visual brain area,
we found that visual modulation was robust and delayed relative to stimulus onset (Fig 4b,
black). Visual modulation was considerably larger in monkey 1 as compared to monkey 2.
Target match modulation (Fig 4b, red) was also (as expected) delayed relative to stimulus onset
and was smaller than visual modulation, but it was well above the level expected by noise (i.e.
zero) and was similar in magnitude in both animals. In contrast, a robust signal reflecting
information about the target identity (Fig 4b, green) appeared before stimulus onset in monkey 1
and was weaker but also present in monkey 2, consistent with a persistent working memory
representation. Note that because the IDMS task was run in blocks with a fixed target, target
identity information was in fact present before the onset of each stimulus. Lastly, we found that
residual modulation was also present but was smaller than target match modulation in both
animals (Fig 4b, cyan). In sum, for a brief period following stimulus onset, visual and target
signals were present, but target match signals were not. After a short delay, target match
signals appeared as well. When quantified in a window positioned 80 to 250 ms following
stimulus onset and computed relative to the size of the target match signal (Fig 4c), visual
modulation was considerably larger than target match modulation (monkey 1: 2.9x, monkey 2:
2.0x; Fig 4c, gray), whereas the other types of modulations were smaller than target match
modulation (target modulation, monkey 1: 0.9x, monkey 2: 0.5x, Fig 4c green; residual
modulation, monkey 1: 0.6x, monkey 2: 0.9x Fig 4c, cyan).

To what degree do these population average traces (Fig 4b) reflect the evolution of visual and
target match signals in the same units as opposed to different units? To address this question,
we ranked units by their ratios of target match and visual modulation, and grouped them into
quantiles of neighboring ranks. Fig 4d shows a plot of the temporal evolution of visual
modulation plotted against the evolution of target match modulation for each 25% quartile. The
lowest-ranked quartile (Fig 4d, red) largely traversed and then returned along the y-axis,
consistent with units that were nearly completely visually modulated. Of interest was whether
quartiles with higher ratios of target match modulation would traverse the x-axis in an analogous
fashion (reflecting pure target match modulation) or whether these units would begin as visually
modulated and become target match modulated at later times. The trajectories for all three
higher quartiles (Fig 4d, orange, green, blue) reflected the latter scenario, as they all began with
a visually dominated component positioned above the unity line (Fig 4d, gray dashed). Later, the
trajectories become more horizontal, indicative of the emergence of target match modulation.
Similarly, the trajectory confined to just the top 5% (n=8) units (Fig 4d, purple dashed) began
with a visually dominated component that later evolved into strong target match modulation.
These results suggest that the evolution of visual to target match modulation is not happening
within distinct subpopulations, but rather is reflected within individual units.

To summarize, the results presented thus far verify the existence of a target match signal in IT
that is on average ~40% of the size of the visual modulation. Additionally, while the arrival of
target match modulation was delayed relative to the arrival of visual modulation, both types of
modulation tend to be reflected in the same units (as opposed to distinct subpopulations).

308
309
IT target match information was reflected as a highly distributed, linearly separable
representation

312
The IDMS task required monkeys to determine whether each condition (an image viewed in the context of a particular target block) was a target match or a distractor. This task ultimately maps all the target match conditions onto one behavioral response (a saccade) and all the distractor conditions onto another (maintain fixation), and as such, this task can be envisioned as a two-way classification across changes in other parameters, including changes in target and image identity (Fig 5a). One question of interest is the degree to which the target match versus distractor classification can be made with a linear decision boundary (or equivalently a linear decoder) applied to the IT neural data, as opposed to requiring a nonlinear decoding scheme. In a previous study, we assessed the format of IT target match information in the context of the classic DMS task design (Pagan et al., 2016; Pagan et al., 2013) and found that while a large component was linear, a considerable nonlinear (quadratic) component existed as well.

To quantify the amount and format of target match information within IT, we began by quantifying cross-validated performance for a two-way target match versus distractor classification with a weighted linear population decoder (a Fisher Linear Discriminant, FLD). Linear decoder performance began near chance and grew as a function of population size, consistent with a robust IT target match representation (Fig 5b, white). To determine the degree to which a component of IT target match information was present in a nonlinear format that could not be accessed by a linear decoder, we measured the performance of a maximum likelihood decoder designed to extract target match information regardless of its format (combined linear and nonlinear, Pagan et al., 2016; Pagan et al., 2013, see Methods). Performance of this nonlinear decoder (Fig 5b, gray) was slightly higher than the linear decoder for the pooled data ($p = 0.022$), and was not consistently higher in both animals (monkey 1 $p = 0.081$; monkey 2 $p = 0.647$). These results suggest that under the conditions of our measurements (e.g. the population sizes we recorded and the specific images used), IT target match information is reflected almost exclusively in a linearly separable format during the IDMS task. These results are at apparent odds with our previous reports of how IT target match information is reflected during a classic DMS task (see Discussion).

341
342
Figure 5. *IT target match information is reflected via weighted linear scheme.* **a)** The target search task can be envisioned as a two-way classification of the same images presented as target matches versus as distractors. Shown are cartoon depictions where each point depicts a hypothetical response of a population of two neurons on a single trial, and clusters of points depict the dispersion of responses across repeated trials for the same condition. Included are responses to the same images presented as target matches and as distractors. Here only 6 images are depicted but 20 images were used in the actual analysis. The dotted line depicts a hypothetical linear decision boundary. **b)** Linear (FLD) and nonlinear (maximum likelihood) decoder performance as a function of population size for a pseudopopulation of 204 units combined across both animals, as well as for the data recorded in each monkey individually (monkey 1: n = 108 units; monkey 2: n = 96 units.) Error bars (SEM) reflect the variability that can be attributed to the random selection of units (for populations smaller than the full dataset) and the random assignment of training and testing trials in cross-validation. **c)** Linear (FLD) decoder performance as a function of the number of top-ranked units removed. Shaded error

357   (SEM) reflects the variability that can be attributed to the random assignment of training and
358   testing trials in cross-validation.
359
360
Next, we wanted to better understand how target match information was distributed across the
IT population. We thus performed an analysis targeted at the impact of excluding the N "best"
target match units for different values of N, with the rationale that if it were the case that the
majority of target match information was carried by a small subpopulation of units, performance
should fall quickly when those units are excluded. For this analysis, we considered the
magnitude but not the sign of the target match modulation (whereas we address questions
related to parsing target match modulation by sign, or equivalently target match enhancement
versus suppression, below in Figure 7). To perform this analysis, we excluded the top-ranked IT
units via a cross-validated procedure (i.e. based on the training data; see Methods). Consistent
with a few units that carry target match signals that are considerably stronger than the rest of
the population, we found that the slope of the performance drop following the exclusion of the
best units was steepest for the top 8% (n=16) ranked units, and that these units accounted for
~25% of total population performance (Fig 5c). However, it was also the case that population
performance continued to decline steadily as additional units were excluded, and consequently,
population performance could not be attributed to a small fraction of top-ranked units alone (Fig
5c). For example, a 50% decrement in performance required removing 27% (n=55/204) of the
best-ranked IT population, and mean +/- SEM performance remained above chance up to the
elimination of 78% (n=160/204) of top-ranked units. These results are consistent with target
match signals that are strongly reflected in a few units (such as Fig 4a example unit 4), and are
more modestly distributed across a large fraction of the IT population (such as Fig 4a example
unit 2).
382
383   Taken together, these results suggest that IT target match information is reflected by a weighted
384   linear scheme and that target match performance depends on signals that are broadly
385   distributed across most of the IT population.
386
387
388   ***Projections along the IT linear decoding axis reflected behavioral confusions***
389
Upon establishing that the format of IT target match information during the IDMS task was linear
(on correct trials), we were interested in determining the degree to which behavioral confusions
were reflected in the IT neural data. To measure this, we focused on the data recorded
simultaneously across multiple units within each session, where all units observed the same
errors. With this data, we trained the linear decoder to perform the same target match versus
distractor classification described for Fig 5 using data from correct trials, and we measured
cross-validated performance on pairs of condition-matched trials: one for which the monkey
answered correctly, and the other for which the monkey made an error. On correct trials, target
match performance grew with population size and reached above chance levels in populations
of 24 units (Fig 6, black). On error trials, mean +/- SE of decoder performance fell below
chance, and these results replicated across each monkey individually (Fig 6, white). These
results establish that IT reflects behaviorally-relevant target match information insofar as
projections of the IT population response along the FLD decoding axis co-vary with the
monkeys' behavior.
404
405

Figure 6. *The IT FLD linear decoder axis reflects behavioral confusions.* Linear decoder performance, applied to the simultaneously recorded data for each session, after training on correct trials and cross-validating on pairs of correct and error trials matched for condition. Error bars (SEM) reflect the variability that can be attributed to the random selection of units (for populations smaller than the full dataset) and the random assignment of training and testing trials in cross-validation. Results are shown for the data pooled across all sessions (main plot, n= 20 sessions) as well as when the sessions are parsed by those collected from each animal (monkey 1, n=10 sessions; monkey 2, n=10 sessions).

Behaviorally-relevant target match signals were reflected as combinations of target match enhancement and suppression:

As described in the introduction, the IT target match signal has largely been studied via the classic DMS paradigm (which includes the presentation of the cue at the beginning of the trial) and previous results have reported approximately balanced mixtures of target match enhancement and suppression (Miller and Desimone, 1994; Pagan et al., 2013). While some have speculated that target match enhancement alone reflects the behaviorally-relevant target match signal (Miller and Desimone, 1994), others have argued that enhancement and suppression are both behaviorally-relevant (Engel and Wang, 2011). The results presented above demonstrate that during the IDMS task, the representation of target match information is largely linear, and projections along the FLD weighted linear axis reflect behavioral confusions. To what degree does IT target match information, including the reflection of behavioral confusions, follow from units that reflect target match information with target enhancement (positive weights) as compared to target suppression (negative weights)? In our study, this question is of particular interest in light of the fact that our experimental design does not include the presentation of a cue at the beginning of each trial, and thus minimizes the degree to which target match suppression follows passively from stimulus repetition.

To investigate this question, we computed a target match modulation index for each unit as the average difference between the responses to the same images presented as target matches versus as distractors, divided by the sum of those two quantities. This index takes on positive values for target match enhancement and negative values for target match suppression. In both monkeys, this index was significantly shifted toward positive values (Fig 7a; Wilcoxon sign rank test, monkey 1: mean = 0.063 $p = 8.44e^{-6}$; monkey 2: mean = 0.071, $p = 2.11e^{-7}$). Notably, while these distributions were dominated by units that reflected target match enhancement, a small fraction of IT units in both monkeys reflected statistically reliable target match suppression as well (fraction of units that were significantly target match enhanced and suppressed, respectively, monkey 1: 49.1%, 17.6%; monkey 2: 41.7%, 8.3%; bootstrap significance test, $p<0.01$).

Figure 7. *Target match signals are reflected as mixtures of enhancement and suppression.* **a)** A target match modulation index, computed for each unit by calculating the mean spike count response to target matches and to distractors, and computing the ratio of the difference and the sum of these two values. Dark bars in each histogram indicate the proportions for all units (Monkey 1: n = 108; monkey 2: n = 96) whereas gray bars indicate the fractions of units whose responses to target matches versus distractors were statistically distinguishable (bootstrap

significance test, p<0.01). Arrows indicate the distribution means. **b)** Target match modulation
index, computed and plotted as in (a), but after excluding responses to repeated presentation of
the same object within a trial. Included are units in which there were at least 10 repeated trials
for each condition (n = 176 of 204 possible units). **c)** Performance of the FLD classifier for the
combined population (n=204 units), computed for all units (as described for Fig 5b), target
match enhanced units ("E units") or target match suppressed units ("S units"). **d)** Performance of
the FLD classifier for populations of size 24 recorded in each session when trained on correct
trials and tested on condition-matched pairs of correct ("Corr.") and error ("Err.") trials (as
described for Fig 6), computed for all units, E units, and S units.
463
464
In our experiment, the same images were not repeated within a trial but the same objects,
presented under different transformations, could be. To what degree did the net target match
enhancement that we observed follow from distractor suppression as a consequence of
adaptation to object repetitions? To assess this, we recomputed target match modulation
indices in a manner than only incorporated the responses to the first presentation of each object
in a trial. Because this sub-selection reduced the number of distractor trials available for each
condition, we equated these with equal numbers of (randomly selected) target match trials. A
unit was only incorporated in the analysis if it had at least 10 trials per condition, yielding a
subpopulation of 176 (of 204 possible) units. In the absence of distractor object repetitions,
target match indices remained shifted toward net enhancement (Fig 7b; Wilcoxon sign rank test,
mean = 0.078 p = $8.09e^{-11}$; fraction of units that were significantly target match enhanced and
suppressed, respectively: 30.0%, 6.3%, bootstrap significance test, p <0.01), and the target
match indices computed without repeated distractors were not statistically distinguishable from
target match indices computed for the full dataset equated for numbers of trials, randomly
selected (not shown; mean = 0.067, p = 0.33). We thus conclude that the dominance of target
match enhancement in our population was not a consequence of distractor suppression that
follows from object repetitions within a trial.
482
To determine the degree to which target match enhanced versus target match suppressed units
contributed to population target match classification performance, we computed performance of
the FLD linear decoder when isolated to the target match enhanced or target match suppressed
subpopulations. More specifically, we focused on the combined data across the two monkeys
(to maximize the numbers of units, particularly given small fraction that were target match
suppressed), and we computed performance for variants of the FLD classifier in which the sign
of modulation was computed for each unit based on the training data. Cross-validated
performance was determined for either the subset of target match enhanced units or the subset
of target match suppressed units with the goal of determining their respective contributions to
overall population performance (while accounting for the fact that their proportions were not
equal). When the analysis was isolated to target match enhanced units ("E units"), performance
was virtually identical to the intact population (Fig 7c, mean+/- SEM performance for all units =
90.9+/-0.02% vs. E units = 90.6+/-0.02%), consistent with target match enhancement as the
primary type of modulation driving population performance. When the analysis was isolated to
target match suppressed units ("S units"), performance on correct trials was lower than that of
the intact population but still well above chance (Fig 7c, performance for S units = 64.4+/-
0.03%). This suggests that while target match suppressed units are smaller in number, the
target match suppressed units that do exist do in fact carry reliable target match signals.
501

What were the relative contributions of E units versus S units to error trial confusions? To
address this question, we repeated the error trial analysis described above for Figure 6, but
isolated to E or S units. Specifically, we repeated the analysis presented in Figure 6 where we
considered the simultaneously recorded data collected across 24 units for each session, but
isolated to the E or S units as described for Figure 7c (based on the training data), and we
compared cross-validated performance on condition-matched correct versus error trials. E units
classified correct trials above chance and misclassified error trials below chance at rates similar
to the entire population (Fig 7d, "All units" vs. "E units"), consistent with a larger overall
proportion of E units. In contrast, performance of the S units on correct trials was weaker and
mean +/- SEM performance was not above chance (53.0+/- 0.04%; Fig 7d "S units, Corr."),
consistent with smaller numbers of these units in IT. Similarly, performance of S units on
correct trials was slightly but not significantly higher than performance on error trials (mean +/-
SE performance on error trials = 46.6+/-0.02%; p = 0.090, Fig 7d, "S units, Err."). These results
indicate that the reflection of behavioral confusions in the IT neural data arises primarily from the
activity of E units, but suggest that behavioral confusions may also be weakly reflected in S
units.
518
As a complementary analysis of behavioral relevance, we also examined the degree to which
the responses to target matches reflected pre-saccadic activity by comparing the same
responses time-locked to stimulus onset versus saccade onset (Fig 8). The saccade-aligned
response was smaller and more diffuse than the stimulus-aligned response and saccade-
aligned responses peaked well before saccade onset (~200 ms), suggesting that on average, IT
responses to target matches do not reflect characteristic pre-saccadic activity.
525
526 **Figure 8.** *Comparison of stimulus-aligned versus reaction time-aligned responses to target*
527 *matches.* **a)** Grand mean PSTH across all units (n=204) for all target match stimuli, aligned to
528 stimulus onset. **b)** Grand mean PSTH across all units (n=204) for all target match stimuli,
529 aligned to behavioral reaction time.
530
Together, these results suggest that in the IDMS experiment, target match signals were
dominated by target match enhancement, but a smaller, target match suppressed subpopulation
exists as well. Additionally, they suggest that the reflection of behavioral confusions in IT neural
responses could largely be attributed to units that are target match enhanced, but behavioral
confusions were weakly reflected in units that are target match suppressed. Finally, while IT
responses reflect behavioral confusions, they were not well-aligned to reaction times.
537
538
539 ***The IT target match representation was configured to minimize interference with IT visual***
540 ***representations:***
541
As a final topic of interest, we wanted to understand how the representation of target match
information was multiplexed with visual representations in IT and more specifically, whether IT
had a means of minimizing the potentially detrimental impact of mixing these two types of
signals. One possible way to achieve this is multiplicative rescaling, as described in Figure 1. To
what degree is this happening in IT? As a first step toward addressing this question, we
quantified the impact of target match modulation as the representational similarity between the
IT population response vectors corresponding to the same images presented as target matches
versus as distractors, using a scale-invariant measure of similarity (the Pearson correlation,

reviewed by Kriegeskorte and Kievit, 2013). More specifically, we measured the Pearson
correlation between pairs of population response vectors via a split-halves procedure (see
Methods), and we compared the representational similarity for the same images presented as
target matches versus as distractors with other benchmarks in our experiment, including: within
the same experimental condition (i.e. random splits across repeated trials); between images
containing different transformations of the same object; and between images containing different
objects.

Shown in Figure 9a is the representational similarity matrix corresponding to all possible
pairwise combinations of the 20 images used in this experiment, averaged across the matrices
computed when the pairs of response vectors under consideration were target matches and
when they were distractors, computed with spike count windows 80-250 ms relative to stimulus
onset (see Methods). The matrix is organized such that the five transformations corresponding
to each object are grouped together. Figure 9b reorganizes the data into plots of the mean and
standard error of representational similarity computed for different pairwise comparisons. As
expected, we found that the representational similarity was the highest for random splits of the
trials corresponding to the same images, presented under the same conditions (Fig 9b, "Same
image & condition", mean = 0.43), which can be regarded as the noise ceiling in our data. In
comparison, the representational similarity was significantly lower for different transformations of
the same object (Fig 9b, "Different transforms."; mean = 0.14; $p = 1.14e^{-8}$) as well as for different
objects (Fig 9b, "Different objects"; mean = -0.02; $p = 1.92e^{-29}$). We note that a representational
similarity value of zero reflects the benchmark of IT population responses that are orthogonal,
and this was the case for the representation of different objects in IT. It was also the case that
representational similarity was significantly lower for different objects as compared to different
transformations of the same object ($p=1.43e^{-7}$), consistent with an IT representation that was
tolerant to changes in identity-preserving transformations. With these benchmarks established,
what impact did target match modulation have on IT visual representations? The average
representational similarity for the same images presented as target matches as compared to
distractors was significantly lower than the noise ceiling (Fig 9b, "Matches versus distractors";
mean = 0.28; $p = 2.09e^{-7}$) but was significantly higher than presenting the same object under a
new transformation (Fig 9b, p = 0.0016) or presenting a different object (Fig 9b, $p = 3.057e^{-20}$).
These results suggest that the multiplexing of IT target match signals was not perfect, but also
had a smaller impact on the population response than changing either the transformation in
which an object was viewed in or the object in view. These results, computed for broad spike
count windows (80-250 ms), were qualitatively replicated in narrower windows positioned early
(80-130 ms), midway (140-190 ms) and late (200-250 ms) relative to stimulus onset (Fig 9c).
Most notably, representational similarity for matches and distractors remained significantly
higher than representational similarity for different transformations of the same object in all
epochs (Fig 9c, "Mtch. v. Dstr." vs. "Diff. trans.", early p = 0.0023, mid p = 0.0081, late p =
0.0092). These results confirm that the impact of target match modulation on IT population
representational similarity remains modest throughout the stimulus-evoked response period.

Figure 9. *Target match signaling has minimal impact on the IT visual population response.* **a)**
The representational similarity matrix, computed as the average Pearson correlation between
the population response vectors computed for all possible pairs of images. Before computing
the correlations between pairs of population response vectors, the responses of each unit were
z-normalized to ensure that correlation values were not impacted by differences in overall firing
rates across units (see Methods). Correlations were computed based on a split halves

procedure. Shown are the average correlations, computed between images with a fixed target and averaged across all possible targets, as well as averaged across 1000 random splits. The matrix is organized such that different transformations of the same object are grouped together, in the same order as depicted in Fig 2. **b)** The average representational similarity, computed across: "Same image and condition": different random splits of the 20 trials into two sets of 10 trials each; "Different transforms.": images containing different transformations of the same object, computed with a fixed target identity; "Different objects": images containing different objects, computed with a fixed target identity; "Match versus distractor": the same image viewed as a target match as compared to as a distractor, averaged across all 9 possible distractor combinations (see Methods). **c)** The analysis described for panel b applied to different time epochs. Error bars (SEM) reflect variability across the 20 images.

To what degree does the modest impact of target match modulation follow from the multiplicative mechanism highlighted in Figure 1? One requirement for multiplicative population responses are individual units whose responses are themselves multiplicatively rescaled. To determine the degree to which our recorded IT units were multiplicative, we computed the impact of target match modulation as a function of stimulus rank and compared it to the benchmarks expected for multiplicative rescaling as well as other alternatives (including subtraction and sharpening; Fig 10a,c). Specifically, we ranked the responses of each unit to the 20 images separately (after averaging across target matches and distractors), and we then computed the average across all units at each rank for target matches and distractors separately. Average IT target match modulation was much better described as multiplicative than as subtractive or sharpening (Fig 10b,d).

Figure 10. *The impact of target match modulation on the visual responses of individual units.* **a)** Cartoon depiction of the impact of different types of target match modulation on the rank-ordered responses to different images. **b)** Mean and SEM of the rank-order responses across units, after ranking the responses for each unit separately (based on the averaged response to target matches and distractors). **c)** The cartoons in panel a, replotted as the difference between target matches and distractors at each rank to visualize the differences between them. **d)** The analysis described in panel c, applied to the data in panel b, reveals that the impact of target match modulation is better described as multiplicative than as subtractive or as sharpening.

A second requirement for multiplicative population response vectors is homogeneity in target match modulation across units (Fig 11a, cyan). Variation across units in terms of the magnitudes of target match modulation (Fig 11a, left, red), and/or variation that includes mixtures of target match enhancement and suppression (Fig 11a, right, red) can produce changes in population response vector positions that could be confounded with changes in the visual identity, if the variations were sufficiently large. Where does the amount of target match modulation heterogeneity that we observed (e.g. Fig 7a) fall relative to the benchmarks of the best versus worst format that it could possibly take? To investigate this question, we performed a series of data-based simulations targeted at benchmarking our results relative to "best case" and "worse case" scenarios for multiplexing given the magnitudes of target match modulation in our data. As a first "replication" simulation, we replicated the responses recorded for each unit by preserving the magnitudes and types of signals as well as each unit's grand mean spike count and we simulated trial variability with an independent, Poisson process (see Methods). The pattern of representational similarities reflected in the raw data (Fig 9b) were approximated in simulation (Fig 11b), suggesting that this simulation procedure was effective at capturing important elements of the data. In the other simulations described below, we began in the same

647 way: by preserving the amounts and types of visual, target and residual modulation recorded in
648 each unit, as well as each unit's grand mean firing rate. What differed between the simulations
649 was how that target match modulation was distributed across units.
650
To simulate the "best case scenario" in our data, we approximated multiplicative rescaling by
distributing the total target match modulation across units in equal proportions relative to their
magnitudes of visual modulation. In this simulation, target match modulation was introduced
with the same sign (target match enhancement) across all units, consistent with the average
sign reflected in the raw data (Fig 7a). Representational similarity between target matches and
distractors in this multiplicative, same-sign simulation was statistically indistinguishable from the
noise ceiling (Fig 11c, $p = 0.395$), confirming intuitions that a population can (in principle)
multiplex target match signals in a multiplicative manner that has minimal interference with
visual representations. To simulate a "worse case scenario" for our data, we increased the
amount of target match modulation heterogeneity across units by both distributing target match
modulation uniformly (as opposed to proportionally) across units as well as preserving the
original sign of each unit's target match modulation (i.e. target match enhancement or
suppression). Representational similarity between target matches and distractors in this
uniform, mixed-sign simulation fell to levels measured for different transformations of the same
object (Fig 11c), confirming that our data do not reflect a "worst case scenario" given the
magnitudes of target match modulation that we observed. Together, these results suggest that
in line with Fig 1, the impact of target match modulation on IT visual representations is modest
(Fig 9) as a consequence of modulation that is approximately (albeit imperfectly) multiplicative,
due both to individual units with target match modulation that is multiplicative on average, as
well as target match modulation that is approximately (albeit imperfectly) functionally
homogenous.
672
Figure 11. *Benchmarking the impact of target match modulation heterogeneity across units.* **a)**
Cartoon depiction of how heterogeneity across units in target match modulation magnitudes
(left) and modulation signs (right) can lead to changes in the population response to the same
images presented as target matches versus distractors. **b)** Three simulated variants of the
recorded data (see Results), including target match modulation for each unit that was:
replicated; enforced to be multiplicative and reflected with the same-sign across all units (i.e.
target match enhancement); enforced to be uniform and reflected with mixed-signs across units
(i.e. target match enhancement or suppression, as determined by the original data).
681
682

Discussion:

Successfully finding a sought target object, such as your car keys, requires your brain to compute a target match signal that reports when a target is in view. Target match signals have been reported to exist in IT, but these signals are not well understood, particularly in the context of the real-world problem of searching for an object that can appear at different identity-preserving transformations. We recorded responses in IT as two monkeys performed a delayed-match-to-sample task in which a target object could appear at different positions, sizes, and background contexts. We found that the IT population reflected a target match representation that was largely linear, and that it reflected behavioral confusions on trials in which the monkeys made errors. IT target match signals were broadly distributed across most IT units, and while they were dominated by target match enhancement, we also found evidence for reliable target match suppression. Finally, we found that IT target match modulation was configured in such a manner as to minimally impact IT visual representations. Together, these results support the existence of a robust, behaviorally-relevant target match representation in IT that is multiplexed with IT visual representations.

Our results support the existence of a robust target match representation in IT during this task that reflects confusions on trials in which the monkeys make errors (Fig 6); this result has not been reported previously. One earlier study also explored the responses of IT neurons in the context of a DMS task in which, like ours, the objects could appear at different identity-preserving transformations (Leuschow et al., 1994), but this study did not sort neural responses based on behavior. Another study examined IT neural responses as monkeys performed a visual target search task that involved free viewing as well as image manipulation during the time of the saccade (Mruczek and Sheinberg, 2007). They reported higher firing rates in IT neurons during trial sequence that normally led to a reward (an association between a target object and a saccade to a response target) versus swap trials in which this sequence was disrupted. Another study (from our lab) used a classic DMS design reported that IT population classifications on error trials fell to chance (Pagan et al., 2013), but this study did not find evidence for significant error trial misclassifications.

IT target match signals have been investigated most extensively in IT via a classic version of the delayed-match-to-sample (DMS) paradigm where each trial begins with a visual cue indicating the identity of the target object, and this cue is often the same image as the target match (Eskandar et al., 1992; Miller and Desimone, 1994; Pagan et al., 2013). In this paradigm, approximately half of all IT neurons that differentiate target matches from distractors do so with enhanced responses to matches whereas the other half are match suppressed (Miller and Desimone, 1994; Pagan et al., 2013). Because match suppressed responses also follow from the repetition of distractors within a trial, some have speculated that the match enhanced neurons alone carry behaviorally-relevant target match information (Miller and Desimone, 1994). In general agreement with those notions, the target match signal is dominated by target match enhancement in situations where the cue and target match are presented at different locations (Chelazzi et al., 1993). Conversely, others have argued that a representation comprised exclusively of match enhanced neurons would confuse the presence of a match with modulations that evoke changes in overall firing rate, such as changes in stimulus contrast (Engel and Wang, 2011). Additionally, these authors proposed that match suppressed neurons could be used in these cases to disambiguate target match versus stimulus-induced modulation. In our experiment, the IDMS task was run in blocks containing a fixed target to minimize the

impact of passive stimulus repetition of the target match. We found evidence for net target
match enhancement in our data (Fig 7a), and that this in turn translated into a type of
homogeneity that minimized the potentially detrimental impact of target match modulation on
visual representations (Fig 11). However, we also found evidence for a smaller subpopulation
of units that reflected reliable target match suppression. Whether the amount of target match
suppression that we observed is sufficient for the disambiguation strategy proposed by Engel
and Wang (2011) is thus unclear - because our experiment did not include variation in
parameters that change overall firing rate (such as contrast), we cannot directly test it with our
data.
740
How does the target match signal arrive in IT? Computation of the target match signal requires a
comparison of the content of the currently-viewed scene with a remembered representation of
the sought target. The existence of target match signals in IT could reflect the implementation of
the comparison in IT itself or, alternatively, this comparison might be implemented in a higher-
order brain area (such as prefrontal cortex) and fed-back to IT. Examination of the timing of the
arrival of this signal in IT (which peaks at 150 ms; Fig 4b) relative to the monkeys' median
reaction times (~340 ms; Fig 2e), does not rule out the former scenario. The fact that neural
responses to target matches were more time locked to stimulus onset than they are to reaction
times suggests that this activity does not reflect classic signatures of motor preparation.
Additional insights into whether or not target match signals are computed in IT might be gained
through analyses of the responses on cue trials, particularly with regard to whether signatures of
the visually-evoked responses to cues persist throughout each block, however, our experimental
design included too few cue presentations for such analyses. Thus while our data are consistent
with target match computations within IT cortex, we cannot definitively distinguish this proposal
from alternative scenarios with this data. Additionally, in this study monkeys were trained
extensively on the images used in these experiments and future experiments will be required to
address the degree to which these results hold under more everyday conditions in which
monkeys are viewing images and objects for the first time.
759
In a previous series of reports, we investigated target match signals in the context of the classic
DMS design in which target matches were repeats of cues presented earlier in the trial and each
object was presented on a gray background (Pagan and Rust, 2014a; Pagan et al., 2016;
Pagan et al., 2013). One of our main findings from that work was that the IT target match
representation was reflected in a partially nonlinearly separable format, whereas an IT
downstream projection area, perirhinal cortex, contained the same amount of target match
information but in a format that was largely linearly separable. In the data we present here, we
did not find evidence for a nonlinear component of the IT target match representation, reflected
as consistently higher performance of a maximum likelihood as compared to linear decoder (Fig
5b). The source of these differences is unclear. They could arise from the fact that the IDMS
task requires an "invariant" visual representation of object identity, which first emerges in a
linearly separable format in the brain area that we are recording from (Rust and DiCarlo, 2010),
whereas in more classic forms of the DMS task, the integration of visual and target information
could happen in a different manner and/or a different brain area. Alternatively, these differences
could arise from the fact that during IDMS, images are not repeated within a trial, and the
stronger nonlinear component revealed in DMS may be produced by stimulus repetition. It may
also be the case that nonlinearly separable information is in fact present in IT during IDMS but
was not detectable under the specific conditions used in our experiments. For example, the
proportion of nonlinearly separable information grows as a function of population size, and it

may be the case that it is detectable during IDMS for larger sized populations. Our current data
cannot distinguish between these alternatives.
781
Our results also add to the growing literature that suggests the brain "mixes" the modulations for
different task-relevant parameters within individual neurons, even at the highest stages of
processing (Freedman and Assad, 2009; Kobak et al., 2016; Mante et al., 2013; Meister et al.,
2013; Raposo et al., 2014; Rigotti et al., 2013; Rishel et al., 2013; Zoccolan et al., 2007). A
number of explanations have been proposed to account for mixed selectivity. Some studies
have documented situations in which signal mixing is an inevitable consequence of the
computations required for certain tasks, such as identifying objects invariant to the view in which
they appear (Zoccolan et al., 2007). Others have suggested that mixed selectivity may be an
essential component of the substrate required to maintain a representation that can rapidly and
flexibly switch with changing task demands (Raposo et al., 2014; Rigotti et al., 2013). Still others
have maintained that broad tuning across different types of parameters is important for learning
new associations (Barak et al., 2013). Our results suggest that IT mixes visual and target match
information within individual units. This could reflect the fact that the comparison of visual and
target match information happens within IT itself, and multiplexing is simply a byproduct of that
computation. Alternatively, if the comparison is performed elsewhere, this would reflect its
feedback to IT for some unknown purpose. In either case, our results suggest that the
multiplexing happens in a manner that is largely but imperfectly multiplicative (Fig 10-11) and
thus configured to minimize interference of visual representations when also signaling target
match information.
801

802 **Acknowledgements:**
803
804 We thank Margot P. Wohl for her contributions to early phases of this work. This work was
805 supported by the National Eye Institute of the National Institutes of Health (award
806 R01EY020851), the Simons Foundation (through an award from the Simons Collaboration on
807 the Global Brain), and the McKnight Endowment for Neuroscience.

METHODS

Experiments were performed on two adult male rhesus macaque monkeys (*Macaca mulatta)* with implanted head posts and recording chambers. All procedures were performed in accordance with the guidelines of the University of Pennsylvania Institutional Animal Care and Use Committee and this study was approved under protocol 804222.

The invariant delayed-match-to-sample (IDMS) task:

All behavioral training and testing was performed using standard operant conditioning (juice reward), head stabilization, and high-accuracy, infrared video eye tracking. Stimuli were presented on an LCD monitor with an 85 Hz refresh rate using customized software (http://mworks-project.org).

As an overview, the monkeys' task required an eye movement response to a specific location when a target object appeared within a sequence of distractor images (Fig 2a). Objects were presented across variation in the objects' position, size and background context (Fig 2b). Monkeys viewed a fixed set of 20 images across switches in the identity of 4 target objects, each presented at 5 identity-preserving transformations (Fig 2c). Monkeys were trained extensively on the set of 20 images shown in Fig 2b before testing. We ran the task in short blocks (~3 min) with a fixed target before another target was pseudorandomly selected. Our design included two types of trials: cue trials and test trials (Fig 2a). Only test trials were analyzed for this report.

Trials were initiated by the monkey fixating on a red dot (0.15°) in the center of a gray screen, within a square window of ±1.5°, followed by a 250 ms delay before a stimulus appeared. Cue trials, which indicated the current target object, were presented at the beginning of each block and after three subsequent trials with incorrect responses. To minimize confusion, cue trials were designed to be distinct from test trials and began with the presentation of an image of each object that was distinct from the images used on test trials (a large version of the object presented at the center of gaze on a gray background; Fig 2a). Test trials, which are the focus of this report, always began with a distractor image, and neural responses to this image were discarded to minimize non-stationarities such as stimulus onset effects. Distractors were drawn randomly from a pool of 15 possible images within each block without replacement until each distractor was presented once on a correct trial, and the images were then re-randomized. On most trials, a random number of 1-6 distractors were presented, followed by a target match (Fig 2a). On a small fraction of trials, 7 distractors were shown, and the monkey was rewarded for fixating through all distractors. Each stimulus was presented for 400 ms (or until the monkeys' eyes left the fixation window) and was immediately followed by the presentation of the next stimulus. Following the onset of a target match image, monkeys were rewarded for making a saccade to a response target within a window of 75 – 600 ms to receive a juice reward. In monkey 1 this target was positioned 10 degrees above fixation; in monkey 2 it was 10 degrees below fixation. If 400 ms following target onset had elapsed and the monkey had not moved its eyes, a distractor stimulus was immediately presented. If the monkey continued fixating beyond the required reaction time, the trial was considered a "miss". False alarms were differentiated from fixation breaks via a comparison of the monkeys' eye movements with the characteristic pattern of eye movements on correct trials: false alarms were characterized by the eyes leaving the fixation window via its top (monkey 1) or bottom (monkey 2) outside the allowable correct

response period and traveling more than 0.5 degrees whereas fixation breaks were
characterized by the eyes leaving the fixation window in any other way. Within each block, 4
repeated presentations of the 20 images were collected, and a new target object was then
pseudorandomly selected. Following the presentation of all 4 objects as targets, the targets
were re-randomized. At least 20 repeats of each condition were collected. Overall, monkeys
performed this task with high accuracy. Disregarding fixation breaks (monkey 1: 11% of trials,
monkey 2: 8% of trials), percent correct on the remaining trials was as follows: monkey 1: 96%
correct, 1% false alarms, and 3% misses; monkey 2: 87% correct, 3% false alarms, and 10%
misses.
866
867
868 **Neural recording:**
869
The activity of neurons in IT was recorded via a single recording chamber in each monkey.
Chamber placement was guided by anatomical magnetic resonance images in both monkeys,
and in one monkey, Brainsight neuronavigation (https://www.rogue-research.com/). The region
of IT recorded was located on the ventral surface of the brain, over an area that spanned 4 mm
lateral to the anterior middle temporal sulcus and 15-19 mm anterior to the ear canals. Neural
activity was largely recorded with 24-channel U probes (Plexon, Inc) with linearly arranged
recording sites spaced with 100 mm intervals, with a handful of units recorded with single
electrodes (Alpha Omega, glass-coated tungsten). Continuous, wideband neural signals were
amplified, digitized at 40 kHz and stored using the OmniPlex Data Acquisition System (Plexon).
Spike sorting was done manually offline (Plexon Offline Sorter). At least one candidate unit was
identified on each recording channel, and 2-3 units were occasionally identified on the same
channel. Spike sorting was performed blind to any experimental conditions to avoid bias. A
multi-channel recording session was included in the analysis if the animal performed the task
until the completion of 20 correct trials per stimulus condition, there was no external noise
source confounding the detection of spike waveforms, and the session included a threshold
number of task modulated units (>4 on 24 channels). The sample size (number of units
recorded) was chosen to approximately match our previous work (Pagan and Rust, 2014a;
Pagan et al., 2016; Pagan et al., 2013).
888
For all the analyses presented in this paper except Fig 4b,d, Fig 8, and Fig 9c, we measured
neural responses by counting spikes in a window that began 80 ms after stimulus onset and
ended at 250 ms. On 1.9% of all correct target match presentations, the monkeys had reaction
times faster than 250 ms, and those instances were excluded from analysis such that spikes
were only counted during periods of fixation. When combining the units recorded across
sessions into a larger pseudopopulation, we screened for units that met three criteria. First, units
had to be modulated by our task, as quantified by a one-way ANOVA applied to our neural
responses (80 conditions * 20 repeats) with $p < 0.01$. Second, we applied a loose criterion on
recording stability, as quantified by calculating the variance-to-mean for each unit (computed by
fitting the relationship between the mean and variance of spike count across the 80 conditions),
and eliminating units with a variance-to-mean ratio > 5. Finally, we applied a loose criterion on
unit recording isolation, quantified by calculating the signal-to-noise ratio (SNR) of the waveform
(as the difference between the maximum and minimum points of the average waveform, divided
by twice the standard deviation across the differences between each waveform and the mean
waveform), and excluding (multi)units with an SNR < 2. This yielded a pseudopopulation of 204
units (of 563 possible units), including 108 units from monkey 1 and 96 units from monkey 2.

905
Quantifying single-unit modulation magnitudes:

907
To quantify the degree to which individual units were modulated by different types of task
parameters (Fig 4b-d), we applied a bias-corrected procedure described in detail by (Pagan and
Rust, 2014b) and summarized here. Our measure of modulation is similar to a multi-way
ANOVA, with important extensions. Specifically, a two-way ANOVA applied to a unit's
responses (configured into a matrix of 4 targets * 20 images * 20 trials for each condition) would
parse the total response variance into two linear terms, a nonlinear interaction term, and an
error term. We make 3 extensions to the ANOVA analysis. First, an ANOVA returns measures
of variance (in units of spike counts squared) whereas we compute measures of standard
deviation (in units of spike count) such that our measures of modulation are intuitive (e.g.,
doubling firing rates causes signals to double as opposed to quadruple). Second, while the
linear terms of the ANOVA map onto our "visual" and "target identity" modulations (after
squaring), we split the ANOVA nonlinear interaction term into two terms, including target match
modulation (i.e. Fig 2c gray versus white) and all other nonlinear "residual" modulation. This
parsing is essential, as target match modulation corresponds to the signal for the IDMS task
whereas the other types of modulations are not. Finally, raw ANOVA values are biased by trial-
by-trial variability (which the ANOVA addresses by computing the probability that each term is
higher than chance given this noise) whereas our measures of modulation are bias-corrected to
provide an unbiased estimate of modulation magnitude.

926
The procedure begins by developing an orthonormal basis of 80 vectors designed to capture all
types of modulation with intuitive groupings. The number of each type is imposed by the
experimental design. This basis b included vectors b_i that reflected 1) the grand mean spike
count across all conditions (b_1, 1 dimension), 2) whether the object in view was a target or a
distractor (b_2, 1 dimension), 3) visual image identity ($b_3 - b_{21}$, 19 dimensions), 4) target object
identity ($b_{22} - b_{24}$, 3 dimensions), and 5) "residual", nonlinear interactions between target and
object identity not captured by target match modulation ($b_{25} - b_{80}$, 56 dimensions). A Gram-
Schmidt process was used to convert an initially designed set of vectors into an orthonormal
basis.

936
Because this basis spans the space of all possible responses for our task, each trial-averaged
vector of spike count responses to the 80 experimental conditions R can be re-expressed as a
weighted sum of these basis vectors. To quantify the amounts of each type of modulation
reflected by each unit, we began by computing the squared projection of each basis vector
b_i and R. An analytical bias correction, described and verified in (Pagan and Rust, 2014b), was
then subtracted from this value:

943
944   (8) $w_i^2 = (\mathbf{R} \cdot \mathbf{b}_i^T)^2 - \frac{\sigma_t^2 \cdot (\mathbf{b}_i^T)^2}{m}$

945
where σ_t^2 indicates the trial variance, averaged across conditions (n=80), and where m indicates
the number of trials (m=20). When more than one dimension existed for a type of modulation,
we summed values of the same type. Next, we applied a normalization factor (1/(n-1)) to convert
these summed values into variances. Finally, we computed the square root of these quantities
to convert them into modulation measures that reflected the number of spike count standard
deviations around each unit's grand mean spike count.

Target match modulation was thus computed as:
954

955   (9) $\sigma_{TM} = \sqrt{\frac{1}{n-1} \cdot w_2^2}$

956
957   visual modulation was computed as:
958

959   (10) $\sigma_{Vis} = \sqrt{\frac{1}{n-1} \cdot \sum_{i=3}^{21} w_i^2}$

960
961   target identity modulation was computed as:
962

963   (11) $\sigma_{TI} = \sqrt{\frac{1}{n-1} \cdot \sum_{i=22}^{24} w_i^2}$

964
965   and residual modulation was computed as:
966

967   (12) $\sigma_{res} = \sqrt{\frac{1}{n-1} \cdot \sum_{i=25}^{80} w_i^2}$

968
969
When estimating modulation population means (Fig 4b,c), the bias-corrected squared values
were averaged across units before taking the square root. Because these measures were not
normally distributed, standard error about the mean was computed via a bootstrap procedure.
On each iteration of the bootstrap (across 1000 iterations), we randomly sampled values from
the modulation values for each unit in the population, with replacement. Standard error was
computed as the standard deviation across the means of these newly created populations.
976
977   To quantify the sign of the modulation corresponding to whether an image was presented as a
978   target match versus as a distractor (Fig 7a,b), we calculated a target match modulation index for
979   each unit by computing its mean spike count response to target matches and to distractors, and
980   computing the ratio of their difference and their sum.
981
982
983   **Population performance:**
984
985   To determine the performance of the IT population at classifying target matches versus
986   distractors, we applied two types of decoders: a Fisher Linear Discriminant (a linear decoder)
987   and Maximum Likelihood decoder (a nonlinear decoder) using approaches that are described
988   previously in detail (Pagan et al., 2013) and are summarized here.
989
When applied to the pseudopopulation data (Fig 5b, Fig 7b), all decoders were cross-validated
with the same resampling procedure. On each iteration of the resampling, we randomly shuffled
the trials for each condition and for each unit, and (for numbers of units less than the full
population size) randomly selected units. On each iteration, 18 trials from each condition were
used for training the decoder, 1 trial was used to determine a value for regularization, and 1 trial
from each condition was used for cross-validated measurement of performance.
996

To ensure that decoder performance was not biased by unequal numbers of target matches and
distractors, on each iteration of the resampling we included 20 target match conditions and 20
(of 60 possible) distractor conditions. Each set of 20 distractors was selected to span all
possible combinations of mismatched object and target identities (e.g. objects 1, 2, 3, 4 paired
with targets 4, 3, 2, 1), of which there are 9 possible sets. To compute proportion correct, a
mean performance value was computed on each resampling iteration by averaging binary
performance outcomes across the 9 possible sets of target matches and distractors, each which
contained 40 test trials. Mean and standard error of performance was computed as the mean
and standard deviation of performance across 1000 resampling iterations. Standard error thus
reflected the variability due to the specific trials assigned to training and testing and, for
populations smaller than the full size, the specific units chosen.
1008
1009
1010 *Fisher Linear Discriminant:*
1011
1012 The general form of a linear decoding axis is:
1013
1014 (1) $f(\boldsymbol{x}) = \boldsymbol{w}^T \boldsymbol{x} + b,$
1015
1016 where **w** is an N-dimensional vector (where N is the number of units) containing the linear
1017 weights applied to each unit, and b is a scalar value. We fit these parameters using a Fisher
1018 Linear Discriminant (FLD), where the vector of linear weights was calculated as:
1019
1020 (2) $\boldsymbol{w} = \Sigma^{-1}(\mu_1 - \mu_2)$
1021
1022 and b was calculated as:
1023
1024 (3) $b = \boldsymbol{w} \cdot \frac{1}{2}(\mu_1 + \mu_2) = \frac{1}{2}\mu_1{}^T\Sigma^{-1}\mu_1 - \frac{1}{2}\mu_2{}^T\Sigma^{-1}\mu_2$
1025
1026 Here $\mu_1\ and\ \mu_2$ are the means of the two classes (target matches and distractors, respectively)
1027 and the mean covariance matrix is calculated as:
1028
1029 (4) $\Sigma = \frac{\Sigma_1 + \Sigma_2}{2}$
1030
1031 where Σ_1 and Σ_2 are the regularized covariance matrices of the two classes. These covariance
1032 matrices were computed using a regularized estimate equal to a linear combination of the
1033 sample covariance and the identity matrix I (Pagan et al., 2016):
1034
1035 (5) $\Sigma_i = \gamma \Sigma_i + (1 - \gamma) \cdot I$
1036
We determined γ by exploring a range of values from 0.01 to 0.99, and we selected the value
that maximized average performance across all iterations, measured with the cross-validation
"regularization" trials set aside for this purpose (see above). We then computed performance for
that value of γ with separately measured "test" trials, to ensure a fully cross-validated measure.
Because this calculation of the FLD parameters incorporates the off-diagonal terms of the
covariance matrix, FLD weights are optimized for both the information conveyed by individual
units as well as their pairwise interactions.
1044

To compare FLD performance on correct versus error trials (Fig 6, 7d), we used the same
methods described above with the following modifications. First, the analysis was applied to the
simultaneously recorded data within each session, and the correlation structure on each trial
was kept intact on each resampling iteration. Second, when more than 24 units were available,
a subset of 24 units were selected as those with the most task modulation, quantified via the p-
value of a one-way ANOVA applied to each unit's responses (80 conditions * 20 repeats).
Finally, on each resampling iteration, each error trial was randomly paired with a correct trial of
the same condition and cross-validated performance was performed exclusively for these pairs
of correct and error responses. As was the case for the pseudopopulation analysis, training
was performed exclusively on correct trials. A mean performance value was computed on each
resampling iteration by averaging binary performance outcomes across all possible error trials
and their condition-matched correct trial pairs, and averaging across different recording
sessions. Mean and standard error of performance was computed as the mean and standard
deviation of performance across 100 resampling iterations. Standard error thus reflected error in
a manner similar to the pseudopopulation analysis - the variability due to the specific trials
assigned to training and testing and, for populations smaller than the full size, the specific units
chosen.
1062
In the case of the ranked-FLD (Fig 5c), all units were considered on each resampling iteration,
and weights were computed for each unit (with the training data) as described by Equation 2.
Weights were then ranked by their magnitude (the absolute values of the signed quantities) and
the top N units were selected for different population size N. Finally, both the weights and the
threshold were recalculated before cross-validated testing with the training data. In the case of
the signed versions of the FLD (which isolated the analysis to target matched enhanced or
suppressed units, Fig 7c-d), the process was similar in that all units were considered on each
resampling iteration and weights were computed for each unit (with the training data) as
described by Equation 2. Weights were then isolated to all of those that were positive "E units"
or all that were negative "S units". Finally, the weights and the threshold were recalculated
before cross-validated testing with the training data.
1074
1075
1076   *Maximum likelihood decoder:*
1077
As a measure of total IT target match information (combined linear and nonlinear), we
implemented the maximum likelihood decoder (Fig 5b) introduced in our previous work (Pagan
et al., 2016; Pagan et al., 2013). We began by using the set of training trials to compute the
average response r_{uc} of each unit u to each of the 40 conditions c. We then computed the
likelihood that a test response k was generated from a particular condition as a Poisson-
distributed variable:
1084
1085 $(7)\ lik_{u,c}(k) = \frac{(r_{uc})^{k} \cdot e^{-r_{uc}}}{k!}$
1086
The likelihood that a population response vector was generated in response to each condition
was then computed as the product of the likelihoods of the individual units. Next, we computed
the likelihood that each test vector arose from the category target match as compared to the
category distractor as the product of the likelihoods across the conditions within each category.
We assigned the population response to the category with the maximum likelihood, and we

computed performance as the fraction of trials in which the classification was correct based on
the true labels of the test data.
1094
1095
1096 **Representational similarity:**
1097
Before computing representational similarity (Fig 9a), the responses of each unit were z-
normalized to have a mean of zero and standard deviation of 1. To compute measures of the
representational similarity between pairs of population response vectors, the 20 repeated trials
for each (of 80) experimental conditions were randomly split into two sets of 10 trials, and the
average population response vector was computed. To obtain measures of the noise ceiling,
Pearson correlation was computed between many random splits of the data for each of the 80
conditions. The mean across 1000 random splits was computed for each condition and the
values were averaged across the splits as well as the 4 target conditions for each image,
resulting in 20 correlations values (1 for each image). Fig 9b "Same image and condition"
depicts the mean and standard deviation across the 20 images. Measures of the
representational similarity between different conditions were computed in a comparable way, by
also selecting 10 (of 20) trials before computing the mean population response vectors. To
measure the representational similarity between the same objects presented at different
transformations, Pearson correlation was computed for all possible pairs of the 5 images
corresponding to each object under the conditions of a fixed target. A mean value was
computed as the average across 1000 random splits and the pairwise comparison between 1
image and other images containing the same object for each of 20 images, and Fig 9b "Different
transforms." depicts the mean and standard deviation across the 20 images. Fig 9b "Different
objects" was computed in a similar manner, but for all possible pairs of one image and the
images containing other objects. Finally, Fig 9b "Match versus distractor" was computed in a
similar manner, but for all possible pairs of one image presented as a target match (viewing an
image while looking for that object as a target) and the three distractor conditions (the three
other targets). The same procedures were carried out for Fig 9c and 11b.
1121
1122 **Simulations:**
1123
To better understand our results, we performed a number of data-based simulations (Fig 11b).
Each simulation began by computing the bias-corrected weights for each unit as described
above. For the "replication" simulation, we rectified bias-corrected modulations that fell below
zero, recomputed the noise-corrected mean spike count responses for each condition, and
generated trial variability with an independent Poisson process.

For the "multiplicative, same-sign" simulation, we replaced the target match modulation for each
unit with an amount that ensured the population total was distributed proportional to each unit's
total visual modulation (Equation 10), and always reflected as target match enhancement. For
the "uniform, mixed-sign" simulation, we replaced each unit's target match modulation with the
same amount, reflected with the sign determined in the original data.
1134
1135 **Statistical tests:**
1136
When comparing performance between the FLD and maximum likelihood classifier (Fig 5b), we
reported *P* values as an evaluation of the probability that differences were due to chance. We

calculated *P* values as the fraction of resampling iterations on which the difference was flipped
in sign relative to the actual difference between the means of the full data set (for example, if the
mean of decoding measure 1 was larger than the mean of decoding measure 2, the fraction of
iterations in which the mean of measure 2 was larger than the mean of measure 1).
1143
When evaluating whether each unit had a statistically different response to target matches as
compared to distractors (Fig 7a-b, light bars), we recomputed each unit's modulation index by
resampling trials with replacement on n = 1000 resampling iterations. A unit was considered as
statistically significant if its resampled modulation indices were flipped in sign from the unit's
actual modulation index less than 0.01% of the resampling iterations. When evaluating whether
the single unit modulation indices (Fig 7a-b) were significantly different from zero, we reported P
values as computed by a Wilcoxon sign rank test. When evaluating whether the single unit
modulation indices computed without repeated distractors (Fig 7b) were significantly different
from modulation indices computed with repeated distractors, we reported P values computed via
a matched *t* test.
1154
1155   When comparing the representational similarity of different groupings of the IT population
1156   response (Fig 7b), we computed a mean Pearson correlation value for each of the 20 images
1157   (as described above), and reported P values as the probability that the observed differences in
1158   means across the 20 images were due to chance via a two-sample t-test.
1159
1160   **Animal husbandry, enrichment, and care:**
1161
Monkeys received a nutritionally balanced diet of biscuits as well as daily supplements of fruit
and nuts. Monkeys were housed in Allentown cages with space that exceeded the minimums
described in the "Guide for Care and Use of Laboratory Animals". Additionally, monkeys had
periodic access to larger playcages that included a variety of enrichment items, such as swings.
Monkeys were also provided daily enrichment by social housing when possible and through the
introduction of toys, games, and puzzles that involved manipulation to receive food treats. To
maintain task motivation, access to water was regulated prior to experimental sessions.
Monkeys received a minimum 20 mL/kg of water a day five days a week and a minimum of 40
mL/kg on the other two days. When off study, animals were allowed unrestricted access to
water. Animals on regulated access were monitored daily for health status and hydration. Daily
hydration status was assessed by body weight, skin turgor, urine and fecal output, and overall
demeanor. Following this study, both animals were used in one other neurophysiology study.
Following the conclusion of the second study, both animals were euthanized in a manner
consistent with the recommendations of the Panel on Euthanasia of the American Veterinary
Medical Association, including sedation followed by the introduction of the euthanasia solution
Euthasol.
1178
1179
1180   **S1 Dataset**. *IT neural data.* The data include the spike count responses recorded from each
1181   monkey, organized into 5-dimensional matrices as units (monkey 1: n = 108; monkey 2: n = 96)
1182   x targets (n = 4) x objects (n = 4) x transformations (n = 5) x trials (n = 20). Spikes were counted
1183   from 80 to 250 ms, and were extracted from trials with correct responses.
1184
1185

1186
1187

References:

Barak, O., Rigotti, M., and Fusi, S. (2013). The sparseness of mixed selectivity neurons controls the generalization-discrimination trade-off. J Neurosci *33*, 3844-3856.

Bichot, N.P., Rossi, A.F., and Desimone, R. (2005). Parallel and serial neural mechanisms for visual search in macaque area V4. Science *308*, 529-534.

Chelazzi, L., Duncan, J., Miller, E.K., and Desimone, R. (1998). Responses of neurons in inferior temporal cortex during memory-guided visual search. J Neurophysiology *80*, 2918-2940.

Chelazzi, L., Miller, E.K., Duncan, J., and Desimone, R. (1993). A neural basis for visual search in inferior temporal cortex. Nature *363*, 345-347.

Chelazzi, L., Miller, E.K., Duncan, J., and Desimone, R. (2001). Responses of neurons in macaque area V4 during memory-guided visual search. Cereb Cortex *11*, 761-772.

DiCarlo, J.J., Zoccolan, D., and Rust, N.C. (2012). How does the brain solve visual object recognition? Neuron *73*, 415-434.

Engel, T.A., and Wang, X.J. (2011). Same or different? A neural circuit mechanism of similarity-based pattern match decision making. J Neurosci *31*, 6982-6996.

Eskandar, E.N., Richmond, B.J., and Optican, L.M. (1992). Role of inferior temporal neurons in visual memory I. Temporal encoding of information about visual images, recalled images, and behavioral context. Journal of Neurophysiology *68*, 1277-1295.

Freedman, D.J., and Assad, J.A. (2009). Distinct encoding of spatial and nonspatial visual information in parietal cortex. J Neurosci *29*, 5671-5680.

Gibson, J.R., and Maunsell, J.H.R. (1997). The sensory modality specificity of neural activity related to memory in visual cortex. Journal of Neurophysiology *78*, 1263-1275.

Haenny, P.E., Maunsell, J.H., and Schiller, P.H. (1988). State dependent activity in monkey visual cortex. II. Retinal and extraretinal factors in V4. Exp Brain Res *69*, 245-259.

Kobak, D., Brendel, W., Constantinidis, C., Feierstein, C.E., Kepecs, A., Mainen, Z.F., Qi, X.L., Romo, R., Uchida, N., and Machens, C.K. (2016). Demixed principal component analysis of neural population data. Elife *5*.

Kosai, Y., El-Shamayleh, Y., Fyall, A.M., and Pasupathy, A. (2014). The role of visual area V4 in the discrimination of partially occluded shapes. J Neurosci *34*, 8570-8584.

Kriegeskorte, N., and Kievit, R.A. (2013). Representational geometry: integrating cognition, computation, and the brain. Trends Cogn Sci *17*, 401-412.

Leuschow, A., Miller, E.K., and Desimone, R. (1994). Inferior temporal mechanisms for invariant object recognition. Cerebral Cortex *5*, 523-531.

Mante, V., Sussillo, D., Shenoy, K.V., and Newsome, W.T. (2013). Context-dependent
computation by recurrent dynamics in prefrontal cortex. Nature *503*, 78-84.

Maunsell, J.H., Sclar, G., Nealey, T.A., and DePriest, D.D. (1991). Extraretinal representations
in area V4 in the macaque monkey. Vis Neurosci *7*, 561-573.

Meister, M.L., Hennig, J.A., and Huk, A.C. (2013). Signal multiplexing and single-neuron
computations in lateral intraparietal area during decision-making. J Neurosci *33*, 2254-2267.

Miller, E.K., and Desimone, R. (1994). Parallel neuronal mechanisms for short-term memory.
Science *263*, 520-522.

Mruczek, R.E., and Sheinberg, D.L. (2007). Activity of inferior temporal cortical neurons predicts
recognition choice behavior and recognition time during visual search. J Neurosci *27*, 2825-
2836.

Pagan, M., and Rust, N.C. (2014a). Dynamic target match signals in perirhinal cortex can be
explained by instantaneous computations that act on dynamic input from inferotemporal cortex.
J Neurosci *34*, 11067-11084.

Pagan, M., and Rust, N.C. (2014b). Quantifying the signals contained in heterogeneous neural
responses and determining their relationships with task performance. J Neurophysiol *112*, 1584-
1598.

Pagan, M., Simoncelli, E.P., and Rust, N.C. (2016). Neural Quadratic Discriminant Analysis:
Nonlinear Decoding with V1-Like Computation. Neural Comput, 1-29.

Pagan, M., Urban, L.S., Wohl, M.P., and Rust, N.C. (2013). Signals in inferotemporal and
perirhinal cortex suggest an untangling of visual target information. Nature neuroscience *16*,
1132-1139.

Raposo, D., Kaufman, M.T., and Churchland, A.K. (2014). A category-free neural population
supports evolving demands during decision-making. Nature neuroscience *17*, 1784-1792.

Rigotti, M., Barak, O., Warden, M.R., Wang, X.J., Daw, N.D., Miller, E.K., and Fusi, S. (2013).
The importance of mixed selectivity in complex cognitive tasks. Nature *497*, 585-590.

Rishel, C.A., Huang, G., and Freedman, D.J. (2013). Independent category and spatial
encoding in parietal cortex. Neuron *77*, 969-979.

Rust, N.C., and DiCarlo, J.J. (2010). Selectivity and tolerance ("invariance") both increase as
visual information propagates from cortical area V4 to IT. J Neurosci *30*, 12978-12995.

Woloszyn, L., and Sheinberg, D.L. (2009). Neural dynamics in inferior temporal cortex during a
visual working memory task. J Neurosci *29*, 5494-5507.

Zoccolan, D., Kouh, M., Poggio, T., and DiCarlo, J.J. (2007). Trade-off between object
selectivity and tolerance in monkey inferotemporal cortex. J Neurosci *27*, 12292-12307.

1256

Figure 1

a

Cue trial: Squirrel block

800 ms   400 ms

Test trial: 1-7 distractors

400 ms   400 ms   squirrel target match   400 ms

b

Target matches   Distractors

up

left

right

big

small

Object 1   Object 2   Object 3   Object 4

c

Looking FOR

Transformation 1 2 3 4 5

Looking AT 1 2 3 4

d

Monkey 1

Percent Correct

1 2 3 4 5 6 7
Number of distractors shown

Monkey 2

1 2 3 4 5 6 7
Number of distractors shown

e

$\bar{x}$ = 332 ms

Proportion

0.15
0.10
0.05
0

Monkey 1

200 400 600
Time after stimulus onset (ms)

$\bar{x}$ = 364 ms

0.15
0.10
0.05
0

Monkey 2

200 400 600
Time after stimulus onset (ms)

Figure 2

Figure 3

Figure 4

a

Target matches

Distractors

Spike count, neuron 2

Spike count, neuron 1

b

Nonlinear

Linear

Chance

Performance

Number of units

Pooled 204

Monkey 1 108

Monkey 2 96

c

Performance

Chance

Number of best neurons removed

Figure 5

Figure 6

Figure 7

Figure 8

a

Representational similarity matrix

b

Spike counts: 80 - 250 ms.

c

Early: 80-130 ms

Midway: 140-190 ms

Late: 200-250 ms

Figure 9

a **Hypothetical benchmarks**

Multiplicative   Sharpening   Subtractive

Response

Target matches   Target matches   Target matches

Distractors   Distractors   Distractors

Rank   Rank   Rank

b **Data**

Firing rate (spk/s)

Target matches

Distractors

Image rank

c

Hypothetical benchmarks

Target matches - distractors

Multiplicative

Subtractive

Sharpening

Rank

d **Data**

Target matches - distractors (spk/s)

Image rank

Figure 10

Figure 11