1
2
3
4 **Representational dynamics of task context and its influence on visual object**
5 **processing**
6
7

8 Hebart, M. N.[1], Bankson, B. B.[1], Harel, A.[2], Baker, C. I.[1]*, & Cichy, R. M.[3]*
9
10
11 [1]Section on Learning and Plasticity, Laboratory of Brain and Cognition, National Institute of
12 Mental Health, National Institutes of Health, Bethesda, MD 20892, USA.
13
14 [2]Department of Psychology, Wright State University, Dayton, OH 45435, USA.
15
16 [3]Department of Education and Psychology, Free University of Berlin, 14195 Berlin, Germany.
17
18 * these authors contributed equally

19
20 Abbreviated title (50/50 characters): Time course of task and object category processing
21
22

23 Correspondence should be addressed to:
24
Martin N. Hebart
Laboratory of Brain and Cognition
National Institute of Mental Health
Building 10 Room 4C108
10 Center Drive
Bethesda, MD 20814
martin.hebart@nih.gov

32
33
34 Number of pages: 22
35 Number of figures: 5
36 Number of words: Abstract: 226, Significance Statement: 117, Introduction: 524, Discussion:
37 1552
38

39 Conflict of Interest: The authors declare no competing financial interests.
40
Acknowledgements: We would like to thank Maryam Vaziri-Pashkam for helpful discussions
and Matthias Guggenmos and Edward Silson for comments on our manuscript. This work was
supported by the Intramural Research Program of the National Institutes of Health (ZIA-MH-
002909) - National Institute of Mental Health Clinical Study Protocol 93-M-0170,
NCT00001360, the German Research Foundation (Emmy Noether Grant CI241-1/1), and a
Feodor-Lynen fellowship of the Humboldt Foundation to M.N.H.

Abstract

Object recognition is commonly described as a feedforward process, yet the tasks we carry out
often affect what information in visual stimuli is diagnostic and may influence their processing.
Surprisingly little is known about how task context is processed and when and how it interacts
with the emerging representation of objects. Here we used magnetoencephalography (MEG) and
multivariate decoding to investigate the temporal dynamics of task and object processing and
their interaction. Participants viewed objects while we varied task context on a trial-by-trial
basis, using both high-level conceptual and low-level perceptual tasks. Time-resolved
multivariate decoding and temporal cross-classification revealed multiple distinct yet
overlapping stages of task processing from the onset of a trial, likely reflecting a sequence of
visual, semantic, mnemonic, and rule-related task representations. Object decoding was stronger
in conceptual than perceptual tasks, with differences emerging around 530 ms after object onset.
However, object decoding generalized well between task contexts, indicating differently strong
but qualitatively similar brain responses. Using model-based MEG-fMRI fusion, we found that
frontoparietal areas were strongly dominated by information about task context throughout the
trial, while occipitotemporal regions reflected a mixture of both task and object category
indicating their parallel encoding in the same brain area. Together, our results reveal the
temporal evolution of task context representations and suggest that the impact of task context
during object processing occurs late in time.

Significance Statement

While much work in the vision sciences has focused on perceptual processing of visual stimuli,
much less is known about the task context in which these stimuli occur. Here we studied the
neural dynamics of task context and how it influences object processing. Using MEG,
multivariate decoding and MEG-fMRI fusion, we reveal that task context evolves in multiple
distinguishable yet overlapping processing stages, affecting object processing late in time. While
frontoparietal regions were dominated by task, occipitotemporal regions exhibited a mixture of
both task and object information. Our findings highlight the importance of temporal information
in unravelling different stages of task processing and demonstrate the value of model-based
MEG-fMRI fusion for a spatiotemporal analysis of cognitive processes.

Introduction

Our behavioral goals strongly influence how we interpret and categorize the objects around us. For example, the way in which we perceive and react towards a painting can vary quite dramatically when judging its period of art, whether it is hand-painted or a print, or whether it contains an animal or not. Despite the importance of task context in our everyday life, much work on the neural processing of objects has focused on single contexts only (e.g. fixation or discrimination). In part, this reflects the common view of object recognition as a hierarchical feedforward process localized to occipitotemporal cortex (Riesenhuber and Poggio, 2002; Serre et al., 2007; DiCarlo et al., 2012), with independent task-related processing in prefrontal and parietal cortex (Duncan, 2010). However, recent work suggests that task context can impact object representations not only in frontoparietal regions, but also in occipitotemporal visual cortex (Harel et al., 2014; Erez and Duncan, 2015; Bracci et al., 2017). In particular, task context has been reported to affect the strength (Erez and Duncan, 2015; Bracci et al., 2017) and qualitiative nature (Harel et al., 2014) of response patterns in occipitotemporal visual cortex.

While these studies demonstrate *where* in the brain task affects object processing, due to the low temporal resolution of fMRI they leave open the critical questions of (1) *when* the impact of task on object representations emerges and (2) *how* task is represented across time. Answers to these questions allow distinguishing alternative accounts for the mediating effects of task on object processing and in that way provide important insights into the neural mechanisms underlying task and object category. For example, changes in occipitotemporal cortex in response to task context could reflect an expectation-related top-down modulation of feedforward processing (Kok et al., 2012; Kok et al., 2013), potentially affecting the initial responses to visual stimuli. Alternatively, these responses may reflect a late, modulatory influence of task (McKee et al., 2014; see also Emadi and Esteky, 2014).

Here we studied the time course of the processing of task context and the effect of task on object category processing using magnetoencephalography (MEG) and time-resolved multivariate decoding (Carlson et al., 2013; Van de Nieuwenhuijzen et al., 2013; Cichy et al., 2014; Isik et al., 2014; Clarke et al., 2015; Kaiser et al., 2016). We measured the brain responses to object categories in four different task contexts, and used multivariate pattern classification to resolve the temporal dynamics of object category and task context, as well as their interaction. To locate the time-resolved task context and object category dynamics in the brain, we conducted model-based MEG-fMRI fusion (Cichy et al., 2014), using fMRI data from a previous study employing the same task (Harel et al., 2014). We found task context to be represented in a cascade of different processing stages across the time course of the trial. Task context affected the strength of object category representations late in time, however, we found no evidence for qualitatively different processing of objects between task types. MEG-fMRI fusion revealed strong task-related effects in frontoparietal regions, whereas task and category-related effects were mixed in occipitotemporal brain areas, suggesting their parallel processing of task and category.

Materials and Methods

Participants

22 healthy volunteers with normal or corrected-to-normal visual acuity took part in the study.
Five participants were excluded due to at least one of the following exclusion criteria: behavioral
performance below 90 % correct, excessive artifacts, or incomplete or corrupted recordings. Data
from the remaining 17 participants (8 female, mean age 25.12, SD = 5.16) were used in all
analyses throughout the study. All participants gave written informed consent as part of the study
protocol (93-M-0170, NCT00001360) prior to participation in the study. The study was approved
by the Institutional Review Board of the National Institutes of Health and was conducted
according to the Declaration of Helsinki.
132
133 *Experimental Design and Stimuli*
134
The goal of this study was to investigate how task context is represented across time and when
and how task context modulates the processing of visual object categories. For that purpose, we
chose four tasks that could be carried out on a set of object images, two targeting low-level
perceptual dimensions of the images, and two high-level conceptual dimensions (Figure 1A).
The perceptual dimensions were Color (red / blue) and Tilt (clockwise / counterclockwise), and
the conceptual dimensions were Content (manmade / natural) and Size (real world, large / small
relative to an oven). Object images were chosen from 8 different categories (Figure 1B):
Butterfly, cow, dresser, flower, motorbike, skate, tree, and vase. For each of the 8 object
categories, we chose five different image exemplars. To allow participants to perform the Color
and Tilt tasks, each object was presented with a thin red or blue outline, and objects were either
tilted 30 degrees clockwise or counterclockwise relative to the principal axis of the object. The
combination of stimulus types led to 160 unique stimulus combinations (8 categories × 5
exemplars × 2 colors × 2 tilts). Each stimulus was presented once in each task context, making a
total of 640 stimulus presentations per participant. The presentation order of these stimulus-task
combinations was randomized. In addition, we interspersed 80 catch trials that were chosen to be
random combinations of task and stimulus (see below).
All stimuli were presented on black background with a white central fixation cross
present throughout the experiment. Object images were greyscale cropped images of objects and
were a subset selected from a previous fMRI study (Harel et al., 2014). Both task cues (e.g.
'Content') and possible responses (e.g. 'manmade' or 'natural') were shown as words in white
font. Task cues were always presented centrally and possible responses were shown left and right
of fixation.
157
158 *Procedure*
159
Prior to the experiment, participants were familiarized with the task by carrying out 36 randomly
chosen trials outside of the MEG. For the actual experiment, participants were seated in an
electromagnetically shielded MEG chamber with their head placed in the mold of the dewar
while stimuli were backprojected on a translucent screen in front of them (viewing distance: 70
cm, image size: 6 degrees of visual angle). Each trial was preceded by a white fixation cross (0.5
s) that turned green (0.5 s) to prepare participants for the upcoming trial. A trial consisted of
three major components: (1) A task cue which indicated the relevant task for the trial, (2) an
object stimulus which was categorized according to the task, and (3) a response-mapping screen
which indicated the task-relevant response options left and right of fixation (Figure 1C). Based
on these components, in the following we separate each trial into three different time periods: a

"Task Cue Period", an "Object Stimulus Period", and a "Response Mapping Period". Each trial
lasted 5 s. A trial began with the Task Cue Period consisting of the presentation of a task cue (0.5
s) followed by a fixation cross (1.5 s). This was followed by the Object Stimulus Period
consisting of the presentation of an object stimulus (0.5 s) followed by another fixation cross (1.0
s). Finally, the trial ended with the Response Mapping Period during which a response-mapping
screen was displayed (1.5 s). Participants responded with the left or right index finger using an
MEG-compatible response box. In addition to the button press, participants were instructed to
make an eye blink during the response period to minimize the contribution of eye blink artifacts
to other time periods. The order of the options on the response-mapping screen was intermixed
randomly to prevent the planning of motor responses before the onset of the response screen
(Hebart et al., 2012).
Participants were instructed to encode the task rule as soon as being presented with the
task cue and to apply it immediately to the stimulus. To encourage this strategy, they were asked
to respond as fast and accurately as possible. To enforce a faster application of task to object
category, we introduced catch trials for which the fixation period between stimulus offset and
response-mapping screen onset was shortened from 1.0 s to 0.2 s. The experiment consisted of
20 runs of 36 trials each (32 experimental trials, 4 catch trials).
187

188
Figure 1. Experimental paradigm. On each trial (Procedure depicted in Panel **C**), participants were presented with a
stimulus from one of eight different object categories (Panel **B**) embedded in one of four task contexts (Panel **A**, top)
indicated at the beginning of each trial. Participants carried out a task that either targeted low-level features
(perceptual tasks) of the object or its high-level, semantic content (conceptual tasks). After a short delay, a response-
mapping screen was shown that presented the possible response alternatives (Panel **A**, bottom) in random order
either left or right of fixation to decouple motor responses from the correct response.
195

MEG Recordings and Preprocessing

196
197
198　MEG data were collected on a 275 channel CTF system (MEG International Services, Ltd.,
199　Coquitlam, BC, Canada) with a sampling rate of 1,200 Hz. Recordings were available from 272
200　channels (dead channels: MLF25, MRF43, MRO13). Preprocessing and data analysis were

carried out using Brainstorm (version 02/2016, Tadel et al., 2011) and MATLAB (version 2015b, The Mathworks, Natick, MA). The specifics of preprocessing and multivariate decoding (see below) were based on previously published MEG decoding work (Cichy et al., 2014; Grootswagers et al., 2016) and fine-tuned on a pilot subject that did not enter the final data set. MEG triggers were aligned to the exact presentation time on the screen that had been recorded using an optical sensor attached to the projection mirror. Data were epoched in 5.1 s trials, starting 100 ms prior to the onset of the task cue and ending with the offset of the response-mapping screen. Then, data were bandpass filtered between 0.1 and 300 Hz and bandstop filtered at 60 Hz including harmonics to remove line noise.

To further increase SNR and to reduce computational costs, we carried out (1) PCA dimensionality reduction, (2) temporal smoothing on PCA components, and (3) downsampling of the data. For PCA, data were concatenated within each channel across all trials. After PCA, the components with the lowest 1 % of the variance were removed (maximum removal: 50 % of components). All further analyses were conducted on the reduced set of principal components. Then, data were normalized relative to the baseline period (for task decoding: -0.1 to 0 s, for object category decoding: 1.9 to 2.0 s). To this end, for each channel we calculated the mean and standard deviation of the baseline period and subtracted this mean from the rest of the data before dividing it by the standard deviation (univariate noise normalization). Finally, the components were temporally smoothed with a Gaussian kernel of $\pm$ 15 ms half duration at half maximum, and downsampled to 120 Hz (621 samples / trial).

Time-resolved Multivariate Decoding

Multivariate decoding was carried out using custom-written code in MATLAB (Mathworks, Natick, MA), as well as functions from The Decoding Toolbox (Hebart et al., 2015), and LIBSVM (Chang and Lin, 2011) using linear support vector machine classification (C = 1). Classification was conducted for each participant separately in a time-resolved manner, i.e. independently for each time point. Each pattern that entered the classification procedure consisted of the principal component scores at a given time point. In the following we describe one iteration of the multivariate classification procedure that was carried out for the example of object category classification. In the first step, we created supertrials by averaging 10 trials of the same object category without replacement (Isik et al., 2014). In the next step, we separated these supertrials into training and testing data, with one supertrial pattern per object category serving as test data and all other supertrial patterns as training data. This was followed by one-vs-one classification of all 28 pairwise comparisons of the 8 object categories (chance-level 50 %). To test the trained classifier on the left-out data, we compared the two predicted decision values and assigned an accuracy of 100 % if the order of the two test samples was predicted correctly and an accuracy of 0 % if the order was the opposite (for two samples and two classes this is mathematically equivalent to the common area-under-the-curve measure of classification performance and represents a classification metric that is independent of the bias term of the classifier). In a last step, the resulting pairwise comparisons were averaged, leading to an estimate of the mean accuracy across all comparisons. This training and testing process was then repeated for each time point. This completes the description of one multivariate classification iteration for the decoding of object category. The procedure for task classification was analogous, with 4 tasks and 6 pairwise combinations. To achieve a more fine-grained and robust estimate of decoding accuracy, we ran a total of 500 such iterations of trial averaging and

247 classification, and the final accuracy time series reflects the average across these iterations. This
248 provided us with time-resolved estimates of MEG decoding accuracy for object category and
249 task classification, respectively.
250
251 *Temporal Generalization of Task*
252
To investigate whether the nature of task-related information remained stable across time or
whether it changed, we carried out cross-classification across time, also known as the temporal
generalization method (King and Dehaene, 2014). The rationale of this method is that if a
classifier can generalize from one time point to another, this demonstrates that the
representational format is similar for these two time points. If, however, a classifier does not
generalize, then under the assumption of stable noise this indicates that the representational
format is different. To carry out this analysis, we repeated the same approach as described in the
previous section, but instead of testing a classifier only at a given time point, we tested the same
classifier for all other time points separately. This cross-classification analysis was repeated with
each time point once serving as training data, yielding a time–time decoding matrix that captures
classifier generalization performance across time.
264
265 *Model-based MEG-fMRI Fusion for Spatiotemporally-Resolved Information*
266
To resolve task and category-related information both in time and space simultaneously, we
carried out RSA-based MEG-fMRI fusion (Cichy et al., 2014, 2016). RSA allows comparison of
brain patterns across modalities in terms of pattern dissimilarity, abstracting from the activity
patterns of measurement channels (e.g. MEG sensors) to all pairwise distances of those patterns
in form of a representational dissimilarity matrices (RDMs). RSA-based MEG-fMRI fusion
allows a researcher to ask the following question: At what point in time does the representational
structure in a given brain area (as determined from fMRI) match the representational structure
determined from the time-resolved MEG signal? The reasoning for this approach is that if the
fMRI RDM of a brain region and the MEG RDM of a time point show a correspondence, this
suggests that there is a shared representational format in a given brain location and at a given
point in time. Here we apply this approach to investigate the spatiotemporal evolution of object
category and task representations.
FMRI RDMs for each combination of task and category ($4 \times 8 = 32 \times 32$ matrices) were
available from five regions of interest (ROIs) in 25 participants who took part in a separate study
employing the same task (Harel et al., 2014). None of these participants overlapped with the
sample from the MEG study. The major difference between the MEG and the fMRI experiments
were (1) that the fMRI study used an extended set of 6 tasks and (2) the exact timing of each trial
was slower and jittered in the fMRI study. Details about data preprocessing have been described
previously (Harel et al., 2014). RDMs were based on parameter estimates in a GLM for each
condition which were converted to *t*-values (univariate noise normalization). Each entry in the
matrix reflects 1 minus the correlation coefficient of the *t*-values across conditions, calculated
separately for each ROI. RDMs were reduced to the relevant four task types. The five ROIs were
early visual cortex (EVC), object-selective LO and pFS, lateral prefrontal cortex (lPFC) and
posterior parietal cortex (PPC). EVC, LO and pFS were defined based on contrasts in an
independent visual and object localizer session, and lPFC and PPC were defined by a

combination of anatomical criteria and responses in the functional localizer session to the
presence of objects.
For better comparability to this previous study, we created correlation-based MEG
pattern dissimilarity matrices for all combinations of task and object category. In particular, for
each combination of task and category, we created a mean pattern, yielding a total 32 brain
patterns per participant (8 categories × 4 tasks). We then ran a Pearson correlation between all
patterns and converted these similarity estimates to dissimilarity estimates (using 1 minus
correlation), providing us with a 32 × 32 RDM for each time point and participant.
Since different groups of participants were tested in the fMRI and MEG studies, we used
the group average pattern dissimilarity matrices of each modality as the best estimate of the true
pattern dissimilarity. These RDMs were symmetrical around the diagonal, so we extracted the
lower triangular component of each pattern dissimilarity matrix and converted them to vector
format for further analyses, in the following referred to as representational dissimilarity vector
(RDV).
For a given brain region, we conducted MEG-fMRI fusion by calculating the squared
Spearman correlation between the fMRI RDV and the MEG RDV for each time point separately.
The squared correlation coefficient is mathematically equivalent to the coefficient of
determination (R^2) of the fMRI RDV explaining the MEG RDV. This approach was repeated for
each fMRI RDV of the five ROIs, providing us with five time courses of representational
similarity between MEG and fMRI.
While MEG-fMRI fusion provides a temporal profile of representational similarities for a
given brain region, these MEG-fMRI fusion time courses do not distinguish whether MEG-fMRI
representational similarities reflect task, object category, or a mixture of the two. To disentangle
task and object category-related information with MEG-fMRI fusion, we extended this approach
by introducing model RDMs of the same size (32 × 32). These RDMs reflected the expected
dissimilarity for the representation of task and category, respectively, with entries of 1 for high
expected dissimilarity (different task / category) and 0 for low expected dissimilarity (same task /
category). This model-based MEG-fMRI fusion approach was carried out using commonality
analysis (Seibold and McPhee, 1979), a variance decomposition approach that allows estimating
the shared variance between more than two variables (see Greene et al., 2016, for a similar
approach using multiple model RDMs). For a given brain region and time point, these variables
reflect (1) an MEG RDV, (2) an fMRI RDV and (3) the two model RDVs for task and object
category representations.
A schematic of this model-based MEG-fMRI fusion is shown in Figure 5A. We
conducted commonality analysis by comparing two squared semi-partial correlation coefficients
(Spearman correlation), one reflecting the proportion of variance shared between MEG and
fMRI partialling out all model variables excluding the variable of interest (e.g. task) from fMRI,
and the other reflecting the proportion of shared variance when partialling out all model variables
from fMRI including this variable of interest. The difference between both coefficients of
determination (R^2) then provides the commonality, which is the variance shared between MEG
and fMRI that is uniquely explained by the variable of interest. Formally, the commonality at
time t and location j can be described as:
334
335 $$C_{X_t,(Y_j,A)} = R^2{}_{X_t,(Y_j.B)} - R^2{}_{X_t,(Y_j.A,B)}$$
336

where *X* reflects MEG, *Y* reflect fMRI, *A* reflects task, and *B* reflects object category. Note that
this variable can become slightly larger than the total R^2 or slightly negative, due to numerical
inaccuracies or the presence of small suppression effects (Pedhazur, 1997). In addition,
commonality coefficients always reflect the shared variance relative to a target variable (in our
case MEG), but depending on the relationship between the variables the estimate of shared
variance can change when a different target variable is used (in our case fMRI). In the present
study, the pattern of results was comparable irrespective of which variable served as a target
variable.
345
346 *Statistical Testing*
347
Throughout this article, we used a non-parametric, cluster-based statistical approach to
test for time periods during which the group of participants showed a significant effect (Nichols
and Holmes, 2002), and bootstrap sampling to determine confidence intervals for peak latencies
and peak latency differences. We did not compute statistics in time periods after the onset of the
response-mapping screen, because (1) these time periods were corrupted by the instructed eye
blinks and (2) information about task is contained in the response-mapping screen, making it
difficult to uniquely assign these responses to task or response-mapping screen. For object
category-related responses we did not compute statistics for time periods prior to the onset of the
object stimulus, because it was not reasonable to assume that these periods would contain
information about the category before its identity is revealed. For completeness, however, we
plot these results in Figures 2 and 3. Please note that the pattern of results reported is very similar
when including these time periods into our statistical analyses.
360
<u>Non-parametric Cluster-based Statistical Approach</u>
The cluster-based approach consists of two steps: first defining clusters as neighboring
time points that all exceed a statistical cutoff (cluster-inducing threshold), and second
determining significant cluster size.
For the first step – the definition of a cluster-inducing threshold – we ran a sign-
permutation test. The null hypothesis is that any directional effect in the given sample of
participants simply came about by chance. To test whether our sample was part of this null
distribution, for each time series of accuracies we created all possible sign-permutations of
measured accuracy values ($2^{17} = 131,072$), and for each of these permutations generated a *t*-value
for each time point. The permutations provided a null distribution of *t*-values of the group effect
for each time point. The cluster-inducing threshold was defined as the 95th percentile of the
distribution at each time point (equivalent to $p < 0.05$, one-sided).
For the second step – determining significant clusters – we determined the maximum
cluster size in each permutation (Nichols and Holmes, 2002). Using this null distribution, we
determined whether candidate clusters in the original time series exceeded the 95th percentile of
maximum cluster sizes (equivalent to $p < 0.05$, one-sided). This provided us with significant
clusters at the pre-specified statistical cutoffs.
For temporal generalization matrices, we extended the cluster-based approach described
above to two dimensions, revealing significant 2D clusters. Because of computational
limitations, we ran only a subset of 10,000 permutations drawn randomly without replacement
from all available permutations.

382  For model-based MEG-fMRI fusion, we used the two-step approach as described above.
However, instead of running a sign-permutation test across participants, we conducted a
randomization test for which we created 5,000 MEG similarity matrices for each of the five
ROIs. These matrices were based on random permutations of the rows and columns of the group
average MEG similarity matrix (Kriegeskorte et al., 2008). We then carried out model-based
MEG-fMRI fusion using these matrices to create an estimated null distribution of information
time courses for each ROI. For each time point in each ROI, a cluster-inducing threshold was
determined by choosing the 95[th] percentile of this estimated null distribution (equivalent to $p <$
0.05, one-sided). This was followed by determining the maximum cluster sizes across all
permutations as described above, but across all ROIs to correct for multiple comparisons
(equivalent to $p < 0.05$, one-sided, corrected for multiple comparisons across ROIs).
393
394 Determining Confidence Intervals for Peak Latencies
395  We used bootstrap sampling to estimate the 95 % confidence intervals (CI) of peak
latencies and peak latency differences, respectively. For each iteration of the bootstrap sampling
approach, we calculated a time course based on the bootstrap sample. For multivariate decoding
analyses, this was a time course of accuracy from an average of n=17 time courses of decoding
accuracy sampled with replacement from the pool of subjects. For MEG-fMRI fusion, this was a
time course of commonality coefficients, generated by sampling n=17 time courses of MEG
similarity matrices from the pool of subjects with replacement, averaging them, and repeating the
model-based MEG-fMRI fusion approach as described above. For each bootstrap sample time
course, we then calculated timing estimates in the relevant time periods (for peak latency: timing
of maximum, for peak latency difference: time difference between maxima). This process was
repeated (100,000 times for multivariate decoding and 5,000 times for MEG-fMRI fusion),
which generated a distribution of timing estimates. The 2.5 and 97.5 percentiles of this
distribution reflect the 95 % confidence interval of the true timing estimate. Since we
downsampled our data (bin width: 8.33 ms), the confidence intervals were conservative and
overestimated by up to 16.67 ms.
410
411 **Results**
412
413 *Behavioral Results*
414
Participants provided correct responses on average on 97.19 % of trials (*SD*: 2.40) and had a
mean response time of 712.2 ms (*SD*: 121.8), with no significant differences between tasks
(accuracy: $F_{(3,48)} = 0.6938$, RT: $F_{(3,48)} = 0.039$) or between object categories (accuracy:
$F_{(7,112)} = 0.6024$, RT: $F_{(7,112)} = 0.5431$). On average, participants missed responses or
responded too slowly (RT > 1,600 ms) in only 1.80 % of all trials (*SD*: 2.26). We included all
trials in further analyses because (1) imbalances in the number of trials per condition would
complicate multivariate analyses, requiring subsampling which would make the results less
sensitive, and (2) there were no differences in accuracy or RT across tasks or objects, making it
unlikely that the results would be biased by including a very small fraction of missed or incorrect
trials.
425
426 *Time-resolved Representation of Task Context and Object Category*
427

The primary aim of this study was to characterize the temporal evolution of task context
representations in the human brain and elucidating at what time task context affects object
category processing. We thus separately analyzed task and object category-related brain signals
using time-resolved multivariate decoding across the trial (see Figure 1C). This allowed us to
describe and compare the temporal profiles of the two resulting classification time courses, one
for object category averaged across task, and one for task averaged across object category.

In the following, we describe and report results from the "Task Cue Period" (0 to 2,000
ms) from onset of the task cue to onset of the object stimulus, and the "Object Stimulus Period"
(2,000 to 3,500 ms) from onset of the object stimulus to onset of the response screen. We did not
statistically analyze the ensuing "Response-Mapping Period" (3,500 ms to 5,000 ms), because it
was contaminated by instructed blinks and response screen-related processes (see *Materials and*
Methods, Statistical Testing). For completeness, we visualize results from this Response-
Mapping Period in Figures 2 and 3.

Task Cue Period. Task-related information rose rapidly in response to the task cue,
peaking around 100 ms (peak of group mean: 100 ms, 95 % CI: 96-121 ms). This was followed
by a slow decay of information that remained significantly above chance until ~1,200 ms after
cue presentation, outlasting the offset of the word cue by ~700 ms. Around 1,800 ms (~200 ms
prior to onset of the object stimulus) task information was again found to be significantly above
chance. As expected, during this time period – prior to the presentation of the object stimulus –
classification of object category was at chance.

Object Stimulus Period. After onset of the object stimulus at 2,000 ms, object category
information increased sharply, peaking around 100 ms later (peak of group mean: 2,104 ms, 95
% CI: 100-108 ms). This was followed by a gradual decline that remained significantly above
chance until the onset of the response-mapping screen at 3,500 ms. This rapid increase in
category-related information was accompanied by a slow rise of task-related information peaking
around 600 ms after object onset (peak of group mean: 2,638 ms, 95 % CI: 2,517-2,825 ms).
Information about task then remained well above-chance until the presentation of the response-
mapping screen.

Together, these results show that both the presentation of task cue and object stimulus
lead to rapid cortical processing. In addition, they suggest that maintained or reactivated task-
related information that is present before object onset becomes gradually and increasingly
relevant during object category processing.

Figure 2. Time-resolved multivariate decoding of task and object category across the trial. After onset of the task cue (Task Cue Period), task-related accuracy increased rapidly, followed by a decay back towards chance, and was significantly above-chance ~200 ms prior to object onset. In contrast, category-related accuracy was at chance as expected. After onset of the object stimulus (Object Stimulus Period), object category-related accuracy increased rapidly, decaying back to chance with the onset of the response-mapping screen. This was paralleled by a gradual increase in task-related accuracy, peaking ~600 ms after object onset and remaining high until onset of the response-mapping screen. Error bars reflect SEM across participants for each time-point separately. Significance is indicated by colored lines above accuracy plots (non-parametric cluster-correction at $p < 0.05$). Time periods after the onset of the response-mapping screen were excluded from statistical analyses, because they were contaminated by instructed eye-blinks and responses to the response-mapping screen itself, but are shown for completeness (see Methods and Results).

Multiple Stages of Task Processing Revealed by Temporal Generalization Analysis

The decoding of task at different time points as described above characterizes the temporal progression of task-related information across the trial. However, these results alone do not allow distinguishing whether the decoding of task reflects a single or a sequence of multiple cognitive processes across time. There are three pertinent candidates that might explain task decoding at different time periods. For one, early decoding of task after task cue onset may reflect an early visual representation of the task cue that is maintained in short-term memory and accessed when the object stimulus appears in order to carry out the task. Alternatively, the task representation during object processing may reflect an abstract representation of the participant's choice that has been formed after initial visual and semantic processing of the task cue. Finally, the visual information about the task cue may reflect a more abstract representation of task rule that is maintained and applied to the object stimulus representation.

To characterize the processing stages of task, we conducted a temporal generalization analysis using multivariate cross-decoding that reveals the temporal evolution of representational

formats of task (Meyers et al., 2008; King and Dehaene, 2014). To this end, we trained a
classifier at each time point during the trial to distinguish the four different tasks and then tested
it at all other time points, providing us with a time × time temporal generalization matrix. The
shape of the results informs about similarities and differences in the way information is
represented across time. If the results show classification that generalizes to all time points, i.e. if
the entire matrix carries information, this indicates that task information is maintained in a
similar format across the entire trial. If the results show very little generalization across time, i.e.
above-chance accuracies only very close to the diagonal, this indicates that task representation is
highly dynamic across the trial. And if there are several quadratic blocks of cross-classification
around the diagonal, this indicates that task representations change abruptly in different periods
of the trial.
The temporal cross-classification analysis revealed multiple separate, but partially
overlapping stages of processing after the onset of the task cue (Figure 3A). At a coarse level, the
temporal generalization matrix exhibited a block structure within the Task Cue Period and
Object Stimulus Period (*Within-Period Cross-Decoding*, Figure 3B, left panel). This indicates a
shared representational format *within* each time period of the trial, but a largely different
representational format *between* those time periods, and an abrupt change in the representational
format of task after onset of the object stimulus. Since visual and semantic representations of the
task cue are likely to emerge early in the Task Cue Period, this result speaks against a visual or
semantic representation during the Object Stimulus Period. However, this separation was not
complete: some time points exhibited cross-decoding between time periods (*Between-Period*
Cross-Decoding, Figure 3B, middle and right panel), as evidenced by the off-diagonals of the
generalization matrix (i.e. training time 0 to 2,000 ms, testing time 2,000 to 3,500 ms, and vice
versa). This indicates a partially shared representational format between these periods of the trial.
Next we focused on the fine-grained dynamics of task processing in the Task and Object
Cue Period, respectively. During the Task Cue Period (0 to 2,000 ms) the results revealed a
block of increased cross-classification lasting from ~100 to ~600 ms after cue onset. This block
likely reflects the time the task cue was available to visual cortex (accounting for the delay
between stimulus onset and cortical processing). After offset of the task cue at 500 ms and prior
to the onset of the object stimulus at 2,000 ms, information continued to be present and was
found to generalize to other time points in the Task Cue Period. This reinforces the notion that
information about task was actively maintained throughout the Task Cue Period, as suggested by
the time-resolved decoding analysis presented above. This short-term memory representation of
task exhibited temporal generalization to most time points of the Task Cue Period, including the
visual presentation of the task cue, indicating that the short-term representation of task included
visual and semantic properties of the task cue. During the Object Stimulus Period, there was a
gradual build-up of task-related information until ~200 ms after object onset. At that point, the
results exhibited high levels of cross-classification until the onset of the response-mapping
screen, indicating a maintained representation of task context that did not change until the onset
of the response mapping screen.
Significant cross-classification between the Task Cue and Object Stimulus Period was
evident in two distinct phases. First, there was generalization from the Task Cue Period to the
first ~200 ms of the Object Stimulus Period (training time ~300 to 2,000 ms, testing time 2,000
to ~2,200 ms, Figure 3B, middle panel), possibly reflecting a maintained short-term
representation that continued until the task rule could be applied to the object. Second, there was
generalization from the end of the Task Cue Period to the Object Stimulus Period (training time

~1,500 to 2,000 ms, testing time 2,000 ms to ~3,300 ms, Figure 3B, right panel), indicating that
the short-term memory representation of task was similar to the representation during application
of the task rule to the object. Interestingly, this cross-classification was specific to the late short-
term memory representation and did not generalize to other time points of the Task Cue Period.
Note that this cannot be explained by a representation of the correct response, because
participants could not know the correct response during this short-term memory representation
prior to the presentation of the object. Together, this pattern of results suggests that the
representation of task during the Object Stimulus Period likely does not reflect visual or semantic
processing of the task cue (which would predict cross-classification from the early Task Cue
Period); nor does it reflect only a representation of the correct response. Rather, the results
indicate that participants form an abstract representation of task rule during the short-term
retention period prior to object onset, which they apply to the object stimulus when it is
presented.
In summary, the results indicate separate, but overlapping stages of task context
processing. These stages likely reflect a cascade of visual, semantic, and mnemonic processes
including an abstract representation of task rule which during object processing is converted into
an abstract behavioral choice reflected in the participant's response.

553
Figure 3. Results of temporal generalization
analysis of task. **A.** Temporal cross-classification
matrix. The y-axis reflects the classifier training
time relative to task cue onset, the x-axis the
classifier generalization time, and the color codes
the cross-classification accuracy for each
combination of training and generalization time.
The outline reflects significant clusters ($p < 0.05$,
cluster-corrected sign permutation test). Results
after the onset of the response-mapping screen are
not included in the statistical evaluation but are
shown for completeness. (see Results) **B.** Panels
that schematically indicate three patters in the
temporal generalization results. First, there was a
block structure (*Within-Period Cross-Decoding*)
separately spanning the Task Cue Period and the
Object Stimulus Period, indicating largely different
representations during the different periods of the
task (left panel). At the same time, there were two
separate patterns of temporal generalization in the
off-diagonals (*Between-Period I and Between-
Period II Cross-Decoding* illustrated in middle and
right panel, respectively*)*, indicating a shared
representational format between these time periods.

584 *Effects of Task Context on Object Category Representations*
585

The robust decoding of task context that increases during object processing raises the question
whether the task context representation is independent of object processing, or whether task
context influences object category representations. If object category processing is influenced by
task type, one prediction is that object information time courses would be different for different
task types. To investigate this question, we conducted time-resolved multivariate decoding of
objects separately for perceptual and conceptual task types and compared the time courses. The
results of this analysis are presented in Figure 4A. The overall time course of object decoding
was very similar for conceptual and perceptual tasks as compared to that reported for object
decoding across tasks, as expected (see *Time-resolved Representation of Task Context and*
Object Category and Figure 2): accuracies increased sharply after stimulus onset, followed by a
gradual decline, dropping back to chance level towards the end of the Object Period. Comparing
the decoding curves for conceptual and perceptual tasks directly revealed higher accuracies for
conceptual tasks. This result reveals that task context affects object representations late in time.

599
600
Figure 4. Comparison of object category decoding for different task types ($p < 0.05$, cluster-corrected sign
permutation test). Error bars reflect standard error of the difference of the means. **A.** Object category decoding
separated by perceptual and conceptual task types. Initially, category decoding for conceptual and perceptual tasks is
the same, followed by decoding temporarily remaining at a higher level for conceptual tasks than perceptual tasks
between 500 and 750 ms post stimulus onset. **B.** Object category decoding within and across task types. A classifier
was trained on data of different categories from one task type and tested either on category data from the same task
type (within tasks) or on category data from the other task type (between tasks). There was no difference in within
and between-task decoding.

609
In addition to these quantitative differences in object category representations across task
types, we investigated whether the object representations were qualitatively similar but
differently strong (more separable patterns), or whether they were qualitatively different across
task types (different patterns). To this end, we compared object category classification *within*
task to object category classification *between* tasks. The rationale of this approach is that if the
between task cross-classification accuracy is lower than the within task accuracy, this
demonstrates that the classifier cannot rely on the same source of information in these two
conditions, i.e. the patterns must be qualitatively different between tasks. The results of this
analysis are shown in Figure 4B. We did not find any differences in object decoding accuracies

within vs. between task types, indicating that the object category-related patterns were
qualitatively similar across time.
Together, our results reveal that task context affects object representations late in time
and provide further evidence for the notion that task affects the strength of object category
representations.
624
625 *Model-based MEG-fMRI Fusion for Spatiotemporally-Resolved Neural Dynamics of Task and*
626 *Object Category*
627
To investigate the cortical origin of the task and object category-related effects, we carried out
MEG-fMRI fusion based on representational similarity analysis (Cichy et al., 2014, 2016). We
calculated time-resolved MEG representational dissimilarity matrices (RDMs) for all
combinations of task and category and compared them to fMRI RDMs derived from brain
activity patterns from five ROIs of a previously-published study employing the same task (Harel
et al., 2014). Similarity between an fMRI ROI RDM and MEG RDMs indicates a
representational format common to that location and those time points. To separately assess the
contributions of object category and task to the representational similarity between MEG and
fMRI, we decomposed the shared variance between MEG and fMRI RDMs using commonality
analysis (Seibold and McPhee, 1979). This procedure identifies the portion of variance shared
between MEG and fMRI that is unique to either task of category (Figure 5A). The task and
category model RDMs were constructed based on the expected dissimilarity matrix for task
irrespective of category, and for category irrespective of task, respectively.
The results of this model-based MEG-fMRI fusion are shown in Figure 5B-F separately
for each ROI. The grey shaded area indicates the amount of variance captured by MEG-fMRI
fusion. Blue and red lines indicate the amount of variance in the MEG-fMRI fusion uniquely
explained by the task and object category model respectively.
In all ROIs and at most time points either the task or object category models explained
the majority of the shared variance between MEG and fMRI, as indicated by the close proximity
of the colored lines to the upper boundary of the grey shaded area. This result demonstrates that
task and category model RDMs are good models for describing the observed spatio-temporal
neural dynamics.
All regions carried information about task context and object category at some point
throughout the trial, indicating overlapping representations of task and object category
distributed across cortical location and time. However, regions differed in the predominance and
mixture of the represented content. Both PPC and lPFC were clearly dominated by effects of task
context, with much weaker object category-related commonality coefficients present in these
areas. These regions exhibited high task-related commonality coefficients both during the Task
Cue Period and the Object Stimulus Period. Interestingly, PPC exhibited significant task-related
commonality coefficients throughout the short-term retention period that were not found in lPFC,
which may speak towards a different functional role of these regions in the retention of task
rules.
In contrast to frontoparietal regions, occipitotemporal regions EVC, LO and pFS
generally exhibited weaker but significant task-related commonality coefficients than PPC and
lPFC. All three regions displayed significant task-related commonality coefficients in the Task
Cue Period. Interestingly, in the Object Stimulus Period all three regions exhibited a mixture of
task and object-category related commonality coefficients, indicating the concurrent encoding of

task and object category in these brain areas. Moreover, the relative size of task-related commonalities increased gradually from EVC through LO to pFS, indicating an increasing importance of task encoding when progressing up the visual hierarchy. In all five regions, after onset of the object stimulus category-related commonality coefficients peaked earlier than task-related commonality coefficients (all $p < 0.05$, based on bootstrap CI for differences in peaks), mirroring the results of the time-resolved multivariate decoding analysis.

Together, we found that the spatiotemporal neural dynamics as revealed by model-based MEG-fMRI fusion predominantly reflected task or object processing, with systematic differences across cortical regions: While PPC and lPFC were dominated by task and PPC carried task information throughout the Task Cue Period, EVC, LO and pFS exhibited a mixture of task and category-related information during the Object Stimulus Period, with relative increases in the size of task-related effects when moving up the visual cortical hierarchy.

Figure 5. Model-based MEG-fMRI fusion procedure and results. **A.** Model-based MEG-fMRI fusion in the current formulation reflects the shared variance (commonality) between three dissimilarity matrices: (1) an fMRI RDM generated from voxel patterns of a given ROI, (2) a model RDM reflecting the expected dissimilarity structure for a variable of interest (e.g. task) excluding the influence of another variable of interest (e.g. category) and (3) an MEG RDM from MEG data at a given time point. This analysis was conducted for each MEG time point independently, yielding a time course of commonality coefficients for each ROI. **B-F.** Time courses of shared variance and commonality coefficients for five regions of interest (ROIs) derived from model-based MEG-fMRI fusion ($p < 0.05$, cluster-corrected randomization test, corrected for multiple comparisons across ROIs): PPC (Panel **B**), lPFC (Panel **C**), EVC (Panel **D**), LO (Panel **E**) and pFS (Panel **F**). Blue plots reflect the variance attributed uniquely to task, while red plots reflect the variance attributed uniquely to object category. Grey shaded areas reflect the total amount of variance shared between MEG and fMRI RDMs, which additionally represents the upper boundary of the variance that can be explained by task or category models.

Discussion

We used MEG and time-resolved multivariate decoding to unravel the representational dynamics
of task context, object category, and their interaction. Information about task was found rapidly
after onset of the task cue and throughout the experimental trial, which was paralleled by
information about object category after onset of the object stimulus. Temporal cross-decoding
revealed separate and overlapping task context-related processes, suggesting a cascade of
representations including visual and semantic encoding of the task cue, the retention of the task
rule, and its application to the object stimulus. Investigating the interaction of task context and
object category, we found evidence for late effects of task context on object category
representations, with differerences in the strength rather than the quality of category-related
MEG patterns. Finally, model-based MEG-fMRI fusion revealed that parietal and frontal regions
were dominated by effects of task, whereas occipitotemporal regions reflected a mixture of task
and object category representations following object presentation, with relative increases in task-
related effects over time and along the visual cortical hierarchy.

Representational Dynamics of Task Context

While previous fMRI studies investigated the cortical location of task effects on visual object
processing (Harel et al., 2014; Erez and Duncan, 2015; Bracci et al., 2017; Bugatus et al., 2017),
they could not provide insight into the temporal dynamics of task context. By manipulating task
context on a trial-by-trial basis we were able to (1) map out the temporal evolution of task
context effects across different stages of the trial, (2) uncover different stages of processing using
temporal generalization analysis, and (3) localize task context-related information to different
regions of the brain using model-based MEG-fMRI fusion.
The results from multivariate decoding and temporal generalization analyses indicate that
following initial encoding of visual and semantic information about task cue (Task Cue Period),
there was a weak but consistent short-term memory representation of this information, paralleled
by a representation of the task rule. Temporal generalization analysis additionally revealed that
after onset of the object stimulus (Object Stimulus Period) the task representation changed
abruptly. This result is in line with previous work in non-human primates (Sigala et al., 2008;
Stokes et al., 2013) demonstrating largely distinct representations of different task phases in
prefrontal cortex. Since the representation of task after object onset did not generalize to early
time periods during the initial processing of the task cue, this indicates that during object
category processing task context is likely not represented in a purely visual or semantic format.
Instead, our temporal generalization results suggest that at least part of the task-related
information after object onset reflects a representation of task rule that is applied to the visually-
presented object stimulus (Wallis et al., 2001; Stoet and Snyder, 2004; Bode and Haynes, 2009;
Woolgar et al., 2011). This interpretation is in line with a recent working memory study
reporting a reemergence of task rule-related MEG patterns during stimulus presentation (Peters
et al., 2016).
Of note, the representation of task context in monkey prefrontal cortex has been shown to
be even more dynamic than described above and not to generalize at all between different
periods of the task (Stokes et al., 2013). Since our results demonstrate phases of cross-
classification between these time periods, this suggests that in the present study the source of the

cross-classification between these periods of the task may not originate from prefrontal cortex,
but from other brain regions such as posterior parietal cortex. Indeed, this interpretation is
supported by our MEG-fMRI fusion results that show no significant prefrontal representations of
task context during the delay period prior to the onset of the object stimulus, but a representation
of task in posterior parietal cortex.
743
744 *Differential Involvement of Frontoparietal and Occipitotemporal Brain Areas in Task and*
745 *Object Category Representations*
746
Previous research has suggested a dominance of parietal and prefrontal cortex in representing
task context (Duncan, 2010; Woolgar et al., 2011), while the processing of object category has
been attributed to occipitotemporal cortex (Grill-Spector et al., 1999; Kravitz et al., 2010; Cichy
et al., 2011). More recently, this view has been challenged: First, object category representations
have been found – with some dependence on task context – in both parietal (Konen and Kastner,
2008; Jeong and Xu, 2016; Bracci et al., 2017) and prefrontal cortex (Harel et al., 2014; Erez and
Duncan, 2015; Bracci et al., 2017). Second, there is some evidence for task context effects in
occipitotemporal cortex, although the extent of such effects remains debated (Harel et al., 2014;
Erez and Duncan, 2015; Lowe et al., 2016; Bracci et al., 2017; Bugatus et al., 2017), and the time
course of any such effects has remained elusive.
Our model-based MEG-fMRI fusion results provide a nuanced spatiotemporal
characterization of task and object category representations in frontoparietal and
occipitotemporal cortex. Frontoparietal cortex was strongly dominated by task context, with
much weaker representations of object category. This result reinforces the notion that the
dominant role of frontoparietal cortex is the representation of task, with a secondary role in
representing object category. In contrast, in occipitotemporal cortex, responses reflected a
mixture of object category and task-related effects after object onset, with an increasing
dominance of task over time and along the visual cortical hierarchy from low- to high-level
visual cortex (EVC, LO, pFS). These results reveal that both task and object category are
encoded in parallel in the same regions of occipitotemporal cortex and suggests an increasing
role of task context in high-level visual cortex.
The finding of parallel effects of category and task suggests an interaction of task context
and object category already in occipitotemporal cortex. This result contrasts with the view of a
"passive" role of occipitotemporal cortex in the processing of object category, according to
which object representations are read out by prefrontal cortex (Freedman et al., 2003). Instead,
our results suggest that task biases late components of object processing along occipitotemporal
cortex, an influence that may originate in brain regions strongly dominated by task in
frontoparietal cortex (Waskom et al., 2014). In addition, our results suggest that this influence
may increase along the visual cortical hierarchy. Indeed, pFS but not EVC or LO was found to
represent task context immediately prior to object onset, suggesting that task context has the
potential to affect the early stages of visual processing through a top-down bias. This bias may
reflect a task-specific modulation of the representational strength of task-relevant object features
after object onset. The concurrent representation of both task and category in the same brain
region may be beneficial for optimizing the tuning of categorical brain responses to the demands
of the task.
782
Interaction of Task Context and Object Category

The direct investigation of the temporal dynamics of task context and object category
interactions revealed three key findings. First, we found that differences in object category
processing between low-level perceptual and high-level conceptual tasks emerged late in time,
suggesting a late top-down modulation of object processing after initial object processing has
been completed, arguing against an early expectation-related modulation of feedforward
processing. This result is consistent with a previous EEG study using natural images in an animal
and vehicle detection task, finding an initial category-related signal followed by a late task-
related response signaling the presence of a target stimulus (VanRullen and Thorpe, 2001).
Similarly, a more recent MEG study (Ritchie et al., 2015) reported results for visual category
processing in two different tasks (object categorization vs. letter discrimination) that are
indicative of late differences in task-dependent stimulus processing. Overall, these combined
results suggest that task representations affect late, rather than early processing of visual
information.
Second, object category-related information leveled off more slowly for conceptual than
perceptual tasks, indicating different neural dynamics for different task types. This suggests that
for conceptual tasks encoding and maintenance of object category may be beneficial for carrying
out the task, in contrast to perceptual tasks that do not necessitate categorical representations.
While differences in the difficulty of the tasks could account for this pattern of results, we found
no differences in response times or accuracy for the different tasks, arguing against the relevance
of task difficulty. In support of this view, a previous study emploing a speeded version of the
same tasks and categories found no differences in response times between tasks (Harel et al.,
2014).
Finally, while task context affected the separability of object-related MEG patterns
between task types, object classification showed no reduction in classification accuracy between
task contexts, indicating that the overall structure of those patterns did not change. This result
contrasts with our prior study demonstrating qualitatively different object-related patterns in
lateral prefrontal and high-level object-selective cortex (Harel et al., 2014). However, the
contribution of multiple brain regions to the MEG response may be masking an interaction
between object category and task context. Indeed, our MEG-fMRI fusion data suggest that both
task context and object category are being processed in parallel in pFS, although future work
with independent data will be needed to resolve this issue.

Conclusions

Our results suggest that task is represented in multiple distinct yet overlapping processing stages
and that the impact of task context during object processing occurs late in time. Our MEG-fMRI
fusion results support the view of strong task-related responses in frontoparietal regions, while
demonstrating the concurrent processing of both task and object category in occipitotemporal
regions. Our findings provide a nuanced spatiotemporally-resolved view of task processing
throughout the human cerebral cortex.

References

Bode S, Haynes J-D (2009) Decoding sequential stages of task preparation in the human brain.
Neuroimage 45:606-613.
Bracci S, Daniels N, de Beeck HO (2017) Task context overrules object- and category-related
representational content in the human parietal cortex. Cerebral Cortex:1-12.
Bugatus L, Weiner KS, Grill-Spector K (2017) Task alters category representations in prefrontal
but not high-level visual cortex. NeuroImage.
Carlson T, Tovar DA, Alink A, Kriegeskorte N (2013) Representational dynamics of object
vision: The first 1000 ms. Journal of Vision 13:1-19.
Chang C-C, Lin C-J (2011) LIBSVM: a library for support vector machines. ACM Transactions
on Intelligent Systems and Technology (TIST) 2:27.
Cichy RM, Chen Y, Haynes J-D (2011) Encoding the identity and location of objects in human
LOC. Neuroimage 54:2297-2307.
Cichy RM, Pantazis D, Oliva A (2014) Resolving human object recognition in space and time.
Nature Neuroscience 17:455-462.
Cichy RM, Pantazis D, Oliva A (2016) Similarity-based fusion of MEG and fMRI reveals spatio-
temporal dynamics in human cortex during visual object recognition. Cerebral
Cortex:bhw135.
Clarke A, Devereux BJ, Randall B, Tyler LK (2015) Predicting the time course of individual
objects with MEG. Cerebral Cortex 25:3602-3612.
DiCarlo JJ, Zoccolan D, Rust NC (2012) How does the brain solve visual object recognition?
Neuron 73:415-434.
Duncan J (2010) The multiple-demand (MD) system of the primate brain: mental programs for
intelligent behaviour. Trends in Cognitive Sciences 14:172-179.
Emadi N, Esteky H (2014) Behavioral demand modulates object category representation in the
inferior temporal cortex. Journal of Neurophysiology 112:2628-2637.
Erez Y, Duncan J (2015) Discrimination of visual categories based on behavioral relevance in
widespread regions of frontoparietal cortex. Journal of Neuroscience 35:12383-12393.
Freedman DJ, Riesenhuber M, Poggio T, Miller EK (2003) A comparison of primate prefrontal
and inferior temporal cortices during visual categorization. Journal of Neuroscience
23:5235-5246.
Greene MR, Baldassano C, Esteva A, Beck DM, Fei-Fei L (2016) Visual scenes are categorized
by function. Journal of Experimental Psychology: General 145:82-94.
Grill-Spector K, Kushnir T, Edelman S, Avidan G, Itzchak Y, Malach R (1999) Differential
processing of objects under various viewing conditions in the human lateral occipital
complex. Neuron 24:187-203.
Grootswagers T, Wardle SG, Carlson TA (2016) Decoding dynamic brain patterns from evoked
responses: A tutorial on multivariate pattern analysis applied to time series neuroimaging
data. Journal of Cognitive Neuroscience.
Harel A, Kravitz DJ, Baker CI (2014) Task context impacts visual object processing
differentially across the cortex. Proceedings of the National Academy of Sciences
111:E962-E971.
Hebart MN, Donner TH, Haynes J-D (2012) Human visual and parietal cortex encode visual
choices independent of motor plans. Neuroimage 63:1393-1403.
Hebart MN, Görgen K, Haynes J-D (2015) The Decoding Toolbox (TDT): a versatile software
package for multivariate analyses of functional imaging data. Frontiers in
Neuroinformatics 8:88.

Isik L, Meyers EM, Leibo JZ, Poggio T (2014) The dynamics of invariant object recognition in
the human visual system. Journal of Neurophysiology 111:91-102.
Jeong SK, Xu Y (2016) Behaviorally relevant abstract object identity representation in the
human parietal cortex. Journal of Neuroscience 36:1607-1619.
Kaiser D, Azzalini DC, Peelen MV (2016) Shape-independent object category responses
revealed by MEG and fMRI decoding. Journal of Neurophysiology 115:2246-2250.
King J, Dehaene S (2014) Characterizing the dynamics of mental representations: the temporal
generalization method. Trends in Cognitive Sciences 18:203-210.
Kok P, Jehee JF, de Lange FP (2012) Less is more: expectation sharpens representations in the
primary visual cortex. Neuron 75:265-270.
Kok P, Brouwer GJ, van Gerven MA, de Lange FP (2013) Prior expectations bias sensory
representations in visual cortex. Journal of Neuroscience 33:16275-16284.
Konen CS, Kastner S (2008) Two hierarchically organized neural systems for object information
in human visual cortex. Nature Neuroscience 11:224-231.
Kravitz DJ, Kriegeskorte N, Baker CI (2010) High-level visual object representations are
constrained by position. Cerebral Cortex 20:2916-2925.
Kriegeskorte N, Mur M, Bandettini PA (2008) Representational similarity analysis-connecting
the branches of systems neuroscience. Frontiers in Systems Neuroscience 2:4.
Lowe MX, Gallivan JP, Ferber S, Cant JS (2016) Feature diagnosticity and task context shape
activity in human scene-selective cortex. NeuroImage 125:681-692.
McKee JL, Riesenhuber M, Miller EK, Freedman DJ (2014) Task dependence of visual and
category representations in prefrontal and inferior temporal cortices. Journal of
Neuroscience 34:16065-16075.
Meyers EM, Freedman DJ, Kreiman G, Miller EK, Poggio T (2008) Dynamic population coding
of category information in inferior temporal and prefrontal cortex. Journal of
Neurophysiology 100:1407-1419.
Nichols TE, Holmes AP (2002) Nonparametric permutation tests for functional neuroimaging: a
primer with examples. Human Brain Mapping 15:1-25.
Pedhazur EJ (1997) Multiple Regression in Behavioral Research: Explanation and Prediction, 3
Edition. Orlando, FL: Harcourt Brace.
Peters B, Bledowski C, Rieder M, Kaiser J (2016) Recurrence of task set-related MEG signal
patterns during auditory working memory. Brain research 1640:232-242.
Riesenhuber M, Poggio T (2002) Neural mechanisms of object recognition. Current Opinion in
Neurobiology 12:162-168.
Ritchie JB, Tovar DA, Carlson TA (2015) Emerging object representations in the visual system
predict reaction times for categorization. PLoS Comput Biol 11:e1004316.
Seibold DR, McPhee RD (1979) Commonality analysis: A method for decomposing explained
variance in multiple regression analyses. Human Communication Research 5:355-365.
Serre T, Oliva A, Poggio T (2007) A feedforward architecture accounts for rapid categorization.
Proceedings of the National Academy of Sciences 104:6424-6429.
Sigala N, Kusunoki M, Nimmo-Smith I, Gaffan D, Duncan J (2008) Hierarchical coding for
sequential task events in the monkey prefrontal cortex. Proceedings of the National
Academy of Sciences 105:11969-11974.
Stoet G, Snyder LH (2004) Single neurons in posterior parietal cortex of monkeys encode
cognitive set. Neuron 42:1003-1012.

Stokes MG, Kusunoki M, Sigala N, Nili H, Gaffan D, Duncan J (2013) Dynamic coding for
cognitive control in prefrontal cortex. Neuron 78:364-375.
Tadel F, Baillet S, Mosher JC, Pantazis D, Leahy RM (2011) Brainstorm: a user-friendly
application for MEG/EEG analysis. Computational intelligence and neuroscience 2011:8.
Van de Nieuwenhuijzen M, Backus A, Bahramisharif A, Doeller C, Jensen O, van Gerven MA
(2013) MEG-based decoding of the spatiotemporal dynamics of visual category
perception. Neuroimage 83:1063-1073.
VanRullen R, Thorpe SJ (2001) The time course of visual processing: From early perception to
decision-making. Journal of Cognitive Neuroscience 13:454-461.
Wallis JD, Anderson KC, Miller EK (2001) Single neurons in prefrontal cortex encode abstract
rules. Nature 411:953-956.
Waskom ML, Kumaran D, Gordon AM, Rissman J, Wagner AD (2014) Frontoparietal
representations of task context support the flexible control of goal-directed cognition.
Journal of Neuroscience 34:10743-10755.
Woolgar A, Thompson R, Bor D, Duncan J (2011) Multi-voxel coding of stimuli, rules, and
responses in human frontoparietal cortex. Neuroimage 56:744-752.
936