PHYLOSCANNER: Inferring Transmission from Within- and Between-Host Pathogen Genetic Diversity

Chris Wymant*[1,2], Matthew Hall*[1,2], Oliver Ratmann[2], David Bonsall[1,3,4], Tanya Golubchik[1,4], Mariateresa de Cesare[4], Astrid Gall[5], Marion Cornelissen[6], Christophe Fraser[†1,2], STOP-HCV Consortium, The Maela Pneumococcal Collaboration, and The BEEHIVE Collaboration[‡]

[1] Oxford Big Data Institute, Li Ka Shing Centre for Health Information and Discovery, Nuffield Department of Medicine, University of Oxford, UK

[2] Medical Research Council Centre for Outbreak Analysis and Modelling, Department of Infectious Disease Epidemiology, Imperial College London, UK

[3] Peter Medawar Building for Pathogen Research, Nuffield Department of Medicine and the NIHR Oxford BRC, University of Oxford, UK

[4] Wellcome Trust Centre for Human Genetics, Nuffield Department of Medicine, University of Oxford, UK

[5] Department of Veterinary Medicine, University of Cambridge, UK

[6] Laboratory of Experimental Virology, Department of Medical Microbiology, Center for Infection and Immunity Amsterdam (CINIMA), Academic Medical Center of the University of Amsterdam, Amsterdam, The Netherlands

* Equal contribution

[†] To whom correspondence should be addressed: christophe.fraser@bdi.ox.ac.uk

[‡] Collaboration members listed in full at the end of the text.

Abstract

A central feature of pathogen genomics is that different infectious particles (virions, bacterial cells, etc.) within an infected individual may be genetically distinct, with patterns of relatedness amongst infectious particles being the result of both within-host evolution and transmission from one host to the next. Here we present a new software tool, phyloscanner, which analyses pathogen diversity from multiple infected hosts. phyloscanner provides unprecedented resolution into the transmission process, allowing inference of the direction of transmission from sequence data alone. Multiply infected individuals are also identified, as they harbour subpopulations of infectious particles that are not connected by within-host evolution, except where recombinant types emerge. Low-level contamination is flagged and removed. We illustrate phyloscanner on both viral and bacterial pathogens, namely HIV-1 sequenced on Illumina and Roche 454 platforms, HCV sequenced with the Oxford Nanopore MinION platform, and *Streptococcus pneumoniae* with sequences from multiple colonies per individual. phyloscanner is available from https://github.com/BDI-pathogens/phyloscanner.

Introduction

The infectious transmission process imposes a hierarchical structure of relatedness on pathogen genomes. The genotype of an individual infectious particle is the result of both within-host evolution and transmission between hosts; a population sample collected from multiple hosts, with multiple genotypes for each host, therefore simultaneously encodes the history of both processes. Despite the existence of many tools for analysing pathogen genomes, none, to our knowledge, are specifically adapted to exploiting this hierarchical genealogical structure.

A central aim of infectious disease epidemiology is the identification of risk factors for transmission. The development of methods that use pathogen genomes to infer transmission events, along with their direction, is therefore a priority. A critical recent insight is that including multiple pathogen genomes per infected individual in such methods makes this inference easier: it is equivalent to the simpler process of inferring ancestry (Romero-Severson et al. 2016). Specifically, if a pathogen has passed from individual X to individual Y (either directly, or indirectly via unsampled intermediate individuals) then all the pathogen particles sampled from individual Y must be descended from the population of pathogen particles from individual X.

Inferring ancestral states is a standard problem in population genetics for which many methods

exist; the novel insight is that this standard approach may be used to infer the direction of

transmission. We illustrate this in Figure 1.

[**Figure 1: pathogen transmission direction via ancestral state reconstruction**. In the left-

hand phylogeny, tips are labelled red or blue according to their state: in our case the state of

interest is 'in which individual was this pathogen found?'. This state is known for the tips, but

can only be inferred for the internal nodes of the phylogeny: these represent coalescence

events, ancestors of the pathogens we have sampled. A change in state corresponds to a

change in the pathogen's host, i.e. to transmission, be it direct or indirect. The central phylogeny

shows one possible ancestral state reconstruction for which the root of the tree is blue, meaning

blue is ancestral to red. This requires at least four changes of state (shown with black branches)

– four sampled lineages transmitted from blue to red. The right-hand phylogeny shows one

possible ancestral state reconstruction for which the root of the tree is red, meaning red is

ancestral to blue. This requires only one change of state – one sampled lineage transmitted

from red to blue. Based on parsimony we would prefer the right-hand scenario.]

A frequently used approach in molecular epidemiology is to describe patterns of genetic

clustering - who is close to whom. However, identifying transmission pairs or clusters without

the ability to infer transmission direction - who infected whom - limits our ability to distinguish

risk factors for transmission from those for simply acquiring the pathogen. One approach for

inferring direction is to augment the sequence data with epidemiological data, and to couple

phylogenetic inference with mathematical models of transmission, for example references (Volz

and Frost 2013; Jombart et al. 2014; Hall et al. 2015; Didelot et al. 2017). However, this requires

strong assumptions from the model. In addition epidemiological data, such as dates and

location of sampling and reported contacts, are not always available, are subject to their own set

of uncertainties and errors, or are sometimes regarded as too sensitive to link to pathogen
genetic data.

Using multiple genotypes per host, and exploiting the link between transmission and ancestral
reconstruction, therefore promises an alternative and potentially powerful approach to molecular
epidemiology. Whilst several studies have used this idea to great effect on an ad hoc basis
(Numminen et al. 2014; Worby et al. 2016), no systematic or automatic tool has been developed
for this task.

Once multiple genotypes per host are included in a study, other questions present themselves
naturally, for example identifying multiply infected individuals. These may be defined as
individuals harbouring pathogen subpopulations resulting from distinct founder pathogen
particles. Multiple infections may be clinically relevant, for example in the case of Human
Immunodeficiency Virus 1 (HIV-1), dual infection is associated with accelerated disease
progression (Cornelissen et al. 2012). Multiple infections also represent unique opportunities for
pathogen evolution, especially for pathogens that recombine. Recombination between divergent
strains accelerates the generation of novel genotypes, and so potentially novel phenotypes. The
distinct pathogen strains in a multiple infection could have been transmitted simultaneously from
the same individual (if that individual harboured sufficient within-host diversity), or sequentially –
'super-infection' – with each strain perhaps originating from a different transmitter. For HIV-1,
mathematical modelling has suggested that recombinants can reach high prevalence even
when the possibility of super-infection is restricted to a short window after initial infection, and
even when recombinants have no fitness advantage, if the epidemic is fuelled by a high-risk
core group (Gross et al. 2004).

Molecular epidemiology is being transformed by the advent of next-generation sequencing
(NGS; also called *high-throughput*) technologies (Goodwin et al. 2016). For many sequencing
protocols applied to pathogens with extensive within-host diversity, such as HIV-1 and Hepatitis
C Virus (HCV), the NGS output from a single sample can capture extensive within-host
diversity. Zanini et al. (Zanini et al. 2015) inferred phylogenies from NGS *reads* - fragments of
DNA - in windows along the genome for longitudinally sampled individuals infected with HIV-1,
to quantify patterns of within-host evolution over time. Here our focus will be on cross-sectional
datasets: by constructing phylogenies from NGS reads from multiple infected individuals at
once, within-host and between-host evolution can be resolved.

We present phyloscanner: a set of methods implemented as a software package, with two central
aims. The first is efficient computation of phylogenies with multiple genotypes per infected host,
and the second is analysis of such phylogenies and inference of biologically and
epidemiologically relevant properties from a set of related phylogenies. Multiple related
phylogenies arise naturally, either by sampling different portions of a genome, or in representing
uncertainty in phylogenetic inference (though bootstrapping, or sampling phylogenies from a
posterior distribution, for example). phyloscanner automatically performs the following steps:

1. Inference of between and within-host phylogenies from NGS data in multiple windows
along the pathogen genome (optionally skipped, if the user has such phylogenies
already);
2. Identification and removal of likely contaminant sequences;
3. Quantification of within-host diversity;
4. Identification of multiple infections;
5. Identification of crossover recombination breakpoints in NGS genotypes;
6. Ancestral host-state reconstruction from multiple phylogenies;
7. Identification of transmission events from ancestral host-state reconstructions.

phyloscanner was intended for analysis of two distinct types of sequence data. Firstly for deep
sequencing data, in which NGS has produced reads from the population of diverse pathogens
represented in the sample. Secondly, for single-genome amplification (SGA), clonal sequencing
or bacterial colony picks, whereby laboratory methods are employed to separate the genomes
of individual pathogen particles prior to amplification and sequencing. Sequencing with primer
IDs (Jabara et al. 2011) may in some cases produce similar results at reduced costs. We also
considered haplotype reconstruction (Zagordi et al. 2011; Prabhakaran et al. 2014; Töpfer et al.
2014), i.e. bioinformatically inferring different haplotypes represented in the short reads of a
mixed sample, but in our hands this approach did not yield satisfactory results (analysis not
shown).

With SGA-style data, within- and between-host phylogenies can be directly inferred using
standard methods, and therefore phyloscanner is not necessary for step 1 in the process
described above. With deep sequencing data, reads for each sample must first be *mapped*
(placed at the correct location in the genome); thereafter phyloscanner begins by aligning reads

in windows of the genome that are matched across infected individuals, and inferring a
phylogeny for each window (Figure 2).

[**Figure 2: phyloscanner schematic for whole-genome deep sequence data.** In this
schematic, pathogens are sampled from the population infecting three hosts. NGS deep
sequencing produces reads, which are fragments of the genome sequence of one pathogen
particle (after amplification if necessary). Mapping to a reference means aligning each read to
the appropriate location in the genome; this must be done beforehand, as mapped reads are the
inputs to phyloscanner. phyloscanner produces alignments of reads in sliding windows along the
genome, automatically adjusting for the fact that the reference may be different for each sample.
Phylogenies are inferred for each alignment. These phylogenies are analysed separately using
ancestral host-state reconstruction (i.e. assigning hosts to internal nodes), and their information
is combined to give biologically and epidemiologically meaningful summaries. For example
here, we infer that the red individual infected the blue individual directly or indirectly, and the
green individual has two distinct pathogen strains.]

Results

The best way to illustrate phyloscanner is through examples. We chose five datasets illustrating
different uses, pathogens, and sequencing platforms. We describe four in the main text, and
one in the Supplementary Information. These are far from systematic samples or population
surveys; they are small selections of infected individuals chosen to illustrate the different

conclusions that can be drawn using phyloscanner. We leave the application of phyloscanner to
large systematic population samples to future work.

Before presenting phylogenies for these data we introduce the term *host subgraph*. Host
subgraphs result from ancestral host-state reconstruction: they are defined as connected
regions of the phylogeny (tips and internal nodes, with the branches joining them) that have all
been assigned the same host state (i.e., the host that pathogen was in). See supplementary
section SI 1 for an explanation of the ancestral state reconstruction algorithm. Each subgraph
can be shown with a solid block of colour corresponding to that host, uninterrupted by colouring
associated with any other host. Figure 3 shows an example.

[**Figure 3: subgraphs defined by a given ancestral state reconstruction.** Here we show
again the two different ancestral state reconstructions on the same phylogeny from Figure 1,
this time illustrating the *host subgraphs* that these reconstructions define: connected regions of
the phylogeny that have all been assigned the same state (blue host or red host). Note that the
set of tips in a subgraph may or may not form a clade. In both of the above reconstructions, the
blue tips are contained in one subgraph and form a monophyletic group (one clade), whereas
the red tips form a polyphyletic group. The minimum number of clades needed to encompass all
and only the red tips is four, coinciding with the four red subgraphs in the left-hand
reconstruction.**]**

Six illustrative HIV-1 infections, sequenced with Illumina MiSeq

We used phyloscanner to analyse data from the BEEHIVE project (*Bridging the Evolution and*
Epidemiology of HIV in Europe), in which whole-genome samples from individuals with well-

characterised dates of HIV-1 infection are being sequenced, primarily to investigate the viral-

molecular basis of virulence (Fraser et al. 2014). We chose two groups of patients for detailed

investigation (presented in this subsection and the next), that together demonstrate interesting

features revealed by phyloscanner.

For the BEEHIVE samples, viral RNA was extracted manually from blood samples following the

procedure of Cornelissen *et al.* (Cornelissen et al. 2016). The RNA was reverse transcribed and

amplified using universal HIV-1 primers that define four overlapping amplicons spanning the

whole genome, then sequenced using the Illumina MiSeq platform, following the procedure of

Gall *et al.* (Gall et al. 2012; Gall et al. 2014). The resulting reads were mapped to a reference

constructed for each sample using IVA (Hunt et al. 2015) and shiver (Wymant et al. 2016),

producing input analogous to the illustration in Figure 2. See Materials and Methods for more

detail.

These mapped reads were analysed with phyloscanner using 54 overlapping windows, each 320

base pairs (bp) wide, covering the whole HIV-1 genome (approximately 9200 bp long; the

window entirely overlapping the variable V1-V2 loop in the envelope gene was not included due

to the richness of insertions and deletions, which leads to poor alignment). To increase

phylogenetic resolution and accuracy, we used the phyloscanner options to merge overlapping

paired-end reads into single, longer reads, and to delete drug resistance sites (Gatanaga et al.

2002; Johnson et al. 2011; Wensing et al. 2015) which are known to be under convergent

evolution.

Figure 4 shows the resulting phylogenies for four windows, chosen for clarity when visually

inspected. The phylogenies illustrate single infection (patient A), dual infection (patient B),

contamination (from the sample of patient C to the sample of patient D) and transmission (from

patient E to patient F, possibly via an unsampled intermediate individual). Colouring on each

phylogeny illustrates host subgraphs.

Contamination. Filtering for contamination is an important part of analysis of NGS data.

Contamination may be physical contamination of one sample into another, or low-level barcode

switching which occurs during the multiplexing and demultiplexing steps which are central to the

high throughput of NGS. phyloscanner uses two criteria to identify reads as likely contaminants

(either criterion is sufficient). The first is that they are exact duplicates of reads from another

patient, but much less numerous; the second is that they form an additional host subgraph
separated from the primary subgraph, but with too few reads to a call of multiple infection. This
The second means that the source of the contaminant reads need not be present in the
analysed dataset to infer contamination. These reads are flagged according to tuneable
parameters (which will depend on the precise sample and method used), and blacklisted from
further analysis (marked by pink crosses in Figure 4). We note that in general, phylogenetic
patterns associated with transmission are distinct from those associated with contamination: the
process of transmission is accompanied by within-host evolution in the recipient, whereas
contamination is not.
251
252 **Multiple infections.** If the phylogeny and host-state reconstruction are correct, the number of
253 subgraphs a patient has equals the number of founder pathogen particles with sampled
254 descendants (for example if this is 2, a dual infection is inferred). Sampling effects mean that
255 representatives of these multiple infections may not be present in all windows.
256
Transmission. Nodes of the phylogeny not in any patient's subgraph are coloured black in our
figures, as are branches connecting nodes not part of the same subgraph. These black regions
connect the different host subgraphs to each other, and so correspond to the pathogen jumping
between hosts; each region must contain one or more transmission events. They may, or may
not, correspond to the passage of the pathogen lineage through one or more unsampled hosts.
The probability of an indirect transmission will increase with the size of the black region and may
be best investigated by examining the subgraph relationships and branch lengths together.
264
265

[**Figure 4: phyloscanner analysis of four illustrative windows of the HIV-1 genome.** A map of

the HIV-1 genome is shown at the bottom with the nine genes in the three reading frames.

Phylogenies are shown for the four windows highlighted in grey, with scale bars measured in

substitutions per site. Tip labels are coloured by patient, as are all nodes assigned to that

patient by ancestral reconstruction, and the branches connecting these tips and nodes; a solid

block of colour therefore defines a single subgraph for one patient (see main text). The number

labelling each tip is the number of times that read was found in the sample, and the size of the

circle at each tip is proportional to this count. The count is after merging all identical reads and

reads differing by a single base pair (merging similar reads can be done for computational

efficiency, or as here, for presentational clarity). External references included for comparison

are shown with black squares. One is HXB2; the other, labelled R, is a subtype C reference

used to root each phylogeny. The six patients are labelled A through F. **Single infection:**

patient A is a singly infected; all reads from this patient form a single subgraph. **Dual infection:**

patient B is inferred to be dually infected, as is apparent by the fact that ancestral reconstruction

produces two subgraphs in each window. **Contamination:** patients C and D are both singly

infected, but we infer that some contamination has occurred from C to D. Patient D's sample

has a small number of reads that are identical to reads from patient C, but much less numerous.
Such reads are removed, but are shown here as crosses in the clade of patient C, for illustrative
purposes. **Transmission:** in all four windows shown here, the reads of patient F are seen to be
wholly descended from within the subgraph of reads of patient E. We infer that patient E
infected patient F, either directly, or indirectly via an unsampled intermediate. Patient F having a
single subgraph that is linked to patient E by a single branch indicates that the viral population
was bottlenecked down to a single sampled ancestor during transmission.]
290
Genome-wide summary statistics. In general, a phyloscanner analysis may produce a large
number of phylogenies and associated ancestral reconstructions. These can be output both as
annotated NEXUS format files, and as PDF files created with ggtree (Yu et al. 2017) for rapid
visual inspection. Statistics are calculated to summarise the wealth of information in the
phylogenies; these are shown for the 6 patients and 54 genomic windows in Figure 5. They
include measures of within-host diversity, measures that allow rapid identification of multiply
infected individuals, and a basic metric of recombination (defined in the supplementary section
S3).
299

[**Figure 5 - Summary statistics for six illustrative HIV-1 infected patients.** Each column

shows data from a single patient; each row is one or two statistics, plotted along the genome.

Top row: number of reads, and number of unique reads (corresponding to tips in the

phylogeny). **Second row:** the number of clades required to encompass all and only the reads

from that patient, and the number of subgraphs (see Fig. 3 for clarification of these quantities).

In many windows, though not all, the reads of patient B form two subgraphs: evidence of dual

infection. For patients C and E, we see a single subgraph but many clades. This is because of

the presence of reads from other patients (D and F, respectively, as seen in Fig. 4) inside what

would otherwise be a single clade, turning a monophyletic group into polyphyletic group (which

requires splitting in order to form clades). **Third row:** within-host divergence, quantified by mean
root-to-tip distance. Defining a patient's subtree as the tree obtained by removing all tips not
from this patient, we calculate root-to-tip distances both in the whole subtree and in just the
largest subgraph. For patient B, this distinction is substantial due to the very large distance
(~0.1 substitutions/site) between the two subgraphs of this dually infected patient. For singly
infected patients, divergence may correlate with time since infection. **Fourth row:** for each
window, a stacked histogram of the proportion of reads in each subgraph. For patient B, when
two subgraphs are present, an appreciable proportion of reads are in the second one (mean
12%). The histogram is absent in the window that was excluded by choice. **Bottom row:** a
score based on Hamming distance (between 0 and 1) of the extent of recombination in that
window. The highest score across all six patients and all windows is indicated with an orange
diamond; the reads giving rise to this score are shown in supplementary Figure S6.**]**

In a single window, phyloscanner classifies two patients to be related if they are adjacent (see
supplementary section SI) and optionally, also "close", i.e. that their subgraphs are within a
prespecified patristic distance of each other. Relationships are further categorised by the
ancestry, or lack of it, that is suggested by the tree topology. To summarise transmission across
all windows, phyloscanner output summarises the number of windows in which each pair of
patients are related, and the topological nature of that relationship. This allows the complete set
of relationships between all patients in the dataset to be visualised in graph form. For example,
in this dataset, only two of the six patients, E and F, are related in at least half of the windows.
In Figure 6A the counts of the different topological relationships between these two patients are
displayed. With many links between many patients these graphs become difficult to interpret
visually; a threshold on the number of windows for links to be displayed is therefore helpful.
phyloscanner also produces a second version of the graph simplified further, shown in Figure
6B. Here a single link appears if relatedness of any type is present in 50% of windows, and that
link is an arrow if transmission in that direction is inferred in at least 33% of windows. (The 50%
and 33% thresholds are defaults that can be changed.) These relationship diagrams were
plotted using Cytoscape 3.5.1 (Shannon et al. 2003).

Diagrams such as those in Figure 6, when extended to greater numbers patients, will not always
represent a single, coherent transmission tree amongst all the patients in the dataset (as can be
seen in Figures 7 and 9). Instead, they simply summarise each pairwise relationship. As a
result, we refer to them as "relationship graphs". The inference of a single, most probable

transmission tree over all windows is complicated by the presence of multiple infections, incomplete transmission bottlenecks, and missing data for some patients in some windows. To our knowledge, no method yet exists to produce a consensus transmission history that takes into account all these possibilities.

[**Figure 6 – Relationship graphs: visual representations of the relationship between two connected patients infected with HIV-1.** The power of phyloscanner in studying transmission events comes from aggregating information over many within- and between-host phylogenies, in this case obtained from different windows of the whole HIV-1 genome. In the top diagram, the outcomes from all 54 windows are shown. The top blue arrow shows that in 41 windows, patient E was inferred to be ancestral to patient F, with a single bottleneck. The bottom blue arrow shows that in 2 windows the reverse was true – F was ancestral to E. The undirected red line shows that in 2 windows, the patients were linked by "complex" ancestry, with the direction unclear. The undirected green line shows that in 9 windows the patient subgraphs were adjacent and close, but no ancestry was implied by the topology. In no window was transmission of more than one lineage inferred, and in no window were the patients distant and unlinked. (See supplementary section SI 1 for more details on these categories.) A simplification of these relational data is shown in the bottom diagram, with a single directed arrow. The first number indicates the proportion of windows supporting transmission in the direction of the arrow, and the second number indicates the proportion of windows supporting transmission in either direction.]

Resolving the transmission pathway within a HIV-1 phylogenetic cluster

To illustrate the resolution into the transmission process that can be obtained by phyloscanner,
we chose a set of 7 patients from the BEEHIVE study that were found to be closely connected
in the chain of transmission (Fig. 7). 3 of the patients' samples were sequenced with Illumina
MiSeq and 4 with Illumina HiSeq; the resulting reads were processed and mapped using IVA
and shiver as previously, with the mapped reads given as input to phyloscanner. phyloscanner
summarises all the pairwise relationships between individuals in each window (Figure 7A),
suggesting a complex network. However, we find that when we focus on the most likely
inferences of source attribution (Figure 7B), phyloscanner largely resolves a complex set of
pairwise relationships into a coherent transmission network, that is consistent with the years of
seroconversion. However, this is not guaranteed to be the case: an exception is the triangle
connecting Patients J, L and M, where there is too much uncertainty in the relationships
amongst the triplet to resolve their ancestry.

[**Figure 7 - The relationship between 7 patients infected with HIV-1.** The colouring and

numbers on the arrows connecting patients are as in Figure 6; in addition, the lower diagram

here contains undirected green lines as well directed blue lines. These green lines suggest that

the pair are close in the transmission network but with unknown transmission direction; the

single number on the line indicates the proportion of windows supporting this. The known or

estimated year of infection is shown in parentheses after each patient's label.]

HIV-1 sequenced with Roche 454

392 A subset of patients from the BEEHIVE study were also sequenced using the Roche 454

393 platform; results from their analysis with phyloscanner are in Supplementary Information section

394 SI 2.

HCV sequenced with Oxford Nanopore MinION

To further illustrate phyloscanner's applicability to different sequencing platforms and also different pathogens, we used it to analyse HCV viral data sequenced using the Oxford Nanopore MinION device. Plasma samples were obtained from four patients in the BOSON study (Foster et al. 2015), a phase 3 randomized trial of antiviral therapy with sofosbuvir (trial registration NCT01962441). Sequencing was performed using RNAseq-based methods previously described for Illumina (Bonsall et al. 2015) and adapted for the MinION device. Briefly, plasma-derived RNA was reverse transcribed, then sequencing libraries were prepared for each sample using Oxford Nanopore adapters and customised barcoded primers. These were pooled and enriched using HCV-specific nucleotide baits before sequencing on a MinION R9.0 flow cell. Viral sequences were identified and mapped using BLASTN (Altschul et al. 1990), standard reference sequences and BWA (Li and Durbin 2009). See Materials and Methods for more details. The resulting BAM files were used as input for phyloscanner, with a window size of 600 bp and no overlap between windows. Nanopore sequencing platforms are capable of producing longer inserts than those of Illumina, at the cost of a higher error rate (approximately 10% erroneous base calls). Despite this error, phyloscanner could phylogenetically resolve the within- and between-host evolution, shown in Figure 8.

[Figure 8 - ᴘʜʏʟᴏsᴄᴀɴɴᴇʀ analysis of two illustrative windows of the HCV genome.
Sequence data from four individuals was obtained with the Oxford Nanopore MinION device. A
continuous region of the phylogeny with the same colour shows a subgraph for one patient (see
main text). Black tips were flagged as contamination and excluded. Patient-derived sequences
clustered with respective genotype 2 and genotype 3 references (G2R, G3R) as expected from
the virus genotypes known from the clinical information available for participants. Two windows,
600 bp in length, are shown for the E2 and NS4B genes at positions given by the genome map
(bottom panel).]

Multiple colony picks per carrier of *S. pneumoniae*

ᴘʜʏʟᴏsᴄᴀɴɴᴇʀ's analysis of phylogenies need not be restricted to those derived from deep
sequencing data in different windows of the genome: it can also be applied to datasets where
within-host diversity is captured by SGA or sequences from multiple colony picks per individual.
We illustrate this approach with the *S. pneumoniae* data of Croucher et al. (Croucher et al.
2016), specifically the BC1-19F cluster. This dataset consists of 286 sequences from 92

individuals carrying the bacterium (with multiple colonies per carrier). These were sequenced

with Illumina HiSeq, though for SGA data sequencing platform is largely irrelevant to

interpretation, since each sequenced sample should not contain any real within-sample diversity

by design. Genomes were processed with Gubbins (Croucher et al. 2015) to remove

substitutions likely to have been introduced by recombination. As each of these sequences is a

whole genome (unlike the short reads produced by NGS), we did not split the genome into

windows to be analysed separately. Instead, we represented phylogenetic uncertainty by

generating a posterior set of 100 phylogenies using MrBayes 3.2.6 (Ronquist et al. 2012) and

analysed these with phyloscanner. Ancestral state reconstruction was performed on each

posterior phylogeny independently, relationships between carriers identified, and the results

summarised over the entire set. In each phylogeny, carriers were inferred as being related if the

minimum patristic distance between two nodes from the subgraphs associated with each was

less than 7 substitutions and they were categorised as adjacent (explained in Supplementary

Information section SI 1.5). This distance threshold was selected to demonstrate the method as

it picked out obvious clades in the phylogeny as groups, and was not chosen to imply direct

transmission. Retaining such relationships where they existed in at least 50% of posterior

phylogenies revealed 18 separate groups of carriers whose bacterial strains were closely

related (see Fig. 9).

10 substitutions

[Figure 9 - Phylogeny and relationships between *S. pneumoniae* carriers. The phylogeny

shown is the MrBayes consensus tree. Tip shapes are coloured by carrier, with mother and

infant pairs sharing the same colour; diamonds represent infants and circles mothers. All nodes

assigned to a carrier by ancestral reconstruction, and the branches connecting these tips and

nodes, are given the same colour as that carrier's tips; a solid block of colour therefore defines a

single subgraph for one carrier (see main text). Regions of the phylogeny not in any carrier's

subgraph are grey. These regions connect carriers' subgraphs to each other, and so each must

contain one or more transmission events. The carrier relationship diagram (inset) displays the

relationships between the carriers in 18 identified groups, in the same fashion as in Figures 6

and 7, except that here the numbers represent the proportion of phylogenies from the posterior

set, rather than the proportion of genomic windows in which both patients have sequence data.

The clades representing these 18 groups are labelled in the phylogeny.]

Note that if some residual signals of recombination remain after processing with Gubbins,

analysing the full-length genomes in windows by choice (rather than by necessity, as with short-

read NGS data) could mitigate this effect at the cost of reduced phylogenetic resolution in each

window. The merits of this could be explored in a dedicated analysis of such a dataset; here we

simply illustrate application of phyloscanner to full-length sequences as opposed to genomic

windows.

Discussion

Improving our understanding of the transmission of pathogens is valuable for identifying

epidemiological risk factors – the first step for targeting public health interventions for efficient

impact. Phylogenetic analysis of one pathogen sequence per infected individual may identify

clusters of similar sequences that are expected to be close in a transmission network. However,

nothing is learned about the direction of transmission within the network. Indeed it may be that

none of the individuals transmitted the pathogen to anyone else, and they were all infected by a

common individual who was not sampled. Through automatic fitting of maximum-likelihood

evolutionary models to within- and between-host genetic sequence data, phyloscanner enhances

resolution into the pathogen transmission process. An evidence base is built up by analysing

many phylogenies, notably through consideration of NGS reads in windows along the

pathogen's genome. The relationship between infected individuals is no longer quantified by a

single number summarising closeness, but by a rich set of data resulting from ancestral host-

state reconstruction for each phylogeny.

Romero-Severson *et al.* (Romero-Severson et al. 2016) demonstrated the utility of parsimony

for the assignment of ancestral hosts to internal nodes in a phylogeny containing many tips from

two infected individuals, for simulated HIV-1 data. We have continued with this approach,

developing it for suitability for real sequence data from many infected individuals. In particular

we allow for (i) contamination, (ii) multiple infections, and (iii) the possible presence of

unsampled hosts in the tree. Details of two such parsimony algorithms, available for use in

phyloscanner, are presented in the supplementary section SI 1. Parsimony has the advantage
that a reconstruction can be completed in reasonable computational time even for phylogenies
with tens of thousands of tips. Other methods of reconstructing the host state of internal nodes
could also be suitable and may be added to the package in future. Our identification of
contamination and multiple infections is highly valuable in its own right: the former because this
is critical for any empirical study of within-host diversity, and the latter because such individuals
may be special cases clinically and for pathogen evolution. Transmission of multiple distinct
pathogen strains may occur simultaneously, or sequentially – 'super-infection'. phyloscanner can
detect both cases, though distinguishing them is difficult without longitudinal sampling (it could
be possible through inference of timed trees, or using the diversity of each separate infection as
a proxy for its age).

Great care must be taken to correctly interpret the ancestry of pathogens infecting individuals.
Even if ancestry were established beyond any doubt, individual X's pathogen being ancestral to
individual Y's pathogen does not imply that X infected Y: the pathogen could have passed
through unsampled intermediate hosts. Nevertheless the ancestry does provide valuable
epidemiological information, as X has been identified as a transmitter (and Y a recipient not far
down the same transmission chain). Finding likely transmitters in a large population cohort
would allow risk factors to be identified and quantified.

Furthermore, inference of ancestry is itself subject to uncertainty. The inference of ancestry
depends on the correct rooting of the phylogeny, in order that the direction in which evolution
proceeded over time is known. Molecular clock analyses (such as implemented in TempEst
(Rambaut et al. 2016)) can aid correct rooting when the sampling dates of the tips of the
phylogeny are known.

The relationships between infected individuals are inferred by phyloscanner across many
phylogenies, for example those constructed from NGS reads in windows along the pathogen
genome. By analysing many phylogenies, phyloscanner mitigates the effect of random error - any
error that is independent in each phylogeny. We therefore give greater credibility to those
relationships observed many times than to those observed only once. However, systematic
error may arise, for example, due to different patients being sampled at different stages of
infection, with different amounts of within-host diversity to analyse (Romero-Severson et al.
2016). Given uncertainties in any individual assignment, we recommend phyloscanner for

population-level analyses, rather than focussing on isolated transmission events (as we have
done here, for simplicity in explaining the method).

The fraction of genomic windows in which a given relationship is inferred between individuals
(for example A infecting B directly or indirectly), is not equal to the probability of that relationship
being true. However it provides a measure of the robustness with which the available data
support that conclusion. This is analogous to bootstrapping – sampling with replacement from
the same sequence alignment, to create a set of similar phylogenies. Here however, different
windows of the genome make use of different sequence data. Given the potential for
disagreement between different windows due to genuine biological variation, imperfect
sequencing procedures etc., agreement between a fraction x of (non-overlapping) windows is a
stronger statement of robustness than agreement between a fraction x of bootstraps.
Identification of transmission events with phyloscanner will involve false positives and false
negatives; these will be context dependent, depending on how strictly transmission thresholds
are defined (which balance sensitivity and specificity) and on the inclusion of sequences similar
to those being investigated. We will illustrate this in two works in preparation examining large
population studies.

Whilst our emphasis has been on extracting broad-brush information from the rich within-and-
between host phylogenies, these phylogenies contain more information that could be used in
future research. A specific example is that by resolving the transmission event at a finer level of
genetic detail, it is possible to identify which pathogen genotypes are typically transmitted and
which ones are not, with potential relevance for vaccine design.

By providing a tool for automatic phylogenetic analysis of NGS deep sequencing data, or
multiple genotypes per host generated by other means, we aim to simplify identification of
transmission, multiple infection, recombination and contamination across pathogen genomics.

Materials and Methods

Generation and assembly of the BEEHIVE Illumina data

Viral RNA was extracted manually from blood samples following the procedure of Cornelissen *et*
al. (Cornelissen et al. 2016). RNA was amplified and sequenced according to the protocol of

Gall *et al.* (Gall et al. 2012; Gall et al. 2014). Briefly, universal HIV-1 primers define four

amplicons spanning the whole genome. 5 µl of amplicon I was pooled with 10 µl each of

amplicons II–IV. Libraries were prepared from 50 to 1000 ng DNA as described in Quail et al.

(Quail et al. 2008; Quail et al.), using one of 192 multiplex adaptors for each sample. Paired-end

sequencing was performed using an Illumina MiSeq instrument with read lengths of length 250

or 300 bp, or in the 'rapid run mode' on both lanes of a HiSeq 2500 instrument with a read

length of 250 bp.

For each sample, the reads were assembled into contigs using the *de novo* assembler IVA. The

reads and contigs were processed using shiver as described previously (Wymant et al. 2016). In

summary: non-HIV contigs were removed based on a BLASTN search against a set of standard

whole-genome references (Kuiken et al. 2012)**.** Remaining contigs were corrected for assembly

error then aligned to the standard reference set using MAFFT (Katoh et al. 2002). A tailored

reference for mapping was then constructed for each sample using the contigs, with gaps

between contigs filled by the corresponding part of the closest standard reference. The reads

were trimmed for adapters, PCR primers and low-quality bases using Trimmomatic (Bolger et al.

2014) and fastaq (https://github.com/sanger-pathogens/Fastaq). Contaminant reads were

removed based on a BLASTN search against the non-HIV contigs and the tailored reference.

The remaining reads were then mapped to the tailored reference using SMALT

(http://www.sanger.ac.uk/science/tools/smalt-0).

Generation and assembly of the HCV Oxford Nanopore MinION data

Viral RNA was extracted from plasma using the NucliSENS® easyMAG® total nucleic acid

extraction system (Biomerieux) and sequencing libraries were prepared using a modified

version of an RNA-seq based protocol with a virus enrichment step. Briefly, the NEBNext®

Ultra™ Directional RNA Library Kit (New England Biolabs, Ipswich, MA, USA) was used to

generate cDNA from 5ul of total RNA. The NEBNext® Ultra™ II End Repair/dA-Tailing Module

and Blunt/TA Ligase (New England Biolabs, Ipswich, MA, USA) were used for end repair of

dsDNA and ligation of PCR adapters (Oxford Nanopore Technologies) to allow for 18 cycles of

PCR using custom barcoded primers with a post-PCR clean-up with 1x Ampure XP (Beckman

Coulter, Pasadena, CA, USA). Each library was quantified by Quant-iT™ Qubit® dsDNA HS

Assay Kit and size distribution analysed using Agilent Tapestation High Sensitivity D5000

ScreenTape System. Approximately equimolar quantities of each library were pooled to a total

of 500 ng mass and processed for probe enrichment using customized xGen® Lockdown®

120mer probes specific to HCV (Integrated DNA Technologies, Inc., Coralville, Iowa, USA) and

a modified Roche NimbleGen protocol for hybridization of amplified sample libraries with a

shorter 4 hours hybridization time and on-bead post-enrichment PCR (12 cycles). The enriched

pool was prepared for sequencing on a MinION R9.0 flow cell using the SQK-NSK007 2d

ligation kit. Raw fasta5 sequence files were base called and demultiplexed using Metrichor

software. Viral sequences were identified and trimmed using a BLASTN search of the Los

Alamos database of HCV genotype references (Kuiken et al. 2005), then mapped to the closest

matching reference using BWA (with the command bwa mem –x ont2d). Consensus sequences

were called from the bam files and used as references for a second iteration of read mapping.

The phyloscanner Method

For application of phyloscanner to deep sequence NGS data, the required input is a set of files in

BAM format (Li et al. 2009) each containing the reads from one sample that have been mapped

to a reference, and a choice of genomic windows to examine. A sensible choice of windows

would normally tile the whole genome, perhaps skipping regions that are rich in insertions and

deletions (leading to poor sequence alignment). Windows should be wide enough to capture

appreciable within-host diversity, but short enough for some reads to fully span them; options in

the code help to inform the user's choice. There is no lower limit to the length of reads given as

input, however as read length decreases, phylogenetic resolution will suffer. phyloscanner

determines the correspondence between windows in different BAM files by aligning the mapping

references in the BAM files. Using the same reference for mapping all samples would negate

the need for this step, but it is of paramount importance to tailor the reference to each sample

before mapping to minimise biased loss of information (Wymant et al. 2016). For each window

in each BAM file, all reads (or inserts, if reads are paired and overlapping) fully spanning the

window are extracted using pysam (https://github.com/pysam-developers/pysam) and trimmed

to the window edges, then identical reads are collapsed to a single read, giving a set of unique

reads each with an associated count (i.e. the number of reads with identical sequence). A basic

metric of recombination is calculated by maximising, over all possible sets of three sequences

and all possible recombination crossover points, the extent to which one of the three sequences

resembles one of the other two sequences more closely on the left and resembles the other

sequence more closely on the right. Further detail is provided in the supplementary section SI 3.

In each window, each sample's set of unique reads is checked against every other sample's set,

with exact matches flagged to warn of between-sample contamination in the analysed dataset;
all unique reads are then aligned with MAFFT, and a phylogeny is inferred with RAxML
(Stamatakis 2014).

phyloscanner contains many options to customise processing and maximise the information
extracted from reads and phylogenies. Standard reference genomes can be included with the
reads for comparison. User-specified sites can be excised to mitigate the effect of known sites
under selection on phylogenetic inference. Greater faith can be placed in the reads by trimming
low-quality ends and wholly discarding reads that are low-quality, improperly paired, or rare.
Reads in the same sample that differ from each other by less than a specified threshold can be
merged into a single read to increase the speed of downstream processing. Overlapping paired
reads can be merged into a single longer read for greater phylogenetic resolution. Every option
of RAxML can be passed as an option to phyloscanner, for example specifying the evolutionary
model to be fitted, or multithreading.

Optionally, the user may skip inference of phylogenies from files of mapped reads, and instead
directly provide as input a phylogeny or a set of phylogenies generated by any other method.

To analyse phylogenies, phyloscanner required that they are rooted. This can be done manually,
or if the phylogenies were constructed by phyloscanner from mapped reads, rooting can be
achieved by providing one or more additional reference sequences with the mapped reads, and
choosing one of these to use as an outgroup. The outgroup should be sufficiently distant from
all sampled isolates that we can assume the most recent common ancestor of it and every
isolate (i.e. the root of the whole tree) was not present in any of the sampled individuals.

Each phylogeny analysed is annotated with a reconstruction of the transition process using a
modified maximum-parsimony approach to assign internal nodes to hosts or to an extra
"unassigned" state. The latter is given to lineages that either must have infected a host outside
the dataset, or to those where the situation is sufficiently ambiguous that this cannot be ruled
out. An important parameter of the reconstruction, designated k, is used to help identify dual
infections and contaminants. It acts as a penalty, in the parsimony algorithm, for the
reconstruction of single infections showing unrealistic within-host diversity. A suitable value of k
will depend on the pathogen under study, but as a rule of thumb, we suggest estimating a level
of pairwise genetic diversity that it would be unrealistic to see in an infection from a single

source, and using the reciprocal of this for *k*. In situations where the phyloscanner user is
confident that dual infections and contaminants are not present, *k* can be set to zero, in which
case no penalty for within-host diversity is applied.

The results of the reconstruction can be represented as a visualisation of the partial pathogen
transmission tree by the process of 'collapsing' each subgraph (i.e. each set of adjacent nodes
with the same reconstructed host; see supplementary Fig. S3) into a single node of a new tree
structure. This "collapsed tree" is then analysed to identify relationships between each pair of
infected individuals, according to the following categories:

1. Minimum distance: what is the smallest patristic distance between a phylogeny node
assigned to one host and a node assigned to the other?
2. Adjacency: is there a path on the phylogeny that connects the two individuals' subgraphs
without passing through a third individual? ("Unassigned" nodes do not interrupt
adjacency.)
3. Topology: how are the regions from each individual arranged with respect to each other?
(See supplementary Fig. S4.)

Combinations of these properties can be used to develop criteria which identify individuals who
are closely linked in the transmission chain. For example, two individuals that are adjacent and
within a suitable distance threshold are likely to be either a transmission pair, or infected via a
small number of unsampled intermediaries. If the distance between subgraphs is large, on the
other hand, separation by unsampled hosts in the chain of transmission is likely even if they are
adjacent. The nature of the topological relationship between them may suggest a direction of
transmission, or be equivocal.

An individual having multiple subgraphs suggests multiple infection, with the ancestor node of
each subgraph inferred to be a distinct founder pathogen particle (the ancestor of that sampled
subpopulation). It can be difficult to distinguish a dual infection from a sample that has been
contaminated by another sample not present in the current data set (i.e. where contamination is
not visible as exact duplication of another individual's read). For NGS data we make the
distinction in each phylogeny based on thresholds on read counts: outside of the subgraph
containing the greatest number of reads, any additional ('minor') subgraph is designated as
contamination and ignored if the number of reads it contains is below an absolute threshold, or

below a threshold relative to the read count in the largest subgraph. By default, minor
subgraphs with read counts exceeding both thresholds are kept, providing evidence for the
presence of multiple distinct subpopulations in that genomic window. (Alternatively, a
phyloscanner option allows all minor subgraphs to be entirely removed from consideration).
Zanini et al. (Zanini et al. 2015) discarded reads suspected of being contamination by
calculating each read's Hamming distance from the consensus, plotting the distribution of these
distances, and discarding reads giving rise either to a second peak or to a 'fat tail' (taken to be
recombinant reads). This approach is not appropriate when the data set may contain multiply
infected individuals, for example for a dual infection we wish to keep the reads from each of two
distinct groups that may be separated by a large distance.
709
710 **The phyloscanner Code**
711
phyloscanner is freely available at https://github.com/BDI-pathogens/phyloscanner. It is written in
Python and R, but can be run from the command line so that no knowledge of either language is
required. Inference of within- and between-host phylogenies from BAM-format mapped reads is
achieved with a single command of the form
phyloscanner_make_trees.py ListOfBamsAndRefs.csv --windows 1,300,301,600,...
where ListOfBamsAndRefs.csv lists the BAM files to be analysed and the fasta-format references
to which the reads were mapped, and the --windows flag above specifies analysis of the
genomic windows with coordinates 1-300, 301-600, ...
Analysis of those trees is achieved with a single command of the form
phyloscanner_analyse_trees.R TreeFiles OutputLabel [choice of ancestral state reconstruction].
722
Included with the code is simple simulated HIV-1 data for ease of immediate exploration of
phyloscanner. Within-host evolution was simulated using SeqGen (Rambaut and Grassly 1997);
each resulting sequence was then converted into error-free fragments that were mapped back
to the founding sequence, giving BAM-format files suitable as input for phyloscanner. We also
created BAM-format files by using shiver to process publicly available HIV-1 reads sequenced
with Illumina MiSeq. A tutorial walking the user through a simple application of phyloscanner to
the simulated data, and a more sophisticated application to this real public data, is available
from the GitHub repository with the code itself.
731

Running phyloscanner on the six HIV-1 samples presented in the first results section took 18
minutes on one core of a standard laptop, 10 minutes of which was running RAxML. A number
of options allow the user to speed up phyloscanner. Firstly it is 'embarrasingly' parallelisable, in
that each window of the genome can be processed separately (e.g. the 54 windows used for the
HIV data could have been processed via 54 jobs run in parallel). Secondly all options of RAxML
can be passed as options to phyloscanner, including multithreading. Thirdly the number of
unique sequences kept for phylogenetic inference can be controlled through various options,
notably merging of similar reads and/or a minimum read count. Fourthly the user can easily use
a different tool for phylogenetic inference instead of RAxML by using the --no-trees option of
phyloscanner_make_trees.py, and running the desired tool on the fasta file of processed reads that
is output for each window. (As an example running FastTree(Price et al. 2009) on the same data
took 28 seconds instead of the 10 minutes needed by RAxML.)
744

Acknowledgments

We thank Katrina Lythgoe for helpful discussions, and Céline Christiansen-Jucht for comments
on the manuscript. This work was funded by ERC Advanced Grant PBDR-339251. We
acknowledge funding from Bill & Melinda Gates Foundation through PANGEA-HIV. The STOP-
HCV Consortium is funded by a grant from the Medical Research Council (MR/K01532X/1). We
thank Gilead Sciences for providing HCV plasma samples from the BOSON clinical study for
use in these analyses. We also thank HCV Research UK (funded by the Medical Research
Foundation) for their assistance in handling and coordinating the release of samples for these
analyses. This work used the computing resources of the UK MEDical BIOinformatics
partnership - aggregation, integration, visualisation and analysis of large, complex data (UK
MED-BIO) which is supported by the Medical Research Council [grant number MR/L01632X/1].

The BEEHIVE Collaboration

Jan Albert, Margreet Bakker, Norbert Bannert, Ben Berkhout, Daniela Bezemer, François
Blanquart, Marion Cornelissen, Jacques Fellay, Katrien Fransen, Christophe Fraser, Astrid Gall,
Annabelle Gourlay, M. Kate Grabowski, Barbara Gunsenheimer-Bartmeyer, Huldrych F.
Günthard, Matthew Hall, Mariska Hillebregt, Paul Kellam, Pia Kivelä, Roger Kouyos, Oliver

Laeyendecker, Kirsi Liitsola, Laurence Meyer, Swee Hoe Ong, Kholoud Porter, Peter Reiss,
Matti Ristola, Ard van Sighem, and Chris Wymant.
766
767 Acknowledged contributors to the cohorts in the BEEHIVE Collaboration are listed in
768 supplementary section SI 4.
769

The STOP-HCV Consortium
Eleanor Barnes, Jonathan Ball, Diana Brainard, Gary Burgess, Graham Cooke, John Dillon,
Graham R Foster, Charles Gore, Neil Guha, Rachel Halford, Cham Herath, Chris Holmes, Anita
Howe, Emma Hudson, William Irving, Salim Khakoo, Paul Klenerman, Diana Koletzki, Natasha
Martin, Benedetta Massetto, Tamyo Mbisa, John McHutchison, Jane McKeating, John
McLauchlan, Alec Miners, Andrea Murray, Peter Shaw, Peter Simmonds, Chris C A Spencer,
Paul Targett-Adams, Emma Thomson, Peter Vickerman, and Nicole Zitzmann.
777

778 **The Maela Pneumococcal Collaboration**
779 Stephen D. Bentley, Claire Chewapreecha, Nicholas J. Croucher, Simon Harris, Jukka
780 Corander, David Goldblatt, Julian Parkhill, Francois Nosten, Claudia Turner, and Paul Turner.
781

782 **Competing Interests**
783
- AJG participated in an advisory board meeting for ViiV Healthcare in July 2016.
784
- KP is a member of the Viiv 'Dolutegravir' Advisory Board and Viiv 'Data and Insights:
785   Standardisation in Measuring and Collecting Care Continuum Data' Advisory Board.
786
- HG reports receipt of grants from the Swiss National Science Foundation, Swiss HIV
787   Cohort Study, University of Zurich, Yvonne Jacob Foundation, and Gilead Sciences; fees
788   for data and safety monitoring board membership from Merck; consulting/advisory
789   board membership fees from Gilead Sciences; and travel reimbursement from Gilead,
790   Bristol-Myers Squibb, and Janssen.
791
- PR through his institution has received independent scientific grant support from Gilead
792   Sciences, Janssen Pharmaceuticals Inc, Merck & Co, Bristol-Myers Squibb, and ViiV
793   Healthcare; he has served on scientific advisory boards for Gilead Sciences and ViiV

794   Healthcare and on a data safety monitoring committee for Janssen Pharmaceuticals Inc,

795   for which his institution has received remuneration.

References

800 Altschul SF, Gish W, Miller W, Myers EW, Lipman DJ. 1990. Basic local alignment search tool.
801   Journal of Molecular Biology 215:403–410.

802 Bolger AM, Lohse M, Usadel B. 2014. Trimmomatic: a flexible trimmer for Illumina sequence
803   data. Bioinformatics 30:2114–2120.

804 Bonsall D, Ansari MA, Ip C, Trebes A, Brown A, Klenerman P, Buck D, null N, Piazza P, Barnes
805   E, et al. 2015. ve-SEQ: Robust, unbiased enrichment for streamlined detection and whole-
806   genome sequencing of HCV and other highly diverse pathogens [version 1; referees: 2
807   approved, 1 approved with reservations]. F1000Research 4.

808 Cornelissen M, Gall A, Vink M, Zorgdrager F, Binter Š, Edwards S, Jurriaans S, Bakker M, Ong
809   SH, Gras L, et al. 2016. From clinical sample to complete genome: Comparing methods for
810   the extraction of HIV-1 RNA for high-throughput deep sequencing. Virus Research.

811 Cornelissen M, Pasternak AO, Grijsen ML, Zorgdrager F, Bakker M, Blom P, Prins JM,
812   Jurriaans S, van der Kuyl AC. 2012. HIV-1 Dual Infection Is Associated With Faster CD4+
813   T-Cell Decline in a Cohort of Men With Primary HIV Infection. Clinical Infectious Diseases
814   54:539.

815 Croucher NJ, Mostowy R, Wymant C, Turner P, Bentley SD, Fraser C. 2016. Horizontal DNA
816   Transfer Mechanisms of Bacteria as Weapons of Intragenomic Conflict. PLOS Biology
817   14:1–42.

818 Croucher NJ, Page AJ, Connor TR, Delaney AJ, Keane JA, Bentley SD, Parkhill J, Harris SR.
819   2015. Rapid phylogenetic analysis of large samples of recombinant bacterial whole genome
820   sequences using Gubbins. Nucleic Acids Research 43:e15.

821 Didelot X, Fraser C, Gardy J, Colijn C. 2017. Genomic Infectious Disease Epidemiology in
822   Partially Sampled and Ongoing Outbreaks. Molecular Biology and Evolution 34:997.

823 Foster GR, Pianko S, Brown A, Forton D, Nahass RG, George J, Barnes E, Brainard DM,
824   Massetto B, Lin M, et al. 2015. Efficacy of Sofosbuvir Plus Ribavirin With or Without
825   Peginterferon-Alfa in Patients With Hepatitis C Virus Genotype 3 Infection and Treatment-
826   Experienced Patients With Cirrhosis and Hepatitis C Virus Genotype 2 Infection.
827   Gastroenterology 149:1462–1470.

828 Fraser C, Lythgoe K, Leventhal GE, Shirreff G, Hollingsworth TD, Alizon S, Bonhoeffer S. 2014.
829   Virulence and Pathogenesis of HIV-1 Infection: An Evolutionary Perspective. Science 343.

830 Gall A, Ferns B, Morris C, Watson S, Cotten M, Robinson M, Berry N, Pillay D, Kellam P. 2012.

Universal Amplification, Next-Generation Sequencing, and Assembly of HIV-1 Genomes.
Journal of Clinical Microbiology 50:3838–3844.

Gall A, Morris C, Kellam P, Berry N. 2014. Complete Genome Sequence of the WHO
International Standard for HIV-1 RNA Determined by Deep Sequencing. Genome
Announcements 2.

Gatanaga H, Suzuki Y, Tsang H, Yoshimura K, Kavlick MF, Nagashima K, Gorelick RJ, Mardy
S, Tang C, Summers MF, et al. 2002. Amino Acid Substitutions in Gag Protein at Non-
cleavage Sites Are Indispensable for the Development of a High Multitude of HIV-1
Resistance against Protease Inhibitors. Journal of Biological Chemistry 277:5952–5961.

Goodwin S, McPherson JD, McCombie WR. 2016. Coming of age: ten years of next-generation
sequencing technologies. Nat Rev Genet 17:333–351.

Gross KL, Porco TC, Grant RM. 2004. HIV-1 superinfection and viral diversity. AIDS 18.

Hall M, Woolhouse M, Rambaut A. 2015. Epidemic Reconstruction in a Phylogenetics
Framework: Transmission Trees as Partitions of the Node Set.Salathé M, editor. PLoS
Comput Biol 11:e1004613.

Hunt M, Gall A, Ong SH, Brener J, Ferns B, Goulder P, Nastouli E, Keane JA, Kellam P, Otto
TD. 2015. IVA: accurate de novo assembly of RNA virus genomes. Bioinformatics.

Jabara CB, Jones CD, Roach J, Anderson JA, Swanstrom R. 2011. Accurate sampling and
deep sequencing of the HIV-1 protease gene using a Primer ID. Proceedings of the
National Academy of Sciences 108:20166–20171.

Johnson VA, Calvez V, Günthard HF, Paredes R, Pillay D, Shafer R, Wensing AM, Richman
DD. 2011. 2011 update of the drug resistance mutations in HIV-1. Top Antivir Med 19:156–
164.

Jombart T, Cori A, Didelot X, Cauchemez S, Fraser C, Ferguson N. 2014. Bayesian
Reconstruction of Disease Outbreaks by Combining Epidemiologic and Genomic
Data.Tanaka MM, editor. PLoS Comput Biol 10:e1003457.

Katoh K, Misawa K, Kuma KI, Miyata T. 2002. MAFFT: a novel method for rapid multiple
sequence alignment based on fast Fourier transform. Nucleic Acids Research 30:3059–
3066.

Kuiken C, Foley B, Leitner T, Apetrei C, Hahn B, Mizrachi I, Mullins J, Rambaut A, Wolinsky S,
Korber B. 2012. HIV Sequence Compendium 2012. Los Alamos National Laboratory,
Theoretical Biology and Biophysics, Los Alamos, New Mexico. LA-UR-12-24653.

Kuiken C, Yusim K, Boykin L, Richardson R. 2005. The Los Alamos hepatitis C sequence
database. Bioinformatics 21:379–384.

Li H, Durbin R. 2009. Fast and accurate short read alignment with Burrows–Wheeler transform.
Bioinformatics 25:1754.

Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, Marth G, Abecasis G, Durbin R,

Subgroup 1GPDP. 2009. The Sequence Alignment/Map (SAM) Format and SAMtools.
Bioinformatics.

Numminen E, Chewapreecha C, Siren J, Turner C, Turner P, Bentley SD, Corander J. 2014.
Two-phase importance sampling for inference about transmission trees. Proceedings of the
Royal Society B: Biological Sciences 281:20141324–20141324.

Prabhakaran S, Rey M, Zagordi O, Beerenwinkel N, Roth V. 2014. HIV Haplotype Inference
Using a Propagating Dirichlet Process Mixture Model. IEEE/ACM Transactions on
Computational Biology and Bioinformatics 11:182–191.

Price MN, Dehal PS, Arkin AP. 2009. FastTree: Computing Large Minimum Evolution Trees with
Profiles instead of a Distance Matrix. Molecular Biology and Evolution 26:1641–1650.

Quail MA, Kozarewa I, Smith F, Scally A, Stephens PJ, Durbin R, Swerdlow H, Turner DJ. 2008.
A large genome center's improvements to the Illumina sequencing system. Nat Meth
5:1005–1010.

Quail MA, Otto TD, Gu Y, Harris SR, Skelly TF, McQuillan JA, Swerdlow HP, Oyola SO. Optimal
enzymes for amplifying sequencing libraries. Nat Meth 9:10–11.

Rambaut A, Grassly NC. 1997. Seq-Gen: an application for the Monte Carlo simulation of DNA
sequence evolution along phylogenetic trees. Bioinformatics 13:235.

Rambaut A, Lam TT, Max Carvalho L, Pybus OG. 2016. Exploring the temporal structure of
heterochronous sequences using TempEst (formerly Path-O-Gen). Virus Evolution
2:vew007.

Romero-Severson EO, Bulla I, Leitner T. 2016. Phylogenetically resolving epidemiologic
linkage. Proceedings of the National Academy of Sciences 113:2690–2695.

Ronquist F, Teslenko M, van der Mark P, Ayres DL, Darling A, Höhna S, Larget B, Liu L,
Suchard MA, Huelsenbeck JP. 2012. MrBayes 3.2: Efficient Bayesian Phylogenetic
Inference and Model Choice Across a Large Model Space. Systematic Biology 61:539.

Shannon P, Markiel A, Ozier O, Baliga NS, Wang JT, Ramage D, Amin N, Schwikowski B,
Ideker T. 2003. Cytoscape: A Software Environment for Integrated Models of Biomolecular
Interaction Networks. Genome Research 13:2498–2504.

Stamatakis A. 2014. RAxML version 8: a tool for phylogenetic analysis and post-analysis of
large phylogenies. Bioinformatics 30:1312.

Töpfer A, Marschall T, Bull RA, Luciani F, Schönhuth A, Beerenwinkel N. 2014. Viral
Quasispecies Assembly via Maximal Clique Enumeration. PLoS Comput Biol 10:1–10.

Volz EM, Frost SDW. 2013. Inferring the Source of Transmission with Phylogenetic
Data.Kosakovsky Pond SL, editor. PLoS Comput Biol 9:e1003397.

Wensing AM, Calvez V, Günthard HF, Johnson VA, Paredes R, Pillay D, Shafer RW, Richman
DD. 2015. 2015 Update of the Drug Resistance Mutations in HIV-1. Top Antivir Med
23:132–141.

Worby CJ, O'Neill PD, Kypraios T, Robotham JV, De Angelis D, Cartwright EJP, Peacock SJ,
Cooper BS. 2016. Reconstructing transmission trees for communicable diseases using
densely sampled genetic data. Ann. Appl. Stat.:395–417.

Wymant C, Blanquart F, Gall A, Bakker M, Bezemer D, Croucher NJ, Golubchik T, Hall M,
Hillebregt M, Ong SH, et al. 2016. Easy and Accurate Reconstruction of Whole HIV
Genomes from Short-Read Sequence Data.

Yu G, Smith DK, Zhu H, Guan Y, Lam TT-Y. 2017. ggtree: an r package for visualization and
annotation of phylogenetic trees with their covariates and other associated data. Methods in
Ecology and Evolution 8:28–36.

Zagordi O, Bhattacharya A, Eriksson N, Beerenwinkel N. 2011. ShoRAH: estimating the genetic
diversity of a mixed sample from next-generation sequencing data. BMC Bioinformatics
12:119.

Zanini F, Brodin J, Thebo L, Lanz C, Bratt G, Albert J, Neher RA. 2015. Population genomics of
intrapatient HIV-1 evolution.Chakraborty AK, editor. eLife 4:e11282.