Title: Domain-General and Domain-Specific Patterns of Activity Supporting Metacognition in Human Prefrontal Cortex

Abbreviated title: Domain-Specific Metacognition in Prefrontal Cortex

Authors: Jorge Morales[1*], Hakwan Lau[2,3,4], Stephen M. Fleming[5,6]

Affiliations:

[1] Department of Philosophy, Columbia University, New York, NY, USA
[2] Department of Psychology, UCLA, Los Angeles, CA, USA
[3] Brain Research Institute, UCLA
[4] Department of Psychology, University of Hong Kong, Hong Kong
[5] Wellcome Centre for Human Neuroimaging, University College London, London, UK
[6] Max Planck UCL Centre for Computational Psychiatry and Ageing Research, University College London, London, UK

[*] Corresponding author: Jorge Morales (jorge.morales@columbia.edu)

Acknowledgements: We thank Aurelio Cortese for his help with the MVPA analyses. This work was partially supported by the National Institute of Neurological Disorders and Stroke of the National Institutes of Health (Grant No. R01NS088628) to H.L. and S.M.F., by the Templeton Foundation (Grant No. 21569) to H.L., and by a Sir Henry Wellcome Fellowship to S.M.F. (Grant No. WT096185). The Wellcome Centre for Human Neuroimaging is supported by core funding from the Wellcome Trust (Grant No. 203147/Z/16/Z).

ABSTRACT: Metacognition is the capacity to evaluate the success of one's own cognitive

processes in various domains, e.g. memory and perception. It remains controversial whether

metacognition relies on a domain-general resource that is applied to different tasks, or whether

self-evaluative processes are domain-specific. Here we directly investigated this issue by

examining the neural substrates engaged when metacognitive judgments were made by human

participants during perceptual and memory tasks matched for stimulus and performance

characteristics. By comparing patterns of functional magnetic resonance imaging (fMRI) activity

while subjects evaluated their performance, we revealed both domain-specific and domain-

general metacognitive representations. Multi-voxel activity patterns in anterior prefrontal cortex

predicted levels of confidence in a domain-specific fashion, whereas domain-general signals

predicting confidence and accuracy were found in a widespread network in the frontal and

posterior midline. The demonstration of domain-specific metacognitive representations suggests

the presence of a content-rich mechanism available to introspection and cognitive control.

SIGNIFICANCE STATEMENT: We use human neuroimaging to investigate processes supporting

memory and perceptual metacognition. It remains controversial whether metacognition relies on

a global resource that is applied to different tasks, or whether self-evaluative processes are

specific to particular tasks. Using multivariate decoding methods, we provide evidence that

perceptual- and memory-specific metacognitive representations cortex co-exist with generic

confidence signals. Our findings reconcile previously conflicting results on the domain-

specificity/generality of metacognition, and lay the groundwork for a mechanistic understanding

of metacognitive judgments.

Metacognition is the capacity to evaluate the success of one's cognitive processes in various

domains, e.g. perception or memory (Flavell, 1979; Nelson and Narens, 1990; Metcalfe and

Shimamura, 1994; Fleming et al., 2012a). Metacognitive ability can be assessed in the laboratory

by quantifying the trial-by-trial correspondence between objective performance and subjective

confidence (Galvin et al., 2003; Maniscalco and Lau, 2012; Overgaard and Sandberg, 2012;

Fleming and Lau, 2014). Anatomical (Fleming et al., 2010; McCurdy et al., 2013; Maniscalco et

al., 2017), functional (Fleck et al., 2006; Yokoyama et al., 2010; Fleming et al., 2012b; Baird et

al., 2013; Hilgenstock et al., 2014) and neuropsychological (Shimamura and Squire, 1986;

Schnyer et al., 2004; Fleming et al., 2014) evidence indicates specific neural substrates

(especially in frontolateral, frontomedial, and parietal regions) contribute to metacognition across

a range of task domains, including perception and memory. However, the neurocognitive

architecture supporting metacognition remains controversial. Does metacognition rely on a

common, domain-general resource that is recruited to evaluate performance on a variety of

tasks? Or is metacognition supported by domain-specific components?

Current computational perspectives (Pouget et al., 2016; Fleming and Daw, 2017)

suggest both domain-general and domain-specific representations may be important for guiding

behavior. On the one hand, one needs to be able to compare confidence estimates in a "common

currency" across a range of arbitrary decision scenarios (de Gardelle and Mamassian, 2014). One

solution to this problem is to maintain a global resource with access to arbitrary sensorimotor

mappings (Holroyd et al., 2005; Heekeren et al., 2006; Cole et al., 2013). Candidate neural

substrates for a domain-general resource are the frontoparietal and cingulo-opercular networks,

known to be involved in arbitrary control operations (Cole et al., 2013). In particular, the

dorsomedial prefrontal cortex (encompassing the paracingulate cortex and pre-supplementary

motor area) has been implicated in representing confidence, monitoring conflict, and detecting

errors across a range of tasks (Gehring et al., 1993; Botvinick et al., 2004; Ridderinkhof et al.,

2004; Fleming et al., 2012b). On the other hand, if the system only had access to generic

confidence signals, appropriate switching between particular tasks or strategies on the basis of

their expected success would be compromised. Functional imaging evidence implicates human

anterior prefrontal cortex in tracking the reliability of specific alternative strategies during

decision-making (Donoso et al., 2014), and such regions may also support domain-specific

representations of confidence.

Current behavioral evidence of a shared resource for metacognition is ambiguous, in part

due to the difficulty of distilling metacognitive processes from those supporting primary task

performance (Galvin et al., 2003; Maniscalco and Lau, 2012; Fleming and Lau, 2014). Some

studies have found that efficient metacognition in one task predicts good metacognition in

another (McCurdy et al., 2013; Ais et al., 2016; Faivre et al., 2017; Ruby et al., 2017; Samaha

and Postle, 2017), whereas others indicate the independence of metacognitive abilities (Kelemen

et al., 2000; Baird et al., 2013; Vo et al., 2014). Recent studies employing bias-free measures of

metacognition have identified differences in the neural correlates of memory and perceptual

metacognition in both healthy subjects (Baird et al., 2013; McCurdy et al., 2013) and

neuropsychological patients (Fleming et al., 2014). However, the study of behavioral individual

differences provides only indirect evidence of the neural and computational architecture

supporting metacognition.

Here, we directly investigate this ontology by examining neural substrates engaged when

metacognitive judgments are made during perceptual and memory tasks matched for stimulus

and performance characteristics. We employ a combination of univariate and multivariate

analyses of functional magnetic resonance imaging (fMRI) data to identify domain-specific and

domain-general neural substrates engaged during metacognitive judgments. We also distinguish

activations engaged by a metacognitive judgment from neural activity which tracks confidence

level. Together, our findings reveal the co-existence of generic and specific confidence

representations, consistent with a computational hierarchy underpinning effective metacognition.

MATERIALS AND METHODS

Participants

Thirty healthy subjects (ages 18-33, mean 24.97 years old; SD=4.44; 14 males) with normal or

corrected-to-normal vision were monetarily compensated and gave written informed consent to

participate in the study at the Center for Neural Science at New York University. The study

protocols were approved by the local Institutional Review Board. The number of participants

was determined a priori at n=30, which is in line with recent guidelines on neuroimaging sample

sizes (Poldrack et al., 2017). Due to behavioral and in-scanner motion cut-off criteria, six

subjects were excluded from further analysis (details below). We present the results of twenty-

four subjects whose data were fully analyzed.

Experimental and Task Design

The experiment had a 2×2×2 design: CONDITION (CONFIDENCE/FOLLOW) × TASK DOMAIN

(PERCEPTION/MEMORY) × STIMULUS TYPE (SHAPES/WORDS). It consisted of six scanner runs, each

with eight 9-trial mini-blocks (72 trials per run, 432 trials in total). Perceptual and memory two-

alternative forced-choice (2-AFC) tasks were presented in separate, interleaved runs (three runs

per task; order counterbalanced across subjects). In each run, there were four pairs of mini-

blocks from the Confidence and Follow conditions. To avoid stimulus confounds, two different

types of stimulus were used throughout the experiment. In each run, two pairs of

Confidence/Follow mini-blocks used words and the remaining two pairs used abstract shapes

(interleaved and order counterbalanced across runs).

In the perceptual task, subjects were asked to report the brighter of two stimuli on each

trial. In the memory task, subjects began each mini-block by learning a set of nine consecutively-

presented stimuli. A stimulus from this set was then presented on each subsequent trial (in

randomized order) alongside a new stimulus. Subjects' task was to identify the studied stimulus.

In mini-blocks from the Confidence condition, subjects had to rate their confidence in their

performance in each trial by selecting a number from a 1-to-4 scale. In mini-blocks from the

Follow condition, subjects had to "follow the computer" in each trial by pressing the button

corresponding to the highlighted number irrespective of their confidence. The highlighted

number was yoked to their ratings in the previous Confidence mini-block (randomized

presentation order) to ensure similar low-level visuomotor characteristics in both conditions for

any given pair of mini-blocks.

Subjects were reminded at the beginning of each mini-block of the condition, task, and

stimulus type that would follow. They used two fingers of their right hand to respond on an MRI-

compatible button box: left stimulus (index) and right stimulus (middle). For confidence ratings,

they used four fingers: 1 (index), 2 (middle), 3 (ring) and 4 (little). If subjects failed to provide

either type of response within the allotted time (see Figure 1A for details), the trial was missed

and an exclamation mark was displayed for the remainder of the trial. Failing to press the

highlighted number counted as a missed trial.

Prior to entering the scanner, participants were familiarized with the tasks and the

confidence rating scale. After computing independent brightness thresholding for words and

abstract shapes, subjects practiced one of each mini-block type (i.e. 8 mini-blocks). Instructions

emphasized that confidence ratings should reflect relative confidence and participants were

encouraged to use all ratings. The whole experiment lasted ~1.5 hours.

Stimuli

The experiment was programmed in MATLAB (MathWorks) and stimuli were presented using

Psychtoolbox (Brainard, 1997). Abstract, 22- or 28-line shapes were randomly created by

specifying an (invisible) grid of 6×6 squares that subtended 4 degrees of visual angle where lines

could connect two vertices horizontally, vertically, or diagonally. The first line always stemmed

from the central vertex of the invisible grid randomly connecting one of the surrounding eight

vertices to ensure shape centrality within the grid. The remaining lines were drawn sequentially,

ensuring all lines were connected. Orientation and originating vertices were selected randomly.

All words were nouns of 6 to 12 letters with 1 to 4 syllables obtained from the Medical

Research Council Psycholinguistic Database (Wilson, 1988). In the perceptual task, words had

high familiarity, concreteness, and imageability ratings (400-700). In the memory task, words

had low ratings (100-400) to increase task difficulty. Each word and each shape was presented

once throughout the experiment (across perceptual and memory blocks, including practice trials).

All subjects were tested on the same words and shapes (counterbalanced across Confidence and

Follow conditions across subjects). Words and rating scales were presented using DS-Digital

font (40 points) to make their visual features similar to the abstract shapes.

To obtain stimulus sets of similar difficulty for shapes and words we ran a series of pilot

studies where participants rated abstract shapes' distinctiveness and then performed the memory

task (15 mini-blocks per subject; 171 Amazon Mechanical Turk participants [73 for shapes; 98

for words] and 6 subjects in the laboratory who performed a complete version of the

experiment). Based on these results, we expected a mean performance in the memory task of

~71% correct responses when 22- and 28-line distinctive shapes were used in the same block,

and ~83% correct when long words (6-12 letters) with low concreteness, imageability and

familiarity ratings (100-400) were used. To further increase difficulty, we created pairs of old

and new words split between Confidence and Follow conditions (counterbalanced across

subjects), blocked by similar semantic category (e.g. finance, argumentation, character traits,

etc.), such that each new word within a block was freely associated with one old word (and when

possible, vice versa) according to the University of South Florida free association normed

database (Nelson et al., 2004).

In the perceptual task, the difference in brightness (Δb) between the two stimuli was

calibrated for each subject and independently for each stimulus type. The brightness of a

randomly located reference stimulus was fixed (mid-gray). The brightness of the non-reference

stimulus was titrated using a staircase procedure similar to previous experiments (Fleming et al.,

2010; 2012b; 2014). During practice, we used a fixed large step size 2-down/1-up procedure

until subjects reached 15 reversals or 90 trials. The step sizes followed recommended ratios to

match the expected performance in memory blocks (García-Pérez, 1998). The experiment began

with a Δb value determined by the average of the Δb values at each reversal, excluding the first

one. Throughout the experiment, we kept a small step size staircase running to account for

learning or tiredness.

A mid-gray fixation cross subtending 0.3 degrees of visual angle was presented between

the two stimuli on a black background. The reference stimulus in the perceptual task and all

stimuli in the memory task were mid-gray. All stimuli were surrounded by an isoluminant blue

bounding box separated from the stimulus by a gap of at least 0.15 degrees of visual angle.

Behavioral data analysis

Data analysis was performed in MATLAB and statistical analysis in RStudio (R Studio

Team, 2015). We estimated metacognitive efficiency by computing $\log(\text{meta-}d'/d')$. d' is a signal

detection theoretic measure of type 1 sensitivity, while meta-d' is a measure of type 2 sensitivity

(i.e. the degree to which a subject discriminates correct form incorrect responses) expressed in

the same units as type 1 sensitivity (d') (Maniscalco and Lau, 2012; Fleming and Lau, 2014).

Meta-d' indicates the d' that would have been predicted to give rise to the observed confidence

rating data assuming a signal detection theoretic ideal observer. Meta-$d'=d'$ indicates an optimal

type II behavior for the observed type I behavior. Meta-d' greater or less than d' indicates

metacognition that is better or worse, respectively, than expected given task performance, as may

occur for instance if first-order decisions and confidence are supported by partly parallel

processing streams (Fleming and Daw, 2017). We used hierarchical Bayesian estimation to

incorporate subject-level uncertainty in group-level parameter estimates (Fleming, 2017).

Certainty on this parameter was determined by computing the 95% high-density interval (HDI)

from the posterior samples (Kruschke, 2010). For correlation and individual differences analyses

we used single-subject Bayesian model fits. Two subjects were discarded for missing more than

10% of the trials (i.e. >1 standard deviation from the average missed trials, which was 5%).

Missed trials were not analyzed.

fMRI data acquisition

Brain images were acquired using a 3T Allegra scanner (Siemens). BOLD-sensitive functional

images were acquired using a T2*-weighted gradient-echo echo-planar images (42 transverse

slices, interleaved acquisition; TR, 2.34s; TE, 30ms; matrix size: 64×64; 3×3mm in-plane

resolution; slice thickness: 3mm; flip angle: 90°; FOV: 126mm). The main experiment consisted

of three runs of 210 volumes and three runs of 296 volumes for the perceptual and memory tasks,

respectively. We collected a T1-weighted MPRAGE anatomical scan (1×1×1mm voxels; 176

slices) and local field maps for each subject.

fMRI data preprocessing

Imaging analysis was carried out using SPM12 (Statistical Parametric Mapping;

www.fil.ion.ucl.ac.uk/spm). The first five volumes of each run were discarded to allow for T1

stabilization. Functional images were realigned and unwarped using local field maps (Andersson

et al., 2001) and then slice-time corrected (Sladky et al., 2011). Each participant's structural

image was segmented into gray matter, white matter, cerebral spinal fluid, bone, soft tissue, and

air/background images using a nonlinear deformation field to map it onto template tissue

probability maps (Ashburner and Friston, 2005). This mapping was applied to both structural and

functional images to create normalized images to Montreal Neurological Institute (MNI) space.

Normalized images were spatially smoothed using a Gaussian kernel (8mm FWHM). We set a

within-run 1mm rotation and 4mm affine motion cut-off criterion, which led to the exclusion of 4

subjects, leaving a total of 24 subjects whose functional and behavioral data were fully analyzed.

Univariate analysis

All our general linear models (GLMs) focus on the 'rating period' of each trial by specifying

boxcar regressors beginning at the subjects' type I response and ending at their type II response

(i.e. either confidence rating or number press). Motion correction parameters were entered as

covariates of no interest along with a constant term per run. Regressors were convolved with a

canonical hemodynamic response function (HRF). Low-frequency drifts were excluded with a

1/128Hz high-pass filter. Missed trials were not modeled. For judgment-related (JR) analyses,

we created a GLM with two regressors of interest per run to estimate BOLD response amplitudes

in each voxel during the 'rating period' in each trial of the Confidence and Follow blocks. For

the confidence level-related (CLR) parametric modulation analysis, a GLM was used to estimate

BOLD responses in Confidence blocks. There were two regressors of interest in each run, one

modeling the confidence 'rating period' and another that encoded a parametric modulation by the

four available confidence ratings (1-4).

Statistical inference

For the JR-analysis, single-subject contrast images of the Confidence and Follow regressors were

entered into a second-level random effects analysis using one-sample *t*-tests against zero to

assess group-level significance. For the CLR-parametric modulation analysis, single-subject

contrast images of the parametric modulator were entered into a similar second-level random

effects analysis. For conjunction analyses of activations common to both domains, second-level

maps thresholded at *P*<0.001 (uncorrected) were intersected to reveal regions of shared

statistically significant JR- and CLR-activity. Activations were visualized using MRIcro

(http://www.mccauslandcenter.sc.edu/crnl/mricro). All second-level unthresholded statistical

images were uploaded to Neurovault (Gorgolewski et al., 2015)

(https://neurovault.org/collections/3232/).

ROI analysis

To define regions of interest (ROIs), 12mm spheres were centered at MNI coordinates identified

from previous literature (Figure 3C). ROIs in left rostrolateral prefrontal cortex (L rlPFC) [-33,

44, 28], right rlPFC (R rlPFC) [27, 53, 25] and dorsal anterior cingulate cortex/pre-

supplementary motor area (dACC/pre-SMA) [0, 17, 46] were created based on (Fleming et al.,

2012b). The mask for precuneus (PCUN) [0, -64, 24] was based on (McCurdy et al., 2013). The

MNI *x*-coordinates for the dACC/pre-SMA and PCUN masks were set to 0 to ensure bilaterality.

Beta values were extracted from subjects' contrast images for the JR- and CLR-univariate

analyses, respectively.

Multi-voxel pattern analysis

Multi-voxel pattern analysis (MVPA) was carried out in MATLAB using The Decoding Toolbox

(Hebart et al., 2015). We classified run-wise beta images from GLMs modeling JR- and CLR-

activity patterns in ROI and whole-brain searchlight analyses. ROI MVPAs were performed on

normalized, smoothed images using the ROI spheres as masks. Previous work has shown that

these preprocessing steps have minimal impact on support vector machine (SVM) classification

accuracy, while allowing meaningful comparison across subject-specific differences in anatomy,

as in standard fMRI analyses (Kamitani and Sawahata, 2010; Op de Beeck, 2010). A single

accuracy value per subject, per condition and per ROI was extracted and used for group analysis

and statistical testing. As a control, we added a 6mm-radius sphere centered at the ventricles [0 2

15].

257   Whole-brain searchlight analyses used 12mm-radius spheres centered around a given

voxel, for all voxels, on spatially realigned and slice-time corrected images from each subject to

create whole-brain accuracy maps. For group-level analyses, these individual searchlight maps

were spatially normalized and smoothed using a Gaussian kernel (8mm FWHM) and entered into

one-sample *t*-tests against chance accuracy (Hebart et al., 2014; 2015). Whole-brain cluster

inference was carried out in the same manner as in univariate analysis. Visualizations were made

with Surf Ice (https://www.nitrc.org/projects/surfice/).

264   Prior to decoding, for JR-activity pattern classification, we modeled two regressors of

interest per run focused on the 'rating periods' in the Confidence and Follow conditions. For

classification of CLR-activity patterns, we collapsed ratings 1 and 2 into a low-confidence

regressor and ratings 3 and 4 into a high-confidence regressor to allow binary classification. The

remaining parameters of no interest were specified as in the univariate case. For the CLR-

searchlight analysis, we used an exclusive mask of activity patterns associated with usage of the

confidence scale obtained from the successful cross-classification of button presses (1-2 vs 3-4)

between the Confidence and Follow conditions to eliminate low-level visuomotor confounds

(Figure 4D).

273   In independent across-domain classifications, we used the run-wise beta images

reflecting JR- and CLR-activity as pattern vectors in a linear support vector classification model

(as implemented in LIBSVM). We assigned each vector from each domain a label corresponding

to the classes Confidence (1) and Follow (-1) in the JR-analysis and Low Confidence (-1) and

High Confidence (1) in the CLR-analysis. We trained an SVM with the vectors from one domain

(3 per class, 6 in total) and tested the decoder on the 6 vectors from the other domain (and vice

versa) (Figure 4A; left), obtaining a mean average classification accuracy value for each of these

two-way cross-classifications.

For within-domain classifications, we ran independent leave-one-run-out cross-

validations for each domain on JR-activity patterns (Confidence vs Follow) and CLR-activity

patterns (Low vs High confidence). Pattern vectors from two of the three runs in each domain

were used to train an SVM to predict the same classes in the vectors from the left-out run. We

compared the true labels of the left-out run with the labels predicted by the model and iterated

this process for the other two runs to calculate a mean cross-validated accuracy independently for

each domain (Figure 4A; right).

We also tested the ability of confidence-related activity patterns to predict objective

performance in the absence of confidence reports. We used a GLM that modeled Low vs High

Confidence trials with a regressor that focused on the 'rating period', and Incorrect vs Correct

Follow trials with a regressor that focused on the 'decision period' (i.e. from stimulus onset to

subjects' type I response). We performed a cross-classification analysis in which a decoder

trained on Confidence trials (Low vs High Confidence) was tested on pattern vectors from

Follow trials (Incorrect vs Correct), and vice versa (collapsed across domain). This confidence-

objective performance generalization score was compared to a leave-one-run-out cross-

validation analysis decoding Low vs High confidence on Confidence trials only (collapsed across

domain). Together, these scores characterize whether a particular set of patterns are specific to

confidence, or also generalize to predict objective performance (Cortese et al., 2016) (Figure 5).

Individual differences

Metacognitive efficiency scores (log meta-*d'/d'*) for each subject were estimated independently

for the perceptual and memory tasks, together with a single score collapsed across domains.

These scores were inserted as covariates in second-level analyses of within-perception, within-

memory, and across-domain classifications of confidence level-related activity, respectively, to

assess the parametric relationship between metacognitive efficiency and decoding success.

RESULTS

We analyzed the data of 24 subjects who underwent hemodynamic neuroimaging while

performing two-alternative forced-choice discrimination tasks in perceptual (PER) and memory

(MEM) domains (Figure 1A). In the perceptual task, subjects were asked to indicate the brighter

of two stimuli (words or abstract shapes). In the memory task, subjects were asked to memorize

exemplars of the same stimulus types, and then select the previously-learned stimulus from two

stimuli presented on each trial. In half of the trials ("Confidence" condition) subjects performed

a metacognitive evaluation after the discrimination task by rating their confidence in the

correctness of their response by selecting a number on a 1-to-4 scale (1=not confident; 4=very

confident). In order to differentiate metacognitive judgment-related activity from visuomotor

activity engaged by use of the confidence scale, in the other half of trials ("Follow" condition)

subjects were asked to respond according to a highlighted number without evaluating confidence

in their response. To avoid stimulus-type confounds, two different types of stimulus—words and

abstract shapes—were used as stimuli in both tasks.

Figure 1. Task design & performance results. (A) Subjects performed two-alternative forced-
choice discrimination tasks about perception and memory. In perception blocks, subjects selected
the brighter of two stimuli. Memory blocks started with an encoding period and then subjects
indicated in each trial which of two stimuli appeared during the encoding period. Abstract shapes
and words were used as stimuli in both tasks. In Confidence blocks, subjects rated their
confidence and in Follow blocks they pressed the highlighted number. **(B)** Percentage correct
responses per block type in the Confidence condition. Each marker represents a subject. **(C)**
Mean percentage correct responses by domain, averaged over subjects and stimulus types.
Dotted lines indicate chance performance. Bars indicate standard error of the mean (s.e.m.). n.s.=
not significant; P=perception; M=memory

Behavior

We first compared task performance, measured by percentage of correct responses, across

condition, task, and stimulus type. A 2×2×2 repeated measures ANOVA (CONFIDENCE/FOLLOW ×

PERCEPTION/MEMORY × SHAPES/WORDS) showed that performance was well-matched across

conditions (Confidence vs Follow) ($F_{1,23}$=3.036, P=0.095). None of the four paired *t*-tests

(DOMAIN×STIMULUS) comparing performance between the Confidence and Follow conditions

returned a significant difference (P>0.05). In the remainder of the behavioral analyses we focus

on the Confidence condition. Matching performance across stimulus type was more challenging

because subjects' memory for words was expected to be considerably higher than that for

abstract shapes trials based on pilot data (see Methods for details). Instead, we aimed to match

subjects' performance independently for each stimulus type across task domains by titrating the

difficulty of the perceptual task to approximate the performance expected for the corresponding

stimulus type in the memory task (shapes: PER M=73%, MEM M=67%; words: PER M=81%, MEM

M=89%; Figure 1B). Critically, this ensured performance was matched across task domains

when averaging stimulus types across participants (PER: M=77%, MEM: M=78%; paired *t*-test

T_{23}=0.38, P=0.70; Figure 1C). A 2×2 repeated measures ANOVA of performance in the

Confidence condition (PERCEPTION/MEMORY × SHAPES/WORDS) confirmed there was no main

effect of domain ($F_{1,23}$= 0.15, P=0.702). However, we observed a main effect of stimulus type

due to greater overall performance on words ($F_{1,23}$=75.69, P= 9.87×10^{-9}) and a DOMAIN ×

STIMULUS interaction, due to a greater difference in performance between shapes and words in

the memory compared to the perception task ($F_{1,23}$=16.74, P=0.00045).

Subjects were faster providing type I responses in perceptual trials (M=636ms) than in

memory trials (M=1222ms). There was also a small difference in reaction times between shape

(M=967ms) and word (M=892ms) trials. A 2×2 repeated measures ANOVA confirmed a main

effect of domain ($F_{1,23}$=367, P=1.23×10^{-15}) driven by slower reaction types in the memory task.

There was also a main effect of stimulus type on response time ($F_{1,23}$=8.95, P=0.006), as well as

a significant DOMAIN × STIMULUS interaction ($F_{1,23}$=5.82, P=0.024).

Figure 2. Metacognitive measures. (A) Mean number of correct and incorrect trials per
confidence rating. **(B)** Metacognitive efficiency measured by log(meta-d'/d'). Zero indicates that
metacognitive sensitivity (meta-d') is equal to task sensitivity d' (i.e. the d' that would have been
predicted to give rise to the observed confidence rating data assuming a signal detection theoretic
ideal observer). Group-level hierarchical Bayesian estimates differed significantly between
domains. Error bars indicate 95% high-density interval (HDI) from posterior samples. **(C)**
Metacognitive efficiency scores obtained from single-subject Bayesian model fits were not
correlated across perceptual and memory domains. **(D)** Domain-general index (DGI) for each
subject that quantifies the similarity between their metacognitive efficiency scores in each
domain (see main text for details). Greater DGI scores indicate less metacognitive consistency
across domains. Mean log(meta-d'/d') values for each stimulus type in both domains are shown
for reference. Bars in (A) and (D) indicate s.e.m. *** $P_{\theta>0}$ ~ 1. P=perception M=memory.
377

As expected, subjects gave higher confidence ratings after correct decisions than after

incorrect decisions (Figure 2A), and mean confidence ratings were similar across task domains

(PER M=2.62, MEM M=2.47; paired *t*-test T_{23}=1.26, *P*=0.22). Reaction times for confidence

ratings were not different between domains (PER M=518ms, MEM M=516ms; paired *t*-test

T_{23}=0.16, *P*=0.87). We next estimated log (meta-*d'*/*d'*), a metacognitive efficiency measure

derived from signal detection theory that assays the degree to which confidence ratings

distinguish between correct and incorrect trials (Maniscalco and Lau, 2012; Fleming and Lau,

2014; Fleming, 2017). We used hierarchical Bayesian estimation to incorporate subject-level

uncertainty in group-level parameter estimates (Fleming, 2017). Metacognitive efficiency in the

perceptual task was significantly lower than in the memory task ($P_{\theta>0}$ ~ 1; see Figure 2B &

Methods for details), consistent with previous findings (Fleming et al., 2014). Metacognitive

efficiency above optimality (meta-*d'*=*d'*) in memory trials suggests subjects had better

metacognition than expected given their task performance, while suboptimal metacognitive

efficiency in perceptual trials suggests subjects had worse metacognition than expected given

their task performance (assuming an ideal observer in both cases). We did not find a correlation

between subjects' individual metacognitive efficiency scores in the perceptual and memory

domains (r_{22}=-0.076; *P*=0.72; Figure 2C). We also evaluated the correlation coefficient within a

hierarchical model of meta-*d'*, which takes into account uncertainty in subject-level model fits

(Fleming, 2017). The 95% confidence interval on the posterior correlation coefficient overlapped

zero in this analysis (ρ=0.205; HDI=[0.826, -0.358]), also indicating a dissociation between

domains.

We next estimated metacognitive efficiency separately for each stimulus type (Figure

2D). A 2×2 repeated measures ANOVA (PERCEPTION/MEMORY × SHAPES/WORDS) indicated

metacognitive efficiency was greater for memory than perception ($F_{1,23}$=22.44, *P*=8.97×10^{-5}).

Importantly, there was no stimulus main effect ($F_{1,23}$=0.015, *P*=0.902) and there was no

interaction between domain and stimulus type ($F_{1,23}$=2.835, P=0.106). To further assess a

potential covariation between metacognitive abilities in each domain, we calculated for each

subject a domain-generality index (DGI) that quantifies the similarity between scores in each

domain for each participant (Fleming et al., 2014):

408   DGI = |log M_P – log M_M|

where M_P = perceptual meta-d'/d' and M_M = memory meta-d'/d'. Lower DGI scores indicate

more similar metacognitive efficiencies between domains (DGI=0 indicates identical scores).

Mean DGI for shapes (1.42), words (0.66) and collapsed by stimulus type (0.95) were higher

than zero (Figure 2D). Metacognition for words was behaviorally more stable across domains as

the DGI was smaller than for shapes (paired t-test: T_{23}=2.86; P=0.009). Together, these results

suggest domain-specific constraints on metacognitive ability.

fMRI analyses

We next turned to our fMRI data to assess the overlap between neural substrates engaged when

metacognitive judgments are made during perceptual and memory tasks. A full understanding of

the neural substrates of metacognition requires an independent examination of the process of

engaging in a metacognitive task and the level of confidence expressed by the subject (Chua et

al., 2014). To this end, in both univariate and multivariate analyses, we focused on two distinct

features of metacognition-related activity. First, we assessed brain regions engaged in judgment-

related (JR) activity (i.e. the difference between Confidence trials requiring a metacognitive

judgment and the Follow condition). Second, we assessed brain regions engaged in confidence

level-related (CLR) activity. In univariate CLR-analysis, we focused on the parametric

relationship between confidence ratings (1 through 4) and neural activity. In multivariate CLR-

analysis, we collapsed ratings 1 and 2 into a low-confidence category and ratings 3 and 4 into a

high-confidence category to allow binary classification of activity patterns.

Univariate results

Judgment-related activity. In standard univariate analyses, we found elevated activity in

dACC/pre-SMA, bilateral insulae and superior and middle frontal gyri when contrasting the

Confidence against the Follow condition (collapsed by domain), consistent with previous

findings (Fleming et al., 2012b) (Figure 3A). There were no significant clusters of activity in the

reverse contrast (Follow>Confidence). Splitting the data by domain (see Table 1), an interaction

contrast [Memory Confidence > Memory Follow] > [Perception Confidence > Perception

Follow] revealed significant clusters of activity in middle cingulate gyrus, left insula, precuneus,

left hippocampus and cerebellum (Figure 3B, blue). No significant clusters of activity were

found in the reverse interaction contrast. In a conjunction analysis, elevated activity for the

Confidence > Follow condition was observed across both perception and memory trials in

anterior cingulate and right insula (Figure 3B, green).

Figure 3. fMRI univariate analysis results. *Judgment-related activity*: **(A)** Whole-brain analysis of significant activation in the Confidence>Follow contrast (collapsed by domain); there were no significant clusters in the Follow>Confidence contrast. **(B)** [Memory Confidence > Memory Follow] > [Perception Confidence > Perception Follow] interaction contrast (blue). There were no significant clusters in the reverse contrast. The conjunction of Memory Confidence > Memory Follow and Perception Confidence > Perception Follow contrasts is indicated in green. **(C)** Spherical binary masks of four a priori regions of interest [1=dACC, 2=L rlPFC, 3=R rlPFC, 4=PCUN] and an ROI in the ventricles [5] used as a control region in multivariate analyses (Figure 4). **(D)** Estimated mean beta values for judgment-related activity by domain in the main four ROIs displayed in (C). *Confidence level-related activity*: **(E)** Whole-brain analysis of activity parametrically modulated by level of confidence (collapsed by domain). Hot colors indicate a positive correlation with confidence and cool colors a negative correlation. **(F)** Memory > Perception contrast (blue) testing for differences between the parametric effect of confidence by domain; there were no significant clusters in the Perception > Memory contrast. A

conjunction analysis revealed shared activity that was positively (green) and negatively (yellow)
correlated with confidence levels in both domains. **(G)** Estimated mean beta values of confidence
level-related activity in the main four ROIs displayed in (C). All displayed whole-brain
activations are significant at a cluster-defining threshold $P<0.001$, corrected for multiple
comparisons $P_{FWE}<0.05$; except for conjunction analyses in which we computed the intersection
of two independent maps thresholded at $P<0.001$, uncorrected. Images displayed at $P<0.001$.
Graded color bars reflect T-statistics. Error bars indicate s.e.m. *** $P<0.001$ ** $P<0.01$ * $P<0.05$.
L=left; R=right; P=perception; M=memory.
467

To further quantify these effects for each task domain, we focused on four a priori

regions of interest (ROI) in (dACC/pre-SMA), bilateral rostrolateral prefrontal cortex (rlPFC)

and precuneus (PCUN) (see Figure 3C & Methods), which previous studies have found to be

recruited by perceptual and memory metacognition (Fleck et al., 2006; Fleming et al., 2010;

2012b; Baird et al., 2013; McCurdy et al., 2013). In a series of repeated measures 2×2 ANOVAS

(CONDITION × TASK) we found a main effect of greater activity on Confidence compared to

Follow trials in all ROIs except precuneus, where instead we observed a main effect of task, with

increased activity on memory trials (Figure 3D; condition main effect: dACC/pre-SMA,

$F_{1,23}=19.34$, $P=0.0002$; left rlPFC, $F_{1,23}=6.62$, $P=0.017$; right rlPFC, $F_{1,23}=9.28$, $P=0.006$; PCUN:

$F_{1,23}=0.40$, $P=0.532$; task main effect: dACC/pre-SMA, $F_{1,23}=2.33$, $P=0.14$; left rlPFC,

$F_{1,23}=0.95$, $P=0.34$; right rlPFC, $F_{1,23}=4.94$, $P=0.036$; PCUN: $F_{1,23}=36.78$, $P=3.47×10^{-6}$). We

found that the difference between Confidence and Follow trials was greater in memory than in

perception trials in dACC/pre-SMA, recapitulating the whole-brain results (CONDITION × TASK

interaction; $F_{1,23}=12.16$, $P=0.0019$; paired t-test, MEM: $T_{23}=5.47$, $P=0.0001$, PER: $T_{23}=1.92$, $P=$

0.067). A similar interaction pattern was observed in precuneus (CONDITION × TASK interaction:

$F_{1,23}=15.86$, $P=0.0006$; paired t-test, MEM: $T_{23}=2.43$, $P=0.023$, PER: $T_{23}=-1.54$, $P=0.136$). There

were no interactions in frontal regions (left rlPFC, $F_{1,23}=0.07$, $P=0.795$; right rlPFC, $F_{1,23}=0.002$,

P=0.968). These results are compatible with previous findings indicating a distinctive

contribution of precuneus to memory metacognition (Baird et al., 2013; McCurdy et al., 2013).

Confidence level-related activity. We next sought to investigate the parametric relationship

between confidence level and neural activity. Collapsing across domains, we found activity in

the left pre- and post-central gyri, the posterior midline, ventral striatum and ventromedial

prefrontal cortex (vmPFC) correlated positively with confidence ratings (Figure 3E, hot colors).

We also replicated negative correlations between confidence and activation in dACC/pre-SMA,

parietal cortex, and bilateral PFC that have been reported in several previous studies (Fleck et al.,

2006; Fleming et al., 2012b; Baird et al., 2013; Hebart et al., 2014) (Figure 3E, cool colors).

When testing for differences between these parametric regressors by domain (see Table 2), a

Memory > Perception contrast revealed a significant cluster of activity in right parietal cortex

(Figure 3F, blue), while there was no significant activity in a Perception > Memory contrast.

Shared positive correlations between confidence and activity in perception and memory trials

were found in ventral striatum and in left pre- and post-central gyri, the latter consistent with use

of the right hand to provide confidence ratings (conjunction analysis; Figure 3F, green). Shared

negative correlations with confidence were found in regions of right dorsolateral PFC and medial

prefrontal cortex, overlapping with pre-SMA (Figure 3F, yellow).

Complementing the ROI analysis of JR-activity, we performed an ROI analysis of CLR-

activity that recapitulated the whole-brain results. We observed negative relationships between

confidence and activity in dACC/pre-SMA and positive relationships in precuneus. Importantly,

no significant differences in the parametric effect of confidence were found between domains in

any of our a priori ROIs (Figure 3G; paired *t*-tests: dACC/pre-SMA, T_{23}=-0.47, *P*=0.643; left

rlPFC, $T_{23}=0.23$, $P=0.820$; right rlPFC, $T_{23}=1.62$, $P=0.119$; PCUN: $T_{23}=0.56$, $P=0.583$).

Together with the lack of marked domain-specific differences in confidence-related activity at

the whole-brain level, these results are suggestive of an absence of domain-specificity in

confidence-related activity. However, a lack of difference between univariate activation profiles

is not necessarily conclusive. For instance, differences in confidence level may be encoded in

fine-grained spatial patterns of activity even when the overall BOLD-activity is evenly

distributed across confidence levels (Cortese et al., 2016). Similarly, while metacognition-related

activity may show similar overall levels of activation across tasks, distributed activity patterns in

frontal and parietal areas may carry distinct task-specific information (Hebart et al., 2014; Cole

et al., 2016). We next turned to multivariate analysis methods, which are sensitive to differences

in spatial activity patterns, to test this hypothesis.

Multivariate results

We performed a series of multi-voxel pattern analyses (MVPA) (Figure 4A) focused on both

judgment-related activity patterns and confidence level-related activity patterns.

ROI analysis of judgment-related activity patterns. If metacognitive judgments are based on

domain-general processes (i.e. shared across perceptual and memory tasks), a decoder trained to

classify JR-activity patterns in perceptual trials should accurately discriminate JR-activity

patterns when tested on memory trials (and vice versa). Alternatively, domain-specific activity

profiles would be indicated by significant within-domain classification of JR-activity patterns in

the absence of across-domain transfer. To adjudicate between these hypotheses, we performed a

support vector machine (SVM) decoding analysis using as input vectors the run-wise beta

images pertaining to Confidence and Follow trials obtained from a GLM (12 input vectors in

total). For within-domain classification we used standard leave-one-out independent cross-

validations for each domain and we tested for across-domain generalization using a cross-

classification analysis (see Methods for details). Chance classification in both analyses was 50%.

Figure 4. MVPA Results. *Classification designs*: **(A)** *Left*: Across-domain classification design.
Pattern vectors (run-wise beta images) from one domain were used to train an SVM decoder on

two classes and then tested in a cross-classification of the same two classes using vectors from
the other domain (and vice versa). Classification of low (L) and high (H) confidence levels is
illustrated here. *Right:* Within-domain classification design. Pattern vectors of two classes (e.g.
low and high confidence) pertaining to one domain were used to train a decoder in a leave-one-
run-out design that was then tested in the left-out pair. The process was iterated three times to
test pairs from every run. An identical, independent cross-validation was performed on vectors
from the other domain. *Judgment-Related Activity Patterns*: **(B)** ROI results for across-domain
(yellow) and mean within-domain (red-blue stripe) classification accuracy of Confidence vs
Follow trials. **(C)** Searchlight analysis for same classifications as in (B). **(D)** Low-level
visuomotor mask used in (F) (see main text and Methods for details). *Confidence Level-Related*
Activity Patterns: **(E)** Low versus high confidence classification accuracy results. **(F)** Searchlight
analysis for the same classifications as in (E) exclusively masked for visuomotor-related activity
patterns. Bars in (B) and (E) indicate means and error bars s.e.m. Dashed lines indicate chance
classification (50%). Diamonds and circles indicate mean independent classification in
perception and memory trials, respectively. White diamonds/circles indicate classification was
significantly different from chance, Bonferroni corrected. All clusters in (C) and (F) are
significant at cluster-defining threshold $P<0.001$, corrected for multiple comparisons at
$P_{FWE}<0.05$. Image displayed at $P<0.001$. Color bars indicate T-scores. P=perception;
M=memory; A=anterior; P=posterior. *** $P\leq0.001$ ** $P\leq0.01$ * $P<0.05$; all one-sample t-tests
are Bonferroni corrected.
559

Mean within-domain classification results were significantly above chance in all ROIs

(one-sample *t*-tests Bonferroni corrected for multiple comparisons α=0.05/4=0.0125: dACC/pre-

SMA $T_{23}=5.77$, $P=6.99\times10^{-6}$; L rlPFC $T_{23}=3.27$, $P=0.003$; R rlPFC $T_{23}=4.47$, $P=0.0002$; PCUN

$T_{23}=2.98$, $P=0.007$; Figure 4B, red-blue stripe bars). In contrast, across-domain generalizations

were not significantly different from chance in any ROI (one sample *t*-test Bonferroni corrected:

dACC/pre-SMA, $T_{23}=1.95$, $P=0.06$; L rlPFC, $T_{23}=0.79$, $P=0.44$; R rlPFC, $T_{23}=1.24$, $P=0.23$;

PCUN $T_{23}=1.40$, $P=0.17$; Figure 4B, yellow bars). As a control, classification accuracy in the

ventricles (VENTR) was not different from chance (across: $T_{23}=0.66$, $P=0.52$; within: $T_{23}=1.04$,

$P=0.31$). This suggests that the patterns of activity that distinguish metacognitive judgments

from the visuomotor control condition in one domain are distinct from analogous patterns in the

other domain. In particular, within-domain classification accuracy was significantly different

from across-domain classification accuracy in (dACC/pre-SMA: $T_{23}=2.88$, $P=0.008$) and right

rlPFC (T_{23}=2.24, P=0.035). These results are consistent with the hypothesis that metacognitive

judgments recruit domain-specific patterns of cortical activity in prefrontal cortex.

Searchlight analysis of judgment-related activity patterns. We ran a similar decoding analysis

using an exploratory whole-brain searchlight, obtaining a classification accuracy value per voxel

(Hebart et al., 2015). Consistent with our ROI results, we observed significant within-domain

classification in large swathes of bilateral PFC for both perception (red) and memory (blue)

(Figure 4C). Within-perception classification was also successful in parietal regions—precuneus

in particular—and within-memory activity patterns were classified accurately in occipital

regions. We also identified clusters showing significant across-domain generalization (yellow) in

dACC, pre-SMA, SFG (BA 9), supramarginal gyrus (BA 40), and bilateral IFG/insula, consistent

with univariate results (Figure 3A).

ROI analysis of confidence level-related activity patterns. We next asked whether confidence is

encoded in a domain-general or domain-specific fashion by applying a similar approach to

discriminate low versus high confidence trials. Note that in this case, ROI univariate analyses did

not reveal any differences in confidence-related activity between domains (Figure 3G). We

hypothesized that if confidence level is encoded by domain-general neural activity patterns, it

should be possible to train a decoder to discriminate low (1-2) from high (3-4) confidence rating

patterns in the perceptual task and then accurately classify confidence patterns on the memory

task (and vice versa). In the absence of across-domain classification, significant within-domain

classification is indicative of confidence level-related domain-specific activity patterns. ROI

cross-classifications and cross-validations were performed in a similar fashion as above. We note

that two subjects did not provide ratings for one of the classes in at least one run and were left

out from the main analysis to avoid entering unbalanced training data into the classifier;

however, including those subjects did not change the main result.

One-sample *t*-tests (Bonferroni-corrected) showed across-domain classification of

confidence was significantly above chance in dACC/pre-SMA (T_{21}=2.83, *P*=0.010) and

precuneus (T_{21}=4.69, *P*=0.0001), indicative of a generic confidence signal, but not in rlPFC (left:

T_{21}=1.36, *P*=0.19; right: T_{21}=0.97, *P*=0.34) (Figure 4E, yellow bars). In contrast, mean within-

domain classification accuracy was significantly above chance in right rlPFC (T_{21}=3.75,

P=0.001), but not in the other ROIs (dACC/pre-SMA: T_{21}=2.42, *P*=0.025; left rlPFC: T_{21}=1.03,

P=0.32; PCUN: T_{21}=1.42, *P*=0.17; Bonferroni-corrected; Figure 4E, red-blue stripe bars). The

mean confidence classification accuracy in right rlPFC was 62% (PER=59%, MEM=64%),

notably above a recently estimated median 55% for decoding task-relevant information in frontal

regions (Bhandari et al., 2017). Importantly, classification accuracy in this ROI also differed

from the corresponding across-domain classification accuracy (paired *t*-test T_{21}=2.37, *P*=0.028).

Classification accuracy in the ventricles was not different from chance (across: T_{21}=-0.24,

P=0.81; within: T_{21}=0.86, *P*=0.40). When subjects with unbalanced data were included, within-

domain classification accuracy in right rlPFC remained at 62%, significantly above chance (T_{23}=

4.22; P=0.0003) and significantly different from across-domain classification accuracy (paired t-

test: T_{23}= 2.54; *P*=0.018). Together, these results suggest the co-existence of two kinds of CLR-

neural activity: dACC/pre-SMA and precuneus encode a generic confidence signal, whereas

patterns of activity in right rlPFC were modulated by task, allowing within- but not across-

domain classification of confidence level.

Searchlight analysis of confidence level-related activity patterns. We ran a similar decoding

analysis of confidence level using an exploratory whole-brain searchlight, obtaining a

classification accuracy value per voxel. Here we leveraged the Follow trials as a control for low-

level visuomotor confounds by exclusively masking out activity patterns associated with usage

of the confidence scale (Figure 4D). The remaining activity patterns can therefore be ascribed to

confidence level-related signals that do not encode visual or motor features of the rating (Figure

4F). We found widespread across-domain classification of confidence (yellow) in a

predominantly midline network including a large cluster encompassing dACC/pre-SMA,

vmPFC, and ventral striatum. Domain-specific confidence level-related activity patterns were

successfully decoded from right PFC (insula, IFG, BA 9, 46) in memory trials (blue) and were

also independently decoded in both domains from dACC/pre-SMA.

Generalization of CLR-activity to objective performance. To further address the question of how

confidence judgments may relate to activity patterns, we examined the relationship between

objective task accuracy and confidence. Previous work suggests that the neural basis (and

associated activation patterns) of confidence and performance may be partly distinct (Rounis et

al., 2010; Cortese et al., 2016). Specifically, we tested the hypothesis that we could train a

decoder using CLR-activity patterns to classify objective performance-related activity patterns

(correct/incorrect) on Follow trials (and vice versa) in a cross-classification analysis (collapsed

across domain). This analysis confirmed that activity patterns in dACC/pre-SMA (T_{21}=2.38,

P=0.027) and right rlPFC (T_{21}=2.64, *P*=0.015) could predict objective accuracy levels in Follow

trials above chance (Figure 5, light gray; uncorrected), but not in left rlPFC (T_{21}=1.49, *P*=0.15)

or precuneus (T_{21}=-0.46, *P*=0.65). We then compared these decoding scores to a leave-one-run-

out cross-validation decoding analysis of low versus high confidence on Confidence trials only

(collapsed by domain; Figure 5, dark gray; uncorrected). Consistent with the analyses reported in

Figure 4E (yellow), this decoder was unable to classify domain-general confidence patterns of

activity in right rlPFC (T_{21}=1.00; P=0.33), but was above chance in dACC/pre-SMA (T_{21}=3.80,

P=0.001), left rlPFC (T_{21}=2.26, P=0.034) and precuneus (T_{21}=2.56, P=0.018). Critically, in

precuneus, confidence classification was significantly greater than confidence-performance

generalization, which was at chance (paired t-test T_{21}=2.16, P=0.043). This result indicates that

confidence-related patterns in precuneus do not generalize to predict objective performance,

consistent with a partly distinct coding of information relevant to task performance and

confidence. In contrast, in dACC/pre-SMA, general confidence level and performance could be

predicted from common patterns of activation.

Figure 5. Generalization of confidence-related activity to objective accuracy. Light gray bars
denote mean cross-classification accuracy results obtained from training a decoder on CLR-
activity and testing it on objective accuracy (correct / incorrect) activity patterns in the Follow
condition (and vice versa). Dark gray bars denote decoding accuracy for a leave-one-out cross-
validation of low and high confidence on Confidence trials only (collapsed by domain). Bars
indicate group means and bars s.e.m. Dotted line indicates chance level. * *P*<0.05 *** *P*<0.001
660

Metacognitive efficiency and confidence level-related activity classification. Finally, we

reasoned that if confidence-related patterns of activation are contributing to metacognitive

judgments, they may also track individual differences in metacognitive efficiency. To test for

such a relation, we asked whether individual metacognitive efficiency scores collapsed across-

domains and independently in each domain predicted searchlight classification accuracy of

confidence level. We did not find any significant clusters after whole-brain correction for

multiple comparisons in domain-general, within-perception, or within-memory analyses.

However, memory metacognitive efficiency predicted memory confidence classification

accuracy in a cluster in right precuneus and left precentral gyrus ($P<0.001$, uncorrected), whereas

perceptual metacognitive efficiency predicted perceptual confidence classification accuracy in

left middle frontal gyrus, right vmPFC, bilateral temporal gyri, and cerebellum ($P<0.001$,

uncorrected). Previous studies (Fleming et al., 2010; McCurdy et al., 2013; Fleming et al., 2014)

have reported similar relations between perceptual and memory metacognitive efficiency and

individual differences in the structure of prefrontal and parietal cortex, respectively. While we do

not interpret these findings further in the current manuscript, for completeness, second-level

unthresholded statistical images of these analyses were uploaded to Neurovault in order to

inform future work (Gorgolewski et al., 2015) (https://neurovault.org/collections/3232/).

DISCUSSION

When performing a cognitive task, confidence estimates allow for comparisons of performance

across a range of different scenarios (de Gardelle and Mamassian, 2014). Such estimates must

also carry information about the task context if they are to be used in decision-making. Here we

investigated the domain-generality and domain-specificity of representations that support

metacognition of perception and memory.

Unlike previous studies (McCurdy et al., 2013), subjects' performance was matched

between domains for two different types of stimulus, thereby eliminating potential performance

and stimulus confounds. Subjects' confidence ratings were also matched between domains and

followed expected patterns of higher ratings after correct decisions than after incorrect decisions.

Metacognitive efficiency scores between tasks were not correlated, and metacognitive efficiency

scores in the memory task were superior to those in the perceptual task. Using univariate and

multivariate analyses, we showed the existence of both domain-specific and domain-general

metacognition-related activity during perceptual and memory tasks. We report four main

findings, and discuss each of these in turn.

First, we obtained convergent evidence from both univariate and multivariate analyses

that a cingulo-opercular network centered on dACC/pre-SMA encodes a generic signal

predictive of confidence level and objective accuracy across memory and perceptual tasks.

Previous studies of metacognition have implicated the cingulo-opercular network in tracking

confidence level (Fleck et al., 2006; Fleming et al., 2012b; Hebart et al., 2014; Hilgenstock et al.,

2014). However, we go beyond these previous studies to provide evidence that these signals

generalize to predict confidence across two distinct cognitive domains. This finding is consistent

with posterior medial frontal cortex as a nexus for monitoring the fidelity of generic

sensorimotor mappings, building on previous findings that error-related event-related potentials

originating from this region are sensitive to variation in subjective certainty (Scheffers and

Coles, 2000; Boldt and Yeung, 2015). The activity in dACC/pre-SMA was also consistently

elevated by the requirement for a metacognitive judgment (Fleming et al., 2012b). However, the

results regarding the generalizability of the pattern of these increases across tasks were

inconclusive. Whole-brain searchlight analysis revealed successful cross-classification of these

activity patterns in dACC and insular regions, consistent with the results of the univariate

analysis. These patterns of activity, however, did not generalize across tasks in a pre-defined

region of interest centered in dACC/pre-SMA.

Notably, while both dACC/pre-SMA and precuneus showed significant domain-general

decoding of confidence, in precuneus these patterns did not generalize to also predict changes in

objective accuracy. While performance and subjective confidence may both depend on similar

decision variables (Kiani and Shadlen, 2009; Fleming and Daw, 2017), behavioral dissociations

between these quantities are also consistent with distinct internal states contributing to decisions

and confidence ratings (Busey et al., 2010; Fleming and Daw, 2017). For instance, hierarchical

models of confidence formation suggest a downstream network "reads out" decision-related

information in a distinct neural population (Insabato et al., 2010). The observed lack of cross-

classification in precuneus (Figure 5) is consistent with the recent observation of distinct neural

patterns of activity pertaining to confidence and first-order performance revealed through multi-

voxel neurofeedback in frontal and parietal regions (Cortese et al., 2016).

Second, in lateral anterior frontal cortex we found activity patterns that tracked both the

requirement for metacognitive judgments and level of confidence. Large swathes of lateral

prefrontal cortex distinguished activity patterns pertaining to metacognitive judgments that were

specific for each domain. Critically, however, confidence-related activity patterns were selective

for domain in right rlPFC (Figure 4E): they differed according to whether the subject was

engaged in rating confidence about perception or memory. Such signals may support the

"tagging" of confidence with contextual information, thereby facilitating the use of confidence

for behavioral control (Donoso et al., 2014; Purcell and Kiani, 2016). The identity of perceptual

and memory tasks can be reliably decoded from activity in right PFC neural populations

(Mendoza-Halliday and Martinez-Trujillo, 2017), consistent with the possibility that this

contextual information is recruited during confidence rating. It is possible that anterior prefrontal

regions combine generic confidence signals with domain-specific information to fine-tune

decision-making and action selection in situations in which subjects need to regularly switch

between tasks or strategies on the basis of their reliability (Donoso et al., 2014). An alternative

hypothesis, also compatible with our data, is that PFC first estimates the confidence level

specifically for the current task, which is then relayed to medial areas to recruit the appropriate

resources for cognitive control in a task-independent manner. Processing dynamics may also

unfold simultaneously in both areas. These possibilities echo a longstanding debate in the

cognitive control literature on the relative primacy of medial and lateral PFC in the hierarchy of

control (Kerns et al., 2004; Tang et al., 2016). Further inquiry and development of computational

models of the hierarchical or parallel functional coupling of these networks in metacognition is

necessary.

Third, we obtained convergent evidence that precuneus plays a specific role in

metamemory judgments. In univariate fMRI analyses, we found the requirement for a

metacognitive judgment recruited our pre-established region of interest centered on precuneus

only on memory, but not perceptual, trials (Figure 3D). Individual metacognitive efficiency

scores in memory trials predicted classification accuracy in a more dorsal precuneal region,

while individual differences in metacognitive efficiency scores in perceptual trials predicted

classification accuracy in ventromedial prefrontal cortex (albeit at uncorrected thresholds). These

findings are consistent with the medial parietal cortex making a disproportional contribution to

memory metacognition (Simons et al., 2010; Baird et al., 2013; McCurdy et al., 2013), and offer

a potential explanation for a decrease in perceptual, but not memory, metacognitive efficiency

seen in patients with frontal lesions (Fleming et al., 2014). However, we do not wish to conclude

that precuneus involvement is specific to metamemory. We note that univariate negative

correlations with confidence were found also on perceptual trials, and multivariate classification

results in precuneus indicated the presence of both perceptual and memory-related signals. This

dual involvement of the precuneus in perception and memory metacognition is consistent with

previous studies which suggest a relationship between precuneus structure and visual perceptual

metacognition (Fleming et al., 2010; McCurdy et al., 2013).

Fourth, we found in both univariate and multivariate whole-brain analyses that domain-

general signals in the ventral striatum and vmPFC (including subgenual anterior cingulate

cortex) were modulated by confidence level. These results are compatible with previous findings

that have found activity in ventral striatum to be positively correlated with confidence (Daniel

and Pollmann, 2012; Hebart et al., 2014; Guggenmos et al., 2016). Evidence of vmPFC encoding

of confidence signals has been reported in connection to decision-making and value judgments

(De Martino et al., 2013; Lebreton et al., 2015). Our experimental design, however, does not

allow us to disentangle whether the signals found in these regions pertain uniquely to confidence

or whether they are entangled with implicit value and reward signals (for instance, the expected

value of being correct). Future experiments are needed to explicitly decouple reward from

confidence to resolve this issue.

In our experimental design perception and memory blocks were interleaved across runs,

which raises the question as to whether the domain-specific neural substrates we found would

persist if subjects had to switch between tasks more often. Due to inter-task "leaks" in

confidence (Rahnev et al., 2015), in which confidence in one task influences confidence ratings

on the following task (or even in the following trial), there is a possibility that interleaving

blocks of different tasks might favor the observation of more domain-general confidence-related

patterns.

Our experimental design assumes that visual perception and memory are distinct

domains. We acknowledge that distinguishing between cognitive domains or individuating

perceptual modalities is not straightforward (Macpherson, 2011). For instance, different

modalities (e.g. vision, audition, touch, etc.), different aspects within a single modality (e.g.

motion and color within vision), or closely related modalities (e.g. visual perception vs visual

short-term memory) could be part of a unified perceptual domain for metacognitive purposes.

Recent findings suggest metacognitive efficiency in one perceptual modality predicts

metacognitive efficiency in others and that they share electrophysiological markers (Faivre et al.,

2017). Metacognitive efficiency is also correlated across vision and visual short-term memory,

especially for features such as orientation (Samaha and Postle, 2017), and dACC and insula

regions similar to those identified here have been found to show univariate confidence signals

across both color and motion tasks in the visual domain (Heereman et al., 2015). However, it is

an open question whether more fine-grained modality-specific patterns of metacognitive activity

could be decoded using multivariate approaches. More research is needed on the neural

architecture of metacognition in other cognitive domains, and whether this architecture changes

in a graded or discrete fashion as a function of task or stimulus.

In summary, our results provide evidence for the co-existence of content-rich

metacognitive representations in anterior prefrontal cortex with generic confidence-related

signals in frontoparietal and cingulo-opercular regions. Such an architecture may be appropriate

for "tagging" lower-level feelings of confidence with higher-order contextual information to

allow effective behavioral control. Previous studies have tended to draw conclusions about either

domain-specific or domain-general aspects of metacognition. Here we reconcile these

perspectives by demonstrating that both domain-specific and domain-general signals co-exist in

the human brain, thus laying the groundwork for a mechanistic understanding of reflective

judgments of cognition.

REFERENCES

Ais J, Zylberberg A, Barttfeld P, Sigman M (2016) Individual consistency in the accuracy and
distribution of confidence judgments. Cognition 146:377–386.

Andersson JLR, Hutton C, Ashburner J, Turner R, Friston K (2001) Modeling Geometric
Deformations in EPI Time Series. Neuroimage 13:903–919.

Ashburner J, Friston KJ (2005) Unified segmentation. Neuroimage 26:839–851.

Baird B, Smallwood J, Gorgolewski KJ, Margulies DS (2013) Medial and Lateral Networks in
Anterior Prefrontal Cortex Support Metacognitive Ability for Memory and Perception. J
Neurosci 33:16657–16665.

Bhandari A, Gagne C, Badre D (2017) Just above chance: is it harder to decode information from
human prefrontal cortex BOLD signals? bioRxiv:1–28.

Boldt A, Yeung N (2015) Shared Neural Markers of Decision Confidence and Error Detection. J
Neurosci 35:3478–3484.

Botvinick MM, Cohen JD, Carter CS (2004) Conflict monitoring and anterior cingulate cortex:
an update. Trends Cogn Sci 8:539–546.

Busey TA, Tunnicliff J, Loftus GR, Loftus EF (2010) Accounts of the confidence-accuracy
relation in recognition memory. Psychon Bull Rev 7:26–48.

Chua EF, Pergolizzi D, Weintraub RR (2014) The Cognitive Neuroscience of Metamemory
Monitoring: Understanding Metamemory Processes, Subjective Levels Expressed, and
Metacognitive Accuracy. In: The Cognitive Neuroscience of Metacognition (Fleming SM,
Frith CD, eds), pp 267–291. Berlin: Springer.

Cole MW, Ito T, Braver TS (2016) The Behavioral Relevance of Task Information in Human
Prefrontal Cortex. Cereb Cortex 26:2497–2505.

Cole MW, Reynolds JR, Power JD, Repovs G, Anticevic A, Braver TS (2013) Multi-task
connectivity reveals flexible hubs for adaptive task control. Nature Neurosci 16:1348–1355.

Cortese A, Amano K, Koizumi A, Kawato M, Lau H (2016) Multivoxel neurofeedback
selectively modulates confidence without changing perceptual performance. Nat Commun
7:13669.

Daniel R, Pollmann S (2012) Striatal activations signal prediction errors on confidence in the
absence of external feedback. Neuroimage 59:3457–3467.

de Gardelle V, Mamassian P (2014) Does confidence use a common currency across two visual
tasks? Psychol Sci 25:1286–1288.

De Martino B, Fleming SM, Garrett N, Dolan RJ (2013) Confidence in value-based choice.
Nature Neurosci 16:105–110.

Donoso M, Collins AGE, Koechlin E (2014) Foundations of human reasoning in the prefrontal
cortex. Science 344:1481–1486.

Faivre N, Filevich E, Solovey G, Kuhn S, Blanke O (2017) Behavioural, modeling, and
electrophysiological evidence for supramodality in human metacognition. J Neurosci.

Flavell JH (1979) Metacognition and cognitive monitoring: A new area of cognitive–
developmental inquiry. Am Psychol 34:906–911.

Fleck MS, Daselaar SM, Dobbins IG, Cabeza R (2006) Role of Prefrontal and Anterior
Cingulate Regions in Decision-Making Processes Shared by Memory and Nonmemory
Tasks. Cereb Cortex 16:1623–1630.

Fleming SM (2017) Hierarchical Bayesian estimation of metacognitive efficiency from
confidence ratings. Neurosci Consc 3:1–14.

Fleming SM, Daw ND (2017) Self-evaluation of decision-making: A general Bayesian
framework for metacognitive computation. Psychol Rev 124:91–114.

Fleming SM, Dolan RJ, Frith CD (2012a) Metacognition: computation, biology and function.
Phil Trans R Soc B 367:1280–1286.

Fleming SM, Huijgen J, Dolan RJ (2012b) Prefrontal Contributions to Metacognition in
Perceptual Decision Making. J Neurosci 32:6117–6125.

Fleming SM, Lau H (2014) How to measure metacognition. Front Hum Neurosci 8:443.

Fleming SM, Ryu J, Golfinos JG, Blackmon KE (2014) Domain-Specific Impairment in
Metacognitive Accuracy Following Anterior Prefrontal Lesions. Brain 137:2811–2822.

Fleming SM, Weil RS, Nagy Z, Dolan RJ, Rees G (2010) Relating Introspective Accuracy to
Individual Differences in Brain Structure. Science 329:1541–1543.

Galvin SJ, Podd JV, Drga V, Whitmore J (2003) Type 2 tasks in the theory of signal
detectability: Discrimination between correct and incorrect decisions. Psychon Bull Rev
10:843–876.

García-Pérez MA (1998) Forced-choice staircases with fixed step sizes: asymptotic and small-
sample properties. Vision Res 38:1861–1881.

Gehring WJ, Goss B, Coles MGH, Meyer DE, Donchin E (1993) A Neural System for Error
Detection and Compensation. Psychol Sci 4:385–390.

Gorgolewski KJ, Varoquaux G, Rivera G, Schwarz Y, Ghosh SS, Maumet C, Sochat VV,
Nichols TE, Poldrack RA, Poline J-B, Yarkoni T, Margulies DS (2015) NeuroVault.org: a
web-based repository for collecting and sharing unthresholded statistical maps of the human
brain. Front Neuroinform 9:8.

Guggenmos M, Wilbertz G, Hebart MN, Sterzer P (2016) Mesolimbic confidence signals guide
perceptual learning in the absence of external feedback. eLife 5:e13388.

Hebart MN, Görgen K, Haynes JD (2015) The Decoding Toolbox (TDT): a versatile software
package for multivariate analyses of functional imaging data. Front Neuroinform 8:88.

Hebart MN, Schriever Y, Donner TH, Haynes JD (2014) The Relationship between Perceptual
Decision Variables and Confidence in the Human Brain. Cereb Cortex 26:118–130.

Heekeren HR, Marrett S, Ruff DA, Bandettini PA, Ungerleider LG (2006) Involvement of
human left dorsolateral prefrontal cortex in perceptual decision making is independent of
response modality. Proc Natl Acad Sci USA 103:10023–10028.

Heereman J, Walter H, Heekeren HR (2015) A task-independent neural representation of
subjective certainty in visual perception. Front Hum Neurosci 9:551.

Hilgenstock R, Weiss T, Witte OW (2014) You'd Better Think Twice: Post-Decision Perceptual
Confidence. Neuroimage 99:323–331.

Holroyd CB, Yeung N, Coles MGH, Cohen JD (2005) A Mechanism for Error Detection in
Speeded Response Time Tasks. J Exp Psychol Gen 134:163–191.

Insabato A, Pannunzi M, Rolls ET, Deco G (2010) Confidence-Related Decision Making. J
Neurophysiol 104:539–547.

Kamitani Y, Sawahata Y (2010) Spatial smoothing hurts localization but not information: Pitfalls
for brain mappers. Neuroimage 49:1949–1952.

Kelemen WL, Frost PJ, Weaver CA (2000) Individual differences in metacognition: evidence
against a general metacognitive ability. Mem Cognit 28:92–107.

Kerns JG, Cohen JD, Stenger VA, Carter CS (2004) Prefrontal cortex guides context-appropriate
responding during language production. Neuron 43:283–291.

Kiani R, Shadlen MN (2009) Representation of Confidence Associated with a Decision by
Neurons in the Parietal Cortex. Science 324:759–764.

Kruschke J (2010) Doing Bayesian Data Analysis. Academic Press.

Lebreton M, Abitbol R, Daunizeau J, Pessiglione M (2015) Automatic integration of confidence
in the brain valuation signal. Nature Neurosci 18:1159–1167.

Macpherson F (2011) Introduction: Individuating the Senses. In: The Senses (Macpherson F, ed),
pp 3–42. Oxford: Oxford University Press.

Maniscalco B, Lau H (2012) A signal detection theoretic approach for estimating metacognitive
sensitivity from confidence ratings. Conscious Cogn 21:422–430.

Maniscalco B, McCurdy LY, Odegaard B, Lau H (2017) Limited Cognitive Resources Explain a
Trade-Off between Perceptual and Metacognitive Vigilance. J Neurosci 37:1213–1224.

McCurdy LY, Maniscalco B, Metcalfe J, Liu KY, de Lange FP, Lau H (2013) Anatomical
Coupling between Distinct Metacognitive Systems for Memory and Visual Perception. J
Neurosci 33:1897–1906.

Mendoza-Halliday D, Martinez-Trujillo JC (2017) Neuronal population coding of perceived and
memorized visual features in the lateral prefrontal cortex. Nat Commun 8:1–13.

Metcalfe J, Shimamura AP eds. (1994) Metacognition. Cambridge, MA: MIT Press.

Nelson DL, McEvoy CL, Schreiber TA (2004) The University of South Florida free association,
rhyme, and word fragment norms. Behav Res Methods Instrum Comput 36:402–407.

Nelson TO, Narens L (1990) Metamemory: A Theoretical Framework and New Findings. In:
The Psychology of Learning and Motivation (Bower G, ed), pp 125–173. New York:
Academic Press.

Op de Beeck HP (2010) Against hyperacuity in brain reading: spatial smoothing does not hurt
multivariate fMRI analyses? Neuroimage 49:1943–1948.

Overgaard M, Sandberg K (2012) Kinds of access: different methods for report reveal different

kinds of metacognitive access. Phil Trans R Soc B 367:1287–1296.

Poldrack RA, Baker CI, Durnez J, Gorgolewski KJ, Matthews PM, Munafò MR, Nichols TE,
Poline J-B, Vul E, Yarkoni T (2017) Scanning the horizon: towards transparent and
reproducible neuroimaging research. Nat Rev Neurosci 18:115–126.

Pouget A, Drugowitsch J, Kepecs A (2016) Confidence and certainty: distinct probabilistic
quantities for different goals. Nature Neurosci 19:366–374.

Purcell BA, Kiani R (2016) Hierarchical decision processes that operate over distinct timescales
underlie choice and changes in strategy. Proc Natl Acad Sci USA 113:E4531–E4540.

R Studio Team (2015) RStudio: Integrated Development for R. Available at:
http://www.rstudio.com.

Rahnev D, Koizumi A, McCurdy LY, D'Esposito M, Lau H (2015) Confidence Leak in
Perceptual Decision Making. Psychol Sci 26:1664–1680.

Ridderinkhof KR, Ullsperger M, Crone EA, Nieuwenhuis S (2004) The role of the medial frontal
cortex in cognitive control. Science 306:443–447.

Rounis E, Maniscalco B, Rothwell JC, Passingham RE, Lau H (2010) Theta-burst transcranial
magnetic stimulation to the prefrontal cortex impairs metacognitive visual awareness. Cogn
Neurosci 1:165–175.

Ruby E, Giles N, Lau H (2017) Finding domain-general metacognitive mechanisms requires
using appropriate tasks. bioRxiv:1–20.

Samaha J, Postle BR (2017) Correlated individual differences suggest a common mechanism
underlying metacognition in visual perception and visual short-term memory. Proc Royal
Soc B 284:20172035.

Scheffers MK, Coles M (2000) Performance monitoring in a confusing world: error-related brain
activity, judgments of response accuracy, and types of errors. J Exp Psychol Human 26:141–
151.

Schnyer DM, Verfaellie M, Alexander MP, LaFleche G, Nicholls L, Kaszniak AW (2004) A role
for right medial prefrontal cortex in accurate feeling-of-knowing judgments: evidence from
patients with lesions to frontal cortex. Neuropsychologia 42:957–966.

Shimamura AP, Squire LR (1986) Memory and Metamemory: A Study of the Feeling-of-
Knowing Phenomenon in Amnesic Patients. J Exp Psychol Learn 12:452–460.

Simons JS, Peers PV, Mazuz YS, Berryhill ME, Olson IR (2010) Dissociation Between Memory
Accuracy and Memory Confidence Following Bilateral Parietal Lesions. Cereb Cortex
20:479–485.

Sladky R, Friston KJ, Tröstl J, Cunnington R, Moser E, Windischberger C (2011) Slice-timing

effects and their correction in functional MRI. Neuroimage 58:588–594.

Tang H, Yu H-Y, Chou C-C, Crone NE, Madsen JR, Anderson WS, Kreiman G (2016) Cascade
of neural processing orchestrates cognitive control in human frontal cortex. eLife 5:e12352.

Vo VA, Li R, Kornell N, Pouget A, Cantlon JF (2014) Young Children Bet on Their Numerical
Skills: Metacognition in the Numerical Domain. Psychol Sci 25:1712–1721.

Wilson M (1988) MRC Psycholinguistic Database: Machine-usable dictionary, version 2.00.
Behav Res Methods Instrum Comput 20:6–10.

Yokoyama O, Miura N, Watanabe J, Takemoto A, Uchida S, Sugiura M, Horie K, Sato S,
Kawashima R, Nakamura K (2010) Right frontopolar cortex activity correlates with
reliability of retrospective rating of confidence in short-term recognition memory
performance. Neurosci Res 68:199–206.

TABLES

Table 1. Univariate fMRI analysis - judgment-related activity interacted with domain.
Significant activations at cluster-defining threshold $P<0.001$, corrected for multiple comparisons
at $P_{FWE}<0.05$. Conjunction of significant activations at cluster-defining threshold $P<0.001$,
uncorrected, of Memory (C>F) and Perception (C>F) contrasts. See Figure 3B. C=confidence,
F=follow

Contrast	Label	Voxels at $P<0.001$	P_{FWE} cluster-corrected	Peak z-score	Peak voxel MNI coordinates	Laterality
Memory (C > F) > Perception (C > F)	Cerebellum	70	0.015	5.17	3, -58, -25	L/R
	Insula	109	0.001	4.89	-33, -10, -7	L
	Posterior cingulate, precuneus	84	0.006	4.29	3, -58, 23	L/R
	Post-central gyrus, BA3	99	0.002	4.25	-45, -31, 62	L
	Hippocampus, parahippocampal gyrus, fusiform area	100	0.002	4.13	-21, -37, -16	L
	Thalamus	66	0.019	4.10	9, -25, -7	R
	Middle and anterior cingulate gyrus, SMA, BA24 & 32	194	<0.001	4.09	-6, 5, 32	L/R
	Inferior frontal gyrus, BA47	61	0.026	4.05	-42, 20, -4	L
Conjunction Memory (C>F) ∩ *Perception (C>F)*	Cingulate gyrus, BA32	12			6, 32, 29	R
	Insula	7			45, 11, -7	R

Table 2. Univariate fMRI analysis - confidence level-related activity interacted with domain.
Significant activations at cluster-defining threshold $P<0.001$, corrected for multiple comparisons at $P_{FWE}<0.05$. Conjunction of significant activations at cluster-defining threshold $P<0.001$, uncorrected, of Memory (M) and Perception (P) contrasts of positive and negative correlations with confidence level. See Figure 3F.

Contrast	Label	Voxels at $P<0.001$	P_{FWE} cluster-corrected	Peak z-score	Peak voxel MNI coordinates	Laterality
Memory > Perception	Precuneus, BA7	93	0.003	4.21	33, -70, 20	R
Conjunction (+M ∩ +P)	Precentral & postcentral gyri, BA6, 4, 3	167			-30, -25, 44	L
	Post-central gyrus	27			-27, -46, 59	L
	SMA, BA6	21			-3, -10, 50	L/R
	Ventral striatum	16			3, 11, 7	L/R
	Cerebellum	7			9, -58, -13	R
	Post-central gyrus	5			-48, -22, 44	R
Conjunction (-M ∩ -P)	Middle frontal gyrus	29			45, 26, 20	R
	Pre-SMA, BA8	19			0, 14, 50	L/R

982 **Table 3. Judgment-related activity obtained from whole-brain searchlight classification**
983 **analyses.** Significant activations at cluster-defining threshold *P*<0.001, corrected for multiple
984 comparisons at P_{FWE}<0.05. See Figure 4C.
985

Classification	Label	Voxels at $P<0.001$	P_{FWE} cluster-corrected	Peak *z*-score	Peak voxel MNI coordinates	Laterality
Across-domain	Insula/IFG	592	0.001	4.31	-33, 23, 5	L
	SFG & BA9 dACC/pre-SMA	928	<0.001	4.29 4.19 4.01	24, 53, 38 -12, 14, 41 12, 44, 23	R L R
	Supramarginal gyrus, BA 40	207	0.039	3.93	-51, -55, 29	L
	IFG/Insula/STG	275	0.016	3.61	48, 5, -13	R
Within-perception	Superior, Middle, Medial, Inferior FG, dACC, pre-SMA, BA 8, 10, 32	4699	<0.001	5.10	-12, 14, 59	L/R
	Parietal cortex, precuneus, supramarginal gyrus, BA 7, 40	1141	<0.001	4.30	51, -46, 44	R
	Precuneus, BA 40	339	0.010	4.21	-36, -46, 47	L
Within-memory	Middle & Superior FG, BA 9, 10	325	0.008	4.54	39, 41, 38	R
	Lingual gyrus, cuneus, calcarine	510	0.001	4.53	9, -91, 2	R
	Superior FG, dACC, pre-SMA	1066	<0.001	4.33	6, -4, 62	L/R
	Middle, Inferior FG, BA 9, 10, 45, 46	1003	<0.001	4.09	-42, 38, 2	L

Table 4. Confidence level-related activity obtained from whole-brain searchlight classification analyses. Accuracy maps were masked to exclude visuomotor-related activity (see Figure 4D). Significant activations at cluster-defining threshold $P<0.001$, corrected for multiple comparisons at $P_{FWE}<0.05$. See Figure 4F.

Classification	Label	Voxels at $P<0.001$	P_{FWE} cluster-corrected	Peak z-score	Peak voxel MNI coordinates	Laterality
Across-domain	Inferior FG, ventral striatum, ACC, BA 11, 32	2434	<0.001	5.20	-21, 44, 2	L/R
	Superior and middle temporal gyri	176	<0.001	4.99	-57, -52, 20	L
	Middle temporal gyrus, anterior cerebellum	1193	<0.001	4.92	3, -46, -34	R
	Middle cingulate gyrus	46	0.017	4.85	-6, -10, 47	L/R
	Superior temporal gyrus	142	<0.001	4.68	66, -7, 5	R
	Precuneus, BA 7, 19	543	<0.001	4.68	-12, -61, 65	L/R
	Superior temporal gyrus	110	<0.001	4.68	-42, 26, -28	L
	Posterior cerebellum	96	<0.001	4.54	-9, -85, -22	L
	SMA, BA 6	84	0.001	4.53	-9, -10, 62	L/R
	Superior FG, dACC, pre-SMA	482	<0.001	4.39	-3, 11, 56	L/R
	Post-central gyrus	186	<0.001	4.33	-57, -19, 23	L
	Middle FG	143	<0.001	4.28	36, 5, 26	R
	Fusiform and parahippocampal gyri	63	0.003	4.27	36, -19, -34	R
	Middle cingulate cortex	64	0.003	4.25	0, -31, 53	L/R
	Posterior cerebellum	53	0.008	4.10	-48, -58, -37	L
	Inferior FG	38	0.039	3.84	27, 23, -25	R
Within-perception	Superior FG, dACC/pre-SMA	185	0.032	3.88	-6, 29, 47	L/R
Within-memory	Inferior and middle FG, insula	503	<0.001	4.35	57, 23, 14	R
	dACC, pre-SMA	211	0.021	3.79	-9, 2, 47	L/R