Building a genome browser with GIVE

AUTHORS

Xiaoyi Cao[1,2], Zhangming Yan[1,2], Qiuyang Wu[1,2], Alvin Zheng[1], Sheng Zhong[1,2]*

[1] Department of Bioengineering, [2] 4D Nucleome Network Organizational Hub, University of California San Diego, La Jolla, CA, USA 92093

* Correspondence: szhong@ucsd.edu

ABSTRACT

Genome browsers that manage, communicate and visualize data have greatly facilitated genomics research. Here, we present an open source programming library, called GIVE, that allows anyone with HTML programming experience to build custom genome browser websites or apps. With a few lines of codes, one can add to a personal webpage an interactive genome browser that host custom data. This portable library encapsulates novel data communication and data visualization technologies, including new data structures and new memory management methods that enable efficient data transfer between the data-hosting website and internet browsers. GIVE is available at: http://www.givengine.org/.

INTRODUCTION

Genome browsers have greatly facilitated genomics research (Zhou et al. 2011; Li et al. 2016; Tyner et al. 2017; Wang et al. 2017). However, establishing a genome browser on the internet requires very specific expertise. Large amounts of research grants are used on creating genome browser platforms for releasing datasets produced by national and international consortiums. We created the open source GIVE programming library to simplify such efforts. GIVE enables nearly all people with programming experience, including high-school students, to build custom genome browsers. The web developer only needs rudimentary knowledge of mySQL and HTML to use GIVE. With approximately 20 lines of codes, the developer can publish a genome browser hosting diverse types of genomic datasets including RNA sequencing, ChIP sequencing, and genome interaction datasets. This simplicity of use came from encapsulation of advanced computing and software technologies, as well as new data structures and data visualization technologies developed by the GIVE development team.

RESULTS

Overview of the GIVE library

GIVE is composed of two major components, that is the database component and the webpage component. The web developer uses the database component with mySQL to create two data tables, one holding genome annotation and the other holding custom genomic datasets (tracks) (Figure S1A). The developer uses the webpage component by inserting HTML tags to a web page, resulting in display of desired genomic regions with annotation and genomic data in web browsers (Figure S1B). Different HTML tags in the GIVE library provides flexibility for the developer to builder a variety of genome browsers, for examples a single-cell transcriptome website (Biase et al. 2014) (https://singlecell.givengine.org/), an epigenome website (The ENCODE Project Consortium 2012; Yue et al. 2014) (https://encode.givengine.org/, Figure S2), an genome interaction website (Mourad et al. 2014) (https://mcf7.givengine.org/, Figure 1), and an RNA-chromatin interaction website (Sridhar et al. 2017) (https://margi.givengine.org/, Figure 2).

Using the website hosting single-cell transcriptomes (https://singlecell.givengine.org/) as an example, we describe the process of building a genome browser with GIVE by a line by line pseudocode (Table S1). This process involves 1) creating a database for the reference genome and specifying the chromosome number and sizes, 2) creating two track annotation tables, one holding the data type for each track, and the other holding other track metadata, 3) loading the data tracks with data and metadata, and 4) creating a website and inserting HTML tags to display the data.

Without additional coding, the website is automatically equipped with a few interactive features. These features were enabled by JavaScript codes that were encapsulated within the GIVE's HTML tags. Visitors to this website can input new genome coordinates (Figure S3A), choose any subset of data tracks to display (Figure S3B), or change genome coordinates by dragging the coordinates to left or right by mouse (Figure S3C) or zoom in or out the genome by scrolling the mouse wheel while the mouse pointer is on top of the genome coordinate area (Figure S3C).

Two layer display of genome interaction data

GIVE implements a two layer display strategy for visualization of genome interaction data. In this display format, two genomic coordinates are plotted in parallel (central panel of Figure 1, Panels B and C of Figure 2). Interactions between genomic regions are displayed as links of correspondent genomic regions between the top and bottom coordinates. When intensity values are associated with the links, the intensities are displayed in a red (large) to green (small) color scale (central panel, Figure 1). This two layer display strategy has two advantages. First, the top and the bottom coordinates can cover different genomic regions, making it flexible to visualize long range interactions (Figure 1). Users can shift or zoom the top and the bottom coordinates independently, making it easy to visualize for example interactions from the XIST locus (RNA end, Figure 2B-C) to the entire X chromosome (DNA end, Figure 2B-C). This two layer design also makes it intuitive to display asymmetric interactions, for example interactions from RNA (top lanes, Figure 2) to DNA (bottom lanes, Figure 2).

New data structures for transfer and visualization of genomic data

We developed two data structures for optimal speed in transferring and visualizing genomic data. These data structures and their associated technologies are essential to GIVE. However, all the technologies described in this section are behind the scene. A website developer who uses GIVE does not have to recognize the existence of these data structures.

We will introduce the rationales for developing the new data structures by a use scenario. When a user browses a genomic region, all genome annotation and data tracks within this genomic region should be transferred from the web server to the user's computer. At this moment, only the data within this genomic region require transfer and display (Figure 3A). Next, the user shifts the genomic region to the left or right. Ideally, the previous data in user's computer should be re-utilized without transferring again, and only the new data in the additional genomic region should be transferred. After data transfer, the previous data and the new data in user's computer should be combined (Figure 3B).

Next, the user zooms out. This action changes the resolution of genome. It is unnecessary to transfer and infeasible to display data at the previous granularity. At this point, the program should adjust the granularity of the already transferred data, and then transfer additional data at the new granularity (Figure 3C). When the user zooms in, the program would adjust to finer granularity, and transfer data at this resolution (Figure 3D). In summary, what is needed is a multiscale data container that can add or remove data from both sides of a genomic window.

To substantiate the above described multiscale data container, we developed two data structures named Oak and Pine. Oak handles sparse data tracks such as genome annotation, gene tracks, peak tracks, and interaction regions (BED, interaction data). Pine handles dense data track in bigWig format (Kent et al. 2010)). Once the user changes the viewing area, Oak and Pine automatically adjust to the optimal tree structure for holding the data in the viewing area, which may involve change of data granularity, change of tree depths, adding or merging nodes, and rearrangement node assignment to branches. These operations minimize data transfer over the internet as well as the amount of data loaded in computer memory.

To optimize the use of memory, we developed an algorithm for removing obsolete data from the memory ("withering"). When the data stored in Oak or Pine nodes have not been accessed by the user for a long time, data in these nodes will be dumped and memory is recycled.

METHODS

System requirements

Both mySQL and PHP have to be available on the data server. Follow GIVE manual for installation of these prerequisites if necessary. The website (HTML file) can be placed on any server, including but not necessarily to be the data server.

Installation

GIVE does not require downloading or installation. Inserting the two following HTML lines with reference to the URL of GIVE library will import the entire GIVE library to your website (Lines 1, 2).

```
<script src="https://www.givengine.org/libWC/webcomponents-lite.min.js"></script>          (Line 1)
```

```
<link rel="import" href="https://www.givengine.org/lib/chart-controller/chart-controller.html">          (Line 2)
```

To display genomics data, the web developer can use either `<chart-controller>` tag or `<chart-area>` tag. The `<chart-controller>` tag will display track data as well as genome navigation features such as shifting, zooming (Figure S3C). For example, adding the following line in addition to the two line above would create a website similar to that in Figure S3 (Line 3).

```
<chart-controller title-text="Single-cell RNA-Seq Genome Browser" group-id-list='["genes", "singleCell",
"customTracks"]' num-of-subs="1"></chart-controller>          (Line 3)
```

Here, the title-text attribute sets the title text of your website. The `<chart-area>` tag will display the track data without metadata controls such as track selection buttons and coordinate input box, while retaining some interactive capacities including dragging and zooming. This option provides the developer greater flexibility for website design. In addition, the `<chart-area>` tag can be used in mobile apps, resulting in insertion of genome tracks to mobile apps.

Data types

The current release of GIVE supports BED and bigWig files. GIVE also accepts genome interaction data stored in BED format (see GIVE Manual).

The following technologies are wrapped inside the GIVE library. Website developers who uses GIVE do not have to understand them or even knowing their existence.

Query

A query is issued when the user views any genomic region (query region). A new query is issued when the user changes the genomic region. A query induces two actions, which are data retrieval and display of data.

Oak, a data structure

A data structure called Oak is developed to effectively load and transfer a subset of data in BED format. The subset is defined as continuous genomic region within a chromosome. Oak is a type of tree data structures, with nodes defined as follows.

A node is composed of a list of key-value pairs and a set of attributes. A key is a pair of starting and ending genomic coordinates, termed left key and right key, respectively. When populated with data, a node keeps the data for a genomic region defined by the first left key and the last right key. The keys in a node partition the genomic region into non-overlapping sub-regions. A node can be either a branch node or a leaf node. Their differences lie in the values. A branch node is a node where the values are other nodes. A leaf node is a node where each value is a set of two lists of data points (Figure S4). Each data point is a row of a BED file. When populated with data, the first list contains all the rows in the BED file where the start position matches the left key. The second list contains all the rows where the start and the end positions cover (span across) the left key. A value in a leaf node can also be empty. Leaf nodes with empty values are used to mark the genomic regions outside the query region.

Creating an Oak instance, populating data, and updating Oak

An Oak instance will be created, populated with data, or get updated in response to a query. These actions accomplish data transfer from server to user's computer. Only the data within the queried region will be transferred. Hereafter we will refer an Oak instance as an Oak.

When the query region is on a new chromosome, an Oak will be created as follows. Every unique start position in the BED file that is contained within the query region is used to create a leaf node. The genomic regions on queried chromosome but outside the query region are inserted as pairs of keys and empty values (placeholders) to the nodes with the nearest keys. The leaf nodes are ordered by their first left keys and sequentially linked by their pointers. A root node is created with all the leaf nodes are its children. This initial tree is fed into a self-balancing algorithm (Bayer and McCreight 1972; Comer 1979) to construct a weight balanced tree, thus finishes the construction of an Oak.

When the query region is on a previously queried chromosome, the query region will be compared with the Oak of that chromosome and the overlapping region will be identified. The data of the overlapping region are already loaded in the Oak and therefore for the purpose of saving time this should not be loaded again. The data in the rest of the query region will be loaded to the Oak. This is done by first creating a leaf node for every additional unique start position, removing the placeholder key-value pairs, and adding new placeholder key-value pairs for the rest of the chromosome. The weight balancing algorithm (Bayer and McCreight 1972) is invoked again to re-balance this Oak. The weight balancing step prepares the Oak for efficient response to future queries.

Pine, a data structure

A data structure called Pine is developed to effectively load and transfer a subset of data in bigWig format. The subset is defined as continuous genomic region within a chromosome. Pine can

automatically determine the data granularity, which avoids transferring data at a higher than necessary resolution. The resolution of displayed data is limited by the number of pixels on the screen. Pine instances are always constructed to the appropriate depth and match the limit of the resolution.

A node is composed of a list of key-value pairs and a set of attributes. The attributes are the same as that of Oak nodes, except for having one additional attribute, called data summary. The data summary includes the following metrics for this node (the genomic region defined by the first left key and the last right key of this node): the number of bases, sum of values (summing over every base), sum of squares of the values, maximum value, and minimum value. A key is a pair of starting and ending genomic coordinates, termed left key and right key, respectively. The keys in a node partition the genomic region into non-overlapping sub-regions. A node can be either a branch node or a leaf node. Their differences lie in the values. A branch node is a node where the values are other nodes (Figure S5A). A leaf node is a node where each value is a list of data points (Figure S5B). Each data point is a row (binary format) of a bigWig file.

A note in Pine can have an empty key-value list and an empty data summary, and in this case we call it a placeholder node.

Creating a Pine instance, populating data, and updating Pine

A Pine is created when a query to a new chromosome is issued. A Pine is created with the following steps. First, the depth of the Pine tree is calculated as:

$$Tree\ depth = Ceiling\ (log_n(chromosome\ length) - log_n(resolution)) \qquad \text{(Equation 1)}.$$

The limit of the resolution (length of genomic region per pixel) is the total length the queried genomic region (viewing area) divided by the number of horizontal pixels, namely the width of the SVG element in JavaScript.

Next, a root node is created with keys covering the entire chromosome, where the query region is contained within. Until reaching the calculated depth, for any node that overlaps with the query region, create a fixed number (n, n=20 in current release) of child nodes by equal partitioning its genomic region. If any of the created child node does not overlap with the query region, use a placeholder node. For each node, point the pointer to the "right hand" node at the same depth. Thus, a Pine is created. This Pine has not loaded with actual data.

To load data, every leaf node issues a request to retrieve the summary data of its covered region (between the first left key and the last right key), which will be responded by a PHP function wrapped within GIVE. This function returns summary data between the input coordinates from the bigWig file. After filling the summary data for all nodes at the deepest level, all parent nodes will be filled, where the summary data are calculated from the summary data of their child nodes. This process continues until reaching the root node.

A Pine will be updated when a new query partially overlaps with a previous query. In this case, the new depth (d2) is calculated using Equation 1. This depth (d2) reflects the new data granularity. If d2 is greater than the previous depth, extend the Pine by adding placeholder nodes until d2 is

reached. From root to depth d2-1, if any placeholder node overlaps with the query region, partition it by creating n child nodes. If any of the newly created child node does not overlap with the query region, use a placeholder node. For any newly created node, point the pointer to the "right hand" node at the same depth. At this step the Pine structure is updated into proper depth. Finally, at depth d2, retrieve summary data for every non-placeholder node that has not had summary data. Update the summary data of their parent nodes until reaching the root. In this way, only the new data within the query region that had not been transferred before will get transferred.

Memory management

We developed a memory management algorithm called "withering". Every time a query is issued, this algorithm is invoked to dump the obsolete data, which are not used in the previous 10 queries. "Withering" works as follows. All nodes are added with a new integer attribute called 'life span'. When a node is created, its life span is set to 10. Every time a query is issued, all nodes overlapping with the query region as well as all their ancestral nodes get their life span reset to 10. The other nodes that do not overlap with the query region get their life span reduced by 1. All the nodes with life span equals 0 are replaced by placeholder nodes.

DISCUSSION

The GIVE library is designed to reduce the needs of specialized knowledge and programming time for building web based genome browsers. GIVE is open source software. The open source nature allows the community at large to contribute to enhancing GIVE. The name GIVE (Genome Interaction Visualization Engine) was given when this project started with a smaller goal. Although it has grown into a more general purpose library, we have decided to keep the acronym.

An important technical consideration is efficient data transfer between the server and user's computers. This is because users typically wish to get instant response when browsing data. To this end, we developed several technologies to optimize the speed of data transfer. The central idea is in three folds, that are 1) only transfer the data in the query region, and 2) minimize repeated data transfer by reusing previously transferred data, and 3) only transfer data at the necessary resolution. To implement these ideas, we developed two new approaches to index the genome, and formalized these approaches with two new data structures, named Oak and Pine.

The Oak and Pine are indexing systems for sparse data (BED) and dense data (bigWig), respectively. BED data typically store genomic segments that have variable lengths. Given this particular feature, we did not index the genome base-by-base but rather developed a new strategy (Oak) to index variable-size segments. The bigWig files contain base-by-base data, which for a large genomic region can become too slow for web browsing. We therefore designed the Pine data structure that can automatically assess and adjust data granularity, which exponentially cut down unnecessary data transfer.

ADDITIONAL INFORMATION

GIVE website is at http://www.givengine.org/, which provides samples websites, GIVE demo, and GIVE manual.

ACKNOWLEDGEMENT

We thank the open source community especially authors of the Polymer programming library (Polymer Authors 2017). This work is funded by NIH U01CA200147 and DP1HD087990.

REFERENCES

Bayer R, McCreight EM. 1972. Organization and maintenance of large ordered indexes. *Acta Informatica* **1**(3): 173-189.

Biase FH, Cao X, Zhong S. 2014. Cell fate inclination within 2-cell and 4-cell mouse embryos revealed by single-cell RNA sequencing. *Genome Research* **24**(11): 1787-1796.

Comer D. 1979. Ubiquitous B-Tree. *ACM Comput Surv* **11**(2): 121-137.

Kent WJ, Zweig AS, Barber G, Hinrichs AS, Karolchik D. 2010. BigWig and BigBed: enabling browsing of large distributed datasets. *Bioinformatics* **26**(17): 2204-2207.

Li R, Liu Y, Li T, Li C. 2016. 3Disease Browser: A Web server for integrating 3D genome and disease-associated chromosome rearrangement data. *Scientific reports* **6**: 34651.

Mourad R, Hsu PY, Juan L, Shen C, Koneru P, Lin H, Liu Y, Nephew K, Huang TH, Li L. 2014. Estrogen induces global reorganization of chromatin structure in human breast cancer cells. *PloS one* **9**(12): e113354.

Polymer Authors. 2017. Polymer. https://www.polymer-project.org/.

Sridhar B, Rivas-Astroza M, Nguyen TC, Chen W, Yan Z, Cao X, Hebert L, Zhong S. 2017. Systematic Mapping of RNA-Chromatin Interactions In Vivo. *Current Biology* **27**(4): 602-609.

The ENCODE Project Consortium. 2012. An integrated encyclopedia of DNA elements in the human genome. *Nature* **489**(7414): 57-74.

Tyner C, Barber GP, Casper J, Clawson H, Diekhans M, Eisenhart C, Fischer CM, Gibson D, Gonzalez JN, Guruvadoo L et al. 2017. The UCSC Genome Browser database: 2017 update. *Nucleic Acids Research* **45**(D1): D626-D634.

Wang Y, Zhang B, Zhang L, An L, Xu J, Li D, Choudhary M, Li Y, Hu M, Hardison R et al. 2017. The 3D Genome Browser: a web-based browser for visualizing 3D genome organization and long-range chromatin interactions. *bioRxiv*.

Yue F Cheng Y Breschi A Vierstra J Wu W Ryba T Sandstrom R Ma Z Davis C Pope BD et al. 2014. A comparative encyclopedia of DNA elements in the mouse genome. *Nature* **515**(7527): 355-364.

Zhou X, Maricque B, Xie M, Li D, Sundaram V, Martin EA, Koebbe BC, Nielsen C, Hirst M, Farnham P et al. 2011. The Human Epigenome Browser at Washington University. *Nat Meth* **8**(12): 989-990.

FIGURE LEGENDS

Figure 1. Screenshot of a custom genome browser hosting epigenome and genome interaction datasets. The top genomic coordinate covers the entire chromosome 17 (chr17:1-81195210). The first three data tracks from the top are RNA-seq, H3K27ac ChIP-seq, Pol2 ChIP-seq data in MCF-7 cells, shown corresponding to the top genomic coordinate. The bottom genomic coordinate at the shows chr17:45000000-55000000. The bottom three data tracks are RNA-seq, H3K27ac ChIP-seq, Pol2 ChIP-seq data shown corresponding to the bottom coordinate. The Hi-C interaction data in the center panel shows Hi-C derived links between the genomic regions (top coordinate) to other genomic regions (bottom coordinate). The strengths of the Hi-C derived genomic interactions are plotted in color scale, with red being strongest and green being weakest.

Figure 2. A custom website hosting genome-wide RNA-DNA interaction datasets. Panels from top to bottom are (A) genome coordinates (chrX:73500000-74500000) and Genes, (B) RNA-DNA interaction data in human embryonic (H9) stem cells, with the RNA end (top) and the DNA end (bottom) shown with different resolutions (coordinate bars), (C) RNA-DNA interaction data in human embryonic kidney (HEK) cells, with the RNA end (top) and the DNA end (bottom) shown with different resolutions (coordinate bars), (D) genes and genome coordinates. Red arrow points to the genomic location of the Xist gene, where no RNA was produced in H9 (B) but plenty of RNA was produced and interact with X chromosome is HEK (C). Data were produced by the MARGI technology (Bharat et al., 2017).

Figure 3. Scenarios for browser use. A) Displaying a segment of the genome. While no data is stored in cache (blank blocks), only those within the queried region needs to be fetched from the server (colored blocks) and is stored in cache for later use; B) Shifting display window. Only the part not in cache needs to be fetched from the server (colored blocks) and merged in cache; C) Zooming out. Existing cache data are used to recalculate new cache at a coarser granularity level, after which non-overlapping data are requested; D) Zooming in. Because no cached data exists at a finer granularity level, all data within the queried region needs to be fetched at that level.

FIGURES

Figure 1

Figure 2

Figure 3