2   EMERGING TREND IN VISION SCIENCE

3   Deep learning: Using machine learning

4   to study biological vision

Najib J. Majaj[1] and Denis G. Pelli[1,2]

[1]Center for Neural Science and [2]Department of Psychology, New York University

ABSTRACT

Today many vision-science presentations employ machine learning and especially "deep

learning", one of the more recent and successful variants. Many neuroscientists use machine

learning to decode neural responses. Many perception scientists try to understand how living

organisms recognize objects. To them, deep neural networks offer several benchmark

accuracies for recognition of learned stimuli. Originally machine learning was inspired by the

brain. Today, machine learning is used as a statistical tool to decode brain activity. Tomorrow,

deep neural networks might become our best model of brain function. This brief overview of the

use of machine learning in biological vision touches on its strengths, weaknesses, milestones,

controversies, and current directions. Here, we hope to help vision scientists assess what role

machine learning should play in their research.

INTRODUCTION

What does machine learning offer to biological-vision

scientists? Machine-learning was developed as a tool for

automated classification, optimized for accuracy.

Physiologists use it to identify stimuli based on neural

activity. Physiologists and psychophysicists are starting to

consider deep learning as a model for object recognition

by human and nonhuman primates (Cadieu et al., 2014;

Ziskind et al., 2014; Yamins et al., 2014; Khaligh-Razavi &

Kriegeskorte, 2014; Testolin, Stoianov, & Zorzi, 2017). We

suppose that most of our readers have heard of machine

learning but are wondering whether it would be useful in

their own research. We begin by describing some of its

pluses and minuses.

PLUSES: WHAT IT'S GOOD FOR

Deep learning is very popular (Fig. 1). Is it just a fad? At

the very least, machine learning is a powerful tool for

interpreting biological data. For computer vision, the old

paradigm was: feature detection, followed by

segmentation, and then grouping (Marr, 1982). With

machine learning tools, the new paradigm is to just define

the task and provide a set of labeled examples, and the

algorithm builds the classifier. Unlike the handcrafted

pattern recognition (including segmentation and

GLOSSARY

Machine learning is a computer algorithm that learns how to perform a task directly from examples, without a human providing explicit instructions or rules for how to do so. Correctly labeled examples are provided to the learning algorithm, which is then "trained" (i.e. its parameters are gradually adjusted) to be able to perform the task correctly on its own and generalize to unseen examples.

Deep learning is a newly successful and popular version of machine learning that uses backprop neural networks with multiple hidden layers. The 2012 success of AlexNet, then the best machine learning network for object recognition, was the tipping point. It is now ubiquitous in the internet. The idea is to have each layer of processing perform successively more complex computations on the data to give the full "multi-layer" network more expressive power. The drawback is that it is much harder to train multi-layer networks (Goodfellow et al. 2016). Deep learning ranges from discovering the weights of a multilayer network to parameter learning in hierarchical belief networks. Note that the complexity of deep learning may be unwarranted for simple problems that are well handled by, e.g. SVM. Try shallow networks first, when they fail, go deep.

grouping) popular in the 70's and 80's, machine-learning

algorithms are generic, with little domain-specificity. They

replace hand-engineered feature detectors with filters that

can be learned from the data. Advances in the mid 90's in

machine learning made statistical learning theory useful

for practical classification, e.g. handwriting recognition

(LeCun et al., 1989; Vapnik, 1999).

Machine learning allows a neurophysiologist to decode

neural activity without knowing the receptive fields (Seung

& Sompolinsky,1993; Hung et al., 2005). Machine learning

shifts the emphasis from how the cells encode to what

they encode, i.e. what that code tells us about the

stimulus. Mapping a receptive field is the foundation of

neuroscience (beginning with Weber's 1834/1996

mapping of tactile "sensory circles"), but many young

scientists are impatient with the limitations of single-cell

recording: looking for minutes or hours at how one cell

responds to each of perhaps a hundred different stimuli.

New neuroscientists are the first generation for whom it is

patently clear that characterization of a single neuron's

receptive field, which was invaluable in the retina and V1,

fails to characterize how higher visual areas encode the

stimulus. Statistical learning techniques reveal "how

neuronal responses can best be used (combined) to

Neural nets are computing systems inspired by biological neural networks that learn tasks by considering examples.

Supervised learning refers to any algorithm that accepts a set of labeled stimuli — a training set — and returns a classifier that can label stimuli similar to those in the training set.

Unsupervised learning works without labels. It is less popular, but of great interest because labeled data are scarce while unlabeled data are plentiful. Without labels, the algorithm discovers structure and redundancy in the data.

Cost function. A function that assigns a real number representing cost to a candidate solution, i.e. a set of weights. Solving by optimization means minimizing cost.

Gradient descent: An algorithm that minimizes cost by incrementally changing the parameters in the direction of steepest descent of the cost function.

inform perceptual decision-making" (Graf, Kohn, Jazayeri,

& Movshon, 2010). The simplicity of the machine

decoding can be a virtue as it allows us to discover what

can be easily read-out (e.g. by a single downstream

neuron) (Hung et al. 2005). Achieving psychophysical

levels of performance in decoding a stimulus object's

identity and location from the neural response shows that

the measured neural performance has all the information

needed for the subject to do the task (Majaj et al. 2015;

Hong et al. 2016).

For psychophysics, Signal Detection Theory (SDT) proved

that the optimal classifier for a known signal in white noise

is a template matcher (Peterson, Birdsall, & Fox, 1954;

Tanner & Birdsall, 1958). Of course, SDT solves only a

simple version of the general problem of object

recognition, which includes variation in viewing conditions

and diverse objects within a category (e.g. a chair can be

any object that affords sitting). SDT introduces the very

useful idea of a mathematically defined ideal observer,

providing a reference for human performance (e.g.

Geisler, 1989; Pelli et al., 2006). However, one drawback

is that it doesn't incorporate learning. Deep learning, on

the other hand, provides a pretty good observer that

learns, which may inform studies of human learning.

Convexity: A problem is convex if there are no local minima other than the global minimum (or minima if there are several equally good solutions). This guarantees that gradient-descent will converge to a global minimum. There might be more than one global minimum, with equal cost, e.g. in problems with symmetric solutions.

Generalization is how well a classifier performs on new, unseen examples that it did not see during training.

Cross validation assesses the ability of the network to generalize, from the data that it trained on, to new data.

Backprop, short for "backward propagation of errors", is widely used to apply gradient-descent learning to multi-layer networks. It uses the chain rule from calculus to iteratively compute the gradient of the cost function for each layer.

Hebbian learning and spike-timing-dependent plasticity (*STDP*). According to Hebb's rule, the efficiency of a synapse increases after correlated pre- and post-synaptic activity. In other words, neurons that fire together, wire together (Löwel & Singer, 1992).

These networks might reveal the constraints imposed by

the training set on learning. Further, unlike SDT, deep

neural networks cope with the complexity of real tasks. It

can be hard to tell whether behavioral performance is

limited by the set of stimuli, their neural representation, or

the observer's decision process (Majaj et al. 2015).

Implications for classification performance are not readily

apparent from direct inspection of families of stimuli and

their neural responses. SDT specifies optimal

performance for classification of known signals but does

not tell us how to generalize beyond a training set.

Machine learning does.

106 MINUSES: COMMON COMPLAINTS

Some biologists point out that neural nets do not match

what we know about neurons (e.g., Crick, 1989; Rubinov,

2015). Biological brains learn on the job, while neural

networks need to converge before they can be used. A

state-of-the-art deep neural network needs five thousand

labelled object images per category to match human

recognition accuracy (Goodfellow et al., 2016). But

children and adults need only a hundred labelled letters of

an unfamiliar alphabet to reach the same accuracy as

fluent native readers (Pelli et al. 2006). In particular, it is

not clear, given what we know about neurons and neural

plasticity, whether a backpropagation network can be implemented using biologically plausible

---

Support Vector Machine (SVM) is a learning machine for classification. SVMs generalize well. An SVM can quickly learn to perform a nonlinear classification using what is called the "kernel trick", mapping its input into a high-dimensional feature space (Cortes & Vapnik, 1999).

Convolutional neural networks (ConvNets) have their roots in the Neocognitron (Fukushima 1980) and are inspired by the simple and complex cells described by Hubel and Wiesel (1962). ConvNets apply backprop learning to multilayer neural networks based on convolution and pooling (LeCun et al., 1989; LeCun et al., 1990; LeCun et al., 1998).

circuits (but see Mazzoni et al., 1991, and Bengio et al., 2015). However, there are several

promising efforts to implement more biological plausible learning rules, e.g. spike-timing-

dependent plasticity (Mazzoni et al., 1991; Bengio et al., 2015; Sacramento, Costa , Bengio, &

Senn 2017).

Unlike the biologists' desire to model, engineers and computer scientists, while inspired by

biological vision, focus on what works. To this, one might counter that every biological model is

an abstraction and can be useful even while failing to capture all the details of the living

organism.

Some physiologists note that decoding neural activity to recover the stimulus is interesting and

useful but falls short of explaining what the neurons do.

Some visual psychophysicists note some salient differences between performance of human

observers and deep networks on tasks lke object recognition and image distortion (Ullman et al.

2016; Berardino et al. 2017).

Some biological modelers complain that neural nets have alarmingly many parameters. Deep

neural networks continue to be opaque. Before neural-network modeling, a model was simpler

than the data it explained. Deep neural nets are typically as complex as the data, and the

solutions are hard to visualize (but see Zeiler & Fergus, 2013). However, while the training sets

and learned weights are long lists, the generative rules for the network (the computer programs)

are short. Traditionally, having very many parameters has often led to overfitting, i.e. a failure to

generalize beyond the training set, but the breakthrough is that deep-learning networks with a

huge number of parameters nevertheless generalize well.

Some cognitive psychologists dismiss deep neural networks as unable to "master some of the

basic things that children do, like learning the past tense of a regular verb" (Marcus et al., 1992).

Some statisticians worry that rigorous statistical tools are being displaced by machine learning,

which lacks rigor (Friedman, 1998; Matloff, 2014, but see Breiman, 2001; Efron & Hastie, 2016).

Assumptions are rarely stated. There are no confidence intervals on the solution. However,

performance is typically cross-validated, showing generalization, and it has been proven that

convex networks can compute posterior probability (e.g. Rojas, 1996). Furthermore, machine

learning and statistics seem to be converging to provide a more general perspective on

probabilistic inference that combines complexity and rigor.

These current limitations drive practitioners to enhance the scope and rigor of deep learning.

But bear in mind that some of the best classifiers in computer science were inspired by

biological principles (Rosenblatt, 1957; 1958; Rumelhart et al., 1986; LeCun, 1985; LeCun et al.

1989; LeCun et al. 1990; Riesenhuber & Poggio, 1999; and see LeCun, Bengio, Hinton 2015).

Some of those classifiers are now so good that they occasionally exceed human performance

and might serve as rough models for how biological systems classify (e.g. Yamins, et al. 2014;

Khaligh-Razavi & Kriegeskorte, 2014; Ziskind, Hénaff, LeCun, & Pelli, 2014; Testolin, Stoianov,

& Zorzi, 2017).

MATHEMATICS VS. ENGINEERING

The history of machine learning has two threads: mathematics and engineering. In the

mathematical thread, two statisticians, Fisher and later Vapnik, developed mathematical

transformations to uncover categories in data, and proved that they give unique answers. They

assumed distributions and proved convergence.

In the *engineering* thread, a loose coalition of psychologists, neuroscientists, and computer

scientists (e.g. Turing, Rosenblatt, Minsky, Fukushima, Hinton, Sejnowski, LeCun, Poggio,

Bengio) sought to reverse-engineer the brain to build a machine that learns. Their algorithms

are typically applied to stimuli with unknown distributions and lack proofs of convergence.

MILESTONES IN CLASSIFICATION

1936: Linear discriminant analysis

1953: Machine learning

1958: Perceptron

1969: Death of the perceptron

1974: Backprop

1980: Neocognitron

1987: NETtalk

1989: ConvNets

1995: Support Vector Machine (SVM)

2006: Backprop, revived

2012: Deep learning

1936: Linear discriminant analysis. Fisher (1936) introduced linear discriminant analysis to

classify two species of iris flower based on four measurements per flower. When the distribution

of the measurements is normal and the covariance matrix between the measurements is known,

linear discriminant analysis answers the question: Supposing we use a single-valued function to

classify, what linear function $y = w_1 x_1 + w_2 x_2 + w_3 x_3 + w_4 x_4$, of four measurements x_1, x_2, x_3, x_4

made on flowers, with free weights w_1, w_2, w_3, w_4, will maximize discrimination of species?[1]

Linear classifiers are great for simple problems for which the category boundary is a hyperplane

in a small number of dimensions. However, complex problems like object recognition typically

require more complex category boundaries in a large number of dimensions. Furthermore, the

distributions of the features are typically unknown and not necessarily normal.

Cortes & Vapnik (1995) note that the first algorithm for pattern recognition was Fisher's optimal

decision function for classifying vectors from two known distributions. Fisher solved for the

optimal classifier in the presence of gaussian noise and known covariance between elements of

the vector. When the covariances are equal, this reduces to a linear classifier. The ideal

template matcher of signal detection theory is an example of such a linear classifier (Peterson et

al., 1954). This fully specified simple problem can be solved analytically. Of course, many

important problems are not fully specified. In everyday perceptual tasks, we typically know only

a "training" set of samples and labels.

1953: Machine learning. The first developments in machine learning were to play chess and

checkers. "Could one make a machine to play chess, and to improve its play, game by game,

profiting from its experience?" (Turing, 1953). Arthur Samuel (1959) defined *machine learning*

as the "Field of study that gives computers the ability to learn without being explicitly

programmed."

1958: Perceptron. Inspired by physiologically measured receptive fields, Rosenblatt (1958)

showed that a very simple neural network, the perceptron, could learn to classify from training

samples. Perceptrons combined several linear classifiers to implement piecewise-linear

---

[1] Linear discriminant analysis is an outgrowth of regression which has a much longer history. Regression is the optimal least-squares linear combination of given functions to fit given data and was applied by Legendre (1805) and Gauss (1809) to astronomical data to determine the orbits of the comets and planets around the sun. The estimates come with confidence intervals and the fraction of variance accounted for, which rates the goodness of the explanation.

separating surfaces. The perceptron learns the weights to use in a linear combination of feature-

detector outputs. The perceptron transforms the stimulus into a binary feature vector and then

applies a linear classifier to the feature vector. The perceptron is piecewise linear and has the

ability to learn from training examples without knowing the full distribution of the stimuli. Only the

final layer in the perceptron learns.

1969: Death of the perceptron. However, it quickly became apparent that the perceptron and

other single-layer neural networks cannot learn tasks that are not linearly separable, i.e. cannot

solve problems like connectivity (Are all elements connected?) and parity (Is the number of

elements odd or even?); people solve these readily (Minsky & Papert, 1969). On this basis

Minsky and Papert announced the death of artificial neural networks.

1974: Backprop. The death of the perceptron showed that learning in a one-layer network was

too limited. This impasse was broken by the introduction of the backprop algorithm, which

allowed learning to propagate through multiple-layer neural networks. The history of backprop is

complicated (see Schmidhuber, 2015). The idea of minimization of error through a differentiable

multi-stage network was discussed as early as the 1960s (e.g. Bryson, Denham, & Dreyfus,

1963). It was applied to artificial neural networks in the 1970s (e.g. Werbos, 1974). In the 1980s,

efficient backprop first gained recognition, and led to a renaissance in the field of artificial neural

network research (LeCun, 1985; Rumelhart, Hinton, & Williams, 1986). During the 2000s

backprop neural networks fell out of favor, due to four limitations (Vapnik, 1999): **1. *No proof of***

convergence. Backprop uses gradient descent. Gradient descent with a nonconvex error

function with multiple minima is only guaranteed to find a local, not the global minimum of the

error function. This has long been considered a major limitation, but Yann LeCun et al. (2015)

claim that it hardly matters in practice in current implementations of deep learning. **2. *Slow.***

Convergence to a local minimum can be slow due to the high dimensionality of the weight

space. **3. *Poorly specified.*** Backprop neural networks had a reputation for being ill-specified,

an unconstrained number of units and training examples, and a step size that varied by

problem. "Neural networks came to be painted as slow and fussy to train [,] beset by voodoo

parameters and simply inferior to other approaches." (Cox & Dean, 2014). **4. *Not biological*.**

Lastly, backprop learning may not to be physiological: While there is ample evidence for

Hebbian learning (increase of a synapse's gain in response to correlated activity of the two cells

that it connects), such changes are never propagated backwards, beyond the one synapse, to a

previous layer. **5. *Inadequate resources***. With hindsight it is clear that backprop in the 80's was

crippled by limited computing power and lack of large labeled datasets.

1980: Neocognitron, the first convolutional neural network. Fukushima (1980) proposed and

implemented the Neocognitron, a hierarchical, multilayer artificial neural network. It recognized

stimulus patterns (deformed numbers) despite small changes in position and shape.

1987: NETtalk, the first impressive backprop neural network. Sejnowski et al. (1987) reported

the exciting success of NETtalk, a neural network that learned to convert English text to speech:

"*The performance of NETtalk has some similarities with observed human performance. (i) The*

learning follows a power law. (ii) The more words the network learns, the better it is at

generalizing and correctly pronouncing new words. (iii) The performance of the networks

degrades very slowly as connections in the network are damaged: no single link or processing

unit is essential. (iv) Relearning after damage is much faster than learning during the original

training…"

1989: ConvNets. Yann LeCun and his colleagues combined convolutional neural networks with

backprop to recognize handwritten characters (LeCun et al., 1989; LeCun et al., 1990). This

network was commercially deployed by AT&T, and today reads millions of checks a day

(LeCun, 1998). Later, adding half-wave rectification and max pooling greatly improved its

accuracy in recognizing objects (Jarrett et al., 2009).

1995: Support Vector Machine (SVM). Cortes & Vapnik (1995) proposed the support vector

network, a learning machine for binary classification problems. SVMs generalize well and are

free of mysterious training parameters. Many versions of the SVM are convex (e.g. Lin, 2001).

2006: Backprop, revived. Hinton & Salakhutdinov (2006) sped up backprop learning by

unsupervised pre-training. This helped to revive interest in backprop. In the same year, a

supervised backprop-trained convolutional neural network set a new record on the famous

MNIST handwritten-digit recognition benchmark (Ranzato et al., 2006).

2012: Deep learning. Geoff Hinton says, "It took 17 years to get deep learning right; one year

thinking and 16 years of progress in computing, praise be to Intel." (Cox & Dean, 2014; LeCun,

Bengio, & Hinton, 2015). It is not clear who coined the term "deep learning".[2] In their book, *Deep*

Learning Methods and Applications, Deng & Yu (2014) cite Hinton et al. (2006) and Bengio

(2009) as the first to use the term. However, the big debut for deep learning was an influential

paper by Krizhevsky et al. (2012) describing AlexNet, a deep convolutional neural network that

classified 1.2 million high-resolution images into 1000 different classes, greatly outperforming

previous state-of-the-art machine learning and classification algorithms.

CONTROVERSIES

The field is growing quickly, yet certain topics remain hot. For proponents of deep learning, the

ideal network is composed of simple elements and learns everything from the training data. On

the other extreme, computer vision scientists argue that we know a lot about how the brain

recognizes objects that we can engineer into the networks before learning (e.g. gain control and

normalization). Some engineers look to the brain only to copy strengths of the biological

solution, others think there are useful clues in its limitations as well (e.g. crowding).

---

[2] The idea of "deep learning" is not exclusive to machine learning and neural networks (e.g. Dechter, 1986)

Is deep learning the best solution for all visual tasks? Deep learning is not the only thing in

the vision scientist's toolbox. Object recognition as a visual task has been very useful in vision

research because it is an objective task that is easily scored as right or wrong, is essential in

daily life, and captures some of the magic of seeing. Deep neural nets solve it, albeit with a

million parameters. Another interesting task is detection of image distortion. Currently a simple

model implementing gain-control normalization performs this much better than deep networks

do (Berardino et al. 2017). Scientists, like the brain, use whatever tool works best.

Unproven convexity. A problem is convex if there are no local minima other than the global

minimum (or minima if there are several equally good solutions). This guarantees that gradient-

descent will converge to a global minimum. As far as we know, classifiers that give inconsistent

results are not useful. Conservation of a solution across seeds and algorithms is evidence for

convexity. For some combinations of stimuli, categories, and classifiers, convexity can be

proved. For others, empirical tests can provide qualified assurance that the solution is a global

minimum. Many widely used networks are not convex, but still give mostly consistent answers

(LeCun, Bengio, & Hinton, 2015). In machine learning, kernel methods, including learning by

SVMs, have the advantage of easy-to-prove convexity, at the cost of limited generalization. In

the 1990s, SVMs were popular because they guaranteed fast convergence even with a large

number of training samples (Cortes & Vapnik, 1995). Thus, when the problem is convex, the

quality of solution is assured, and one can rate implementations by their demands for size of

network and training sample. Deep neural networks, on the other hand, generalize well, but are

not convex.

Shallow vs. deep networks. The field's imagination has focused alternately on shallow and

deep networks, beginning with the Perceptron in which only one layer learned, to backprop,

which allowed multiple layers and cleared the hurdles that doomed the Perceptron. Then SVM,

with its single layer, sidelined the multilayer backprop. Today multilayer deep learning reigns;

Krizhevsky et al. (2012) attributed the success of their network to its 8-layer depth; it performed

worse with fewer layers.

Supervised vs. unsupervised. Learning algorithms for a classifier can be supervised or not,

i.e. need labels for training, or don't. Today most machine learning is *supervised* (LeCun,

Bengio, & Hinton, 2015). The images are labeled (e.g. "car" or "face"), or the network receives

feedback on each trial from a cost function that assesses how well its answer matches the

image's category. In *unsupervised* learning, no labels are given. The algorithm processes

images, typically to minimize error in reconstruction, with no extra information about what is in

the (unlabeled) image. A cost function can also reward decorrelation and sparseness (e.g.

Olshausen and Field, 1996). This allows learning of image statistics and has been used to train

early layers in deep neural networks. Human learning of categorization is sometimes done with

explicitly named objects — "Look at the tree!" — but more commonly the feedback is implicit.

Consider reaching your hand to raise a glass of water. Contact informs vision. On specific

benchmarks, where the task is well-defined and labeled examples are available, supervised

learning can excel (e.g. AlexNet), but unsupervised learning may be more useful when few

labels are available.

CURRENT DIRECTIONS

What does deep learning add to the vision-science toolbox? Deep learning is more than

just a souped-up regression (Marblestone et al., 2016). Like Signal Detection Theory (SDT), it

allows us to see more in our behavioral and neural data. In the 1940's, Norbert Wiener and

others developed algorithms to automate and optimize signal detection and classification. A lot

of it was engineering. The whole picture changed with the SDT theorems, mainly the proof that

the maximum-likelihood receiver is optimal for a wide range of simple tasks (Peterson et al.,

1954). In white noise a traditional receptive field computes the likelihood of the presence of a

signal matching the receptive field weights. It was exciting to realize that the brain contains 10^{11}

likelihood computers. Later work added prior probability, for a Bayesian approach. Tanner &

Birdsall (1958) noted that, when figuring out how a biological system does a task, it is very

helpful to know the optimal algorithm and to rate observed performance by its *efficiency* relative

to the optimum. SDT solved detection and classification mathematically, as maximum likelihood.

It was the classification math of the sixties. Machine learning is the classification math of today.

Both enable deeper insight into how biological systems classify. In the old days we used to

compare human and ideal classification performance (Pelli et al. 2006). Today, we also

compare human and machine learning. Deep learning is the best model we have today for how

complex systems of simple units can recognize objects as well as the brain does. Deep

learning, i.e. learning by multi-layered neural networks using backprop, is not just AlexNet but

also includes ConvNets and other architectures of trained artificial neural networks. Several labs

are currently comparing patterns of activity of particular layers to neural responses in various

cortical areas of the mammalian visual brain (Yamins et al. 2014; Khaligh-Razavi &

Kriegeskorte, 2014).

What computer scientists can learn from psychophysics. Computer scientists build

classifiers to recognize objects. Vision scientists, including psychologists and neuroscientists,

study how people and animals classify in order to understand how the brain works. So, what do

computer and vision scientists have to say to each other? Machine learning accepts a set of

labelled stimuli to produce a classifier. Much progress has been made in physiology and

psychophysics by characterizing how well biological systems can classify stimuli. The

psychophysical tools (e.g. threshold and signal detection theory) developed to characterize

behavioral classification performance are immediately applicable to characterize classifiers

produced by machine learning (e.g. Ziskind, Hénaff, LeCun, & Pelli, 2014; Testolin, Stoianov, &

Zorzi, 2017).

Psychophysics. "Adversarial" examples have been presented as a major flaw in deep neural

networks. These slightly doctored images of objects are misclassified by a trained network,

even though the doctoring has little effect on human observers. The same doctored images are

similarly misclassified by several different networks trained with the same stimuli (Szegedy, et

al., 2013). Humans too have adversarial examples. Illusions are robust classification errors. The

blindspot-filling-in illusion is a dramatic adversarial example in human vision. While viewing with

one eye, two finger tips touching in the blindspot are perceived as one long finger. If the image

is shifted a bit so that the fingertips emerge from the blindspot the viewer sees two fingers.

Neural networks lacking the anatomical blindspot of human vision are hardly affected by the

shift. The existence of adversarial examples is intrinsic to classifiers trained with finite data,

whether biological or not. In the absence of information, neural networks interpolate and so do

biological brains. Psychophysics, the scientific study of perception, has achieved its greatest

advances by studying classification errors (Fechner, 1860). Such errors can reveal "blindspots".

Stimuli that are physically different yet indistinguishable are called *metamers*. The systematic

understanding of color metamers revealed the three dimensions of human color vision (Palmer,

1777; Young, 1802; Helmholtz, 1860). In recent work, many classifiers have been trained solely

with the objects they are meant to classify, and thus will classify everything as one of those

categories, even doctored noise that is very different from all of the images. It is important to

train with sample images that represent the entire test set.

CONCLUSION

Machine learning is here to stay. Deep learning is better than the "neural" networks of the

eighties. Machine learning is useful both as a model for perceptual processing, and as a

decoder of neural processing, to see what information the neurons are carrying. The large size

of the human cortex is a distinctive feature of our species and crucial for learning. It is

anatomically homogenous yet solves diverse sensory, motor, and cognitive problems. Key

biological details of cortical learning remain obscure, even if they ultimately preclude backprop,

the performance of current machine learning algorithms is a useful benchmark.

ACKNOWLEDGEMENTS

Thanks to Yann LeCun for helpful conversations. Thanks to Aenne Brielmann, Kaitie Holman,

Laura Suciu, and Avi Ziskind for helpful comments on the manuscript. We thank both reviewers,

Nikolaus Kriegeskorte and anonymous, for many constructive suggestions. DGP was supported

by NIH grant R01 EY027964.

REFERENCES

Bengio, Y. (2009). Learning deep architectures for AI. *Foundations and Trends in Machine Learning*, 2(1), 1–127.

Bengio, Y., Lee, D. H., Bornschein, J., Mesnard, T., & Lin, Z. (2015). Towards biologically plausible deep learning. *arXiv preprint arXiv:1502.04156*.

Berardino, A., Laparra, V., Ballé, J., & Simoncelli, E. (2017). Eigen-Distortions of Hierarchical Representations. In *Advances in Neural Information Processing Systems* (pp. 3533-3542).

Breiman, L. (2001). Statistical modeling: The two cultures (with comments and a rejoinder by the author). *Statistical science*, *16*(3), 199-231.

Bryson, A. E., Denham, W. F., & Dreyfus, S. E. (1963). Optimal programming problems with inequality constraints. *AIAA journal*, 1(11), 2544-2550.

Cadieu, C. F., Hong, H., Yamins, D. L., Pinto, N., Ardila, D., Solomon, E. A., Majaj, N. J. & DiCarlo, J. J. (2014). Deep neural networks rival the representation of primate IT cortex for core visual object recognition. *PLoS computational biology*, *10*(12), e1003963.

Caporale, N., & Dan, Y. (2008). Spike timing-dependent plasticity: a Hebbian learning rule. *Annu. Rev. Neurosci.*, *31*, 25-46.

Cox, D. D., & Dean, T. (2014). Neural networks and neuroscience-inspired computer vision. *Current Biology*, 24(18), R921-R929.

Crick, F. (1989). The recent excitement about neural networks. Nature, 337(6203), 129.

Dechter, R. (1986). Learning while searching in constraint-satisfaction-problems. In *Proceedings of the Fifth AAAI National Conference on Artificial Intelligence* (pp. 178-183). AAAI Press.

Deng, L., & Yu, D. (2014). Deep learning: methods and applications. *Foundations and Trends® in Signal Processing*, *7*(3–4), 197-387.

Efron, B., & Hastie, T. (2016). *Computer Age Statistical Inference: Algorithms, Evidence, and Data Science* (Vol. 5). Cambridge University Press.

Fechner, GT (1860). Elements of psychophysics. Breitkopf & Härtel, Leipzig (reprinted in 1964 by Bonset, Amsterdam); German translation by HE Adler (1966): Elements of psychophysics.

Fisher, R. A. (1922). The goodness of fit of regression formulae, and the distribution of regression coefficients. *Journal of the Royal Statistical Society*, 85(4), 597-612. doi:10.2307/2341124.

Friedman, J. H. (1998). Data mining and statistics: What's the connection? *Computing Science and Statistics*, *29*(1), 3-9

Fukushima, K. (1980). Neocognitron: A self-organizing neural network model for a mechanism of pattern recognition unaffected by shift in position. *Biological cybernetics*, *36*(4), 193-202.

Galton, F. (1877). Typical laws of heredity. *Nature*, 15(389), 512-514.

Gauss, C.F. (1809). *Theoria motus corporum coelestium in sectionibus conicis solem ambientium*. Hamburg: Friedrich Perthes und I. H. Besser.

Geisler, W. S. (1989). Sequential ideal-observer analysis of visual discriminations. *Psychological review*, *96*(2), 267.

Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep learning* (Vol. 1). Cambridge: MIT press.

Helmholtz, H. von (1860/1925). *Handbuch der physiologischen Optik*, volume II. Leopold Voss, Leipzig, third edition. Translated as *Treatise on Physiological Optics*, volume II. The Optical Society of America, 1925. Edited by James P. C. Southall.

Hinton, G. E., Osindero, S., & Teh, Y. W. (2006). A fast learning algorithm for deep belief nets. *Neural computation*, 18(7), 1527-1554.

Hubel, D. H., & Wiesel, T. N. (1962). Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *The Journal of physiology*, *160*(1), 106-154.

Hong, H., Yamins, D. L., Majaj, N. J., & DiCarlo, J. J. (2016). Explicit information for category-orthogonal object properties increases along the ventral stream. *Nature neuroscience*, *19*(4), 613.

Hung, C. P., Kreiman, G., Poggio, T., & DiCarlo, J. J. (2005). Fast readout of object identity from macaque inferior temporal cortex. *Science*, *310*(5749), 863-866.

Ivakhnenko, A. G. (1971). Polynomial theory of complex systems. *IEEE Transactions on Systems, Man and Cybernetics*, 4, 364-378.

Ivakhnenko, A. G. & Lapa, V. G. (1965). *Cybernetic Predicting Devices*. CCM Information Corporation.

Jarrett, K., Kavukcuoglu, K., & LeCun, Y. (2009). What is the best multi-stage architecture for object recognition? In *IEEE 12th International Conference on Computer Vision*. pp. 2146-2153.

Khaligh-Razavi, S. M., & Kriegeskorte, N. (2014). Deep supervised, but not unsupervised, models may explain IT cortical representation. *PLoS computational biology*, *10*(11), e1003915.

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems,* pp. 1097-1105.

LeCun, Y. (1985). Une procedure d'apprentissage pour reseau a seuil asymmetrique (A learning scheme for asymmetric threshold networks). In *Proceedings of Cognitiva* 85, Paris, France. pp. 599-604.

LeCun, Y., Boser, B., Denker, J. S., Henderson, D., Howard, R. E., Hubbard, W., & Jackel, L. D.
(1989). Backpropagation applied to handwritten zip code recognition. *Neural computation*, *1*(4),
541-551.

LeCun, Y., Boser, B. E., Denker, J. S., Henderson, D., Howard, R. E., Hubbard, W. E., & Jackel,
L. D. (1990). Handwritten digit recognition with a back-propagation network. In *Advances in*
neural information processing systems (pp. 396-404).

LeCun, Y., Bottou, L., Bengio, Y., & Haffner, P. (1998). Gradient-based learning applied to
document recognition. *Proceedings of the IEEE*, *86*(11), 2278-2324.

LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*, 521(7553), 436-444.

Legendre, A. M. (1805). *Nouvelles méthodes pour la détermination des orbites des comètes*
(No. 1). F. Didot.

Lin, C. J. (2001). On the convergence of the decomposition method for support vector
machines. *IEEE Transactions on Neural Networks*, *12*(6), 1288-1298.

Lowel, S., & Singer, W. (1992). Selection of intrinsic horizontal connections in the visual cortex
by correlated neuronal activity. *Science*, *255*(5041), 209.

Majaj, N. J., Hong, H., Solomon, E. A., & DiCarlo, J. J. (2015). Simple learned weighted sums of
inferior temporal neuronal firing rates accurately predict human core object recognition
performance. *Journal of Neuroscience*, *35*(39), 13402-13418.

Marcus, G. F., Pinker, S., Ullman, M., Hollander, M., Rosen, T. J., Xu, F., & Clahsen, H. (1992).
Overregularization in language acquisition. *Monographs of the society for research in child*
development, i-178.

Marr, D. (1982). *VIsion: A computational investigation into the human representation and*
processing of visual information. San Francisco, CA: Freeman and Company.

Matloff, N. (2014). Statistics: Losing Ground to CS, Losing Image Among Students. *Revolutions*.
August 26, 2014. http://blog.revolutionanalytics.com/2014/08/statistics-losing-ground-to-cs-losing-image-among-
students.html

Marblestone, A. H., Wayne, G., & Kording, K. P. (2016). Toward an integration of deep learning
and neuroscience. *Frontiers in computational neuroscience*, *10*.

Mazzoni, P., Andersen, R. A., & Jordan, M. I. (1991). A more biologically plausible learning rule
for neural networks. *Proceedings of the National Academy of Sciences*, *88*(10), 4433-4437.

Minsky, M., & Papert, S. (1988). *Perceptrons: An Introduction to Computational Geometry*.
Cambridge, MA: MIT press.

Olshausen, B. A., & Field, D. J. (1996). Emergence of simple-cell receptive field properties by
learning a sparse code for natural images. *Nature*, *381*(6583), 607.

Palmer, G. (1777). *Theory of Colour and Vision*, London: Leacroft.

Pearson, K., Yule, G. U., Blanchard, N., & Lee, A. (1903). The law of ancestral heredity.
Biometrika, 2(2), 211-236.

Pelli, D. G., Burns, C. W., Farell, B., & Moore-Page, D. C. (2006). Feature detection and letter
identification. *Vision research*, *46*(28), 4646-4674.

Peterson, W. W. T. G., Birdsall, T., & Fox, W. (1954). The theory of signal detectability.
Transactions of the IRE professional group on information theory, 4(4), 171-212.

Ranzato, M. A., Huang, F. J., Boureau, Y. L., & LeCun, Y. (2007). Unsupervised learning of
invariant feature hierarchies with applications to object recognition. In *2007 IEEE conference on*
computer vision and pattern recognition, pp. 1-8.

Ranzato, M. A., Poultney, C., Chopra, S., & LeCun, Y. (2007). Efficient learning of sparse
representations with an energy-based model. In *Proceedings of NIPS*.

Riesenhuber, M., & Poggio, T. (1999). Hierarchical models of object recognition in
cortex. *Nature neuroscience*, *2*(11), 1019-1025.

Rojas, R. (1996). A short proof of the posterior probability property of classifier neural networks.
Neural Computation, *8*(1), 41-43.

Rosenblatt, F. (1958), The Perceptron: A Probabilistic Model for Information Storage and
Organization in the Brain, *Psychological Review*, 65, 6, pp. 386–408.

Rubinov, M. (2015). Neural networks in the future of neuroscience research. *Nature Reviews*
Neuroscience.

Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-
propagating errors. *Nature*, 323, 533-536. doi:10.1038/323533a0.

Samuel, A. L. (1959). Some studies in machine learning using the game of checkers. *IBM*
Journal of research and development, *3*(3), 210-229.

Samuel, A. L. (1967). Some studies in machine learning using the game of checkers. II—recent
progress. *IBM Journal of research and development*, *11*(6), 601-617.

Schmidhuber, J. (2015). Deep learning in neural networks: An overview. *Neural networks*, *61*,
85-117.

Sejnowski, T. J., & Rosenberg, C. R. (1987). Parallel networks that learn to pronounce English
text. *Complex systems*, 1(1), 145-168.

Seung, H. S., & Sompolinsky, H. (1993). Simple models for reading neuronal population codes.
Proceedings of the National Academy of Sciences, *90*(22), 10749-10753.

Szegedy, C., Zaremba, W., Sutskever, I., Bruna, J., Erhan, D., Goodfellow, I., & Fergus, R.
(2013). Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*.

Tanner Jr, W. P., & Birdsall, T. G. (1958). Definitions of *d'* and *η* as psychophysical measures.
The Journal of the Acoustical society of America, 30(10), 922-928.

Testolin, A., Stoianov, I., & Zorzi, M. (2017). Letter perception emerges from unsupervised deep
learning and recycling of natural image features. *Nature Human Behaviour*, *1*(9), 657.

Turing, A.M. (1953). 'Digital computers applied to games'. in 'Faster than thought', ed. B.V.
Bowden, London 1953. Published by Pitman Publishing.

Ullman, S., Assif, L., Fetaya, E., & Harari, D. (2016). Atoms of recognition in human and
computer vision. *Proceedings of the National Academy of Sciences*, *113*(10), 2744-2749.

Vapnik, V. (2013). *The nature of statistical learning theory*. Springer Science & Business Media.

Weber, E. H. (1834/1996). *EH Weber on the tactile senses*. Psychology Press. Translated by
Helen E. Ross from E.H Weber (1834) *De Tactu.*

Werbos, P. (1974). *Beyond regression: New tools for prediction and analysis in the behavioral*
sciences. PhD thesis, Harvard University.

Yamins, D. L., Hong, H., Cadieu, C. F., Solomon, E. A., Seibert, D., & DiCarlo, J. J. (2014).
Performance-optimized hierarchical models predict neural responses in higher visual
cortex. *Proceedings of the National Academy of Sciences*, *111*(23), 8619-8624.

Young, T. (1802). The Bakerian Lecture. On the theory of light and colours, *Philosophical*
Transactions of the Royal Society of London 92, 12-48. doi: 10.1098/rstl.1802.0004

Yule, G. U. (1897). On the theory of correlation. *Journal of the Royal Statistical Society*, 60(4),
812-854.

Zeiler, M. D., & Fergus, R. (2013). Visualizing and understanding convolutional networks. arXiv
preprint arXiv:1311.2901.

Ziskind, A.J., Hénaff, O., LeCun, Y., & Pelli, D.G. (2014) The bottleneck in human letter
recognition: A computational model. Vision Sciences Society, St. Pete Beach, Florida, May 16-
21, 2014, 56.583. http://f1000.com/posters/browse/summary/1095738

Figure 1. Top: The frequency of appearance of each of five terms — "linear classifier", "perceptron", "support vector machine", "neural net" and "backprop" — in books indexed by Google in each year of publication. Frequency is reported as a fraction of all instances of that number of words (1,2, or 3) normalized by the number of books published that year (ngram / year / books published). The figure was created using Google's n-gram viewer (https://books.google.com/ngrams), which contains a yearly count of n-grams found in sources printed between 1500 and 2008. **Bottom:** Numbers represent worldwide search interest relative to the highest point on the chart for the given year for the term "deep learning" (as reported by https://trends.google.com/trends/).