Neck muscle spindle noise biases reaches in a multi-sensory integration task

Parisa Abedi Khoozani[1,2], Gunnar Blohm[1,2,3]

[1]Centre for Neuroscience Studies, Queen's University, Kingston, Ontario, Canada
[2]Canadian Action and Perception Network (CAPnet), Toronto, Ontario, Canada
[3]Association for Canadian Neuroinformatics and Computational Neuroscience (CNCN), Kingston, Ontario, Canada

Abstract

Reference frame Transformations (RFTs) are crucial components of

sensorimotor transformations in the brain. Stochasticity in RFTs has been

suggested to add noise to the transformed signal due to variability in

transformation parameter estimates (e.g. angle) as well as the stochastic nature

of computations in spiking networks of neurons. Here, we varied the RFT angle

together with the associated variability and evaluated the behavioral impact in a

reaching task that required variability-dependent visual-proprioceptive multi-

sensory integration. Crucially, reaches were performed with the head either

straight or rolled 30deg to either shoulder and we also applied neck loads of 0 or

1.8kg (left or right) in a 3x3 design, resulting in different combinations of

estimated head roll angle magnitude and variance required in RFTs. A novel 3D

stochastic model of multi-sensory integration across reference frames was fitted

to the data and captured our main behavioral findings: (1) neck load biased head

angle estimation across all head roll orientations resulting in systematic shifts in

reach errors; (2) Increased neck muscle tone led to increased reach variability,

due to signal-dependent noise; (3) both head roll and neck load created larger

angular errors in reaches to visual targets away from the body compared to

reaches toward the body. These results show that noise in muscle spindles and

stochasticity in general have a tangible effect on RFTs underlying reach

planning. Since RFTs are omnipresent in the brain, our results could have

implication for processes as diverse as motor control, decision making, posture /

balance control, and perception.

New & Noteworthy: We show that increasing neck muscle tone systematically

biases reach movements. A novel 3D multisensory integration across reference

frames model captures the data well and provides evidence that the brain must

have online knowledge of full body geometry together with the associated

variability to accurately plan reach movements.

Introduction

Different sensory and motor signals are encoded in different coordinates in the brain, e.g. early vision in eye/gaze-centered, primary arm proprioception in shoulder-centered. Conversions between reference frames are vital to transform signals into reference frames that are appropriate for processes as diverse as motor control, decision making, posture / balance control, and perception (Flanders et al., 1992; Buneo et al., 2002; Vetter et al., 1999; Blohm & Crawford, 2007). Previous studies have suggested that reference frame transformations (RFTs) should be regarded as stochastic processes which modulate the reliability of transformed signals (Alikhanian et al., 2015, Schlicht & Shrater, 2007; Burns & Blohm, 2010, 2011). Furthermore, several studies proposed that humans flexibly select the coordinates that minimize the effect of stochasticity (Sober & Sabes, 2005). Cue reliability-based multi-sensory integration studies have shown that stochastic RFTs affect human behavior (Schlicht & Shrater, 2007; Burns & Blohm, 2010, 2011); however, the sources of stochasticity in RFTs as well as the underlying mechanisms of how RFTs affect transformed signals remain unclear.

In order to accurately perform RFTs, the brain must have an estimate of 3D body articulation (Blohm & Crawford, 2007); i.e. an internal estimate of different body parts with regard to each other (such as eye re. head translation) as well as an estimate of joint angles (such as head/eye orientations). While the former is likely learned and does not change, the latter could stem from at least 2 sources, noisy afferent sensory signals (proprioception) and efferent copies of motor commands. Both signals are inherently variable due to the uncertainty of

sensory reading and the variability of neuronal spiking (Poisson noise). Several

studies have suggested that varying body articulation, e.g. the head roll angle,

increases the behavioral variability due to signal-dependent sensory and neural

noise affecting the RFT (Alikhanian et al., 2015; Schlicht & Shrater, 2007; Burns

& Blohm, 2010, 2011). Signal-dependent sensory noise can arise from variability

in the muscle spindle activity, the vestibular system, or both (Lechner-

Steinleitner, 1987; Scott & Loeb, 1994; Cordo et al., 2002; Sadeghi et al., 2007;

Faisal et al., 2008). Thus, larger joint angle estimates are accompanied by higher

uncertainty (Wade & Curthoys, 1997; Van Beuzekom & Van Gisbergen, 2000;

Blohm & Crawford, 2007), which results in an increased trial-to-trial variability in

the RFT.

The effect of stochastic RFTs on the reliability of transformed signals has

been studied using a multi-sensory integration task. Multisensory integration

combines different sources of sensory information to create the best possible

estimate of the state of our body within the environment in a way that is generally

well captured by Bayes-optimal integration (Stein & Meredith, 1993; Landy et al.,

1995; Atkins et al., 2001; Landy & Kojima, 2001; Kersten et al., 2004; Stein &

Stanford, 2008; Ernst & Banks, 2002; Knill & Pouget, 2004). For instance, both

visual and proprioceptive information can be combined in a reliability-weighted

fashion to estimate hand position. It is believed (weak fusion hypothesis, Clark &

Yuille, 1990) that prior to integration any signals must first be converted into a

common coordinate system; this requires a (stochastic) RFT. Within this

framework, the reliability of the transformed signal is affected by stochasticity in

RFTs (Alikhanian et al., 2015), thus modulating the multisensory integration

weights (Burns & Blohm, 2010; Burns et al., 2011). However, it is not clear how

varying multisensory weights due to stochastic RFTs affects reaching

movements to visual targets.

Here, we deployed a modified version of the standard visual-

proprioceptive integration-based reaching task (Van Beers et al., 1999; Sober &

Sabes, 2003, 2005) to systematically investigate the behavioral consequences of

biases and variability in sensory estimates used for stochastic RFTs. We asked

human participants to perform a center-out reaching task while the seen and

actual hand positions were dissociated. In addition, reaches were performed with

the head either straight or rolled 30deg to either shoulder and we also applied

neck loads of 0 or 1.8kg (left or right) in a 3x3 design. Our results demonstrate

that applying the neck load increased the variability of reach movements and

biased the reaching behavior toward the applied load in all head roll orientations.

Our prediction was that these effects on reaching behavior can be explained by a

change in multisensory integration weights due to stochastic RFTs, which

consequently enabled us to quantify the relative contribution of neck muscle

spindles to the estimation of head roll angle. To test this hypothesis, we

implemented a novel 3D stochastic model of multisensory integration across

reference frames. Our model was able to capture the pattern of behavioral data

well and allowed us to make two main conclusions: the effect of neck load on

reaching behavior can be explained by changes in multisensory weights due to

stochastic RFTs and the source of this stochasticity in RFTs is signal-dependent

noise.

Material and Method

Participants

Nine healthy humans (8 male) between 20 to 35 years of age with normal

or corrected to normal vision participated in our reaching task. They performed

their reaching with their dominant right hand. Experimental conditions were

approved by the Queen's University General Board of Ethics and all the

participants gave their written consent. Monetary compensation was provided for

participating in the experiment ($10/hour).

Apparatus

A virtual reality robotic setup (KINARM End Point Robot, BKIN

Technologies) was used for performing the center-out reaching task. Participants

stood in front of the robot while positioning their head by resting the forehead on

the robot in front of the screen and their chin on a chinrest. Participants grasped

a vertical handle attached to the robotic arm in order to reach to the viewed

target on the mirrored surface. The vision of participants' hand was occluded

using an opaque board and eye movements were tracked using embedded

technology (Eyelink 1000, SR Research). A pulley system and a helmet were

used for measuring the head roll and loading the neck (see Figure 1 A and C).

Figure 1. Apparatus- A) KINARM end point robot (BKIN technology website) arrangement. B) Visual targets were distributed evenly on a 10cm-radius circle. The hand was shifted 2.5cm either vertically or horizontally while the visual indicator stayed at the center. C) Picture of the pulley system for measuring the head roll and loading the neck, in this picture the participant had 30CW HR and neck load on the left side. The attached indicator on the helmet was used to measure the head angle.

Task Design

Participants stood in front of the robot and grasped the handle. At the

beginning of each trial, participants were instructed to position their hand on the

start position (cross) in the center of the display field. The robotic arm moved the

hand toward the center and released it when the hand was within 3 centimeter of

the central cross; a red dot representing hand position appeared at this point.

After the participant positioned the hand correctly on the cross, one of the eight

targets, distributed evenly on the circle with radius 10 cm, appeared. Participants

were instructed to move through the target quickly and accurately while keeping

their gaze fixated on the center cross. Once the participant's hand begun to

move (85 mm/s velocity threshold), the hand cursor disappeared. If they reached

the target in less than 750ms, the trial was successful and participants would

hear a successes beep, otherwise a failure beep was played indicating that the

trial had been aborted and would have to be repeated. At the end of each trial,

the center cross disappeared and participants had to wait 500ms to start the next

trial. The next trial started with the reappearance of the center cross and the

movement of the robotic arm driving the participant's hand to the start position.

This was to ensure that participants did not have visual feedback of their

previous trial's performance.

There were several different conditions in our experiment: The hand was

physically shifted randomly either up/down or left/right with respect to the visual

feedback of the hand. For example, participants would align their hand cursor to

the center cross while their actual hand position was 2.5cm left of the cross. This

discrepancy was introduced to enable us to measure the relative weighting of

vision and proprioception in the multisensory integration process, similar to the

logic employed in Sober and Sabes (2003, 5005) and Burns and Blohm (2010).

In addition, the reaching movements were performed while the participants either

kept their head straight or rolled their head 30deg toward each shoulder and

while a neck load (0 or 1.8kg) was applied to the left or right side (the value of the

weight was chosen to stimulate the same force as a 30deg head roll on neck

muscles). Combinations of different head roll (HR) and neck load (NL) conditions

are shown in Figure 2. We hypothesized that altering head roll and neck muscle

force would create a conflict for head roll estimation as well as changing the

signal-dependent noise which will affect the weights of multi-sensory integration.

Participants completed 640 trials (5 hand positions * 8 targets * 16 repetitions) for

each of the 9 combinations of head roll/neck load, for a total of 5760 trials

(640*9) in 6 one hour sessions. In order to avoid any biases due to a specific

order of experiment conditions, we employed Latin squares method to counter

balance among different experimental conditions (Jacobson & Matthews, 1996).

Figure 2. Experimental conditions.
Participants performed the reaching task under 9 different combinations of HR and NL conditions during our experiment.

Data Analysis

Hand and eye movement were captured with sampling rates of 1000Hz

and 500Hz respectively. MATLAB software was used for offline analysis: A low-

pass filter (autoregressive forward-backward filter, cutoff frequency = 50 Hz) was

used to smooth the acquired data. First and second derivative of hand position

data was calculated (using a central difference algorithm) to obtain hand velocity

and acceleration. Trials in which participants moved their eyes after the visual

target is displayed or moved their hand in a predictive direction except the target

direction were removed (3% of overall trials). The time span from when

participants started to move until their hand crossed a 9cm circle is defined as

the initial movement duration. Movements were typically straight and had very

little curvature; thus movement angle was derived through regression of data

points acquired throughout the initial movement duration. Since the visual and

proprioceptive hand position was dissociated, we defined visual movement as

the movement obtained when subtracting visual hand from target information

(red arrow, Figure 1B) and proprioceptive movement as the movement direction

obtained when subtracting proprioceptive hand position from the visual target

information (green arrow, Figure 1B). Subtracting predicted visual

(proprioceptive) movement from the measured movement angle yielded the

directional visual (proprioceptive) movement errors, which we used for our

analysis. We then used an analytical model to capture the pattern of movement

errors measured across conditions and targets (see model description below).

Statistical Analysis

An n-way repeated measure ANOVA (rm-ANOVA) was used to assess the

statistical differences (MATLAB 2013a, anovan.m) and post-Hoc analysis using

the Bonferroni criterion (MATLAB 2013a, multcompare.m) was performed to

assess the interaction between different parameters. A paired t-test (MATLAB

2013a, ttest.m) was used to assess the statistical significance in reach error

variability for different head roll and neck load conditions. In all the statistical

analysis $p < 0.001$ was considered as the criterion for statistical significance.

Model description

The goal of our model was to understand which intrinsic and extrinsic variables

were required to perform the RFTs accurately and more importantly, how

variation of such variables affects human movement behavior. In order to

understand the effect of RFTs on reach planning, we first explain the required

steps in our model to plan a reach movement. Sober and Sabes (2003) proposed

a two-step model for planning a reach movement in which first a movement plan

is calculated by subtracting the hand position from the target position. Then this

movement plan transformed to a desired change in arm angles through

performing inverse kinematics. We extended previous models (Sober & Sabes,

2003; Burns & Blohm, 2010) that considered two steps for planning a reach

movement: 1) calculating the movement plan and 2) generating the motor

command. Several neurophysiology studies suggested that the movement plan is

coded in visual (retinal) coordinates (Andersen & Buneo, 2002; Batista et al.

1999) while motor commands are coded in joint coordinates (Crawford et al.

2004). Following the same logic, in our model the two steps were performed in

two different coordinates respectively: visual and proprioceptive coordinates.

Visual information of hand and target positions were coded as retinal information

in gaze-centered coordinates, $X_h=(x_{1,h},x_{2,h})$ and $X_t=(x_{1,t},x_{2,t})$ respectively (left

panel in **Error! Reference source not found.** Figure 3), while the proprioceptive

information of initial hand position was coded as joint angles in shoulder-centered

coordinates, $(\Theta_{1,h},\Theta_{2,h})$, (right panel in Figure **Error! Reference source not**

found.3).

Figure 3. Model schematic. In order to perform the reach movement successfully, IHP is calculated in both visual and proprioceptive coordinates. In visual coordinate, IHP is computed by transforming proprioceptive information into visual coordinates. Visual and transformed proprioceptive information are weighted and combined based on Bayesian theory. A movement vector is calculated by comparing the estimated IHP and target positions. The same process takes place in proprioceptive coordinate to generate a proprioceptive IHP estimate. Using inverse kinematic, the transformed movement vector and IHP can be combined to calculate the movement plan based on the required changes in joint angles. The blue box represents the RFTs process. RFTs are performed by considering eye and head orientation as well as the translations between rotation centers of the body. The head orientation is estimated by combining visual/vestibular and neck muscle spindle information using Bayesian statistics (see Methods for details).

Reference frame transformation (Blue box Figure 3)

In order to accurately transform information between the visual and

proprioceptive coordinates the full body geometry must be taken into account

(Blohm & Crawford 2007). This is specifically important when the head is not

straight, i.e. rotating the head results in shifts of centers of rotation of the eye,

head, and shoulder relative to each other (Henriques & Crawford, 2002;

Henriques et al., 2003). To capture this, we performed a series of rotations (R)

and translations (T), formulated in equations (1) and (2) respectively.

$X_{rotated} = R * X_{original}$ (1)

Where $R = \begin{bmatrix} \cos & \sin \\ -\sin & \cos \end{bmatrix}$, > 0 holds for clock wise rotations.

$X_{translated} = X_{original} + T$ (2)

In the following section, we explain the required steps to transform hand position

from eye-centered to shoulder-centered coordinates.

Retinal-to-shoulder transformation

As it is depicted in Figure 3, in order to transform retinal-coded information

into joint-coded information the theoretically required sequential transformations

can be done by first transforming retinal to head coordinates, then from head to

shoulder and finally from should to joint coordinates (Note that this is likely

different from how the brain is performing this transformation):

1- Retinal-to-head

250              $X_{h,eye}^{v} = R_{eye} * X_{h,retinal}^{v}$ (3)

251              $X_{h,head}^{v} = R_{head} * (X_{h,eye}^{v} + T_{eye-head})$ (4)

252   In which R_{eye} and R_{head} are rotations based on eye angle and head angle

253   respectively and $T_{eye-head}$ is the translation between eye and head which

254   is the distance between the center of two eyes (eye-centered coordinate)

255   and the joint of head and neck (head centered coordinate). $X_{h,eye}^{v}$ is the

256   visual information of hand position in eye-centered coordinate: Subscript

'h' represents information related to the hand position and the following

subscript represents the related coordinate at that step. In addition, we

deployed superscripts 'v' or 'p' to dissociate if the information is originally

provided by vision or proprioception respectively. All the following

parameters have the same pattern.

2- Head-to-shoulder

263
$$X^v_{h,shoulder} = X^v_{h,head} + T_{head-shoulder} \quad (5)$$

264   Since the body was upright, a translation is sufficient to perform the

265   transformation between the shoulder and head. In our setup, the shoulder

266   was located downward and to the right of the head.

267   *3- Shoulder-to-joint*

268
$$^v_{h,joint} = A(x^0) * X^v_{h,shoulder} \quad (6)$$

In which $A(x^0)$ is the forward kinematic matrix and has the same form as

equation (7) by Burn and Blohm (2010), since our experimental

configuration is the same. In order to transform the information from joint

angle coordinates to retinal coordinates, the same procedure can be

performed only in the reverse order (since we used the same configuration

as Burns and Blohm (2010), both forward and inverse kinematic matrices

have the same format).

In addition to the full body geometry, we considered the noise of

transformation in our model. Similar to Burns and Blohm (2010), we have two

noise component resulted from the transformation: fixed transformation noise

(σ^2_{fT}) to simulate the fact that any transformation has a cost (Sober and Sabes

2005), and variable transformation noise (σ^2_{VT}) to simulate the different head

orientations and neck load conditions of our experiment (this is the same as the

variability in the estimated head angle).

Estimating head angle

As mentioned in the previous section, participants performed reaching

with different head roll and neck load conditions. Therefore, our model must

include a head angle estimation component as a crucial part of the RFTs

processes. Previous studies showed that humans combine visual, vestibular, and

neck proprioceptive information for estimating head orientation, similar to a

Bayesian optimal observer (Mergner et al., 1983, 1991, and 1997; Clemens et

al., 2011; Alberts et al., 2016). For instance, Mergner et al. (1991) demonstrated

that the stimulation of neck muscles by rotating the trunk on a fixed head caused

a sensation of head rotation and also increased the uncertainty of head position

estimation. In addition, two studies carried out in Medendorp's group

demonstrated that the noise in both vestibular and proprioceptive information

should be considered signal-dependent (Clemens et al., 2011; Alberts et al.

2016). Therefore, we used a similar principle for our head angle estimation in

RFTs processes. Thus, following the same rational, we included neck load in our

experimental condition with the goal of investigating the contribution of the

mentioned sources of information for estimating the head angle. Assuming that

each source of information has a Gaussian distribution, the head angle signal

has a Gaussian distribution as well and its mean and variance can be estimated

as follows:

$$\delta_{HA}^2 = \frac{\delta_{V/V}^2 * \delta_{NM}^2}{\delta_{V/V}^2 + \delta_{NM}^2} \qquad (7)$$

$$\mu_{HA} = \frac{\delta_{HA}^2}{\delta_{V/V}^2} * \mu_{\frac{V}{V}} + \frac{\delta_{HA}^2}{\delta_{NM}^2} * \mu_{NM} \qquad (8)$$

In which δ_{HA}^2, $\delta_{V/V}^2$, and δ_{NM}^2 are associated variability in head angle

estimation, visual/vestibular information, and neck muscle information

respectively and μ_{HA}, $\mu_{V/V}$, and μ_{NM} are the associated means in the same order.

Therefore, we also were able to extract the relative visual/vestibular vs. neck

muscle contribution in estimating head angle ($C = \frac{\delta_{NM}^2}{\delta_{V/V}^2}$).

As mentioned earlier, one of the key features of our model is including

signal dependent noise in our RFTs: The assumption is that when we roll the

head, the variability of both vestibular and neck muscle spindle signals increase

due to higher signal value. In addition, applying the neck load increases the force

on the neck muscle which results in increasing the variability of neck muscle

spindle signal. In the conditions of applying the neck load while the head is not

straight, the two forces on the neck muscle are combined in order to drive the

predicted neck muscle force. Therefore, we differentiated the variability for the

head straight and no load condition from the other head roll and neck load

conditions. Similar to Vingerhoets et al. (2008), we used a linear model to explain

the increase in variability due to increase in the signal value:

$$\delta_{V/V}^2 = \delta_{V/V,h0}^2 + head\ roll * \delta_{V/V,h \neq 0}^2 \qquad (9)$$

$$\delta_{NM}^2 = \delta_{NM,h0}^2 + mucls\ force\ from\ (HR\&NL) * \delta_{NM,h \neq 0}^2 \qquad (10)$$

In which $\delta^2_{V/V,h0}$ and $\delta^2_{NM,h0}$ are visual/vestibular and neck muscle variability for

head straight condition and $\delta^2_{V/V,h\neq0}$ and $\delta^2_{NM,h\neq0}$ are the ones for other

experimental conditions. This will result in having $\mu_{HA,h0}$ and $\mu_{HA,h\neq0}$.

At the final step, the required head angle for the transformation ($_{HA}$) is

derived by scaling the estimated head angle (μ_{HA}) (obtained by sampling from

the above Gaussian distribution) by a gain factor β: $_{HA} = \beta * \mu_{HA}$.

Multisensory integration

In order to estimate the initial hand position (IHP), visual (V) and

proprioceptive (P) information are combined using multisensory integration

principles. In our model, the multisensory integration is happening twice: once in

visual coordinates (coded in Euclidean) in order to calculate the movement

vector (MV) and once in proprioceptive coordinates (coded in joint angles) in

order to generate the motor command using inverse kinematics (INV). We

assumed that each piece of information has a Gaussian distribution (before and

after RFTs) and therefore using multivariate Gaussian statistics the mean and

covariance of the combined IHP estimated from vision (V) and proprioception (P)

in each coordinate can be written as:

$$\textstyle\sum_{IHP} = (\textstyle\sum_P^{-1} + \textstyle\sum_V^{-1})^{-1} \qquad (11)$$

$$\mu_{IHP} = \textstyle\sum_{IHP} . \textstyle\sum_P^{-1} * \mu_P + \textstyle\sum_{IHP} * \textstyle\sum_V^{-1} . \mu_V \qquad (12)$$

Where $\textstyle\sum_{IHP}$ is the covariance matrix of IHP and $\textstyle\sum_V$ and $\textstyle\sum_P$ are covariance

matrices of visual and proprioceptive information respectively. Similarly, μ_{IHP}, μ_P,

and μ_V are the mean values (in the vector format) for IHP, visual, and

proprioceptive information. Therefore, the visual weight in each of the visual and

proprioceptive coordinates is calculated as:

347
$$\alpha_{MV} = \sum_{IHP,v} * \sum_{V,v}^{-1} \quad (13)$$

348
$$\alpha_{INV} = \sum_{IHP,p} * \sum_{V,p}^{-1} \quad (14)$$

Where α_{MV} is the multisensory integration weight for visual information in

visual coordinates and α_{INV} is the multisensory weight for visual information in

proprioceptive coordinates. Where $\sum_{IHP,v}$ is the covariance matrix of IHP in visual

coordinates and $\sum_{V,v}$ is the covariance matrix of visual information in visual

coordinates. Similarly, $\sum_{IHP,p}$ is the covariance matrix of IHP in proprioceptive

coordinates and $\sum_{V,p}$ is the covariance matrix of visual information in

proprioceptive coordinates.

Final motor command and movement direction

After estimating the IHP, the desired movement vector is calculated by

subtracting the hand position from the target positon; $\Delta x = tar - \mu_{IHP,v}$. We used

the velocity command model (Sober & Sabes 2003; Burns & Blohm 2010) to

transform the desired movement vector to the required motor command:

$\dot{x} = J(\theta)J^{-1}(\theta)\Delta x$ (where $J(\theta)$ and $J^{-1}(\theta)$ have the same form as equation (16)

and (17) in Burns and Blohm 2010).

At the final step the movement direction is calculated by transforming the

movement command from Euclidean coordinates to polar coordinates using the

following equations:

366
$$r = \sqrt{x^2 + y^2} \qquad (15)$$

367
$$tan\varphi = \frac{y}{x} \qquad (16)$$

Generating quantitative model predictions

In order to generate our model predictions we used a Monte Carlo approach (Binder & Heermann, 2002); we assumed that the sensory information (visual and proprioceptive information of initial hand position, visual/vestibular and proprioceptive information of head position) can be sampled from a Gaussian distribution with a specific mean and covariance matrix. Then, the RFT procedure is performed on each sample based on sampled head roll signals to obtain the distribution of the transformed signal. The movement direction was calculated for each sample and the final movement mean and variance were calculated based on this distribution. The model code is available on Github (https://github.com/Parisaabedi/NeckMuscleLoad).

Model parameters

Based on average body physiology, upper arm and lower arm (including fist) lengths were set constant to L1 = 30 and L2 = 45 cm respectively. Shoulder location was assumed 30 cm backward from the target and 25 cm rightward of the target, the distance between eye and top of the head considered 13 cm, and the head length considered 28 cm (40 cm including the neck). IHPs and target positions were taken from the experimental data.

There were seven free parameters in the model, i.e. the variance of both proprioceptive (σ_p^2) joint angles and visual IHP (σ_v^2) - we assumed that the two dimensions in both coordinates are independent with the same variability-, the visual/vestibular vs. neck muscle spindle contribution factor (C), the variance of

head angle estimation for head straight (σ_{h0}^2), a fixed reference frame

transformation cost (σ_{fT}^2), and a variable reference frame transformation cost

(σ_{VT}^2).

As it is mentioned before, the σ_{VT}^2 is resulted from the variability in the

head angle estimation; δ_{HA}^2. By substituting $C = \frac{\delta_{NM}^2}{\delta_{VV}^2}$ in equation (7), we were

able to extract the variance of neck muscle spindles (σ_{NM}^2) and visual/vestibular

($\sigma_{V/V}^2$). Furthermore, we added an additional variance component to account for

the added variability during performing the planned movement (σ_{MV}^2).

In order to estimate the model parameters we used a standard maximum

likelihood procedure. We calculated the negative log-likelihood of the angular

reach error data to fit on the proposed model given parameter set ρ as:

$$L_\rho(\mu, \sigma^2 | y) = -(-\frac{n}{2}\ln(2\pi) - \frac{n}{2}\ln(\sigma^2) - \frac{1}{2\sigma^2}\sum_i (y_i - \mu)^2) \qquad (17)$$

Where (μ, σ^2) are the mean and variance driven from the model given the

parameter set ρ, n is the number of data points and y_i is each data point from the

experiment. It should be noted that (μ, σ^2) are calculated separately for each of

the 360 experimental conditions: 8 visual targets * 5 IHPs * 3 head rolls * 3 neck

loads. We then searched for the set of parameters which minimized the L_ρ over

the parameter space using 'fmincon.m' in MATLAB 2017. Table 1 provides the

fitting values for different model parameters for individual participants along with

confidence interval for each parameter. We added one additional parameter C,

which indicate the contribution of neck muscle information compared to

combined visual/vestibular information by dividing the first by the second.

Results

Previous work (Burns & Blohm, 2010; Schlicht & Schrater, 2007; Sober & Sabes 2003) suggests human behavior is affected by stochastic RFTs. Burns and Blohm (2010) showed that rolling the head will increase the variability of reach movements and argued that could be due to the signal dependent noise in the sensed head angles: rolling the head increases the amplitude of the sensed head angle and the associated variability accordingly. Here, our goal was to investigate the sources of stochasticity in RFTs and the effect of such stochasticity on human reaching movements. To this aim, we asked human participants to perform reaching movements while their head was either straight or rolled toward each shoulder and a neck load of 0 or 1.8kg was applied to the right or left side in a 3×3 design. The experimental logic was that applying head roll and neck load will vary the sensed head angle and the associated noise due to signal-dependent noise. Since RFTs are based on these sensed angles, applying head roll / neck load increases the stochasticity of RFTs which modulates the multisensory integration weights and thus resulting in more variable and potentially biased reaching movements compared to the condition where the head is straight and no load is applied.

General Observations

A total of 51840 trials were collected, with 1529 trials being excluded due to either eye movements or predictive hand trajectories. We used directional reach errors to determine how participants weighted their visual information vs. proprioceptive information. Directional reach error (in angular degrees) was

computed by subtracting proprioceptive (visual) hand-target direction from overall

movement direction (see Methods), where 0deg means no deviation from

proprioceptive (visual) hand-target direction. By introducing the shift in the visual

feedback of the initial hand position, a discrepancy between visual and

proprioceptive information was created and as a result, we could determine how

visual and proprioceptive information was weighted and integrated based on how

participants responded to this discrepancy.

To evaluate how humans weight visual and proprioceptive information, we

compared reach errors for each hand offset condition. In order to calculate the

reach errors, we can use either the visual hand-target direction (red line in

Figure 1B) or the actual (proprioceptive) hand-target direction (green line

in

Figure 1B). We called the first one visual reach errors and the second one

proprioceptive reach errors and used them for different sections of this

manuscript in order to show the effects more clearly. The difference in reach

462 errors among different hand offsets indicates that both visual and proprioceptive

463 information were used during reach planning. Figure 4 displays both

464 proprioceptive and visual reach error curves across target directions for different

465 initial hand position conditions for head straight and no load condition.

Figure 4. Reach error curves.

Reach errors are calculated for each target by subtracting the proprioceptive or visual hand-target direction from the performed reach movement. Solid colored lines are representing upward/rightward shifts. A,C) proprioceptive reach error curves: (A) reach errors for horizontal hand shift (green, stays the same in the rest of the manuscript) and (C) reach errors for vertical hand shift (blue, stays the same in the rest of the manuscript). B,D) visual reach error curves: (B) reach errors for horizontal shift and (D) reach errors for vertical shifts.

To quantify these weights, we fitted a previously proposed model (Sober &

Sabes 2003) to the normalized data. The data was normalized by subtracting the

0 hand offset from the other hand offsets. The model by Sober and Sabes (2003)

fits our data well (Figure 5, R-squared for pooled data across all participants was

equal to 0.91 and 0.93 respectively for the right and left panels) and confirms that

the participants used both visual and proprioceptive information to plan their

reach movement. Based on this close fit of our data to the model, we can now

use this model in a first step to investigate how head roll and neck load affects

the weighting of vision and proprioceptive information about the hand.

Figure 5. Sober and Sabes 2005 model fit on the data. The reach error curves are normalized to zero by subtracting the 0 hand offset from the other hand offsets.

Head Roll effect

Participants performed the reach-out movements for different head roll

conditions: 30deg counter clock wise (CCW), 0deg, and 30deg clock wise (CW)

head roll. In the first step we examined if the same effect reported by Burns and

Blohm (2010) could be reproduced. As the author explained changing the head

roll had two different effects on the reach error trajectories. First, the reach error

curves shifted up/down -ward and second the variability of reach errors increased

for the tilted head conditions compared to the head upright condition.

Figure 6 depicts the effect of changing HR on both reach errors and

movement variability. As it can be seen, there are both a bias effect and an

increased variability effect for altering the head orientation compared to head

straight. The n-way ANOVA with factors HR, target directions, and participants

showed a significant main effect for altering head orientation, $F(2,98) = 11.85$, p

< 0.01; and significant interaction between reaching to different targets and

different HR conditions, $F(14,98) = 5.59$, $p < 0.01$; which shows that the effect of

altering HR is different for different target directions. Bonferroni-corrected post-

hoc analyses indicated that the bias effect was significant among all the HR

conditions. Regarding movement variability, we performed a paired t-test across

all participants for each HR condition vs. no HR condition: The increase in

standard deviation due to the rolled head is significant for both sides, HR =

30deg CW vs. HR = 0: $t(8) = -3.6133$, $p < 0.01$; HR = 30deg CCW vs. HR = 0:

$t(8) = -5.6011$, $p < 0.01$. These results are consistent with the results reported by

Burns and Blohm (2010).

We also used the Sober and Sabes (2003) model to extract the weights

for different conditions. There, the visual and proprioceptive weights were the two

free parameters of the model (Sober & Sabes, 2003) which is used to estimate

the hand position, by integrating visual and proprioceptive information, in two

different stages: visual weight in the movement planning stage and

proprioceptive weight in the motor command generating stage. Therefore, the

weights can be extracted after fitting the model on the data. As it is depicted in

Figure 6, the visual weights in visual coordinates did not change very much by

varying head roll, however, the visual weight in proprioceptive coordinate

decreased for rolled head conditions. This is consistent with our hypothesis that

higher noise in RFTs results in lower reliability of transformed signals which leads

to higher weights for proprioceptive information in the proprioceptive coordinates

compared to the head straight condition.

Neck Load effect

In addition to altering the head roll a neck load (rightward, no load, or

leftward) was applied. We assumed that if the neck load was not taken into

account, there should be no difference in the reach errors between the neck load

conditions and no load condition. Alternatively, if the neck load was taken into

account in estimating head roll, then we expected to observe similar effects as

during head roll; up/down -ward shifts in reach error curves and increased

movement variability. This is because loading the neck while the head is upright

would create a discrepancy between the neck muscle spindle information and the

combined visual/proprioceptive information. In addition, due to signal dependent

noise, the neck muscle information should become less reliable when the neck is

loaded compared to the no load condition. Consequently, the sensed head angle

estimated by integrating neck muscle and visual/vestibular signal should be

biased toward the neck load and have more variability resulting in biased and

more variable movements.

As it can be seen in Figure 7(A), applying the neck load created an

up/down -ward shift of the reach movement error curves. An n-way ANOVA with

factors NL, target location, and participants revealed a significant main effect for

different NL, F(2,98) = 6.12, p < 0.01. Bonferroni-corrected post-hoc analyses

indicated that the bias effect was significant among all the NL conditions. The

interaction between targets and different NL was not significant, F(14,98) = 1.06,

p = 0.402, which means that the effect of varying NL on reach movement was

independent of different target directions.

Figure 7. Effect of applying neck load on reach movement behavior. A) Reach error curves (solid line for IHP shifts to right and dotted line for IHP shifts to left) are shifted upward for applying neck load on the right (n-way ANOVA, F(2,98) = 6.12, p < 0.01). The shift in reach error curves for applying neck load on left is not statistically significant. B) The movement variability is increased significantly for applying the load on the left compared to the no load condition (paired t-test, t(8) = 2.7552, p = 0.0283). C) The visual weights derived by fitting the Sober and Sabes (2003) model on the data. We only observed a significant change in visual weight in proprioceptive coordinate due to applying neck load on the left side. Significance was tested using paired t-test (P<0.05 is considered as a significant difference).

Figure 7(B) represents the variability of reach errors in the no load

condition vs. neck loaded conditions. As the figure demonstrates, the variability

of reach errors is higher for applying the load compared to no load condition. We

performed paired t-tests between all three different conditions across all eight

participants. Movement variability was significantly higher for applying the load

on the left side compared to no load condition t(8) = 2.7552, p = 0.0283. The

paired t-tests revealed no significance difference among other conditions.

Comparison

So far, we showed that there are both biases and increased movement

variability effects for either applying NL or HR. In the next step, we compared the

variability of reach movements in the NL conditions vs. HR conditions. Based on

stochasticity in RFTs we expected to have higher variability for higher amplitudes

of head angle during different experimental conditions. For example, we

predicted to have higher movement variability for applying only HR compare to

applying only NL or have the highest variability for conditions in which both HR

and NL are applied in the same direction.

Figure 8. Effect of different experimental conditions on reaching movement variability. Head upright and no load condition (considered as the control condition) and the combined HR/NL conditions are sorted based on the expected increase in the variability based on the signal-dependent noise hypothesis right and left of the control condition. Rolling the head consistently increased the variability compared to the control condition. Significance was tested using paired t-test (P<0.05 is considered as a significant difference).

Based on Figure 8 the variability in HR conditions is higher than in NL

conditions. We first ran paired t-tests between each condition separately and the

significant statistical differences are shown in the Figure 8. Applying the load on

the left side increased the variability compared to the control condition. Then, we

performed paired t-test between combined similar conditions: for example both

head upright and neck load on either side are combined and created the overall

NL condition. The paired t-test between HR condition and NL condition showed a

significant difference, $t(8) = 2.7444$, $p = 0.0287$; the difference between HR

condition and control condition was significant as well, $t(8) = 2.7444$, $p = 0.0020$;

however the difference between the control and NL conditions was not

significant. Together all of the above observations provide evidence for the

existence of signal dependent noise in the head angle estimation and

consequently the RFTs processes. However, it is not clear how such stochastic

RFTs affect the reaching movement. First, contrary to the initial hypothesis no

modulation of variability was observed by varying NL while the head was rolled

CW/CCW. In addition, in all the conditions we observed larger effects when

rolling the head on reach errors for targets away from body (45-135 degree)

compared to the targets toward the body (215-315 degree). Both previous

models (Sober & Sabes 2003 and Burns & Blohm 2010) fail to explain the

previousely mentioned effects. Based on both previous models, there shouldn't

be any difference in biases effect due to head roll condition and they predict a

constant up/down –ward shift in the reaching error curves. We propose that

these effects can be explained by a Bayesian framework which performs

geometrically accurate RFTs.

Modeling the stochastic reference frame transformations

The above analyses demonstrate that RFTs should be considered as stochastic process. Therefore, to understand the effect of such stochastic RFTs on reach planning we developed a Bayesian model of multi-sensory integration for reach planning and explicitly included the RFTs.

Error! Reference source not found. Figure 3 depicts the schematic of our proposed model. The working principles of our model are similar to previous ones (Sober & Sabes, 2003; Burns & Blohm, 2010) with the addition of an explicit head orientation estimator (Figure 9, blue box). In summary, our model calculates the required reach movement through first calculating the movement vector in visual coordinates, by comparing estimated initial hand position and target position, and then generates the movement commands by transforming the movement vector from visual coordinates to proprioceptive coordinates.

We added several crucial features to the proposed model compared to the previous models (Sober & Sabes 2003, 2005; Burns & Blohm 2010). First, we explicitly included the RFTs. The RFTs processes transforms information between different coordinates considering the full body geometry; head orientation, eye orientation, head-eye translation, and head-shoulder translation. In addition, to perform the required transformations, we included a head angle estimator. The head angle estimator combines muscle spindle information and visual/vestibular information in a statistically optimal manner. Similar to Burns and Blohm (2010), we modeled both mean behavior and the associated

variability for each source of information; vision, proprioceptive, vestibular, and

muscle spindles. To examine the effect of noisy transformations on the

visual/proprioceptive information, we deployed Monte Carlo simulations. This

method gave us the opportunity to explicitly study the effect of RFTs on the

covariance matrices and consequently the MSI weights.

Model fit

In the following section we first provide the fitting results for a sample

participant (#6) and then evaluate the fitting results across all nine participants.

Figure 9 provides the fitting vs. data for participant # 6. Figure 9 (A and B)

depicts model fitting for all different initial hand positions for different head rolls

while no neck load was applied. As it can be seen, our model is able to

accurately capture the reach errors for different IHP and HR conditions. Figure

9C provides the model prediction for changes in variance for different conditions.

Error bars were derived using bootstrapping with N=1000. Since the results for

horizontal and vertical hand shifts are very similar, for all the other conditions we

only provided the results for the horizontal initial hand shifts. Figure 9D-F depicts

the fitting for varying the NL for different Head angles; 0°, $\pm 30^\circ$.

Figure 9. Model fit for a sample participant (#6). Model fit on the reach error curves for
different IHPs and HR/NL conditions. A-B) model fit on the reach error curves for varying head orientation
without applying neck load: A) solid line represents results for IHP shifts to the right and dotted line
represents results for IHP shifts to the left, B) solid line represents results for IHP shifts to the up and dotted
line represents results for IHP shifts to the down. C) model fit on the changes in movement variability due to
varying HR and NL conditions. D-F) Model fit on reach errors for varying NL for different HR conditions. Only
data for horizontal shifts are presented. The results for vertical hand shifts are similar.

After demonstrating that our model was capable of predicting the reach

error behavior for a single participant, Table 1 summarizes the fitting results for

all the participants. The most interesting finding here is the relatively higher

contribution of visual/vestibular signal compared to neck muscle spindle (C≈26).

This is was consistent across all the subjects. We also observed very high

movement variability across our participants.

Table 1. Model parameter fits

Participants	(rad^2)	(mm^2)	(mm^2)	(deg^2)	(deg^2)	(deg^2)	C	(mm^2)
S1	4.69*10^{-4}	13.50	56.68	3.04*10^{-2}	7.89*10^{-1}	5.66	25.92	100.87
S2	4.86*10^{-4}	21.59	56.10	1.49*10^{-1}	3.87	5.61	25.76	48.53
S3	4.86*10^{-4}	16.50	56.72	1.54*10^{-1}	4.00	5.79	26.00	49.00
S4	3.11*10^{-4}	9.01	32.71	2.36*10^{-1}	5.92	4.97	25.13	11.56
S5	2.45*10^{-4}	15.00	26.86	1.08*10^{-1}	2.81	5.00	25.98	95.75
S6	4.81*10^{-4}	15.03	38.78	1.23*10^{-1}	3.20	5.77	26.00	37.97
S7	4.84*10^{-4}	20.97	38.81	3.07*10^{-1}	7.97	5.80	25.91	26.99
S8	2.87*10^{-4}	16.09	38.44	1.18*10^{-1}	3.08	5.80	26.00	41.32
S9	3.20*10^{-4}	18.99	38.58	2.97*10^{-1}	7.68	5.74	25.89	26.98
95% CI	[3.13, 4.80] *10^{-4}	[13.12, 19.47]	[33.57, 51.69]	[0.94, 2.44] *10^{-1}	[2.44, 6.30]	[5.30, 5.85]	[25.61, 26.07]	[23.93, 73.62]

Figure 10 provides the model prediction vs. data for both reach errors and

variances for different experimental conditions. Different participants are

differentiated by different colors. We used several different analyses to evaluate

the goodness of our model fit. First, we calculated r-squared value for each

individual participants and the pool of all the participants: [54, 61, 56, 75, 50, 60,

66, 71, 71, and 94] for S1-S9 and the pool of data respectively. Secondly, since

the variance data was very noisy, we grouped them in bins and calculated the

confidence interval for each predicted variance using the following equation (J. S.

Williams, 1962):

$$\frac{(n-1).s^2}{\chi^2_{\alpha/2}} \leq \sigma^2 \leq \frac{(n-1).s^2}{\chi^2_{1-\alpha/2}} \qquad (18)$$

In which σ^2 is the population variance, s^2 is the sample variance, n is the

sample size, and $\chi^2_{\alpha/2}$ is chi-square distribution. Since we wanted to find the 95%

confidence interval, we set $\alpha = 0.05$. The boxed colored area in Figure 11(B, C)

is the calculated confidence interval for the variances. Based on this analysis, we

could see that our model provides a decent fit on the data.

Finally, we examined if our residual has a random pattern by examining

the normality of our model residual using normal probability plot, plotted using

MATLAB 2016 'normplot.m'. Figure 11 provides the normal probability plot of our

fitting for all nine participants. As it is depicted, residual values for all the

participants approximately have a normal distribution which implicates that our

model captures all the features in the data. More details of how our model

explains the data can be found in supplementary materials.

Figure 10. Model predication vs. observed data for each individual participant. Data for each individual participant was fitted to our model. Each color represents an individual participant. A) The model prediction vs. observed data for reach errors. B) The model prediction vs. observed data for reach variability. C) Same data as in section B grouped into bins of 0.25 deg2 (mean and standard error). The gray box represents the confidence interval for predicted variances based on our model.

Figure 11. Residual analysis: normal probability plot. The probability plot is depicted for each participant, different colors. As it can be seen the residuals of our model fit compared to the participants' data has almost a normal distribution for all the participants.

Discussion

We assessed the effect of neck muscle spindle noise on multi-sensory integration during a reaching task and found that applying neck load biased head angle estimation across all head roll angles resulting in systematic shifts in reach errors. We also examined the effect of head roll on reach errors and observed

both an increase in movement variability and biases in reaching errors; similar to

Burns & Blohm (2010). To quantitatively examine the effect of noise on reaching

movements, we developed a novel 3D stochastic model of multisensory

integration across reference frames. The effect of neck muscle spindle noise and

head roll could be explained by a misestimation of head orientation and signal-

dependent noise in the RFTs between visual and proprioceptive coordinates. The

model was able to successfully reproduce the reaching patterns observed in the

data providing evidence that the brain has online knowledge of full body

geometry as well as the reliability associated with each signal and uses this

information to plan the reach movement in a statistically optimal manner.

Model discussion

In our model, the multisensory integration process occurs in specific

reference frames; i.e. in visual and proprioceptive coordinates. Therefore, signals

should be transformed into the appropriate coordinate frame before integration

which is done by a series of coordinate rotations and translations. However, we

do not claim that the brain performs these computations in the same explicit

serial way. Alternatively, neurons could directly combine different signals across

reference frames (Abedi Khoozani et al., 2016; Blohm et al., 2009; Ma et al.

2006; Beck et al., 2011), e.g. by gain modulation mechanisms. Regardless of the

mechanism used, we expect very similar behavioral outcomes.

In addition, we assumed that all the distributions remain Gaussian after

performing RFT processes to simplify the required Bayesian computations.

However, in general, this is not necessarily correct. For example, it has been

shown that noisy transformations can dramatically change the distribution of

transformed signals (Alikhanian et al., 2015). Since the noise in our RFTs was

small enough, the deviations from a Gaussian distribution are negligible and this

approximation did not affect our model behavior dramatically. It would be

interesting, though, to examine how considering the actual distribution and

performing the basic Bayesian statistics (Press, 1989) will change the model

behavior.

Interpretation of observations

We suggest that neck load biased head angle estimation across all head

roll angles, which resulted in systematic biases in reach error curves. Our model

accounted for these shifts by assuming that neck load biases the head angle

estimation toward the direction of the load. How our brain estimates the head

orientation has previously been investigated. The vestibular system and

especially otolith system is very important for estimating the static head

orientation relative to gravitational axes (Fernandez et al., 1972; Sadeghi et al.,

2007). Vingerhoets et al. (2009) demonstrated that tilted visual and vestibular

cues bias the perception of visual verticality. The author showed that a Bayesian

model that integrates visual and vestibular cues can capture the observed biases

in verticality perception. Furthermore, muscle spindles play an important role in

determining joint position sense (Goodwin et al., 1972; Scott & Loeb, 1994)

compared to the other sources; e.g. tendons or cutaneous receptors (Gandevia

et al., 1992 and Jones, 1994). Armstrong et al. (2008) showed that the muscles

in the cervical section of the spine have a high density of muscle spindles

providing an accurate representation of head position relative to the body.

Therefore, head angle can be estimated from a combination of visual, vestibular

and neck muscle spindle information.

We included multisensory integration of visual/vestibular, and neck muscle

spindle signals in our model. Since we only modulated neck muscle information,

we assumed that a combination of visual/vestibular signals is integrated with

neck muscle spindle information. We were able to retrieve the relative

contribution of visual/vestibular information vs. neck muscle spindle information

by fitting our model to the data. We found that the contribution of neck muscle

spindle information was very low (in the order of 5%) compared to

visual/vestibular information.

There could be several possible explanations for observing a relatively low

contribution of the neck muscle information. First, we selected the amount of the

neck load in a way to apply force comparable to 30deg head tilt. However, due to

the complex organization of neck muscles (Armstrong et al., 2008) we couldn't

directly measure the changes in muscles' activity. Therefore, to accurately

measure the effect of applying load on neck muscle spindle information, a

detailed model of neck muscle organization would be required. Moreover, usually

neck muscle information agrees with the skin receptor (i.e. Cutaneous receptor)

information. In our task, however, the neck muscle information and Cutaneous

receptor information are in conflict, which might be a potential reason for down-

weighting neck proprioceptive information (Körding et al. 2007).

Unexpectedly, we observed that applying head roll creates larger reaching

movement biases for visual targets away from the body compared to visual

targets toward the body. This pattern can be captured by including the full body

geometry in the RFT processes in our model. Previously, Blohm and Crawford

(2007) showed that in order to accurately plan a reaching movement to visual

targets, the full body geometry (both rotations and translations) has to be taken

into account by the brain. Based on our model, the displacement of centers of

rotation between head- and eye-centered coordinate spaces caused this

asymmetry in the reaching movements.

In addition to biases, we observed that reaching movements were more

variable in the straight head with neck load conditions compared to the straight

head and no load condition. We considered this as evidence for neck load

affecting RFTs; we assumed that the neck muscle spindles have signal-

dependent noise (Scott & Loeb, 1994). Therefore, applying the neck load

increases the noise in the neck muscle spindle information and consequently the

sensed head orientation. This noisier sensed head angle resulted in noisier RFTs

and accordingly more variable reach movements.

Surprisingly, we observed an asymmetry in the amount of variability

increase by applying neck load on the right vs. left side when the head was

upright. One explanation could be that since all participants were right-handed,

they were more sensitive to the changes on the left side. Several imaging studies

demonstrated that right-handed people have bigger left hemispheres with more

neural resources associated to the right-side of the body (Bauermeister, 1987;

Linkenauger et al., 2009; Linkenauger et al., 2012). Bauermeister (1987) tested

the effect of handedness on perceiving verticality and showed that right-handed

participants are more responsive to the right sided stimulus than to the left sided

stimulus.

Since head roll with no neck load caused higher increase in movement

variability compared to applying neck load while the head was upright, we

expected to see a systematic modulation of movement variability by applying

neck load while the head was tilted. Specifically, we expected to observe the

highest amount of movement variability when the neck load and head roll were

applied on the same side; e.g. 30deg CW head roll and right side neck load. The

logic is that when both head roll and neck load are applied in the same direction,

the neck muscle signal indicates the highest angle and due to signal dependent

noise the associated variability of head angle estimations has the highest value.

However, applying the load on the same side as the tilted head did not increase

the movement variability significantly compared to only tilting the head.

A possible explanation for the lower effect of applying load on the same

side of titled head can be relatively low contribution of neck muscle spindle

information vs. visual/vestibular information during head angle estimation,

provided by our model. The remarkable observation is that even though the

contribution of neck muscle information is low, applying neck load still has a

tangible effect on reaching movements for all head roll conditions, observed both

in our data and model predictions. Another explanation is that the brain might not

integrate the visual/vestibular information in this condition due to the big

discrepancy between neck muscle information and visual/vestibular information

(due to lack of causality; Kording et al. 2007). In our experimental design we

selected the neck load value to simulate the same force as when the head is

titled 30deg (head weight*sin(60deg) = 0.5*head weight). Consequently, when

the head is tilted 30deg CW and the load is applied on the right side the total

force on the neck muscle can be calculated as: 0.5*head weight (head

tilt)+0.5*head weight (head load) = full head weight; this force is stimulating the

neck muscle as if the head was tilted 90deg, which is very unlikely. Therefore,

the brain might ignore the neck muscle spindle information fully.

We interpreted the observed increase in movement variability as an

indication of signal dependent noise in the RFT process. However, an alternative

hypothesis to the signal dependent noise is uncommon posture (Körding &

Sabes 2011). According to the uncommon posture hypothesis, we might have

more neuronal resources allocated to the head straight posture since we perform

most of our movements with the head straight. As a result, rolling the head

creates higher uncertainty due to uncommon posture independent of signal

dependent noise. Even though this argument might be valid for head roll, it

cannot explain the increased movement variability due to applying neck load. In

other words, applying neck load while the body posture was kept unchanged still

increased the movement variability which is in contrary to the uncommon posture

hypothesis.

We observed that changing head roll and/or applying neck load modulated

multisensory weights in both visual and proprioceptual coordinates. We validated

this finding by both fitting Sober and Sabes' (2003) model and our new full

Bayesian RFTs model to the data. We found that increasing the noise in the

sensed head angle estimation decreased the reliability of transformed signals,

which we hypothesized is the result of the stochastic RFTs, and consequently

lowered weights for transformed signals in the multisensory integration process.

Therefore, we conclude that both body geometry and signal-dependent noise

influence multi-sensory integration weights through stochastic RFTs.

We demonstrated that head position estimation plays a vital role in RFT

processes required for reach movements. Previous studies showed that non-

visual information of head position in space, i.e. from the neck muscle spindles

(Proske & Gandevia, 2012) and from the vestibular system (Angelaki & Cullen

2008; Cullen 2012), decline over time providing better information about the

relative changes in head position than about the absolute position. This behavior

is explained based on proprioceptive drift; afferent discharges decline over time

(Tsay et al., 2014) resulting in imprecise absolute estimation of the head position.

We evaluated the temporal evolution of head angle estimation and its possible

effect on reaching movements by dividing each block of our experiment into 4

bins (data not shown); however we found no changes in movement biases or

variability. Therefore, we believe that our experiment design and timing was not

appropriate to investigate changes of head angle estimation over time on

reaching behaviour. This question, however, is an intriguing question and should

be investigated in future experiments.

Implications

Our findings have implications for behavioral, perceptual,

electrophysiology, and modeling studies. First, we have demonstrated that both

body geometry and stochasticity in RFTs modulate multisensory integration

weights. It is possible that other contextual variables such as attention or prior

knowledge also modulate multisensory weights and will subsequently affect both

perception and action. In addition, we have shown that such modulations in

multisensory weights can create asymmetrical biases in reach movements. Such

unexpected biases may be prevalent in behavioral data obtained during

visuomotor experiments in which participants perform the task in a robotic setup

while their body is in various geometries, e.g. tilted head forward or elevated

elbow. Therefore, it is important to consider that forcing specific body

configurations can create unpredicted effects that are important for interpreting

the behavioral data.

Our findings also suggest that the brain must have online knowledge of

the statistical properties of the signals involved in multisensory integration. This

could be achieved by population codes in the brain (Ma et al., 2009), which

agrees with the current dominant view that the brain performs the required

computations through probabilistic inferences (Pitkow & Angelaki, 2017).

Alternatively, multisensory weights and the change of weights with contextual

parameters could be learned (Mikula et al., 2018). Learned weights could be

specially advantageous when it is difficult to estimate sensory reliability.

Computational models that include required latent variables are crucial to

understand the required computations. An important benefit of such models is

that they can be used to generate training sets for neural networks in order to

investigate potential neural mechanisms underlying probabilistic inference. Such

studies will motivate appropriate electrophysiology experiments to validate/refute

predications of related models.

References

870 **References**

871 **Abedi Khoozani, P., Standage, D., and Blohm, G.**, An approximate
872 normalization model for multisensory integration across reference frames, in the
873 Annual meeting of Society for Neuroscience, San Diego, 2016.
874

875 **Alikhanian, H., Carvalho, S., and Blohm, G.**, Quantifying effects of stochasticity
876 in reference frame transformations on posterior distributions, *Frontiers in*
877 *Computational Neuroscience,* 2015.
878

879 **Andersen, R., and Buneo, C.**, Intentional maps in posterior parietal cortex.
880 *Annual Review of Neuroscience*, 25(1), 189, 2002.
881

Angelaki, D. E., & Cullen, K. E., Vestibular System: The Many Facets of a
Multimodal Sense. *Annual Review of Neuroscience,* 31(1), 125–150, 2008.
https://doi.org/10.1146/annurev.neuro.31.060407.125555

Armstrong, B., McNair, P., and Williams, M., Head and neck position sense.
Sports Med. 38, 101–117, 2008.
Atkins, J. E., Fiser, J., and Jacobs, R. A.. Experience-dependent visual cue
integration based on consistencies between visual and haptic precepts. *Vision*
Res. 41, 449–461, 2001.
890

891 **Batista, A. P., Buneo, C. A., Snyder, L. H., & Andersen, R. A.**, Reach plans in
892 eye-centered coordinates. Science, 285, 257–260, 1999.
893

894 **Bauermeister, M.** Effect of body tilt on apparent verticality, apparent body
895 position, and their relation. *Journal of Experimental Psychology*, 1964,67, 142-
896 147.
897

898 **Beck, J. M., Latham, P. E., and Pouget A.**, Marginalization in neural circuits
899 with divisive normalization. *J Neuroscience,* 31, 15310-9, 2011.
900

901 **Binder, K. and Heermann, D.W.**, *Monte Carlo Simulation in Statistical Physics.*
902 *An Introduction (4th edition).* Springer, 2002.
903

904 **Blohm, G., Keith, G. P., and Crawford, J. D.**, Decoding the cortical
905 transformations for visually guided reaching in 3D space. *Cerebral Cortex, 19*(6),
906 1372-1393, 2009.
907

908 **Blohm, G. & Crawford, J.D.**, Computations for geometrically accurate visually
909 guided reaching in 3-D space. *Journal of Vision.* 7, 1–22, 2007.
910

Buneo, C. A., Jarvis, M. R., Batista, A. P., and Andersen, R. A., Direct vis-
uomotor transformations for reaching. *Nature* 416, 632–636, 2002.

Burns, J. K., and Blohm, G., Multi-sensory weights depend on contextual noise
in reference frame transformations. *Frontiers in Human Neuroscience*, 4, 221,
2010.

Burns, J. K., Nashed, J. Y., and Blohm, G., *Head roll influences perceived*
hand position. Journal of Vision. 11(9):3, 1–9, 2011.

Clark, J. J., and Yuille, A. L., Data fusion for sensory information processing
systems. *Boston, MA: Kluwer*, 1990.

Commentary: Sober, S. J., and Körding, K., What silly postures tell us about
the brain? *Front. Neurosci.* 6:154, 2012.

Cordo, P. J., Flores-Vieira, C., Verschueren, S. M. P., Inglis, J. T., and
Gurfinke., Positions sensitivity of human muscle spindles: Single afferent and
population representations. *J. Neurophysiol.* 87, 1186–1195, 2002.

Crawford, J. D., Medendorp, W. P., & Marotta, J. J., Spatial transformations for
eye–hand coordination. Journal of Neurophysiology, 92, 10–19, 2004.

Cullen, K. E., The vestibular system: Multimodal integration and encoding of
self-motion for motor control. *Trends in Neurosciences*, *35*(3), 185–196, 2012.
https://doi.org/10.1016/j.tins.2011.12.001

Ernst, M. O., and Banks, M. S., Humans integrate visual and haptic information
in a statistically optimal fashion. *Nature, 415*, 429, 2002.

Ernst, M. O., and Bülthoff, H. H., Merging the senses into a robust percept.
Trends in Cognitive Sciences, 8(4), 162-169, 2004.

Faisal, A. A., Selen, L. P., and Wolpert, D. M., Noise in the nervous system.
Nature Reviews Neuroscience, 9, 292, 2008.

Fernandez, C., Goldberg, J. M., and Abend, W. K.,. Response to static tilts of
peripheral neurons innervating otolith organs of the squirrel monkey. *J.*
Neurophysiol. 35, 978–987, 1972.

Flanders, M., Tillery, S., and Soechting, J., Early stages in a sensorimotor
transformation. *Behavioral and Brain Sciences, 15*(2), 309-320, 1992.

Gandevia S., C., McCloskey DI, Burke D. Kinaesthetic, signals and muscle
contraction. *Trends in Neuro- logical Science,*15: 62–65, 1992.

Gellman, R. S., and Fletcher, W. A., Eye position signals in human saccadic
processing. *Exp. Brain Res.* 89, 425–434, 1992.

Goodwin, G. M., McCloskey, D. I., and Mathews, P. B. C., The contribution of muscle afferents to kinesthesis shown by vibration induced illusions of movement and by the effect of paralysing joint afferents. *Brain 95*, 705–748, 1972.

Henriques, D. Y., & Crawford, J. D., Role of eye, head, and shoulder geometry in the planning of accurate arm movements. Journal of Neurophysiology, 87, 1677–1685, 2002.

Henriques, D. Y., Medendorp, W. P., Gielen, C. C., & Crawford, J. D., Geometric computations underlying eye–hand coordination: Orientations of the two eyes and the head. Experimental Brain Research, 152, 70–78, 2003.

Jacobson, M. T., Matthews, P., Generating uniformly distributed random Latin squares. Journal of Combinatorial Designs. 4 (6): 405–437,1996.

Jones, L. A.. Peripheral mechanisms of touch and proprioception. *Canadian Journal of Pharmacology* 72: 484–487, 1994.

Kersten, D., Mamassian, P., and Yuille, A., Object perception as Bayesian inference. *Annu. Rev. Psychol.* 55, 271–304, 2004.

Knill, D. C., and Pouget, A., The Bayesian brain: the role of uncertainty in neural coding and computation. *Trends Neurosci.* 27, 712–719.

Knudsen, E. I., Lac, S., and Esterly, S. D., Computational maps in the brain. *Annual Review of Neuroscience, 10*(1), 41-65, 1987.

Körding, K. P., and Wolpert, D. M., Bayesian decision theory in sensorimotor control. *Trends in Cognitive Sciences, 10*(7), 319-326, 2006.

Körding, K. P., Beierholm, U., Ma, W. J., Quartz, S., Tenenbaum, J. B., Shams L., Causal Inference in Multisensory Perception. PLoS ONE 2(9): e943.

Landy, M. S., and Kojima, H., Ideal cue combination for localizing texture-defined edges. *J. Opt. Soc. Am. A.* 18, 2307–2320, 2001.

Landy, M. S., Maloney, L., Johnston, E. B., and Young, M., Measurement and modeling of depth cue combination: in defense of weak fusion. *Vision Res.* 35, 389–412, 1995.

Lechner-Steinleitner, S., Interaction of labyrinthine and somatoreceptor inputs as determinants of the subjective vertical. *Psychol. Res.* 40, 65–76, 1987.

Li, W., and Matin, L., Visual direction is corrected by a hybrid extraretinal eye position signal. *Ann. N.Y. Acad. Sci.* 656, 865–867, 1992.

Linkenauger, S. A., Witt, J. K., Bakdash, J. Z., Stefanucci, J. K., & Proffitt, D. R., Asymmetrical body perception: A possible role for neural body representations. *Psychological Science*, 20, 1373–1380, 2009.

Linkenauger, S.A., Witt, J.K., Stefanucci, J.K., Bakdash, J.Z., and Proffitt, D.R., The effects of handedness and reachability on perceived distance. *Journal of Experimental Psychology: Human Perception and Performance*, 35, 1649–1660, 2009.

Ma, W. J., Beck, J. M., Latham, P. E. & Pouget, A., Bayesian inference with probabilistic population codes. *Nature Neuroscience.* 9, 1432–1438, 2006.

Mergner, T., Nardi, G. L., Becker, W., & Deecke, L.. The role of canal-neck interaction for the perception of horizontal trunk and head rotation. *Experimental Brain Research*, 49(2), 198–208, 1983. https://doi.org/10.1007/BF00238580

Menrgner, T., Siebold, C., Schweigart, G., & Becker, W., *BrainR. Experimental Brain Research*, 389–404, 1991.

Mergner, T., Huber, W., Becker, W., Vestibular-neck interaction and transformation of sensory coordinates. *J Vestib Res*, 347-36, 1997.

Mikula, L., Gaveau, V., Pisella, L., Khan, Z., A., and Blohm, G., Learned rather than online relative weighting of visual-proprioceptive sensory cues, *in press*, 2018.

Pitcow, X., and Angelaki, D., How the brain might work: statistics flowing in redundant population codes. arXiv:1702.03492v2

Press, S.J., Bayesian statistics: principles, models and applications, *Wiley, New York*, 1990.

Proske, U., & Gandevia, S. C., The Proprioceptive Senses: Their Roles in Signaling Body Shape, Body Position and Movement, and Muscle Force. *Physiological Reviews*, *92*(4), 1651–1697, 2012. https://doi.org/10.1152/physrev.00048.2011

Sadeghi, S. G., Chacron, M. J., Taylor, M. C., and Cullen, K. E., Neural variability, detection thresholds, and information transmission in the vestibular system. *J. Neurosci.* 27, 771–781, 2007.

Scott, S. H. and Loeb, G. E., The computation of position sense from spindles in mono- and multiarticular muscles. J. Neurosci. 14, 7529–7540, 1994.

Schlicht, E. J., and Schrater, P. R., Impact of coordinate transformation uncertainty on human sensorimotor control. Journal of Neurophysiology, 97(6), 4203–4214, 2007.

Stein, B. E., and Meredith, M. A., The *Merging of the Senses. Cambridge*, MA: MIT Press, 1993.

Stein, B. E., and Stanford, T. R., Multisensory integration: current issues from the perspective of the single neuron. *Nat. Rev. Neurosci.* 9, 255–266, 2008.

Sober, S. J., and Sabes, P. N., Multisensory integration during motor planning. *Journal of Neuroscience, 23*(18), 6982-6992, 2003.

Sober, S. J., and Sabes, P. N., Flexible strategies for sensory integration during movement planning. *Nature Neuroscience, 8*, 490, 2005.

Sober SJ and Körding K (2012). What silly postures tell us about the brain. *Front. Neurosci. 6:154*

Soechting, J. F., and Flanders, M., Moving in three-dimensional space: Frames of reference, vectors, and coordinate systems. *Annual Review of Neuroscience, 15*(1), 167-191, 1992.

Tsay, A., Savage, G., Allen, T. J., & Proske, U., Limb position sense, proprioceptive drift and muscle thixotropy at the human elbow joint. *Journal of Physiology, 592*(12), 2679–2694, 2014. https://doi.org/10.1113/jphysiol.2013.269365

Van Beuzekom, A. D., and Van Gisbergen, J. A. M., Properties of the internal representation of gravity inferred from spatial-direction and body-tilt estimates. *J. Neurophysiol.* 84, 11–27, 2000.

Van Beers, R. J., Sittig, A. C. & Denier van der Gon, J. J. Integration of proprioceptive and visual position information: An experimentally supported model. *J. Neurophysiol.* **81**, 1355–1364, 1999.

Vetter, P., Goodbody, S. J., & Wolpert, D. M., Evidence for an eye-centered spherical representation of the visuomotor map. Journal of Neurophysiology, 81, 935–939, 1999.

Vingerhoets R. A., De Vrijer M., Van Gisbergen J. A., Medendorp W. P., Fusion of visual and vestibular tilt cues in the perception of visual vertical. *Journal of Neurophysiology* 101:1321–1333, 2009.

Wade, S. W., and Curthoys, I. S., The effect of ocular torsional position on perception of the roll-tilt of visual stimuli. *Vision Res.* 37, 1071–1078, 1997.

Williams, J. S., A confidence interval for variance components, *Biometnka,* 49, 278 281, 1962.

 Supplementary materials

In this section we provide more details of how our model performs RFTs

on different sensory signals (modeled as Gaussian distributions). In the

manuscript, we demonstrated that the proposed model was able to replicate our

behavioral data pattern (Figure 9). In this section, we use the model to provide a

mechanistic explanation of the observed reach movement patterns.

Sober and Sabes (2003) demonstrated that reaching errors caused by

dissociating visual and proprioceptive information can be explained by two

components: MV error that is the error at the vector planning stage and INV error

which is the error at the motor command generation stage. They showed that

adding these two reaching errors leads to the error pattern observed in human

participants. Furthermore, Burns and Blohm (2010) demonstrated that the

observed up- and downward shifts in reaching error curves can be explained by

RFTs; any misestimation in the sensed head angle results in an erroneous

rotation of movement vector which results in up- and downward shifts in reach

error curves. The logic is the same in our model for explaining the observed

biases in reach error curves for the head roll condition. Similarly, the up/down -

ward shifts in reach error curves for the neck load condition can be explained by

erroneous RFTs; applying a neck load biases the head angle, which leads to an

erroneous rotation of the movement vector, resulting in shifts of error curves.

Applying a neck load enabled us to evaluate the contribution of neck

muscle spindle information to head angle estimation. To achieve this we included

a Bayesian head angle estimator in our model in which the visual/vestibular and

neck muscle spindle information are integrated to estimate the head angle.

Applying a neck load biases the neck muscle spindle information toward the

direction of the load and consequently biases the head angle estimation

(equations 7 and 8). This bias in estimated head angle depends on two

parameters: 1) relative neck muscle reliability compared to visual/vestibular

reliability and 2) overall head angle estimation variability (similar to the variable

RFTs variance in Burns and Blohm's (2010) model)**Error! Reference source**

not found..

As explained before, in our model we estimate the head angle by

integrating visual/vestibular information with neck muscle information. As a result,

the overall sensed head angle variability depends on the variability of each of

aforementioned information. Consider the situation in which overall head angle

estimation variability is low (**Error! Reference source not found.** Figure S1 A-

B). Low variability for head angle estimation resulted from high reliability for both

visual/vestibular and neck muscle spindle information. Similarly, high variability of

head angle estimation resulted from low reliability of both visual/vestibular and

neck muscle spindle information and consequently applying neck load creates

smaller biases (**Error! Reference source not found.** Figure S1 C-D). We expect

that applying a neck load will create higher shifts in reach error curves for when

the reliability of sensed head angle is high compared to when the reliability of

sensed head angle is low, regardless of their relative contribution (compare

Figure S1A vs. Figure S1D and Figure S1B vs. Figure S1C).

In addition, the amount of shifts in reach error curves depends on the

relative reliability of neck muscle spindle information vs. visual/vestibular

information. When the relative reliability of neck muscle information is high, the

bias in reach error curves is higher compared to when its reliability is low (Figure

S1**Error! Reference source not found.**B vs. Figure S1C). In our data, we

observed high variability for head angle estimation as well as relatively higher

contribution of visual/vestibular information compared to neck muscle spindle

information (　　　　　); Figure S1**Error! Reference source not found.**C.

1153

Figure S1. Effect of varying the reliability of neck muscle spindle signals
vs. visual/vestibular signals. Head angle is estimated by combining the neck muscle spindle
information with combined visual and vestibular information using the Bayesian method, therefore, the effect
of applying neck load depends on two factors: 1) absolute variability of head angle estimation and 2) relative
reliability of neck muscle spindle information compared to visual/vestibular information. A-B) lower absolute
value for head angle estimation variability: this lower variability results from the high reliability of both
visual/vestibular and neck muscle information. Therefore, the up/down -ward shifts induced due to applying
neck load is higher compared with when the head angle estimation variability is high (panel C and D). In
addition to the absolute head angle estimation variability, the relative reliability of neck muscle spindle vs.
visual/vestibular information impacts how much applying neck load biases the reaching movement: A, C) the
lower the reliability of neck muscle spindle information vs. visual/vestibular information, the lower the
up/down ward shifts in reaching error curves, B, D) increasing the relative reliability of neck muscle
information increases the up/down ward shifts in reaching errors by applying neck load..

As mentioned before, at the heart of our RFT process there is a head angle

estimator which enabled us to retrieve the sensed head angle based on the

reach error patterns. Figure S2 demonstrates the biases in head angle estimation

for all the experimental conditions. As can be seen, applying neck load biased

the head angle estimation toward the applied neck load for all head angles. We

performed t-test analysis and observed that all the changes in head angle

estimation due to applying neck load are significant $-11 < t(8) < 12$, $p < 0.001$.

1174
FigureS2. Biases in head angle estimation due to different head roll and
neck load conditions. Applying neck load biased the head angle estimation toward the applied load
for all head angles. Error bars are standard deviations.

In addition to up/down –ward shifts in reach error curves by applying neck load

and head roll, we observed a very surprising pattern in our data: both head roll

and neck load created greater biases in reaching movements when reaching to

targets away from the body (45-135 deg) compared to reaching to targets toward

the body (215-315 deg). This observation was surprising and to our knowledge

none of the previous models (Sober & Sabes 2003 and Burns & Blohm 2010)

could predict/explain this pattern.

At this point it should come as no surprise that our model explains the difference

in head roll/neck load effect for different targets by stochastic RFTs processes.

Blohm and Crawford (2007) demonstrated that the brain considers the full 3D

body geometry to accurately plan reach movements. As mentioned in the model

description, we included the 3D body geometry in our RFTs procedure: RFT

processes are carried out by sequential rotations/translations between different

coordinates centered on different body sections. Figure S3A demonstrates

different coordinates that have been considered in our model in relation to each

other. Including the 3D body geometry resulted in a displacement in the center of

rotation between different coordinates and specifically in our experiment between

gaze-centered and head-centered coordinates. This displacement of the center

of rotation caused greater biases in reaching movements for visual targets further

away from vs. closer to the body (Figure S3A). Figure S3B provides a detailed

example of how the difference in the center of rotation results in an asymmetry in

the movement biases induced by head roll/neck load. The first block in Figure

S3B shows the actual scene in front of the participants with two targets at 90deg

and 270deg. In our experiment the participants fixated their eyes on the cross

and this cross was indicated as their visual information of the initial hand position

as well. In this example, the hand was shifted 25cm horizontally to the right. The

dotted arrows show the visual movement vector toward the targets. Box #1

demonstrates the retinal representation of targets for head roll 30deg CCW. We

assumed that the torsion effect on retinal information was small and therefore

ignored it. Since the head is rotated 30deg CCW, the retinal image on the back

of the head is rotated 30deg CW (actual head angle) and the center of this

rotation is the cross (gaze-position). In order to estimate the hand position,

proprioceptive information must be transformed to the retinal coordinates and at

the heart of this transformation is the head rotation based on the estimated head

angle (Blue box in figure 3). In this specific example, we assumed that the head

angle is overestimated by 5deg and is estimated as 35deg. In addition, since the

centers of rotation for head-centered and gaze-centered coordinates are

different, the transformed hand position is no longer in symmetry with the rotation

in gaze-centered coordinates and displaced and biased toward the body. The

next two steps in our model are multisensory integration to estimate the hand

position and movement vector calculations (Box #2). As it has been shown by

Sober and Sabes (2003, 2005) any transformation adds noise and therefore,

visual information is more reliable in the retinal coordinates and the estimated

initial hand position is biased toward the visual initial hand position and the

movement vector is calculated by subtracting target position from this estimated

initial hand position. This movement vector, then, is transformed into shoulder-

center coordinates to be executed, employing RFTs (Box #3). We compared the

transformed movement vector with the visual movement vector in Box #4 and as

it can be seen the misestimation in head angle created greater biases for target

away from the body (90deg) compared to the target toward the body (270deg).

1228
Figure S3. RFT processes mechanism. A) Different coordinates in our RFT module. The
difference in the center of rotation between gaze-centered coordinate and head-centered coordinate
resulted in an asymmetry of transformed hand position for 30deg CW vs CCW head rolls. B) A detailed
example of the higher effect of stochastic RFTs on movement away from the body compared to movements
toward the body for head roll 30deg CCW: Actual scene: in our experiment, participants had fixated their
eyes on the center cross and the visual feedback of the hand indicated their hand on the center as well. The
actual hand position is shifted to the right in this example and it is occluded, Box#1: the retinal image of the
target is rotated 30 CW, we ignored the torsion effects on retinal projection. Proprioceptive hand position is
transformed using our RFT module (we assumed that head roll estimation is erroneous; 35deg), Box#2:
Initial hand position is estimated by combining visual information and transformed proprioceptive information
of the hand. Then, the movement vector is calculated by subtracting target position from the initial hand
position, Box#3: The calculated movement vector is transformed to the proprioceptive coordinate using the
RFTs module, Box#4: comparing the planned movement with the movement only considering visual
information. As it can be seen, the misestimation in head angle, created larger error for movement away
from body vs. movement toward the body. This happened due to the offset in the center of rotations
between different coordinates.

Determining how stochastic noise in RFTs modulates multi-sensory weights was

one of the goals of this experiment. In figures 6 and 7, we fitted Sober and

Sabes' (2003) model to the data and demonstrated that both head roll and neck

load modulates multi-sensory integration weights. Similar to Burns and Blohm

(2010), we were able to retrieve multisensory integration weights from the

covariance matrices. As it has been demonstrated in figure S4, RFTs

dramatically change the distribution of the transformed signal and consequently

the covariance matrix (Alikhanian et al., 2015). In order to account for such

variations, we calculated the determinant of the covariance matrix for calculating

the multi-sensory weights. Figure S4 shows visual weights in both visual (A) and

proprioceptive (B) coordinates.

1256
Figure S4. visual weights for multi-sensory integration. A) Visual weights in visual
coordinate: Visual weights increase in visual coordinate due to decreased reliability of proprioceptive
information caused by stochastic RFTs, B) Visual weights in proprioceptive coordinate: rolling the head
30deg CCW didn't affect the visual weights while rolling the head 30deg CW decreased visual weights. The
reason for this asymmetry is the nonlinearity in the inverse kinematic process. Error bars are standard error
of the mean. The significance was tested using paired t-test (P < 0.05 is considered as a significant
difference).

1264
Visual weights were lowest for head straight and no load condition in visual

coordinates and increased by rolling the head and/or applying neck load. Our

paired t-test showed that this increase was significant for all head roll and neck

load conditions (t(8) < -3, p < 0.05). More specifically, applying the neck load

increased the visual weights in visual coordinate while the head was upright (t(8)

< -3, p < 0.05) while it didn't significantly change when the head wasn't upright

and neck load was applied (t(8) < -1, p ≈ 0.2). Applying neck load or rolling the

head didn't significantly changed visual weights in visual coordinates except for

when the head rolled 30deg CW (t(8) < -18, p < 0.001) or the neck load applied

to the left side (t(8) < 3, p < 0.05). Combination of head roll and neck load only

modulated the visual weights when the head was rolled 30deg CW and neck load

applied to the either sides ($|t(8)| < 4$, $p < 0.05$). Therefore, our data and model

show that both noise in RFTs and the geometry of the body can influence multi-

sensory integration in a way that is explained through changes in reliability of

transformed signal by stochastic and geometrically accurate RFT processes.