Title: From lake to estuary, the tale of two waters. A study of aquatic continuum biogeochemistry.

Manuscript Category: Research Article
Running Header: River and Estuary Aquatic Continuum

Paul Julian II[1] and Todd Z. Osborne[2,3]

[1] University of Florida, Soil and Water Sciences
2199 South Rock Rd, Ft. Pierce, FL 34945
ORCID ID: 0000-0002-7617-1354
*Corresponding Author: pjulian@ufl.edu

[2] University of Florida, Soil and Water Sciences, Gainesville, FL 32611
[3] University of Florida, Whitney Laboratory for Marine Bioscience, St Augustine, FL 32080
Email: osbornet@ufl.edu

Abstract

The balance of fresh and saline water is essential to estuarine ecosystem function. Along the fresh-brackish-saline water gradient within the C-43 canal/Caloosahatchee River estuary (CRE) the quantity, timing and distribution of water and associated water quality significantly influences ecosystem function. Long-term trends of water quality and quantity were assessed from Lake Okeechobee to the CRE between May 1978 to April 2016. Significant changes to monthly flow volumes were detected between the lake and the estuary which correspond to changes in upstream management. and climatic events. Across the 37-year period total phosphorus (TP) flow-weighted mean (FWM) concentration significantly increased at the lake, meanwhile total nitrogen (TN) FMW concentrations significantly declined at both the lake and estuary headwaters. Between May 1999 and April 2016, TN, TP and total organic carbon (TOC), ortho-P and ammonium conditions were assessed within the estuary at several monitoring locations. Generally nutrient concentrations decreased from upstream to downstream with shifts in TN:TP from values >20 in the freshwater portion, ~20 in the estuarine portion and <20 in the marine portion indicating a spatial shift in nutrient limitations along the continuum. Aquatic productivity analysis suggests that the estuary is net heterotrophic with productivity being negatively influenced by TP, TN and TOC likely due to a combination of effects including shading by high color dissolved organic matter. We conclude that rainfall patterns, land use and the resulting discharges of run-off drives the ecology of the C-43/CRE aquatic continuum and associated biogeochemistry rather than water management associated with Lake Okeechobee.

Keywords: Water Management, Aquatic Productivity, Aquatic Continuum, Water Quality, Climate

Introduction

The aquatic continuum concept (ACC) originated from an ecohydrological concept to understand the transport of material between landscape level patches (i.e. ecosystems) through the aquatic-terrestrial continuum (Jenerette and Lal 2005). Within the literature the ACC is at times synonymous with the river continuum concept (RCC) developed by (Vannote et al. 1980), which formulated a conceptual model and framework for characterizing lotic (running water) ecosystems to describe the ecology of communities along a river system. Both the ACC and RCC bridge terrestrial and aquatic biogeochemical processes by shared fundamental concepts such as nutrient limitation, ecosystem nutrient retention and controls of nutrient transitions (Grimm et al. 2003). The one important link between the terrestrial and aquatic ecosystem is the flow of water and energy (Abrantes and Sheaves 2010; England and Rosemond 2004; Mendoza–Lera et al. 2012). Sediment, organic carbon and nutrient loading from land journey through the continuum that includes a path through soils to the open ocean and all compartments between (i.e. groundwater, floodplains, rivers, lakes, estuaries, etc.). The progression of materials and energy through these systems act as a succession of filters in which the hydrology, ecology and biogeochemical processing are tightly coupled and act to retain a significant fraction of the nutrients transported through each system (Bouwman et al. 2013). Retention of nutrients along the aquatic continuum not only influences the total amount of nutrients reaching the aquatic end-member (i.e. ocean) but also how the systems modify the stoichiometry and forms of these nutrients en-route (Billen 1993; Ensign and Doyle 2006; Reddy et al. 1999). However, anthropogenic alteration of the ecosystem has changed the hydrology and nutrient stoichiometry and forms along the aquatic continuum.

Primary production forms a critical base to estuarine food webs, strongly influencing oxygen and

nutrient dynamics (Caffrey et al. 2013). The magnitude and relative values of gross primary

productivity (GPP) and ecosystem respiration (ER) can vary due to flow (stagnant versus

flowing conditions), inputs of terrestrial or anthropogenic organic carbon (OC) and nutrients

(Odum 1956). Organic matter (OM) in river and estuarine systems are principally derived from

terrestrial vegetation and soils, considered recalcitrant and transported conservatively to the

ocean. However, several biogeochemical processes can contribute to non-conservative behavior

of OM in estuarine ecosystems (Bianchi 2013). Nutrients enter estuaries from either terrestrial

sources via run-off, upstream from freshwater rivers and wetlands or tidal exchange of marine

waters and in some areas, terrestrial inputs of nutrients have had deleterious effects on estuarine

and coastal ecosystems (Bianchi 2013; Jickells 1998). Hydrologic pulsing of freshwater and the

associated delivery of OC and nutrients have been observed to influence net aquatic productivity

in river, wetland and coastal wetland ecosystems (Gallardo et al. 2012; Maynard et al. 2012;

Shen et al. 2015).

Inflow of freshwater to an estuary is a significant landscape process that shapes community

structure (Mannino and Montagna 1997). The management of freshwater inflows to estuaries can

have profound effects on conditions and ecosystem function (Alber 2002; Kimmerer 2002; Sklar

and Browder 1998). Similar to many urbanized coastal areas, south Florida estuaries have been

significantly altered (Macauley et al. 2002). Along with the loss of shoreline habitat and

function, the draining and channelization of wetlands for the purposes of agriculture and

diversion of water for urban development has led to increased wet season flows and decreased

dry season flows (Doering and Chamberlain 1999). This change in flow patterns has changed

the distribution and abundance of key estuarine indicator species such as seagrasses and oysters

(Buzzelli et al. 2015). Oysters are sensitive to salinity and siltation (T. K. Barnes et al. 2007;

Soniat et al. 2013) while salinity patterns also influence the composition, distribution and

abundance of seagrass habitats in estuarine ecosystems (Doering et al. 2002; Greenawalt-

Boswell et al. 2006; Livingston et al. 1998). Unlike other estuaries, artificial connections to Lake

Okeechobee create the potential for transport of material to the Caloosahatchee and St. Lucie

Estuaries from an expanded drainage area extending to the chain of lakes near Orlando, a

distance of over 300 km. In combination with alterations to the local watersheds of both systems

(Doering et al. 2006; Sun et al. 2016; Wan et al. 2014), this connection has resulted in significant

alteration to the timing, distribution and volume of water entering these estuaries.

The completion of the Lake Okeechobee levy in 1937 brought the loss of connectivity with the

Florida Everglades and reduced its total area by 50% (Steinman et al. 2002) and ultimately

disrupting the aquatic continuum. Loss of the Everglades connection also resulted in the loss of

significant amounts of water storage and simultaneously increased nutrient loading to the

Caloosahatchee and St. Lucie estuaries.   While much attention has been directed at Florida Bay,

the coral reefs of the Florida Keys and the Everglades wetlands downstream of Lake Okeechobee

(Porter and Porter 2002), the conditions within the Caloosahatchee and St. Lucie Estuaries are

dictated by base flows, local basin stormwater runoff and regulatory releases from Lake

Okeechobee (Doering and Chamberlain 1999; Chamberlain and Hayward 1996). Two major

problems for the Caloosahatchee River Estuary (CRE) are excessive nutrient loading and high

frequency and duration of undesirable salinity ranges within the estuary (T. Barnes 2005; South

Florida Water Management District et al. 2009).

This study had three objectives to contrast the ecological and biogeochemical processes across

the aquatic continuum. The first objective was to evaluate changes in water quality and quantity

of freshwater flows into the CRE with the hypothesis that upstream water management and

localized climatic conditions have increased flows entering the estuary during the baseline period

(May 1^{st} 1978 – April 30^{th} 2016) resulting in degraded water quality entering the estuary and

increasing long-term trends. The second objective was to investigate water quality characteristics

and limiting nutrients testing the hypothesis that the estuary is a "right-side up" with limiting

nutrients being supplied by up-stream rather than "upside down" estuaries with limiting nutrients

being supplied by marine or ocean sources (Childers et al. 2006a; Walters et al. 1988). The third

objective was to evaluate how freshwater quantity and quality influences aquatic productivity in

the CRE testing the hypothesis that freshwater flow positively influences productivity at

freshwater sites and negatively influence productivity at estuarine or marine sites.

Methods

Study Area

The Caloosahatchee River and its estuary are located on the lower west coast of Florida, USA

(Fig. 1). The historic Caloosahatchee River was originally shallow, meandering with its

headwaters located approximately 100 km inland and tidally influenced up to approximately 70

km upstream. However, to accommodate navigation, flood-control and land-reclamation needs

the river was extended eastward and connected to Lake Okeechobee in late 1800's and early

1900's by what is now called the C-43 canal. Smaller secondary canals were constructed to

irrigate and drain lands surrounding the river. In addition to connecting the river to Lake

Okeechobee three lock-and-dam structures were also installed on the river to control flow and

stage height. The final downstream structure, the S-79 regulates flow into the estuary and acts as

a salinity barrier (T. Barnes 2005; Doering and Chamberlain 1999).

The CRE drains a watershed of approximately 3,450 km^2 including the C-43 basin (70%) and the

tidal basin (30%). Irrigated agricultural lands are among the major land use types in the

watershed and impart a significant demand for water during the dry season. The C-43 canal

conveys basin runoff and releases for flood control and water supply from Lake Okeechobee to

the estuary via the S-79. The pattern and magnitude of flows to the CRE is highly variable due to

the subtropical climate receiving approximately 134 cm yr^{-1} of rainfall (historical average from

1965 to 2005) discharges (including flood control and water supply releases) from Lake

Okeechobee, and withdrawals for irrigation and water supply for agricultural and urban uses

(Qiu and Wan 2013),. Water releases from Lake Okeechobee are made according to a

comprehensive regulation schedule used by the U.S. Army Corps of Engineers (USACE) to

manage the lake water levels for these diverse and often competing uses (U.S. Army Corps of

Engineers and South Florida Water Management District 2010).

Data Sources

Water quality and hydrologic data were retrieved from the South Florida Water Management

District (SFWMD) online database (DBHYDRO; www.sfwmd.gov/dbhydro) for sites within the

Caloosahatchee and the C-43 canals (Fig. 1). Water quality sites were grouped by their location

within the CRE, and historic salinity values (Supplemental Fig. 1); sites S-79, CES02 and CES03

were classified as freshwater, CES04 to CES09 were classified as estuarine and CES11 and

ROOK471 were classified as marine (Fig. 1). The period of record (POR) for flow data spanned

the period between water year (WY) 1979 and 2016 (May 1, 1978 – April 30, 2016). Estuarine

water quality data was slightly more limited, covering WY2000 to 2016. Water quality

parameters used in this study include total phosphorus (TP), orthophosphate (OPO4), total

nitrogen (TN), ammonia (NH4) and nitrate-nitrite (NOx) and total organic carbon (TOC). Total

nitrogen was either directly measured or calculated from the sum of nitrate-nitrite and total

kjeldahl nitrogen. Summary of analytical methods used for each parameter can be found in Table

1.

Water quality data were screened based on laboratory qualifier codes, consistent with FDEP's

quality assurance rule (Florida Administrative Code 2008). Any datum associated with a fatal

qualifier indicating a potential data quality problem was removed from the analysis. Additional

considerations in the handling of analytical data were the accuracy and sensitivity of the

laboratory method used. For purposes of data analysis and summary statistics, data reported as

less than method detection limit (MDL) were assigned the maximum MDL determined during

this study, unless otherwise noted. Conventionally data less-than the MDL are assigned either the

MDL or ½ the MDL, however due to the long POR and changes in MDL values during the study

the highest MDL was selected to advert potential biases in long-term trend analyses.

More recently, *in situ* data collected at high frequencies are available for key parameters related

to estuary function. The River, Estuary and Coastal Observing Network (RECON) are real-time

sensor platforms at fixed sites in the Caloosahatchee Estuary, San Carlos Bay, Pine Island Sound

and Gulf of Mexico. For the purposes of this study, only sites within the Caloosahatchee Estuary,

San Carlos Bay and Gulf of Mexico were considered (Fig. 1) between WY2009 and 2016 (May

1, 2008 and April 30, 2016). The RECON sensor platforms record several biological, chemical

and physical parameters and are mounted to pilings at a depth of 1.5 meters below mean lower

low water (MLLW). Instruments are deployed and maintained from small boats with a maximum

service interval of one to two months (Milbrandt et al. 2016). Chlorophyll, turbidity,

conductivity/salinity, temperature, dissolved oxygen and pressure/depth were measured by the

WET Labs Water Quality Monitoring instrument package (WQM) and colored (chromophoric)

dissolved organic matter (CDOM) was measured by the WET Labs ECO FLS instrument (ECO).

A subset of parameters was used in this study including specific conductance/salinity,

temperature, dissolved oxygen and CDOM. The Seabird Coastal instruments (WQM, ECO) were

calibrated at the factory annually. During service, sensors were cleaned monthly with a nonionic

surfactant (i.e. Triton X-100) and distilled water. The protective cage and exterior surfaces were

coated with antifouling paint prior to deployment and after 1 year, the exterior was stripped and

re-painted. Discrete samples were collected for each monthly service visit using a YSI EXO2

hand-held sonde at the sensor depth to cross validate *in situ* sensor data.

Data Analysis

Annual total and monthly flows were summarized for S-77, S-79 and C-43 basin for the

Caloosahatchee estuary. C-43 basin flow was estimated as the difference between the S-79 and

S-77. Monthly and annual Mann-Kendall trend analysis was performed on each flow datasets

from WY1979 to 2016 using the 'mk.test' function and Pettitt's test for change point detection

using the 'pettitt.test' function in the 'trend' R-package (Pholert 2016). Segmented regression

was applied to cumulative annual flow volume from the S79 and cumulative annual average

rainfall across the watershed to determine changes in the flow-rainfall relationship related to

freshwater inputs into the estuary using the 'segmented' function in the 'segmented' R-package

(Vito and Muggeo 2003). Hydraulic loading rate (HLR) was calculated for each water control

structure by dividing the total annual flow by the area around the C-43 Canal (~334 km^2) and the

CRE (~108 km^2) for the S-77 and S-79, respectively.

Annual TP and TN loads and flow-weighted mean (FWM) concentrations were computed for the

S-77 and S-79 structures, by interpolating water quality concentration daily from grab samples

collected at each respective structure during days of observed flow. Daily interpolated water

quality concentrations were then multiplied by daily flow and summed for each WY. Annual

FWM values were calculated by dividing total annual nutrient load by total annual flow. Mann-

Kendall trend analysis was also performed on annual TP and TN FWM concentrations for the S-

77 and S-79 structures using the 'mk.test' function and change point detection using the

'pettitt.test'. Annual nutrient loads were compared to HLR for both the C-43 canal and CRE

using spearman rank correlation.

Annual arithmetic mean concentrations were computed for each station within the CRE with

greater than six samples per year. Annual mean concentrations were compared between regions

(i.e. freshwater, estuary and marine) using the Dunn's test for multiple comparison for TP, TN,

NH_4 and OPO_4 between WY2000 to 2016 using the 'dunn.test' function in the 'dunn.test' R-

package (Dinno 2015). Longitudinal gradient analysis of annual TP, TN and TOC concentrations

along the estuary was conducted using a Thiel-Sen estimate to derive a non-parametric linear

model using the 'zyp.sen' function in the 'zyp' R-package (Bronaugh and Werner 2013) with

greater than six sampling locations along the longitudinal distance of the estuary. Kendall trend

analysis was performed on annual slope values of the non-parametric linear model for each

parameter (i.e. TP, TN and TOC) by WY.

In addition to decadal trend analysis of water flows and quality, more recent high frequency data

allowed for an analysis of aquatic productivity. Aquatic productivity was estimated using hourly

DO, surface water temperature, salinity, wind speed, air temperature and barometric pressure

data measured at sites along the CRE between May 1st 2009 and April 30th 2016 (Fig. 1).

Sampling locations at Beautiful Island, Fort Myers and Shell Point are characteristically

estuarine while Tarpon Bay and Gulf of Mexico are characteristically marine. Gross primary

productivity (GPP), ecosystem respiration (ER) and net aquatic productivity (NAP) was

estimated using the DO rate of change method first proposed by (Odum 1956) and employed by

others (Cole et al. 2000; Hagerthey et al. 2010; Staehr et al. 2010; E. Thébault and Loreau 2003).

Daily NAP, GPP and ER was calculated on the basis of changes in DO concentrations thought to

be driven by the rates of photosynthesis, respiration and atmospheric exchange (Odum 1956).

Where NAP and ER can be determined directly from the sensor data, GPP is estimated by mass

balance. Within a one-hour interval it is assumed that the change in DO is equality to sum of the

respiration rate and oxygen diffusion rate minus the rate of photosynthesis (Equation 1).

$$\frac{dC}{dt} = P - R + D \qquad\qquad (1)$$

C = Dissolved oxygen concentration (mg L^{-1})
t = time (h)
P = rate of photosynthesis (mg L^{-1} h^{-1})
R= respiration rate (mg L^{-1} h^{-1})
D = rate of oxygen uptake by diffusion across the air-
water interface (mg L^{-1} h^{-1})

230   The rate of oxygen uptake by diffusion across the air-water interface (D) is regulated by the

231   difference in O_2 in the water column from atmospheric equilibrium and the temperature-

232   dependent gas exchange coefficient for oxygen. Wind produces turbulence in the stationary

233   water bodies, facilitating gas exchange processes driven by wind speed (Equation 2).

$$D = k_a(C_s - C) \qquad\qquad (2)$$

D = rate of oxygen uptake by diffusion across the air-
water interface (mg L^{-1} h^{-1})
k_a= volumetric reaeration coefficient (h^{-1})
C_s= Dissolved oxygen saturation concentration (mg L^{-1})
C = Dissolved oxygen concentration (mg L^{-1})

It was assumed that wind speed measured at the Fort Myers weather RECON and the Fort Myers

NOAA weather stations would be a reasonable surrogate for the wind conditions for the

Beautiful Island and Fort Myers RECON stations. Meanwhile the Gulf of Mexico RECON and

the University of South Florida BCP weather stations was used as surrogate for wind conditions

at the Gulf of Mexico, Shell Point and Tarpon Bay RECON stations (Fig. 1 and Supplemental

Table 1). Volumetric reaeration coefficient (k_a) was calculated using three different functions of

wind speed, barometric pressure, air temperature and surface water salinity consistent with

methods by (E. Thébault and Loreau 2003) and (Caffrey et al. 2013).

Net aquatic productivity is the difference between photosynthesis and respiration which can be

computed by rearranging Equation 1. For each day NAP was calculated by summing hourly

diffusion-corrected rates of DO change ($\frac{dC}{dt} - D$) over a 24-hour period, starting and ending at

sunrise. Sunrise and sunset were estimated using algorithms developed by NOAA in a modified

version of the 'metab_day' function in the R package 'SWMPr' (Beck 2016). Hourly ER was

computed as the mean night-time diffusion corrected rates of DO change, it is assumed that GPP

at night is zero (Cole et al. 2000) and the change in DO within an hourly interval during the night

is attributed to respiration and diffusion. Assuming that night time ER is equal to daytime ER,

daily respiration was calculated by multiplying hourly ER by 24 hours. Hourly photosynthesis

was calculated by subtracting ER from diffusion corrected rates of DO change during the

daylight period while daily photosynthesis was computed by summing hourly photosynthesis

values from sunrise to sunset. Volumetric rates of GPP, ER and NAP were multiplied by depth to

yield areal productivity rates (g O_2 m^{-2} d^{-1}) consistent with methods used by others (Caffrey et al.

2013; Cole et al. 2000; Hagerthey et al. 2010; Staehr et al. 2010; E. Thébault and Loreau 2003).

Productivity calculations were performed using a modified version of the 'metabolism' function

in the R package 'SWMPr' (Beck 2016).

The ratio between GPP and ER was compared to zero using the Mann-Whitney/Wilcoxon Rank

Sum test, if the GPP:ER is significantly less than zero the site would be dominantly heterotrophic

meanwhile if the GPP:ER ratio is greater than zero the site would be dominantly autotrophic.

Aquatic productivity rates (GPP, ER and NAP) were compared between ecosystems using

Kruskal-Wallis rank sum test for the entire POR. River, Estuary and Coastal Observing Network

monitoring sites were paired with near-by ambient water quality monitoring locations on days

when water quality samples were collected. Spearman's rank sum correlation was used to

compare daily NAP with TP, TN and TOC concentrations, OC:N, OC:P and N:P molar ratios at

each RECON-Water Quality paired site. Piecewise regression was used to detect change points

in the NAP-TOC, NAP-TP and NAP-TN relationships using the 'piecewise.regression' function

in the 'SiZer' R-package (Sonderegger 2012).

Unless otherwise noted all statistical operations were performed using the base stats R-package.

All statistical operations were performed with R© (Ver 3.1.2, R Foundation for Statistical

Computing, Vienna Austria). The critical level of significance was set to $\alpha = 0.05$.

Results

C-43 Canal-Caloosahatchee River Estuary Hydrology

Annual flow from the Lake Okeechobee to the C-43 basin via the S-77 ranged from 0.05 to 2.68

km^3 yr^{-1} and a mean of 0.73 ± 0.11 km^3 yr^{-1} during the 37-year period between water year 1979

(WY1979) to WY2016 (Fig. 2) with no significant annual trend in annual flow (τ=0.11, ρ=0.35)

and a weak increasing trend in monthly total flow volume (τ=0.14, ρ<0.001). A significant

change point was detected in monthly flow volume after August 1994 (K=16048, ρ<0.001).

Intra- and inter-annual flows entering the C-43 Basin from Lake Okeechobee were highly

variable with little seasonality as indicated by monthly (Supplemental Fig. 2) and annual flow

volumes (Fig. 2) observed at the S-77 structure across the POR. Furthermore, the POR monthly

inter-quantile range is relatively narrow with several monthly values above the 75th quantile.

The Franklin Lock and Dam (S-79) is the final downstream structure along the C-43 canal and

acts as an impediment to saltwater intrusion to the now the C-43 canal (T. Barnes 2005; Buzzelli

et al. 2015). Freshwater flows to the CRE via the S-79 ranged from 0.10 to 3.99 km^3 yr^{-1} during

the same period (Fig. 2) with a POR mean 1.64 ± 0.16 km^3 yr^{-1} with no significant annual trend

in total flow volume (τ=0.09, ρ=0.45) and a weak increasing statistically significant monthly

(τ=0.09, ρ<0.01) trend in flow volume. Monthly flows from the S-79 exhibit a strong seasonality

with peak flows occurring during the August/September time period and low flows occurring

between November and April following the characteristic wet season-dry season cycle

(Supplemental Fig. 2). Annual flow through the S-79 structure was 174 to 321 percent of the

annual flow observed at the S-77, suggesting that in most years, rainfall driven runoff from the

C-43 watershed is the dominant source of water to the CRE at S-79.

Due to localized rainfall and runoff within the C-43 basin, annual flow from the basin ranged

from 0.04 to 1.96 km^3 yr^{-1} between WY1979 and 2016 (Fig. 2) with a mean of 0.92 ± 0.07 km^3

yr^{-1} and no significant annual trend in flow (τ=0.03, ρ=0.82) and a weak increasing trend in

monthly total flow volume (τ=0.15, ρ<0.001). Furthermore, a significant change point in the

time series of flow volume occurred during June 2007 (K=28610, ρ<0.001), likely a response to

a passing tropical storm (Tropical Storm Barry; (Avila 2007) after a prolonged drought period.

Monthly basin flow volumes follow the characteristic wet to dry season pattern with the highest

flow peaking during August and the lowest between November and April (Supplemental Fig. 2).

Furthermore, daily average annual total rainfall across the C-43 basin ranged from 0.82 to 1.94 m

yr^{-1} during the POR with a mean of 1.34 ± 0.04 m yr^{-1}.

Reviewing the record of flow at the S-79 structure and the C-43 basin rainfall, there were notable

changes to the relationship between rainfall and runoff that has occurred throughout the POR

(Fig 3). Additionally, the piecewise regression analysis approach identified several statistically

significant breakpoints in the cumulative rainfall-discharge relationship for the S-79 structure

(R^2=1.00, $F_{(9,28)}$ = 2936, ρ<0.001). The breakpoints along the rainfall and runoff relationship for

the S-79 correspond to WY1986, 1992, 2007 and 2012, which suggests significant changes in

either water management (i.e. S-79 flows), occurrence of extreme climatic events including high

rains or droughts or a combination of both. Based on the double mass curve, the periods 1986 to

1992 and 2007 to 2012 periods were relatively dry periods with respect to rainfall (Supplemental

Fig. 3) and flow as indicated by the decreases in slope. By comparison, the 1992 to 2007 period

was relatively wet.

C-43 Canal-Caloosahatchee River Estuary Water Quality

Annual nutrient loads from Lake Okeechobee to the C-43 basin via the S-77 structure range from

4,925 to 361,792 kg yr^{-1} TP and 86,437 to 4,307278 kg yr^{-1} TN across POR (Fig. 4 and 5) with a

mean of 63,699 ± 10,884 kg yr^{-1} TP and 1,231,271 ± 176,718 kg yr^{-1} TN, respectively. Annual

HLR was significantly positively correlated with annual TN (r = 0.98, ρ<0.001) and TP (r =

0.95, ρ<0.001) loads at the S-77 structure. Meanwhile, annual nutrient loads at the S-79 range

from 24,473 to 535,958 kg yr^{-1} TP and 138,759 to 6,532,271 kg yr^{-1} TN throughout the POR

(Fig. 4 and 5). The mean POR nutrient loads at the S-79 were $224,571 \pm 18,906$ kg yr^{-1} TP and

$2,588,347 \pm 235,791$ kg yr^{-1} TN, respectively. Period of record mean TP load from the S-79 was

approximately 4 times higher than POR mean TP load observed at S-77 while mean TN load at

S-79 was approximately two-times greater than mean TN load at S-77. Annual HLR was

significantly positively correlated with S-79 annual TN (r = 0.92, ρ<0.001) and TP (r = 0.89,

ρ<0.001) loads. The correlation coefficients for annual TN and TP loads versus HLR were lower

for the S-79 than the S-77 suggesting more variability in the load and HLR relationship at the S-

79.

At the S-77 structure, annual FWM TP concentrations ranged from 51 to 165 µg L^{-1} with a mean

of 86 ± 4.2 µg L^{-1} across the POR exhibiting a statistically significant increase (τ=0.31,

ρ<0.001). A breakpoint was observed in FWM TP concentrations at WY1999 (K=249, ρ<0.01)

concurrent with a significant change in flow volume timing through the S-77 (Fig. 4). This

breakpoint corresponds to a period of high tropical activity followed by drought and eventual

changes in water management regulation schedules for Lake Okeechobee. Furthermore, monthly

TP FWM concentrations exhibited a seasonal pattern throughout the POR with higher FWM

concentrations occurring in the late "wet" season (August and September) and lower

concentrations during the "dry" season months between November to April (Supplemental Fig.

4). Annual TN FWM concentrations significantly decreased over the POR (τ=-0.27, ρ<0.05)

ranging from 1.27 to 2.79 mg L^{-1} (Fig 5) with a POR mean of 1.71 ± 0.06 mg L^{-1}. No

statistically significant breakpoint was detected (K=170, ρ=0.09) in annual TN FWM

concentrations at the S-77 structure.

Further downstream at the S-79, annual TP FWM concentrations ranged from 78 to 250 µg L^{-1}

with a mean of 151 ± 6.9 µg L^{-1} for the 37-year period. However, due to inter annual variability

annual FWM concentration did not exhibit a statistically significant trend through time (τ=-0.08,

ρ=0.47) (Fig. 4) and no significant breakpoints detected (K=126, ρ=0.37). Similar to the S-77,

the S-79 exhibited a seasonal fluctuation in TP FWM concentrations during the period record

with concentrations peaking during the June, July and August timeframe (Supplemental Fig. 4).

Annual TN FWM concentrations ranged from 1.17 to 2.57 mg L^{-1} with a mean of 1.64 ± 0.06 mg

L^{-1} during the POR. In contrast to TP, TN exhibited a statistically significant declining trend (τ=-

0.39, ρ<0.001) at the S-79 structure (Fig. 5). A statistically significant breakpoint was detected

for annual TN FWM concentration after WY1995 (K=245, ρ<0.01) where between year

variability decreased resulting in more consistent concentrations with less between year

variability (Fig. 5). Total Nitrogen FWM concentrations for the S-79 were similar to that of the

S-77 with a couple of anomalous WYs that deviate from POR data (Supplemental Fig. 4).

Nutrient Stoichiometry and Water Quality Longitudinal Analysis

The longitudinal water quality gradient along the CRE was evaluated in two ways, the first

compared mean differences between freshwater, estuarine and marine regions over the entire

POR and the second compared the steepness of the gradient on an annual basis. Along the C-43

Canal and CRE, water quality differed between regions (i.e. freshwater, estuary and marine).

Nitrogen (i.e. TN and NH_4), phosphorus (TP and OPO_4) and TOC significantly declined along

the freshwater to marine gradient (Table 2) between WY1999 and WY2016. Orthophosphate

followed the same trend as TP, therefore the remaining analysis will focus on TP.

Stoichiometric ratios of TN:TP ad OC:TP were significantly different between all regions of the

estuary (Table 2), while OC:N ratios were not statistically different between regions (Table 2).

The annual mean TN:TP differed along the CRE with freshwater portions exhibiting a clear

spatial trend with freshwater portion above a molar ratio of 20:1 (Guildford and Hecky 2000)

similar to the Redfield ratio (16:1) derived for dissolved N:P in oceanic systems (Redfield 1958),

estuarine portions were approximately 20 while marine were below 20 (Table 2). This suggests

that the CRE transitions from a potentially P-limited system in the freshwater portion to potential

N-limitation in the marine portion, with the estuarine shifting between N and P limiting

depending on the influence of tidal and freshwater flow. The variability in annual mean TN:TP

were greater in marine (variance: 13.5; range: 8.0– 19.0) and estuarine (variance: 45.2; range: 7.7

– 35.0) portions of the CRE with marine portions always being below a TN:TP ratio of 20 and in

some years the estuarine portion experiencing TN:TP ratios less than 20. Meanwhile freshwater

(variance: 7.5; range: 24.6 – 32.7) portions of the CRE were well above the TN:TP ratio of 20

(Table 2).

Trends in inorganic nutrient stoichiometry differed slightly from bulk nutrient stoichiometry.

Most notably annual mean DIN:DIP ratios were below the Redfield 16:1 ratio (Redfield 1958)

and slightly above the 5:1 ratio suggested by (Doering et al. 2006). However there are instances

when DIN:DIP ratios fell below the 5:1 DIN:DIP ratio in freshwater and estuarine portions of the

CRE (Supplemental Fig. 5). Annual mean DIN:DIP ratios were statistically similar between

estuary and marine portions of the CRE and statistically different from that of the freshwater

portion. Annual mean OC:DIP molar ratio differed significantly along the CRE and OC:DIN

ratios were statistically similar between freshwater and estuarine portions but statistically

different from the marine portion.

Along the gradient of fresh to marine waters TP, TN and TOC decreased (Fig 6). A total of 12

years of annual mean TP data were used in the longitudinal gradient analysis, however, WYs

2003 to 2006 and 2008 were excluded due to the lack of suitable number of samples and

representative stations. Annual mean TP concentrations are highly variable in the freshwater and

estuary reaches while concentrations observed at marine stations are consistent from year to year

(Fig. 6). Concentration gradient rates (i.e. slopes) range from -3.4 to -1.1 μg L^{-1} TP km^{-1} with

rates generally increasing over time (Fig. 6). However, due to the high variability (variance: 0.46

μg L^{-1} TP km^{-1}) the trend in concentration gradient rates was not statistically significant (τ=0.12,

ρ=0.63). Similar to the TP longitudinal gradient analysis, 12 years of annual mean TN data were

used. Concentration gradient slopes ranged from -0.03 to -0.02 mg L^{-1} TN km^{-1} with slopes

increasing over time (τ=0.55, ρ<0.05; Fig. 6). A total of 11 years of annual mean TOC data was

used in the longitudinal gradient analysis specific to TOC, WYs 2003 to 2008 were excluded

from the analysis due to lack of a suitable number of samples and representative stations.

Concentration gradient rates range from -3.8 to -2.4 mg L^{-1} TOC km^{-1} with no significant

temporal trend (τ=-0.31, ρ=0.21; Fig. 6). Furthermore, TP (r=0.81, ρ<0.001), TN (r=0.84,

ρ<0.001) and TOC (r=0.85, ρ<0.001) were positively correlated with monthly mean CDOM at

the RECON-water quality paired sites along the CRE.

Aquatic Metabolism and Influencing Factors

Between WY2009 and WY2016 the Ft Myers, Shell Point and GOM monitoring locations had

adequate data to calculate aquatic metabolism for all WYs during this period. However, data for

Beautiful Island was limited to WY2013-2016 and Tarpon Bay was limited to WY2011-2016.

During the POR daily NAP estimates ranged from -8.4 to 8.2 g O$_2$ m^{-2} d^{-1}, GPP estimates ranged

from -18.8 to 14.0 g O$_2$ m^{-2} d^{-1} and ER estimates ranged from -16.9 to 20.3 g O$_2$ m^{-2} d^{-1} for the five

RECON sites used in this study.

The CRE is predominately heterotrophic with respect to aquatic metabolism in that all sites within the

CRE had a statistically significant GPP:ER ratio less than one indicating that GPP < ER (Table 3). Daily

GPP was significantly different between marine and estuarine regions (χ^2=304.32,

df=1,ρ<0.001), with GPP in marine (1.90 ± 0.03 g O_2 m^{-2} d^{-1}) portions being greater than

estuarine (1.41 ± 0.02 g O_2 m^{-2} d^{-1}) portions of the CRE. Meanwhile, daily ER estimates were

significantly greater in estuarine portions (-1.64 ± 0.02 g O_2 m^{-2} d^{-1}) relative to marine portions (-

1.96 ± 0.02 g O_2 m^{-2} d^{-1}) of the CRE (χ^2=138.61, df=1,ρ<0.001). As a result of the balance

between GPP and ER, daily NAP estimates were significantly greater in marine portions (-0.07 ±

0.01 g O_2 m^{-2} d^{-1}) relative to estuarine portions (-0.24 ± 0.01 g O_2 m^{-2} d^{-1}) of the CRE

(χ^2=341.41, df=1,ρ<0.001).

Daily NAP was negatively correlated with TP (r=-0.31, ρ<0.001), TN (r=-0.41, ρ<0.001), TOC

(r=-0.37, ρ<0.001), TN:TP molar ratio (r=-0.40, ρ<0.001) and TOC:TP molar ratio (r=-0.28,

ρ<0.01) but not correlated with TOC:TN molar ratio (r=-0.03, ρ=0.76). Change-point analysis

identified statistically significant breakpoints for TP, TN and TOC when compared to NAP. A

statistically significant breakpoint was identified in the relationship between NAP and TP (R^2

=0.08, $F_{(3,100)}$=2.71, ρ<0.05) occurring at 53 µg L^{-1} which corresponds with the P boundary

between marine and estuary suggesting different controls of net productivity between regions

(Fig. 7). Additionally, a statistically significant breakpoint was identified in the relationship

between NAP and TN (R^2 =0.12, $F_{(3,100)}$=4.54, ρ<0.01), however the breakpoint identified an

area where only two other samples occurred after the breakpoint at a TN concentration of 0.65

mg L^{-1} (Fig. 7). Even though the piecewise regression indicated a significant change in slope, the

R^2 was relatively low and the breakpoint occurred in an area of decreased data density to the

point that the line after the breakpoint would be unrepresentative. Therefore, the NAP-TN

breakpoint should be viewed with caution, additional investigation is needed to further elucidate

the interaction between TN and NAP in marine and estuarine systems such as the CRE. A

statistically significant breakpoint was identified in the relationship between NAP and TOC (R^2

=0.11, $F_{(3,100)}$=4.06, $\rho<0.01$) at a TOC concentration of 11.89 mg L^{-1} (Fig. 7).

Discussion

Hydrologic dynamics within C-43 Canal-Caloosahatchee River Estuary aquatic continuum

Overall the C-43 Basin and the CRE have undergone numerous alterations to facilitate

navigation, flood control and regulatory releases from Lake Okeechobee (Qiu and Wan 2013).

The conglomeration of these modification in combination with climatic shifts and changes in

upstream water management may confound the interpretation of statistically significant changes

observed in flow dynamics at structures along the C-43 canal and into the CRE. The observed

change in monthly flow volume from the S-77 during WY1994 marks a period where one of the

first Lake Okeechobee regulation schedules known as Operational Schedule 25 or "Run 25"

became effective (Fig. 8). The "Run 25" regulation schedule represented a trip-line type of

operation where if the lake water elevation passes a regulation line, action was taken. During

"Run 25" water levels in Lake Okeechobee were managed from regulatory (flood-control) and

non-regulatory (primarily water supply) purposes while attempting to maintain a relatively high

stage for prolonged periods of time. This high water level within the lake resulted in unintended

impacts to lake ecology (SFWMD 2005; SFWMD and USACE 1999; Vearil 2008). The intra-

and inter-annual variability observed in the flow volumes (Supplemental Fig. 2 and Fig. 2)

suggests a high degree of variability reflective in water management associated with water needs

in either the upstream or downstream waterbodies rather than seasonal hydrologic management.

The pattern and magnitude of flow observed at the S-77 is influenced by the subtropical climate

of south Florida regulatory discharges from Lake Okeechobee and withdrawals for irrigation and

water supply for agricultural and urban uses (Qiu and Wan 2013).

Estimated annual total flow from the C-43 basin was greater than flow from Lake Okeechobee

(i.e. S-77) indicating that on average, basin flow rather than lake management contributed to

excessive freshwater flows to the estuary. Furthermore, the double-mass curve analysis (Fig. 3)

identified several changes in the discharge run-off relationship within the C-43 basin to the

estuary via the S-79, some of these changes corresponded with upstream management

adjustments while other resulted from changes in climate (Fig. 8, Supplement Fig. 3). The period

of 1992 to 2007 included El Nino weather patterns and several hurricanes and tropical storms

making landfall or passed near southwest Florida (Fig. 8), resulting in significant contributions

of rainfall. Due to the large size of the C-43 basin (watershed) and modification to the watershed

to facilitate drainage and irrigation, rainfall-driven watershed run-off is a significant contributor

of flow volume to the estuary. Additionally, during this period several upstream operational

changes came into effect including for Lake Okeechobee implementation of "Run 25" mentioned

earlier, the Water Supply and Environmental (WSE) Operational Schedule which came into

effect in 2000 and the implementation of the Lake Okeechobee Regulation Schedule (LORS)

effective 2008 (SFWMD and USACE 1999; Vearil 2008) (Fig. 8). Prior to May 2000, the Lake

experienced prolonged water depths. Therefore, in an attempt to restore ecological function to

the Lake, a managed recession of occurred in April-May 2000 followed by a prolonged drought

(Fig. 8) therefore WSE was not officially implemented until after the drought broke in 2003.

Similarly, during 2006-2008 timeframe, a severe drought prolonged the official implementation

of LORS and was not initiated until after 2008 (Fig. 8)(Abtew et al. 2009).

Freshwater flow to the CRE is a combination of several upstream dynamics. These dynamics are

driven in part by long- and short-term climate which affects water management for ecological,

flood protection and water supply purposes. The operation of Lake Okeechobee and flows from

the C-43 basin are at times decoupled due to regional climate and rainfall and upstream water

management.

Freshwater Aquatic Environment and Watershed Dynamics

Generally, nutrient loads were greater at S-79 than at S-77 suggesting that the C-43 basin, at

times can act as a nutrient source however it is uncertain if this is due to legacy nutrients in the

river and canal bottom, high nutrient ground water upwelling, basin sourced nutrient run-off or a

mixture of these factors. Furthermore, both the S-77 and S-79 TP and TN loads exhibited large

inter-annual variations predominately driven by changes in flow volumes in response to either

changes in management strategies, climatic events or a combination of these factors (Fig. 4, 5

and 8). As seen in larger river systems flow and watershed run-off drive trends in water quality

with respect to loads (i.e. flow and concentration) (Hagy et al. 2004; Perona et al. 1999; Shrestha

and Kazama 2007; Turner and Rabalais 2003). The CRE upstream watershed is predominately

agricultural lands (~40%) which both creates a significant demand for water during the dry

season and becomes a source of stormwater run-off and nutrients during the wet season

influencing the water quality inputs to the CRE (Qiu and Wan 2013).

In the Chesapeake Bay, year-to-year variability of flow and associated nitrate load from the

Susquehanna River in addition to watershed level effects accounted for changes in downstream

biological response (i.e. volume of hypoxic water; (Hagy et al. 2004). Turner and Rabalais

(2003) have suggested that conversion of lands to intense farming in the Mississippi river

watershed over the past two-centuries has significantly altered water quality downstream. In the

warm and dry Mediterranean climate, seasonal increases in human activates such as domestic

water use and agricultural activates have been linked to high nutrient concentrations in the

Alberche River located in Spain (Perona et al. 1999). In the temperate Fuji River watershed of

Japan, variation in water quality was related to flow, water temperature, and nutrient inputs from

different regions of surrounding watersheds with a variety of land uses (Shrestha and Kazama

2007). Across these systems, flow volume is the primary influence on trends in water quality

downstream.

Change points in annual TP and TN FWM concentrations at both the S-77 and S-79 (Fig. 4 and

5) occurred during or after periods of changes in upstream operations (see previous discussion),

climatic events, changes in off-site agricultural management practices such as best management

practices (BMPs) or implementation of regulatory framework (Fig. 8). The differences in water

quality change points is partly reflective of changes in Lake regulation schedules, climatic events

and regional climate patterns resulting in variability in runoff volumes from the C-43 basin

altering the timing of TP delivered to the C-43 canal and subsequent CRE. However, the change

in TN FWM concentrations at the S-77 seemed to be associated with changes in climatic

conditions within the region and implementation of several environmental regulatory

frameworks used to address water quality issues or a combination of both. These regulatory

frameworks include the Florida Surface Water Improvement and Management (SWIM) act of

1987 which required the implementation of agricultural BMPs. In addition to the SWIM act of

1987, the state of Florida promulgated the "Dairy Rule" in 1987 (62-670.500 Florida

Administrative Code) which reduced run-off from dairy operation entering waterways by

requiring waste water treatment systems in an attempt to reduce nutrient loads (Anderson and

Flaig 1995). In addition to SWIM and the Dairy Rule other regulatory frameworks were

authorized by the State of Florida focusing on the development, implementation and regulation

of BMPs including the Everglades Protection Act, Everglades Forever Act, Lake Okeechobee

Protection Act and the Northern Everglades and Estuaries Protection Program (Fig. 8).

The variability of TP FWM concentration at the S-79 structure could be linked to the

"flashiness" of the C-43 basin facilitated by watershed modifications to promote drainage and

water control (Cook 2014). The CRE and C-43 canal were linked to Lake Okeechobee through

the evolution of the Central and South Florida Flood Control Project (C&SF) during the late

1800's and early 1900's with subsequent modifications to improve navigation and recreation in

the mid 1900's. The features of the C&SF project include a system of canals, water control

structures and storage areas spanning the entirety of southern and central Florida. In addition to

changes of hydrology from the C&SF project a multitude of other structural and physical

alterations has occurred in the CRE and C-43 basin. These alterations resulted in changes to the

historic hydrologic conditions of the watershed due to secondary and tertiary canals that connect

to both the C-43 canal and CRE. These canals provide navigational access and convey water for

both drainage and irrigation purposed to accommodate agricultural and urban areas (Buzzelli et

al. 2016). Due to these canals, in combination with increased development and impervious

surfaces stormwater runoff volumes have increased relative to predevelopment conditions.

Therefore, the variability of TP FWM concentrations at the S-79 structure could be due to

several factors including contributions of flow dependent changes in P concentrations due to

differences in volumes and sources of water (i.e. stormwater run-off, upstream lake management,

etc.).

In addition to the "flashiness" of the basin the seasonality of TP FWM concentrations are

somewhat out of sync of what one would intuitively think. During any given WY, the peak

monthly TP FWM concentrations occur first at downstream water control feature (i.e. S-79)

early in the wet season (i.e. May – August) presumably in response to run-off from the upstream

basin. Meanwhile, peak monthly TP FWM concentrations at the upstream water control feature

(i.e. S-77) occur toward the end of the wet season (i.e. August – October). Timing of nutrient

loads from the structures are similar to FWM concentration trends. This timing in nutrient

delivery is likely important to the ecology of the river and downstream estuary with an

immediate wet season pulse of nutrients at the onset of the wet season followed by a later (less

intense) delivery of nutrients delivered from further upstream subsidizing nutrients required and

are facilitated by retention time of the river (i.e. weeks to months), localized climatic events and

water management.

Nutrient dynamics along the aquatic continuum

Generally, nutrient limitation shifts along the reach of an estuary (R. Howarth et al. 2011). As

waters transition from freshwater to brackish and finally to marine, the water quality

characteristics also change due to sources of inputs (i.e. runoff), internal processes and outputs

from the given system. Generally, the supply of P regulates the production in freshwater systems

while N regulates production in estuarine and marine systems (Conley et al. 2009). Integral to

the concept of nutrient limitation is the supply of one resource relative to another (i.e.

stoichiometry), The difference in limiting nutrients between ecosystems could be linked to the

availability of N, P or both (Doering et al. 1995). The identifiable stoichiometric relationship,

known as the Redfield ratio, suggests that marine planktonic nutrient composition has a

characteristic molar ratio and the abundance of nutrients are regulated by reciprocal interactions

between organisms and the environment (Redfield 1958). The Redfield dissolved N: dissolved P

molar ratio of 16:1 is often used as a benchmark for differentiating N from P growth limiting

conditions for phytoplankton in marine environments (Geider and La Roche 2002; Redfield

1958). However when considering total nutrient values, a ratio of 20:1 has been used to indicate

algal nutrient limitations (Guildford and Hecky 2000) and a ratio of 8:1 for microbial community

nutrient limitation (Heil et al. 2007; McPherson and Miller 1990). It has also been suggested that

total fractions rather than dissolved fractions are better indicators of trophic state and nutrient

limitation as demonstrated in stream ecosystems (Walter K. Dodds 2003).

The aquatic continuum along the C-43 Canal/CRE followed the typical "right side-up" estuarine

pattern (Childers et al. 2006b) with decreasing nutrient concentrations along the flow path with

relatively higher nutrient concentrations at the estuary's headwaters (i.e. freshwater reaches) and

lower nutrient concertation along the downstream segments of the flow path. It is broadly

assumed that N is the primary limiting nutrient in the marine portions of the CRE and P is the

limiting nutrient in the freshwater (i.e. headwaters of the CRE and upstream of the S-79) portions

of the CRE. The TN:TP molar ratio of 20 to indicate N-limitation suggests that freshwater and

estuarine portions of the CRE are P growth limiting or N and P co-limiting. However, there are

times in which the lower estuarine portions of the CRE becomes N-limited (i.e. TN:TP<20)

consistent with results presented by (Doering et al. 2006). Furthermore, the TN:TP molar ratio of

8:1 suggests a potential P growth-limiting conditions to microbial communities in lower estuary

and marine portions of the CRE (Supplemental Fig. 4). Near-shore at the terminus of the CRE,

(Heil et al. 2007) observed low dissolved inorganic N:P (DIN:DIP) molar ratio of 4.5 and

particulate N:P < 8 suggesting N growth limiting conditions for microbial communities. Low

N:P molar ratios are not uncommon and have been observed in other ecosystems including Port

Phillip Bay, Australia, other Australian rivers (i.e. Murray River, Victorian River) and the Peel-

Harvey system in Washington (USA) with some studies suggesting trace metal availability rather

than nutrient limitation regulates phytoplankton/algal blooms (Harris 2001) which could also be

problematic to the CRE and near shore region. These potential nutrient growth limitations to the

CRE is driven in large part by flow and nutrient regimes from upstream sources.

Freshwater discharge from rivers influences estuarine water quality through changes in salinity

regimes, nutrient composition (organic versus inorganic), nutrient quantity (i.e. increased loads)

and inputs of growth limiting nutrients altering the balance of nutrients potentially causing the

occurrence of algal blooms, hypoxia, and other adverse effects to the ecosystem (W.K. Dodds

2006; Doering and Chamberlain 1999; Perez et al. 2010). Indirectly, freshwater discharges also

influence estuarine water quality based on the effects of discharges on estuarine hydrodynamics,

more specifically residence time. The change to residence time and its effect to water quality is

two-fold, with lower residence times particulate nutrients have less time/distance to settle to the

river bottom and lower residence times do not allow for sufficient time for biological uptake

(Doering and Chamberlain 1999; Eyre 1998; Harris 2001; Paerl et al. 1998). The most notable

difference in the CRE water quality over time is the relative increase in the slope of the TN

longitudinal gradient (Fig. 6) over time even though TN concentrations entering the estuary have

significantly declined across the long-term POR. While concentrations are on the decline

entering the estuary, the slightly increasing trend of monthly flow could negatively impact the

water retention time of the estuary, with concurrent point source increases TN load, and/or

increased loads from run-off to the tidal basins (not accounted for in this study)(Buzzelli et al.

2016) could contributing to the increase in the TN gradient of the CRE. Thereby the interplay

between water quality inputs, hydrodynamic variability and estuary dynamics all influence the

water quality condition of the CRE.

Estuarine Metabolism

Estuaries are generally net heterotrophic with respect to aquatic productivity, resulting in

negative NAP estimates (Caffrey 2004; Caffrey et al. 2013). Caffrey (2004) estimated aquatic

productivity across 22 National Estuary Research Reserves spanning five geographic regions

using data from 42 monitoring sites and concluded that all but three were heterotrophic. Hoellein

et al. (2013) also reported the majority of estuaries reviewed in their study were net

heterotrophic. Much like other estuaries, the CRE is predominately heterotrophic with respect to

aquatic productivity in that negative NAP estimates were observed at all sites within the CRE

(Table 3). Aquatic productivity estimates observed in the CRE during this study were consistent

with values observed in other estuarine and river systems as reported in previous studies (Caffrey

2004; Caffrey et al. 2013; Hoellein et al. 2013; Shen et al. 2015; J. Thébault et al. 2008).

Aquatic productivity can be limited by both nutrients and light (Petersen et al. 1997).

Furthermore, a debate regarding which nutrient limits productivity and the roles that N and P

play in limiting productivity across the aquatic continuum has been ongoing (R. Howarth and

Paerl 2008; Paerl 2009; Schindler et al. 2008). Some studies have suggested that productivity can

be limited by N or P but also co-limited by either (R. W. Howarth and Marino 2006; Lewis et al.

2011). In lake ecosystems TP and DOC concentrations were important drivers of aquatic

productivity (Cole et al. 2000; del Giorgio and Peters 1994). Within the CRE the negative

correlation of TP, TN and TOC could be the result of trade-offs between limiting factors of

aquatic productivity. Both nutrients and highly colored freshwater could limit productivity in the

CRE. However, more intensive analysis is needed to determine specific limiting factors related

to light conditions, nutrient concentrations and freshwater influences on aquatic production in the

CRE.

The relationship of NAP and TOC observed within the CRE is consistent with observations in

lake ecosystems, where aquatic productivity changes occurred across OC concentration

gradients. Hanson et al. (2003) observed a breakpoint in NAP estimates at a DOC concentration

of approximately 10 mg L^{-1}. Within the CRE, at low TOC concentrations GPP was relatively

comparable to R which suggests that autochthonous carbon provides most of the liable substrate

for aquatic respiration. Low TOC concentrations were generally associated with marine and

tidally influenced estuary sites (i.e. Gulf of Mexico, Tarpon Bay and Shell Point) (Fig. 6) where

frequent exchange of ocean water occurs and transformation of OC occurs due to changes in

salinity (i.e. ionic strength). Meanwhile, high TOC concentrations and variable NAP were

associated with more freshwater or brackish water sites (i.e. Fort Myers and Beautiful Island).

Variability in the NAP and TOC relationship at these sites could be driven by OC from

freshwater deliveries to the estuary, transformation of OC due to changes in ionic strength,

infrequent tidal flushing high in the estuary and local tidal basin run-off. The difference between

OC change points observed in lake (Hanson et al. 2003; Prairie et al. 2002) and estuary (this

study) ecosystem could also be due to differences in hydrology and TP concentrations. The lake

systems studied by previous researchers (Hanson et al. 2003; Prairie et al. 2002) observed TP

concentrations <20 µg L^{-1}, while TP concentrations within this study were >20 µg L^{-1} (Fig. 7).

Organic C has been shown to increase heterotrophic respiration and microbial productivity, but

OC can also limit productivity via shading of autotrophic organism via increased CDOM or self-

shading via increased biomass (Hanson et al. 2003; Hoellein et al. 2013; Karlsson et al. 2009;

Maranger et al. 2005). Therefore, a region-specific trade-off between CDOM, OC, TP and

aquatic productivity across aquatic ecosystems within the aquatic continuum where water

column parameters directly (nutrient limitation) or in-directly (shading due to high OC) regulate

productivity could occur. Regardless more research is needed to further explore the role of

nutrients and OC in regulating productivity across the aquatic continuum to better understand

and protection flora and fauna in a high managed system.

The Caloosahatchee River Restoration Effort

As part of the Comprehensive Everglades Restoration Plan (CERP) the CRE and surrounding

estuaries were identified as regions of interest. Restoration of these systems to a healthy,

productive aquatic ecosystem is important to maintaining the ecological integrity of the region

(U.S. Army Corps of Engineers and South Florida Water Management District 2010). To restore

the ecological integrity of the CRE, several alternative restoration plans were considered all

emphasized storage of water upstream of the estuary during the wet season to prevent or reduce

high discharge events and treatment of water to reduce nutrient loads to the estuary.

The selected project included a deep reservoir with 0.21 km^3 (170,000 acre-feet) of storage. This

storage capability will allow the reduction of high flow events and greater control of freshwater

releases to the estuary and help improve water quality. Based on modeling efforts to support the

selected restoration plan, weekly high flow characterized as volumes >127 m^3s^{-1} (4,500 ft^3) could

be reduced by approximately 80% and nutrient (i.e. TP and TN) and sediments loads to the

estuary will be reduced by approximately 30% (National Research Council 2010). Furthermore,

modeling suggests an overall improvement to the estuarine environment including estuarine

indicator species such as oysters and seagrasses (U.S. Army Corps of Engineers and South

Florida Water Management District 2010). Based on this information the implementation of the

CERP project for the CRE/C-43 would result in the reduction of flow and nutrient load to the

estuary which in turn could reduce the flow-weighted mean nutrient concentrations. Assuming

that a freshwater condition still exists at the CRE headwater (i.e. S-79), the same longitudinal

gradients observed during this study should persist however the rate of change in nutrient

concentrations along the gradient should hypothetically decline due to the reduction of nutrients

entering the estuary via the S-79, assuming the marine end-member of the gradient doesn't

change. This reduction in nutrients and volume could alter nutrient limitations within the CRE

along the aquatic continuum and potentially reduce the variability observed in this study.

Conclusions

Upstream water management and watershed characteristics are profound drivers of downstream

estuarine ecology. With respect to the CRE, modifications to the C-43 basin have significantly

altered the flow of water and nutrients through the basin and into the estuary resulting in large

inputs of runoff from the terrestrial ecosystem upstream of the CRE (starting point of the aquatic

continuum). Rainfall and run-off from the C-43 basin accounts for the majority of flow into the

CRE rather than water management associated with Lake Okeechobee. Furthermore, the data

presented in this study indicates that the C-43 basin contributes more nutrients to the CRE than

Lake Okeechobee. However, changes in water quality conditions in the C-43 and CRE have

changed through time, responding to changes in upstream water management and regulatory

action intended to improve water quality conditions for the upstream waterbodies (i.e. Lake

Okeechobee), C-43 basin and CRE. Upstream water management plays a significant role in

regulating ecosystem level productivity due to changes in available TP, OC, fresh/saline water

balance and dissolved organic matter.

This work helps to better understand the potential impact of upstream water management, basin

level actions and local mechanisms on water quality and ecological integrity of the CRE by

applying an aquatic continuum approach. Because this approach allows for independent analysis

of each region (i.e. freshwater, estuarine, marine) of the ecosystem, we can better differentiate

how each portion plays an important role in the overall function of the system. We also conclude

that more research is needed to understand aquatic productivity of the CRE and how hydrologic

dynamics such as freshwater releases to the CRE, local tidal basin run-off and groundwater

seepage influence aquatic productivity and ecosystem function. Further, more specific

investigation is needed to address the source and role of nutrients to the CRE and contrast the

function of riverine-estuarine ecosystems in response to upstream pressures.

Acknowledgements

We would like to thank Eric Millbrandt, South Florida Water Management District and the

Sanibel-Captiva Conservation Foundation staff for field and analytical support. The River,

Estuary and Coastal Observing Network is partially supported by NOAA award to E.C.M. and B.

Kirkpatrick for the Gulf of Mexico Coastal Ocean Observing System (GCOOS)

(#NA16NOS0120018) and the LAT Foundation. The authors would like to thank Peter Doering,

John Kominoski, the anonymous reviewers and editor(s) for their efforts and constructive review

of this manuscript.

References

Abrantes, K. G., & Sheaves, M. (2010). Importance of freshwater flow in terrestrial–aquatic energetic

connectivity in intermittently connected estuaries of tropical Australia. *Marine Biology*, *157*(9),

2071–2086. doi:10.1007/s00227-010-1475-8

Abtew, W., & Ciuca, V. (2017). Hydrology of the South Florida Environment. In *South Florida*

Environmental Report. West Palm Beach, FL: South Florida Water Management District.

Abtew, W., Pathak, C., huebner, R. S., & Ciuca, V. (2009). Hydrology of the South Florida Environment. In

South Florida Environmental Report. West Palm Beach, FL: South Florida Water Management

District.

Alber, M. (2002). A conceptual model of estuarine freshwater inflow management. *Estuaries*, *25*(6),

1246–1261. doi:10.1007/BF02692222

Anderson, D. L., & Flaig, E. G. (1995). Agricultural best management practices and surface water

improvement and management. *Water Science and Technology*, *31*(8), 109–121.

Avila, L. A. (2007). *Tropcial Cyclone Report: Tropical Storm Barry (AL022007)* (p. 12). Miami, FL: National

Oceanic and Atmospheric Adminstration - National Hurrican Center.

http://www.nhc.noaa.gov/data/tcr/AL022007_Barry.pdf

Barnes, T. (2005). Caloosahatchee Estuary conceptual ecological model. *Wetlands*, *25*(4), 884–897.

doi:10.1007/BF03173126

Barnes, T. K., Volety, A. K., Chartier, K., Mazzotti, F. J., & Pearlstine, L. (2007). A habitat suitability index

model for the eastern oyster (Crassostrea virginica), a tool for restoration of the Caloosahatchee

Estuary, Florida. *Journal of Shellfish Research*, *26*(4), 949–959.

Beck, M. W. (2016). *SWMPr: Retrieving, Organizing, and Analyszing Estuary Monitoring Data*. CRAN R-

Project. http://CRAN.R-project.org/package=SWMPr

Bianchi, T. S. (2013). Estuarine Chemistry. In J. W. Day, B. C. Crump, W. M. Kemp, & a. Yanez-Aranciba

(Eds.), *Estuarine Ecology* (2nd ed.). New York, NY: John Wiley & Sons.

Billen, G. (1993). The Phison River System: A Conceptual Model of C, N and P Transformations in the

Aquatic Continuum from Land to Sea. In R. Wollast, F. T. Mackenzie, & L. Chou (Eds.),

Interactions of C, N, P and S Biogeochemical Cycles and Global Change (pp. 141–161). Springer

Berlin Heidelberg. doi:10.1007/978-3-642-76064-8_5

Bouwman, A. F., Bierkens, M. F. P., Griffioen, J., Hefting, M. M., Middelburg, J. J., Middelkoop, H., &

Slomp, C. P. (2013). Nutrient dynamics, transfer and retention along the aquatic continuum from

land to ocean: towards integration of ecological and biogeochemical models. *Biogeosciences*,

10(1), 1–22. doi:10.5194/bg-10-1-2013

Bronaugh, D. B., & Werner, A. (2013). *Zhang + Yue-Pilon trends package*. CRAN R-Project. http://CRAN.R-

project.org/package=zyp

Buzzelli, C., Doering, P., Wan, Y., Coley, T., Sun, D., Chen, Z., et al. (2016). *DRAFT: Assessment of the*

responses of the Caloosahatchee River Estuary to low freshwater inflow in the dry season (p.

200). West Palm Beach, FL: South Florida Water Management District.

Buzzelli, C., Gorman, P., Doering, P., Chen, Z., & Wan, Y. (2015). The application of oyster and seagrass

models to evaluate alternative inflow scenarios related to Everglades restoration. *Ecological*

Modelling, *297*, 154–170. doi:10.1016/j.ecolmodel.2014.10.029

Caffrey, J. M. (2004). Factors controlling net ecosystem metabolism in U.S. estuaries. *Estuaries*, *27*(1),

90–101. doi:10.1007/BF02803563

Caffrey, J. M., Murrell, M. C., Amacker, K. S., Harper, J. W., Phipps, S., & Woodrey, M. S. (2013). Seasonal

and Inter-annual Patterns in Primary Production, Respiration, and Net Ecosystem Metabolism in

Three Estuaries in the Northeast Gulf of Mexico. *Estuaries and Coasts*, *37*(1), 222–241.

doi:10.1007/s12237-013-9701-5

Childers, D. L., Boyer, J. N., Davis, S. E., Madden, C. J., Rudnick, D. T., & Sklar, F. H. (2006a). Relating

precipitation and water management to nutrient concentrations in the oligotrophic "upside-

down" estuaries of the Florida Everglades. *Limnology and Oceanography*, *51*(1part2), 602–616.

Childers, D. L., Boyer, J. N., Davis, S. E., Madden, C. J., Rudnick, D. T., & Sklar, F. H. (2006b). Relating

precipitation and water management to nutrient concentrations in the oligotrophic" upside-

down" estuaries of the Florida Everglades. *Limnology and Oceanography*, *51*(1), 602–616.

Cole, J. J., Pace, M. L., Carpenter, S. R., & Kitchell, J. F. (2000). Persistence of net heterotrophy in lakes

during nutrient addition and food web manipulations. *Limnology and Oceanography, 45*(8),

1718–1730. doi:10.4319/lo.2000.45.8.1718

Conley, D. J., Paerl, H. W., Howarth, R. W., Boesch, D. F., Seitzinger, S. P., Karl, E., et al. (2009).

Controlling eutrophication: nitrogen and phosphorus. *Science, 123*, 1014–1015.

Cook, J. (2014). *Influence of freshwater inflow on the abundance and distribution of decapod*

zooplankton in the Caloosahatchee Rvier, Florida (Master of Science). Florida Gulf Coast

University, Fort Myers, FL.

del Giorgio, P. A., & Peters, R. H. (1994). Patterns in planktonic P: R ratios in lakes: Influence of lake

trophy and dissolved organic carbon. *Limnol. Oceanogr, 39*(4), 772–787.

Dinno, A. (2015). *Dunn's test of multiple comparisons using rank sums*. CRAN R-Project. http://CRAN.R-

project.org/package=dunn.test

Dodds, W. K. (2003). Misuse of inorganic N and soluble reactive P concentrations to indicate nutrient

status of surface waters. *Journal of the North American Benthological Society, 22*(2), 171–181.

Dodds, W. K. (2006). Nutrients and the '"dead zone"': the link between nutrient ratios and dissolved

oxygen in the northern Gulf of Mexico. *Frontiers in Ecology and the Environment, 4*(4), 211–217.

Doering, P. H., & Chamberlain, R. H. (1999). Water Quality and Source of Freshwater Discharge to the

Caloosahatchee Estuary, Florida. *JAWRA Journal of the American Water Resources Association,*

35(4), 793–806. doi:10.1111/j.1752-1688.1999.tb04175.x

Doering, P. H., Chamberlain, R. H., & Haunert, D. E. (2002). Using submerged aquatic vegetation to

establish minimum and maximum freshwater inflows to the Caloosahatchee estuary, Florida.

Estuaries, 25(6), 1343–1354. doi:10.1007/BF02692229

Doering, P. H., Chamberlain, R. H., & Haunert, K. M. (2006). Chlorophyll a and its use as an indicator of

eutrophication in the Caloosahatchee Estuary, Florida. *Florida Scientist, 69*, 51.

Doering, P. H., Oviatt, C. A., Nowicki, B. L., Klos, E. G., & Reed, L. W. (1995). Phosphorus and nitrogen

806   limitation of primary production in a simulated estuarine gradient. *Marine Ecology Progress*

807   *Series*, *124*, 271–287.

808   England, L. E., & Rosemond, A. D. (2004). Small reductions in forest cover weaken terrestrial-aquatic

809   linkages in headwater streams. *Freshwater Biology*, *49*(6), 721–734. doi:10.1111/j.1365-

810   2427.2004.01219.x

811   Ensign, S. H., & Doyle, M. W. (2006). Nutrient spiraling in streams and river networks. *Journal of*

812   *Geophysical Research: Biogeosciences*, *111*(G4), G04009. doi:10.1029/2005JG000114

813   Eyre, B. (1998). Transport, retention and transformation of material in Australian estuaries. *Estuaries*,

814   *21*(4), 540–551. doi:10.2307/1353293

815   Florida Administrative Code. Chapter 62-160 Quality Assurance (2008).

816   Gallardo, B., Español, C., & Comin, F. A. (2012). Aquatic metabolism short-term response to the flood

817   pulse in a Mediterranean floodplain. *Hydrobiologia*, *693*(1), 251–264. doi:10.1007/s10750-012-

818   1126-9

819   Geider, R., & La Roche, J. (2002). Redfield revisited: variability of C:N:P in marine microalgae and its

820   biochemical basis. *European Journal of Phycology*, *37*(1), 1–17.

821   doi:10.1017/S0967026201003456

822   Greenawalt-Boswell, J. M., Hale, J. A., Fuhr, K. S., & Ott, J. A. (2006). Seagrass species composition and

823   distribution trends in relation to salinity fluctuations in Charlotte Harbor, Florida. *Florida*

824   *Scientist*, *69*, 24.

825   Grimm, N. B., Gergel, S. E., McDowell, W. H., Boyer, E. W., Dent, C. L., Groffman, P., et al. (2003).

826   Merging aquatic and terrestrial perspectives of nutrient biogeochemistry. *Oecologia*, *137*(4),

827   485–501. doi:10.1007/s00442-003-1382-5

828 Guildford, S. J., & Hecky, R. E. (2000). Total nitrogen, total phosphorus, and nutrient limitation in lakes

829   and oceans: Is there a common relationship? *Limnology and Oceanography*, *45*(6), 1213–1223.

830   doi:10.4319/lo.2000.45.6.1213

831 Hagerthey, S. E., Cole, J. J., & Kilbane, D. (2010). Aquatic metabolism in the Everglades: Dominance of

832   water column heterotrophy. *Limnology and Oceanography*, *55*(2), 653–666.

833 Hagy, J. D., Boynton, W. R., Keefe, C. W., & Wood, K. V. (2004). Hypoxia in Chesapeake Bay, 1950–2001:

834   Long-term change in relation to nutrient loading and river flow. *Estuaries*, *27*(4), 634–658.

835   doi:10.1007/BF02907650

836 Hanson, P. C., Bade, D. L., Carpenter, S. R., & Kratz, T. K. (2003). Lake metabolism: Relationships with

837   dissolved organic carbon and phosphorus. *Limnology and Oceanography*, *48*(3), 1112–1119.

838   doi:10.4319/lo.2003.48.3.1112

839 Harris, G. P. (2001). Biogeochemistry of nitrogen and phosphorus in Australian catchments, rivers and

840   estuaries: effects of land use and flow regulation and comparisons with global patterns. *Marine*

841   *and Freshwater Research*, *52*(1), 139–149.

842 Heil, C. A., Revilla, M., Glibert, P. M., & Murasko, S. (2007). Nutrient quality drives differential

843   phytoplankton community composition on the southwest Florida shelf. *Limnology and*

844   *Oceanography*, *52*(3), 1067–1078. doi:10.4319/lo.2007.52.3.1067

845 Hoellein, T. J., Bruesewitz, D. A., & Richardson, D. C. (2013). Revisiting Odum (1956): A synthesis of

846   aquatic ecosystem metabolism. *Limnology and Oceanography*, *58*(6), 2089–2100.

847   doi:10.4319/lo.2013.58.6.2089

848 Howarth, R., Chan, F., Conley, D. J., Garnier, J., Doney, S. C., Marino, R., & Billen, G. (2011). Coupled

849   biogeochemical cycles: eutrophication and hypoxia in temperate estuaries and coastal marine

850   ecosystems. *Frontiers in Ecology and the Environment*, *9*(1), 18–26. doi:10.1890/100008

Howarth, R., & Paerl, H. W. (2008). Coastal marine eutrophication: control of both nitrogen and

phosphorus is necessary. *Proceedings of the National Academy of Sciences*, pnas–0807266106.

Howarth, R. W., & Marino, R. (2006). Nitrogen as the limiting nutrient for eutrophication in coastal

marine ecosystems: Evolving views over three decades. *Limnology and Oceanography*,

51(1part2), 364–376. doi:10.4319/lo.2006.51.1_part_2.0364

Jenerette, G. D., & Lal, R. (2005). Hydrologic sources of carbon cycling uncertainty throughout the

terrestrial–aquatic continuum. *Global Change Biology*, *11*(11), 1873–1882. doi:10.1111/j.1365-

2486.2005.01021.x

Jickells, T. D. (1998). Nutrient Biogeochemistry of the Coastal Zone. *Science*, *281*(5374), 217–222.

doi:10.1126/science.281.5374.217

Karlsson, J., Byström, P., Ask, J., Ask, P., Persson, L., & Jansson, M. (2009). Light limitation of nutrient-

poor lake ecosystems. *Nature*, *460*(7254), 506–509. doi:10.1038/nature08179

Kimmerer, W. J. (2002). Effects of freshwater flow on abundance of estuarine organisms: physical effects

or trophic linkages? *Marine Ecology Progress Series*, *243*, 39–55.

Lewis, W. M., Wurtsbaugh, W. A., & Paerl, H. W. (2011). Rationale for Control of Anthropogenic Nitrogen

and Phosphorus to Reduce Eutrophication of Inland Waters. *Environmental Science &*

Technology, *45*(24), 10300–10305. doi:10.1021/es202401p

Livingston, R. J., McGlynn, S. E., & Niu, X. (1998). Factors controlling seagrass growth in a gulf coastal

system: Water and sediment quality and light. *Aquatic Botany*, *60*(2), 135–159.

doi:10.1016/S0304-3770(97)00079-X

Macauley, J. M., Summers, J. K., Engle, V. D., & Harwell, L. C. (2002). The ecological condition of south

Florida estuaries. *Environmental monitoring and assessment*, *75*(3), 253–269.

Mannino, A., & Montagna, P. A. (1997). Small-scale spatial variation of macrobenthic community

structure. *Estuaries*, *20*(1), 159–173.

Maranger, R. J., Pace, M. L., del Giorgio, P. A., Caraco, N. F., & Cole, J. J. (2005). Longitudinal Spatial

Patterns of Bacterial Production and Respiration in a Large River–Estuary: Implications for

Ecosystem Carbon Consumption. *Ecosystems*, *8*(3), 318–330. doi:10.1007/s10021-003-0071-x

Maynard, J. J., Dahlgren, R. A., & O'Geen, A. T. (2012). Quantifying spatial variability and biogeochemical

controls of ecosystem metabolism in a eutrophic flow-through wetland. *Ecological Engineering*,

47, 221–236. doi:10.1016/j.ecoleng.2012.06.032

McPherson, B. F., & Miller, R. L. (1990). Nutrient Distribution and Variability in the Charlotte Harbor

Estuarine System, Florida. *JAWRA Journal of the American Water Resources Association*, *26*(1),

67–80. doi:10.1111/j.1752-1688.1990.tb01352.x

Mendoza–Lera, C., Larrañaga, A., Pérez, J., Descals, E., Martínez, A., Moya, O., et al. (2012). Headwater

reservoirs weaken terrestrial-aquatic linkage by slowing leaf-litter processing in downstream

regulated reaches. *River Research and Applications*, *28*(1), 13–22. doi:10.1002/rra.1434

Milbrandt, E. C., Bartleson, R. D., Martignette, A. J., Siwicke, J., & Thompson, M. (2016). Evaluating light

attenuation and low salinity in the lower Caloosahatchee Estuary with the River, Estuary, and

Coastal Observing Network (RECON). *Florida Scientist*, *79*(2).

National Research Council. (2010). *Progress Toward Restoring the Everglades: The 3rd Biennial Review*

(p. 312). Washington DC: The National Academies Press.

Odum, H. T. (1956). Primary production in flowing waters. *Limnol. Oceanogr*, *1*(2), 102–117.

Paerl, H. W. (2009). Controlling Eutrophication along the Freshwater–Marine Continuum: Dual Nutrient

(N and P) Reductions are Essential. *Estuaries and Coasts*, *32*(4), 593–601. doi:10.1007/s12237-

009-9158-8

Paerl, H. W., Pinckney, J. L., Fear, J. M., & Peierls, B. L. (1998). Ecosystem responses to internal and

watershed organic matter loading: consequences for hypoxia in the eutrophying Neuse River

Estuary, North Carolina, USA. *Marine Ecology Progress Series*, *166*, 17.

Perez, B. C., Jr, J. W. D., Justic, D., Lane, R. R., & Twilley, R. R. (2010). Nutrient stoichiometry, freshwater

residence time, and nutrient retention in a river-dominated estuary in the Mississippi Delta.

Hydrobiologia, *658*(1), 41–54. doi:10.1007/s10750-010-0472-8

Perona, E., Bonilla, I., & Mateo, P. (1999). Spatial and temporal changes in water quality in a Spanish

river. *Science of The Total Environment*, *241*(1–3), 75–90. doi:10.1016/S0048-9697(99)00334-4

Petersen, J. E., Chen, C.-C., & Kemp, W. M. (1997). Scaling aquatic primary productivity: Experiments

under nutrient- and light-limited conditions. *Ecology*, *78*(8), 2326–2338. doi:10.1890/0012-

9658(1997)078[2326:SAPPEU]2.0.CO;2

Pholert, T. (2016). *Non-Parametric Trend Tests and Change-Point Detection*. CRAN R-Project.

http://CRAN.R-project.org/package=trend

Prairie, Y. T., Bird, D. F., & Cole, J. J. (2002). The summer metabolic balance in the epilimnion of

southeastern Quebec lakes. *Limnology and Oceanography*, *47*(1), 316–321.

Qiu, C., & Wan, Y. (2013). Time series modeling and prediction of salinity in the Caloosahatchee River

Estuary. *Water Resources Research*, *49*(9), 5804–5816. doi:10.1002/wrcr.20415

Reddy, K. R., Kadlec, R. H., Flaig, E., & Gale, P. M. (1999). Phosphorus Retention in Streams and

Wetlands: A Review. *Critical Reviews in Environmental Science and Technology*, *29*(1), 83–146.

doi:10.1080/10643389991259182

Redfield, A. C. (1958). The biological control of chemical factors in the environment. *American Scientist*,

46(3), 230A–221.

Schindler, D. W., Hecky, R. E., Findlay, D. L., Stainton, M. P., Parker, B. R., Paterson, M. J., et al. (2008).

Eutrophication of lakes cannot be controlled by reducing nitrogen input: Results of a 37-year

whole-ecosystem experiment. *Proceedings of the National Academy of Sciences*, *105*(32),

11254–11258. doi:10.1073/pnas.0805108105

SFWMD. (2005). *Documentation of the South Florida Water Management Model Version 5.5*. West Palm

Beach, FL: South Florida Water Management District.

SFWMD, & USACE. (1999). *Implementation Strateges Towards the Most Efficient Water Managment:*

The Lake Okeechobee WSE Operation Guideline (Final). Jacksonville, FL: The Operational

Planning Core Team.

Shen, X., Sun, T., Tang, S., & Yang, W. (2015). Short-Term Response of Aquatic Metabolism to Hydrologic

Pulsing in the Coastal Wetlands of Yellow River Delta. *Wetlands*, *36*(1), 81–94.

doi:10.1007/s13157-015-0710-y

Shrestha, S., & Kazama, F. (2007). Assessment of surface water quality using multivariate statistical

techniques: A case study of the Fuji river basin, Japan. *Environmental Modelling & Software*,

22(4), 464–475. doi:10.1016/j.envsoft.2006.02.001

Sklar, F. H., & Browder, J. A. (1998). Coastal Environmental Impacts Brought About by Alterations to

Freshwater Flow in the Gulf of Mexico. *Environmental Management*, *22*(4), 547–562.

doi:10.1007/s002679900127

Sonderegger, D. (2012). *SiZer: SiZer: Significant Zero Crossings*. CRAN R-Project. https://CRAN.R-

project.org/package=SiZer

Soniat, T. M., Conzelmann, C. P., Byrd, J. D., Roszell, D. P., Bridevaux, J. L., Suir, K. J., & Colley, S. B.

(2013). Predicting the Effects of Proposed Mississippi River Diversions on Oyster Habitat Quality;

Application of an Oyster Habitat Suitability Index Model. *Journal of Shellfish Research*, *32*(3),

629–638. doi:10.2983/035.032.0302

South Florida Water Management District, Florida Department of Environmental Protection, & Flroida

Department of Agriculture and conserver Services. (2009). *Caloosahatchee River Watershed*

Protection Plan. West Palm Beach, FL: South Florida Water Management District.

http://www.sfwmd.gov/northerneverglades.

Staehr, P. A., Bade, D., Van de Bogert, M. C., Koch, G. R., Williamson, C., Hanson, P., et al. (2010). Lake

metabolism and the diel oxygen technique: State of the science. *Limnology and Oceanography:*

Methods, 8, 628–644. doi:10.4319/lom.2010.8.0628

Steinman, A. D., Havens, K. E., Rodusky, A. J., Sharfstein, B., James, R. T., & Harwell, M. C. (2002). The

influence of environmental variables and a managed water recession on the growth of

charophytes in a large, subtropical lake. *Aquatic Botany, 72*(3–4), 297–313. doi:10.1016/S0304-

3770(01)00207-8

Sun, D., Wan, Y., & Qiu, C. (2016). Three dimensional model evaluation of physical alterations of the

Caloosahatchee River and Estuary: Impact on salt transport. *Estuarine, Coastal and Shelf Science,*

173, 16–25. doi:10.1016/j.ecss.2016.02.018

Thébault, E., & Loreau, M. (2003). Food-web constraints on biodiversity–ecosystem functioning

relationships. *Proceedings of the National Academy of Sciences, 100*(25), 14949–14954.

doi:10.1073/pnas.2434847100

Thébault, J., Schraga, T. S., Cloern, J. E., & Dunlavey, E. G. (2008). Primary production and carrying

capacity of former salt ponds after reconnection to San Francisco Bay. *Wetlands, 28*(3), 841–

851. doi:10.1672/07-190.1

Turner, R. E., & Rabalais, N. N. (2003). Linking Landscape and Water Quality in the Mississippi River Basin

for 200 Years. *BioScience, 53*(6), 563–572. doi:10.1641/0006-

3568(2003)053[0563:LLAWQI]2.0.CO;2

U.S. Army Corps of Engineers, & South Florida Water Management District. (2010). *Central and Southern*

Florida Project Caloosahatchee River (C-43) West Basin Storage Reservoir Integrated Project

Implementation Report and Environmental Impact Statement. Jacksonville, FL: U.S. Army Corps

of Engineers.

Vannote, R. L., Minshall, G. W., Cummins, K. W., Sedell, J. R., & Cushing, C. E. (1980). The River

Continuum Concept. *Canadian Journal of Fisheries and Aquatic Sciences*, *37*(1), 130–137.

doi:10.1139/f80-017

Vearil, J. (2008). *History of Lake Okeechobee Operating Criteria*. Presented at the Greater Everglades

Ecosystem Restoration, Naples, FL.

https://conference.ifas.ufl.edu/GEER2008/Presentation_PDFs/Thursday/Royal%20Palm%20VIII/

1140%20J%20Vearil.pdf

Vito, M., & Muggeo, R. (2003). Estimating regression models with unknown break-points. *Statistics in*

Medicine, *22*, 3055–3071.

Walters, R. A., Josberger, E. G., & Driedger, C. L. (1988). Columbia Bay, Alaska: an 'upside down' estuary.

Estuarine, Coastal and Shelf Science, *26*(6), 607–617.

Wan, Y., Qian, Y., Migliaccio, K. W., Li, Y., & Conrad, C. (2014). Linking Spatial Variations in Water Quality

with Water and Land Management using Multivariate Techniques. *Journal of Environmental*

Quality, *43*(2), 599–610. doi:10.2134/jeq2013.09.0355

Figures and Tables

Figure 1. The C-43 and Caloosahatchee River Estuary (CRE) with water quality, River, Estuary and Coastal Observing Network (RECON), flow, weather and rainfall monitoring locations identified. *Upper left insert* identifies study location relative to the rest of peninsula Florida, USA. *Upper right insert* identifies the C-43 canal, C-43 basin and estuary relative to Lake Okeechobee and associated water control structures.

Figure 2. Annual total flow volumes for the C-43 Canal and Caloosahatchee river estuary between WY1979 and WY2016 (May 1, 1978 – April 30, 2016).

Figure 3. C-43 basin average cumulative rainfall versus S-79 cumulative flow from WY1979 to WY2016 (May 1, 1978 – April 30, 2016). Piecewise regression line is depicted by the black line through the points and breakpoints are identified by the vertical dashed lines. These breakpoints correspond to changes in water management practices and extreme climatic events (i.e. changes in rainfall).

Figure 4. Annual total phosphorus load and annual flow-weighted mean for the S-77 and S-79 structures of the C-43 canal and Caloosahatchee river estuary between WY1979 and WY2016 (May 1, 1978 – April 30, 2016).

Figure 5. Annual total nitrogen load and annual flow-weighted mean for the S-77 and S-79 structures of the C-43 canal and Caloosahatchee river estuary between WY1979 and WY2016 (May 1, 1978 – April 30, 2016).

Figure 6. Left: Annual mean Total Phosphorus (TP), Total Nitrogen (TN) and Total Organic Carbon (TOC) along the Caloosahatchee River Estuary (CRE) between water year (WY) 2000 and 2016 (May 1, 1999 – April 30, 2016). Distance zero is the S-79 structure, the start of the freshwater portion of the CRE. Dark lines indicate earlier water years while light lines indicate later years. Right: Concentration gradient rate for each parameter by WY between WY2000 and 2016, dashed black line indicates Kendall trend using the Thiel-Sen estimate.

Figure 7. Piecewise regression of water quality parameters and net aquatic productivity along the Caloosahatchee River Estuary (CRE) between water year (WY) 2008 and 2016 (May 1, 2007 – April 30, 2016) using five River, Estuary and Coastal Observing Network (RECON) sites and associated paired ambient water quality stations. Piecewise regression lines and associated breakpoints are identified in soil red line and vertical dashed black line, respectively.

Figure 8. Lake Okeechobee operation timeline relative to climatic events and regional regulatory action. El Niño (red point) and La Niña (blue points) occurrence (Data Source: http://www.cpc.noaa.gov), Tropical activity with relative size of the point indicating the number of storms (Data Source: https://coast.noaa.gov) and identification of drought years (yellow points; Data Source: (Abtew et al. 2009; Abtew and Ciuca 2017). SWIM=Surface Water Improvement and Management; 'Dairy Rule' authorized by 62-670.500 Florida Administrative Code; EFA=Everglades Forever Act (Everglades Protection Act and EFA authorized by § 373.4592 Florida Statute); LOPA=Lake Okeechobee Protection Act NEEPPA=Northern

1023   Everglades and Estuaries Protection Program (LOPA and NEEPPA authorized under § 373.4595

1024   Florida Statute).

Load   Flow-Weighted Mean

Table 1. Summary of parameters and analytical methods used for this study.

Parameter	Abbreviation	Method	Reference
Total Nitrogen	TN	SM4500N C	Clesceri et al. (1998)
Total Kjeldahl Nitrogen	TKN	EPA 351.2 SM4500N$_{Org}$ D	US EPA (1993) Clesceri et al. (1998)
Nitrate-Nitrite	NO$_X$	EPA 353.2 SM4500NO$_3$ F	US EPA (1993b) Clesceri et al. (1998)
Ammonia	NH4	EPA 350.1 SM4500NH$_3$ H	US EPA (1993c) Clesceri et al. (1998)
Dissolved Inorganic Nitrogen	DIN	Calculation (NO$_X$ + NH$_4$)	---
Total Phosphorous	TP	EPA 365.1 SM4500PP F	US EPA (1993d) Clesceri et al. (1998)
Ortho-Phosphate	OPO4 or DIP	EPA 365.1 SM4500P F	US EPA (1993d) Clesceri et al. (1998)
Total Organic Carbon	TOC	SM5310 B	Clesceri et al. (1998)

Table 2. Mean, Standard Error (Mean ± SE) and statistical comparison of water quality parameter for each region of the Caloosahatchee River estuary for data collected between May 1, 1999 and April 30, 2016. Values with different letters indicate statistically significant difference according to Dunn's Multiple Comparison test using a critical value of α=0.05. Nutrient ratios (N:P, OC:N, OC:P, DIN:DIP, OC:DIP and OC:DIN) are represented as molar ratios.

Parameter	Units	Freshwater	Estuary	Marine	Kruskal-Wallis Statistics		
					χ^2	df	ρ-value
Total Nitrogen	mg L^{-1}	1.29 ± 0.02 (A)	0.85 ± 0.03 (B)	0.44 ± 0.02 (C)	91.86	2	<0.01
Ammonia	mg L^{-1}	0.073 ± 0.003 (A)	0.058 ± 0.002 (B)	0.051 ± 0.001 (C)	57.28	2	<0.01
Nitrate-Nitrite	mg L^{-1}	0.19 ± 0.012 (A)	0.08 ± 0.005 (B)	0.02 ± 0.002 (C)	92.95	2	<0.01
Total Phosphorus	µg L^{-1}	133.3 ± 4.5 (A)	96.1 ± 3.7 (B)	52.5 ± 0.5 (C)	80.54	2	<0.01
Ortho Phosphate	µg L^{-1}	89.2 ± 3.7 (A)	60.0 ± 2.0 (B)	40.1 ± 0.1 (C)	82.83	2	<0.01
Total Organic Carbon	mg L^{-1}	16.69 ± 0.21 (A)	11.89 ± 0.82 (B)	7.25 ± 2.61 (C)	83.58	2	<0.01
N:P	unitless	26.99± 0.41 (A)	20.57 ± 0.69 (B)	13.56 ± 0.69 (C)	21.69	2	<0.01
OC:P	unitless	29.35 ± 0.53 (A)	30.52 ± 4.43 (B)	33.24 ± 12.76 (C)	21.452	2	<0.01
OC:N	unitless	1.08 ± 0.02 (A)	2.01 ± 0.50 (A)	2.92 ± 1.29 (A)	0.35	2	0.84
DIN:DIP	unitless	8.96 ± 0.44 (A)	7.69 ± 0.19 (B)	7.48 ± 0.11 (B)	9.82	2	<0.05
OC:DIP	unitless	132.3 ± 1.3 (A)	131.0 ± 17.5 (B)	130.5 ± 48.7 (C)	24.30	2	<0.01
OC:DIN	unitless	15.78 ± 0.44 (A)	16.59 ± 2.04 (A)	17.94 ± 6.82 (B)	16.70	2	<0.01

1   Table 3. Mean ± standard error (minimum - maximum) gross primary productivity (GPP), respiration (R),
2   net aquatic productivity (NAP) and GPP: R ratio estimates. Wilcoxon rank sign nonparametric test
3   statistic results comparing site daily GPP:R values to a value of zero (μ=0).

| Site | GPP | R (g O$_2$ m^2 d^{-1}) | NAP | GPP:R | DF | Rank Sign Test | | | |
						Test Statistic	>t	>|t|	<t
Beautiful Island	0.87 ± 0.04 (-4.24 - 6.74)	-1.37 ± 0.03 (-6.39 - 1.91)	-0.5 ± 0.01 (-4.59 - 1.07)	-0.31 ± 0.20 (-31.53 - 195.04)	1027	61693	<0.001	<0.001	1.0(
Ft Myers	1.14 ± 0.04 (-18.84 - 14.05)	-1.34 ± 0.04 (-16.94 - 20.27)	-0.2 ± 0.02 (-4.79 - 7.08)	-1.14 ± 0.25 (-473.04 - 92.87)	2465	389812	<0.001	<0.001	1.0(
Shell Point	1.92 ± 0.03 (-6.25 - 11.72)	-2.08 ± 0.03 (-12.22 - 6.27)	-0.16 ± 0.01 (-3.64 - 6.32)	-0.93 ± 0.03 (-34.26 - 24.97)	2405	93231	<0.001	<0.001	1.0(
Tarpon Bay	2.84 ± 0.04 (-5.97 - 10.65)	-2.89 ± 0.04 (-10.69 - 2.28)	-0.05 ± 0.02 (-8.2 - 2.54)	-0.98 ± 0.01 (-17.69 - 2.68)	1519	10417	<0.001	<0.001	1.0(
GOM	1.23 ± 0.02 (-5.2 - 6.41)	-1.32 ± 0.02 (-11.69 - 3.44)	-0.08 ± 0.01 (-5.84 - 4.03)	-0.89 ± 0.08 (-53.61 - 96.92)	2169	85048	<0.001	<0.001	1.0(

5