LRSDAY: Long-read Sequencing Data Analysis for Yeasts

Jia-Xing Yue[1][*] and Gianni Liti[1][*]

Institutions

1. Université Côte d'Azur, CNRS, INSERM, IRCAN, Nice, France.

Corresponding author statement:

* Corresponding authors: yuejiaxing@gmail.com, gianni.liti@unice.fr

Abstract

Long-read sequencing technologies have become increasingly popular in genome projects due to their strengths in resolving complex genomic regions. As a leading model organism with small genome size and great biotechnological importance, the budding yeast, *Saccharomyces cerevisiae*, has many isolates currently being sequenced with long reads. However, analyzing long-read sequencing data to produce high-quality genome assembly and annotation remains challenging. Here we present LRSDAY, the first one-stop solution to streamline this process. LRSDAY can produce chromosome-level end-to-end genome assembly and comprehensive annotations for various genomic features (including centromeres, protein-coding genes, tRNAs, transposable elements and telomere-associated elements) that are ready for downstream analysis. Although tailored for *S. cerevisiae*, we designed LRSDAY to be highly modular and customizable, making it adaptable for virtually any eukaryotic organisms. Applying LRSDAY to a *S. cerevisiae* strain takes ~43 hrs to generate a complete and well-annotated genome from ~100X Pacific Biosciences (PacBio) reads using four threads.

Key words

Saccharomyces cerevisiae, genome assembly, annotation, PacBio, Oxford Nanopore.

INTRODUCTION

Twenty years ago, the genome sequence of the budding yeast *Saccharomyces cerevisiae* was published. As the first complete eukaryotic genome ever sequenced, this marked a major scientific milestone in biology. Since then, the genomes of many model and non-model organisms have been sequenced especially after the emergence of next-generation sequencing (NGS) technologies. Despite the notably improved throughputs, these NGS technologies suffer from the limitation of short reads and usually result in highly fragmented genome assemblies containing numerous gaps and local mis-assemblies. The recently developed long-read sequencing technologies represented by Pacific Biosciences (PacBio) and Oxford Nanopore offer compelling alternatives to overcome such hurdles, producing high-quality genome assemblies with significantly improved continuity and accuracy. Although initially tested in microbial genome sequencing, their recent applications in complex mammalian and plant genomes also achieved very impressive results[1–4]. With such new sequencing technologies, challenging genomic regions with enriched repetitive elements, strongly biased GC%, or complex structural variants can often be correctly resolved. It is therefore anticipated that genome sequencing projects will routinely adopt long-read-based sequencing technologies in the coming years.

Yeast is a leading model organism with great importance in both basic biomedical research and biotechnological applications. Its small genome size makes it particularly suitable for long-read-based high-coverage genome sequencing. The resulting complete genome assembly with fully-resolved subtelomere structure can in turn illuminate the genetic basis of many complex phenotypic traits with unprecedented resolution. Recently, we used the long-read sequencing technologies to generate the first panel of population-level end-to-end reference genomes of 12 yeast strains representing the major subpopulations of the partially domesticated *S. cerevisiae* and its sister species *Saccharomyces paradoxus*[5]. In addition, there have been a number of other studies carrying out long-read sequencing for many *S. cerevisiae* strains[6–9]. Given the vast genomic and phenotypic diversity of *S. cerevisiae*, we expect the incoming collection of long-read-based high-quality genome assemblies of strains from widespread geographic locations and ecological niches will substantially deepen our understanding on the *S. cerevisiae* natural genetic variation and its associated biotechnological values.

Here we present a highly organized and modular computational framework named Long-Read
Sequencing Data Analysis for Yeasts (LRSDAY), which enables effortless high-quality yeast
genome assembly and annotation production from raw long-read sequencing data. Although a
few popular long-read-based genome assemblers[10–12] and one yeast-specific gene annotation
tools[13] have been developed, a single integrated solution that handles the entire process in a
seemless way is still much needed. Toward this goal, we revamped our original workflow for
deriving the yeast population-level reference genomes[5] into a highly streamlined and self-
contained package with modular design and automated implementation. Under the hood,
LRSDAY contains a series of task-specific modules handling long-read-based *de novo* genome
assembly, short-read-based assembly polishing, reference-guided assembly scaffolding, as well
as comprehensive genomic feature annotations. These tasks can be run individually, selectively
or coordinately depending on users' needs. LRSDAY supports both leading long-read
sequencing technologies: PacBio and Oxford Nanopore. Running the full LRSDAY workflow, the
final output is a chromosome-level genome assembly with high-quality annotations of
centromeres, protein-coding genes, tRNAs, transposable elements (TEs; Ty1-Ty5 for yeasts),
and telomere associated core X and Y' elements. LRSDAY is shipped with various auxiliary
scripts, configuration files and supporting data that enable its semi-automatic installation,
configuration, and execution with minimal manual intervention. This design concept greatly
alleviates the technical barrier for bench biologists with limited bioinformatics experiences (Box
1). In addition, a real case example and its final outputs are also provided for users' test and
comparison. All these task-specific modules, auxiliary files, installed tools, sample outputs,
together with the user-created project directories for the testing example and users' own data
are hosted under the same home directory ($LRSDAY_HOME) in a self-contained fashion (Fig.
1). This design makes LRSDAY well-isolated from the rest of the system and therefore greatly
improved its portability. To sum up, LRSDAY is a highly transparent, automated and powerful
computational framework that handles both genome assembly and annotation, which suits the
needs of the yeast community in the era of long-read sequencing.
98

Overview of the LRSDAY workflow

Genome assembly and annotation are complex computational processes with many
intermediate steps and inputs/outputs involved. With LRSDAY, we designed a highly structured
project directory system to help users to run the whole workflow in an organized and modular
way (Fig. 2). Within such project directory system, the three subdirectories holding the pre-

shipped reference genome as well as the user-supplied long (PacBio or Oxford Nanopore) and
short (Illumina) reads are numbered as "00" and the task-specific subdirectories are numbered
sequentially from "01" to "13" according to their execution orders. For each subdirectory, a self-
explained name is attached after the number index to help users to navigate through the whole
workflow. To run each task, users only need to edit (e.g. to specify the input and output file
paths) and execute the task-specific pipeline scripts pre-placed in these subdirectories. These
pipeline scripts will automatically set environment variables, process the data, and formulate the
results. All computationally intensive tasks can be processed using multiple threads to
substantially save computation time. Below we briefly describe the computational processes
underneath each task-specific module:

01. Long-read-based_Genome_Assembly: Long reads generated from PacBio or Oxford
Nanopore technologies are used to perform *de novo* genome assembly using an
overlap-layout-consensus (OLC) algorithm.

02. Illumina-read-based_Assembly_Polishing: Illumina reads are first clipped and
trimmed to remove potential sequencing adapters and low-quality regions. The cleaned
reads are subsequently mapped to the raw long-read-based genome assembly. The
resulting bam file is further processed for alignment sorting, mate information and read
group fixing, duplicates removal as well as local realignment. Finally, the processed bam
file is used for correcting base-level errors of the long-read-based assembly.

03. Reference-guided_Assembly_Scaffolding: The contigs from the polished genome
assembly are first aligned to the reference genome to identify their shared sequence
homology, based on which reference-guided assembly scaffolding is subsequently
performed. The chromosomal identity of each scaffold is labeled accordingly. Structural
rearrangements captured in the original contigs will stay untouched during the
scaffolding.

04. Centromere_Identity_Profiling: The pre-shipped *S. cerevisiae* centromere sequences
are searched against the scaffolded assembly for chromosome-specific centromere
identity profiling.

05. Mitochondrial_Genome_Assembly_Improvement: The polished contigs
corresponding to the mitochondrial genome are re-collected from the scaffolded
assembly. The mitochondrial contigs spanning over the designated starting point (the
ATP6 gene by default) are broken into subsegments to prevent assembly problems
caused by the circular organization of the mitochondrial genome. The resulting contigs
are then re-assembled into a single linear sequence, which is further circularized by the

138  designated *ATP6* starting point. The nuclear scaffolds and the circularized mitochondrial
139  sequence together form the improved genome assembly.

140 **06. Supervised_Final_Assembly**: A modification list containing the ordering, orientation
141  and naming information of each sequence from the improved genome assembly is
142  generated for users to review and to make manual adjustment when needed. The final
143  genome assembly is further generated based on the user-edited modification list.

144 **07. Centromere_Annotation**: The pre-shipped *S. cerevisiae* centromere sequences are
145  searched against the final genome assembly for centromere annotation.

146 **08. Gene_Annotation**: *De novo* protein-coding and tRNA gene annotations are performed
147  for the final genome assembly, which are further leveraged by the expressed sequence
148  tags (ESTs) and protein sequences alignments.

149 **09. TE_Annotation**: The pre-shipped curated TE library (containing the LTRs and internal
150  sequences of the *S. cerevisiae* and *S. paradoxus* Ty1-Ty5 by default) is searched
151  against the final genome assembly to identify TEs. The identified TEs are further curated
152  and classified into the full-length, truncated, and solo-LTRs of Ty1-Ty5.

153 **10. Core_X_Element_Annotation**: The pre-shipped curated hidden Markov model (HMM)
154  of the *S. cerevisiae* core X elements is searched against the final genome assembly to
155  annotate core X elements.

156 **11. Y_Prime_Element_Annotation**: The pre-shipped representative *S. cerevisiae* Y'
157  element sequence is searched against the final genome assembly to annotate Y'
158  elements. Note that Y' element can have long, short or degenerated forms[14], and we
159  used a representative long-form Y' element as the query to maximize the power of our Y'
160  element annotation.

161 **12. Gene_Orthology_Identification**: The annotated protein-coding genes are compared
162  with the reference protein-coding genes based on both sequence homology and gene
163  order conservation to identify gene orthology relationship between these two sets. Based
164  on such gene orthology relationship, the *Saccharomyces* Genome Database (SGD;
165  http://www.yeastgenome.org/) systematic names are assigned to the annotated protein-
166  coding genes.

167 **13. Annotation_Integration**: The annotations of centromeres, TEs, protein-coding genes,
168  tRNAs, as well as core X and Y' elements are combined and sorted to form a final
169  integrated multi-feature annotation.

Limitations and potential adaptation

In its distributed form, LRSDAY is tailored for the model budding yeast *S. cerevisiae* and its closely related sister species *S. paradoxus* with a number of pre-shipped auxiliary data files configured accordingly. However, given its modular design, the backbone of LRSDAY can be adapted for virtually any eukaryotic organisms to perform genome assembly, assembly polishing, reference-guided scaffolding, protein-coding genes and tRNA annotations, gene orthology identification, and annotation integration. Moreover, those assembly polishing, scaffolding and various annotation modules (Task 02-13) can also be used to analyze existing genome assemblies derived from any or any combination of sequencing technologies. Such flexibility makes LRSDAY very useful for expanded use cases and therefore suits the needs of a broader audience.

Expected improvements

As thousands of yeast strains have been or are currently under sequencing[15–17], our knowledge in the overall genome content diversity[18] of this important model organism is expanding rapidly, revealing a whole new picture of the pan-genome diversity of *S. cerevisiae*. For example, our lab is currently working on characterizing the pan-genome of >1,000 *S. cerevisiae* isolates across the globe (http://1002genomes.u-strasbg.fr/). Future developments of LRSDAY will incorporate such pan-genome dataset to provide additional annotation information for those non-reference genes, especially with regard to their evolutionary origin, population prevalence, and putative functions. Such information will greatly help users to dissect and interpret complex genotype-phenotype interactions in diverse ecological and biotechnological settings. In the protocol described below, we provide a step-by-step walkthrough on how to install, configure, and run LRSDAY for our prepared testing example. Further tips on adapting LRSDAY to other eukaryotic organisms can be found in Box 2.

MATERIALS

EQUIPMENT

Hardware, operating system and network

● This protocol is designed for a desktop or computing server running with x86-64-bit
Linux operating system. Multithreaded processors are preferred to speed up the process
since many steps can be configured to use multiple threads in parallel. For assembling
and analyzing the budding yeast genomes (genome size = ~12 Mb), at least 16 Gb of
RAM and 100 Gb of free disk space are reccomended. When adapted for other
eukaryotic organisms with larger genome sizes, the RAM and disk space consumption
will scale up, majorly during *de novo* genome assembly (performed by Canu[12]). Plese
refer to Canu's manual (http://canu.readthedocs.io/en/latest/tutorial.html) for suggested
RAM and disk space consumption for assembling large genomes. Stable Internet
connection is required for the installation and configuration of LRSDAY as well as for
retrieving the test data.

Software or library requirements

● Bash (https://www.gnu.org/software/bash/)
● Bzip2 (http://www.bzip.org/)
● Cmake (https://cmake.org/)
● GCC and G++ v4.7 or newer (https://gcc.gnu.org/)
● Git (https://git-scm.com/)
● GNU make (https://www.gnu.org/software/make/)
● Gzip (https://www.gnu.org/software/gzip/)
● Java runtime environment (JRE) v1.8.0 or newer (https://www.java.com)
● Perl v5.12 or newer (https://www.perl.org/)
● Python v2.7.9 or newer (https://www.python.org/)
● Python v3.6 or newer (https://www.python.org/)
● Tar (https://www.gnu.org/software/tar/)
● Virtualenv v15.1.0 or newer (https://virtualenv.pypa.io)
● Wget (https://www.gnu.org/software/wget/)

Input data

● Long reads: A single FASTQ file containing PacBio or Oxford Nanopore reads is
needed, which will be used for long-read based *de novo* genome assembly (Task 01).
● Short reads: If paired-end Illumina sequencing is performed, two FASTQ files containing
the forward and reverse Illumina reads respectively are needed. If only single-end

Illumina sequencing data is available, one FASTQ file containing the single-end reads is
needed. The short-read sequencing reads will be used for assembly polishing (Task 02).

● Reference genome: For the budding yeast *S. cerevisiae*, we pre-shipped two reference
genome files (one original assembly and one with subtelomeres and chromosome-ends
hard-masked based on our previous study[5]). The masked version is used for
chromosomal scaffolding to minimize the confounding effect due to interchromosomal
subtelomeric rearrangemnets. When working with organisms of which the subtelomeric
regions are undefined, users can just use a single raw reference genome instead. The
reference genome file(s) will be used for reference-guided scaffolding, mitochondrial
genome assembly improvement and supervised final genome assembly (Task 03, 05
and 06 respectively).

● A number of *S. cerevisiae*-specific auxiliary data have been pre-shipped with LRSDAY
for genomic feature annotation and gene orthology identification (Task 07-12).

Example data

● The test run sequencing data comes from our recent study[5], which consists of both
PacBio and Illumina reads produced from the *S. cerevisiae* strain SK1. The PacBio
reads can be retrieved with the ENA analysis accession number ERZ448251. The
Illumina reads can be retrieved with the SRA sequencing run accession number
SRR4074258. The *S. cerevisiae* reference genome files used by LRSDAY is taken from
the same study with the Genbank accession number GCA_002057635.1. For the testing
example, we have provided bash scripts to automatically download and setup these data
in LRSDAY.

PROCEDURE
259

Download, install and configure LRSDAY   ● **TIMING** **<1 h**
260

1) Enter the following commands in a terminal window:
$ git clone https://github.com/yjx1217/LRSDAY.git
$ cd LRSDAY
$ bash install_dependencies.sh

▲**CRITICAL STEP** Make sure you have a fast and stable internet connection when

running this step since many tools will be downloaded here. Check that all the

prerequisites (see this protocol or the "prerequisite.txt" file in the downloaded LRSDAY

directory) have been installed on your system.

▲**CRITICAL STEP** Upon the successful completion of executing the bash script, you

should see a confirmation message prompted out: "LRSDAY message: This bash script

has been successfully processed! :)". Otherwise, it means an error has occurred during

the execution of the bash script, which interrupted the automatic installation process.

This also apply to all the bash scripts used in Step 25-45. Whenever an error is

encountered, please check the error message and refer to the troubleshooting section

when available. When the cause of the error is fixed, it is always recommended to

completely delete the output files generated by the old run before re-initiate the new run.

? TROUBLESHOOTING

2) Load the environment settings for LRSDAY by entering:

$ source env.sh

After loading the pre-configured environment settings, the current directory should be

assigned to the environment variable $LRSDAY_HOME. You can check to see if the full

path to your current directory is displayed after entering:

$ echo $LRSDAY_HOME

▲**CRITICAL STEP** Make sure to run this command to load the pre-configured

environment settings before the manual setup of LRSDAY in Step 3-22. If you exited

your terminal session before or in the middle of your manual setup, you need to re-load

the environment settings before proceeding. These environment settings will be

automatically loaded each time the task-specific bash pipelines of LRSDAY are

executed.

? TROUBLESHOOTING

3) Pay attention to the final message produced by the install_dependencies.sh script (Step

1) on manual setup instructions. Although most required tools have been automatically

installed and configured, manual downloading and/or configuration are needed for

GATK[19], RepeatMasker[20] and MAKER[21] due to license restriction of these tools or of

their dependent databases. Below, we will go over this process in Step 4-22.

4) Go to the official website of GATK (https://software.broadinstitute.org/gatk/download)

and download GATK-3.8 after logging in. Registration is needed for unregistered GATK

users.

5) Place the downloaded GATK package (file name: "GenomeAnalysisTK-3.8-0.tar.bz2") in

the "LRSDAY/build/GATK-3.8" directory by entering the following command in terminal:

$ mv GenomeAnalysisTK-3.8-0.tar.bz2 $LRSDAY_HOME/build/GATK-3.8

6) Uncompress and set up GATK by entering:

$ tar xjf GenomeAnalysisTK-3.8-0.tar.bz2

$ mv GenomeAnalysisTK-3.8-0*/GenomeAnalysisTK.jar .

$ chmod 755 GenomeAnalysisTK.jar

7) Go to the official website of MAKER ([http://yandell.topaz.genetics.utah.edu/cgi-](http://yandell.topaz.genetics.utah.edu/cgi-bin/maker_license.cgi)

[bin/maker_license.cgi](http://yandell.topaz.genetics.utah.edu/cgi-bin/maker_license.cgi)) and download MAKER v3.00.0-beta" after registration.

8) Place the downloaded file (named as "maker-3.00.0-beta.tgz") in the "LRSDAY/build/"

directory by entering the following command in terminal:

$ mv maker-3.00.0-beta.tgz $LRSDAY_HOME/build/

9) Uncompress MAKER by entering:

$ tar xzf maker-3.00.0-beta.tgz

10) Relocate to the "./maker/src" subdirectory by entering:

$ cd ./maker/src

11) Replace the "Build.PL" script with the LRSDAY pre-shipped copy:

$ cp $LRSDAY_HOME/misc/maker_Build.PL Build.PL

12) Run the replaced "Build.PL" script to configure MAKER:

$ perl Build.PL

13) The Build.PL script will prompt prerequisite warnings/errors and a question related to

"MPI". Here, you should not see any required Perl library that is not installed. You might

see the recommended Perl library "DBD::Pg" is not installed, which is fine. You can

safely ignore the warnings for all required external programs. Accept the default answer

to the MPI question by just pressing enter.

? TROUBLESHOOTING

14) Finalize the installation by entering:

$ ./Build install

15) Relocate to the "$LRSDAY_HOME/build/RepeatMasker" directory :

$ cd $LRSDAY_HOME/build/RepeatMasker

16) Go to the website (http://tandem.bu.edu/trf/trf409.linux64.download.html) to download trf

v4.09.   Place   the   downloaded   file   ("trf409.linux64")   in   the

"$LRSDAY_HOME/build/RepeatMasker"   directory.   Then,   change   the   access

permissions and create a symbolic link for this file by entering:

333	$ chmod 755 trf409.linux64
334	$ ln -s trf409.linux64 trf

17) Go to the website (http://www.girinst.org) and register a user account to download the

most recent version of the RepeatMasker-edition RepBase database (current version:

RepBaseRepeatMaskerEdition-20170127) for RepeatMasker. Place the downloaded file

in the "$LRSDAY_HOME/build/RepeatMasker" directory.

18) Uncompress the RepBase database:

$ tar xzf RepBaseRepeatMaskerEdition-*.tar.gz

19) Get the full path to the current directory by entering:

$ pwd

Remember this path since it will be used for Step 22.

20) Get the full path to $blast_dir by entering:

$ echo $blast_dir

Remember this path since it will be used for Step 22.

? TROUBLESHOOTING

21) Run the configure script for RepeatMasker:

$ perl ./configure

22) The configure script above will prompt several questions:

●   Enter "env" for the question about the installation path of Perl.

●   Just press enter for the question about the installation path of RepeatMasker.

●   Enter the path that you obtained in Step 19.

●   Enter "2" for the question about selecting a search engine. Then enter the path

355   that you obtained in Step 20.

●   Just press enter for the question about the default search engine.

●   Enter "5" to finalize the configuration.

Run LRSDAY with a testing example   ● **TIMING** 42 h

Before proceeding to your own project, it is advised to first run our prepared testing example to

check if LRSDAY is working properly as well as to get acquainted with the logic and workflows

of LRSDAY.

23) Go to the $LRSDAY_HOME directory by entering:

`$ cd $LRSDAY_HOME`

24) Create the project directory. When running LRSDAY with your own data, it is

recommended to make a copy of our "Project_Template" directory to create your own

project directory such as "Project_abc", where "abc" can be any string containing letters,

numbers, or underscores. For this test example, we will make a copy of the

"Project_Template" directory and named it as "Project_Example" by entering:

`$ cp -r Project_Template Project_Example`

25) Prepare the reference genome files. When running LRSDAY with your own data, you

can directly put the reference genome (in FASTA format) in the "00.Ref_Genomes"

subdirectory of your project directory (e.g. "Project_abc"). For this testing example or if

your sequenced organism is *S. cereviaie*/*S. paradoxus*, you can prepare the reference

genome by entering:

`$ cd ./Project_Example/00.Ref_Genome`

`$ bash LRSDAY.00.Prepare_Sc_Ref_Genome.sh`

26) Prepare the long reads. When running LRSDAY with your own data, you can directly put

the long reads in the "00.Long_Reads" subdirectory of your project directory (e.g.

"Project_abc"). For this testing example, you can download the long reads by entering:

`$ cd ./../00.Long_Reads`

`$ bash LRSDAY.00.Retrieve_Reads_from_ENA_BAM.sh`

27) Prepare the Illumina reads. Like for the long reads, you can directly put your Illumina

reads in the "00.Illumina_Reads" subdirectory of your project directory (e.g.

"Project_abc") when running LRSDAY for your own data. For this testing example, you

can download the Illumina reads by entering:

`$ cd ./../00.Illumina_Reads`

`$ bash LRSDAY.00.Retrieve_Reads_from_SRA.sh`

? TROUBLESHOOTING

28) Run long-read-based *de novo* genome assembly. This step can be run with multiple

threads to speed up the process. Depending on the CPU configuration of your Linux

server/desktop, you might want to edit the "threads=" option in the bash script

"LRSDAY.01.Long-read-based_Genome_Assembly.sh" to enable multiple threading.

You can do the same for all the following tasks whenever the "threads=" option is

provided in the corresponding task-specific bash script. Simple text editors such as

emacs, vim, gedit or pico are highly recommended for such editing. Rich text editors

might not work. Upon the completion of genome assembly, a summary file

("SK1.canu.stats.txt" for this test example) will be generated to report some basic

summary statistics (e.g. total assembly size, N50, L50, GC%, etc) to help you to gauge

the genome assembly quality (Table 1).

$ cd ./../01. Long-read-based_Genome_Assembly

$ bash LRSDAY.01.Long-read-based_Genome_Assembly.sh

▲**CRITICAL STEP** Note this step will take long to finish (see **TIMING**), so we

recommend to run this step and all the other time-consuming steps using "nohup"

(https://en.wikipedia.org/wiki/Nohup), which allows the process to continue running after

you exit the terminal or logout from the server. As an example, you can run the bash

script using nohup as follows:

$ nohup bash LRSDAY.01.Long-read-based_Genome_Assembly.sh >run_log.txt 2>&1

&

▲**CRITICAL STEP** When running LRSDAY with your own data, modify the bash script

to specify the file paths and the prefix for your input and output data (same for all

following steps).

? TROUBLESHOOTING

29) Polishing genome assembly with Illumina reads. This step can be run with multiple

threads.

$ cd ./../02.Illumina-read-based_Assembly_Polishing

$ bash LRSDAY.02.Illumina-read-based_Assembly_Polishing.sh

▲**CRITICAL STEP** When running LRSDAY for your own data, if you performed PacBio

sequencing and also have access to the PacBio SMRT Analysis software package

(http://www.pacb.com/products-and-services/analytical-software/smrt-analysis/),   we

recommend to run the first-pass of assembly polishing based on the raw PacBio reads

by using PacBio's own Quiver/Arrow pipeline[10] before proceeding to this step. Likewise,

if you performed Oxford Nanopore sequencing, we recommend using nanopolish

(https://github.com/jts/nanopolish) or equivalent tools to polish the genome assembly

using the raw Nanopore reads first.

30) Chromosome-level scaffolding for the raw *de novo* assembly. This step can be run with

multiple threads. Upon completion, a list of summary statistics ("SK1.ragout.stats.txt" for

this test example) will be generated for the scaffolded assembly (Table 1).

$ cd ./../03.Reference-guided_Assembly_Scaffolding

$ bash LRSDAY.03.Reference-guided_Assembly_Scaffolding.sh

▲**CRITICAL STEP** Please check the generated genome-wide dotplot

"SK1.ragout.filter.pdf" (Fig. 3a) to verify the correctness of chromosome assignment and

435	applying manual adjustment if necessary in Step 32. When running LRSDAY with your
436	own data, you might see one scaffold correspond to more than one reference
437	chromosomes, which could be due to shared sequence homology between duplicated
438	regions or interchromosomal rearrangements Both types of events can be correclty
439	interpreted based on the genome-wide dotplot generated in this Step. In either case,
440	LRSDAY can correctly assign chromosomal identity of the corresponding scaffold based
441	on its centromere annotation in Step 31. Also please check the "SK1.ragout.agp" file for
442	the details of reference-based scaffolding. When running LRSDAY for your own data, if
443	you have strong evidence for mis-scaffolding based on prior knowledge or other
444	experimental data (e.g. mate-pair libraries or chromosomal contact data), you can break
445	up the corresponding ragout scaffolds back to contigs and re-joined them with corrected
446	order using the pre-shipped Perl scripts "break_scaffolds_by_N.pl",
447	"join_contigs_by_N.pl" and "extract_region_from_genome.pl" in the
448	"$LRSDAY_HOME/scripts" directory. A scenario for such use case is when the
449	breakpoints of structural rearrangements are also the breakpoints of the genome
450	assembly. In this case, the reference-based scaffolding will arrange the contigs
451	according to the reference genome configuration and therefore un-do the genome
452	rearrangement.
453	▲CRITICAL STEP Due to the high AT and repeat contents and the circular
454	conformation of the mitochondrial genome, multiple contigs corresponding to the
455	mitochondrial genome are often observed, as shown in the mitochondrial genome
456	dotplot "SK1.ragout.chrMT.filter.pdf" (Fig. 3a, inset). A list of such mitochondrial contigs
457	will be generated in the file "SK1.mt_contig.list", which will be used in Step 32 for
458	improving mitochondrial genome assembly.
459	31) Perform centromere profiling for the scaffolded genome assembly.
460	$ cd ./../04.Centromere_Identity_Profiling
461	$ bash LRSDAY.04.Centromere_Identity_Profiling.sh
462	▲CRITICAL STEP The chromosome-specific centromere identies profiled here will be
463	used as another layer of information for the final chromosomal identity assignment in
464	Step 33. The profiled centromere idenitites should usually agree well with the
465	chromosomal identity labeled in Step 30, so that chrI will have the CEN1 centromere and
466	chrII will have the CEN2 centromere, etc. Exception can occur when interchromosomal
467	rearrangements are involved in your sequenced species/strain. In such case, we

| 468 | recommend to name those rearranged chromosomes based on their encompassed |
| 469 | centromeres in Step 33. |

32) Mitochondrial genome assembly improvement.

    $ cd ./../05.Mitochondrial_Genome_Assembly_Improvement

    $ bash LRSDAY.05.Mitochondrial_Genome_Assembly_Improvement.sh

    ▲**CRITICAL STEP** Check the "SK1.mt_improved.chrMT.filter.pdf" file for the final mitochondrial genome dotplot and compared with the mitochondrial genome dotplot generated in Step 30 to see if the mitochondrial genome assembly has been improved (Fig. 3b, inset).

33) Finalize the chromosome assignment and the genome assembly. This step consists of two substeps with manual intervention in between:

    i) Generate the SK1.modification.list file.

        $ cd ./../06.Supervised_Final_Assembly

        $ bash LRSDAY.06.Supervised_Final_Assembly.1.sh

    ii) Edit the generated "SK1.modification.list" file based on the genome-wide dotplot generated in Step 30 and the centromere profiles generated in Step 31. The "SK1.modification.list" file consists of three comma-separated columns, which correspond to the original sequence name, sequence orientation, and new sequence name respectively. With this file, you can do three types of editing:

        a) If you need to change the current sequence order, you can move the corresponding row of that sequence upward or downward to reflect the correct order.

        b) If you need to invert the orientation of a given sequence, you can change its orientation from "+" to "-" in column 2.

        c) If you need to rename a given sequence, you can modify column 3 to specify the new name.

    For the testing example here, we need to move the row "chrIX,+,chrIX" downward to place it after the row "chrVIII,+,chrVIII", so that chrIX will be placed after chrVIII in the final assembly. Also, we need to change the row "chrMT_Contig1,+,chrMT_Contig1" to "chrMT_Contig1,+,chrMT" to rename the sequence name for the mitochondrial genome assembly.

    iii) Once all the modifications have been specified, run the following script to generate the final genome assembly as well as the associated genome-wide dotplot (Fig. 3b) and assembly statistics (Table 1):

$ bash LRSDAY.06.Supervised_Final_Assembly.2.sh

34) Re-run centromere annotation for the final genome assembly:

$ cd ./../07.Centromere_Annotation

$ bash LRSDAY.07.Centromere_Annotation.sh

35) Annotate protein-coding genes and tRNAs for the final genome assembly. This step can
be run with multiple threads.

$ cd ./../08.Gene_Annotation

$ bash LRSDAY.08.Gene_Annotation.sh

▲CRITICAL STEP When running LRSDAY with your own data, if you have native
transcriptome/EST assembly for your sequenced strain/species, you can first make a
copy of the default configuration file "$LRSDAY_HOME/misc/maker_opts.ctl" and place
it in the task-specific directory "$LRSDAY_HOME/Project_abc/08.Gene_Annotation".
Then, edit the line 16 of the configuration file that you have just created to provide the
full path of your transcriptome/EST assembly. Finally, edit the line 13 of the bash script
"LRSDAY.08.Gene_Annotation.sh" to provide the full path of your edited configuration
file. This path should be:
"$LRSDAY_HOME/Project_abc/08.Gene_Annotation/maker_opts.ctl". For all these
changes, you should replace "Project_abc" with the real directory name that you created
in Step 24.

36) (Optional) A file containing a list of genes with suspicious annotations will be generated
in the file "SK1.maker.manual_check.list". As labeled in this file, these annotated gene
models could be fragmented, frameshifted or containing internal stop codons.
Potentially, these genes could be good candidates for pseudogenes. You can manually
inspect the annotated gene models of these genes by loading the annotation result
"SK1.maker.gff3" together with the protein/EST-alignment evidence files generated
during the annotation (SK1.protein_evidence.gff3 and SK1.est_evidence.gff3) into IGV[22]
for further curation.

37) (Optional) Dedicated mitochondrial protein-coding and RNA annotation. If you are
interested in studying mitochondrial genomes, we highly recommend running dedicated
mitochondrial feature annotation with specialized software such as MFannot
(http://megasun.bch.umontreal.ca/cgi-bin/mfannot/mfannotInterface.pl). Although
MFannot does not support local installation by far, you can run MFannot conveniently via
its web portal. Select the correct genetic code table (e.g. "3 Yeast Mitochondrial" for
annotating yeast mitochondrial genomes) for your analysis.

38) Annotate transposable elements (TEs) for the final genome assembly. This step can be
run with multiple threads.
$ cd ./../09.TE_Annotation
$ bash LRSDAY.09.TE_Annotation.sh
39) (Optional) TE activity can be highly dynamic in the genome with many complex cases
such as fragmentation and nested insertion. In LRSDAY, we used REannotate[23] to
automatically resolve these complex cases, which works greatly for most cases but it
could occasionally misjoin two adjacent TEs when they are closely spaced. You can
further inspect and curate the LRSDAY TE annotation ("SK1.TE.gff3") by visualizing it in
IGV[22] together with the raw REannotate annotation ("SK1.REannotate.gff"). For each TE
found in the file "SK1.TE.gff3", examine its corresponding LTR and internal region
structure based on the file "SK1.REannotate.gff" to check for misjoinings. If needed, you
can manually edit the corresponding annotation in the "SK1.TE.gff3" file to decouple the
misjoinings.
40) Annotate yeast telomere-associated core X elements for the final genome assembly:
$ cd ./../10.Core_X_Element_Annotation
$ bash LRSDAY.10.Core_X_Element_Annotation.sh
41) (Optional) In LRSDAY, we label the identified core X elements to be "partial" if they are
shorter than 300 bp. This should work for most cases but we recommend to inspect the
generated alignment file ("SK1.X_element.aln.fa") for further curation and to manually
adjust such "partial" labeling in the annotation file ("SK1.X_element.gff3") when needed.
42) Annotate yeast telomere-associated Y' elements for the final genome assembly:
$ cd ./../11.Y_Prime_Element_Annotation
$ bash LRSDAY.11.Y_Prime_Element_Annotation.sh
43) (Optional) Like for the core X element annotation, we used a hard length cutoff (3500 bp)
to label if the identified Y' elements are "partial". We suggest to manually inspect the
generated alignment file ("SK1.Y_prime_element.aln.fa") to check if the "partial" labeling
is needed and edit the annotation file ("SK1.Y_prime_element.gff3") accordingly.
44) Orthology identification for protein coding genes. In this step, we create a gene orthology
relationship list between the annotated proteome and the SGD *S. cerevisiae* reference
proteome based on both sequence similarity and synteny conservation. Based on this
list, we further attach SGD systematic names to our gene annotation as shown in the
"Name=" field of the generated GFF3 file ("SK1.updated.gff3"). For a given annotated
gene, when more than one orthologous gene can be found in the SGD reference

proteome, we will labeled all of its co-orthologs in the "Name=" filed with "/" in between,

whereas when no orthologous gene can be found, we will label its gene name as

"Name=NA". This step can be run with multiple threads.

$ cd ./../12.Gene_Orthology_Identification

$ bash LRSDAY12.Gene_Orthology_Identification.sh

45) Integrate the annotation of different genomic features into a unified GFF3 file.

$ cd ./../13.Annotation_Integration

$ bash LRSDAY.13.Annotation_Integration.sh

? TROUBLESHOOTING

581 Troubleshooting advice can be found in Table 2.

● TIMING

The following timing information was measured on a Linux computing server with an Intel Xeon

CPU E5-2630L v3 (1.80GHz) using four threads. Enable multithreading can substantially

decrease the processing time. Those optional steps were not processed when measuring the

computation time.

Step 1-22, set up LRSDAY: < 1h.

Step 23-24, prepare the project directory for the test example: 5 s.

Step 25, prepare the reference genomes for the test example: 1 s.

Step 26, prepare the long reads for the test example: 22 min.

Step 27, prepare the Illumina reads for the test example: 20 min.

Step 28, *de novo* assembly using long-reads: 18 h.

Step 29, assembly polishing using Illumina reads: 1h.

Step 30, reference-guided scaffolding for the raw assembly: 8 min.

Step 31, centromere identity profiling for the scaffolded assembly: 1 s.

Step 32, mitochondrial genome assembly improvement: 4 min.

Step 33, finalize genome assembly with supervised editing: 1 min.

Step 34, centromere annotation for the final assembly: 1s.

Step 35, protein-coding gene and tRNA annotation for the final assembly: 21 h.

602  Step 38, TE annotation for the final assembly: 5 min.

603  Step 40, core X element annotation for the final assembly: 2 min.

604  Step 42, Y' element annotation for the final assembly: 2.5 min.

605  Step 44, gene orthology identification for the annotated protein-coding genes: 20 min.

606  Step 45, final annotation integration: 1 min.

ANTICIPATED RESULTS

In this section, we describe the major outputs of the test run "Project_Example" as follows. The

final genome assembly and annotation outputs generated with this test example is provided in

the directory "Example_Outputs" for users to make direct comparison with their own results.

Task 01 (Step 28):

● SK1.canu.fa: the long-read-based *de novo* genome assembly containing all the

contigs assembled by Canu[12].

● SK1.canu.stats.txt: the summary table of basic assembly statistics, including

information on the number of the assembled sequences, the total length of the

assembled sequences, the minimal, maximal, mean and median lengths of the

assembled sequences, the N50, L50, N90, and L90 of the assembled

sequences, as well as the base composition (A%, T%, G%, C%, AT%, GC% and

N%) of the assembled sequences. Users can compare this file with the similar

file generated in Step 30 and Step 33. We also summarized such comparison in

Table 1.

● SK1_canu_out: the directory containing all the output files of Canu.

Task02 (Step 29):

● SK1.pilon.fa: the polished genome assembly generated by Pilon[24].

● SK1.pilon.vcf: the variants identified by Pilon based on short reads mapping

against the input genome assembly.

● SK1.pilon.changes: a space-delimited record of all the changes that Pilon made

during the assembly polishing. The four columns are: the original sequence

coordinate, the new sequence coordinate after the correction, the original base,

the new base after the correction.

● SK1.realn.bam: the bam file of short reads mapping against the input genome

assembly.

Task 03 (Step 30):

● SK1.ragout.fa: the scaffolded genome assembly based on the reference

genome.

● SK1.ragout.stats.txt: the summary table of basic assembly statistics for the

scaffolded genome assembly. Users can compare this file with the similar file

generated in Step 28 and Step 33. We also summarized such comparison in

Table 1.

● SK1.ragout.agp: the NCBI AGP file recording the order and orientation of each
input contigs used during scaffolding.
● SK1_ragout_out: the directory containing all the output files of Ragout[25].
● SK1.ragout.filter.pdf: the genome-wide dotplot for the comparison between the
scaffolded assembly and the reference genome.
● SK1.mt_contig.list: the list of contigs in the scaffolded assembly that corresponds
to the mitochondrial genome. This file will be used for Step 32.
● SK1.mt_contig.fa: the sequences of the contigs in the scaffolded assembly that
corresponds to the mitochondrial genome.
● SK1.ragout.chrMT.filter.pdf: the dotplot for the comparison between the
scaffolded mitochondrial genome assembly and the reference mitochondrial
genome.
Task 04 (Step 31):
● SK1.centromere.gff3: the profiled centromere idenities for the scaffolded genome
assembly.
Task 05 (Step 32):
● SK1.mt_improved.fa: the improved genome assembly with better processing (re-
assembling and circularization) of the mitochondrial genome.
● SK1.mt_improved.chrMT.filter.pdf: the dotplot for the comparison between the
improved mitochondrial genome assembly and the reference mitochondrial
genome. You should see much better collinearity in this plot than the similar plot
generated in Step 30.
Task 06 (Step 33):
● SK1.modification.list: the assembly modification list for manual editing to guide
the final genome assembly.
● SK1.final.fa: the final genome assembly generated by LRSDAY.
● SK1.final.filter.pdf: the genome-wide dotplot for the comparison between the final
genome assembly and the reference genome.
● SK1.final.stats.txt: the summary table of basic assembly statistics for the final
genome assembly. Users can compare this file with the similar file generated in
Step 28 and Step 30. We also summarized such comparison in Table 1.
Task 07 (Step 34):
● SK1.centromere.gff3: the centromere annotation for the final genome assembly.
Task 08 (Step 35):

- SK1.maker.raw.gff3: the raw MAKER[21] annotation for protein-coding genes and tRNA genes.
- SK1.maker.gff3: the processed MAKER annotation for protein-coding genes and tRNA genes with systematically assigned gene IDs.
- SK1.maker.output: the output directory of the MAKER run.
- SK1.protein_evidence.gff3: the protein-to-genome alignment evidences generated by MAKER. This file can be used for manual curation of those suspicious annotations.
- SK1.est_evidence.gff3: the EST-to-genome alignment evidences generated by MAKER. This file can be used for manual curation of those suspicious annotations.
- SK1.maker.trimmed_cds.fa: the CDSs of the MAKER protein-coding annotation with the out-of-frame parts trimmed.
- SK1.maker.trimmed_cds.log: the log file of the CDS trimming for the MAKER protein-coding gene annotation.
- SK1.maker.pep.fa: the translated protein sequences of the trimmed CDSs derived from the MAKER protein-coding gene annotation.
- SK1.maker.manual_check.list: a list of suspicious gene annotations for manual curation.
- SK1.maker.PoFF.gff: the gene synteny information derived from "SK1.maker.gff3", which will be used for Task 12 (Step 44).
- SK1.maker.PoFF.ffn: same as "SK1.maker.trimmed_cds.fa" but with simpler sequence IDs, which could be used for Task 12 (Step 44).
- SK1.maker.PoFF.ffa: same as "SK1.maker.protein.fa" but with simpler sequence IDs, which will be used for Task 12 (Step 44).

Task 09 (Step 38):
- SK1.REannotate.gff: the raw TE annotation from REannotate. This file can be used for further curating TE annotation.
- SK1.TE.gff3: the final TE annotation from LRSDAY.

Task 10 (Step 40):
- SK1.X_element.gff3: the final core-X element annotation from LRSDAY.
- SK1.X_element.fa: the sequences of all the annotated core X elements.
- SK1.X_element.aln.fa: the sequence alignment of all the annotated core X elements for further checking whether the annotated feature is complete or

partial and whether this is consistent with the labeling in the annotation file
"SK1.X_element.gff3".

Task 11 (Step 42):

● SK1.Y_prime_element.gff3: the final Y' element annotation from LRSDAY.

● SK1.Y_prime_element.fa: the sequences of all the annotated Y' elements.

● SK1.Y_prime_element.aln.fa: the sequence alignment of all the annotated Y'
elements for further checking whether the annotated feature is complete or
partial and whether this is consistent with the labeling in the annotation file
"SK1.Y_prime_element.gff3".

Task 12 (Step 44):

● SK1.proteinortho: the gene orthology mapping between the annotated assembly
and the reference genome based only on sequence similarity.

● SK1.poff: the gene orthology mapping between the annotated assembly and the
reference genome based on both sequence similarity and synteny conservation.

● SK1.updated.gff3: updated gene annotation with reference-based gene name
labeling.

Task 13 (Step 45):

● SK1.final.gff3: the final integrated annotation from LRSDAY.

● SK1.final.trimmed_cds.fa: the CDSs of the final protein-coding gene annotation
with the out-of-frame parts trimmed.

● SK1.final.trimmed_cds.log: the log file of the CDS trimming for the final protein-
coding gene annotation.

● SK1.final.pep.fa: the translated protein sequences of the trimmed CDSs derived
from the final protein-coding gene annotation.

● SK1.final.manual_check.list: a list of suspicious gene annotations for manual
curation.

AKNOWLEDGEMENTS

We thank Gilles Fischer, Samuel O'Donnell and Lorenzo Tattini for testing LRSDAY and providing valuable feedback. This work was supported by ATIP-Avenir (CNRS/INSERM), Fondation ARC pour la Recherche sur le Cancer (PJA20151203273), Marie Curie Career Integration Grants (322035), Agence Nationale de la Recherche (ANR-16-CE12-0019, ANR-13-BSV6-0006-01 and ANR-11-LABX-0028-01), Cancéropôle PACA (AAP émergence 2015) and a DuPont Young Professor Award to G.L. J.-X.Y. is supported by a postdoctoral fellowship from Fondation ARC pour la Recherche sur le Cancer (PDF20150602803).

AUTHOR CONTRIBUTIONS

J.-X.Y. designed, implemented, and tested the LRSDAY workflow. G.L. coordinate the work. J.-X.Y. and G.L. wrote the manuscript.

COMPETING FINANCIAL INTERESTS

The authors declare that they have no competing financial interests.

REFERENCES

1. Gordon, D. *et al.* Long-read sequence assembly of the gorilla genome. *Science* **352,** aae0344 (2016).

2. VanBuren, R. *et al.* Single-molecule sequencing of the desiccation-tolerant grass *Oropetium thomaeum*. *Nature* **527,** 508–11 (2015).

3. Bickhart, D. M. *et al.* Single-molecule sequencing and chromatin conformation capture enable *de novo* reference assembly of the domestic goat genome. *Nat. Genet.* **49,** 643–650 (2017).

4. Badouin, H. *et al.* The sunflower genome provides insights into oil metabolism, flowering and Asterid evolution. *Nature* **546,** 148–152 (2017).

5. Yue, J.-X. *et al.* Contrasting evolutionary genome dynamics between domesticated and

769   wild yeasts. *Nat. Genet.* **49,** 913–924 (2017).

770 6. Goodwin, S. *et al.* Oxford Nanopore sequencing, hybrid error correction, and de novo

771   assembly of a eukaryotic genome. *Genome Res.* **25,** 1750–1756 (2015).

772 7. McIlwain, S. J. *et al.* Genome sequence and analysis of a stress-tolerant, wild-derived

773   strain of *Saccharomyces cerevisiae* used in biofuels research. *G3 (Bethesda).* **6,** 1757–

774   66 (2016).

775 8. Istace, B. *et al. De novo* assembly and population genomic survey of natural yeast

776   isolates with the Oxford Nanopore MinION sequencer. *Gigascience* **6,** 1–13 (2017).

777 9. Giordano, F. *et al. De novo* yeast genome assemblies from MinION, PacBio and MiSeq

778   platforms. *Sci. Rep.* **7,** (2017).

779 10. Chin, C.-S. *et al.* Nonhybrid, finished microbial genome assemblies from long-read SMRT

780   sequencing data. *Nat. Methods* **10,** 563–9 (2013).

781 11. Berlin, K. *et al.* Assembling large genomes with single-molecule sequencing and locality-

782   sensitive hashing. *Nat. Biotechnol.* **33,** 623–630 (2015).

783 12. Koren, S. *et al.* Canu: Scalable and accurate long-read assembly via adaptive *k*-mer

784   weighting and repeat separation. *Genome Res.* **27,** 722–736 (2017).

785 13. Proux-Wéra, E. *et al*. A pipeline for automated annotation of yeast genome sequences by

786   a conserved-synteny approach. *BMC Bioinformatics* **13,** 237 (2012).

787 14. Louis, E. J. & Haber, J. E. The structure and evolution of subtelomeric Y' repeats in

788   Saccharomyces cerevisiae. *Genetics* **131,** 559–574 (1992).

789 15. Strope, P. K. *et al.* The 100-genomes strains, an *S. cerevisiae* resource that illuminates

790   its natural phenotypic and genotypic variation and emergence as an opportunistic

791   pathogen. *Genome Res.* **25,** 762–774 (2015).

792 16. Almeida, P. *et al.* A population genomics insight into the Mediterranean origins of wine

793   yeast domestication. *Mol. Ecol.* **24,** 5412–27 (2015).

794 17. Gallone, B. *et al.* Domestication and divergence of *Saccharomyces cerevisiae* beer

795   yeasts. *Cell* **166,** 1397–1410.e16 (2016).

796 18. Bergström, A. *et al.* A high-definition view of functional genetic variation from natural

797   yeast genomes. *Mol. Biol. Evol.* **31,** 872–888 (2014).

798 19. McKenna, A. *et al.* The genome analysis toolkit: A MapReduce framework for analyzing

799   next-generation DNA sequencing data. *Genome Res.* **20,** 1297–1303 (2010).

800 20. Smit, A., Hubley, R. & Green, P. RepeatMasker Open-4.0. 2013-2015 .

801   *http://www.repeatmasker.org* (2013).

802 21. Holt, C. & Yandell, M. MAKER2: an annotation pipeline and genome-database

management tool for second-generation genome projects. *BMC Bioinformatics* **12,** 491

(2011).

22.   Robinson, J. T. *et al.* Integrative genomics viewer. *Nat. Biotechnol.* **29,** 24–26 (2011).

23.   Pereira, V. Automated paleontology of repetitive DNA with REANNOTATE. *BMC*

Genomics **9,** 614 (2008).

24.   Walker, B. J. *et al.* Pilon: An integrated tool for comprehensive microbial variant detection

and genome assembly improvement. *PLoS One* **9,** (2014).

25.   Kolmogorov, M. *et al.* Ragout - A reference-assisted assembly tool for bacterial genomes.

Bioinformatics **30,** (2014).

26.   Haas, B. J. *et al.* Automated eukaryotic gene structure annotation using

EVidenceModeler and the program to assemble spliced alignments. *Genome Biol.* **9,** R7

(2008).

27.   Lowe, T. M. & Eddy, S. R. A computational screen for methylation guide snoRNAs in

yeast. *Science* **283,** 1168–71 (1999).

28.   Minkin, I. *et al*. Sibelia: A scalable and comprehensive synteny block generation tool for

closely related microbial genomes. in *Lecture Notes in Computer Science (including*

subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)

8126 LNBI, 215–229 (2013).

FIGURE LEGENDS

830 Figure 1. Overview of the LRSDAY directory system. All the top-level directories (boxes, solid
831 lines) and individual files of LRSDAY are listed and briefly described. Additional directories and
832 files will be generated during the installation or execution of LRSDAY (boxes, dashed lines).
833
834 Figure 2. The workflow of LRSDAY. Each box represents an individual module. These modules
835 are numbered according to their processing order in LRSDAY. Modules that can be adapted for
836 other eukaryotes are colored in light blue while those yeast-specific ones are colored in light
837 red.
838
Figure 3. Genome-wide dotplots of the *S. cerevisiae* SK1 PacBio assembly generated in the
LRSDAY testing example. Both the raw scaffolded assembly (panel a; generated at Step 30)
and the final assembly (panel b, generated at Step 33) are analyzed. The forward and reverse
sequence matches are depicted in red and blue respectively, while the zoomed-in views of the
mitochondrial genome (chrMT) comparison are shown in insets. The scaffolding gap of the
mitochondrial genome is indicated by the black arrow.
845
846
847

TABLES

850 **TABLE 1** | Assembly statistics for *S. cerevisiae* SK1 assembled in the testing example.
851

Assembly statistics	Raw assembly	Scaffolded assembly	Final assembly
Total sequence count	22	20	20
Total sequence length (bp)	12282921	12292985	12261860
Min sequence length (bp)	24410	24410	24410
Max sequence length (bp)	1480192	1480198	1480198
Mean sequence length (bp)	558314.59	614649.25	613093.00
Median sequence length (bp)	558503.50	637681.50	637681.50
N50 (bp)	829956	923665	923665
L50	6	6	
N90 (bp)	462498	462493	462493
L90	14	13	13
GC%	38.21	38.17	38.24
N%	0.00	0.08	0.04

852
853

TABLE 2 | Troubleshooting table.

Step	Problem	Possible reason	Solution

1	Downloading errors or unresponsive remote servers	Unstable internet connection or temporary problems of the remote servers where the tools for downloading are hosted.	Stabilizing the internet connection and give another try. Delete the partially installed "build" directory and re-run the "install_dependencies.sh" script by entering:
			 $ rm -rf build
			 $ bash install_dependencies.sh

1	Compilation or installation error for specific tools.	Prerequisites not satisfied or corner cases due to your specific system settings.	If missing prerequisites are found, install the missing prerequisites and give another try as described above. Otherwise, record the error message and email it to the developers of the problematic tools or the authors of this protocol for further problem diagnosis.
2	Cannot find the file "env.sh".	Step 1 has failed.	Check the error message that you got when running Step 1 and refer to the troubleshootings for Step 1.
13	Missing required Perl modules.	Step 2 has failed or your terminal session got interrupted before this step.	Re-load environment settings in Step 2 and then re-try this step.
20	"echo $blast_dir" returns nothing.	Step 2 has failed or your terminal session got interrupted before this step.	Re-load environment settings in Step 2 and then re-try this step.
27	Downloading warnings/errors encountered.	Temporary SRA server problems.	Directly download the reads by running the following commands: $ wget

			ftp://ftp.sra.ebi.ac.uk/vol1/fastq/SRR407/008/SRR4074258/SRR4074258_1.fastq.gz
			$ ln -s SRR4074258_1.fastq.gz SRR4074258_pass_1.fastq.gz
			$ wget ftp://ftp.sra.ebi.ac.uk/vol1/fastq/SRR407/008/SRR4074258/SRR4074258_2.fastq.gz
			$ ln -s SRR4074258_2.fastq.gz SRR4074258_pass_2.fastq.gz

28	The total assembly size is much smaller than the expected value or the assembly is too fragmented.	Insufficient sequencing depth of coverage.	Obtain more reads. In general, a minimal sequencing depth of 50X is recommended.
28	Only partial assembly is obtained for the mitochondrial genome.	High AT and repetitive content of the mitochondrial genome is challenging for *de novo* genome assembly.	If the sequencing is done with PacBio, obtaining more reads should solve the problem. If sequencing is done with Oxford Nanopore data, currently there is no satisfying solution. Future improvement of the Oxford Nanopore sequencing technology will likely solve this problem given the rapid development of this technology.

857
858
859

BOXES

BOX1: Pre-shipped supporting data for LRSDAY

With LRSDAY, we pre-shipped the following supporting datasets for the automatic execution of LRSDAY. Unless labeled otherwise, most of these pre-shipped datasets were either described or generated in our previous study[5].

ATP6.cds.fa # The coding sequence (CDS) of the *S. cerevisiae* S288C *ATP6* gene.

evm_weights.txt # the evidence weights file for EVidenceModeler (EVM)[26] (shipped with MAKER).

FungiDB_Sc.est.simple.fa # the *S. cerevisiae* EST data from FungiDB (http://fungidb.org/fungidb/).

fuzzy_defragmentation.txt # the fuzzy defragmentation file for REannotate[23].

Proteome_DB_for_annotation.CDhit_I95.fa # our curated proteome dataset for *S. cerevisiae* and other closely related yeast *sensu stricto* species.

query.Y_prime_element.long.fa # the sequence of a representative *S. cerevisiae* Y' element.

S288C.ASM205763v1.fa.gz # the *S. cerevisiae* S288C genome assembly.

S288C.ASM205763v1.noncore_masked.fa.gz # the *S. cerevisiae* S288C genome assembly with subtelomeres and chromosome-ends hard-masked.

S288C.centromere.fa # the centromere sequence of *S. cerevisiae* S288C.

S288C.gene.hmm # the hidden Markov model (HMM) for *de novo* gene annotation based on *S. cerevisiae* S288C.

S288C.X_element.hmm # the hidden Markov model (HMM) for the core X element annotation based on *S. cerevisiae* S288C.

Sc-meth.sites # the *S. cerevisiae* methylation sites (shipped with snoScan[27]).

Sc-rRNA.fa # the *S. cerevisiae* rRNA sequences (shipped with snoScan[27]).

SGDref.PoFF.faa # the proteinortho proteome file generated for the SGD reference genome.

SGDref.PoFF.ffn # the proteinortho CDS file generated for the SGD reference genome.

SGDref.PoFF.gff # the proteinortho gene order gff file generated for the SGD reference genome.

te_proteins.fasta # protein sequences for genes encoded within TEs (shipped with MAKER[21]).

TY2_specific_region.fa # the sequence of a Ty2 specific regions for differentiating Ty1 and Ty2.

TY_lib.Yue_et_al_2017_NG.fa # a custom RepeatMasker library for Ty annotation in *S. cerevisiae* and *S. paradoxus*.

892 TY_lib.Yue_et_al_2017_NG.LTRonly.fa # representative Ty LTR sequences of *S. cerevisiae*

893 and *S. paradoxus*.

BOX2: Tips for adapting LRSDAY to other eukaryotic organisms

The backbone modules of LRSDAY can be easily adapted for other eukaryotic organisms. Here
are some tips with regard to this:

1) For Task 01, be sure to adjust the genome size parameter in line 13 of the bash script
"LRSDAY.01.Long-read-based_Genome_Assembly.sh" based on the estimated genome
size of the organism that you sequenced.

2) For Task 03, be sure to modify the bash script "LRSDAY.03.Reference-
guided_Assembly_Scaffolding.sh" to provide the reference genome file of your
sequenced organisms to guide the scaffolding and chromosome assignment. It is very
likely that the chromosomal cores and subtelomeres of your reference genome have not
been clearly defined. In such case, you can provide the same reference genome file for
both the "ref_genome_raw=" and "ref_genome_noncore_masked=" parameters. The
"chrMT_tag=" and "gap_size=" parameters should also be adjusted based on your own
project.

3) By default, Task 03 performs reference-guided scaffolding using the whole genome
alignment constructed by Sibelia[28]. Sibelia is not designed for processing small genomes
(<100 Mb). For organisms with large genomes, you should install Progressive Cactus
(https://github.com/glennhickey/progressiveCactus) and use it to build the whole genome
alignment in HAL format and feed it directly to Ragout[25]. Please refer to Ragout's user
manual for this advanced usage. We have preshipped the HAL tools
(https://github.com/ComparativeGenomicsToolkit/hal) to enable Ragout to process the
HAL file generated by Progressive Cactus.

4) For Task 05, be sure to modify the "gene_start=", "ref_genome_raw=", and
"chrMT_tag=" parameters in the bash script
"LRSDAY.05.Mitochondrial_Genome_Assembly_Improvement.sh" based on your own
project.

5) While many of the genomic feature annotation tasks are yeast-specific, Task 08
(protein-coding genes and tRNA annotation) can be adapted for any eukaryotic
organism. Please refer to MAKER's own Wiki page
(http://weatherby.genetics.utah.edu/MAKER/wiki/index.php/Main_Page) and protocols
(https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4286374/) for technical details and
advanced usage.

6) While Task 09 (TE annotation) is heavily tuned for yeasts, the same tools that we used

here (RepeatMasker[20] and REannotate[23]) can be used for any eukaryotic organism. We

recommend to read their respective manuals for adapting these tools in your own study.

7) For Task 12, you need to edit the "ref_PoFF_faa=" and "ref_PoFF_gff=" parameters

based on the reference gene annotation that you used. Please check ProteinOrtho's

manual (https://www.bioinf.uni-leipzig.de/Software/proteinortho/manual.html) for more

details on required file formats. The pre-shipped Perl script "prepare_PoFFfaa_simple.pl"

and "prepare_PoFFgff_simple.pl" in the "$LRSDAY_HOME/scripts" directory should help

for this.

$LRSDAY_HOME   # the LRSDAY home directory

./pipelines/   # the directory containing all task-specific bash scripts

./scripts/   # the directory containg all auxiliary Perl scripts

./data/   # the directory containing all supporting data files (listed in Box 1)

./misc/   # the directory containing all supporting configuration files

./Example_Outputs/   # the directory containing the final outputs of the testing example

./Project_Template/   # the directory containing a sample project directory system (see Fig. 2)

./Project_Example/   # the project directory that will be created by users for the testing example

./Project_abc/   # the project directory that will be created by users for their own projects, where "abc" can be any user-defined names

./build/   # the directory that will be generated during the auto-installation of LRSDAY to hold all the installed dependencies

env.sh   # environment settings that will be generated during the auto-installation of LRSDAY

prerequisites.txt   # the list of prerequisites needed for setting up LRSDAY

install_dependencies.sh   # the bash script controlling the auto-installation of LRSDAY

README.md   # the breif description of LRSDAY

Manual.pdf   # the user manual of LRSDAY

Figure 1

Figure 2

Figure 3