MACS – a new SPM toolbox for model assessment, comparison and selection

Joram Soch[1, 2*], Carsten Allefeld[1, 3]

[1]Bernstein Center for Computational Neuroscience, Charité Universitätsmedizin Berlin, Germany, [2]Department of Psychology, Humboldt-Universität zu Berlin, Germany, [3]Berlin Center for Advanced Neuroimaging, Charité Universitätsmedizin Berlin, Germany

MACS – a new SPM toolbox for model assessment, comparison and selection

Joram Soch [1,3,*] **and Carsten Allefeld** [1,2]

[1] *Bernstein Center for Computational Neuroscience, Charité – Universitätsmedizin Berlin, Germany*

[2] *Berlin Center for Advanced Neuroimaging, Charité – Universitätsmedizin Berlin, Germany*

[3] *Department of Psychology, Humboldt-Universität zu Berlin, Germany*

Correspondence*:
Joram Soch, BCCN Berlin, Philippstraße 13, Haus 6, 10115 Berlin, Germany
joram.soch@bccn-berlin.de

ABSTRACT

We introduce a new SPM toolbox for model assessment, comparison and selection (MACS) of
general linear models (GLMs) applied to functional magnetic resonance imaging (fMRI) data.
MACS includes classical, information-theoretic and Bayesian methods of model assessment previ-
ously applied to GLMs for fMRI as well as recent methodological developments of model selection
and model averaging in fMRI data analysis. The toolbox – which is freely available from GitHub –
directly builds on the Statistical Parametric Mapping (SPM) software package and is easy-to-use,
general-purpose, modular, readable and extendable. We validate the toolbox by reproducing
model selection and model averaging results from earlier publications. Increased attention on
model quality will lead to lower false-positive rates in cognitive neuroscience and increased
application of the MACS toolbox will increase the reliability of GLM results and reproducibility of
fMRI studies.

Keywords: fMRI-based neuroimaging, mass-univariate GLM, model assessment, model comparison, model selection

Words: 133 (Abstract) + 72 (Headings) + 4829 (Text) + 907 (Captions, Footnotes)

1 INTRODUCTION

In functional magnetic resonance imaging (fMRI), general linear models (GLMs) are routinely applied to relate measured hemodynamic signals with controlled experimental variables in order to make statements about the localization of cognitive functions in brain regions (Friston et al., 1994; Holmes and Friston, 1998). Like any other statistical inference, GLM analyses are dependent of the particular choice of the model (Andrade et al., 1999; Carp, 2012) and model quality can have a profound effect on sensitivity and specificity of statistical tests (Razavi et al., 2003; Monti, 2011).

Model assessment (Akaike, 1974; Schwarz, 1978), model comparison and selection (Kass and Raftery, 1995) as well as model averaging (Hoeting et al., 1999) are established techniques to control for model quality by inferring the most likely model given the data and by conditioning data analysis on the optimal model for each data set. While model assessment (Friston et al., 2007), comparison (Penny et al., 2004; Penny, 2012), selection (Stephan et al., 2009) and averaging (Penny et al., 2010) have become standard practice in dynamic causal modelling (DCM) for fMRI (Friston et al., 2003), such techniques are almost not used in the application of GLMs for fMRI (Friston et al., 1994).

Previous attempts to control for model quality in GLMs for fMRI include statistical tests for goodness of fit (Razavi et al., 2003) and the application of Akaike's or Bayesian information criterion for activation detection (Seghouane and Ong, 2010) or theory selection (Gläscher and O'Doherty, 2010). Additionally, voxel-wise Bayesian model assessment (Penny et al., 2003, 2005, 2007) and random-effects Bayesian model selection (Rosa et al., 2010) have been included in the popular software package *Statistical Parametric Mapping* (SPM), but are only rarely used due to low visibility, high analytical complexity and interpretational difficulty. Finally, a toolbox for frequentist model diagnosis and exploratory data analysis called *SPMd* ("d" for "diagnostic") has been released for SPM (Luo and Nichols, 2003), but was discontinued several years ago[1] (Nichols, 2013).

With this work, we provide a new SPM toolbox for **m**odel **a**ssessment, **c**omparison and **s**election termed *MACS* (pronounced as "Max"). Purposes of this software package are (i) to unify classical, information-theoretic and Bayesian measures of model quality previously applied to fMRI data, (ii) to provide a common pipeline for our previously developed methods of cross-validated Bayesian model selection (cvBMS; Soch et al., 2016) and averaging (cvBMA; Soch et al., 2017) that so far existed as seperate toolkits and (iii) to build a framework in which all these model quality measures can be conveniently applied to GLMs estimated in SPM by directly building on `SPM.mat` files.

The rest of the paper falls into three parts. First, we give a technical overview of the features included in the MACS toolbox (see Section 2). Among others, we have implemented goodness-of-fit (GoF) measures, classical information criteria (ICs) and the Bayesian log model evidence (LME). Second, we explain the structure of the MACS toolbox and how it facilitates diverse and user-specific analyses (see Section 3). Most importantly, the embedding of MACS into SPM's batch systems accelerates and simplies fMRI analyses. Finally, we present two exemplary applications illustrating cvBMS and cvBMA as our latest methodological advances for fMRI (see Section 4) and discuss our work.

---

[1] Thomas Nichols gave a "Requiem for SPMd" on slide 3 of his talk "Building Confidence in fMRI Results with Model Diagnosis" in the workshop "How Not to Analyze Your Data: A Skeptical Introduction to Modeling Methods" at the 2013 Annual Meeting of the Organization for Human Brain Mapping. The talk can be accessed at: https://www.pathlms.com/ohbm/courses/250/sections/2156/slide_presentations/17067.

2 FEATURES IN THE TOOLBOX

52 In the MACS toolbox, methods of model inference are broadly categorized into the three categories *model*
53 *assessment* (MA), *model comparison* (MC) and *model selection* (MS). This section gives a technical
54 introduction of these different techniques which are also summarized in Table 1.

2.1 Model assessment

Model assessment (MA) is defined as any method that quantifies the quality of an individual model by a
single real number. MA methods can again be sub-divided into three groups of tools: (i) *goodness-of-fit*
measures (GoF), (ii) *classical information criteria* (ICs) and (iii) *Bayesian log model evidence* (LME).

In all of the following, we consider a generative model m with model parameters θ describing measured
data y with estimated parameters $\hat{\theta}$ giving predicted data $\hat{y}$, with number of data points n and number of
model parameters p. In the context of first-level fMRI data analysis, m is typically a *general linear model*
(GLM), i.e. univariate linear regression analysis; θ includes the *regression coefficients* β and the *residual*
variance σ^2; y is a time course of the *blood-oxygenation level dependent* (BOLD) signal measured via
fMRI; $\hat{y}$ is the fitted BOLD signal; n is the number of fMRI scans and p is the number of GLM regressors[2].

2.1.1 Goodness-of-fit measures

66 The purpose of GoF measures is to get a first impression of how well a model – in this case: a GLM –
67 describes a given set of data – in this case: voxel-wise fMRI signals. One obvious thing to look at would be
68 the *residual variance* of the GLM calculated as

$$
\hat{\sigma}^2_{\mathrm{ML}} = \frac{1}{n} \sum_{i=1}^{n} (y_i - \hat{y}_i)^2
$$

$$
\hat{\sigma}^2_{\mathrm{ub}} = \frac{1}{n-p} \sum_{i=1}^{n} (y_i - \hat{y}_i)^2 \tag{1}
$$

69 where $\hat{\sigma}^2_{\mathrm{ML}}$ is the maximum-likelihood estimator and $\hat{\sigma}^2_{\mathrm{ub}}$ is the unbiased estimator of that quantity. In
70 SPM, the residual variance is calculated somewhat differently as

$$
\hat{\sigma}^2_{\mathrm{SPM}} = \frac{1}{\mathrm{tr}(RV)} \sum_{i=1}^{n} (y_i - \hat{y}_i)^2 \tag{2}
$$

71 where R is the residual forming matrix and V is the error correlation matrix of the corresponding GLM
72 which accounts for the loss of effective residual degrees of freedom (erdf) by whitening and filtering the
73 data. Generally, the lower the residual variance, the better model predictions and measured data agree with
74 each other. However, as the residual variance does not have an upper bound, it is more useful to look at the
75 *coefficient of determination* (Razavi et al., 2003, eq. 2)

---

[2] Note that p is the number of GLM regressors in GoF measures, but this number plus one in classical ICs, because information criteria account for the total number of model parameters which include the residual variance σ^2 in addition to the regression coefficients β.

$$R^2 = 1 - \frac{\text{RSS}}{\text{TSS}} = \frac{\text{ESS}}{\text{TSS}} \tag{3}$$

76   where RSS is the residual sum of squares $\sum_{i=1}^{n}(y_i - \hat{y}_i)^2$, ESS is the explained sum of squares $\sum_{i=1}^{n}(\hat{y}_i -$
77    $\bar{y})^2$ and TSS is the total sum of squares $\sum_{i=1}^{n}(y_i - \bar{y})^2$, such that $\text{TSS} = \text{ESS} + \text{RSS}$. Generally, the
78   closer R^2 gets to 1, the better the model captures the variation. However, as the coefficient of determination
79   always increases when another variable is included in the model, an improved measure is given by the
80   *adjusted coefficient of determination* (Razavi et al., 2003, eq. 4)

$$R^2_{\text{adj}} = 1 - \frac{\text{RSS}/\text{df}_r}{\text{TSS}/\text{df}_t} \tag{4}$$

81   where the residual degress of freedom $\text{df}_r = n - p$ and the total degrees of freedom $\text{df}_t = n - 1$ are used
82   to adjust the sums of squares to account for additional model parameters. For this reason, the adjusted R^2
83   can be seen as a precursor to classical information criteria (see next section).

84   Note that, whereas R^2 always falls between 0 and 1, R^2_{adj} can also become negative. Both R^2 and R^2_{adj} are
85   also related to the F-statistic in an F-test of a GLM against only the constant regressor which is given by

$$F = \frac{(\text{TSS} - \text{RSS})/\text{df}_n}{\text{RSS}/\text{df}_d} \tag{5}$$

86   where the numerator degress of freedom $\text{df}_n = p - 1$ and the denominator degrees of freedom $\text{df}_d = n - p$
87   are the parameters of the F-distribution under the null hypothesis that the signal only consists of a mean μ.

88   Goodness-of-fit measures also include the *signal-to-noise ratio* (SNR):

$$\text{SNR}_{\text{mf}} = \frac{|\hat{\mu}|}{\hat{\sigma}}, \quad \hat{\mu} = \bar{y}$$
$$\text{SNR}_{\text{mb}} = \frac{\text{var}(X\hat{\beta})}{\hat{\sigma}^2} \ . \tag{6}$$

Here, SNR_{mf} is the model-free SNR which is calculated as the inverse of the *coefficient of variation*
(CoV) and quantifies the ratio of signal average to signal variation (Welvaert and Rosseel, 2013, def. 1).
Signals that are very low or very variable will receive a lower SNR given this measure. In contrast, SNR_{mb}
corresponds to a model-based SNR which divides the variance of the explained signal by the variance of
the unexplained signal (Welvaert and Rosseel, 2013, def. 5).

Note that, if the measured signal y and the predicted signal $\hat{y}$ have the same mean, $\text{var}(X\hat{\beta}) = \text{var}(\hat{y})$ is
proportional to the explained sum of squares and $\text{SNR}_{\text{mb}} = \text{ESS}/\text{RSS} = R^2/(1 - R^2)$. Crucially, with a
change of the GLM, the model-based SNR will also change while the model-free SNR will not.

In our toolbox, all these measures are implemented via the routine `MA_inspect_GoF` and can be
exported as whole-brain maps or explored in a voxel-wise manner (see Figure 4A).

2.1.2 Classical information criteria

Classical information criteria (ICs), in the terminology of the MACS toolbox, are model quality measures
that only depend on the *maximum log-likelihood* (MLL), as a measure of model accuracy, as well as n
and p, giving rise to some measure of model complexity. The first of these ICs was *Akaike's information*
criterion (Akaike, 1974)

$$\text{AIC} = -2\log p(y|\hat{\theta}, m) + 2k \tag{7}$$

104 where the maximum log-likelihood $\text{MLL} = \log p(y|\hat{\theta}, m)$ and $k = p+1$ is the number of model parameters
105 (see Fn. 2). The *corrected AIC*, an improved version of the AIC for finite-sample calculations, has been
106 derived as (Hurvich and Tsai, 1989)

$$\text{AIC}_\text{c} = \text{AIC} + \frac{2k(k+1)}{n-k-1} \ . \tag{8}$$

107 Historically, the second IC was the *Bayesian information criterion* (Schwarz, 1978)

$$\text{BIC} = -2\log p(y|\hat{\theta}, m) + k\log n \tag{9}$$

which means that AIC and BIC are equal for sample sizes around $n = e^2 \approx 7.39$. Although the name
suggests that the BIC rests on Bayesian inference, it does not and is only theoretically connected to
Bayesian statistics by being an infinite-sample approximation to the Bayesian log model evidence (see next
section).

In contrast to that, the *deviance information criterion* is a "real" Bayesian information criterion, because it
requires the specification of prior distributions on the model parameters and posterior distributions are used
to calculate expected likelihoods. Technically, the DIC therefore depends on more than just MLL, n and p.
Formally, the DIC is given by (Spiegelhalter et al., 2002)

$$\text{DIC} = -2\log p(y|\langle\theta\rangle_{\theta|y}, m) + 2p_D \quad \text{with} \quad p_D = \langle D(\theta)\rangle_{\theta|y} - D(\langle\theta\rangle_{\theta|y}) \tag{10}$$

116 where $D(\theta)$ is the log-likelihood function on the deviance scale

$$D(\theta) = -2\log p(y|\theta, m) \ , \tag{11}$$

such that $\langle D(\theta)\rangle_{\theta|y}$ is proportional to the *posterior expected log-likelihood* (PLL) and $D(\langle\theta\rangle_{\theta|y})$ is pro-
portional to the *log-likelihood at the posterior expectation* (LLP). In these equations, the operator $\langle\cdot\rangle_{\theta|y}$
denotes an expectation across the posterior distribution (Woolrich et al., 2004) which naturally depends on
the prior distribution. However, the DIC is very robust with respect to the choice of the prior and we have
therefore implemented it with a non-informative prior (Soch et al., 2016, eq. 15).

In our toolbox, all these criteria are implemented via the routine `MA_classic_ICs` which can also be
accessed through the corresponding batch editor job (see Figure 2).

2.1.3 Bayesian log model evidence

An alternative to those classical information criteria are Bayesian measures of model quality based on the
marginal log-likelihood, also called the *log model evidence* (LME) which is given by (Gelman et al., 2013,
eq. 1.3; Bishop, 2007, eq. 1.45)

$$\mathrm{LME}(m) = \log p(y|m) = \log \int p(y|\theta, m)\, p(\theta|m)\, \mathrm{d}\theta \ . \tag{12}$$

Note that, while classical ICs operate on the deviance scale (see eq. 11), the LME operates on the log-
likelihood scale (see eq. 12), so that thresholds commonly applied to LME differences (Kass and Raftery,
1995) must be multiplied by -2 when applying them to classical ICs. Such thresholds include log Bayes
factors of 0, 1, 3 or 5 corresponding to Bayes factors of around 1, 3, 20 or 150 (see next section).

The LME has several advantages over classical information criteria including (i) its automatic penalty
for additional model parameters (Penny, 2012), (ii) its natural decomposition into model accuracy and
model complexity (Penny et al., 2007) and (iii) its consideration of the whole uncertainty about parameter
estimates (Friston et al., 2007). The LME however has the disadvantage that it depends on a prior distribution
$p(\theta|m)$ over model parameters and the choice of the prior can have a profound impact on resulting model
comparisons. In recent work on GLMs for fMRI, we have therefore suggested the *out-of-sample log model*
evidence (Soch et al., 2016, eq. 13)

$$\mathrm{oosLME}_i(m) = \log \int p(y_i|\theta, m)\, p(\theta| \cup_{j \neq i}\ y_j, m)\, \mathrm{d}\theta \tag{13}$$

139 and the *cross-validated log model evidence* (Soch et al., 2016, eq. 14)

$$\mathrm{cvLME}(m) = \sum_{i=1}^{S} \log \int p(y_i|\theta, m)\, p(\theta| \cup_{j \neq i}\ y_j, m)\, \mathrm{d}\theta \tag{14}$$

where S is the number of data subsets – in our case: fMRI recording sessions. These can be seen as Bayesian
measures of model quality, but avoid having to specify prior distributions on the model parameters. Instead,
the prior distribution is obtained by training the model on independent data of the same kind.

Given that LME, cvLME or oosLME have been calculated and models m can be sensibly grouped into
model families f, *log family evidences* (LFE) can be easily calculated using the law of marginal probability
as (Soch et al., 2016, eq. 18)

$$\mathrm{LFE}(f) = \log p(y|f) = \log \sum_{m \in f} p(y|m)\, p(m|f) \tag{15}$$

146 where $p(y|m)$ is the exponential of LME, cvLME or oosLME and $p(m|f)$ is a within-family prior, usually
147 set to a discrete uniform distribution, embodying the assumption that within each family, all the models are
148 equally likely *a priori*.

149 In our toolbox, the cvLME is the default model selection criterion and can be calculated via the routine
150 `MA_cvLME_multi` or the corresponding batch editor job (see Figure 2).

2.2 Model comparison

Model comparison (MC) is defined as any method that quantifies the quality difference between two models by a single real number. Most trivially, one can for example calculate the *difference between two information criteria* (Penny et al., 2004, eq. 23)

$$\Delta\text{IC}_{ij} = \text{IC}(m_i) - \text{IC}(m_j) \tag{16}$$

which can be performed for AIC, BIC etc. and compared with particular scales. When calculating this difference between two LMEs, the result is called the logarithm of a Bayes factor or a *log Bayes factor* (Penny et al., 2004, eq. 22)

$$\text{BF}_{ij} = \frac{p(y|m_i)}{p(y|m_j)} \quad \text{or} \quad \text{LBF}_{ij} = \text{LME}(m_i) - \text{LME}(m_j) \tag{17}$$

which can be applied to LME, cvLME or oosLME. When analyzing a group of subjects in an experimental study and assuming independence across subjects, subject-level LMEs can be summed up into a *group-level LME* (Penny et al., 2010, eq. 6)

$$p(Y|m) = \prod_{i=1}^{N} p(y_i|m) \quad \text{or} \quad \log p(Y|m) = \sum_{i=1}^{N} \log p(y_i|m) \tag{18}$$

where $Y = \{y_1, \ldots, y_N\}$ are the group data and N is the number of subjects. Comparing two models across several subjects then gives rise to a group Bayes factor or *log group Bayes factor* which is given by (Stephan et al., 2007, eq. 20)

$$\text{GBF}_{ij} = \frac{p(Y|m_i)}{p(Y|m_j)} \quad \text{or} \quad \text{LGBF}_{ij} = \log p(Y|m_i) - \log p(Y|m_j) . \tag{19}$$

Importantly, this LGBF approach assumes the same model for each subject and therefore corresponds to a fixed-effects (FFX) analysis. If this assumption cannot be justified, a random-effects (RFX) model has to be used (see next section).

Finally, in the case that just two models are considered and a uniform prior across models is assumed, (log) Bayes factors can be directly transformed into *posterior model probabilities* using the simple relation (Penny and Ridgway, 2013, eq. 10)

$$p(m_i|y) = \frac{\text{BF}_{ij}}{\text{BF}_{ij} + 1} = \frac{\exp(\text{LBF}_{ij})}{\exp(\text{LBF}_{ij}) + 1} \tag{20}$$

and additionally

$$p(m_j|y) = 1 - p(m_i|y) . \tag{21}$$

171 **2.3 Model selection**

172 Model selection (MS) is defined as any method that chooses one particular model from a set of candidate
173 models based on some objective criterion. For example, *fixed-effects Bayesian model selection* (FFX BMS)
174 generalizes posterior model probabilities to more than two models, such that (Penny et al., 2010, eq. 7)

$$p(m_i|Y) = \frac{p(Y|m_i)\, p(m_i)}{\sum_{j=1}^{M} p(Y|m_j)\, p(m_j)} \tag{22}$$

175 where M is the number of models. In contrast to that, *random-effects Bayesian model selection* (RFX
176 BMS) allows for the possibility that different subjects have different optimal models. In each subject,
177 the generating model is assumed to come from a multinomial distribution with a Dirichlet as the prior
178 distribution over multinomial frequencies. However, the models are not observed directly, but only indirectly
179 via the model evidences from first-level model assessment (Stephan et al., 2009, eqs. 3-5):

$$p(y|m) = \prod_{i=1}^{N} p(y_i|m_i) = \prod_{i=1}^{N} \prod_{j=1}^{M} p(y_i|e_j)^{m_{ij}}$$

$$p(m|r) = \prod_{i=1}^{N} \mathrm{Mult}(m_i; 1, r) = \prod_{i=1}^{N} \prod_{j=1}^{M} r_j^{m_{ij}} \tag{23}$$

$$p(r|\alpha) = \mathrm{Dir}(r; \alpha) = \frac{\Gamma(\sum_{j=1}^{M} \alpha_j)}{\prod_{j=1}^{M} \Gamma(\alpha_j)} \prod_{j=1}^{M} r_j^{\alpha_j - 1}$$

Together, these probability distribution define a second-level hierarchical population proportion model that
can be inverted using either Variational Bayes (VB) (Stephan et al., 2009, eq. 14) or Gibbs Sampling (GS)
(Penny et al., 2010, eqs. 13-17) techniques.

Finally, *Bayesian model averaging* (BMA) is also grouped under model selection here as it implicitly
consists in, based on the set of candidate models, fitting a larger model which effectively marginalizes over
modelling approaches. In our implementation, BMA estimates are calculated as (Soch et al., 2017, eq. 8)

$$\hat{\beta}_{\mathrm{BMA}} = \sum_{i=1}^{M} \hat{\beta}_i \cdot p(m_i|y) \tag{24}$$

where $\hat{\beta}_i$ is the i-th model's parameter estimate for a particular regressor in the GLM and $p(m_i|y)$ is the
i-th model's posterior probability calculated from cvLMEs.

Whereas *model selection* decides for one particular model that maximizes a certain function such as log
model evidence, posterior model probability or group-level model frequency, *model averaging* combines
several models using their posterior probabilities calculated from model evidences. Given that finite
data never provide absolute certainty about the modelling approach, this approach allows to account for
modelling uncertainty by utilizing parameter estimates from all models in the model space instead of
discarding the valuable information from all but one model.

3   STRUCTURE OF THE TOOLBOX

194 The MACS toolbox is written in MATLAB and designed to work as an extension for Statistical Parametric
195 Mapping (SPM), Version 8 oder 12 (SPM8/12). This section describes how three layers of implementation
196 make the toolbox accessible for different users and how two modes of batch processing make the toolbox
197 useful in different contexts.

3.1   Three layers of implementation

An overview of the toolbox functions is given in Figure 1. This figure shows the three types of functions
included in the toolbox: (i) mathematical functions, (ii) interface functions and (iii) batch functions. *Math-*
ematical functions (see Figure 1C) directly implement the statistical analyses (such as `ME_GLM_NG` for
estimating a Bayesian GLM) required for toolbox features. *Interface functions* (see Figure 1B) represent
toolbox features (such as `MA_cvLME_multi` for calculating the voxel-wise cvLME) and execute mathe-
matical functions. *Batch functions* (see Figure 1A) take information from SPM batch editor jobs (such as
`batch_MA_cvLME_auto` for performing cvLME assessment) and use it to call interface functions.

Regular toolbox users will never access any of these functions directly in MATLAB, but will use toolbox
features through SPM's batch editor only. This can be achieved by installing the MACS toolbox and
opening the SPM batch editor (see Section 6 and Figure 3). Users can then fill out regular batch jobs like in
SPM and directly run them from the batch editor. Batch job templates only use few options most of which
can often be left at their default values. Examples are given in Figures 3 and 4:
211
– Figure 3 : batch for cross-validated Bayesian model selection
– Figure 4A: output from goodness-of-fit inspection for a GLM
– Figure 4B: output from high-dimensional data visualization

Intermediate toolbox users may also use the batch editor, but will additionally call the interface functions
via MATLAB's command-line interface. This could for example happen in a pipeline script which is
intended to process many models applied to many subjects. Note however that those pipeline-style analyses
can also be implemented using the regular batch system. An exemplary command-line call could look like
this:

```
220  >> load C:\fMRI\SUB_01\GLM_A\SPM.mat      % load GLM estimated in SPM
221  >> MA_cvLME_multi(SPM)                     % calculate voxel-wise cvLME
222  >> MA_classic_ICs(SPM)                     % calculate voxel-wise AIC/BIC
```

223 *Advanced toolbox users* and developers can also rely on the batch editor and interface functions, but
224 will additionally call mathematical functions to perform their own customized analyses. This could for
225 example happen when one is interested in Bayesian GLM parameter estimates or when the cvLME is to be
226 calculated for a large number of models in a small number of voxels. This type of usage can also lead to
227 new methods developments. An extract from a possible script could read like this:

```
228  01  % load model specification and prepare model estimation
229  02  load C:\fMRI\SUB_01\GLM_A\SPM.mat    % load GLM estimated in SPM
230  03  Y = MA_load_data(SPM);               % load voxel-wise fMRI data
231  04  X = SPM.xX.X;                        % get design matrix
232  05  V = SPM.xVi.V;                       % get covariance matrix
233  06  P = spm_inv(V);                      % get precision matrix
234  07  [n, p] = size(X);                    % get model dimensions
235  08  m0 = zeros(p,1);                     % set prior beta mean
236  09  L0 = zeros(p,p);                     % set prior beta covariance
237  10
238  11  % estimate general linear model with normal-gamma priors
239  12  [mn, Ln, an, bn] = ME_GLM_NG(Y, X, P, m0, L0, 0, 0);
```

240 3.2 Two modes of batch processing

An overview of the toolbox modules is given in Figure 2. This figure shows the two modes of batch
processing that the toolbox allows: (i) automatic processing and (ii) manual processing. In short, automatic
processing requires specifying the model space only once whereas manual processing requires that log
model evidence images are entered for each model and each subject in every processing step.

Automatic processing consists in creating a model space file called MS.mat that contains references to
SPM.mat files belonging to several GLMs for several subjects. Given that the model space has been
specified, cvLME model assessment, Bayesian model comparison, model selection, model averaging and
other modules can be implemented by a simple reference to the model space file which automatically
applies the analyses to all subjects. The automatric procesing mode is the preferred one as it allows larger
analyses in shorter time and also avoids unnecessary analysis errors.

Manual processing means that GLM folders or cvLME maps are not referenced automatically using a
model space file, but manually by reference to their filepaths. This is useful when for example cvLME
model assessment is prefered to be performed in one batch with GLM model estimation or when LME
images are processed, e.g. spatially smoothed or recalculated into LFE images, before further steps such as
model comparison, model selection or model averaging are performed.

Like the SPM batch system, the MACS toolbox uses *dependencies between modules*. Dependencies are
references to files generated in earlier processing steps that are to be used in later processing steps. For
example, an SPM.mat file generated during model estimation may be used for cvLME calculation; or a
cvLME map generated during model assessment may be used for group-level BMS; or a BMS.mat file
generated during model selection may be used for generation of selected-model maps (SMM); etc. The
MACS toolbox encourages the use of dependencies and they are most conveniently implemented in the
automatic processing mode.

4 SUGGESTED PIPELINES

263 The MACS toolbox was primarily designed to summarize tools for *cross-validated Bayesian model*
264 *selection* (cvBMS) and *cross-validated Bayesian model averaging* (cvBMA). In this section, we propose
265 pipelines and analyze examples to demonstrate how these techniques can be effortlessly implemented with
266 MACS. Before that, we describe analyses illustrating how to apply goodness-of-fit measures and classical
267 information criteria to first-level GLMs in SPM.

4.1 Model assessment: repetition priming

To demonstrate first-level model assessment, we reanalyze a single-subject, single-session data set from
a study on repetition priming (Henson et al., 2002) that is used as example data in the SPM manual
(Ashburner et al., 2016, ch. 31). In this experiment, subjects were viewing faces which either belonged
to famous or non-famous people ("familiarity") and each face was presented twice ("repetition"). This
implies a 2×2 experimental design with 4 experimental conditions. This demonstration builds on data
preprocessed according to the SPM12 manual (Ashburner et al., 2016, sec. 31.1) and addresses model
assessment for the "categorical" model (Ashburner et al., 2016, sec. 31.2) and the "parametric" model
(Ashburner et al., 2016, sec. 31.3).

First, we want to get an impression of where in the brain the categorical model performs better and where
it performs worse. We use the MACS module for goodness-of-fit inspection to assess signal-to-noise ratio
(SNR) and coefficient of determination (R^2) across the whole brain. We find that in visual cortex, especially
fusiform face area (FFA), the model achieves the highest variance explanation which is consistent with the
facial stimuli of the experiment (see Figure 4A).

Second, we want to find out where the model fit is supported by which model parameters. We use the
MACS module for high-dimensional data visualization to explore the estimated regression coefficients
from the main experimental conditions in a voxel-wise fashion. For orientation purposes, we overlay this
query with an R^2 image obtained in the first step. We find that in one region of parietal cortex, possibly
the superior parietal gyrus (SPG), there is a negative effect of both experimental factors, familiarity and
repetition (see Figure 4B).

Finally, we want to compare the categorical against the parametric GLM. We use the MACS module for
classical information criteria (ICs) to compute the voxel-wise Bayesian information criterion (BIC) for
both models. Computing the information difference (ΔIC) between the two models is then implemented
using the log Bayes factor (LBF) module. Model comparison at an ad-hoc threshold of ΔIC > 10 in favor
of the parametric model gives rise to a large cluster in parietal cortex, close to the postcentral gyrus (PCG),
that was also reported when performing an F-test on the additional regressors in the parametric model[3]
(Ashburner et al., 2016, fig. 31.17).

---

[3] Note that (i) we of course advocate to perform this model comparison using Bayesian model quality measures such as the cvLME rather than information
criteria like BIC and (ii) the model comparison performed here is, strictly speaking, not equivalent to the F-test in the SPM manual, because the parametric model
also excludes regressors that are included in the categorical model, namely experimental condition regressors convolved with the hemodynamic derivatives.

4.2 Model selection: orientation pop-out

To demonstrate the cvBMS pipeline, we reanalyze data from an earlier study (Bogler et al., 2013) that has previously been used for the cvBMS paper (Soch et al., 2016). In this data set, we compared three models: a categorical model (GLM I) that describes the 4×4 experimental design using 16 regressors, one for each experimental condition; a linear-parametric model (GLM II) that uses one onset regressor indicating stimulation phases (orientation pop-out) and two parametric modulators encoding levels of the two factors (left and right orientation contrast); and a nonlinear-parametric model (GLM III) that uses nonlinear parametric regressors, motivated by behavioral pre-tests (Bogler et al., 2013; Soch et al., 2016). In this demonstration, we will build on estimated first-level GLMs and only describe the steps of model assessment and model selection.

First, in order to avoid model dilution, we want to compare the family of categorical models (consisting of GLM I only) against the family of parametric models (consisting of GLMs II & III). To this end, we specify a job in which we define a model space that consists of all 3 models applied to 22 subjects. Using dependencies on this model space information, automatic calculation of cvLME maps and LFE maps is performed (see Figure 5A). Following model family assessment, group-level BMS has to be specified manually, because log *family* evidences are not associated to particular *models* – which would be necessary for the automatic processing mode –, but only exist as individual images. After group-level BMS, selected-model maps are generated (see Figure 5A). This analysis leads to the results depicted in Figure 3B of the cvBMS paper.

Second, within the winning family of parametric models, we want to compare the linear-parametric (GLM II) to the nonlinear-parametric (GLM III) model. To this end, we define a new model space consisting only of these 2 models applied to 22 subjects. As cvLME maps have already been generated in the first step, model assessment does not have to be performed in this second step. Using dependencies on model space information, automatic group-level BMS and generation of SMMs are performed (see Figure 5A). This analysis leads to the results depicted in Figure 3C of the cvBMS paper.

Third, using the winning nonlinear-parametric model, we want to investigate the effect of removing the parametric modulator either for left or for right orientation contrast (OC), i.e. the effect of visual hemifield on model preference. This leads to a model describing only left OC (GLM III-l) and a model describing only right OC (GLM III-r). Again, we define a model space consisting of these 2 models applied to 22 subjects. As these are new models, cvLME maps have to be calculated (automatically). Finally, group-level BMS and selected-model maps are added to the pipeline (see Figure 5A). From the SMMs, we extract the proportion of voxels in left and right V4, respectively, with preferences for left or right OC, respectively, according to the group-level model selection. This analysis leads to the results depicted in Figure 5C of the cvBMS paper.

4.3 Model averaging: conflict adaptation

To demonstrate the cvBMA pipeline, we reanalyze data from another study (Meyer and Haynes, in prep.) that has previously been used for the cvBMA paper (Soch et al., 2017). For this data set, we estimated four models: all models include regressors for main blocks and delay phases in a conflict adaptation paradigm (Meyer and Haynes, in prep.); one model includes no additional processes (GLM 1); one model additionally describes the first trials following preparatory delays (GLM 2); one model additionally describes the cue phases preceding preparatory delays (GLM 3); and one model includes both additional processes, cue phases and first trials (GLM 4). Critically, cue phases and first trials are temporally correlated to preparatory delays, such that model choice influences parameter estimates for the delays phases. However, as each model includes regressors for the delay phases, we can use Bayesian model averaging to remove this modelling uncertainty (Soch et al., 2017). In this demonstration, we will build on estimated first-level GLMs and only describe the steps of model assessment and model averaging.

First, following model estimation, we want to calculate averaged estimates for the common model parameters in these four GLMs. To this end, we specify a job in which we define a model space that consists of all 4 models applied to 24 subjects. Using dependencies on this model space information, automatic calculation of cvLME maps and automatic group-level BMA are performed (see Figure 5B). Additionally, we perform automatic group-level BMS and generate selected-model maps. This analysis leads to the results reported in Table 2 and Figure 4A of the cvBMA paper. Group-level SMMs can be used for masking second-level analyses – an alternative to BMA that is not included in this demonstration, but discussed in the publication (Soch et al., 2017).

Second, following model averaging, we want to perform second-level analysis, but based on the averaged model parameter estimates calculated in the first step instead of the parameter estimates from a particular GLM as in standard processing pipelines. To this end, we use SPM's factorial design specification to set up a paired t-test between parameter estimates belonging to the two delay phase regressors (see Figure 5B). Subsequent model estimation, contrast calculation and statistical inference lead to the results reported in Table 1 and Figure 4A of the cvBMA paper. As expected, a main effect between switch and stay delays phases and, in more detail, a positive effect of switch over stay delay phases can be observed in left primary motor cortex (Soch et al., 2017).

SPM batch editor job files from all demonstrations, classical model assessment as well as cvBMS and cvBMA, are included as mat-files in the MACS toolbox repository. They can be used for educational purposes illustrating suggested pipelines or as analysis templates underlying the user's applications. Additionally, time consumption of creating and executing these demonstrations are reported in Table 2. In summary, when using the automatic processing mode, complex analyses, such as whole cvBMS and cvBMA pipelines, can be quickly implemented, because almost all analysis steps can simply reference the model space module which usually is the only time-consuming operation.

5 DISCUSSION

In functional magnetic resonance imaging (fMRI), model quality of general linear models (GLMs) is
rarely assessed (Razavi et al., 2003) which may have contributed to the current reproducibility crisis
in cognitive neuroscience (Pernet and Poline, 2015). We have introduced an SPM toolbox for model
assessment, comparison and selection (MACS) of GLMs for fMRI. The MACS toolbox implements
classical, information-theoretic and Bayesian measures of model quality and allows to guide first- and
second-level fMRI analyses by identifying optimal modelling approaches (Soch et al., 2016, 2017).
Increased application of the MACS toolbox should increase the methodological quality of statistical
analyses in fMRI research.

The key features of our toolbox are (i) *simplicity* – the toolbox is very easy to use and directly operates on
`SPM.mat` files from GLM estimation in SPM; (ii) *generality* – model assessment and selection are not
restricted to special model comparisons, but operate on arbitrary design matrices; (iii) *modularity* – toolbox
features can be combined into unique processing batches or even appended to existing SPM infrastructure;
(iv) *readability* – toolbox code is clearly written for developers and includes extensive comments explaining
mathematical background as well as implementational details[4]; and (v) *extendability* – the toolbox can be
easily augmented with other methods of model assessment, e.g. when one wants to employ Variational
Bayesian (Penny et al., 2007) or Empirical Bayesian (Penny and Ridgway, 2013) versions of the log model
evidence instead of our cvLME approach (Soch et al., 2016).

Version 1.0 of the MACS toolbox has been uploaded to GitHub in May 2017 (DOI: 10.5281/zenodo.845404).
The developers intend to immediately commit bug fixes to this repository (see Section 6). Future develop-
ments of the MACS toolbox may include group-level statistical tests for goodness-of-fit measures (Razavi
et al., 2003) and information criteria (Vuong, 1989) as well as improved voxel-wise visualization for
second-level model selection results.

6 SOFTWARE NOTE

The latest version of the MACS toolbox can be downloaded from GitHub[5] and has to be placed as a
sub-directory "MACS" into the SPM toolbox folder. Upon starting SPM, batch modules for toolbox
features can be assessed by clicking "SPM → Tools → MACS Toolbox" in the SPM batch editor (see
Figure 3). MACS is optimized for SPM12, but also compatible with SPM8.

With the adoption of MACS, software for cross-validated Bayesian model selection[6] (cvBMS) and cross-
validated Bayesian model averaging[7] (cvBMA) has become obsolete and the user is highly encouraged to
replace their old pipelines with the new toolbox.

---

[4] Information on any toolbox function (see Figure 1) can be obtained by simply typing `help MACS_fct_name` (e.g. `help MA_cvLME_multi`) into the MATLAB command window after successful MACS toolbox installation (see Section 6). A list of functions with descriptions can be generated using the built-in script `function_index` (resulting in `function_index.xls`).

[5] https://github.com/JoramSoch/MACS/releases

[6] https://github.com/JoramSoch/cvBMS

[7] https://github.com/JoramSoch/cvBMA

7   ACKNOWLEDGEMENTS

This work was supported by the Bernstein Computational Neuroscience Program of the German Federal Ministry of Education and Research (BMBF grant 01GQ1001C), the Research Training Group "Sensory Computation in Neural Systems" (GRK 1589/1-2), the Collaborative Research Center "Volition and Cognitive Control: Mechanisms, Modulations, Dysfunctions" (SFB 940/1) and the German Research Foundation (DFG grants EXC 257 and KFO 247).

Joram Soch received a Humboldt Research Track Scholarship from the Humboldt University and an Elsa Neumann Scholarship from the State of Berlin.

The authors would like to thank Carsten Bogler and Achim Meyer for acquiring the fMRI data sets used in this publication.

8   AUTHOR CONTRIBUTIONS

JS and CA developed the methods. JS implemented the methods and analyzed the data. JS created figures and tables. JS and CA wrote the paper.

9   CONFLICT OF INTEREST

The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

REFERENCES

Akaike, H. (1974). A new look at the statistical model identification. *IEEE Transactions on Automatic Control* 19, 716–723. doi:10.1109/TAC.1974.1100705

Andrade, A., Paradis, A.-L., Rouquette, S., and Poline, J.-B. (1999). Ambiguous Results in Functional Neuroimaging Data Analysis Due to Covariate Correlation. *NeuroImage* 10, 483–486. doi:10.1006/nimg.1999.0479

[Dataset] Ashburner, J., Friston, K., Penny, W., Stephan, K. E., et al. (2016). SPM12 Manual

Bishop, C. M. (2007). *Pattern Recognition and Machine Learning* (New York: Springer), 1st ed. 2006. corr. 2nd printing 2011 edn.

Bogler, C., Bode, S., and Haynes, J.-D. (2013). Orientation pop-out processing in human visual cortex. *NeuroImage* 81, 73–80. doi:10.1016/j.neuroimage.2013.05.040

Carp, J. (2012). On the Plurality of (Methodological) Worlds: Estimating the Analytic Flexibility of fMRI Experiments. *Frontiers in Neuroscience* 6. doi:10.3389/fnins.2012.00149

Friston, K., Harrison, L., and Penny, W. (2003). Dynamic causal modelling. *NeuroImage* 19, 1273–1302. doi:10.1016/S1053-8119(03)00202-7

Friston, K., Mattout, J., Trujillo-Barreto, N., Ashburner, J., and Penny, W. (2007). Variational free energy and the Laplace approximation. *NeuroImage* 34, 220–234. doi:10.1016/j.neuroimage.2006.08.035

Friston, K. J., Holmes, A. P., Worsley, K. J., Poline, J.-P., Frith, C. D., and Frackowiak, R. S. J. (1994). Statistical parametric maps in functional imaging: A general linear approach. *Human Brain Mapping* 2, 189–210. doi:10.1002/hbm.460020402

Gelman, A., Carlin, J. B., Stern, H. S., Dunson, D. B., Vehtari, A., and Rubin, D. B. (2013). *Bayesian Data Analysis* (Boca Raton: Chapman and Hall/CRC), 3rd edition edn.

Gläscher, J. P. and O'Doherty, J. P. (2010). Model-based approaches to neuroimaging: combining reinforcement learning theory with fMRI data. *Wiley Interdisciplinary Reviews: Cognitive Science* , n/a–n/adoi:10.1002/wcs.57

Henson, R. N. A., Shallice, T., Gorno-Tempini, M. L., and Dolan, R. J. (2002). Face Repetition Effects in Implicit and Explicit Memory Tests as Measured by fMRI. *Cerebral Cortex* 12, 178–186. doi:10.1093/cercor/12.2.178

Hoeting, J. A., Madigan, D., Raftery, A. E., and Volinsky, C. T. (1999). Bayesian Model Averaging: A Tutorial. *Statistical Science* 14, 382–401

Holmes, A. and Friston, K. (1998). Generalisability, random effects & population inference. *NeuroImage* 7, S754

Hurvich, C. M. and Tsai, C.-L. (1989). Regression and Time Series Model Selection in Small Samples. *Biometrika* 76, 297. doi:10.2307/2336663

Kass, R. E. and Raftery, A. E. (1995). Bayes Factors. *Journal of the American Statistical Association* 90, 773–795. doi:10.1080/01621459.1995.10476572

Luo, W.-L. and Nichols, T. E. (2003). Diagnosis and exploration of massively univariate neuroimaging models. *NeuroImage* 19, 1014–1032. doi:10.1016/S1053-8119(03)00149-6

Meyer, A. and Haynes, J.-D. (in prep.). Decoding behavioral adaptation under stimulus conflict

Monti, M. (2011). Statistical Analysis of fMRI Time-Series: A Critical Review of the GLM Approach. *Frontiers in Human Neuroscience* 5. doi:10.3389/fnhum.2011.00028

[Dataset] Nichols, T. E. (2013). Building Confidence in fMRI Results with Model Diagnosis

Penny, W. (2012). Comparing Dynamic Causal Models using AIC, BIC and Free Energy. *NeuroImage* 59, 319–330. doi:10.1016/j.neuroimage.2011.07.039

Penny, W., Flandin, G., and Trujillo-Barreto, N. (2007). Bayesian comparison of spatially regularised
general linear models. *Human Brain Mapping* 28, 275–293. doi:10.1002/hbm.20327

Penny, W., Kiebel, S., and Friston, K. (2003). Variational Bayesian inference for fMRI time series.
NeuroImage 19, 727–741. doi:10.1016/S1053-8119(03)00071-5

Penny, W., Stephan, K., Mechelli, A., and Friston, K. (2004). Comparing dynamic causal models.
NeuroImage 22, 1157–1172. doi:10.1016/j.neuroimage.2004.03.026

Penny, W. D. and Ridgway, G. R. (2013). Efficient Posterior Probability Mapping Using Savage-Dickey
Ratios. *PLoS ONE* 8, e59655. doi:10.1371/journal.pone.0059655

Penny, W. D., Stephan, K. E., Daunizeau, J., Rosa, M. J., Friston, K. J., Schofield, T. M., et al. (2010).
Comparing Families of Dynamic Causal Models. *PLoS Computational Biology* 6, e1000709. doi:10.
1371/journal.pcbi.1000709

Penny, W. D., Trujillo-Barreto, N. J., and Friston, K. J. (2005). Bayesian fMRI time series analysis with
spatial priors. *NeuroImage* 24, 350–362. doi:10.1016/j.neuroimage.2004.08.034

Pernet, C. and Poline, J.-B. (2015). Improving functional magnetic resonance imaging reproducibility.
GigaScience 4. doi:10.1186/s13742-015-0055-8

Razavi, M., Grabowski, T. J., Vispoel, W. P., Monahan, P., Mehta, S., Eaton, B., et al. (2003). Model
assessment and model building in fMRI. *Human Brain Mapping* 20, 227–238. doi:10.1002/hbm.10141

Rosa, M., Bestmann, S., Harrison, L., and Penny, W. (2010). Bayesian model selection maps for group
studies. *NeuroImage* 49, 217–224. doi:10.1016/j.neuroimage.2009.08.051

Schwarz, G. (1978). Estimating the Dimension of a Model. *The Annals of Statistics* 6, 461–464.
doi:10.1214/aos/1176344136

Seghouane, A.-K. and Ong, J. L. (2010). A Bayesian model selection approach to fMRI activation detection.
In *2010 IEEE International Conference on Image Processing* (IEEE), 4401–4404. doi:10.1109/ICIP.
2010.5653354

Soch, J., Haynes, J.-D., and Allefeld, C. (2016). How to avoid mismodelling in GLM-based fMRI data
analysis: cross-validated Bayesian model selection. *NeuroImage* doi:10.1016/j.neuroimage.2016.07.047

Soch, J., Meyer, A. P., Haynes, J.-D., and Allefeld, C. (2017). How to improve parameter estimates in
GLM-based fMRI data analysis: cross-validated Bayesian model averaging. *bioRxiv* doi:10.1101/095778

Spiegelhalter, D. J., Best, N. G., Carlin, B. P., and van der Linde, A. (2002). Bayesian measures of model
complexity and fit. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* 64,
583–639. doi:10.1111/1467-9868.00353

Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J., and Friston, K. J. (2009). Bayesian model
selection for group studies. *NeuroImage* 46, 1004–1017. doi:10.1016/j.neuroimage.2009.03.025

Stephan, K. E., Weiskopf, N., Drysdale, P. M., Robinson, P. A., and Friston, K. J. (2007). Comparing
hemodynamic models with DCM. *NeuroImage* 38, 387–401. doi:10.1016/j.neuroimage.2007.07.040

Vuong, Q. H. (1989). Likelihood Ratio Tests for Model Selection and Non-Nested Hypotheses.
Econometrica 57, 307. doi:10.2307/1912557

Welvaert, M. and Rosseel, Y. (2013). On the Definition of Signal-To-Noise Ratio and Contrast-To-Noise
Ratio for fMRI Data. *PLoS ONE* 8, e77089. doi:10.1371/journal.pone.0077089

Woolrich, M., Jenkinson, M., Brady, J., and Smith, S. (2004). Fully Bayesian Spatio-Temporal Modeling
of FMRI Data. *IEEE Transactions on Medical Imaging* 23, 213–231. doi:10.1109/TMI.2003.823065

FIGURES AND TABLES

Figure 1. Architecture of the MACS toolbox. This figure is for developers only and lists all functions from the toolbox. A black arrow indicates that one function calls the other. The horizontal dimension corresponds to the type of function (see Section 3.1): Generally, (A) batch functions call (B) interface functions which in turn call (C) mathematical functions. The vertical dimension corresponds to the type of feature (see Section 2): Interface functions consist of tools for model assessment (function prefix "MA"), model comparison (MC) and model selection (MS); mathematical functions consist of tools for model estimation (ME), many distributions (MD) and more functions (MF).

Figure 2. Batch modules in the MACS toolbox. This figure lists batch modules from the toolbox that are accessible via the SPM batch editor. Modules either belong to (A) the automatic processing stream or (B) the manual processing stream (see Section 3.2): automatic processing is based on a model space file (MS.mat) whereas manual processing is based on manual input of GLM info (SPM.mat) or cvLME maps (LME.nii). Modules take (C) particular input files and result in (D) particular output files: MATLAB files contain structured information (such as GLM info) and NIfTI files are brain images (such as cvLME maps). For abbreviations, confer the list of features (see Section 2 and Table 1).

Figure 3. Exemplary batch for Bayesian model selection. This figure shows the SPM batch editor with a typical batch for cross-validated Bayesian model selection (cvBMS) including an active module for group-level Bayesian model selection (BMS). The unfolded menu also hints at where to find features from the MACS toolbox upon successful integration into the SPM software, with the module for automatic cvLME model assessment being highlighted by mouse-over.

Figure 4. Demonstrations of voxel-wise visualization. This figure shows SPM graphics windows resulting from voxel-wise visualization tools included in the MACS toolbox. (A) Using the module "inspect goodness of fit", measured and predicted fMRI signal are shown alongside goodness-of-fit measures (see Section 2.1.1) which can be browsed for every in-mask voxel included in a particular first-level analysis (see Ashburner et al., 2016, sec. 31.2). The lower panel highlights voxels with the top 5% (yellow, good fit) and the bottom 5% (red, bad fit) in terms of coefficient of determination (R^2) for this GLM. (B) Using the module "visualize high-dimensional data", several data points in each brain region can be displayed and browsed in a voxel-wise fashion. The lower panel highlights voxels in which the R^2 of a GLM (the same as in A) is larger than $0.\bar{3}$. The upper panel bar plots beta estimates from the four experimental condition regressors of this model, indicating a negative effect of both two-level factors in this voxel (see Ashburner et al., 2016, fig. 31.1). Note that this feature may also be used to display voxel-wise posterior probabilities or model frequencies in large model spaces for comparing model preferences in different regions of interest.

Figure 5. Suggested pipelines for the MACS toolbox. This figure shows processing pipelines underlying the examples reported in this paper (see Section 4). (A) For Bayesian model selection (BMS), SPM model estimation should be followed by definition of the model space, automatic calculation of cvLME maps, automatic group-level BMS and generation of selected-model maps (SMM) from BMS results. In the case that individual models can be grouped into model families, automatic calculation of LFE maps would be followed by manual group-level BMS. (B) For Bayesian model averaging (BMA), SPM first-level analysis should be followed by definition of the model space, automatic calculation of cvLME maps, automatic group-level BMA which invokes subject-level BMAs (see Figure 1) and SPM second-level analysis based on averaged parameters.

Abbreviation	Feature	Equation	Reference
Model assessment: goodness-of-fit measures			
R^2	coefficient of determination	$R^2 = 1 - \frac{\text{RSS}}{\text{TSS}}$	Razavi et al., 2003
R^2_{adj}	coefficient of determination (adjusted)	$R^2_{\text{adj}} = 1 - (1 - R^2)\frac{n-1}{n-p}$	Razavi et al., 2003
SNR_{mf}	signal-to-noise ratio (model-free)	$\text{SNR} = \frac{|\hat\mu|}{\hat\sigma},\ \hat\mu = \bar y$	Welvaert and Rosseel, 2013
SNR_{mb}	signal-to-noise ratio (model-based)	$\text{SNR} = \frac{\text{var}(X\hat\beta)}{\hat\sigma^2}$	Welvaert and Rosseel, 2013
Model assessment: classical information criteria			
AIC	Akaike's information criterion	$\text{AIC} = -2\log p(y|\hat\theta, m) + 2k$	Penny et al., 2004
AIC_{c}	Akaike's information criterion (corrected)	$\text{AIC}_{\text{c}} = \text{AIC} + \frac{2k(k+1)}{n-k-1}$	Penny, 2012
BIC	Bayesian information criterion	$\text{BIC} = -2\log p(y|\hat\theta, m) + k\log n$	Penny et al., 2004
DIC	Deviance information criterion	$\text{DIC} = -2\log p(y|\langle\theta\rangle_{\theta|y}, m) + 2p_D$	Woolrich et al., 2004
Model assessment: Bayesian log model evidence			
LME	log model evidence	$p(y|m) = \int p(y|\theta, m)\,p(\theta|m)\,\mathrm{d}\theta$	Penny et al., 2007
oosLME	out-of-sample log model evidence	$\text{oosLME}_i = \log \int p(y_i|\theta, m)\,p(\theta\,|\,\cup_{j\neq i} y_j, m)\,\mathrm{d}\theta$	Soch et al., 2016
cvLME	cross-validated log model evidence	$\text{cvLME} = \sum_{i=1}^S \text{oosLME}_i$	Soch et al., 2016
LFE	log family evidence	$p(y|f) = \sum_{m\in f} p(y|m)\,p(m|f)$	Soch et al., 2016
Model comparison			
ΔIC	information difference	$\Delta\text{IC}_{ij} = \text{IC}(m_i) - \text{IC}(m_j)$	Penny et al., 2004
LBF	log Bayes factor	$\text{LBF}_{ij} = \text{LME}(m_i) - \text{LME}(m_j)$	Penny et al., 2004
LGBF	log group Bayes factor	$\text{LGBF}_{ij} = \log p(Y|m_i) - \log p(Y|m_j)$	Stephan et al., 2007
PP	posterior model probability	$p(m_i|y) = \frac{\exp(\text{LBF}_{ij})}{\exp(\text{LBF}_{ij})+1}$	Penny and Ridgway, 2013
Model selection			
FFX BMS	fixed-effects Bayesian model selection	$p(m_i|Y) = \frac{p(Y|m_i)\,p(m_i)}{\sum_{i=1}^M p(Y|m_i)\,p(m_i)}$	Penny et al., 2010
RFX BMS (VB)	random-effects Bayesian model selection (Variational Bayes)	see eq. 14 in reference	Stephan et al., 2009
RFX BMS (GS)	random-effects Bayesian model selection (Gibbs Sampling)	see eqs. 13–17 in reference	Penny et al., 2010
BMA	Bayesian model averaging	$\hat\beta_{\text{BMA}} = \sum_{i=1}^M \hat\beta_i \cdot p(m_i|y)$	Soch et al., 2017

Table 1. Features in the MACS toolbox. This table summarizes methods of model inference in MACS. References correspond to exemplary applications in the fMRI literature. For the respective statistical literature, confer the list of features (see Section 2).

Modules	time needed to create batch	time needed to execute batch
Model assessment: repetition priming		
Step 1: goodness of fit of categorical model	1 model	
inspect GoF	< 1 min	< 00:01 h
visualize HD data	1 min	< 00:01 h
Step 2: categorical model vs. parametric model	2 models	
model space, ICs (auto.), LBF (auto.)	2 min	< 00:01 h
Model selection: orientation pop-out		
Step 1: categorical GLM vs. parametric GLMs	3 models / 2 families	
model space, cvLME (auto.), LFE (auto.)	15 min	02:38 h
BMS (man.), SMM from BMS	15 min	< 00:01 h
Step 2: linear-parametric vs. nonlinear-parametric GLM	2 models	
model space, BMS (auto.), SMM from BMS	3 min	< 00:02 h
Step 3: nonlinear-parametric GLM with left vs. right OC	2 models	
model space, cvLME (auto.), BMS (auto.), SMM from BMS	8 min	01:43 h
Model averaging: conflict adaptation		
Step 1: averaged model parameter estimates	4 models	
model space, cvLME (auto.), BMA (auto.), BMS (auto.), SMM	25 min	07:05 h
Step 2: second-level statistical analysis	1 (averaged) model	
factorial design, model estimation, contrast manager (SPM)	10 min	< 00:01 h

Table 2. Demonstrations using the MACS toolbox. This table lists processing steps used in first-level model assessment or belonging to cvBMS and cvBMA pipelines (see Section 4). The second and third column give times required for specifying and running each batch in the SPM batch editor. The person that created the batch modules had 7 years of experience with SPM and was listening to Disc 1 of The Beatles' *White Album* while operating the MACS toolbox.