Improving the Generation and Selection of Virtual Populations in Quantitative Systems Pharmacology Models

Theodore R. Rieger[1], Richard J. Allen[1], Lukas Bystricky[2], Yuzhou Chen[3], Glen Wright Colopy[4], Yifan Cui[5], Angelica Gonzalez[6], Yifei Liu[7], R. D. White[8], R. A. Everett[8], H. T. Banks[8], Cynthia J. Musante[1]

[1]Internal Medicine Research Unit, Pfizer Inc, Cambridge, MA, USA
[2]Department of Computer Science, Florida State University, Tallahassee, FL, USA
[3]Department of Mathematical Sciences, University of Texas-Dallas, Dallas, TX, USA
[4]Institute of Biomedical Engineering, Department of Engineering Science, University of Oxford, Oxford, UK
[5]Department of Statistics and Operations Research, University of North Carolina-Chapel Hill, Chapel Hill, NC, USA
[6]Department of Mathematics, University of Arizona, Tucson, AZ, USA
[7]Department of Statistics, University of Wisconsin-Madison, Madison, WI, USA
[8]Center for Research in Scientific Computation, North Carolina State University, Raleigh, NC, USA

* Correspondence:
Theodore Rieger
ted.rieger@pfizer.com

Abstract

Quantitative systems pharmacology (QSP) models aim to describe mechanistically the pathophysiology of disease and predict the effects of therapies on that disease. For most drug development applications, it is important to predict not only the mean response to an intervention but also the distribution of responses, due to inter-patient variability. Given the necessary complexity of QSP models, and the sparsity of relevant human data, the parameters of QSP models are often not well determined. One approach to overcome these limitations is to develop alternative virtual patients (VPs) and virtual populations (Vpops), which allow for the exploration of parametric uncertainty and reproduce inter-patient variability in response to perturbation. Here we evaluated approaches to improve the efficiency of generating Vpops. We aimed to generate Vpops without sacrificing diversity of the VPs' pathophysiologies and phenotypes. To do this, we built upon a previously published approach (Allen, Rieger et al. 2016) by (a) incorporating alternative optimization algorithms (genetic algorithm and Metropolis-Hastings) or alternatively (b) augmenting the optimized objective function. Each method improved the baseline algorithm by requiring significantly fewer plausible patients (precursors to VPs) to create a reasonable Vpop. #ddct #qsp

1 Keywords

Global optimization, acceptance rejection sampling, mathematical modeling, ordinary differential equations, genetic algorithm, Metropolis-Hastings

2 Abbreviations

GA – Genetic Algorithm

GoF – Goodness of Fit

HDL_c – High Density Lipoprotein Cholesterol

LDL_c - Low Density Lipoprotein Cholesterol

MH – Metropolis-Hastings

NHANES – National Health And Nutrition Examination Survey

NSA – Nested Simulated Annealing

SA – Simulated Annealing

PP – Plausible Patient

QSP – Quantitative Systems Pharmacology

TC – Total Cholesterol

VP – Virtual Patient

Vpop – Virtual Population

3 Introduction

Physiologically based mathematical models are often used to describe and predict the response of a patient to an existing therapy or novel agent. These models, frequently referred to as quantitative systems pharmacology (QSP) models, are used to simulate clinical trials in drug development (Musante, Ramanujan et al. 2017). In these applications, it is important that they not only capture the mean patient response to treatment but also inter-patient variability and how that variability may evolve over time. In addition, due to the novel nature of many therapies; the complexity of human physiology; and generally limited human data, QSP models are rarely fully determined by data. One approach to these challenges is to develop alternate parameter sets to capture the variability in the real clinical trial population and sample as much uncertainty in the model parameters as possible (Gadkar, Budha et al. 2014, Hallow, Lo et al. 2014, van de Pas, Rullmann et al. 2014).

Previously, we published an algorithm for the generation and selection of these alternative value sets (Allen, Rieger et al. 2016). The algorithm used simulated annealing (SA) to generate as large a population of "plausible patients" (PPs) as was practical. SA was used with a cost functional that optimized solutions to be biologically feasible. These PPs, which we call a "plausible population", were termed plausible since each generated parameter set simulated a patient that was physiologically reasonable, and could be in a clinical trial, but there was not yet any selection for how *likely* it was for that patient to have been in a particular clinical trial. We then used our novel selection technique to choose those patients from the plausible population that most resembled a desired clinical population. These

selected patients were then termed virtual patients (VPs), and as a collection they
were called a virtual population (Vpop).

Since the original algorithm created a plausible population that was naïve to the
targeted Vpop distribution, significant computational effort was expended in
generating PPs in unlikely regions of the target distribution. Here we propose
alternative algorithms to improve the generation of the plausible population for
more efficient generation of the Vpop. The common approach for each newly tested
algorithms is to use information about the target distribution in generating the
plausible population. We explored this idea in three ways:

(1) Nested simulated annealing (NSA), which augments the SA method by
targeting PP generation using the probability density function of the target
distribution;
(2) A genetic algorithm (GA), which iteratively builds a plausible population
according to a fitness function defined by the desired distribution; and lastly
(3) A Metropolis-Hastings (MH) inspired importance-sampling technique.

Results of the original SA method were re-generated, for direct comparison to each
of the three new approaches.

4 Methods

This current work is the evaluation of three approaches for the generation of Vpops
that match distributions of clinical cohorts or populations. The general flow for our
algorithm is (Figure 1):

1. Implement an ordinary differential equation (ODE) model that describes the
biological system of interest;
2. For each state (variable) in the model, define a lower and upper limit for
assessing if a steady state solution is plausible (all states between lower and
upper limits) or not;
3. For each parameter of the model (e.g., rate constants, Michaelis-Menten
constants), also define a plausible lower and upper limit for the search
algorithms;
4. Optimize, using one of four algorithms, for solutions of the model that are
PPs;
5. Collect the PPs generated by the optimization into a plausible population,
terminating the search for PPs when the optimization achieves a preset
number of PPs in the plausible population;
6. Perform acceptance/rejection sampling on the plausible population to select
the VPs from the PPs that allow us to match the statistics of the target clinical
population.

This section is organized to describe these three methods (NSA, modified GA, and
modified MH), and how to apply them to generate VPs. This is followed by a
description of how the results were analyzed, including a novel metric to quantify
the uniqueness of a collection of parameter sets.

4.1 Mathematical Model and Data

Following our previous approach, we tested our proposed methods using a
published ODE model of lipoprotein metabolism (van de Pas, Woutersen et al.
2012). In brief, the van de Pas model is a model of cholesterol production by the
liver and its transit through the plasma. The ODE cholesterol model has nine
equations, or state variables (Supplementary Table S1). These state variables
correspond to the mass or concentrations of species within particular
compartments (e.g., liver, plasma, peripheral tissues). The focus or primary outputs
of the model are calculating levels of high-density lipoprotein cholesterol (HDL$_c$)
and "non-high-density lipoprotein cholesterol", which we assumed to be equivalent
to low-density lipoprotein cholesterol (LDL$_c$). Thus the parameters of the ODE
model we changed in the global optimization methods were the rate constants of the
mass action model (e.g., production, reaction, clearance constants, see
Supplementary Table S2). For the present work of creating baseline PPs and VPs, we
only used the ODE model to simulate physiologically reasonable patients at steady
state and were not concerned with the transient changes of the model.

While the ODE model has nine states, not all of them are frequently collected in
clinical trials. The outputs of the model we matched to the statistics of human
clinical data through our Vpop selection algorithm were: HDL$_c$, LDLc, and total
cholesterol (TC). As in original paper, for our reference population to match we used
the National Health and Nutrition Examination Survey dataset (NHANES 2011-
2012). The NHANES dataset contained fasting values for plasma cholesterol levels
in 2,942 patients. The data was well represented by a joint lognormal distribution
(Supplementary Figure S1).

4.2 Summary of Original SA Algorithm (Baseline Comparator)

148 In (Allen, Rieger et al. 2016) we optimized the steady-state solutions, x^*, to fall
149 within biologically reasonable ranges rather than to a specific point using the cost
150 functional

151
$$g(\boldsymbol{p}) = \sum_{i=1}^{N} \max\left[\left(x_i^*(\boldsymbol{p}) - \frac{l_i+u_i}{2}\right)^2 - \left(\frac{u_i}{2} - \frac{l_i}{2}\right)^2, 0\right], \ (1)$$

where N is the number of states of the model (N = 9 for van de Pas et al.), and l_i and
u_i represent the biologically plausible lower and upper bounds for the i^{th} state
variable's steady-state solution (see Supplementary Table S1). Note that if $x_i^*(\boldsymbol{p})$ is
within the plausible biological bounds, then $g(\boldsymbol{p}) = 0$, and the parameter set $\boldsymbol{p}$ is
called a PP. SA iteratively proposes values of $\boldsymbol{p}$ until $g(\boldsymbol{p}) = 0$. A new initial $\boldsymbol{p}$ is then
generated, and the SA optimization is repeated until a plausible population is

created.

4.3 NSA Algorithm

The NSA algorithm incorporates information about the target data distribution in
the process of generating the plausible population. By modifying the cost functional,
equation (1), we can include information about the desired distribution, thus
decreasing the number of PPs required per VP. The joint distribution of NHANES
patient's LDL$_c$, HDL$_c$, and TC is well approximated by a multivariate lognormal
distribution, with a probability density function that is roughly ellipsoidal in iso-
density lines. The hypercube in which $g(\boldsymbol{p}) = 0$ in equation 1, was changed to an
ellipsoidal shape, in the dimensions $x_i^*(\boldsymbol{p})$ that correspond to LDL$_c$, HDL$_c$, and TC.
The edge of this ellipsoid corresponds to the least-probable value (with respect to
the multivariate log-normal) for which $g(\boldsymbol{p}) = 0$.

However, the modified g(p) makes no distinction between low-probability solutions,
at the edge of the ellipse, and high-probability solution, near the centroid of the
ellipsoid. Hence, to fully use information from the target distribution, we considered
multiple nested ellipsoids, relegating acceptable PPs according to whether they
achieve sufficiently high probability density with respect to this target distribution.
From this, the modified g(p) controls the number of PPs generated in each ellipse.

Note that while biological upper and lower bounds exist for all of the nine model
outputs, we only have distributional information regarding LDL$_c$, HDL$_c$, and TC. As a
result, the modified cost function still achieves a minimum when the remaining six
dimensions falls within the hypercube of biologically plausible solutions.

We use the following equation for the surface of an ellipsoid that will encompass the
data:

182
$$(\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) = c^2, \quad (2)$$

where $\boldsymbol{X}$ is a 3 × 1 vector representing a point in the log-scaled vector of [LDL$_c$,
HDL$_c$, and TC], and $\boldsymbol{\mu}$ and Σ are maximum likelihood estimates of the mean and
covariance matrix of the multivariate normal distribution, and c^2 controls the
extreme point of the ellipsoid. By letting $\boldsymbol{X}$ be the data point furthest from the mean
in (2), we can explicitly calculate the minimum value for c^2 that allows the data to
be encompassed by the ellipsoid.

First consider only one ellipsoid region. Then the modified cost functional is

190
$$h(\boldsymbol{p}) = g(\boldsymbol{p}) - \gamma((\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) - c^2), \quad (3)$$

where $g(\boldsymbol{p})$ is given by equation (1) for N = 6, and is calculated for the 6 state
variables for which we do not have distributional information. We can interpret this
cost functional as forcing these 6 state variables to be within plausible biological
bounds while forcing the remaining 3 log-scaled observables to be within the

smallest ellipsoid region that encompasses the clinical data. Notice we have an
additional parameter, γ, which is a scaling factor that is a free parameter of the
method for balancing the weight of the ellipsoid term on the cost functional. A value
of $\gamma = 0.1$ was used for all simulations (Rieger and Allen 2017).

Now consider several nested ellipsoid regions. The cost functional for each nested
ellipsoid is given in (3) but with modified c^2 values in order to control the
distribution of the plausible population. The number of nested ellipsoids, R, is
another free parameter of this method. We denote the ellipsoids as $E_1 \subset E_2 \subset \cdots \subset$
E_R, with the k^{th} ellipsoid centered at the mean $\boldsymbol{\mu}$ and defined as $E_k = \{\boldsymbol{X} : (\boldsymbol{X} -$
$\boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) \leq c_k^2\}$.

We choose the c_k values such that a k/R proportion of the observations are within
the k^{th} ellipsoid:

207
$$\int_{E_k} \Phi(x)dx = \frac{k}{R} \quad , \qquad (4)$$

208 where $\Phi(x)$ is the multivariate normal distribution, and $k = 1 \ldots R$. We find an
209 approximate solution, c_k , to this integral, by using a Monte Carlo approach.
210 Equivalently,

211
$$\int_{E_1} \Phi(x)dx = \frac{1}{R} \qquad (5)$$

212
$$\int_{E_k \backslash E_{k-1}} \Phi(x)dx = \frac{1}{R}. \qquad (6)$$

For this method, we sequentially populate each ellipsoid uniformly such that the
final plausible population approximates the distribution for the target patient
distribution. We therefore need to calculate how many PPs are required for each
ellipsoid, given a desired total number of PPs. Define q_k as the proportion of the
total plausible population within the k^{th} ellipsoid. Then, since we assume the data
are approximately uniformly distributed throughout each ellipsoid, we want to
solve a system of R equations for each q_k obtained by solving

221
$$\frac{1}{R} = \sum_{k=j}^{R} \frac{V_j - V_{j-1}}{V_k} q_k, \qquad (7)$$

222 for $j = 1, \ldots, R$. Where V_j is the volume of the j^{th} ellipsoid. We define $V_0 = 0$. Note
223 that $V_j \propto c_j^n$, where n is the dimension of the multi-dimensional distribution. Then,
224 equation (7) can be re-written as

225
$$\frac{1}{R} = \sum_{k=j}^{R} \frac{c_j^n - c_{j-1}^n}{c_k^n} q_k, \qquad (8)$$

which can be solved recursively for the q_k (starting with $k = R$, and defining $c_0^n = $
0).

Alternatively, since the NHANES data provided individual level data, the target
distributions c_k (and q_k) were calculated empirically, see source code (Rieger and
Allen 2017).

With the ellipsoids defined we can generate the plausible population by randomly
generating a parameter set in the ranges we defined from a uniform distribution.
Then, for a pre-defined plausible population of size m, for $l = 1$ to m, we identify a
PP by minimizing:

235
$$h_k(\boldsymbol{p}) = g(\boldsymbol{p}) - \gamma((\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) - c_k^2), \quad (9)$$

where $g(\boldsymbol{p})$ is given by equation (1) for N = 6, and is calculated for the 6 state
variables for which we do not have distributional information. See Supplementary
Text 1 for further details.

This method requires choosing the number of nested ellipsoids. The greater the
number of ellipsoids, the closer the distribution of the plausible population will
match that of the clinical population, thus reducing the number of PPs required per
VP. However, an increase in the number of ellipsoids increases computation time for
the plausible population. In this case, we used five ellipsoids. We then use our
rejection sampling method to select the VPs from the plausible population.

4.4 Modified GA

A commonly used population-based approach for optimizing nonlinear models is a
genetic algorithm (GA), (Golberg 1989, Conn, Gould et al. 1991). For our problem,
we created our plausible population using MATLAB's *ga* function (MATLAB 2016).
This algorithm first creates an initial population, where each patient is drawn from a
uniform distribution. The algorithm then assigns a fitness value to each patient
using a cost (fitness) functional. Similar to the NSA method, we modify equation (1)
by incorporating information about the desired distribution. Specifically, the cost
functional is given by

254
$$H(\boldsymbol{p}) = \left\{ \begin{array}{ll} g(\boldsymbol{p}) & \text{if } g(\boldsymbol{p}) > 0 \\ -\gamma(\boldsymbol{p}) & \text{otherwise,} \end{array} \right. \quad (10)$$

255 where $\gamma(\boldsymbol{p})$ is the likelihood of a given log-scaled observable value $\boldsymbol{X}$ given by

256
$$\gamma(\boldsymbol{p}) = \frac{1}{\sqrt{(2\pi)^3 |\Sigma|}} \exp\left(-\frac{1}{2}(\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu})\right). \quad (11)$$

This cost functional can be interpreted as forcing all state variables to be within
plausible biological bounds and additionally assessing a penalty as the log-scaled

observables deviate from $\boldsymbol{\mu}$.

As the algorithm progresses, children are created for each generation; those with a
cost functional value $H(\boldsymbol{p}) < 0$ become PPs. Since many PPs are created each
generation, there is no way to specify the exact number of PPs generated. Thus we
must preset the minimum number of PPs desired, but in practice we tended to
generate slightly more than sought (see Supplementary Code). Once the plausible
population is created, we use rejection sampling to determine the Vpop from the
plausible population.

4.5   Modified MH Algorithm

The Metropolis-Hastings (MH) algorithm can be used to approximate a desired
distribution, for a review see (Robert 2015). To apply the MH approach here we
need to modify the algorithm. To see why, consider the original algorithm. Let $\pi(\boldsymbol{p})$
be our desired target multivariate probability distribution for the vector $\boldsymbol{p}$. The MH
algorithm generates a sequence of $\boldsymbol{p}$, such that the distribution of this sequence,
$\{\boldsymbol{p_0}, \dots, \boldsymbol{p_N}\}$ converges to $\pi(\boldsymbol{p})$ as $samplings \rightarrow \infty$. Let $Q(\boldsymbol{p}, \boldsymbol{q})$ be some symmetric
proposal distribution, which is interpreted as generating a proposed value $\boldsymbol{q}$ from
$Q(\boldsymbol{p}, \boldsymbol{q})$ when the process is at value $\mathbf{p}$. Then the original MH algorithm is as follows:

1. Generate an initial vector $\boldsymbol{p_0}$, set $i = 1$.
2. Generate a proposed vector $\boldsymbol{p}^* \sim Q(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*)$.
3. Calculate the probability $\boldsymbol{p}^*$ is accepted, $\alpha = \min\left(1, \frac{\pi(\boldsymbol{p}^*)}{\pi(\boldsymbol{p_{i-1}})}\right)$.
4. Generate $Y \sim U(0,1)$, if $y \leq \alpha$, set $\boldsymbol{p_i} = \boldsymbol{p}^*$. If $Y > \alpha$, set $\boldsymbol{p_i} = \boldsymbol{p_{i-1}}$.
5. Repeat steps 2 to 4 for $i = 1, \dots, number\ of\ samples$ to collect $\{\boldsymbol{p_0}, \dots, \boldsymbol{p_N}\}$ as
281   a sampling from the target distribution.

This MH algorithm approximates the target distribution $\pi(\boldsymbol{p})$ by randomly sampling
from it. At first glance, this approach appears immediately applicable to the problem
at hand and will generate a plausible population that will converge to the Vpop as
$N \rightarrow \infty$. However, this algorithm requires modification because we do not know
$\pi(\boldsymbol{p})$ $a\ priori$; i.e., we do not know how the parameters sets should be distributed
such that the model, when simulated using those parameters, matches the data.

We rewrite our target distribution as $T(\boldsymbol{X_p})$, where $\boldsymbol{X}$ is the observable outcomes
generated by the model M, using a parameter set (which in this case is in the log-
space, so $\boldsymbol{X_p} = \log M(\boldsymbol{p})$). Then our algorithm becomes

1. Generate an initial vector $\boldsymbol{p_0}$, set $i = 1$.
2. Generate a proposed vector $\boldsymbol{p}^* \sim Q(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*)$, write
293             $Q_m(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*) = M(Q(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*))$.
294   3. Calculate the probability $\boldsymbol{p}^*$ is accepted, $\alpha = \min\left(1, \frac{T(\boldsymbol{X_{p^*}})Q_m(\boldsymbol{p}^*, \boldsymbol{p_{i-1}})}{T(\boldsymbol{X_{p_{i-1}}})Q_m(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*)}\right)$,

$$\text{assume } \alpha \cong \min\left(1, \frac{T(X_{p^*})}{T(X_{p_{i-1}})}\right).$$

4. Generate $y \sim U(0,1)$, if $y \leq \alpha$, set $\boldsymbol{p}_i = \boldsymbol{p}^*$. If $y > \alpha$, set $\boldsymbol{p}_i = \boldsymbol{p}_{i-1}$.
5. Repeat steps 2 to 4 for $i = 1, \ldots, N$ to collect $\{\boldsymbol{p}_1, \ldots, \boldsymbol{p}_N\}$ as a sampling from the target distribution.

In the canonical version of the MH algorithm α is independent of the proposal distribution Q because it is symmetric and cancels out of the equation. In the modified version above, Q_m is unknown and, in fact, is unlikely to be symmetric. In order to proceed we assume that Q_m is approximately symmetric $Q_m(\boldsymbol{p}^*, \boldsymbol{p}_{i-1}) \sim Q_m(\boldsymbol{p}_{i-1}, \boldsymbol{p}^*)$, so that we can calculate α as above. Because of this approximation it is still necessary, following our previously published algorithm, to apply acceptance-rejection sampling to finalize the Vpop from the plausible population.

4.6 Assessing Similarity Between VPs

It is desirable to examine the parameter space in the Vpop to ensure heterogeneity of the VPs (while still reproducing available data). The baseline method ensured this diversity by generating VPs independently and from different initial parameter estimates. However, this is not necessarily the case for the GA and MH methods.

To assess the diversity of a Vpop we devised a test metric $d(\boldsymbol{p}_i, \boldsymbol{p}_j)$ which scores how similar two VPs are. By randomly sampling pairs of VPs from a given Vpop, we built up a distribution for d and could compare the resultant cumulative density function (CDF) for each method. The test metric d is simply the normalized dot-product of $\boldsymbol{p}_i$ and $\boldsymbol{p}_j$ after they are scaled and shifted:

$$d(\boldsymbol{p}_i, \boldsymbol{p}_j) = \frac{\hat{\boldsymbol{p}}_i \cdot \hat{\boldsymbol{p}}_j}{|\hat{\boldsymbol{p}}_i||\hat{\boldsymbol{p}}_j|} \qquad (12)$$

$$\hat{\boldsymbol{p}} = \text{diag}(V^{-1}(\boldsymbol{p} - \boldsymbol{l})) - \frac{1}{2}$$

where V is a diagonal matrix such that $\boldsymbol{v}_{ii} = \boldsymbol{u}_i - \boldsymbol{l}_i$. Hence, $\text{diag}(V^{-1}(\boldsymbol{p} - \boldsymbol{l}))$ uses the defined upper and lower bound for each parameter (the elements of $\boldsymbol{u}$ and $\boldsymbol{l}$ respectively), to scale each parameter in $\boldsymbol{p}$ to be between 0 and 1. To ensure that $d \in [-1,1]$ we further subtract ½ from each element. This means that, in principle, $\hat{\boldsymbol{p}}$ can be orientated in any direction in m-dimensional space (where m is the number of parameters). This also means that if the elements of $\boldsymbol{p}$ are sampled uniformly between the upper and lower bounds that, by symmetry, the expected value of the distribution should be zero (i.e., the CDF crosses 0.5 at $d = 0$). This is the optimal parameter set in terms of diversity, but may not be achievable given the constraints applied to the model. Conversely, if we generate Vpops from very similar parameter sets then the distribution will be right-shifted towards d=1.

4.7 Assessing Goodness of Fit

The goodness of fit (GoF) to the empirical target distribution was assessed by using the Kolmogorov-Smirnov statistic for the marginal distribution over each dimension:

$$\text{GoF} = \sum \sup |F_i(x) - D_i(x)| \qquad (13)$$

where $F_i(x)$ is the empirical cumulative distribution function for the i^{th} model observable that we are fitting the observed cumulative distribution of the data, $D_i(x)$. Note that for a perfect fit GoF=0, and that GoF $\in [0, n]$, where n is the number of distributions being fitted.

4.8 Source Code and Simulations

All algorithms were implemented in MATLAB 2016b (v9.1) using the Global Optimization Toolbox (v3.4.1) where a pre-packaged routine was available (e.g., GA, SA). The ODE model was implemented in SimBiology (v5.5). The K-S Test for GoF utilizes MATLAB's Statistics and Machine Learning Toolbox (v11.0). The full source code is available for download from a GitHub repository (Rieger and Allen 2017). The source code utilizes three independent packages from MathWorks File Exchange (Johnson 2004, Jos 2016, Dorn 2017).

All simulations were performed sequentially on a MacBook Pro with a 2.9 GHz Intel Core i7 processor and 16 GB of RAM. For each choice of algorithm and pre-set number of PPs, simulations were repeated five times and the mean and standard deviation calculated.

5 Results

5.1 Comparing the various algorithms

To compare the three proposed algorithms (NSA, GA and MH) we evaluated four metrics to measure performance of the algorithm compared to the original SA method. For each algorithm, we evaluated:

1. **Efficiency:** How many PPs were needed to achieve a certain GoF of the final Vpop to the observables?
2. **Computational Cost:** How fast was the generation of PPs and VPs?
3. **Diversity:** Are the VPs parametrically similar or do they maintain the parametric heterogeneity of the PPs?
4. **Convergence**: Do the methods benefit from the acceptance/rejection step or can a Vpop be generated directly?

5.2   Comparison of algorithms for efficiency of yield

For each algorithm, we targeted generation of between 100 and 7,500 total PPs;
those PPs were then converted into VPs through the acceptance/rejection
algorithm. The GoF of the resulting Vpop was calculated as discussed in Methods. By
comparing the GoF achieved for the Vpops with varying PPs (Figure 2) we find that
as the number of PPs→5,000+, all of the algorithms generated essentially
indistinguishable GoFs for the final Vpop (albeit with different VPs in each Vpop).
However, the three new algorithms were more efficient than the original SA method,
especially when the number of PPs < 1,000. In fact, Vpops generated with as few as
100 PPs could have similar fits to the observable data as the SA method with 500+
PPs.

5.3   Comparison of algorithms for computational cost

Even if an algorithm can generate the same GoF through far fewer PPs than the
original SA algorithm, this does not necessarily mean the process was
computationally more efficient. We further compared each method based on the
clock time (evaluated via MATLAB's *tic/toc* functions) required to generate a Vpop
from 7,500 PPs (Figure 3). While the NSA method was arguably superior based on
yield, this algorithm required approximately the same amount of time to execute as
the SA method. Based on time, the MH and GA were the fastest algorithms and the
SA remains among the least efficient.

5.4   Comparison of algorithms for parametric diversity of the final Vpop

An advantage of the SA algorithm is its ability to generate Vpops that maintain most
of the parametric diversity of the original PPs (Supplementary Figure S2-3). This
diversity in the Vpop is an essential feature for QSP models since they are often
utilized in simulation of clinical trials involving novel therapies. If the underlying
parameters of VPs are highly similar/correlated, clinical trial simulations performed
with the Vpop may incorrectly predict a very narrow range of therapeutic response.
Therefore, we need to ensure that as we introduce new algorithms, we do not trade
parametric diversity for computational gains. We measured the diversity of the
Vpops generated by each algorithm by uniformly sampling pairs of VPs and
calculating the dot product between each set of parameters (see Methods). As a
reference point/positive control, we included a set of uniformly, randomly
generated model parameters (Figure 4). The closer each algorithm's final VP
parameter distribution is to the random reference, the more diverse we considered
the set of VPs in the Vpop. For this criterion, the SA method was found to have the
most diversity, indistinguishably followed by NSA and MH. The GA method showed
distinct rightward shifts in its distribution, indicating that fewer independent
parameter sets were identified in the generation of the Vpops. Supplementary
figures show the violin plot for each method for both the PPs and VPs for a single
iteration (Supplementary Figures S3, S5, S7, and S9).

5.5 Convergence of the algorithms to the data

In contrast to the original SA method, each of the methods tested use information
about the desired population distribution and thus requires fewer PPs to achieve an
acceptable fit for the Vpop (Figure 2). To evaluate if the final selection step was still
required as part of the algorithm workflow, we compared the GoF for each of the
methods before and after the acceptance/rejection step, starting with ~7,500 PPs in
each case (Figure 5). As expected, the largest improvement in Vpop fit from the PPs
to VPs was for the SA method; however, all of the methods showed at least a 3-fold
improvement in GoF through the final selection step. The NSA method showed the
best initial fit for its PPs to the NHANES data, reasonably reproducing both the 1-
dimensional and 2-dimensional histograms before the selection step (Figure S3A-F).
These fits were approximately equivalent to the final Vpop fit for the SA method
starting with 1,000 PPs.

6 Discussion

By design, most quantitative systems pharmacology models are not identifiable
from available data. While it would be desirable to have parameters well
determined and characterized, the uncertainty in parameter values in QSP models
often reflects our current knowledge (or lack thereof) of human (patho)-physiology.
Therefore, with this perspective, we can use these models in a hypothesis-
generation/testing mode to explore how these knowledge gaps translate to
uncertainties in clinical outcomes and clinical trial design. In our opinion, the most
thorough and robust way of doing this is by generating the most diverse Vpops
given the available data.

Exploring the parameter space of under-determined quantitative systems
pharmacology models remains a challenge but it is essential for robust predictions
of safety and efficacy for novel compounds. Here we presented three methods for
generating diverse parameter sets in a QSP model. While this exercise is by no
means an exhaustive exploration of global optimization techniques, each algorithm
improved at least one of the testing metrics compared to our previously published
SA method. The seemingly simple question of which method is "the best" cannot be
definitively answered here but it is important to be aware of the pros and cons for
each and potential steps to improve performance.

We previously discussed the advantages and disadvantages of using the SA method
for this application (Allen, Rieger et al. 2016). In comparison to other methods
tested it was the slowest (or tied with NSA) and required the most PPs for a quality
fit. Conversely, it also generated the most diverse Vpop with the fewest imposed
correlations. The ease of implementation is also an advantage for SA. As
implemented, the algorithm required no prior knowledge of the final Vpop
distribution and there was a minimal set of tuning parameters required, most of
which were default MATLAB options (i.e., no arbitrary decision about number of

ellipsoids, number of generations). As such, the algorithm remains relevant as a
"first try" for generating VPs. Furthermore, it is the only method that can be run (at
least in part) without prior knowledge of the target distribution. This relaxed
requirement can make it an attractive choice for pre-computing plausible
populations or for exploring how the parameter space relates to the model output
(for example, identifying parameters in the model that can give rise to sub-
populations of interest).

The NSA approach iterates on the SA method by utilizing prior knowledge of the
final parameter distribution and forcing the algorithm to regions with the most
desired patient density. This method is likely most efficient when the target
distribution is approximately multivariate normal. Fortunately, for the example
here, the target distribution was well approximated as a multivariate lognormal.
The viability of this method for more eccentric or bimodal distributions would need
to be studied by applying it to other case studies. However, such distributions are
less commonly observed in clinical trials. For our case study, the computational cost
to generate a plausible population was comparable between the NSA and SA
methods; however, the NSA approach demonstrated vastly improved yield (VP per
PP), which facilitated an overall more efficient Vpop generation process. The
algorithm was as good, or better, than the other methods tested for direct
generation (pre-selection/rejection) of a reasonable Vpop, without the imposed
correlations found in Vpops generated by GA. While essentially the same as the SA
method to implement, there is a problem-specific choice for the number of ellipsoids
to use. Here we used five regions, regardless of the number of PPs being generated.
Fine-tuning based on the model/number of PPs may potentially improve
performance.

MH is unique amongst the approaches we tried in that it is a Markov Chain, which
should imply some degree of correlation between the PPs. The advantage of this
technique was an increase in speed and compared to the two methods based on SA;
however, there also was a right-shift in the dot product cumulative distribution,
implying a slightly less diverse final population. Methods have been published to
attempt to reduce this correlation (Santoso, Phoon et al. 2011) and to improve
performance in higher dimensions (Betancourt 2017), but we chose to evaluate only
the common form of the algorithm and to leave further exploration for future
improvements. While straightforward to implement, MH requires the choice of a
proposal distribution. As noted in the Methods, because we indirectly sample the
distribution of the observables by first sampling the parameter space and then
generate the observables through model simulation we do not have direct control
over the choice of a proposal distribution. The implications of this for direct
convergence of this method will depend on the symmetry of the observable
distribution (induced by the parameter sampling) around every point on the
Markov chain. In this case, the approximation we assumed (see Methods) appeared
to hold sufficiently for the MH algorithm to approximate the empirical distributions.
However, the final Vpop was improved by acceptance/rejection sampling.

The GA was very similar to MH in that, compared to the SA-based methods, a 10-fold
improvement in computational speed was achieved at the cost of some lost
heterogeneity in the final Vpop. The GA is easy to implement for QSP models and the
supplied routine with MATLAB's Global Optimization Toolbox was sufficient for our
purposes. GA requires some problem-specific decisions, which may affect overall
performance; for example, the size of the population, number of generations, and
mutation rate can be adjusted as needed.

The curse of under-determined models has led to a long history of using different
global optimization techniques for generating parameter sets within the bounds of
the data (van de Pas, Woutersen et al. 2012, Gadkar, Budha et al. 2014, Hallow, Lo et
al. 2014). Use of global optimization techniques often feels like more of an art than a
science due to how problem-specific their application can be. For this reason, we
examined several algorithms with different approaches for exploring constrained,
multidimensional parameter spaces. Requiring only minimal tuning, each of these
algorithms successfully explored the range of our 23-dimensional parameter space
and generated reasonable PPs. The choice of algorithm to use for a new problem,
particularly one with higher dimensions and a less Gaussian set of observations, will
need to be evaluated on a case-by-case basis. For example, for models that are slow
to simulate the most constraining factor is computational cost. In this case the MH
or GA approaches may be the most successful; however, as we have shown, without
adaptation these methods may come at a cost of diversity in the final Vpop.

We hope that the results presented here will provide a guide to selection and
implementation of these algorithms to facilitate the generation of robust Vpops in
mathematical models of (patho)-physiology.

7   Author contributions

RJA conceived of the original algorithm. CJM, RJA, and TRR conceived of the updated
algorithm objectives. AG, GWC, LB, RW, YC1, YC2, and YL selected and coded the new
algorithms and performed the initial proof-of-concept testing. CJM, RE, HTB, RJA,
and TRR supervised and advised the initial work. RJA, RE, RW, TRR, HTB, and CJM
drafted the manuscript. All authors reviewed, revised, and approved of the final
manuscript.

8   Conflict of interest

518   TRR, RJA, and CJM were employees of Pfizer Inc. during the completion and
519   analysis of this study.

9   Funding

This research was supported in part by the National Institute on Alcohol Abuse and
Alcoholism under grant number 1R01AA022714-01A1, in part by the Air Force
Office of Scientific Research under grant number AFOSR FA9550-15-1-0298, and in

part by the US Department of Education Graduate Assistance in Areas of National
Need (GAANN) under grant number P200A120047. GWC was supported by the
Clarendon fund and EPSRC. Pfizer Inc. supported the research of TRR, RJA, and CJM.

10 Acknowledgements

528   The authors thank Ilse Ipsen and Thomas Gehrmann for organizing the 2016 SAMSI
529   Workshop at North Carolina State University, which initially facilitated this
530   collaboration.

11 References

Allen, R. J., T. R. Rieger and C. J. Musante (2016). "Efficient Generation and Selection
of Virtual Populations in Quantitative Systems Pharmacology Models." CPT
Pharmacometrics Syst Pharmacol **5**(3): 140-146.

Betancourt, M. (2017) "A Conceptual Introduction to Hamiltonian Monte Carlo."
ArXiv e-prints **1701**, 60.

Conn, A. R., N. I. Gould and P. Toint (1991). "A globally convergent augmented
Lagrangian algorithm for optimization with general constraints and simple bounds."
SIAM Journal on Numerical Analysis **28**(2): 545-572.

Dorn, J. (2017). Violin Plots for plotting multiple distributions (distributionPlot.m).
https://www.mathworks.com/matlabcentral/fileexchange/23661-violin-plots-for-
plotting-multiple-distributions--distributionplot-m-, MathWorks File Exchange.

Gadkar, K., N. Budha, A. Baruch, J. D. Davis, P. Fielder and S. Ramanujan (2014). "A
Mechanistic Systems Pharmacology Model for Prediction of LDL Cholesterol
Lowering by PCSK9 Antagonism in Human Dyslipidemic Populations." CPT
Pharmacometrics Syst Pharmacol **3**: e149.

Golberg, D. E. (1989). Genetic algorithms in search, optimization, and machine
learning. Reading, MA, Addison-Wesley Publishing Co.

Hallow, K. M., A. Lo, J. Beh, M. Rodrigo, S. Ermakov, S. Friedman, H. de Leon, A.
Sarkar, Y. Xiong, R. Sarangapani, H. Schmidt, R. Webb and A. G. Kondic (2014). "A
model-based approach to investigating the pathophysiological mechanisms of
hypertension and response to antihypertensive therapies: extending the Guyton
model." AJP: Regulatory, Integrative and Comparative Physiology **306**(9): R647-
R662.

Johnson, A. (2004). error_ellipse.
http://www.mathworks.com/matlabcentral/fileexchange/4705-error-ellipse,
MathWorks File Exchange.

Jos (2016). ALLCOMB - All combinations.
https://www.mathworks.com/matlabcentral/fileexchange/10064-allcomb-
varargin-, MathWorks File Exchange.

MATLAB (2016). MATLAB and Global Optimization Toolbox Release 2016b. Natick,
Massachussetts, USA.

Musante, C. J., S. Ramanujan, B. J. Schmidt, O. G. Ghobrial, J. Lu and A. C.
Heatherington (2017). "Quantitative Systems Pharmacology: A Case for Disease
Models." Clin Pharmacol Ther **101**(1): 24-27.

NHANES. (2011-2012). "National Health and Nutrition Examination Survey
(NHANES) Data." 2011-2012. from http://www.cdc.gov/nchs/nhanes.htm.

Rieger, T. and R. Allen (2017). vpop-gen. https://doi.org/10.5281/zenodo.1117870,
Pfizer Inc.

Robert, C. P. (2015). "The Metropolis-Hastings algorithm." ArXiv e-prints **1504**:
arXiv:1504.01896.

Santoso, A., K. Phoon and S. Quek (2011). "Modified Metropolis–Hastings algorithm
with reduced chain correlation for efficient subset simulation." Probabilistic
Engineering Mechanics **26**(2): 331-341.

van de Pas, N. C. A., J. A. C. Rullmann, R. A. Woutersen, B. van Ommen, I. M. C. M.
Rietjens and A. A. de Graaf (2014). "Predicting individual responses to pravastatin
using a physiologically based kinetic model for plasma cholesterol concentrations."
Journal of Pharmacokinetics and Pharmacodynamics **41**(4): 351-362.

van de Pas, N. C. A., R. A. Woutersen, B. van Ommen, I. M. C. M. Rietjens and A. A. de
Graaf (2012). "A physiologically based in silico kinetic model predicting plasma
cholesterol concentrations in humans." The Journal of Lipid Research **53**(12): 2734-
2746.

12 Figure Captions

12.1 Flowchart of algorithm

Figure 1. Flowchart of algorithm. The initial problem setup is shared by each of the methods attempted, where biologically plausible ranges are placed on model parameters and states. Once the problem is setup, the generation of plausible patients is carried out by one of four algorithms. Post-plausible-patient generation, each algorithm follows the same acceptance/rejection sampling steps to create the virtual population.

12.2 Goodness-of-fit vs. number of plausible patients

Figure 2. Goodness-of-fit (lower number is better) of the final virtual population vs. the number of plausible patients generated for each method. Shown is mean±standard deviation of 5 runs. SA = simulated annealing (blue circles), NSA = nested simulated annealing (red squares), MH = Metropolis-Hastings (yellow diamonds), GA = genetic algorithm (purple x's).

12.3 Comparison of VP and PP generation time for each method

Figure 3. Comparison of the time/plausible patient (open bars) or time/virtual patient (filled bars) for each method. For each method, ~7,500 plausible patients were generated and then a virtual population was selected from those plausible patients. Shown is mean±standard deviation of 5 runs. Time was calculated via the functions *tic/toc* in MATLAB. SA = simulated annealing (blue), NSA = nested simulated annealing (red), MH = Metropolis-Hastings (yellow), GA = genetic algorithm (purple).

12.4 Diversity of VPs in final Vpops

Figure 4. Cumulative distribution vs. the dot-product of the vector of virtual patients' (VPs) parameters to assess the diversity of parameter values in the virtual population. For each method, 50,000 dot-products of randomly chosen VPs were calculated and the cumulative distribution plotted. Shown is mean±standard deviation of 5 runs. As a positive control, a set of parameters from a uniform distribution was generated (solid, black line). Distributions closer to the uniform random control indicate a more diverse set of VPs. Distributions skewed towards the right indicates a more uniform set of VPs. SA = simulated annealing (blue circles, solid), NSA = nested simulated annealing (red squares, dashed), MH = Metropolis-Hastings (yellow diamonds, dotted), GA = genetic algorithm (purple x's, dashed).

12.5 Efficiency of the acceptance/rejection algorithm

Figure 5. Improvement of goodness-of-fit (lower number is better) from the plausible patients (open bars) → virtual patients (filled bars) for each method starting from ~ 7,500 plausible patients. Shown is mean±standard deviation of 5

626   runs. SA = simulated annealing (blue), NSA = nested simulated annealing (red), MH
627   = Metropolis-Hastings (yellow), GA = genetic algorithm (purple).