Improving the Generation and Selection of Virtual Populations in Quantitative Systems Pharmacology Models

Theodore R. Rieger[1], Richard J. Allen[1], Lukas Bystricky[2], Yuzhou Chen[3], Glen Colopy[4], Yifan Cui[5], Angelica Gonzalez[6], Yifei Liu[7], R. D. White[8], R. A. Everett[8], H. T. Banks[8], Cynthia J. Musante[1]

[1]Internal Medicine Research Unit, Pfizer Inc, Cambridge, MA, USA
[2]Department of Computer Science, Florida State University, Tallahassee, FL, USA
[3]Department of Statistics, University of Texas-Dallas, Dallas, TX, USA
[4]Institute of Biomedical Engineering, Oxford University, Oxford, UK
[5]Department of Statistics, University of North Carolina-Chapel Hill, Chapel Hill, NC, USA
[6]Department of Mathematics, University of Arizona, Tucson, AZ, USA
[7]Department of Statistics, University of Wisconsin-Madison, Madison, WI, USA
[8]Center for Research in Scientific Computation, North Carolina State University, Raleigh, NC, USA

* Correspondence:
Theodore Rieger
ted.rieger@pfizer.com

Abstract

Quantitative systems pharmacology (QSP) models aim to mechanistically describe disease progression and predict the effects of existing therapies or novel compounds on disease biomarkers or outcomes. For most drug development applications, it is important to predict not only the mean response to the intervention but also the inter-patient variability. In addition, given the complexity of QSP models and the sparsity of relevant human data, the parameters of QSP models are often not well-determined. One approach to overcome these limitations is to develop Virtual Populations (VPops), which allow for the exploration of parametric uncertainty and reproduce the variability in response to perturbation. Here we evaluate approaches to improve the efficiency of generating VPops. We aimed to generate these populations without sacrificing diversity of the Virtual Patients' (VPs) pathophysiologies and phenotypes. To do this, we used our previously published approach (Allen, Rieger et al. 2016) together with two established algorithms (genetic algorithm and Metropolis-Hastings) as well as developing a novel approach, which we call "nested simulated annealing." Each method improved our previously-published algorithm in at least one aspect. For example, all of the methods tested required significantly fewer plausible patients (PP), the precursors to VPs, to create a reasonable VPop, but we found there may be tradeoffs in terms of parametric and phenotypic diversity of the VPs. However, the improved methodologies introduced here may be appropriate in many applications.

1 Introduction

Physiologically-based mathematical models are often used to describe and predict the response of a patient to an existing therapy or novel agent. These models, frequently referred to as quantitative systems pharmacology (QSP) models, are used to simulate clinical trials in drug development (Musante, Ramanujan et al. 2017). In these applications, it is important that they not only capture the mean patient response to treatment but also interpatient variability and how that variability may evolve over time. In addition, due to the novel nature of many therapies; the complexity of human physiology; and generally limited human data, QSP models are rarely fully determined by data. One approach to these challenges is to develop alternate parameter sets to capture the variability in the real clinical trial population and sample as much uncertainty in the model parameters as possible (Gadkar, Budha et al. 2014, Hallow, Lo et al. 2014, van de Pas, Rullmann et al. 2014).

Previously, we published an algorithm for the generation and selection of these alternative value sets (Allen, Rieger et al. 2016). The flow of the algorithm was to use simulated annealing to generate as large a population of "plausible virtual patients" as was practical. Simulated annealing was used with a given cost functional that optimized solutions to be biologically feasible. These plausible patients, and as a collection plausible population, were termed plausible since each generated parameter set simulated a patient that was physiologically reasonable, and could be in a clinical trial, but there was not yet any selection for how *likely* it was for that patient to have been in a particular clinical trial. We then used our novel selection technique to choose those patients from the plausible population that most resembled a desired clinical population. These selected patients were then termed virtual patients (VPs), and as a collection they were called a virtual population (Vpop).

Since the original algorithm created a plausible population that was naïve to the targeted virtual population distribution, significant computational effort was expended in generating spurious plausible patients outside of the target distribution. Here we propose additional algorithms to improve the generation of the plausible population for more efficient generation of the virtual population. The common extension of our previous approach in each of the tested algorithms is to use information about the target distribution in generating the plausible population. We explored this idea in three ways: (1) a novel method we have termed "nested simulated annealing" (NSA), which repeatedly targets a simulated annealing method to fill portions of the output-space at the correct frequency to approximate the target distribution; (2) a population-based global optimization approach, in this case MATLAB's genetic algorithm (GA); and lastly, (3) an important-sampling technique, which for this application we chose the Metropolis-Hastings (MH) method (Figure 1). We also re-simulated the original method, which uses simulated annealing, for direct comparison to the three new approaches.

2 Methods

The focus of this paper is the evaluation of three approaches for the generation of virtual populations that match empirical distributions of clinical cohorts or populations. This section is organized to describe these three methods (NSA- nested simulated annealing, GA- modified genetic algorithm, and MH- modified Metropolis-Hastings), and how to apply them to generate virtual patients (VPs). This is followed by a description of how the results were analyzed, including a novel metric for assessing the uniqueness of a collection of parameter sets.

2.1 Mathematical Model and Data

Following our previous approach, we test our proposed methods using a publicly-available lipoprotein metabolism model (van de Pas, Woutersen et al. 2012) and clinical data from the National Health and Nutrition Examination Survey (NHANES 2011-2012). In brief, the van de Pas model is a model of cholesterol production by the liver and its transit through the plasma. The focus of the model is on calculating dynamic changes to high-density lipoprotein cholesterol (HDL$_c$) and "non-high-density lipoprotein cholesterol", which we assume to be equivalent to low-density lipoprotein cholesterol (LDL$_c$). The goal of this paper is to assess the model's ability to generate physiologically reasonable patients at baseline (i.e., at steady state, before the application of cholesterol therapies). We compare the distributions of LDLc, HDLc, and total cholesterol (TC, or LDL$_c$+ HDL$_c$) in our PPs and VPs to the multivariate distributions available in the NHANES database.

2.2 Nested Simulated Annealing

The nested simulated annealing (NSA) approach is a novel method we developed to use information about the target data distribution in the process of generating the plausible population. Previously we optimized the steady-state solutions, x^*, to within biologically reasonable ranges rather than to a specific point using the following cost functional

$$g(\boldsymbol{p}) = \sum_{i=1}^{N} \max\left[\left(x_i^*(\boldsymbol{p}) - \frac{l_i+u_i}{2}\right)^2 - \left(\frac{u_i}{2} - \frac{l_i}{2}\right)^2, 0\right], \qquad (1)$$

where N is the number of states, and l_i and u_i represent the biologically reasonable lower and upper bounds for the i^{th} state variable's steady-state solution. Note that if $x_i^*(\boldsymbol{p})$ is within the biological bounds, then $g(\boldsymbol{p}) = 0$, and the parameter set $\boldsymbol{p}$ is called a plausible patient. This optimization is repeated until a plausible population is created.

Here we modified the cost functional, equation (1), in order to include information about the desired distribution, thus decreasing the number of plausible patients required per VP. Since the NHANES data is well approximated by a multivariate log-

normal distribution, which is roughly an ellipsoidal space, we modified the
hypercube to an ellipsoidal shape, in the dimensions for which we have data, that
encapsulates the data (with the most extreme data being on the surface of the
ellipse). However, an immediate problem with this approach was points at the edge
of the ellipse were accepted and generated as frequently as those near the centroid
of the data. Hence, to fully use information from the target distribution, we
considered multiple ellipsoids nested within one another such that we can control
the number of plausible patients generated in each ellipse.

Note that while biological upper and lower bounds exist for all of the nine model
outputs, we only have distributional information regarding LDL_C, HDL_C, and TC. As a
result, it is necessary to still minimize the original cost functional (1) for the
remaining six dimensions to ensure the optimized parameter sets do not produce
biologically implausible solutions.

We use the following equation for the contour of an ellipsoid that will encompass
the data:

$$(\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) = c^2, \quad (2)$$

where $\boldsymbol{X}$ is a 3 × 1 vector representing a point in the log-scaled observable space, $\boldsymbol{\mu}$
and Σ are maximum likelihood estimation of the mean and covariance matrix of the
multivariate normal distribution, and c^2 controls the size of the ellipsoid. By letting
$\boldsymbol{X}$ be the data point furthest from the mean in (2), we can explicitly calculate the
minimum value for c^2 that allows the data to be encompassed by the ellipsoid.

First consider only one ellipsoid region. Then the modified cost functional is

$$h(\boldsymbol{p}) = g(\boldsymbol{p}) - \gamma((\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) - c^2), \quad (3)$$

where $g(\boldsymbol{p})$ is given by equation (1) for N = 6, and is calculated for the 6 state
variables for which we do not have distributional information. We can interpret this
cost functional as forcing these 6 state variables to be within plausible biological
bounds while forcing the remaining 3 log-scaled observables to be within the
smallest ellipsoid region that encompasses the clinical data. Notice we have an
additional parameter, γ, which is simply a scaling factor that is a free parameter of
the method.

Now consider several nested ellipsoid regions. The cost functional for each nested
ellipsoid is given in (3) but with modified c^2 values in order to control the
distribution of the plausible population. The number of nested ellipsoids, R, is
another free parameter of this method. Denote the ellipsoids as $E_1 \subset E_2 \subset \cdots \subset E_R$,
with the k^{th} ellipsoid centered at the mean $\boldsymbol{\mu}$ and defined as $E_k = \{\boldsymbol{X} :$ $(\boldsymbol{X} -$
$\boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) \leq c_k^2\}$.

We choose the c_k values such there is a k/R probability of the data being observed
within the k^{th} ellipse:

$$\int_{E_k} \Phi(x)dx = \frac{k}{R} \quad , \qquad (4)$$

160 where $\Phi(x)$ is the multivariate normal distribution, and $k = 1 \ldots R$. We find an
161 approximate solution, c_k , to this integral, by using a Monte Carlo approach.
162 Equivalently,

$$\int_{E_1} \Phi(x)dx = \frac{1}{R} \qquad (5)$$

$$\int_{E_k \backslash E_{k-1}} \Phi(x)dx = \frac{1}{R}. \quad (6)$$

For this method, we are going to populate each ellipsoid such that the proportion of
plausible patients within each ellipsoid matches the target distribution. We
therefore need to calculate how many plausible patients are required for each
ellipsoid, given a desired total number of plausible patients. Define q_k as the
proportion of the total plausible population within the k^{th} ellipsoid. Then, since we
assume the observables are approximately uniformly distributed throughout each
ellipsoid, we want to solve a system of R equations for each q_k obtained by solving

$$\frac{1}{R} = \sum_{k=j}^{R} \frac{V_j - V_{j-1}}{V_k} q_k, \qquad (7)$$

174 for $j = 1, \ldots, R$. Where V_j is the volume of the j^{th} ellipse. We define $V_0 = 0$. Note that
175 $V_j \propto c_j^n$, where n is the dimension of the multi-dimensional distribution. Then,
176 equation (7) can be re-written as

$$\frac{1}{R} = \sum_{k=j}^{R} \frac{c_j^n - c_{j-1}^n}{c_k^n} q_k, \qquad (8)$$

which can be solved recursively for the q_k (starting with $k = R$, and defining $c_0^n =$
0).

Alternatively, since the NHANES data provided individual level data, the target
distributions c_k (and q_k) were calculated empirically (see code, Supplementary
Materials).

With the ellipses defined we can generate the plausible population by randomly
generating a parameter set in the ranges we defined from a uniform distribution.
Then, for a plausible population of size m, for $l = 1$ to m, we optimize from our
initial parameter estimate to our final plausible patient via minimizing

187
$$h_k(\boldsymbol{p}) = g(\boldsymbol{p}) - \gamma((\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu}) - c_k^2), \quad (9)$$

where $g(\boldsymbol{p})$ is given by equation (1) for N = 6, and is calculated for the 6 state
variables for which we do not have distributional information.

This method requires choosing the number of nested ellipsoids. The greater the
number of ellipsoids, the closer the distribution of the plausible population will
match that of the clinical population, thus reducing the number of plausible patients
required per virtual patient. However, an increase in the number of ellipsoids
increases computation time for the plausible population. We then use rejection
sampling to select the virtual patients from the plausible population.

2.3   Modified Genetic Algorithm

A commonly used population-based approach for optimizing nonlinear models is a
genetic algorithm (GA), (Golberg 1989, Conn, Gould et al. 1991). For our problem,
we created our plausible population using MATLAB's *ga* function (MATLAB 2016).
This algorithm first creates an initial population, where each patient is generated
from a uniform distribution bounded by biologically reasonable values. The
algorithm then assigns a fitness value to each patient using a cost (fitness)
functional. Similar to the nested simulated annealing methods, we modify equation
(1) by incorporating information about the desired distribution. Specifically, the
cost functional is given by

206
$$H(\boldsymbol{p}) = \left\{ \begin{array}{ll} g(\boldsymbol{p}) & \text{if } g(\boldsymbol{p}) > 0 \\ -\gamma(\boldsymbol{p}) & \text{otherwise,} \end{array} \right. \quad (10)$$

207   where $\gamma(\boldsymbol{p})$ is the likelihood of a given log-scaled observable value $\boldsymbol{X}$ given by

208
$$\gamma(\boldsymbol{p}) = \frac{1}{\sqrt{(2\pi)^3 |\Sigma|}} \exp\left(-\frac{1}{2}(\boldsymbol{X} - \boldsymbol{\mu})^T \Sigma^{-1} (\boldsymbol{X} - \boldsymbol{\mu})\right). \quad (11)$$

This cost functional can be interpreted as forcing all state variables to be within
plausible biological bounds and additionally assessing a penalty as the log-scaled
observables deviate from $\boldsymbol{\mu}$.

In implementing this algorithm, we start with an initial population of individuals,
where each individual is created by random selection of parameter values from a
uniform distribution with biologically-reasonable bounds. As the algorithm
progresses, children are created for each generation; those with a cost functional
value $H(\boldsymbol{p}) < 0$ become plausible patients. Since many plausible patients are
created each generation, there is no way to specify the exact number of plausible
patients generated. Thus we must preset the minimum number of plausible patients
desired, but in practice we tended to generate slightly more than sought (see
Supplementary Code). Once the plausible population is created, we follow the
remaining steps in Allen et al. and use rejection sampling to determine the virtual

population from the plausible population.

2.4 Modified Metropolis-Hastings

First, recall the original Metropolis-Hasting (MH) algorithm to approximate a
desired distribution, for a review see for example (Robert 2015). Let $\pi(\boldsymbol{p})$ be our
desired target multivariate probability distribution for the vector $\boldsymbol{p}$ (in this case $\boldsymbol{p}$ is
a parameter set of the model). The MH algorithm generates a sequence of $\boldsymbol{p}$, such
that the distribution of this sequence, $\{\boldsymbol{p_0}, \dots, \boldsymbol{p_N}\}$ converges to $\pi(\boldsymbol{p})$ as $N \to \infty$. Let
$Q(\boldsymbol{p}, \boldsymbol{q})$ be some symmetric proposal distribution, which is interpreted as
generating a proposed value $\boldsymbol{q}$ from $Q(\boldsymbol{p}, \boldsymbol{q})$ when the process is at value $\mathbf{p}$. Then the
original Metropolis Hastings algorithm is as follows:

1. Generate an initial vector $\boldsymbol{p_0}$, set $i = 1$.
2. Generate a proposed vector $\boldsymbol{p}^* \sim Q(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*)$.
3. Calculate the probability $\boldsymbol{p}^*$ is accepted, $\alpha = \min\left(1, \frac{\pi(\boldsymbol{p}^*)}{\pi(\boldsymbol{p_{i-1}})}\right)$.
4. Generate $y \sim U(0,1)$, if $y \leq \alpha$, set $\boldsymbol{p_i} = \boldsymbol{p}^*$. If $y > \alpha$, set $\boldsymbol{p_i} = \boldsymbol{p_{i-1}}$.
5. Repeat steps 2 to 4 for $i = 1, \dots, N$ to collect $\{\boldsymbol{p_0}, \dots, \boldsymbol{p_N}\}$ as a sampling from
the target distribution.

This MH algorithm approximates the target distribution $\pi(\boldsymbol{p})$ by randomly sampling
from it. At first glance, this approach appears immediately applicable to the problem
at hand and will generate a plausible population that will converge to the virtual
population as $N \to \infty$. However, this algorithm requires modification because we do
not know $\pi(\boldsymbol{p})$ $a\ priori$; i.e., we do not know how the parameters sets should be
distributed such that the model, when simulated using those parameters, matches
the data.

We rewrite our target distribution as $T(\boldsymbol{X_p})$, where $\boldsymbol{X}$ is the observable outcomes
generated by the model M, using a parameter set (which in this case is in the log-
space, so $\boldsymbol{X_p} = \log M(\boldsymbol{p})$). Then our algorithm becomes

1. Generate an initial vector $\boldsymbol{p_0}$, set $i = 1$.
2. Generate a proposed vector $\boldsymbol{p}^* \sim Q(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*)$, write $Q_m(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*) =$
$M(Q(\boldsymbol{p_{i-1}}, \boldsymbol{p}^*))$.
3. Calculate the probability $\boldsymbol{p}^*$ is accepted, $\alpha = \min\left(1, \frac{T(X_{\boldsymbol{p}^*})Q_m(\boldsymbol{p}^*,\boldsymbol{p}_{i-1})}{T(X_{\boldsymbol{p}_{i-1}})Q_m(\boldsymbol{p}_{i-1},\boldsymbol{p}^*)}\right)$,
assume $\alpha \sim \min\left(1, \frac{T(X_{\boldsymbol{p}^*})}{T(X_{\boldsymbol{p}_{i-1}})}\right)$.
4. Generate $y \sim U(0,1)$, if $y \leq \alpha$, set $\boldsymbol{p_i} = \boldsymbol{p}^*$. If $y > \alpha$, set $\boldsymbol{p_i} = \boldsymbol{p_{i-1}}$.
5. Repeat steps 2 to 4 for $i = 1, \dots, N$ to collect $\{\boldsymbol{p_1}, \dots, \boldsymbol{p_N}\}$ as a sampling from
the target distribution.

In the canonical version of the MH algorithm α is independent of the proposal
distribution Q because it is symmetric and cancels out of the equation. In the
modified version above, Q_m is unknown and, in fact, is unlikely to be symmetric. In
order to proceed we assume that Q_m is approximately symmetric
$Q_m(\boldsymbol{p}^*, \boldsymbol{p}_{i-1}) \sim Q_m(\boldsymbol{p}_{i-1}, \boldsymbol{p}^*)$, so that we can calculate α as above. Because of this
approximation it is still necessary, following our previously published algorithm, to
apply acceptance-rejection sampling to determine the virtual population from the
plausible population.

2.5 Assessing Similarity Between Virtual Patients

It is desirable to examine the parameter space in the virtual population to ensure
heterogeneity of the virtual patients (while still reproducing available data). In our
method this was previously ensured by generating VPs independently and from
different initial parameter estimates. However, this is not necessarily the case for
the GA and MH methods.

To assess the diversity of a virtual population we devised a test metric $d(\boldsymbol{p}_i, \boldsymbol{p}_j)$
which scores how similar two VPs are. By bootstrapping sampling pairs of VPs from
a given virtual population, we built up a distribution for d and could compare the
resultant cumulative density function (CDF) for each method. The test metric d is
simply the normalized dot-product of $\boldsymbol{p}_i$ and $\boldsymbol{p}_j$ after they are scaled and shifted:

$$
d(\boldsymbol{p}_i, \boldsymbol{p}_j) = \frac{\widehat{\boldsymbol{p}}_i \cdot \widehat{\boldsymbol{p}}_j}{|\widehat{\boldsymbol{p}}_i||\widehat{\boldsymbol{p}}_j|}
$$
275
$$
\widehat{\boldsymbol{p}} = \mathbf{diag}(V^{-1}(\boldsymbol{p} - \boldsymbol{l})) - \frac{1}{2} \quad (12)
$$

where V is a diagonal matrix such that $\boldsymbol{v}_{ii} = \boldsymbol{u}_i - \boldsymbol{l}_i$. Hence, $\mathbf{diag}(V^{-1}(\boldsymbol{p} - \boldsymbol{l}))$ uses
the defined upper and lower bound for each parameter (the elements of $\boldsymbol{u}$ and $\boldsymbol{l}$
respectively), to scale each parameter in $\boldsymbol{p}$ to be between 0 and 1. To ensure that
$d \in [-1,1]$ we further subtract ½ from each element. This means that, in principle,
$\widehat{\boldsymbol{p}}$ can be orientated in any direction in m-dimensional space (where m is the
number of parameters). This also means that if the elements of $\boldsymbol{p}$ are sampled
uniformly between the upper and lower bounds that, by symmetry, the expected
value of the distribution should be zero (i.e., the CDF crosses 0.5 at $d = 0$). This is
the optimal parameter set in terms of diversity, but may not be achievable given the
constraints applied to the model. Conversely, if we generate virtual populations
from very similar parameter sets then the distribution will be right-shifted towards
d=1.

2.6 Assessing Goodness of Fit

289 The goodness of fit (GoF) to the empirical target distribution was assessed by using
290 the Kolmogorov-Smirnov statistic for each marginal distribution in one dimension:

291
$$\mathrm{GoF} = \sum \sup |F_i(x) - D_i(x)| \qquad (13)$$

292 where $F_i(x)$ is the empirical cumulative distribution function for the i^{th} model
293 observable that we are fitting the observed cumulative distribution of the data,
294 $D_i(x)$. Note that for a perfect fit GoF=0, and that GoF $[0, n]$, where n is the number of
295 distributions being fitted.

2.7   Source code
297 All algorithms were implemented in MATLAB 2016b (v9.1.0.441655) using the
298 Global Optimization Toolbox (v3.4.1) where a pre-packaged routine was available
299 (e.g., GA, SA). The ODE model was implemented in SimBiology (v5.5). The K-S Test
300 for GoF utilizes MATLAB's Statistics and Machine Learning Toolbox (v11.0). The full
301 source code is available for download from a GitHub repository (Rieger 2017).
302
303 All simulations were performed sequentially on a MacBook Pro with an Intel Core i7
304 2.9 GHz processor and 16 GB of RAM.

3   Results
3.1   Comparing the various algorithms

To compare the three proposed algorithms (NSA, GA and MH) we evaluated four
metrics to measure performance of the algorithm compared to the original
simulated annealing method. For each algorithm, we evaluated:

1. **Efficiency:** How many PPs were needed to achieve a certain GoF of the final
Vpop to the observables?
2. **Computational Cost:** How fast was the generation of PPs and VPs?
3. **Diversity:** Are the VPs parametrically similar or do they maintain the
parametric heterogeneity of the PPs?
4. **Convergence**: Do the methods benefit from the acceptance/rejection step or
can a VPop be generated directly?

3.2   Comparison of algorithms for efficiency of yield

For each algorithm, we targeted generation of between 100 and 10,000 total PPs;
those PPs were then converted into VPs through the acceptance/rejection
algorithm. The GoF of the resulting VPop was calculated as discussed in Methods. By
comparing the GoF achieved for the VPops with varying PPs (Figure 2) we find that
as the number of PPs→10,000+, all of the algorithms generated essentially
indistinguishable GoFs for the final VPop (albeit with different VPs in each VPop).
However, the three new algorithms were more efficient than the original SA method,
especially when the number of PPs < 1,000. In fact, VPops generated with as few as
100 PPs could have similar fits to the observable data as the SA method with 500+
PPs.

3.3 Comparison of algorithms for computational cost

Even if an algorithm can generate the same GoF through far fewer PPs than the original SA algorithm, this does not necessarily mean the process was computationally more efficient. We further compared each method based on the clock time (evaluated via MATLAB's *tic/toc* functions) required to generate a VPop from 10,000 plausible patients (Figure 3). While the NSA method was arguably superior based on yield, this algorithm required approximately the same amount of time to execute as the SA method. Based on time, the MH and GA were the fastest algorithms and the SA remains among the least efficient.

3.4 Comparison of algorithms for parametric diversity of the final virtual population

An advantage of the SA algorithm is its ability to generate VPops that maintain most of the parametric diversity of the original PPs (Supplementary Figure S1-2). This diversity in the VPop is an essential feature for QSP models since they are often utilized in simulation of clinical trials involving novel therapies. If the underlying parameters of VPs are highly similar/correlated, clinical trial simulations performed with the VPop may incorrectly predict a very narrow range of therapeutic response. Therefore, we need to ensure that as we introduce new algorithms, we do not trade parametric diversity for computational gains. We measured the diversity of the VPops generated by each algorithm by uniformly sampling pairs of VPs and calculating the dot product between each set of parameters (see Methods). As a reference point, we included a set of uniformly, randomly generated model parameters (Figure 4). The closer each algorithm's final VP parameter distribution is to the random reference, the more diverse we considered the set of VPs in the Vpop. For this criterion, the SA method was found to have the most diversity, closely followed by NSA and MH. The GA method showed distinct rightward shifts in its distribution, indicating that fewer independent parameter sets were identified in the generation of the VPops. Supplementary figures show the violin plot for each method for both the PPs and VPs (Figures S2, S4, S6, and S8).

3.5 Convergence of the algorithms to the data

In contrast to the original SA method, each of the methods tested use information about the desired population distribution and thus requires fewer plausible patients to achieve an acceptable fit for the VPop (Figure 2). To evaluate if the final selection step was still required as part of the algorithm workflow, we compared the GoF for each of the methods before and after the acceptance/rejection step, starting with ~10,000 PPs in each case (Figure 5). As expected, the largest improvement in VPop fit from the PPs to VPs was for the SA method; however, all of the methods showed at least a 3-fold improvement in GoF through the final selection step. The NSA method showed the best initial fit for its plausible patients to the NHANES data, reasonably reproducing both the 1-dimensional and 2-dimensional histograms

368 before the selection step (Figure S3A-F). These fits were approximately equivalent
369 to the final VPop fit for the SA method starting with 1,000 PPs.

4 Discussion

By design, most quantitative systems pharmacology models are not identifiable
from available data. While it would be desirable to have parameters well
determined and characterized, the uncertainty in parameter values in QSP models
often reflects our current knowledge (or lack thereof) of human (patho)-physiology.
Therefore, with this perspective, we can use these models in a hypothesis-
generation/testing mode to explore how these knowledge gaps translate to
uncertainties in clinical outcomes and clinical trial design. In our opinion, the most
thorough and robust way of doing this is by generating the most diverse virtual
populations given the available data.

Exploring the parameter space of under-determined quantitative systems
pharmacology models remains a challenge but it is essential for safety and efficacy
predictions for novel compounds. Here we presented three methods for generating
diverse parameter sets in a QSP model. While this exercise is by no means an
exhaustive exploration of global optimization techniques, each algorithm improved
at least one of the testing metrics compared to our previously published SA method.
The seemingly simple question of which method is "the best" cannot be definitively
answered here but it is important to be aware of the pros and cons for each and
potential steps to improve performance.

We have previously discussed the advantages and disadvantages of using the SA
method for this application (Allen, Rieger et al. 2016). In comparison to other
methods tested it was the slowest (or tied with NSA), required the most plausible
patients for a quality fit but on the plus side it also generated the most (or tied with
NSA) diverse virtual population with the fewest imposed correlations. The ease of
implementation was also an advantage for SA. As implemented, the algorithm
required no prior knowledge of the final virtual population distribution and there
was a minimal set of tuning parameters required, most of which were default
MATLAB options (i.e., no arbitrary decision about number of ellipses, number of
generations). As such, the algorithm remains relevant as a "first try" for generating
VPs. Furthermore, it is the only method that can be run (at least in part) without
prior knowledge of the target distribution. This relaxed requirement can make it an
attractive choice for pre-computing plausible populations or for exploring how the
parameter space relates to the model output (for example, identifying parameters in
the model that can give rise to sub-populations of interest).

The NSA approach iterates on the SA method by utilizing prior knowledge of the
final parameter distribution and forcing the algorithm to regions with the most
desired patient density. This method is likely most efficient when the target
distribution is approximately ellipse-shaped. Fortunately, for the example here, the

target distribution was well approximated as a multivariate lognormal. The viability
of this method for more eccentric or bimodal distributions would need to be studied
by applying it to other case studies. However, such distributions are less commonly
observed in clinical trials. For our case study, the computational cost to generate a
plausible population was comparable between the NSA and SA methods; however,
the NSA approach demonstrated vastly improved yield (VP per PP), which
facilitated an overall more efficient VPop generation process. The algorithm was as
good, or better, than the other methods tested for direct generation (pre-
selection/rejection) of a reasonable Vpop, without the imposed correlations found
in VPops generated by GA. While essentially the same as the SA method to
implement, there is a problem-specific choice for the number of ellipses to use. Here
we used five regions, regardless of the number of plausible patients being
generated. Fine-tuning based on the model/number of plausible patients may
potentially improve performance.

Metropolis-Hastings is unique amongst the approaches we tried in that it is a
Markov Chain, which should imply some degree of correlation between the
plausible patients. The advantage of this technique was an increase in speed and
compared to the two methods based on SA; however, there also was a right-shift in
the dot product cumulative distribution, implying a slightly less diverse final
population. Methods have been published to attempt to reduce this correlation
(Santoso, Phoon et al. 2011) and to improve performance in higher dimensions
(Betancourt 2017), but we chose to evaluate only the common form of the algorithm
and to leave further exploration for future improvements. While straightforward to
implement, MH requires the choice of a proposal distribution. As noted in the
Methods, because we indirectly sample the distribution of the observables by first
sampling the parameter space and then generate the observables through model
simulation we do not have direct control over the choice of a proposal distribution.
The implications of this for direct convergence of this method will depend on the
symmetry of the observable distribution (induced by the parameter sampling)
around every point on the Markov chain. In this case, the approximation we
assumed (see Methods) appeared to hold sufficiently for the MH algorithm to
approximate the empirical distributions. However, the final Vpop was improved by
acceptance/rejection sampling.

The genetic algorithm was very similar to MH in that, compared to the SA-based
methods, a 10-fold improvement in computational speed was achieved at the cost of
some lost heterogeneity in the final virtual population. The GA is easy to implement
for QSP models and the supplied routine with MATLAB's Global Optimization
Toolbox was sufficient for our purposes. GA requires some problem-specific
decisions, which may affect overall performance; for example, the size of the
population, number of generations, and mutation rate can be adjusted as needed.

The curse of under-determined models has led to a long history of using different
global optimization techniques for generating parameter sets within the bounds of
the data (van de Pas, Woutersen et al. 2012, Gadkar, Budha et al. 2014, Hallow, Lo et

al. 2014). Use of global optimization techniques often feels like more of an art than a
science due to how problem-specific their application can be. For this reason, we
examined several algorithms with different approaches for exploring constrained,
multidimensional parameter spaces. Requiring only minimal tuning, each of these
algorithms successfully explored the range of our 23-dimensional parameter space
and generated reasonable PPs. The choice of algorithm to use for a new problem,
particularly one with higher dimensions and a less Gaussian set of observations, will
need to be evaluated on a case-by-case basis. For example, for models that are slow
to simulate the most constraining factor is computational cost. In this case the MH
or GA approaches may be the most successful; however, as we have shown, without
adaptation these methods come at a cost of diversity in the final Vpop.

We hope that the results presented here will provide a guide to selection and
implementation of these algorithms to facilitate the generation of robust Vpops in
mathematical models of (patho)-physiology.

5 Abbreviations

GA – Genetic Algorithm
GoF – Goodness of Fit
MH – Metropolis-Hastings
NSA – Nested Simulated Annealing
SA – Simulated Annealing
PP – Plausible Patient
VP – Virtual Patient
VPop – Virtual Population

6 Author contributions

475 RA conceived of the original algorithm. CM, RA, and TR conceived of the updated
476 algorithm objectives. AG, GC, LB, RW, YC1, YC2, and YL selected and coded the new
477 algorithms and performed the initial proof-of-concept testing. CM, RE, HB, RA, and
478 TR supervised and advised the initial work. RA, RE, RW, TR, HB, and CM drafted the
479 manuscript. All authors reviewed, revised, and approved of the final manuscript.

7 Conflict of interest

481 TRR, RJA, and CJM were employees of Pfizer Inc. during the completion and
482 analysis of this study.

8 Funding

484 This research was supported in part by the National Institute on Alcohol Abuse and
485 Alcoholism under grant number 1R01AA022714-01A1, in part by the Air Force
486 Office of Scientific Research under grant number AFOSR FA9550-15-1-0298, and in
487 part by the US Department of Education Graduate Assistance in Areas of National
488 Need (GAANN) under grant number P200A120047.

9 Acknowledgements

492 The authors thank Ilse Ipsen and Thomas Gehrmann for organizing the 2016 SAMSI
493 Workshop at North Carolina State University, which initially facilitated this
494 collaboration.

10 References

Allen, R. J., T. R. Rieger and C. J. Musante (2016). "Efficient Generation and Selection
of Virtual Populations in Quantitative Systems Pharmacology Models." CPT
Pharmacometrics Syst Pharmacol **5**(3): 140-146.

Betancourt, M. (2017) "A Conceptual Introduction to Hamiltonian Monte Carlo."
ArXiv e-prints **1701**, 60.

Conn, A. R., N. I. Gould and P. Toint (1991). "A globally convergent augmented
Lagrangian algorithm for optimization with general constraints and simple bounds."
SIAM Journal on Numerical Analysis **28**(2): 545-572.

Gadkar, K., N. Budha, A. Baruch, J. D. Davis, P. Fielder and S. Ramanujan (2014). "A
Mechanistic Systems Pharmacology Model for Prediction of LDL Cholesterol
Lowering by PCSK9 Antagonism in Human Dyslipidemic Populations." CPT
Pharmacometrics Syst Pharmacol **3**: e149.

Golberg, D. E. (1989). Genetic algorithms in search, optimization, and machine
learning. Reading, MA, Addison-Wesley Publishing Co.

Hallow, K. M., A. Lo, J. Beh, M. Rodrigo, S. Ermakov, S. Friedman, H. de Leon, A.
Sarkar, Y. Xiong, R. Sarangapani, H. Schmidt, R. Webb and A. G. Kondic (2014). "A
model-based approach to investigating the pathophysiological mechanisms of
hypertension and response to antihypertensive therapies: extending the Guyton
model." AJP: Regulatory, Integrative and Comparative Physiology **306**(9): R647-
R662.

MATLAB (2016). MATLAB and Global Optimization Toolbox Release 2016b. Natick,
Massachussetts, USA.

Musante, C. J., S. Ramanujan, B. J. Schmidt, O. G. Ghobrial, J. Lu and A. C.
Heatherington (2017). "Quantitative Systems Pharmacology: A Case for Disease
Models." Clin Pharmacol Ther **101**(1): 24-27.

NHANES. (2011-2012). "National Health and Nutrition Examination Survey
(NHANES) Data." 2011-2012. from http://www.cdc.gov/nchs/nhanes.htm.

Rieger, T. (2017). "Source code repository for vpop-gen, code for evaluating
methods to fit virtual populations." from https://zenodo.org/record/999552.

Robert, C. P. (2015). "The Metropolis-Hastings algorithm." ArXiv e-prints **1504**:
arXiv:1504.01896.

Santoso, A., K. Phoon and S. Quek (2011). "Modified Metropolis–Hastings algorithm
with reduced chain correlation for efficient subset simulation." Probabilistic
Engineering Mechanics **26**(2): 331-341.

van de Pas, N. C. A., J. A. C. Rullmann, R. A. Woutersen, B. van Ommen, I. M. C. M.
Rietjens and A. A. de Graaf (2014). "Predicting individual responses to pravastatin
using a physiologically based kinetic model for plasma cholesterol concentrations."
Journal of Pharmacokinetics and Pharmacodynamics **41**(4): 351-362.

van de Pas, N. C. A., R. A. Woutersen, B. van Ommen, I. M. C. M. Rietjens and A. A. de
Graaf (2012). "A physiologically based in silico kinetic model predicting plasma
cholesterol concentrations in humans." The Journal of Lipid Research **53**(12): 2734-
2746.

11 Figures

11.1 Flowchart of algorithm

542
543
Figure 1. Flowchart of algorithm. The initial problem setup is shared by each of the
methods attempted, where biologically plausible ranges are placed on model
parameters and states. Once the problem is setup, the generation of plausible
patients is carried out by one of four algorithms. Post-plausible patient generation,
each algorithm follows the same acceptance/rejection sampling steps to create the
virtual population.
550
551

552   **11.2 Goodness-of-fit vs. number of plausible patients**
553

554
555
556   Figure 2. Goodness-of-fit (lower number is better) of the final virtual population vs.
557   the number of plausible patients generated for each method. SA = simulated
558   annealing (blue circles), NSA = nested simulated annealing (red squares), MH =
559   Metropolis-Hastings (yellow diamonds), GA = genetic algorithm (purple x's).
560
561

11.3 Comparison of VP and PP generation time for each method

564
565
Figure 3. Comparison of the time/plausible patient (open bars) or time/virtual
patient (filled bars) for each method. For each method, ~10,000 plausible patients
were generated and then a virtual population was selected from those plausible
patients. Time was calculated via the functions *tic/toc* in MATLAB. SA = simulated
annealing (blue), NSA = nested simulated annealing (red), MH = Metropolis-
Hastings (yellow), GA = genetic algorithm (purple).
572
573

11.4 Diversity of VPs in final Vpops

Figure 4. Cumulative distribution vs. the dot-product of the vector of virtual patients' (VPs) parameters to assess the diversity of parameter values in the virtual population. For each method, 10,000 dot-products of randomly chosen VPs were calculated and the cumulative distribution plotted. As a positive control, a set of parameters from a uniform distribution was generated (solid, black line). Distributions closer to the uniform random control indicate a more diverse set of VPs. Distributions skewed towards the right indicates a more uniform set of VPs. SA = simulated annealing (blue circles, solid), NSA = nested simulated annealing (red squares, dashed), MH = Metropolis-Hastings (yello diamonds, dotted), GA = genetic algorithm (purple x's, dashed).

589 ## 11.5 Efficiency of the acceptance/rejection algorithm
590

591
592
593 Figure 5. Improvement of goodness-of-fit (lower number is better) from the
594 plausible patients (open bars) → virtual patients (filled bars) for each method
595 starting from ~ 10,000 plausible patients. SA = simulated annealing (blue), NSA =
596 nested simulated annealing (red), MH = Metropolis-Hastings (yellow), GA = genetic
597 algorithm (purple).
598
599
600
601