Predicting Geographic Location from Genetic Variation with Deep Neural Networks

C.J. Battey[1], Peter L. Ralph[1], and Andrew D. Kern[1]

[1]University of Oregon Institute of Ecology and Evolution

May 15, 2020

Abstract

Most organisms are more closely related to nearby than distant members of their species, creating spatial autocorrelations in genetic data. This allows us to predict the location of origin of a genetic sample by comparing it to a set of samples of known geographic origin. Here we describe a deep learning method, which we call `Locator`, to accomplish this task faster and more accurately than existing approaches. In simulations, `Locator` infers sample location to within 4.1 generations of dispersal and runs at least an order of magnitude faster than a recent model-based approach. We leverage `Locator`'s computational efficiency to predict locations separately in windows across the genome, which allows us to both quantify uncertainty and describe the mosaic ancestry and patterns of geographic mixing that characterize many populations. Applied to whole-genome sequence data from *Plasmodium* parasites, *Anopheles* mosquitoes, and global human populations, this approach yields median test errors of 16.9km, 5.7km, and 85km, respectively.

Introduction

In natural populations, local mate selection and dispersal create correlations between geographic location and genetic variation – each individual's genome is a mosaic of material inherited from recent ancestors that are usually geographically nearby. Given a set of genotyped individuals of known geographic provenance, it is therefore possible to predict the location of new samples from genetic information alone (Guillot et al., 2015; Yang et al., 2012; Wasser et al., 2004; Rañola et al., 2014; Bhaskar et al., 2016; Baran et al., 2013). This task has forensic applications – for example, estimating the location of trafficked elephant ivory as in Wasser et al. (2004) – and also offers a way to analyze variation in geographic ancestry without assuming the existence of discrete ancestral populations.

The most common approaches to estimating sample locations are based on unsupervised genotype clustering or dimensionality reduction techniques. Genetic data from samples of both known and unknown origin are jointly analyzed, and unknown samples are assigned to the location of known individuals with which they share a genotype cluster or region of PC space (Breidenbach et al., 2019; Battey et al., 2018; Cong et al., 2019). However, these methods require an additional mapping from genotype clusters or PC space to geography, and can produce nonsensical results if unknown samples are hybrids or do not originate from any of the sampled reference populations.

Existing methods for estimating sample location that explicitly model continuous landscapes use a two-step procedure. A smoothed map describing variation in allele frequencies over space

is first estimated for each allele based on the genotypes of individuals with known locations, and locations of new samples are then predicted by maximizing the likelihood of observing a given combination of alleles at the predicted location. In methods like SPASIBA (Guillot et al., 2015) and SCAT (Wasser et al., 2004), allele frequency surfaces are estimated by fitting parameters of a Gaussian function of set form (but see Rañola et al. (2014) for an alternate approach based on smoothing techniques from image analysis).

Since all such methods use relatedness to other contemporary samples, any information about the location of a new sample necessarily comes from ancestors shared with the reference set. As illustrated in Figure 1, we expect *a priori*, that the genealogical relationships among a set of samples (and therefore the spatial location of ancestors) will vary along the genome. This means that a complete look at geographic ancestry would include not just a point estimate of spatial location, but an estimate of uncertainty that accounts for the partially correlated genealogies of recombining chromosomes.

In the past few years there has been a explosion in the use of supervised machine learning for population genetics for a number of tasks, including detecting selection (Schrider and Kern, 2016; Mughal and DeGiorgio, 2018; Sugden et al., 2018), inferring admixture (Schrider et al., 2018; Durvasula and Sankararaman, 2019), and performing demographic model selection (Pudlo et al., 2015; Villanea and Schraiber, 2019). Applications to population genetics increasingly make use of the latest generation of machine learning tools: deep neural networks (a.k.a. "deep learning") (Sheehan and Song, 2016; Kern and Schrider, 2018; Chan et al., 2018; Flagel et al., 2018; Adrion et al., 2020). A significant feature of neural networks is that they allow the input of raw genotype information, as we perform below, without initial compression into summary statistics.

In this paper, we introduce `Locator`, a highly efficient deep learning method for the prediction of geographic origin of individuals from unphased genotype data. `Locator` uses deep neural networks to perform prediction directly from genotypes, but without assuming any explicit model of how genotypes vary over the landscape. Moreover, unlike many modern supervised machine learning methods in population genetics, (e.g., Kern and Schrider, 2018) our training set need not be obtained via simulation. We assume only that there is some function relating geographic locations to the probability of observing a given combination of alleles, and use a deep, fully-connected neural network to approximate this mapping for a set of genotyped individuals with known locations. The trained network is then evaluated against a set of known individuals held out from the training routine and used to predict the geographic location of new samples based on their genotypes. Applied separately to windows across the genome, `Locator` also estimates uncertainty in individual-level predictions, and can reveal portions of an individual's genome enriched for ancestry from specific geographic areas.

For the empirical population genomic data we analyze here, `Locator` achieves state-of-the-art accuracy an order of magnitude faster than competing methods. Here we describe the implementation, test on simulated data, and demonstrate its use in empirical data by estimating sampling locations for *Anopheles* mosquitoes in Africa from the AG1000G project (The Anopheles gambiae 1000 Genomes Consortium, 2015), *P. falciparum* parasites from Asia, Africa, and the Americas from the *P. falciparum* community project (Pearson et al., 2019), and global human populations from the Human Genome Diversity Project (HGDP; Bergström et al. (2020)).

Results

`Locator` is fast and accurate

We first evaluated `Locator`'s performance in simulations of populations evolving in continuous space with varying rates of dispersal – an idealized setting in which all alleles should vary smoothly over the map. In Figure 2 we show that validation error increases along with the dispersal rate

Figure 1: Conceptual schematic of our approach. Regions of the genome reflect correlated sets of genealogical relationships (A), each of which represents a set of ancestors with varying spatial positions back in time. We extract genotypes from windows across the genome (B), and train a deep neural network to approximate the relationship between genotypes and locations using Euclidean distance as the loss function (C). We can then use the trained network to predict the location of new genotypes held out from the training routine (D).

Figure 2: Validation error for `Locator` runs on simulations with varying dispersal rates. Simulations were on a 50 x 50 landscape and error is expressed in map units. A: True and predicted locations by population mean dispersal rate and number of SNPs. 450 randomly-sampled individuals were used for training. B: Error for runs with 100,000 SNPs and varying numbers of training samples. C: Error for runs with 450 training samples and varying number of SNPs. Plots with error in terms of generations of expected dispersal are shown in Figure S2.

of the population. Interestingly, error is roughly constant when measured in terms of the mean per-generation dispersal rate, ranging from 3.16 to 4.09 generations of dispersal given our largest training dataset (450 samples, 100,000 SNPs; Figure S2). This suggests that error primarily reflects the underlying biological processes of dispersal and mate selection rather than simple noise from model fitting.

Increasing the number of training samples or the number of SNPs improves accuracy for all simulations (Figure 2B). However, we observed diminishing returns when using over 10,000 SNPs or over 200 training samples. Median error for all simulations was also below 10 generations of dispersal for all but the least-dispersive simulation using just 25 training samples; suggesting that even relatively small training datasets can allow inference of broad-scale spatial locations. We discuss theoretical limits on the accuracy of genetic location estimation in Appendix 1 .

We were interested to compare the performance of `Locator` to that of `SPASIBA` (Guillot et al., 2015), the current state-of-the-art method for geographic prediction of genotype data (Figure 3). However, we were unable to succesfully run `SPASIBA` with 100,000 or more SNPs from a simulated dataset or on simulations with dispersal rates of 0.63 or 1.29 map units/generation, due to out-of-memory errors on a 64-bit system with 400Gb of RAM. We could however compare at smaller numbers of SNPs and reduced dispersal. At a mean dispersal distance of 0.45 map units `SPASIBA`'s median test error was slightly lower when run on 1,000 SNPs (Wilcoxon test, $p=0.009$) but results were similar at 100 or 10,000 SNPs. (Wilcoxon test, $p = 0.184$ and 0.936). However, `Locator` is much faster – training on 10,000 SNPs in less than two minutes while SPASIBA requires around six and a half hours (Figure 2). These long run times are caused in part by the large number of training localities in our simulated data, because SPASIBA's run time scales with the product of the number of genetic variants and the number of training localities (Guillot et al., 2015).

While the simulations conform well to modeling assumptions of most methods, we can also compare performance on empirical data. By way of example, we applied `Locator` and `SPASIBA` to subsets of SNPs from the first five million base pairs of chromosome 2L from the Ag1000G dataset Miles and Harding (2017) (figure 3). `Locator` achieves much lower mean error on all runs with more than 100 SNPs, and runs from 3.1x to 532x faster, depending on the number of SNPs. Two factors likely explain this improved accuracy: `Locator` can handle abrupt changes in allele frequencies across the landscape better than `SPASIBA`'s geostatistical model, and the limited number of sampling localities in the AG1000G dataset may act as a prior encouraging `Locator` to assign samples to specific sampling sites. Maps of predictions from both methods are shown in Figure S5. Extrapolating from these run times, running a windowed whole-genome analysis of *Anopheles* in SPASIBA would require roughly 70 days of computation on an 80-CPU system for model training alone, versus 3.2 hours on one GPU for `Locator`.

Uncertainty and Variation along the Genome

By running `Locator` in windows across the genome we aim to integrate over error associated with the model training procedure while also representing the inherent uncertainty caused by spatial drift of ancestral lineages backwards in time (Kelleher et al., 2016). This produces a cloud of predicted locations distributed around the true sample location (Figure 4). For individuals near the center of the landscape these clouds are roughly symmetrical, as expected from our model. Predictions for individuals close to the edge of the landscape appear slightly asymmetrical and are bounded by the true landscape edges, suggesting that our networks have learned the rough shape of the sampled range. The true location was within the 50% contour of a 2d-kernel density surface estimated from the set of per-window predictions for all test samples, demonstrating that this distribution is indeed centered on the true location. We also tested the alternate approach of bootstrapping over a single set of SNPs, which could be useful for smaller datasets or those lacking a reference alignment. Results for this method are discussed in Supplementary figure S4.

Figure 3: Test error and run times for `Locator` and SPASIBA on simulated data with dispersal distance equal to 0.45 map units/generation (top; 450 randomly sampled training samples) and empirical data from the ag1000g phase 1 dataset (bottom; 612 training samples from 14 sampling localities).

Windowed analyses for the three empirical systems we studied are shown in the bottom panels
of Figures 5–7. We discuss the implications of these predictions for each species in the following
sections, but in general we find that the windowed analysis provides a good depiction of uncer-
tainty in a sample's location – either surrounding a single location for samples with low error, or
distributed across a wide region including multiple training localities for samples with high error.
In several cases predicted locations also project in the direction of known historic migrations (as
in human data), or are split among localities shown in previous analyses to experience high gene
flow (as in *Anopheles*).

We summarize genome-wide window predictions in two ways: 1) by taking a kernel density
estimate of the predictions and then finding the point of maximum density, and 2) by computing the
centroid of the windowed predictions. These estimates are similar in spirit to ensemble prediction
methods (Ho, 1995; Breiman, 1996), but should not be interpreted as true statistical confidence
intervals. At least in the context of windowed analyses, differences in predictions among windows
appears to primarily reflect variation in ancestry rather than uncertainty in the inference itself, so
we suggest the intervals returned by `Locator`'s kernel density estimation are best interpreted as
representing areas from which a given proportion of the genome is likely to have originated. In
general we found that the maximum kernel density estimator has lower error, but tends to show
classification behavior more than the centroid estimator – snapping to a single training locality
rather than interpolating between sets of localities for samples with variable window predictions.

151 Empirical Analysis

152 *Anopheles* mosquitoes

153 We next turn our attention to the application of `Locator` to empirical population genomic datasets.
154 In Figure 5 we show predicted and true locations for 153 individuals from the Ag1000g dataset of

Figure 4: Predicted and true locations for 8 individuals simulated in a population with mean per-generation dispersal 0.45 (roughly 1% of the landscape width). Black points are predictions from 2Mbp windows, blue points are training sample locations, and the red point is the true location for each individual. Contours show the 95%, 50%, and 10% quantiles of a two-dimensional kernel density across all windows.

Figure 5: **Top** – Predicted locations for 153 *Anopheles gambiae / coluzzii* genomes from the AG1000G panel, using 612 training samples and a 2Mbp window size. The geographic centroid of per-window predictions for each individual is shown in black points, and lines connect predicted to true locations. Sample localities are colored by the mean test error with size scaled to the number of training samples. **Bottom** – Uncertainty from predictions in 2Mbp windows. Contours show the 95%, 50%, and 10% quantiles of a two-dimensional kernel density across windows.

Anopheles gambiae and *A. coluzzii*, estimated in 2Mbp windows across the genome. The location
with highest kernel density across all windows had a median error of 5.7km, and the centroid of the
per-window predictions had a median error of 36 km (Table S3). Significant prediction error occurs
only between sites in Cameroon, Burkina Faso, and the Republic of Guinea – localities which were
also assigned to a single ancestry cluster in the ADMIXTURE analysis in Miles et al. (2017).
However uncertainty for these samples was relatively well described by visualizing the spread of
per-window predictions, with predicted locations generally lying between sets of localities. The
true locality was within the 95% interval of the kernel density across all windows for all samples.

Plasmodium falciparum

In a windowed analysis of *P. falciparum*, `Locator`'s median error is 16.92 km using the maximum
kernel density and 218.99 km using the geographic centroid of window predictions (Figure 6;
Table S3). Mean predicted locations across all windows consistently separate populations in the
Americas, West Africa, East Africa, southeast Asia, and Papua New Guinea; consistent with the
major population subdivisions described via PCA in Pearson et al. (2019). We also see good
discrimination within clusters, particularly in southeast Asia where the average test error is less
than 200km for all but two localities. Error is highest in West Africa, where mean predictions tend
towards the center of a set of regional collecting localities (Figure 6). These patterns are consistent
with previous findings of fine-scale spatial structure in *P. falciparum* in Cambodia (Miotto et al.,
2013) and low levels of relative genetic differentiation (as measured by F_{ST}) in Africa (Pearson
et al., 2019).

Rates of mixed-strain infection are elevated in West Africa relative to Southeast Asia (Zhu
et al., 2019; Pearson et al., 2019), which we hypothesized could explain the higher prediction error
in this region. To test this effect we plotted `Locator`'s centroid prediction error as a function of
within-host diversity (F_{WS}; Auburn et al. (2012)). F_{WS} measures the proportion of population
genetic diversity present in individual hosts, with a value of 0 representing maximum within-
host diversity and 1 minimum within-host diversity. If mixed-strain infections explain outliers of
prediction error, we would expect that samples with the highest prediction error had low F_{WS}.
Instead we found a weak positive relationship (Figure S6), with the highest prediction errors seen
in samples with maximum F_{WS} (i.e., minimum infection diversity). Test error then likely reflects
low levels of differentiation within *Plasmodium* lineages in West Africa rather than local prevalence
of mixed-strain infections.

Again we found that visualizing per-window predictions reflects expected patterns of uncer-
tainty in samples with high mean prediction error. For example, sample QM0215-C was collected
in Madagascar and has a mean predicted location in Mozambique, but the spread of per-window
predictions indicates a 95% interval that includes the true locality (Figure 6, bottom right).

The good performance we observed on this dataset also highlights a strength of `Locator`'s
model-free approach. Recall that the sequencing strategy of preparing libraries from human blood
samples suggests variant calls represent binned allele frequencies across the population of *Plas-*
modium in a human blood sample rather than SNPs in a single *Plasmodium* individual. From the
perspective of the network; however, the input genotypes are simply a set of normalized vectors,
and the network can approximate the relationship between these vectors and the spatial location
of training samples regardless of the generative process.

Human Populations

198 For humans in the HGDP dataset, the location with highest kernel density across all windows has
199 a median test error of 85km, and the centroid of window predictions has a median error of 452.6
200 kilometers (Figure 7, Table S3). Visualizing the geographic distribution of predictions across the
201 genome shows that predictions tend to cluster around the true reported sampling location, but

Figure 6: **Top** – Predicted locations for 881 *Plasmodium falciparum* from the *Plasmodium falciparum* Community Project (Pearson et al., 2019) (5% of samples for each collecting locality), using 5084 training samples and a 500Kbp window size. The geographic centroid of per-window predictions for each individual is shown in black points, and lines connect predicted to true locations Sample localities are colored by the mean test error with size scaled to the number of training samples. **Bottom** – Uncertainty from predictions in 500Kbp windows. Contours show the 95%, 50%, and 10% quantiles of a two-dimensional kernel density across windows.

Figure 7: Top – Predicted locations for 162 individuals from the HGDP panel, using 773 training samples and a 10Mbp window size. The geographic centroid of per-window predictions for each individual is shown in black points, and lines connect predicted to true locations. Sample localities are colored by the mean test error with size scaled to the number of training samples. Bottom – Uncertainty from predictions in 10Mbp windows.[11]Contours show the 95%, 50%, and 10% quantiles of a two-dimensional kernel density across windows.

also extend towards other sampling locations in a manner that reflects known patterns of human migration.

For example, the two largest individual errors in our analysis are found in South African Bantu individuals and Xibo people from western China. Predicted locations of South African Bantu people project towards the historic source of Bantu migrations in west Africa (De Filippo et al., 2012), with some regions of the genome also projecting in the direction of east African Bantu populations (Figure 7, sample HGDP00993). In the case of Xibo people from western China Locator consistently predicts locations in Manchuria, central China, and southern Sibera – significantly east of the true sample location. This may reflect the known movement of this population, which historically originated in Manchuria and was resettled in western China during the 18th century (Gorelova, 2002; Zikmundová, 2013) (Figure 7, sample HGDP01250). A sample of individual-level predictions is included in Figure 7.

To test whether outlier geographic predictions reflect error in the model fitting procedure versus true variation in ancestry in a given region of the genome, we ran principal component analyses on windows for which a Maya individual (sample HGDP00871) has predicted locations in Europe and Africa. In these windows the Maya sample clusters with other individuals from the regions predicted by Locator – western Europe and Africa, respectively – rather than with other individuals from the Americas (Figure S9). This suggests outlier predictions primarily reflect variation in ancestry in different regions of the genome, rather than stochastic error in model fitting.

Genomic Factors Affecting Prediction Accuracy

Locator's prediction accuracy varied widely along the human genome. To assess the sources of this variation we first examined how recombination rate interacts with the accuracy of Locator predictions generated from different regions of the genome. *A priori* we might expect recombination rate to affect accuracy because in regions of the genome with higher recombination, there are a greater number of distinct genealogies, and hence a given sample has inherited from a larger subset of the possible ancestors. Test error was estimated as the distance in kilometers from the true sampling location to the geographic centroid of the cloud of per-window predictions, and is shown in figure 8 plotted against local recombination rates from the HapMap genetic map (International HapMap Consortium, 2003). We find a relatively strong negative correlation ($p < 0.0001$, $R^2 = 0.27$) – windows with the lowest recombination rates in general have the highest prediction error. This is consistent with our expectation that regions of the genome representing a greater number of marginal genealogies will yield more accurate predictions of a sample's location.

Figure 8: Per-window test error and mean recombination rate for human populations in the HGDP dataset. The top 2% of windows by test error were excluded from this analysis. The slope of the least-squares linear fit is -99.9723 km/(cM/Mbp) and has adjusted $R^2 = 0.2704$.

This finding suggests recombination-based distances may be a better basis for establishing win-
dow bounds. We tested this by replicating our analysis of HGDP samples using a 10-centiMorgan
window size, which yields approximately the same number of windows across the genome. We
found the distribution of centroid prediction errors across windowing methods was very similar
(Figure S12) but the variance in per-window prediction error was lower when using recombination-
based windows (Figure S13; Levene's test $p = 0.0002$, df=654). Examining plots of window error
along the genome suggests much of this effect is caused by high error in windows containing a
centromere when using physical distance-based windows (Figure S10, Figure S11). Centromere
presence explains 26.9% of variance in window prediction error using 10Mb windows, but just
2.6% of variance with centiMorgan-based windows. Thus we recommend researchers interested in
analyzing individual window predictions use recombination-based windows when possible, but find
that using fixed windows is sufficient for estimating individual-level locations.
Last, to examine how predictions vary near a well-known geographically differentiated region
of the genome, we trained a `Locator` model using SNPs from within 100kb of the *EDAR* gene.
The rs3827760 SNP is a $A \rightarrow G$ mutation that created a derived allele which has reached high
frequency in East Asian and North American populations but is rare elsewhere (Bryk et al., 2008).
This variant is thought to be associated with traits including hair thickness (Fujimoto et al., 2008),
and the EDAR region has been proposed as a site of recent positive selection in several analyses
(Voight et al., 2006; Tang et al., 2007; Williamson et al., 2007). We focused on predictions for
samples from central Asia, in the middle of the East-West cline in rs3827760 allele frequencies
across Eurasia.
In this analysis the direction of prediction error generally followed the genotype at rs3827760
– individuals with a G allele tend to predict east of their true location (Figure 9). This was
particularly clear in heterozygous populations. For example, homozygous G/G Xibo and Hazara
individuals predict east of their true location, while one homozygous A/A Uyghur sample pre-
dicts well west of the sampling site. 3 of 4 heterozygous samples also predict east of their true
location, and 5 other A/A Central/South Asian samples predict significantly west. These dis-
crepancies between sampling and predicted locations likely in fact represent signal: haplotypes
carrying a G allele at this locus likely have more "close" relatives in eastern than western Eurasia.
These patterns are magnified versions of the trends seen in windowed analyses, suggesting that
strong differentiation in this genomic region biases location predictions away from the center of
the geographic cline.

Effects of Unsampled Populations

In figures S7 and S8 we show predictions from a single window in the *Anopheles* dataset when
no samples from a given geographic region are included in the training set at two scales – either
dropping only sites from a specific sampling location or dropping all sites from a given country.
Prediction error is much higher for individuals from regions excluded from training – increasing
from a median of 14km when training and test samples are randomly split to 116km when excluding
individual localities, and 778km when excluding whole countries.
In most cases predicted locations appear to project towards the nearest locality included in the
training set (figure S8). This is particularly the case when populations at the edge of the map
are excluded. `Locator` networks appear to learn something about the boundaries of the landscape
based on the distribution of training points, and show a tendency to project towards the middle of
the landscape when given a small number of SNPs (e.g., the top right panel of Figure 2A), a trivial
optimization of the loss function. We also see evidence of `Locator` learning some nonlinear aspects
of population structure in the sample. For example, when Angolan *A. coluzzii* are excluded from
the training set many of their predicted locations project towards the *A. coluzzii* sample localities
in Burkina Faso rather than the much closer sampling localities for *A. gambiae* in Cameroon and

Figure 9: Predicted locations for HGDP samples from central Asia using a model trained on SNPs within 100kb of *EDAR*. Black points show sampling locations. Arrows are colored by genotype at variant rs3827760 and point towards the predicted location. Frequency of the A allele by longitude is shown below the map.

Gabon. In general we find that `Locator` can interpolate unsampled localities relatively well when genetic differentiation is smooth over the landscape (as among *A. gambiae* localities in west Africa), but does not extrapolate outside the bounds of the training set. Sampling the full landscape, or at least a sufficient portion thereof, is thus an important consideration in running our method.

Discussion

The correlation of genealogy and geography leaves genetic signals of ancestral location across the genome that one can leverage for practical inference. For instance, tracking the migratory routes of disease vectors such as *Anopheles* (Huestis et al., 2019) could in principle be achieved if one could accurately predict origin from DNA sequence data. Similarly, establishing the location of origin from biological samples is critical to anti-poaching conservation efforts (Wasser et al., 2004), and efforts to map transmission during the ongoing SARS-CoV-2 pandemic have been informed by analysis of geographically restricted genetic variants (see e.g., `https://nextstrain.org/ncov/global`). In this report we present a new tool, `Locator`, which uses a deep neural network to predict the geographic location of a sample on the basis of its genotype. We show that `Locator` is highly accurate, computationally efficient, and can scale to thousands of genomes.

In simulations we found that our method achieves similar accuracy as a state-of-the-art model-based approach, SPASIBA (Guillot et al., 2015), and does so at least an order of magnitude faster.

We show that the accuracy of our estimator is naturally measured in terms of the dispersal rate of
the population and that predictions from `Locator` are consistently within 3–4 generations of mean
dispersal across a wide range of dispersal distances (Figure 2, Figure S2). However the greatest
increase in accuracy relative to SPASIBA was in empirical data (Figure 3). This seems to reflect
two aspects of our approach that highlight its strengths and weaknesses: as a process-agnostic
model `Locator` can easily handle situations in which allele frequencies do not vary smoothly over
the landscape. However, the spatial concentration of the *Anopheles* samples may act as a strong
prior that incentivizes the network to predict sample locations near sampling localities (Figure
3, Figure 5), thus acting more as a classifier than a continuous predictor. Thus sampling should
be taken into account when interpreting `Locator`'s output, and when possible users should avoid
highly clustered sampling regimes.

`Locator`'s computational efficiency makes it practical to estimate uncertainty through resam-
pling approaches like windowed analysis or bootstrapping over the complete genotype matrix. The
full windowed analysis of the HGDP data took roughly 30 hours to run on a single GPU, and
windowed analysis of all 5,965 complete *Plasmodium* genomes took just 8 hours. Thus training
`Locator` models for biobank-scale datasets including whole genomes of tens or hundreds of thou-
sands of samples is well within reach, particularly if windows can be run on separate GPUs. This
allows us to estimate uncertainty in predicted locations due both to our prediction methodology as
well as biology; with repeated training runs integrating over error associated with network training
and prediction and the windowed analysis allowing us to predict geographic origins for regions of
the genome reflecting distinct sets of genealogical relationships.

Disentangling these sources of error is challenging, but analysis of human data for which we
have strong prior knowledge of recent population movements suggests that much of the variation in
genome-wide prediction we see reflects historic patterns of migration rather than simple prediction
error. For example, genomes from Hazara individuals in central Asia return predicted locations
extending from central Asia to Mongolia (Figure 7 bottom, sample HGDP00118), which is consis-
tent with historic records (Qamar et al., 2002), previous analysis of Y chromosome data (Zerjal
et al., 2003), and identity-by-descent tract sharing (Lawson et al., 2012) all of which find evidence
of recent shared ancestry between Mongolian and Hazara individuals. Similarly some Maya indi-
viduals found to have a small proportion of European ancestry in previous analyses (Rosenberg
et al., 2002) have predicted locations extending from central Mexico across the Atlantic to Europe
and west Africa in windowed `Locator` analysis (Figure 7 bottom, sample HGDP00871), and these
signals are replicated in principal components analysis (Figure S9).

The correspondence between our explicitly geographic method and unsupervised clustering or
dimensionality reduction methods highlights the implicit prior assumption of genetic-geographic
correlation often made when interpreting the output of STRUCTURE or PCA. Rather than map-
ping population structure to geography as a post-hoc interpretation, `Locator` and other continuous
assignment methods directly incorporate space in the model. This also points to a critical con-
sideration in running any form of supervised population clustering. Information about population
structure comes only from the relative relationships among training and test samples, and inter-
pretations can only be made relative to the set of training samples used. In the case of the HGDP
panel, samples were intentionally selected to cover what were thought to be distinctive populations
reflecting a vaguely pre-modern distribution of human genetic diversity (Harry and Marks, 1999),
and so would probably not be a good reference set for random individuals drawn from areas with
recent histories of large population movements such as the United States.

Here we have shown that our method, `Locator`, is fast, accurate, and scales well to large
samples. However we see several next steps that could improve the approach. First, our current
implementation uses only diploid genotypes and does not pass the network any direct information
about haplotype structure. Incorporating SNP position information and phased haploid sequences
would likely increase inferential power, as in the case of unsupervised clustering (Lawson et al.,

2012). Running this method on phased, haploid genomes could also in theory allow us to predict
parental locations individually for loci with ancestry from different geographic regions. Second,
our network currently uses a simple fully-connected architecture; it could be that other network
architectures such as recurrent neural networks might be better suited for this task (e.g., Adrion
et al., 2020). Indeed the application of deep learning to population genetics is still in its infancy
and we imagine much progress will be made in the coming years along these lines.

A central issue in this task will be understanding the limits of process-agnostic inference:
when and how can we best use machine learning approaches in population genetics? `Locator` is
essentially a flexible regressor designed without direct reference to genealogical or genetic process,
so the exact design of the network or the arrangement of the weights and biases in a trained model
gives little insight into the underlying mechanisms driving its inferences. These are instead best
assessed by carefully studying the natural history of the focal organism, and by interpreting model
output with population genetic theory and simulations. We suggest machine learning methods
be seen as tools to answer narrowly-defined questions, used as a complement to process-based
statistical models that give deeper insight into the mechanisms generating the data being analyzed.

In principle, a completely process-based inference method that accurately modeled spatial
population dynamics might provide the most accurate and best-calibrated inference of location
and/or ancestry. However, the problem of modeling spatial populations is not solved, and all
existing methods are based on assumptions (e.g., an unchanged species range on a uniform land-
scape (Wright, 1943)) that may not hold in practice. For this reason, machine learning approaches
might outperform methods based on process. Beyond the present application we believe a power-
ful approach will be to combine process-based population genetic models with the generalization
abilities of deep learning – analogous to natural language processing methods that supplement
neural network word embeddings with syntax models (Strubell and McCallum, 2018). This could
allow us to leverage theory where assumptions are well-founded while turning to robust generalized
optimization techniques when they are not.

Methods

Preprocessing

`Locator` transforms input data in VCF or Zarr format to vectors of allele counts per individual
using the scikit-allel (Miles and Harding, 2017) and numpy (Van Der Walt et al., 2011) libraries.
Sites with missing data are replaced with two draws from a binomial distribution with probability
equal to the frequency of the derived allele across all individuals – a discrete version of the common
practice of assigning missing data as the mean allele frequency in genotype PCAs (e.g., the default
settings for PCA in the R package adegenet (Jombart, 2008)). We provide functions for filtering
SNPs based on minor allele count, and by default remove singleton sites from the alignment prior
to model fitting. The geographical x and y coordinates are scaled to have mean 0 and variance
1 prior to training, while allele counts are scaled prior to model fitting by a batch normalization
layer within the network. Batch normalization Z-normalizes activations of a neural network during
training to reduce shifts in the distribution of parameter values across batches, which allows faster
learning rates and sometimes reduces overfitting (Ioffe and Szegedy, 2015).

`Locator` selects user-defined fraction of the samples with known locations to use in training the
model (the default is 0.9); remaining samples with known locations are kept aside as "validation"
samples. The validation set is used to tune the learning rate of the optimizer and set the stopping
time of model training, but does not directly contribute to the loss used to fit model parameters.
Throughout this manuscript we use "validation loss" to refer to error estimated on the validation
set, and "test error" to refer to error calculated on a set of samples entirely held out from the
model training procedure.

For datasets with small sample sizes the random train/test split may lead to some regions
being under- or overrepresented in the training sample. To mitigate this we suggest fitting multiple
models with different random seeds, yielding an ensemble of models trained on different subsets
of the original dataset. Predictions from this ensemble can then be summarized in the same way
as windows or bootstrap samples (see below). An example of this approach is included in the
`Locator` documentation (`https://github.com/kern-lab/locator`).

Network

We use the unphased, diploid genotype vector of each individual as input to the network, whose
target output is the two-dimensional coordinates of that individual in space. `Locator` uses a deep
neural network consisting of a stack of fully-connected "dense" layers, implemented using the Keras
(Chollet et al., 2015) frontend to tensorflow (Abadi et al., 2015). Roughly speaking, the network
is trained to estimate a nonlinear function mapping genotypes to locations using gradient-based
optimization. Models start with randomized initial parameters and are fit to data by looping
through the training set and iteratively adjusting the weights and biases of the network. We use
an early stopping function to monitor loss during training and under default settings stop training
runs when validation loss has not improved for 100 epochs. We also use a learning rate scheduler
to decrease the learning rate of the optimizer when validation loss stops improving, which we found
to be effective in preventing the trajectories of training and validation loss from diverging. The
program also outputs a plot of training and validation loss after each training run (Figure S1).

`Locator`'s architecture uses a batch normalization layer followed by a sequence of fully-connected
layers with a dropout layer in the middle of the network (Figure 1). The "dropout" layer sets a
random selection of weights to zero during each training step, which helps prevent overfitting (Sri-
vastava et al., 2014). Our implementation allows users to adjust the shape of the network, but
current default settings use 10 dense layers of 256 nodes each with "ELU" activations (Clevert
et al., 2015) and a 25% dropout after the fifth layer. We describe performance under varying
network width and depth in Supplementary Figure S3. In general we found that all networks with
over four layers perform similarly.

We use the Adam optimizer (Kingma and Ba, 2014) with Euclidean distance as a loss function:

$$\text{loss} = \sqrt{(x_{\text{predicted}} - x_{\text{true}})^2 + (y_{\text{predicted}} - y_{\text{true}})^2}. \tag{1}$$

Uncertainty and Genome-wide Variation

Individuals are born at a single location, but have inherited their genomes as a mosaic from
ancestors spreading geographically into the past (as discussed in, for instance, Wright (1943);
Kelleher et al. (2016); Bradburd and Ralph (2019)). Any signal our method hopes to extract from
the data must be due to geographic signal of recent ancestors shared between the test and training
datasets. This suggests that any analogous method must quantify, roughly, "which modern day
populations are most similar to this genome?". The spatial spread of genetic relatedness both
back in time from an individual's to its ancestors' locations and forward in time from ancestors to
the present-day location of training samples means that even a perfect inference algorithm should
have significant uncertainty associated with any predicted location from genetic data, and the
magnitude of uncertainty should be in part a function of the dispersal rate of the population. In
particular, no such method can infer locations more accurately than the mean dispersal distance,
because in most cases an individual's genome is not informative about where they live relative to
their parents. Besides this fundamental limit to uncertainty, error in georeferencing of training
samples and in model fitting will introduce additional prediction uncertainty.

We use a windowed analysis across the genome to describe this uncertainty, which is possible
thanks to `Locator`'s computational efficiency. Genealogical relatedness on each contiguous stretch
of genome can be described by a sequence of genealogical trees, separated by ancestral recombina-
tion events. By running `Locator` on a particular window of the genome, we restrict inference to
a subset of these marginal trees, and hence to a subset of the genetic relationships between test
and training samples. Predictions from different regions of the genome can then be visualized as
a cloud of points, and the distribution of these points in space gives us a rough idea of the uncer-
tainty associated with an individual-level prediction. Because windowed analyses involve repeated
training runs from randomized starting parameters, they also help us to integrate over uncertainty
associated with the model fitting process.

Some datasets lack the size or reference alignments necessary to conduct windowed analyses.
In this case we recommend uncertainty be assessed by training replicate models on bootstrapped
samples drawn from a single set of unlinked SNPs (that is, resampling SNPs with replacement).
Though this procedure does not reduce the number of marginal trees represented in the data, it
does allow us to assess uncertainty associated with model training and prediction. In both cases
we summarize uncertainty in predicted locations by estimating a two-dimensional kernel density
surface over a set of predicted locations, and provide plotting scripts to visualize the 95%, 50%,
and 10% quantiles in geographic space (see figures 5–7 for examples). The location of an individual
can then be predicted as either the location with highest kernel density (the modal prediction) or
the geographic center of the cloud of predictions (the mean prediction).

We tested this approach in simulated data and in all empirical datasets. To explore factors
affecting the accuracy of predicted locations generated from different regions of the genome, we
also examined the relationship between recombination rate and test error from windowed *Locator*
runs on human data from the HGDP panel (Bergström et al., 2020). Recombination rates for
each window were estimated by averaging per-base rates from the HapMap project (International
HapMap Consortium, 2003).

Simulations

We first evaluated our method on genotypes from populations simulated by SLiM v3 (Haller and
Messer, 2019), using the model of continuous space described in Battey et al. (2019). We simulated
a 50×50 unit square landscape with expected density (d) of 5 individuals per unit area, resulting
in census sizes of around 12,500. We varied the mean parent-offspring dispersal distance σ across
simulations from 0.45 to 3, to create populations with varying levels of isolation by distance.
In terms of Wright's "neighborhood size" (Wright, 1946), defined as $N_{\text{loc}} = 4\pi\sigma^2 d$, this yields
populations with neighborhood sizes from 13 to 565. Each diploid individual carried two copies of
a 10^8 bp chromosome on which mutations and recombinations occured at a rate of 10^{-8} per bp
per generation. Simulations were run until all extant individuals shared a single common ancestor
within the simulation at all locations on the genome (i.e., the tree sequence had coalesced). 500
individuals were randomly sampled from the final generation of each simulation for use in model
fitting.

We selected 50 individuals from each simulation as a validation set and ran `Locator` while
varying the number of training samples from 10 to 450 and the number of SNPs from 100 to 100,000.
The SNPs used were a subset sampled from the full genotype matrix without replacement and thus
mimic the semi-random distribution of genome-wide SNPs generated by reduced-representation
sequencing approaches like RADseq (Etter et al., 2012). To compare performance with an existing
model-based approach, we also ran SPASIBA (Guillot et al., 2015) on the simulation with $\sigma = 0.44$
using 450 training samples and varying the number of SNPs from 100 to 100,000. `Locator` was
run on a CUDA-enabled GPU and `SPASIBA` was run on 80 CPU cores. Last, we ran a windowed
analysis on the $\sigma = 0.63$ (neighborhood size ≈ 25) simulation in `Locator` using a 2Mbp window

size (each window then contains $\approx 8,000$ SNPs).

Empirical Data

We applied `Locator` to three whole-genome resequencing datasets of geographically widespread
samples: (1) 765 mosquitoes from the *Anopheles gambiae / coluzzii* species complex collected
across sub-Saharan Africa (Miles et al., 2017), (2) 5,965 samples of the malaria parasite *Plasmodium*
falciparum sequenced from human blood samples collected across Papua New Guinea, southeast
Asia, sub-Saharan Africa, and northern South America (Pearson et al., 2019) and (3) whole-genome
data for 56 human populations from the Human Genome Diversity Project (Bergström et al., 2020).
Genotype calls for the *Anopheles* dataset are available at `https://www.malariagen.net/data/`
`ag1000g-phase1-ar3`, for *P. falciparum* at `https://www.malariagen.net/resource/26`, and for
human data at `ftp://ngs.sanger.ac.uk/production/hgdp`. We used VCF files as provided with
no further postprocessing.

The *Plasmodium falciparum* dataset is unusual relative to our other empirical examples in
that sequencing libraries were prepared from blood samples without filtering for coinfections or
isolating individual *Plasmodium*. Sequence reads returned from short read sequencing then reflect
the population of *Plasmodium* present in a human blood sample, or even multiple lineages of
parasite if an individual is co-infected with multiple strains (Zhu et al., 2019), rather than individual
Plasmodium. The VCFs we analyzed were prepared by aligning illumina short read sequences to
the *Plasmodium falciparum* reference genome prepared by the Pf3K project (Pf3K Consortium
(2016); `https://www.malariagen.net/data/pf3K-5`), then calling SNPs in GATK (McKenna
et al., 2010). Variant calls then represent the pool of mutations present in the infecting *Plasmodium*
population rather than SNPs in a single individual. We used only field-collected samples from the
"analysis" set, as described in (Pearson et al., 2019).

For the *Anopheles* dataset we ran `Locator` in 2Mbp windows across the genome with a randomly
selected 10% of individuals held out as a test set. We also ran `SPASIBA` on subsets sampled from
the first five million base pairs of chromosome 2L while varying the number of SNPs from 100 to
100,000. For the *P. falciparum* dataset we used 500kb windows and held out 5% of samples from
each collection locality as a test set. Last, for humans we used 10Mbp windows and selected three
individuals from each HGDP population to hold out as a test set. Window sizes in each case were
chosen to include roughly 100,000–200,000 SNPs per window. All empirical analyses were run
with default settings (10×256 network size, patience 100, 25% dropout, a random 10% of training
samples used for validation).

We also tested `Locator`'s performance with empirical data when the true location is not rep-
resented in the training sample. To do this we ran a series of models on 10,000 SNPs randomly
selected from the first 5Mbp of chromosome 2L in the *Anopheles* data. For each run we held out all
samples from a given sampling locality from the training set, then predicted the locations of these
individuals using the trained model. We also tested this approach while holding out all samples
collected in a given country, which eliminates even nearby localities from the training set.

Data & Code

`Locator` is implemented as a command-line program written in Python: `www.github.com/kern-lab/`
`locator`. SNP calls for the *Anopheles* dataset are available at `https://www.malariagen.net/`
`data/ag1000g-phase1-ar3`, for *P. falciparum* at `https://www.malariagen.net/resource/26`,
and for the HGDP at `ftp://ngs.sanger.ac.uk/production/hgdp`. Code to run continuous-
space simulations can be found at `https://github.com/kern-lab/spaceness/blob/master/`
`slim_recipes/spaceness.slim` (Battey et al., 2019). This publication uses data from the Malar-

iaGEN Plasmodium falciparum Community Project as described in Pearson et al. (2019). Statistical analyses and many plots were produced in R (R Core Team, 2018).

Competing Interests

The authors declare no competing interests.

Acknowledgements

We thank members of the Kern-Ralph co-lab, Daniel Schrider, Matthew Hahn, and Ethan Linck for comments and suggestions on this work, and Mara Lawniczak for the suggestion to look at the *Plasmodium* dataset. CJB and ADK were funded by NIH award R01GM117241. PLR was funded in part by an I3 award from the University of Oregon.

References

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL `http://tensorflow.org/`. Software available from tensorflow.org.

Jeffrey R Adrion, Jared G Galloway, and Andrew D Kern. Predicting the Landscape of Recombination Using Deep Learning. *Molecular Biology and Evolution*, 02 2020. ISSN 0737-4038. doi: 10.1093/molbev/msaa038. URL `https://doi.org/10.1093/molbev/msaa038`. msaa038.

Sarah Auburn, Susana Campino, Olivo Miotto, Abdoulaye A Djimde, Issaka Zongo, Magnus Manske, Gareth Maslen, Valentina Mangano, Daniel Alcock, Bronwyn MacInnis, et al. Characterization of within-host *Plasmodium falciparum* diversity using next-generation sequence data. *PloS one*, 7(2):e32891, 2012.

Yael Baran, Inés Quintela, Ángel Carracedo, Bogdan Pasaniuc, and Eran Halperin. Enhanced localization of genetic samples through linkage-disequilibrium correction. *The American Journal of Human Genetics*, 92(6):882–894, 2013.

CJ Battey, Ethan B Linck, Kevin L Epperly, Cooper French, David L Slager, Paul W Sykes Jr, and John Klicka. A migratory divide in the Painted Bunting (*Passerina ciris*). *The American Naturalist*, 191(2):259–268, 2018.

CJ Battey, Peter L Ralph, and Andrew D Kern. Space is the place: Effects of continuous spatial structure on analysis of population genetic data. *BioRxiv*, page 659235, 2019.

Anders Bergström, Shane A. McCarthy, Ruoyun Hui, Mohamed A. Almarri, Qasim Ayub, Petr Danecek, Yuan Chen, Sabine Felkel, Pille Hallast, Jack Kamm, Hélène Blanché, Jean-François Deleuze, Howard Cann, Swapan Mallick, David Reich, Manjinder S. Sandhu, Pontus Skoglund, Aylwyn Scally, Yali Xue, Richard Durbin, and Chris Tyler-Smith. Insights into human genetic variation and population history from 929 diverse genomes. *Science*, 367(6484), 2020. ISSN 0036-8075. doi: 10.1126/science.aay5012. URL `https://science.sciencemag.org/content/367/6484/eaay5012`.

Anand Bhaskar, Adel Javanmard, Thomas A Courtade, and David Tse. Novel probabilistic models of spatial genetic ancestry with applications to stratification correction in genome-wide association studies. *Bioinformatics*, 33(6):879–885, 2016.

Gideon S. Bradburd and Peter L. Ralph. Spatial population genetics: It's about time. *Annual Review of Ecology, Evolution, and Systematics*, 50(1):427–449, 2019. doi: 10.1146/annurev-ecolsys-110316-022659. URL `https://doi.org/10.1146/annurev-ecolsys-110316-022659`.

Natalie Breidenbach, Oliver Gailing, and Konstantin V Krutovsky. Assignment of frost tolerant coast redwood trees of unknown origin to populations within their natural range using nuclear and chloroplast microsatellite genetic markers. *bioRxiv*, page 732834, 2019.

Leo Breiman. Bagging predictors. *Machine learning*, 24(2):123–140, 1996.

Jarosław Bryk, Emilie Hardouin, Irina Pugach, David Hughes, Rainer Strotmann, Mark Stoneking, and Sean Myles. Positive selection in east asians for an edar allele that enhances nf-κb activation. *PLOS ONE*, 3(5):1–6, 05 2008. doi: 10.1371/journal.pone.0002209. URL `https://doi.org/10.1371/journal.pone.0002209`.

Jeffrey Chan, Valerio Perrone, Jeffrey Spence, Paul Jenkins, Sara Mathieson, and Yun Song. A likelihood-free inference framework for population genetic data using exchangeable neural networks. In *Advances in Neural Information Processing Systems*, pages 8594–8605, 2018.

François Chollet et al. Keras. `https://keras.io`, 2015.

Djork-Arné Clevert, Thomas Unterthiner, and Sepp Hochreiter. Fast and accurate deep network learning by exponential linear units (ELUs). *arXiv preprint arXiv:1511.07289*, 2015.

Qian Cong, Jinhui Shen, Jing Zhang, Wenlin Li, Lisa N. Kinch, John V. Calhoun, Andrew D. Warren, and Nick V. Grishin. Genomics reveals the origins of ancient specimens. *bioRxiv*, 2019. doi: 10.1101/752121. URL `https://www.biorxiv.org/content/early/2019/09/04/752121`.

Cesare De Filippo, Koen Bostoen, Mark Stoneking, and Brigitte Pakendorf. Bringing together linguistic and genetic evidence to test the Bantu expansion. *Proceedings of the Royal Society B: Biological Sciences*, 279(1741):3256–3263, 2012.

Arun Durvasula and Sriram Sankararaman. A statistical model for reference-free inference of archaic local ancestry. *PLoS genetics*, 15(5):e1008175, 2019.

Paul D Etter, Susan Bassham, Paul A Hohenlohe, Eric A Johnson, and William A Cresko. SNP discovery and genotyping for evolutionary genetics using RAD sequencing. In *Molecular methods for evolutionary genetics*, pages 157–178. Springer, 2012.

Lex Flagel, Yaniv Brandvain, and Daniel R Schrider. The unreasonable effectiveness of convolutional neural networks in population genetic inference. *Molecular biology and evolution*, 36(2): 220–238, 2018.

Akihiro Fujimoto, Ryosuke Kimura, Jun Ohashi, Kazuya Omi, Rika Yuliwulandari, Lilian Batubara, Mohammad Syamsul Mustofa, Urai Samakkarn, Wannapa Settheetham-Ishida, Takafumi Ishida, et al. A scan for genetic determinants of human hair morphology: Edar is associated with asian hair thickness. *Human molecular genetics*, 17(6):835–843, 2008.

Liliya M Gorelova. *Manchu grammar*. Brill, 2002.

Gilles Guillot, Hákon Jónsson, Antoine Hinge, Nabil Manchih, and Ludovic Orlando. Accurate continuous geographic assignment from low- to high-density SNP data. *Bioinformatics*, 32 (7):1106–1108, 11 2015. ISSN 1367-4803. doi: 10.1093/bioinformatics/btv703. URL `https://doi.org/10.1093/bioinformatics/btv703`.

Benjamin C Haller and Philipp W Messer. SLiM 3: Forward genetic simulations beyond the Wright–Fisher model. *Molecular biology and evolution*, 36(3):632–637, 2019.

Debra Harry and Jonathan Marks. Human population genetics versus the HGDP. *Politics and the Life Sciences*, 18(2):303–305, 1999.

Tin Kam Ho. Random decision forests. In *Proceedings of 3rd international conference on document analysis and recognition*, volume 1, pages 278–282. IEEE, 1995.

Diana L. Huestis, Adama Dao, Moussa Diallo, Zana L. Sanogo, Djibril Samake, Alpha S. Yaro, Yossi Ousman, Yvonne-Marie Linton, Asha Krishna, Laura Veru, Benjamin J. Krajacich, Roy Faiman, Jenna Florio, Jason W. Chapman, Don R. Reynolds, David Weetman, Reed Mitchell, Martin J. Donnelly, Elijah Talamas, Lourdes Chamorro, Ehud Strobach, and Tovi Lehmann. Windborne long-distance migration of malaria mosquitoes in the Sahel. *Nature*, 2019. doi: 10.1038/s41586-019-1622-4. URL `https://doi.org/10.1038/s41586-019-1622-4`.

International HapMap Consortium. The international HapMap project. *Nature*, 426(6968):789, 2003.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Thibaut Jombart. adegenet: a R package for the multivariate analysis of genetic markers. *Bioinformatics*, 24(11):1403–1405, 2008.

Jerome Kelleher, AM Etheridge, Amandine Véber, and Nicholas H Barton. Spread of pedigree versus genetic ancestry in spatially distributed populations. *Theoretical population biology*, 108: 1–12, 2016.

Andrew D Kern and Daniel R Schrider. diploS/HIC: an updated approach to classifying selective sweeps. *G3: Genes, Genomes, Genetics*, 8(6):1959–1970, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Daniel John Lawson, Garrett Hellenthal, Simon Myers, and Daniel Falush. Inference of population structure using dense haplotype data. *PLoS genetics*, 8(1):e1002453, 2012.

Aaron McKenna, Matthew Hanna, Eric Banks, Andrey Sivachenko, Kristian Cibulskis, Andrew Kernytsky, Kiran Garimella, David Altshuler, Stacey Gabriel, Mark Daly, et al. The genome analysis toolkit: a MapReduce framework for analyzing next-generation DNA sequencing data. *Genome research*, 20(9):1297–1303, 2010.

Alistair Miles and Nick Harding. cggh/scikit-allel: v1.1.8, July 2017. URL `https://doi.org/10.5281/zenodo.822784`.

Alistair Miles, Nicholas J Harding, and the AG1000G consortium. Genetic diversity of the African malaria vector *Anopheles gambiae*. *Nature*, 552(7683):96, 2017.

Olivo Miotto, Jacob Almagro-Garcia, Magnus Manske, Bronwyn MacInnis, Susana Campino, Kirk A Rockett, Chanaki Amaratunga, Pharath Lim, Seila Suon, Sokunthea Sreng, et al. Multiple populations of artemisinin-resistant *Plasmodium falciparum* in Cambodia. *Nature genetics*, 45(6):648, 2013.

Mehreen R Mughal and Michael DeGiorgio. Localizing and classifying adaptive targets with trend filtered regression. *Molecular biology and evolution*, 36(2):252–270, 2018.

Richard D Pearson, Roberto Amato, Dominic P Kwiatkowski, and MalariaGEN Plasmodium falciparum Community Project. An open dataset of *Plasmodium falciparum* genome variation in 7,000 worldwide samples. *bioRxiv*, 2019. doi: 10.1101/824730. URL `https://www.biorxiv.org/content/early/2019/11/07/824730`.

Pf3K Consortium. The Pf3K project (2016): pilot data release 5, 2016. URL `www.malariagen.net/data/pf3k-5`.

Pierre Pudlo, Jean-Michel Marin, Arnaud Estoup, Jean-Marie Cornuet, Mathieu Gautier, and
Christian P Robert. Reliable ABC model choice via random forests. *Bioinformatics*, 32(6):
859–866, 2015.

Raheel Qamar, Qasim Ayub, Aisha Mohyuddin, Agnar Helgason, Kehkashan Mazhar, Atika Man-
soor, Tatiana Zerjal, Chris Tyler-Smith, and S Qasim Mehdi. Y-chromosomal DNA variation in
Pakistan. *The American Journal of Human Genetics*, 70(5):1107–1124, 2002.

R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for
Statistical Computing, Vienna, Austria, 2018. URL https://www.R-project.org/.

John Michael Rañola, John Novembre, and Kenneth Lange. Fast spatial ancestry via flexible allele
frequency surfaces. *Bioinformatics*, 30(20):2915–2922, 2014.

Noah A Rosenberg, Jonathan K Pritchard, James L Weber, Howard M Cann, Kenneth K Kidd,
Lev A Zhivotovsky, and Marcus W Feldman. Genetic structure of human populations. *science*,
298(5602):2381–2385, 2002.

Daniel R Schrider and Andrew D Kern. S/HIC: Robust identification of soft and hard sweeps using
machine learning. *PLoS Genet*, 12(3):e1005928, Mar 2016. doi: 10.1371/journal.pgen.1005928.

Daniel R Schrider, Julien Ayroles, Daniel R Matute, and Andrew D Kern. Supervised machine
learning reveals introgressed loci in the genomes of *Drosophila simulans* and *D. sechellia*. *PLoS
genetics*, 14(4):e1007341, 2018.

Sara Sheehan and Yun S Song. Deep learning for population genetic inference. *PLoS computational
biology*, 12(3):e1004845, 2016.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov.
Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine
learning research*, 15(1):1929–1958, 2014.

Emma Strubell and Andrew McCallum. Syntax helps elmo understand semantics: Is syntax still
relevant in a deep neural architecture for srl?, 2018.

Lauren Alpert Sugden, Elizabeth G Atkinson, Annie P Fischer, Stephen Rong, Brenna M Henn,
and Sohini Ramachandran. Localization of adaptive variants in human genomes using averaged
one-dependence estimation. *Nature communications*, 9(1):703, 2018.

Kun Tang, Kevin R Thornton, and Mark Stoneking. A new approach for using genome scans to
detect recent positive selection in the human genome. *PLoS biology*, 5(7), 2007.

The Anopheles gambiae 1000 Genomes Consortium. Ag1000G phase 1 AR3 data release. *Malar-
iaGEN*, 2015. URL http://www.malariagen.net/data/ag1000g-phase1-AR3.

Stefan Van Der Walt, S Chris Colbert, and Gael Varoquaux. The numpy array: a structure for
efficient numerical computation. *Computing in Science & Engineering*, 13(2):22, 2011.

Fernando A Villanea and Joshua G Schraiber. Multiple episodes of interbreeding between nean-
derthal and modern humans. *Nature ecology & evolution*, 3(1):39, 2019.

Benjamin F Voight, Sridhar Kudaravalli, Xiaoquan Wen, and Jonathan K Pritchard. A map of
recent positive selection in the human genome. *PLoS biology*, 4(3), 2006.

Samuel K Wasser, Andrew M Shedlock, Kenine Comstock, Elaine A Ostrander, Benezeth Mutay-
oba, and Matthew Stephens. Assigning African elephant DNA to geographic region of origin:
applications to the ivory trade. *Proceedings of the National Academy of Sciences*, 101(41):
14847–14852, 2004.

Scott H Williamson, Melissa J Hubisz, Andrew G Clark, Bret A Payseur, Carlos D Bustamante,
and Rasmus Nielsen. Localizing recent adaptive evolution in the human genome. *PLoS genetics*,
3(6), 2007.

S Wright. Isolation by distance. *Genetics*, 28(2):114–138, March 1943. URL `http://www.`
`genetics.org/cgi/reprint/28/2/114`.

Sewall Wright. Isolation by distance under diverse systems of mating. *Genetics*, 31(1):336, 01
1946. URL `https://www.ncbi.nlm.nih.gov/pubmed/21009706`.

Wen-Yun Yang, John Novembre, Eleazar Eskin, and Eran Halperin. A model-based approach
for analysis of spatial structure in genetic data. *Nature Genetics*, 44:725 EP –, 05 2012. URL
`https://doi.org/10.1038/ng.2285`.

Tatiana Zerjal, Yali Xue, Giorgio Bertorelle, R Spencer Wells, Weidong Bao, Suling Zhu, Raheel
Qamar, Qasim Ayub, Aisha Mohyuddin, Songbin Fu, et al. The genetic legacy of the Mongols.
The American Journal of Human Genetics, 72(3):717–721, 2003.

Sha Joe Zhu, Jason A Hendry, Jacob Almagro-Garcia, Richard D Pearson, Roberto Amato, Alistair
Miles, Daniel J Weiss, Tim CD Lucas, Michele Nguyen, Peter W Gething, et al. The origins and
relatedness structure of mixed infections vary with local prevalence of *P. falciparum* malaria.
eLife, 8:e40845, 2019.

Veronika Zikmundová. *Spoken sibe: morphology of the inflected parts of speech*. Karolinum
Press, 2013. URL `https://www.google.com/books/edition/Spoken_Sibe_Morphology_of_`
`the_Inflected/PUs3BAAAQBAJ?hl=en&gbpv=1`.

Appendix 1: Theoretical limits on accuracy

Suppose that we know the spatial locations of some relatives of a given individual, and want to predict the location of that focal individual. This is a best-case scenario for our actual problem, as in fact we would have to infer the degrees of relatedness of the reference set to the focal individual, but the calculations are useful in establishing a lower bound on the resolution of inference.

Suppose furthermore that the displacement in spatial position along each parent-child relationship has mean zero and variance σ^2, so that the net distance traveled along any path along k links in the pedigree has mean zero and variance $k\sigma^2$. Given the location of n relatives of a focal individual, a simple estimator of that individual's spatial location is simply the average of their locations. How well does this do?

We can associate each link between parent p and child c in the pedigree with the displacement between them, $X_{pc} = -X_{cp}$; we have assumed that $\mathrm{var}[X_{cp}] = \sigma^2$ for each. Suppose that the i^{th} relative can be reached by traversing relatives $r_{i1}, \ldots, r_{ik_i}$, and so their location relative to the focal individual is $Y_i = X_{r_{i1}, r_{i2}} + \cdots + X_{r_{i(k_i-1)}, r_{ik_i}}$. To compute the variance of our estimator, $\bar{Y} = \sum_{i=1}^{n} Y_i / n$, let n_{cp} be the number of i for which X_{cp} appears in the sum for Y_i, so that $\bar{Y} = \sum_{cp} n_{cp} X_{cp} / n$. Then, simply, $\mathrm{var}[\bar{Y}] = \sum_{cp} (n_{cp}/n)^2 X_{cp}$. For instance, if those relatives are all 2^k ancestors k generations ago (i.e., the great^{k-2}-grandparents) of the focal individual, then each of the 2^ℓ links between the ℓ^{th} and $(\ell-1)^{\mathrm{th}}$ generations are traversed by $2^{k-\ell}$ of the paths, and so

$$\mathrm{var}[\bar{Y}] = \sum_{\ell=1}^{k} 2^\ell \left(\frac{2^{k-\ell}}{2^k} \right)^2 \sigma^2 = (1 - 2^{-k})\sigma^2.$$

Clearly, with less full pedigree coverage and more distant relatives, the error would become worse, but it does not depend strongly on the degree of relatedness used: in general, using a few close or many distant relatives should give an estimate of location within some moderate factor of σ.

Supplementary Figures and Tables

Neighborhood Size	Expected dispersal (map units/gen)	Error (map units) *mean (95% interval)*	Error (generations)
13	0.45	1.84 (0.259-3.633)	4.09
25	0.63	2.44 (0.388-6.033)	3.87
105	1.29	4.07 (0.685-8.874)	3.16
251	2.00	6.44 (0.639-14.526)	3.22
565	3.00	9.70 (0.871-21.146)	3.23

Table S1: Validation error in terms of map units and generations of dispersal for `Locator` runs in simulations with 450 training samples and 100,000 SNPs.

Data	SNPs	method	mean error	median error
Simulation	100	Locator	6.47	5.59
Simulation	100	SPASIBA	5.74	4.04
Simulation	1000	Locator	2.50	2.54
Simulation	1000	SPASIBA	1.88	1.70
Simulation	10000	Locator	1.85	1.68
Simulation	10000	SPASIBA	1.84	1.75
Simulation	100000	Locator	1.72	1.52
Anopheles	100	Locator	564.72	103.07
Anopheles	100	SPASIBA	690.95	243.47
Anopheles	1000	Locator	137.28	42.63
Anopheles	1000	SPASIBA	453.83	302.87
Anopheles	10000	Locator	70.16	9.77
Anopheles	10000	SPASIBA	364.70	250.05
Anopheles	100000	Locator	56.91	7.65
Anopheles	100000	SPASIBA	245.44	216.75

Table S2: Mean and median prediction error for `Locator` and `SPASIBA` run on simulations and *Anopheles* data as shown in Figure 3. Error is in terms of map units for simulated data (total landscape width = 50) and in kilometers for *Anopheles*.

Species	kernel peak error (km)	centroid error (km)
	median (90% interval)	
Plasmodium falciparum	16.92 (1.357 - 892.751)	218.98 (16.186 - 978.691)
Anopheles gambiae/coluzzii	5.69 (0.52 - 654.66)	36.03 (2.27 - 1579.79)
Homo sapiens	84.97 (4.42 - 2826.33)	452.62 (37.67 - 2178.94)

Table S3: Test error for windowed analyses of empirical datasets using the location with highest kernel density and the centroid of per-window predictions, as *median (90% interval)*.

Figure S1: Example training and validation loss histories. The first three epochs (with very high loss) were excluded from the plot to improve axis scaling.

Figure S2: Validation error for `Locator` runs on simulations with varying dispersal distance, expressed in generations of mean dispersal (test error divided by mean dispersal distance per generation). A: Error for runs with 100,000 SNPs and varying numbers of training samples. B: Error for runs with 450 training samples and varying number of SNPs.

Figure S3: Comparison of cross-validation performance on the ag1000g dataset using SNPs from chromosome 3R, under varying network architectures and numbers of SNPs. Boxplots show the distribution of Euclidean distance between the true and predicted locations of validation samples across 10 replicate training runs. Network shapes are described on the horizontal axis as "layers × width". Though 2-layer networks are typically the least accurate, no single architecture provides consistently better performance across datasets of different sizes. Missing networks required over 12GB GPU RAM.

Figure S4: Predicted and true locations for 8 individuals simulated in a population with an expected dispersal rate of 0.63 map units / generation, using a set of 10,000 randomly sampled SNPs. Here we generate predictions (black points) from bootstrap samples of the complete genotype matrix (in contrast to using separate sets of SNPs extracted from windows as used for figures in the main text). This could be useful for low-density genotyping data from approaches like ddRADseq, or when users lack a reference genome for windowing. In this setting we see that the distribution of predictions is much smaller than fitting individual windows.

Figure S5: Predicted (colored points) and true (black circles) locations for Locator and SPASIBA on the ag1000g dataset. Number of SNPs per run is shown on the right. Both methods were run on randomly selected SNPs with minor allele count > 2 from the first five million base pairs of chromosome 2L.

Figure S6: Centroid prediction error as a function of within-host diversity (F_{WS}) for the *Plasmodium falciparum* dataset. F_{WS} scales from 0 (maximum complexity) to 1 (minimum complexity). The blue line shows a linear regression ($p < 2.2e-16$, $R^2 = 0.006$, $slope = 148.1$). High within-host diversity does not appear to explain outliers in Locator's prediction error.

Figure S7: Performance on 10,000 SNPs from chromosome 2L in the ag1000g phase 1 dataset when all samples from localities in the true country are dropped from the training set.

Figure S8: Performance on 10,000 SNPs from chromosome 2L in the ag1000g phase 1 dataset when all samples from the true locality are dropped from the training set.

Figure S9: Outliers in windowed `Locator` analyses identify genomic regions enriched for admixed ancestry. A: Windowed `Locator` predictions for Maya sample HGDP00871. B: PCAs of all HGDP samples run on SNPs extracted from windows with predicted locations in western Europe (left) and west Africa (right). In these windows sample HGDP00871 (open points) clusters with individuals from region predicted by `Locator` in PC space, rather than with other genomes from the Americas.

Figure S10: Mean test error for HGDP samples in 10-megabase windows. Triangles show approximate centromere locations.

Figure S11: Mean test error for HGDP samples in 10-centimorgan windows. Triangles show approximate centromere locations.

Figure S12: Distributions of centroid prediction error across samples. Despite differences in error among genomic windows (Figure S10,S11), error in the mean genome-wide predicted location is very similar when using megabase (top) or centimorgan (bottom) windows.

Figure S13: Distributions of prediction error across windows when using megabase- versus centimorgan-based windows.