Computational characteristics of the striatal dopamine system

described by reinforcement learning with fast generalization

Short title: Computational characteristics of the striatal dopamine system

Yoshihisa Fujita[1]*, Sho Yagishita[2,3], Haruo Kasai[2,3], and Shin Ishii[1,3]

[1] Integrated Systems Biology Laboratory, Department of Systems Science, Graduate

School of Informatics, Kyoto University, Yoshida-Honmachi 36-1, Sakyo-ku, Kyoto

606-8501, Japan

[2] Laboratory of Structural Physiology, Center for Disease Biology and Integrative

Medicine, Faculty of Medicine, University of Tokyo, Bunkyo-ku, Tokyo 113-0033,

Japan

[3] International Research Center for Neurointelligence, Bunkyo-ku, Tokyo 113-0033,

Japan

*Corresponding author

E-mail: fujita.yoshihisa.4s@kyoto-u.ac.jp

Abstract

Generalization enables applying past experience to similar but nonidentical situations. Therefore, it may be essential for adaptive behaviors. Recent neurobiological observation indicates that the striatal dopamine system achieves generalization and subsequent discrimination by updating corticostriatal synaptic connections in differential response to reward and punishment. To analyze how the computational characteristics in this system affect behaviors, we proposed a novel reinforcement learning model with multilayer neural networks in which the synaptic weights of only the last layer are updated according to the prediction error. We set fixed connections between the input and hidden layers so as to maintain the similarity of inputs in the hidden-layer representation. This network enabled fast generalization, and thereby facilitated safe and efficient exploration in reinforcement learning tasks, compared to algorithms which do not show generalization. However, disturbance in the network induced aberrant valuation. In conclusion, the unique computation suggested by corticostriatal plasticity has the advantage of providing safe and quick adaptations to unknown environments, but on the other hand has the potential defect which can induce maladaptive behaviors like delusional symptoms of psychiatric disorders.

Author summary

The brain has an ability to generalize knowledge obtained from reward- and punishment-related learning. Animals that have been trained to associate a stimulus with subsequent reward or punishment respond not only to the same stimulus but also to resembling stimuli. How does generalization affect behaviors in situations where individuals are required to adapt to unknown environments? It may enable efficient learning and promote adaptive behaviors, but inappropriate generalization may disrupt behaviors by associating reward or punishment with irrelevant stimuli. The effect of generalization here should depend on computational characteristics of underlying biological basis in the brain, namely, the striatal dopamine system. In this research, we made a novel computational model based on the characteristics of the striatal dopamine system. Our model enabled fast generalization and showed its advantage of providing safe and quick adaptation to unknown environments. By contrast, disturbance of our model induced abnormal behaviors. The results suggested the advantage and the shortcoming of generalization by the striatal dopamine system.

Introduction

Animals' survival with reward-seeking behaviors should be accompanied with risks. Outcome observation resulting from the pairing of a current state and a taken action could be a clue to ensure optimal behaviors, but it may be associated with substantial energy consumption and aversive experience. Such a learning process is inefficient and even harmful, especially when animals are required to adapt to new environments. Animals instead generalize their past experience for predicting outcome, even in novel situations. Generalization may be essential for efficient adaptive behaviors, whereas generalization to an abnormal extent can be maladaptive and is implicated in psychiatric disorders [1-3].

Psychological studies have investigated generalization by using the conditioning paradigm in behavioral experiments [4]. If a response has been established by a stimulus paired with an outcome (i.e., reward or punishment), then resembling stimuli evoke similar responses. This "law of effect" depends on the extent that the second stimulus resembles the first stimulus, and is termed "stimulus generalization" [4, 5]. Discrimination can then occur if the first stimulus is paired with a reward but the resembling stimulus is paired with no reward; as a consequence, only the first stimulus elicits a response. How the brain establishes stimulus generalization has been explained, based on artificial neural networks [6-9]. Previous studies [6-9] have focused on the stimulus–response relationship, although generalization can be incorporated in the interaction between individuals and the environment. Reinforcement learning involves this interaction and is used as a model of reward-driven learning [10-12]. In the field of artificial intelligence, reinforcement learning in combination with artificial neural networks achieves a high performance, which suggests the contribution of generalization to adaptive behaviors [13]. However, neurobiological evidence indicates that the neural system has a unique computation for reward-driven learning and

generalization, compared to algorithms used for artificial intelligence [14]. This fact

raises the question regarding how its computational characteristics differ from those of

ordinary algorithms. Advantages and shortcomings should exist with regard to adaptive

behaviors.

Theoretical attempts have focused on separate systems that process positive and

negative values in the brain [15-18], which is not adopted when using ordinary

reinforcement learning. Dopamine and its main target, the striatum, have central roles in

reward- and punishment-related learning [19]. Dopamine neurons show a positive

response to a greater-than-expected reward and a negative response to a

less-than-expected reward, which indicates that dopamine codes reward prediction error

[20]. The striatum receives dopamine signals and glutamatergic input from the cortex

and thalamus [21]. Dopamine modulates synaptic plasticity between the cortex and the

striatum during reward-related learning [22]. The striatum is primarily composed of

spiny projection neurons (SPNs), which can be divided into SPNs that primarily express

the dopamine D1 receptor (D1-SPNs) and SPNs that express the dopamine D2 receptor

(D2-SPNs) [23]. The D1-SPNs respond to the phasic increase in dopamine [24],

whereas D2-SPNs may respond to the phasic decrease in dopamine [25]. Perturbing the

activity of the D1- and D2-SPNs inhibits reward learning and punishment learning,

respectively [25]. The advantages of having such separate systems have been discussed

in computational studies [26, 27]. One study [26] demonstrated an advantage in learning

reward uncertainty. Another study [27] showed the possibility of achieving safe

behaviors.

However, recent neural recordings and optogenetic manipulations provide some

data that suggests different roles of SPNs from those in existing models [28]. Our new

experiments with a classical conditional task found that D1- and D2-SPNs are

differentially responsible for stimulus generalization and discrimination (Yagishita,

Kasai and others, unpublished). The same series of experiments revealed that stimulus

generalization/discrimination occurred solely by dopamine-dependent plasticity of SPN

spines that receive cortical inputs, which implies that updating in other connections

(e.g., intracortical synaptic connections) would be minor. These observations suggest

learning rules that update the synaptic weights of the last layer in a multilayer neural

network—in our case, corticostriatal connections—are essential. Such learning rules

actually enable remarkably fast learning in reservoir computing (RC) and extreme

learning machine (ELM) [29-31]. Reservoir computing and ELM are neural networks

that train only their readouts (i.e., the last layer connections); RC has recurrent

connections, whereas ELM does not.

In this study, we propose a novel reinforcement learning model that reproduces stimulus

generalization and discrimination, while accounting for the physiological characteristics

of striatal SPNs. We used a neural network for value estimation and introduced fixed

connections between the input and hidden layers, as in RC and ELM. Reservoir

computing has the potential for context-dependent value estimation because of its

recurrent connections. However, for simplicity, we adopted a feed-forward neural

network with the same architecture as ELM. The extent of stimulus generalization

depends on the similarity of stimuli; therefore, we did not use random and fixed

connections implemented in ordinary ELM. We instead set the fixed connections so as

to maintain the similarity of inputs in the hidden-layer representation. In addition, we

introduced connections, the weights of which are separately updated by positive and

negative reward prediction errors, while taking into account the differential roles of D1-

and D2-SPNs in the striatum. This neural network enabled generalization in a quick

manner. We named this model "Outspread Valuation for Reward Learning and

Punishment Learning" ("OVaRLAP"). The OVaRLAP model achieved safe and

efficient exploration in painful grid-world navigation tasks. This achievement suggested

that quick generalization contributed to safe and efficient reward-seeking and

pain-avoiding. We also tested disturbed OVaRLAP to examine whether abnormal

generalization underlies maladaptive behaviors, as implied in psychological and

psychiatric studies [3, 32, 33]. The OVaRLAP method with noisy generalization and

impaired discrimination induced aberrant valuation, after repeating reward-seeking

behaviors. These results showed that the unique computation suggested by the striatal

dopamine system enabled safe and efficient exploration, but on the other hand had the

potential defect which can cause maladaptive behaviors.

Methods

We developed OVaRLAP to analyze how the computational characteristics in the

striatal dopamine system affect behaviors. We first evaluated OVaRLAP in a spatial

navigation task in painful grid-worlds by comparing its performance with those of two

other representative algorithms (Fig 1A-1B). We then examined behaviors of disturbed

OVaRLAP in a spatial navigation task in a painless grid-world (Fig 1C-1D).

Fig 1. The architecture of TD learning algorithms and the task. (**A**) Schematic

diagrams of OVaRLAP (left), simple TD learning (middle), and MaxPain (right). In

OVaRLAP, the value prediction is conducted using a neural network with fixed

connections (gray arrows) and distinct connections updated by positive and negative TD

errors (red and blue arrows, respectively). In our implementations of simple TD learning

and MaxPain, the predicted value is represented by lookup tables in which the state, s_k,

indicates a position (x,y) in the two-dimensional grid-world. (**B**) The navigation task

in the two-dimensional grid-world. The nongray squares and gray squares indicate

passable and not passable, respectively. The black square is the starting position, and

the blue and yellow squares are the goals at which the agent receives the positive

rewards of 1 and 2, respectively. When the agent receives a positive reward, an episode

ends so that the agent restarts the task from the starting position. If an agent hits a wall

(i.e., a not passable square), it receives a negative reward of −1, but continues the task

by staying at the same square. (**C**) Schematic diagram of OVaRLAP in which updating

connections, based on the negative TD error (blue connections), are impaired. In
addition, noise was introduced to induce an anomaly in the initialization of the fixed
connections between the input and the hidden layers (for the details of noise here, see
the Methods section). (**D**) The navigation task in the two-dimensional grid-world. The
black square is the starting position. The green squares are the goals at which the agent
receives a positive reward of 1. If the agent receives a positive reward, a single episode
ends, and a new episode restarts from the starting position. In this task, when the agent
hits a wall (i.e., a gray square), no negative reward is given, and the agent remains at the
same square.

Model description of OVaRLAP

A neural network was used for value estimation in OVaRLAP. It consists of an input

layer, a hidden layer, two pre-output neurons, and an output neuron (Fig 1A, left). The

input represents the state at discretized time, t. We applied our learning method to two

types of navigation tasks, both in two-dimensional grid-worlds, in which position (x,y),

$x \in \{1,...,20\}$, and $y \in \{1,...20\}$ were simply represented by a two-dimensional index

function:

185
$$I_{ij}(x,y,t) = \begin{cases} 1, & \text{if } i = x \text{ and } j = y \\ 0, & \text{otherwise.} \end{cases}$$

The input signals were transformed by fixed connections into hidden-layer

activity patterns. We set the number of hidden-layer neurons and the weight of fixed

connections so as to reproduce the shape of the generalization gradient, which has been

commonly observed across various species, behavioral contexts, and sensory modalities

[4]. The number of hidden-layer neurons was set to 900. The hidden-layer activity $h_k($

$x,y,t)$ for $k = 1,...,900$ was given by

192
$$h_k(x,y,t) = \sum_i \sum_j M_{ij,k} I_{ij}(x,y,t),$$

193   in which $M_{ij,k}$ is the weight of the fixed connection from the input-layer neuron (i,j)

194   to the hidden-layer neuron k. Based on the definition of $I_{ij}(x,y,t)$, $h_k(x,y,t)$ was also

195   given by

196
$$h_k(x,y,t) = M_{xy,k}$$

in which (x,y) is the agent's position at time t.

For the generalization capability, we assumed the hidden-layer representation

becomes similar when the input signal is similar. In our case, the values of $h_k(x_1,y_1,t)$

and $h_k(x_2,y_2,t)$ are similar if position (x_1,y_1) is close to position (x_2,y_2), based on

Euclidian distance. To reflect this request, we set the fixed connections $M_{ij,k}$ to follow

the two-dimensional Gaussian function:

203
$$M_{ij,k} = \frac{\exp\left\{-\left(\left(\frac{(i-a_k)^2}{2\sigma_k^2}\right) + \left(\frac{(j-b_k)^2}{2\sigma_k^2}\right)\right)\right\} + \varepsilon_{ij,k}}{D}$$

in which D is the number of the input-layer neurons used for normalization ($D = 400$,

because of the 20×20 grid-worlds); a_k and b_k denote the center and are set as a_k

$\in \{1,...,20\}$, $b_k \in \{1,...,20\}$, and $20(a_k - 1) + b_k = ceil(400k/900)$ so that the center

location was linearly correlated in the 2D space; σ_k^2 is the variance sampled from a

log-normal distribution, $\sigma_k^2 \sim \text{LogN}(-0.7, 0.7)$; and $\varepsilon_{ij,k}$ is the noise, as defined later.

The distribution of σ_k^2 resulted that the hidden-layer neurons ranged from neurons that

responded to specific input to neurons that responded to a wide range of input. This

setting is consistent with physiological observations [34]. The noise $\varepsilon_{ij,k}$ is unnecessary

in the normal case; however, we introduced it for the purpose of analyzing the effect of

abnormal perturbation in OVaRLAP (Fig 1C). When simulating abnormal perturbation,

the noise $\varepsilon_{ij,k}$ was added by using the following formulas:

215
$$\text{P}\left(\varepsilon_{k,ij} = 0.5\right) = \rho$$

216   and

217
$$P\left(\varepsilon_{k,ij}=0\right)=1-\rho.$$

218 No noise apparently exists if ρ is zero. This noise was initially introduced but not

219 changed through the learning process. In our simulation experiment, we applied

220 different patterns of noise $\varepsilon_{ij,k}$ under a specific value of ρ, and examined the collective

221 behaviors of the learning.

222  The two pre-output neurons then received signals from the hidden-layer

223 neurons. For $m=1,2$, the activities of the pre-output neurons $d_m(x,y,t)$ are given by

224
$$d_m(x,y,t)=\sum_k w_{m,k}(t)h_k(x,y,t),$$

225 in which $w_{m,k}(t)$ is the weight of the connection from hidden-layer neuron k to the

226 pre-output neuron m. In this instance, $d_1(x,y,t)$ and $d_2(x,y,t)$ represented the

227 positive and negative values, respectively. The final output of the network $v(x,y,t)$

228 integrated these values, as follows:

229
$$v(x,y,t)=d_1(x,y,t)-d_2(x,y,t).$$

230  During the interaction between the agent and the environment, the connection

231 weights $w_{m,k}(t)$ were updated, depending on the prediction error, δ. To calculate δ, we

232 used an action-value function $Q(s,a,t)$ for state s and action a at time t [35]. We

233 defined $Q(s,a,t)$ by using the output of the network, as follows:

234
$$Q(s,a,t)=v(x',y',t),$$

235 in which $s=(x,y)$, $a=(\Delta x,\Delta y)$, $x'=x+\Delta x$, and $y'=y+\Delta y$. In our

236 navigation tasks, $(\Delta x,\Delta y)=(1,0)$, $(-1,0)$, $(0,-1)$, or $(0,1)$, if the action was

237 effective. The prediction error δ was given by

238
$$\delta(t)=r(s,a)+\gamma Q(s',a',t)-Q(s,a,t),$$

239 in which $r(s,a)$ is the actual reward, s' denotes the state at time $t+1$, a' denotes the

240 action at time $t+1$, and γ is the discount factor. We used temporal difference (TD)

learning for the action-value function (i.e., state–action–reward–state–action [SARSA])

[36] because the agent needed to remain at the same square after an ineffective action

(i.e., hitting a wall). If we used a simple TD for the state-value function, such ineffective

actions would introduce noise to the value learning. The connection weight $w_{1,k}(t)$

was updated only when $\delta(t)$ was positive, and $w_{2,k}(t)$ was updated only when $\delta(t)$

was negative. In the actual implementation, the updating rules were as follows:

247
$$w_{1,k}(t+1) = \begin{cases} w_{1,k}(t) + \dfrac{\alpha_1 \delta(t) h_k(x',y',t) d_1(x',y',t)}{N_1(x',y',t)}, & \text{if } \delta(t) > 0 \\ w_{1,k}(t), & \text{otherwise,} \end{cases}$$

248 and

249
$$w_{2,k}(t+1) = \begin{cases} w_{2,k}(t) + \dfrac{\alpha_2[-\delta(t)] h_k(x',y',t) d_2(x',y',t)}{N_2(x',y',t)}, & \text{if } \delta(t) < 0 \\ w_{2,k}(t), & \text{otherwise,} \end{cases}$$

250 in which α_1 and α_2 are the learning rates and $N_1(x,y,t)$ and $N_2(x,y,t)$ are the

251 normalization terms, which are given by

252
$$N_m(x,y,t) = d_m(x,y,t) \sum_k h(x,y,t)^2.$$

253 for $m = 1,2$. These normalization terms are introduced to make sure that

254
$$Q(s,a,t+1) = \begin{cases} Q(s,a,t) + \alpha_1 \delta(t), & \text{if } \delta(t) > 0 \\ Q(s,a,t) + \alpha_2 \delta(t), & \text{otherwise.} \end{cases}$$

255 **Algorithms for comparison**

256 We also implemented two representative algorithms to compare with the OVaRLAP

257 model. One algorithm was simple TD learning [35] (Fig 1A, middle); in our particular

258 case, the algorithm was SARSA. In our implementation, a value function of states, v_s

259 (x,y,t), was represented as a look-up table and updated as follows:

260
$$v_s(x,y,t+1) = v_s(x,y,t) + \alpha_s \delta_s(t)$$

261 in which α_s is the learning rate and δ_s is the prediction error, called the "TD error."

262 This error is given by

263
$$\delta_s(t) = r(s,a) + \gamma_s Q_s(s',a',t) - Q_s(s,a,t)$$

264 in which γ_s is the discount factor. The action-value function, $Q_s(s,a,t)$, is given by

265
$$Q_s(s,a,t) = v_s(x',y',t).$$

266  The other algorithm is the MaxPain algorithm [27] (Fig 1A, right). This method

267 is characterized by its distinct systems for the learning values for reward and pain (or

268 punishment). The policy is dependent on the linear combination of the two value

269 functions. In our implementation, we slightly modified the originally proposed MaxPain

270 algorithm to make it comparable with the other methods, while maintaining the essential

271 idea of MaxPain.

272  First, we used state-value functions of states $v_r(x,y,t)$ and $v_p(x,y,t)$, and their

273 linear combination $v_L(x,y,t)$, to define the action-value functions $Q_r(s',a',t)$, Q_p

274 (s',a',t), and $Q_L(s',a',t)$, as follows:

275
$$Q_r(s,a,t) = v_r(x',y',t),$$

276
$$Q_p(s,a,t) = v_p(x',y',t),$$

277 and

278
$$Q_L(s,a,t) = v_L(x',y',t).$$

279 Second, we set the linear combination $v_L(x,y,t)$ without normalization, as follows:

280
$$v_L(x,y,t) = v_r(x,y,t) - v_p(x,y,t).$$

281 The couple of state-value functions were implemented as look-up tables and updated as

282
$$v_r(x,y,t+1) = v_r(x,y,t) + \alpha_r \delta_r(t)$$

283 and

284
$$v_p(x,y,t+1) = v_p(x,y,t) + \alpha_p \delta_p(t)$$

285 in which α_r and α_p are the learning rates for reward and pain, respectively, and δ_r

286 and δ_p are the prediction errors for reward and pain, respectively. The prediction errors

287 were calculated, depending on whether the reward observation was positive or negative,

288 as follows:

289
$$\delta_r(t) = \varphi(r(s,a)) + \gamma_r Q_r(s',a',t) - Q_r(s,a,t)$$

290 and

291
$$\delta_p(t) = \varphi(-r(s,a)) + \gamma_p Q_p(s',\underset{a'}{\arg\min}\left(Q_L(s',a',t)\right),t) - Q_p(s,a,t)$$

in which $\varphi(z) = \max(z,0)$ and γ_r and γ_p are the discount factors. These update

rules were the same as those in the original study. The pain prediction error, δ_p, was

used for maximizing future pain (i.e., for predicting the worst case).

Action selection

We used the softmax behavioral policy consistently for the three methods. It depends on

the value function $\tilde{v}(x,y,t)$ [i.e., $v(x,y,t)$ for OVaRLAP, $v_s(x,y,t)$ for the simple TD

learning, and $v_L(x,y,t)$ for MaxPain]. The probability that the agent selects an action a

at position (x,y) at time t is given by

301
$$\pi(a\,|\,x,y,t) = \frac{\exp\,(\tilde{v}(x',y',t)/\tau)}{\sum_c \exp\,(\tilde{v}(x_c,y_c,t)/\tau)}$$

302 in which x' and y' denote the new state after selecting action a, x_c and y_c denote

303 the new state after selecting one of the possible actions, and τ is the temperature that

304 controls the trade-off between exploration and exploitation. In our implementation, we

305 used the common $\tau = 0.5,$ for the three learning methods.

Painful grid-world navigation task

The purpose of this task was to navigate from the starting position to either of the two goals, while avoiding hitting the wall. Possible actions at each time step were moving one step north, south, east, and west. For example, if the agent moved one step north, $(\Delta x, \Delta y) = (0,1)$. Two goals exist with reward of 1 or 2. If the agent hits a wall, then it received a negative reward of -1 and remained at the same position. This was an exceptional case. In other cases, the agent could by necessity move to the next square. An episode began when the agent started from the starting position and ended when the agent reached either of the goals. The agent repeated such learning episodes.

A single run consisted of 500 learning episodes, after initializing the value function so that the value for each state was zero. We ran 50 separate runs each for OVaRLAP, simple TD learning, and MaxPain with a single grid-world configuration. We conducted five simulation experiments for each of which we used a grid-world with a consistent character but different configuration. The structure of each grid-world is shown in Fig 1B and in S1 Fig. We set the metaparameters for each algorithm, as follows: $\rho = 0$, $\alpha_1 = \alpha_2 = 0.1$, and $\gamma = 0.95$ for OVaRLAP; $\alpha_s = 0.1$ and $\gamma_s = 0.95$ for simple TD learning; and $\alpha_r = \alpha_p = 0.1$, $\gamma_r = 0.95$, and $\gamma_p = 0.5$ for MaxPain. OVaRLAP and MaxPain are extended algorithms, based on simple TD; therefore, they use common metaparameters with simple TD, when they could share them.

The five configurations in S1 Figure were generated, based on the following rules, while avoiding symmetric or similar structures. Each configuration had a wide passage from which a narrow passage branched off. These passages had fixed widths and lengths. The starting position and the goal with a reward of 1 were at either end of a wide passage. A goal with reward of 2 was at the end of a narrow passage. S1 Fig. legend has more details of the rules.

Grid-world navigation task for disturbed OVaRLAP

The purpose of this task was to navigate from the starting position to either of four

goals. The structure of the grid-world is shown in Fig 1D. Possible actions at each time

step were moving one step north, south, east, and west. Multiple goals existed, each of

which gave a reward of 1. The topic in this study was not on risk aversion; therefore, we

did not apply a negative reward to the actions that resulted in hitting a wall (i.e., no

pain). The agent simply remained at the same position after hitting a wall. Even in this

no pain setting, the agents after reinforcement learning likely avoid wall hits, due to the

discount factor in the value functions. An episode began when the agent moved from

the starting position and ended when the agent reached one of the four goals. A single

run consisted of a total of 40,000 time steps (i.e., 378.8 learning episodes on average)

after the value function initialization at the onset of the first learning episode. We ran 50

separate runs for OVaRLAP for each of the following settings: normal or no update for

a negative TD error (i.e., "intact" or "impaired") and with or without noise in the fixed

connections (i.e., "noised" or "unnoised"). We set the metaparameters, as follows:

$\rho = 0.005$ for the noised case and $\rho = 0$ for the unnoised case; $\alpha_1 = 0.1$; $\alpha_2 = 0.1$

for the intact setting (which was the same as in the previous experiment) and $\alpha_2 = 0$

for the impaired setting; $\gamma = 0.8$; and $\tau = 0.5$. In the noised setting, the noise, $\varepsilon_{ij,k}$,

was generated independently for each run and was fixed within each run.

Results

The behavior of OVaRLAP

We evaluated OVaRLAP in a spatial navigation task in painful grid-worlds by

comparing its performance with those of simple TD learning and MaxPain [27]. These

algorithms are schematically shown in Fig 1A. On account that OVaRLAP utilizes a

fixed neural network (gray arrows in Fig 1A, left) for the preprocessing of the value

learning network (blue and red arrows in Fig 1A, left), it achieves stimulus

generalization, based on the similarity of states (Fig 2, left). By contrast, the other two

algorithms, which have look-up tables, show no stimulus generalization (Fig 2, middle

and right). The task in this study was to seek rewarded goals while avoiding painful

wall hits in which the agent had to manage the trade-off between obtaining a reward and

avoiding pain (Fig 1B). We used five different grid-worlds, each of which had a safe but

lowly rewarded goal and a risky but highly rewarded goal (S1 Fig).

Fig 2. State values after a single update. The value function is updated after receiving

a positive reward of 1 once with OVaRLAP (left), simple TD learning (middle), and

MaxPain (right) at the center of a two-dimensional grid-world in Fig 1B.

Figure 3A–3C show the average learning curves at each episode over 50

independent runs for the grid-world shown in Fig 1B. The reward per step of the

OVaRLAP agent was higher than that of the MaxPain agent, but it did not exceed that

of the simple TD learning agent (Fig 3A). Compared to the other agents, the OVaRLAP

agent reached each of the goals with a smaller number of steps in the early learning

phase (Fig 3B). After 100 learning episodes, all three agents showed a similar number

of steps to reach either of the goals. With regard to pain aversion, the OVaRLAP agent

also showed quick learning. The OVaRLAP agent exhibited smaller numbers of wall

hits in the early learning phase than did the other agents. However, after 50 learning

episodes, the number of wall hits of the OVaRLAP agent was comparable to that of the

simple TD learning agent (Fig 3C). By contrast, the MaxPain agent first hit the walls as

many times as the simple TD learning agent, but the number of wall hits then quickly

decreased. The OVaRLAP agent showed its characteristic performance in the five

grid-worlds with different configurations (Fig 3D–3F). These results suggested that the

OVaRLAP agent could learn a reward approach and pain aversion in a very efficient

manner owing to its generalization capability, whereas it was inferior to the simple TD

in long-term reward learning and to MaxPain in long-term pain aversion.

Fig 3. Average performance of OVaRLAP, the simple TD learning, and MaxPain

in the painful grid-world navigation task. (**A**) The average reward per step, (**B**) the

average number of steps to either of the two goals, and (**C**) the average number of wall

hits, based on the three types of agents after each number of learning episodes on the

horizontal axis. The grid world shown in Fig 1B was used. The number of steps to

either of the two goals and the number of wall hits for the first 50 learning episodes are

magnified in the top right insets of panels B and C, respectively. Each average (on the

vertical axis) was taken over 50 separate runs and then smoothened as moving averages

over nearby 11 episodes (on the horizontal axis). The thick lines represent the moving

averages and the shadow areas indicate the moving standard deviations. (**D–F**) The

average performance over five simulation experiments, each of which used a grid-world

with different configurations. The grid world shown in Fig 1B and its variants were

used (S1 Fig presents the details of the variants.). (**D**) The average reward per step, (**E**)

the average number of steps to either of the two goals, and (**F**) the average number of

wall hits, based on the three types of agents after 5 learning episodes and 500 learning

episodes, are shown. Each bar indicates the average of five values (i.e., for five different

grid-world configurations), each of which is the average over 50 separate runs. Each

error bar represents the standard deviation over the five values.

Figure 4 shows how the value function was developed by using the three

methods, in which OVaRLAP showed unique profiles (Fig 4, top). First, the values of

positions close to the walls decreased, as did the values of the positions of the walls.

This generalization constructed a safe passage to the lowly rewarded goal and

simultaneously a hazard to approach the risky, but highly rewarded goal, after only five

learning episodes. This value hazard completely disappeared after 500 episodes because

the reward learning had been propagated to the squares on the passage to the

high-reward goal. Thus, quick pain learning was essential for risk aversion and

conservative reward-seeking in the early learning stage.

Fig 4. Transition of the value function for each model in the grid-world navigation

task. The average state values over 50 separate runs after 5, 30, 150, and 500 learning

episodes for OVaRLAP (top row), simple TD learning (middle row), and MaxPain

(bottom row), when applied to the painful grid-world navigation task shown in Fig 1B.

For MaxPain, the result of the subtraction of the value function for the pain from the

value function for the positive reward (i.e., the main factor for decision-making) is

displayed.

The simple TD learning algorithm did not construct any value hazard to the

high-reward goal during its learning process, because no special system existed for pain

learning (Fig 4, middle). The MaxPain algorithm also produced hazards on the passage

to the high-reward goal (Fig 4, bottom). In contrast to OVaRLAP, the hazard

progressively increased as the learning proceeded and was never flattened owing to its

strong ability toward pain learning. For this reason, the MaxPain algorithm persistently

maintained low values on the way to the high-reward goal.

The effect of a disturbed OVaRLAP

We next examined how the learning behaviors of OVaRLAP were disturbed by

disabling weight updating by negative TD errors and introducing noise to the fixed

network (Fig 1C). The generalization after obtaining a reward became a little noisy

because of the noise introduction (Fig 5A). We applied this disturbed OVaRLAP to a

grid-world navigation task without pain (Fig 1D). We tested each of the following

two-by-two settings: normal or no update for the negative TD error (i.e., "intact" or

"impaired"), and with or without noise in the fixed network (i.e., "noised" or

"unnoised").

Fig 5. The TD learning task for disturbed OVaRLAP. (A) The value function is

updated after reaching the left-bottom goal of the grid-world shown in Fig 1D once with

OVaRLAP without noise (left) and with noise (right). (**B**) The value function after 120

learning episodes in a single run for OVaRLAP with intact and impaired updates (top

and bottom rows, respectively) for the negative TD error with and without noise (right

and left columns, respectively) in the fixed connections. (**C**) The maximum value and

its position in the value function after a total of 40,000 time steps (378.8 learning

episodes on average) in each run. Each panel shows the maximum values in 50 separate

runs for OVaRLAP under the following settings: intact or impaired updates (top or

bottom row, respectively) for the negative TD error, and without noise or with noise

(left or right column, respectively) in the fixed connections. In the noisy case, the noise

was independently introduced to the initialization of the fixed connections for each run.

The impaired noised agent acquired an aberrant value function: it increased the

value for a specific position distant from the goals, as if the position would give a

positive reward (Fig 5B, bottom right). The value function of the intact noised agent

was slightly noisy (Fig 5B, top right), but nearly the same as that of the intact unnoised

agent (Fig 5B, top left). The impaired unnoised agent made the values around the goals

higher than those of the intact agents, but the values for positions distant from the goals

remained low (Fig 5B, bottom left).

We ran 50 runs for each setting to confirm the reproducibility. For the noised

agent, a different pattern of noise was applied in each run. Fig 5C presents the

maximum value and its position in the value function after 40,000 steps in each run. The

intact agents always established the maximum values at the positions of goals and

maintained them consistent to the actual amount of the rewards (Fig 5C, top row). The

maximum values of the impaired unnoised agent were higher than the actual amount of

the rewards (Fig 5C, bottom left). Their positions were not necessarily the same as the

actual goals, but they were, at most, two steps away from the goals. In contrast to these

three agents, the impaired-noised agent yielded maximum values that were quite apart

from the actual goals (Fig 5C, bottom right). Their values were higher than the actual

amount of rewards and were sometimes exceedingly high.

Discussion

In this study, we proposed a novel reinforcement learning model named OVaRLAP to

analyze how the computational characteristics in the striatal dopamine system affect

behaviors. The OVaRLAP model reproduced stimulus generalization and discrimination

for reward learning and for punishment learning. If reward learning precedes in a

generalized manner, then discrimination is achieved by subsequent value reshaping,

based on punishment learning or on the omission of an unpredicted reward. By contrast,

if punishment learning precedes and is generalized, then subsequent reward learning or

the omission of unexpected punishment causes a discrimination. In the navigation task

in the painful grid-worlds (Figs 3 and 4), pain was preceded because it was relatively

frequently observed, and the situation was then in the latter case. By contrast, in the

painless grid-world (Fig 5), the former case appeared.

The OVaRLAP model enabled safe and efficient exploration in the painful

grid-world navigation task. The transition of the value function for the OVaRLAP agent

shows how stimulus generalization and discrimination contributed to managing the

trade-off between reward-seeking and risk aversion (Fig 4, top).

First, punishment learning due to hitting walls was generalized quickly, as

shown in the value function after five episodes. It led to a preference for the center of

the passage (i.e., risk aversion). The OVaRLAP agent indeed first showed fewer wall

hits than did the simple TD learning and MaxPain agents (Fig 3C and 3F). It contributed

to reducing the number of steps to reach either of the goals in the early learning phase

(Fig 3B and 3E). The OVaRLAP agent thereafter increased the values of positions close

to the walls. This transition indicated that the agent discriminated between the safe and

painful positions. This discrimination increased the tendency to reach the high-reward

goal. In short, stimulus generalization of punishment learning induced risk aversion,

followed by discrimination for switching to reward-seeking. The simple TD learning

agent did not show risk aversion (Fig 4, middle). Its value function was optimized to

maximize future reward, which is consistent with its high reward per step (Fig 3A and

3D). The MaxPain agent showed strong risk aversion, based on its separate value

learning system to expect future pain (Fig 4, bottom row). It achieved very few wall hits

(Fig 3B and 3E), but meanwhile, it maintained risk aversion and low values on the way

to the high-reward goal, which corresponded to a lower reward per step, compared to

the other agents (Fig 3A and 3D).

Stimulus generalization and discrimination were effective in safe and efficient

exploration; however, its dysfunction may induce aberrant learning behaviors, as

demonstrated by the disturbed OVaRLAP (Fig 5). The impaired update for the negative

TD error in combination with the noise in the fixed connections induced aberrant

valuation. The value increased by noisy stimulus generalization was not reshaped by

discrimination because of the impairment of the punishment learning. A single update

of the value was only slightly affected by the noisy stimulus generalization (Fig 5A);

however, as the number of arrivals to the actual goals increased, such aberrant updates

of the value function would have allotted abnormally high values to some positions that

were actually of no reward (Fig 5B–5C).

The structure of OVaRLAP gives insight into the neurobiological basis of

stimulus generalization and discrimination. The two pre-output neurons separately

responded to positive and negative prediction errors so as to update the connections

between the hidden-layer neurons and the corresponding pre-output neuron. This hybrid

learning system exhibits good correspondence to the striatal dopamine system in which

D1- and D2-SPNs differentially respond to dopamine so that the connections between

the cortex and the striatal SPNs are differently modulated [22, 24, 25]. Transforming the

input into the hidden-layer activity is an approximation of the process by which an

external stimulus and the internal state are encoded into neural activity patterns of the

cortex. This process is assumed to be rather independent from dopamine-dependent

plasticity. However, this process should not be simply based on random connections

because the similarity of the inputs has to be maintained in the encoding process to

achieve stimulus generalization. The encoding could instead be learned in a different

manner from the reward-related learning. Therefore, the fixed connections between the

input and hidden layers in OVaRLAP can be the result of learning for such encoding

process. How the brain learns the encoding process is a topic for future research, but

some implications are derived from computational models of the primary visual cortex

and the primary auditory cortex that adopted unsupervised learning [37, 38].

Compared to ordinary reinforcement learning algorithms, the uniqueness of the

OVaRLAP model is that it is characterized by fast generalization and value separation.

Its advantage regarding safe and efficient exploration primarily occurred by fast

generalization, whereas its potential defect in causing maladaptive behaviors was

derived from fast generalization and from value separation. Mikhael et al. [26]

previously demonstrated the advantage of value separation. Their model coded reward

uncertainty into the sum of the synaptic weights of D1 and D2 SPNs. In addition, their

model can adjust the tendency to choose or avoid risky options by changing the weight

of the positive and negative values, which is assumed to reflect tonic dopamine level.

The further advantages of the value separation were not major topics in our current

study, although the OVaRLAP model can also enjoy such advantages. The OVaRLAP

model can encode reward uncertainty in distinct connections updated by positive and

negative TD errors (red and blue arrows, respectively, in Fig. 1A, left), and can adjust

risk-taking tendency by changing the connection weights between the pre-output

neurons to the output neuron, which were set constant for simplicity in this study.

The potential defect of OVaRLAP causing maladaptive behaviors can provide a

hypothesis on psychiatric disorders. Based on the correspondence between OVaRLAP

and the brain, the result for the disturbed OVaRLAP showed the possibility that the

noisy encoding process in the cortex and the impairment of dopamine-dependent

plasticity induce abnormal stimulus generalization and discrimination, which may

underlie delusional symptoms. The relationship between cortical disconnectivity and

disrupted learning in schizophrenia has been implied in computational studies [39, 40];

therefore, alterations in cortical connectivity could be a cause of a noisy encoding

process. Histologic examinations and diffusion tensor imaging studies for patients with

schizophrenia revealed reduced spine density and disrupted white matter connectivity,

respectively [41-43]. Reinforcement learning models have been used for attempts to

explain positive symptoms, including delusion, in schizophrenia [44-46]. However,

these studies do not link abnormal cortical connectivity to positive symptoms. They

attribute positive symptoms to aberrant salience (i.e., a surprise response to nonsalient

events) [47]. Thus, they focused on an abnormality in the dopamine system, which was

also supported by neurobiological evidence [48, 49]. The OVaRLAP model is a new

corticostriatal learning model that relates delusional symptoms to an abnormality in

cortical connectivity and in the dopamine system.

The relationship between abnormal stimulus generalization and schizophrenia

has been investigated by psychological research [3, 32, 33]. The research is based on the

hypothesis that abnormal generalization underlies delusional symptoms in

schizophrenia. Some studies imply heightened stimulus generalization in schizophrenia.

However, the reported abnormality was not sufficiently remarkable for explaining

delusion in a straightforward manner. This finding can be attributed to the conditioning

paradigm used for their behavioral experiments. Patients with schizophrenia have

various deficits in cognitive function; therefore, the experimental design needed to be

simple to attribute the result to stimulus generalization rather than other factors.

Computational models may potentially be used to investigate how a specific deficit in

cognitive function leads to psychotic symptoms through complex learning processes.

The OVaRLAP model showed that a small abnormality in stimulus generalization in

combination with an unbalanced response to positive and negative prediction error may

induce aberrant valuation after reward-related learning, including action selection, state

transition, and obtaining rewards from multiple sources.

Acknowledgement

We would like to thank Hidetoshi Urakubo for his helpful comments.

References

1. Dunsmoor JE, Paz R. Fear Generalization and Anxiety: Behavioral and Neural Mechanisms. Biol Psychiatry. 2015;78(5):336-343.

2. Asok A, Kandel ER, Rayman JB. The Neurobiology of Fear Generalization. Front Behav Neurosci. 2018;12:329.

3. Kahnt T, Tobler PN. Dopamine regulates stimulus generalization in the human hippocampus. Elife. 2016;5:e12678.

4. Ghirlanda S, Enquist M. A century of generalization. Anim Behav. 2003;66(1):15-36.

5. Thorndike EL. Animal intelligence: An experimental study of the associative processes in animals. Psychol Monogr. 1898;2(8).

6. Ghirlanda S, Enquist M. Artificial neural networks as models of stimulus control. Anim Behav. 1998;56(6):1383-1389.

7. Franks DW, Ruxton GD. How robust are neural network models of stimulus generalization? Biosystems. 2008;92(2):175-181.

8. Shepard RN, Kannappan S. Connectionist Implementation of a Theory of Generalization. In: Advances in Neural Information Processing Systems 3. 1990 Proceedings of the Neural Information Processing Systems (NIPS) Conference. NIPS: San Diego, CA. 1991. p. 665-671.

9. Wisniewski MG, Radell ML, Guillette LM, Sturdy CB, Mercado E 3rd. Predicting shifts in generalization gradients with perceptrons. Learn Behav. 2012;40(2):128-144.

10. Glimcher PW. Understanding dopamine and reinforcement learning: the dopamine reward prediction error hypothesis. Proc Natl Acad Sci USA. 2011;108(Suppl 3):15647-15654.

11. Frank MJ, Seeberger LC, O'reilly RC. By carrot or by stick: cognitive reinforcement learning in parkinsonism. Science. 2004;306(5703):1940-1943.

620 12.  Doya K. Reinforcement learning: computational theory and biological

621   mechanisms. HFSP J. 2007;1(1):30-40.

622 13.  Mnih V, Kavukcuoglu K, Silver D, Rusu AA, Veness J, Bellemare MG, et al.

623   Human-level control through deep reinforcement learning. Nature.

624   2015;518(7540):529-533.

625 14.  Whittington JCR, Bogacz R. Theories of Error Back-Propagation in the Brain.

626   Trends Cogn Sci. 2019;23(3):235-250.

627 15.  DeLong MR. Primate models of movement disorders of basal ganglia origin.

628   Trends Neurosci. 1990;13(7):281-285.

629 16.  Nambu A. Globus pallidus internal segment. Prog Brain Res. 2007;160:135-150.

630 17.  Amemori K, Gibb LG, Graybiel AM. Shifting responsibly: the importance of

631   striatal modularity to reinforcement learning in uncertain environments. Front

632   Hum Neurosci. 2011;5:47.

633 18.  Collins AG, Frank MJ. Opponent actor learning (OpAL): modeling interactive

634   effects of striatal dopamine on reinforcement learning and choice incentive.

635   Psychol Rev. 2014;121(3):337-366.

636 19.  Meredith GE, Baldo BA, Andrezjewski ME, Kelley AE. The structural basis for

637   mapping behavior onto the ventral striatum and its subdivisions. Brain Struct

638   Funct. 2008;213(1-2):17-27.

639 20.  Schultz W. Neuronal Reward and Decision Signals: From Theories to Data.

640   Physiol Rev. 2015;95(3):853-951.

641 21.  Tepper JM, Abercrombie ED, Bolam JP. Basal ganglia macrocircuits. Prog Brain

642   Res. 2007;160:3-7.

643 22.  Reynolds JN, Hyland BI, Wickens JR. A cellular mechanism of reward-related

644   learning. Nature. 2001;413(6851):67-70.

645 23.  Surmeier DJ, Shen W, Day M, Gertler T, Chan S, Tian X, et al. The role of

646   dopamine in modulating the structure and function of striatal circuits. Prog Brain

Res. 2010;183:149-167.

24. Yagishita S, Hayashi-Takagi A, Ellis-Davies GC, Urakubo H, Ishii S, Kasai H. A
critical time window for dopamine actions on the structural plasticity of dendritic
spines. Science. 2014;345(6204):1616-1620.

25. Hikida T, Yawata S, Yamaguchi T, Danjo T, Sasaoka T, Wang Y, et al.
Pathway-specific modulation of nucleus accumbens in reward and aversive
behavior via selective transmitter receptors. Proc Natl Acad Sci USA.
2013;110(1):342-347.

26. Mikhael JG, Bogacz R. Learning reward uncertainty in the basal ganglia. PLoS
Comput Biol. 2016;12(9):e1005062.

27. Elfwing S, Seymour B. Parallel reward and punishment control in humans and
robots: Safe reinforcement learning using the MaxPain algorithm. In: Proceedings
of the 2017 Joint IEEE International Conference on Development and Learning
and Epigenetic Robotics (ICDL-EpiRob), September 18–21, 2017. IEEE:
Piscataway, NJ. 2017. pp. 140-147.

28. Cox J, Witten IB. Striatal circuits for reward learning and decision-making. Nat
Rev Neurosci. 2019;20(8):482-494.

29. Huang G-B, Zhu Q-Y, Siew C-K. Extreme learning machine: Theory and
applications. Neurocomputing. 2006;70(1-3):489-501.

30. Lukoševičius M, Jaeger H. Reservoir computing approaches to recurrent neural
network training. Comput Sci Rev. 2009;3(3):127-49.

31. Maass W, Natschläger T, Markram H. Real-time computing without stable states:
a new framework for neural computation based on perturbations. Neural Comput.
2002;14(11):2531-2360.

32. Ralph DE. Stimulus generalization among schizophrenics and normal subjects. J
Abnorm Psychol. 1968;73(6):605-609.

33. Buss AH, Daniell EF. Stimulus generalization and schizophrenia. J Abnorm

Psychol. 1967;72(1):50-53.

34.   Bordi F, LeDoux J. Sensory tuning beyond the sensory system: an initial analysis

of auditory response properties of neurons in the lateral amygdaloid nucleus and

overlying areas of the striatum. J Neurosci. 1992;12(7):2493-2503.

35.   Sutton RS, Barto AG. Reinforcement Learning: An Introduction. 2nd ed. MIT

Press: Cambridge, MA. 2018.

36.   Rummery G, Niranjan M. On-Line Q-Learning Using Connectionist Systems.

Technical Report CUED/F-INFENG/TR 166. Cambridge University Engineering

Department, Cambridge, United Kingdom. 1994.

37.   Hyvärinen A, Hoyer PO. A two-layer sparse coding model learns simple and

complex cell receptive fields and topography from natural images. Vision Res.

2001;41(18):2413-2423.

38.   Terashima H, Okada M. The topographic unsupervised learning of natural sounds

in the auditory cortex. In: Advances in Neural Information Processing Systems 25.

Neural Information Processing Systems Foundation: San Diego, CA. 2012. pp.

2312-2320.

39.   Hoffman RE, Dobscha SK. Cortical pruning and the development of

schizophrenia: a computer model. Schizophr Bull. 1989;15(3):477-490.

40.   Hoffman RE, McGlashan TH. Synaptic elimination, neurodevelopment, and the

mechanism of hallucinated "voices" in schizophrenia. Am J Psychiatry.

1997;154(12):1683-1689.

41.   van den Heuvel MP, Scholtens LH, de Reus MA, Kahn RS. Associated Microscale

Spine Density and Macroscale Connectivity Disruptions in Schizophrenia. Biol

Psychiatry. 2016;80(4):293-301.

42.   Garey LJ, Ong WY, Patel TS, Kanani M, Davis A, Mortimer AM, et al. Reduced

dendritic spine density on cerebral cortical pyramidal neurons in schizophrenia. J

Neurol Neurosurg Psychiatry. 1998;65(4):446-453.

43.   Ellison-Wright I, Bullmore E. Meta-analysis of diffusion tensor imaging studies in

schizophrenia. Schizophr Res. 2009;108(1-3):3-10.

44.   Deserno L, Boehme R, Heinz A, Schlagenhauf F. Reinforcement learning and

dopamine in schizophrenia: dimensions of symptoms or specific features of a

disease group? Front Psychiatry. 2013;4:172.

45.   Maia TV, Frank MJ. An Integrative Perspective on the Role of Dopamine in

Schizophrenia. Biol Psychiatry. 2017;81(1):52-66.

46.   Katahira K, Yamashita Y. A Theoretical Framework for Evaluating Psychiatric

Research Strategies. Comput Psychiatr. 2017;1:184-207.

47.   Kapur S. Psychosis as a state of aberrant salience: a framework linking biology,

phenomenology, and pharmacology in schizophrenia. Am J Psychiatry.

2003;160(1):13-23.

48.   Howes OD, Kambeitz J, Kim E, Stahl D, Slifstein M, Abi-Dargham A, et al. The

nature of dopamine dysfunction in schizophrenia and what this means for

treatment. Arch Gen Psychiatry. 2012;69(8):776-786.

49.   Daberkow DP, Brown HD, Bunner KD, Kraniotis SA, Doellman MA, Ragozzino

ME, et al. Amphetamine paradoxically augments exocytotic dopamine release and

phasic dopamine signals. J Neurosci. 2013;33(2):452-463.

Supporting information

S1 Fig. The grid-world configurations used in the painful grid-world navigation task. The grid-world shown in Fig 1B is displayed again at the left top. These five grid-world configurations were generated under the following rules, while avoiding symmetric or similar structures. A wide passage consists of rectangles in which the shorter width/height is 5 (based on the number of grids) and the longer width/height is more than 7; the wide passage does not have a dead end. A narrow passage exists with a width of 2 and a length of 6. The starting position and a goal with a lower reward of 1 are located two grids away from the end of the wide passage and three grids away from side walls (i.e., relatively apart from the walls). The passages have to be surrounded by walls. If the passages are separated by walls, the distance between these passages has to be more than three grids. A goal with a higher reward of 2 is one grid away from the end of the narrow passage (i.e., relatively close to the walls). The shortest path to either of the goal requires 26 steps if the agent has to move to the center of the wide passage before turning to the narrow passage.

739   **Fig 1.**

742   **Fig 2.**

744
745   **Fig 3.**
746

748 **Fig 4.**

Fig 5.

754