Computational characteristics of the striatal dopamine system

described by reinforcement learning with fast generalization

Short title: Computational characteristics of the striatal dopamine system

Yoshihisa Fujita[1]*, Sho Yagishita[2,3], Haruo Kasai[2,3], and Shin Ishii[1,3]

[1] Integrated Systems Biology Laboratory, Department of Systems Science, Graduate

School of Informatics, Kyoto University, Yoshida-Honmachi 36-1, Sakyo-ku, Kyoto

606-8501, Japan

[2] Laboratory of Structural Physiology, Center for Disease Biology and Integrative

Medicine, Faculty of Medicine, University of Tokyo, Bunkyo-ku, Tokyo 113-0033,

Japan

[3] International Research Center for Neurointelligence, Bunkyo-ku, Tokyo 113-0033,

Japan

*Corresponding author

E-mail: fujita.yoshihisa.4s@kyoto-u.ac.jp

Abstract

Generalization enables applying past experience to similar but nonidentical situations.

Therefore, it may be essential for adaptive behaviors. Recent neurobiological

observation indicates that the striatal dopamine system achieves generalization and

subsequent discrimination by updating corticostriatal synaptic connections in

differential response to reward and punishment. To analyze how the computational

characteristics in this system affect behaviors, we proposed a novel reinforcement

learning model with multilayer neural networks in which the synaptic weights of only

the last layer are updated according to the prediction error. We set fixed connections

between the input and hidden layers so as to maintain the similarity of inputs in the

hidden-layer representation. This network enabled fast generalization, and thereby

facilitated safe and efficient exploration in reinforcement learning tasks, compared to

algorithms which do not show generalization. However, disturbance in the network

induced aberrant valuation. In conclusion, the unique computation suggested by

corticostriatal plasticity has the advantage of providing safe and quick adaptations to

unknown environments, but on the other hand has the potential defect which can induce

maladaptive behaviors like delusional symptoms of psychiatric disorders.

Author summary

The brain has an ability to generalize knowledge obtained from reward- and punishment-related learning. Animals that have been trained to associate a stimulus with subsequent reward or punishment respond not only to the same stimulus but also to resembling stimuli. How does generalization affect behaviors in situations where individuals are required to adapt to unknown environments? It may enable efficient learning and promote adaptive behaviors, but inappropriate generalization may disrupt behaviors by associating reward or punishment with irrelevant stimuli. The effect of generalization here should depend on computational characteristics of underlying biological basis in the brain, namely, the striatal dopamine system. In this research, we made a novel computational model based on the characteristics of the striatal dopamine system. Our model enabled fast generalization and showed its advantage of providing safe and quick adaptation to unknown environments. By contrast, disturbance of our model induced abnormal behaviors. The results suggested the advantage and the shortcoming of generalization by the striatal dopamine system.

Introduction

Animals' survival with reward-seeking behaviors should be accompanied with risks. Outcome observation resulting from the pairing of a current state and a taken action could be a clue to ensure optimal behaviors, but it may be associated with substantial energy consumption and aversive experience. Such a learning process is inefficient and even harmful, especially when animals are required to adapt to new environments. Animals instead generalize their past experience for predicting outcome, even in novel situations. Generalization may be essential for efficient adaptive behaviors, whereas generalization to an abnormal extent can be maladaptive and is implicated in psychiatric disorders [1-3].

Psychological studies have investigated generalization by using the conditioning paradigm in behavioral experiments [4]. If a response has been established by a stimulus paired with an outcome (i.e., reward or punishment), then resembling stimuli evoke similar responses. This "law of effect" depends on the extent that the second stimulus resembles the first stimulus, and is termed "stimulus generalization" [4, 5]. Discrimination can then occur if the first stimulus is paired with a reward but the resembling stimulus is paired with no reward; as a consequence, only the first stimulus elicits a response. How the brain establishes stimulus generalization has been explained, based on artificial neural networks [6-9]. Previous studies [6-9] have focused on the stimulus–response relationship, although generalization can be incorporated in the interaction between individuals and the environment. Reinforcement learning involves this interaction and is used as a model of reward-driven learning [10-12]. In the field of artificial intelligence, reinforcement learning in combination with artificial neural networks achieves a high performance, which suggests the contribution of generalization to adaptive behaviors [13]. However, neurobiological evidence indicates that the neural system has a unique computation for reward-driven learning and

generalization, compared to algorithms used for artificial intelligence [14]. This fact

raises the question regarding how its computational characteristics differ from those of

ordinary algorithms. Advantages and shortcomings should exist with regard to adaptive

behaviors.

Theoretical attempts have focused on separate systems that process positive and

negative values in the brain [15-18], which is not adopted when using ordinary

reinforcement learning. Dopamine and its main target, the striatum, have central roles in

reward- and punishment-related learning [19]. Dopamine neurons show a positive

response to a greater-than-expected reward and a negative response to a

less-than-expected reward, which indicates that dopamine codes reward prediction error

[20]. The striatum receives dopamine signals and glutamatergic input from the cortex

and thalamus [21]. Dopamine modulates synaptic plasticity between the cortex and the

striatum during reward-related learning [22]. The striatum is primarily composed of

spiny projection neurons (SPNs), which can be divided into SPNs that primarily express

the dopamine D1 receptor (D1-SPNs) and SPNs that express the dopamine D2 receptor

(D2-SPNs) [23]. The D1-SPNs respond to the phasic increase in dopamine [24],

whereas D2-SPNs may respond to the phasic decrease in dopamine [25]. Perturbing the

activity of the D1- and D2-SPNs inhibits reward learning and punishment learning,

respectively [25]. The advantages of having such separate systems have been discussed

in computational studies [26, 27]. One study [26] demonstrated an advantage in learning

reward uncertainty. Another study [27] showed the possibility of achieving safe

behaviors.

However, recent neural recordings and optogenetic manipulations provide some

data that suggests different roles of SPNs from those in existing models [28]. Our new

experiments with a classical conditional task found that D1- and D2-SPNs are

differentially responsible for stimulus generalization and discrimination (Yagishita,

Kasai and others, unpublished). The same series of experiments revealed that stimulus

generalization/discrimination occurred solely by dopamine-dependent plasticity of SPN spines that receive cortical inputs, which implies that updating in other connections (e.g., intracortical synaptic connections) would be minor. These observations suggest learning rules that update the synaptic weights of the last layer in a multilayer neural network—in our case, corticostriatal connections—are essential. Such learning rules actually enable remarkably fast learning in reservoir computing (RC) and extreme learning machine (ELM) [29-31]. Reservoir computing and ELM are neural networks that train only their readouts (i.e., the last layer connections); RC has recurrent connections, whereas ELM does not.

In this study, we propose a novel reinforcement learning model that reproduces stimulus generalization and discrimination, while accounting for the physiological characteristics of striatal SPNs. We used a neural network for value estimation and introduced fixed connections between the input and hidden layers, as in RC and ELM. Reservoir computing has the potential for context-dependent value estimation because of its recurrent connections. However, for simplicity, we adopted a feed-forward neural network with the same architecture as ELM. The extent of stimulus generalization depends on the similarity of stimuli; therefore, we did not use random and fixed connections implemented in ordinary ELM. We instead set the fixed connections so as to maintain the similarity of inputs in the hidden-layer representation. In addition, we introduced connections, the weights of which are separately updated by positive and negative reward prediction errors, while taking into account the differential roles of D1- and D2-SPNs in the striatum. This neural network enabled generalization in a quick manner. We named this model "Outspread Valuation for Reward Learning and Punishment Learning" ("OVaRLAP"). The OVaRLAP model achieved safe and efficient exploration in painful grid-world navigation tasks. This achievement suggested that quick generalization contributed to safe and efficient reward-seeking and pain-avoiding. We also tested disturbed OVaRLAP to examine whether abnormal generalization

underlies maladaptive behaviors, as implied in psychological and psychiatric studies [3,

32, 33]. The OVaRLAP method with noisy generalization and impaired discrimination

induced aberrant valuation, after repeating reward-seeking behaviors. These results

showed that the unique computation suggested by the striatal dopamine system enabled

safe and efficient exploration, but on the other hand had the potential defect which can

cause maladaptive behaviors.

Methods

We developed OVaRLAP to analyze how the computational characteristics in the striatal

dopamine system affect behaviors. We first evaluated OVaRLAP in a spatial navigation

task in painful grid-worlds by comparing its performance with those of two other

representative algorithms (Fig 1A-1B). We then examined behaviors of disturbed

OVaRLAP in a spatial navigation task in a painless grid-world (Fig 1C-1D).

Fig 1. The architecture of TD learning algorithms and the task. (**A**) Schematic

diagrams of OVaRLAP (left), simple TD learning (middle), and MaxPain (right). In

OVaRLAP, the value prediction is conducted using a neural network with fixed

connections (gray arrows) and distinct connections updated by positive and negative TD

errors (red and blue arrows, respectively). In our implementations of simple TD learning

and MaxPain, the predicted value is represented by lookup tables in which the state, s_k,

indicates a position (x, y) in the two-dimensional grid-world. (**B**) The navigation task

in the two-dimensional grid-world. The nongray squares and gray squares indicate

passable and not passable, respectively. The black square is the starting position, and the

blue and yellow squares are the goals at which the agent receives the positive rewards of

1 and 2, respectively. When the agent receives a positive reward, an episode ends so that

the agent restarts the task from the starting position. If an agent hits a wall (i.e., a not

passable square), it receives a negative reward of -1, but continues the task by staying

at the same square. (**C**) Schematic diagram of OVaRLAP in which updating connections,

based on the negative TD error (blue connections), are impaired. In addition, noise was

introduced to induce an anomaly in the initialization of the fixed connections between

the input and the hidden layers (for the details of noise here, see the Methods section).

(D) The navigation task in the two-dimensional grid-world. The black square is the

starting position. The green squares are the goals at which the agent receives a positive

reward of 1. If the agent receives a positive reward, a single episode ends, and a new

episode restarts from the starting position. In this task, when the agent hits a wall (i.e., a

gray square), no negative reward is given, and the agent remains at the same square.

Model description of OVaRLAP

A neural network was used for value estimation in OVaRLAP. It consists of an input

layer, a hidden layer, two pre-output neurons, and an output neuron (Fig 1A, left). The

input represents the state at discretized time, t. We applied our learning method to two

types of navigation tasks, both in two-dimensional grid-worlds, in which position

(x, y), $x \in \{1, \dots, 20\}$, and $y \in \{1, \dots 20\}$ were simply represented by a

two-dimensional index function:

$$I_{ij}(x, y, t) = \begin{cases} 1, & \text{if } i = x \text{ and } j = y \\ 0, & \text{otherwise.} \end{cases}$$

The input signals were transformed by fixed connections into hidden-layer

activity patterns. We set the number of hidden-layer neurons and the weight of fixed

connections so as to reproduce the shape of the generalization gradient, which has been

commonly observed across various species, behavioral contexts, and sensory modalities

[4]. The number of hidden-layer neurons was set to 900. The hidden-layer activity

$h_k(x, y, t)$ for $k = 1, \dots, 900$ was given by

$$h_k(x, y, t) = \sum_i \sum_j M_{ij,k} I_{ij}(x, y, t),$$

in which $M_{ij,k}$ is the weight of the fixed connection from the input-layer neuron

(i, j) to the hidden-layer neuron k. Based on the definition of $I_{ij}(x, y, t)$, $h_k(x, y, t)$

was also given by

$$h_k(x, y, t) = M_{xy,k}$$

in which (x, y) is the agent's position at time t.

For the generalization capability, we assumed the hidden-layer representation
becomes similar when the input signal is similar. In our case, the values of $h_k(x_1, y_1, t)$
and $h_k(x_2, y_2, t)$ are similar if position (x_1, y_1) is close to position (x_2, y_2), based on
Euclidian distance. To reflect this request, we set the fixed connections $M_{ij,k}$ to follow
the two-dimensional Gaussian function:

$$M_{ij,k} = \frac{\exp\left\{-\left(\frac{(i - a_k)^2}{2\sigma_k^2} + \frac{(j - b_k)^2}{2\sigma_k^2}\right)\right\} + \varepsilon_{ij,k}}{D}$$

in which D is the number of the input-layer neurons used for normalization ($D = 400$,
because of the 20×20 grid-worlds); a_k and b_k denote the center and are set as
$a_k \in \{1, \dots, 20\}$, $b_k \in \{1, \dots, 20\}$, and $20(a_k - 1) + b_k = ceil(400k/900)$ so that the
center location was linearly correlated in the 2D space; σ_k^2 is the variance sampled
from a log-normal distribution, $\sigma_k^2 \sim \text{LogN}(-0.7, 0.7)$; and $\varepsilon_{ij,k}$ is the noise, as
defined later. The distribution of σ_k^2 resulted that the hidden-layer neurons ranged from
neurons that responded to specific input to neurons that responded to a wide range of
input. This setting is consistent with physiological observations [34]. The noise $\varepsilon_{ij,k}$ is
unnecessary in the normal case; however, we introduced it for the purpose of analyzing
the effect of abnormal perturbation in OVaRLAP (Fig 1C). When simulating abnormal
perturbation, the noise $\varepsilon_{ij,k}$ was added by using the following formulas:

$$P(\varepsilon_{k,ij} = 0.5) = \rho$$

215 and

$$P(\varepsilon_{k,ij} = 0) = 1 - \rho.$$

No noise apparently exists if ρ is zero. This noise was initially introduced but not

changed through the learning process. In our simulation experiment, we applied

different patterns of noise $\varepsilon_{ij,k}$ under a specific value of ρ, and examined the collective

behaviors of the learning.

The two pre-output neurons then received signals from the hidden-layer

neurons. For $m = 1,2$, the activities of the pre-output neurons $d_m(x, y, t)$ are given by

223
$$d_m(x, y, t) = \sum_k w_{m,k}(t) h_k(x, y, t),$$

224   in which $w_{m,k}(t)$ is the weight of the connection from hidden-layer neuron k to the

225   pre-output neuron m. In this instance, $d_1(x, y, t)$ and $d_2(x, y, t)$ represented the

226   positive and negative values, respectively. The final output of the network $v(x, y, t)$

227   integrated these values, as follows:

228
$$v(x, y, t) = d_1(x, y, t) - d_2(x, y, t).$$

229   During the interaction between the agent and the environment, the connection

230   weights $w_{m,k}(t)$ were updated, depending on the prediction error, δ. To calculate δ, we

231   used an action-value function $Q(s, a, t)$ for state s and action a at time t [35]. We

232   defined $Q(s, a, t)$ by using the output of the network, as follows:

233
$$Q(s, a, t) = v(x', y', t),$$

234   in which $s = (x, y)$, $a = (\Delta x, \Delta y)$, $x' = x + \Delta x$, and $y' = y + \Delta y$. In our navigation

235   tasks, $(\Delta x, \Delta y) = (1,0)$, $(-1,0)$, $(0,-1)$, or $(0,1)$, if the action was effective. The

236   prediction error δ was given by

237
$$\delta(t) = r(s, a) + \gamma Q(s', a', t) - Q(s, a, t),$$

in which $r(s, a)$ is the actual reward, s' denotes the state at time $t + 1$, a' denotes

the action at time $t + 1$, and γ is the discount factor. We used temporal difference (TD)

learning for the action-value function (i.e., state–action–reward–state–action [SARSA])

[36] because the agent needed to remain at the same square after an ineffective action

(i.e., hitting a wall). If we used a simple TD for the state-value function, such ineffective

actions would introduce noise to the value learning. The connection weight $w_{1,k}(t)$

was updated only when $\delta(t)$ was positive, and $w_{2,k}(t)$ was updated only when $\delta(t)$

was negative. In the actual implementation, the updating rules were as follows:

246
$$w_{1,k}(t+1) = \begin{cases} w_{1,k}(t) + \dfrac{\alpha_1 \delta(t) h_k(x',y',t) d_1(x',y',t)}{N_1(x',y',t)}, & \text{if } \delta(t) > 0 \\ w_{1,k}(t), & \text{otherwise,} \end{cases}$$

247   and

248
$$w_{2,k}(t+1) = \begin{cases} w_{2,k}(t) + \dfrac{\alpha_2 [-\delta(t)] h_k(x',y',t) d_2(x',y',t)}{N_2(x',y',t)}, & \text{if } \delta(t) < 0 \\ w_{2,k}(t), & \text{otherwise,} \end{cases}$$

249   in which α_1 and α_2 are the learning rates and $N_1(x,y,t)$ and $N_2(x,y,t)$ are the

250   normalization terms, which are given by

251
$$N_m(x,y,t) = d_m(x,y,t) \sum_k h(x,y,t)^2.$$

252   for $m = 1,2$. These normalization terms are introduced to make sure that

253
$$Q(s,a,t+1) = \begin{cases} Q(s,a,t) + \alpha_1 \delta(t), & \text{if } \delta(t) > 0 \\ Q(s,a,t) + \alpha_2 \delta(t), & \text{otherwise.} \end{cases}$$

254   **Algorithms for comparison**

255   We also implemented two representative algorithms to compare with the OVaRLAP

256   model. One algorithm was simple TD learning [35] (Fig 1A, middle); in our particular

257   case, the algorithm was SARSA. In our implementation, a value function of states,

258   $v_s(x,y,t)$, was represented as a look-up table and updated as follows:

259
$$v_s(x,y,t+1) = v_s(x,y,t) + \alpha_s \delta_s(t)$$

260   in which α_s is the learning rate and δ_s is the prediction error, called the "TD error."

261   This error is given by

262
$$\delta_s(t) = r(s, a) + \gamma_s Q_s(s', a', t) - Q_s(s, a, t)$$

263 in which γ_s is the discount factor. The action-value function, $Q_s(s, a, t)$, is given by

264
$$Q_s(s, a, t) = v_s(x', y', t).$$

The other algorithm is the MaxPain algorithm [27] (Fig 1A, right). This method

is characterized by its distinct systems for the learning values for reward and pain (or

punishment). The policy is dependent on the linear combination of the two value

functions. In our implementation, we slightly modified the originally proposed MaxPain

algorithm to make it comparable with the other methods, while maintaining the essential

idea of MaxPain.

First, we used state-value functions of states $v_r(x, y, t)$ and $v_p(x, y, t)$, and

their linear combination $v_L(x, y, t)$, to define the action-value functions $Q_r(s', a', t)$,

$Q_p(s', a', t)$, and $Q_L(s', a', t)$, as follows:

274
$$Q_r(s, a, t) = v_r(x', y', t),$$

275
$$Q_p(s, a, t) = v_p(x', y', t),$$

276 and

277
$$Q_L(s, a, t) = v_L(x', y', t).$$

278 Second, we set the linear combination $v_L(x, y, t)$ without normalization, as follows:

279
$$v_L(x, y, t) = v_r(x, y, t) - v_p(x, y, t).$$

280 The couple of state-value functions were implemented as look-up tables and updated as

281
$$v_r(x, y, t + 1) = v_r(x, y, t) + \alpha_r \delta_r(t)$$

282 and

283
$$v_p(x, y, t + 1) = v_p(x, y, t) + \alpha_p \delta_p(t)$$

in which α_r and α_p are the learning rates for reward and pain, respectively, and δ_r

and δ_p are the prediction errors for reward and pain, respectively. The prediction errors

were calculated, depending on whether the reward observation was positive or negative,

as follows:

$$\delta_r(t) = \varphi\big(r(s,a)\big) + \gamma_r Q_r(s',a',t) - Q_r(s,a,t)$$

and

$$\delta_p(t) = \varphi\big(-r(s,a)\big) + \gamma_p Q_p\big(s',\underset{a'}{\mathrm{argmin}}\big(Q_L(s',a',t)\big),t\big) - Q_p(s,a,t)$$

in which $\varphi(z) = \max(z,0)$ and γ_r and γ_p are the discount factors. These update

rules were the same as those in the original study. The pain prediction error, δ_p, was

used for maximizing future pain (i.e., for predicting the worst case).

Action selection

We used the softmax behavioral policy consistently for the three methods. It depends on

the value function $\tilde{v}(x,y,t)$ [i.e., $v(x,y,t)$ for OVaRLAP, $v_s(x,y,t)$ for the simple

TD learning, and $v_L(x,y,t)$ for MaxPain]. The probability that the agent selects an

action a at position (x,y) at time t is given by

$$\pi(a|x,y,t) = \frac{\exp\big(\tilde{v}(x',y',t)/\tau\big)}{\sum_c \exp\big(\tilde{v}(x_c,y_c,t)/\tau\big)}$$

in which x' and y' denote the new state after selecting action a, x_c and y_c denote

the new state after selecting one of the possible actions, and τ is the temperature that

controls the trade-off between exploration and exploitation. In our implementation, we

used the common $\tau = 0.5$, for the three learning methods.

Painful grid-world navigation task

The purpose of this task was to navigate from the starting position to either of the two

goals, while avoiding hitting the wall. Possible actions at each time step were moving

one step north, south, east, and west. For example, if the agent moved one step north,

$(\Delta x, \Delta y) = (0,1)$. Two goals exist with reward of 1 or 2. If the agent hits a wall, then it

received a negative reward of -1 and remained at the same position. This was an

exceptional case. In other cases, the agent could by necessity move to the next square.

An episode began when the agent started from the starting position and ended when the

agent reached either of the goals. The agent repeated such learning episodes.

A single run consisted of 500 learning episodes, after initializing the value

function so that the value for each state was zero. We ran 50 separate runs each for

OVaRLAP, simple TD learning, and MaxPain with a single grid-world configuration.

We conducted five simulation experiments for each of which we used a grid-world with

a consistent character but different configuration. The structure of each grid-world is

shown in Fig 1B and in S1 Fig. We set the metaparameters for each algorithm, as

follows: $\rho = 0$, $\alpha_1 = \alpha_2 = 0.1$, and $\gamma = 0.95$ for OVaRLAP; $\alpha_s = 0.1$ and $\gamma_s =$

0.95 for simple TD learning; and $\alpha_r = \alpha_p = 0.1$, $\gamma_r = 0.95$, and $\gamma_p = 0.5$ for

MaxPain. OVaRLAP and MaxPain are extended algorithms, based on simple TD;

therefore, they use common metaparameters with simple TD, when they could share

them.

The five configurations in S1 Figure were generated, based on the following

rules, while avoiding symmetric or similar structures. Each configuration had a wide

passage from which a narrow passage branched off. These passages had fixed widths

and lengths. The starting position and the goal with a reward of 1 were at either end of a

wide passage. A goal with reward of 2 was at the end of a narrow passage. S1 Fig.

legend has more details of the rules.

Grid-world navigation task for disturbed OVaRLAP

The purpose of this task was to navigate from the starting position to either of four goals.

The structure of the grid-world is shown in Fig 1D. Possible actions at each time step

were moving one step north, south, east, and west. Multiple goals existed, each of which

gave a reward of 1. The topic in this study was not on risk aversion; therefore, we did

not apply a negative reward to the actions that resulted in hitting a wall (i.e., no pain).

The agent simply remained at the same position after hitting a wall. Even in this no pain

setting, the agents after reinforcement learning likely avoid wall hits, due to the discount

factor in the value functions. An episode began when the agent moved from the starting

position and ended when the agent reached one of the four goals. A single run consisted

of a total of 40,000 time steps (i.e., 378.8 learning episodes on average) after the value

function initialization at the onset of the first learning episode. We ran 50 separate runs

for OVaRLAP for each of the following settings: normal or no update for a negative TD

error (i.e., "intact" or "impaired") and with or without noise in the fixed connections

(i.e., "noised" or "unnoised"). We set the metaparameters, as follows: $\rho = 0.005$ for

the noised case and $\rho = 0$ for the unnoised case; $\alpha_1 = 0.1$; $\alpha_2 = 0.1$ for the intact

setting (which was the same as in the previous experiment) and $\alpha_2 = 0$ for the

impaired setting; $\gamma = 0.8$; and $\tau = 0.5$. In the noised setting, the noise, $\varepsilon_{ij,k}$, was

generated independently for each run and was fixed within each run.

Results

The behavior of OVaRLAP

We evaluated OVaRLAP in a spatial navigation task in painful grid-worlds by

comparing its performance with those of simple TD learning and MaxPain [27]. These

algorithms are schematically shown in Fig 1A. On account that OVaRLAP utilizes a

fixed neural network (gray arrows in Fig 1A, left) for the preprocessing of the value

learning network (blue and red arrows in Fig 1A, left), it achieves stimulus

generalization, based on the similarity of states (Fig 2, left). By contrast, the other two algorithms, which have look-up tables, show no stimulus generalization (Fig 2, middle and right). The task in this study was to seek rewarded goals while avoiding painful wall hits in which the agent had to manage the trade-off between obtaining a reward and avoiding pain (Fig 1B). We used five different grid-worlds, each of which had a safe but lowly rewarded goal and a risky but highly rewarded goal (S1 Fig).

Fig 2. State values after a single update. The value function is updated after receiving a positive reward of 1 once with OVaRLAP (left), simple TD learning (middle), and MaxPain (right) at the center of a two-dimensional grid-world in Fig 1B.

Figure 3A–3C show the average learning curves at each episode over 50 independent runs for the grid-world shown in Fig 1B. The reward per step of the OVaRLAP agent was higher than that of the MaxPain agent, but it did not exceed that of the simple TD learning agent (Fig 3A). Compared to the other agents, the OVaRLAP agent reached each of the goals with a smaller number of steps in the early learning phase (Fig 3B). After 100 learning episodes, all three agents showed a similar number of steps to reach either of the goals. With regard to pain aversion, the OVaRLAP agent also showed quick learning. The OVaRLAP agent exhibited smaller numbers of wall hits in the early learning phase than did the other agents. However, after 50 learning episodes, the number of wall hits of the OVaRLAP agent was comparable to that of the simple TD learning agent (Fig 3C). By contrast, the MaxPain agent first hit the walls as many times as the simple TD learning agent, but the number of wall hits then quickly decreased. The OVaRLAP agent showed its characteristic performance in the five grid-worlds with different configurations (Fig 3D–3F). These results suggested that the OVaRLAP agent could learn a reward approach and pain aversion in a very efficient manner owing to its generalization capability, whereas it was inferior to the simple TD in long-term reward learning and to MaxPain in long-term pain aversion.

Fig 3. Average performance of OVaRLAP, the simple TD learning, and MaxPain in the painful grid-world navigation task. (**A**) The average reward per step, (**B**) the average number of steps to either of the two goals, and (**C**) the average number of wall hits, based on the three types of agents after each number of learning episodes on the horizontal axis. The grid world shown in Fig 1B was used. The number of steps to either of the two goals and the number of wall hits for the first 50 learning episodes are magnified in the top right insets of panels B and C, respectively. Each average (on the vertical axis) was taken over 50 separate runs and then smoothened as moving averages over nearby 11 episodes (on the horizontal axis). The thick lines represent the moving averages and the shadow areas indicate the moving standard deviations. (**D**–**F**) The average performance over five simulation experiments, each of which used a grid-world with different configurations. The grid world shown in Fig 1B and its variants were used (S1 Fig presents the details of the variants.). (**D**) The average reward per step, (**E**) the average number of steps to either of the two goals, and (**F**) the average number of wall hits, based on the three types of agents after 5 learning episodes and 500 learning episodes, are shown. Each bar indicates the average of five values (i.e., for five different grid-world configurations), each of which is the average over 50 separate runs. Each error bar represents the standard deviation over the five values.

Figure 4 shows how the value function was developed by using the three methods, in which OVaRLAP showed unique profiles (Fig 4, top). First, the values of positions close to the walls decreased, as did the values of the positions of the walls. This generalization constructed a safe passage to the lowly rewarded goal and simultaneously a hazard to approach the risky, but highly rewarded goal, after only five learning episodes. This value hazard completely disappeared after 500 episodes because the reward learning had been propagated to the squares on the passage to the high-reward goal. Thus, quick pain learning was essential for risk aversion and conservative reward-seeking in the early learning stage.

Fig 4. Transition of the value function for each model in the grid-world navigation task. The average state values over 50 separate runs after 5, 30, 150, and 500 learning episodes for OVaRLAP (top row), simple TD learning (middle row), and MaxPain (bottom row), when applied to the painful grid-world navigation task shown in Fig 1B. For MaxPain, the result of the subtraction of the value function for the pain from the value function for the positive reward (i.e., the main factor for decision-making) is displayed.

The simple TD learning algorithm did not construct any value hazard to the high-reward goal during its learning process, because no special system existed for pain learning (Fig 4, middle). The MaxPain algorithm also produced hazards on the passage to the high-reward goal (Fig 4, bottom). In contrast to OVaRLAP, the hazard progressively increased as the learning proceeded and was never flattened owing to its strong ability toward pain learning. For this reason, the MaxPain algorithm persistently maintained low values on the way to the high-reward goal.

The effect of a disturbed OVaRLAP

We next examined how the learning behaviors of OVaRLAP were disturbed by disabling weight updating by negative TD errors and introducing noise to the fixed network (Fig 1C). The generalization after obtaining a reward became a little noisy because of the noise introduction (Fig 5A). We applied this disturbed OVaRLAP to a grid-world navigation task without pain (Fig 1D). We tested each of the following two-by-two settings: normal or no update for the negative TD error (i.e., "intact" or "impaired"), and with or without noise in the fixed network (i.e., "noised" or "unnoised").

Fig 5. The TD learning task for disturbed OVaRLAP. (A) The value function is updated after reaching the left-bottom goal of the grid-world shown in Fig 1D once with

OVaRLAP without noise (left) and with noise (right). (**B**) The value function after 120 learning episodes in a single run for OVaRLAP with intact and impaired updates (top and bottom rows, respectively) for the negative TD error with and without noise (right and left columns, respectively) in the fixed connections. (**C**) The maximum value and its position in the value function after a total of 40,000 time steps (378.8 learning episodes on average) in each run. Each panel shows the maximum values in 50 separate runs for OVaRLAP under the following settings: intact or impaired updates (top or bottom row, respectively) for the negative TD error, and without noise or with noise (left or right column, respectively) in the fixed connections. In the noisy case, the noise was independently introduced to the initialization of the fixed connections for each run.

The impaired noised agent acquired an aberrant value function: it increased the value for a specific position distant from the goals, as if the position would give a positive reward (Fig 5B, bottom right). The value function of the intact noised agent was slightly noisy (Fig 5B, top right), but nearly the same as that of the intact unnoised agent (Fig 5B, top left). The impaired unnoised agent made the values around the goals higher than those of the intact agents, but the values for positions distant from the goals remained low (Fig 5B, bottom left).

We ran 50 runs for each setting to confirm the reproducibility. For the noised agent, a different pattern of noise was applied in each run. Fig 5C presents the maximum value and its position in the value function after 40,000 steps in each run. The intact agents always established the maximum values at the positions of goals and maintained them consistent to the actual amount of the rewards (Fig 5C, top row). The maximum values of the impaired unnoised agent were higher than the actual amount of the rewards (Fig 5C, bottom left). Their positions were not necessarily the same as the actual goals, but they were, at most, two steps away from the goals. In contrast to these three agents, the impaired-noised agent yielded maximum values that were quite apart from the actual goals (Fig 5C, bottom right). Their values were higher than the actual

amount of rewards and were sometimes exceedingly high.

Discussion

In this study, we proposed a novel reinforcement learning model named OVaRLAP to

analyze how the computational characteristics in the striatal dopamine system affect

behaviors. The OVaRLAP model reproduced stimulus generalization and discrimination

for reward learning and for punishment learning. If reward learning precedes in a

generalized manner, then discrimination is achieved by subsequent value reshaping,

based on punishment learning or on the omission of an unpredicted reward. By contrast,

if punishment learning precedes and is generalized, then subsequent reward learning or

the omission of unexpected punishment causes a discrimination. In the navigation task

in the painful grid-worlds (Figs 3 and 4), pain was preceded because it was relatively

frequently observed, and the situation was then in the latter case. By contrast, in the

painless grid-world (Fig 5), the former case appeared.

The OVaRLAP model enabled safe and efficient exploration in the painful

grid-world navigation task. The transition of the value function for the OVaRLAP agent

shows how stimulus generalization and discrimination contributed to managing the

trade-off between reward-seeking and risk aversion (Fig 4, top).

First, punishment learning due to hitting walls was generalized quickly, as

shown in the value function after five episodes. It led to a preference for the center of

the passage (i.e., risk aversion). The OVaRLAP agent indeed first showed fewer wall

hits than did the simple TD learning and MaxPain agents (Fig 3C and 3F). It contributed

to reducing the number of steps to reach either of the goals in the early learning phase

(Fig 3B and 3E). The OVaRLAP agent thereafter increased the values of positions close

to the walls. This transition indicated that the agent discriminated between the safe and

painful positions. This discrimination increased the tendency to reach the high-reward

goal. In short, stimulus generalization of punishment learning induced risk aversion, followed by discrimination for switching to reward-seeking. The simple TD learning agent did not show risk aversion (Fig 4, middle). Its value function was optimized to maximize future reward, which is consistent with its high reward per step (Fig 3A and 3D). The MaxPain agent showed strong risk aversion, based on its separate value learning system to expect future pain (Fig 4, bottom row). It achieved very few wall hits (Fig 3B and 3E), but meanwhile, it maintained risk aversion and low values on the way to the high-reward goal, which corresponded to a lower reward per step, compared to the other agents (Fig 3A and 3D).

Stimulus generalization and discrimination were effective in safe and efficient exploration; however, its dysfunction may induce aberrant learning behaviors, as demonstrated by the disturbed OVaRLAP (Fig 5). The impaired update for the negative TD error in combination with the noise in the fixed connections induced aberrant valuation. The value increased by noisy stimulus generalization was not reshaped by discrimination because of the impairment of the punishment learning. A single update of the value was only slightly affected by the noisy stimulus generalization (Fig 5A); however, as the number of arrivals to the actual goals increased, such aberrant updates of the value function would have allotted abnormally high values to some positions that were actually of no reward (Fig 5B–5C).

The structure of OVaRLAP gives insight into the neurobiological basis of stimulus generalization and discrimination. The two pre-output neurons separately responded to positive and negative prediction errors so as to update the connections between the hidden-layer neurons and the corresponding pre-output neuron. This hybrid learning system exhibits good correspondence to the striatal dopamine system in which D1- and D2-SPNs differentially respond to dopamine so that the connections between the cortex and the striatal SPNs are differently modulated [22, 24, 25]. Transforming the input into the hidden-layer activity is an approximation of the process by which an

external stimulus and the internal state are encoded into neural activity patterns of the

cortex. This process is assumed to be rather independent from dopamine-dependent

plasticity. However, this process should not be simply based on random connections

because the similarity of the inputs has to be maintained in the encoding process to

achieve stimulus generalization. The encoding could instead be learned in a different

manner from the reward-related learning. Therefore, the fixed connections between the

input and hidden layers in OVaRLAP can be the result of learning for such encoding

process. How the brain learns the encoding process is a topic for future research, but

some implications are derived from computational models of the primary visual cortex

and the primary auditory cortex that adopted unsupervised learning [37, 38].

Compared to ordinary reinforcement learning algorithms, the uniqueness of the

OVaRLAP model is that it is characterized by fast generalization and value separation.

Its advantage regarding safe and efficient exploration primarily occurred by fast

generalization, whereas its potential defect in causing maladaptive behaviors was

derived from fast generalization and from value separation. Mikhael et al. [26]

previously demonstrated the advantage of value separation. Their model coded reward

uncertainty into the sum of the synaptic weights of D1 and D2 SPNs. In addition, their

model can adjust the tendency to choose or avoid risky options by changing the weight

of the positive and negative values, which is assumed to reflect tonic dopamine level.

The further advantages of the value separation were not major topics in our current

study, although the OVaRLAP model can also enjoy such advantages. The OVaRLAP

model can encode reward uncertainty in distinct connections updated by positive and

negative TD errors (red and blue arrows, respectively, in Fig. 1A, left), and can adjust

risk-taking tendency by changing the connection weights between the pre-output

neurons to the output neuron, which were set constant for simplicity in this study.

The potential defect of OVaRLAP causing maladaptive behaviors can provide a

hypothesis on psychiatric disorders. Based on the correspondence between OVaRLAP

and the brain, the result for the disturbed OVaRLAP showed the possibility that the noisy encoding process in the cortex and the impairment of dopamine-dependent plasticity induce abnormal stimulus generalization and discrimination, which may underlie delusional symptoms. The relationship between cortical disconnectivity and disrupted learning in schizophrenia has been implied in computational studies [39, 40]; therefore, alterations in cortical connectivity could be a cause of a noisy encoding process. Histologic examinations and diffusion tensor imaging studies for patients with schizophrenia revealed reduced spine density and disrupted white matter connectivity, respectively [41-43]. Reinforcement learning models have been used for attempts to explain positive symptoms, including delusion, in schizophrenia [44-46]. However, these studies do not link abnormal cortical connectivity to positive symptoms. They attribute positive symptoms to aberrant salience (i.e., a surprise response to nonsalient events) [47]. Thus, they focused on an abnormality in the dopamine system, which was also supported by neurobiological evidence [48, 49]. The OVaRLAP model is a new corticostriatal learning model that relates delusional symptoms to an abnormality in cortical connectivity and in the dopamine system.

The relationship between abnormal stimulus generalization and schizophrenia has been investigated by psychological research [3, 32, 33]. The research is based on the hypothesis that abnormal generalization underlies delusional symptoms in schizophrenia. Some studies imply heightened stimulus generalization in schizophrenia. However, the reported abnormality was not sufficiently remarkable for explaining delusion in a straightforward manner. This finding can be attributed to the conditioning paradigm used for their behavioral experiments. Patients with schizophrenia have various deficits in cognitive function; therefore, the experimental design needed to be simple to attribute the result to stimulus generalization rather than other factors. Computational models may potentially be used to investigate how a specific deficit in cognitive function leads to psychotic symptoms through complex learning processes.

The OVaRLAP model showed that a small abnormality in stimulus generalization in

combination with an unbalanced response to positive and negative prediction error may

induce aberrant valuation after reward-related learning, including action selection, state

transition, and obtaining rewards from multiple sources.

Acknowledgement

We would like to thank Hidetoshi Urakubo for his helpful comments.

References

1. Dunsmoor JE, Paz R. Fear Generalization and Anxiety: Behavioral and Neural Mechanisms. Biol Psychiatry. 2015;78(5):336-343.

2. Asok A, Kandel ER, Rayman JB. The Neurobiology of Fear Generalization. Front Behav Neurosci. 2018;12:329.

3. Kahnt T, Tobler PN. Dopamine regulates stimulus generalization in the human hippocampus. Elife. 2016;5:e12678.

4. Ghirlanda S, Enquist M. A century of generalization. Anim Behav. 2003;66(1):15-36.

5. Thorndike EL. Animal intelligence: An experimental study of the associative processes in animals. Psychol Monogr. 1898;2(8).

6. Ghirlanda S, Enquist M. Artificial neural networks as models of stimulus control. Anim Behav. 1998;56(6):1383-1389.

7. Franks DW, Ruxton GD. How robust are neural network models of stimulus generalization? Biosystems. 2008;92(2):175-181.

8. Shepard RN, Kannappan S. Connectionist Implementation of a Theory of Generalization. In: Advances in Neural Information Processing Systems 3. 1990 Proceedings of the Neural Information Processing Systems (NIPS) Conference. NIPS: San Diego, CA. 1991. p. 665-671.

9. Wisniewski MG, Radell ML, Guillette LM, Sturdy CB, Mercado E 3rd. Predicting shifts in generalization gradients with perceptrons. Learn Behav. 2012;40(2):128-144.

10. Glimcher PW. Understanding dopamine and reinforcement learning: the dopamine reward prediction error hypothesis. Proc Natl Acad Sci USA. 2011;108(Suppl 3):15647-15654.

11. Frank MJ, Seeberger LC, O'reilly RC. By carrot or by stick: cognitive reinforcement learning in parkinsonism. Science. 2004;306(5703):1940-1943.

12. Doya K. Reinforcement learning: computational theory and biological mechanisms.

HFSP J. 2007;1(1):30-40.

13. Mnih V, Kavukcuoglu K, Silver D, Rusu AA, Veness J, Bellemare MG, et al.

Human-level control through deep reinforcement learning. Nature.

2015;518(7540):529-533.

14. Whittington JCR, Bogacz R. Theories of Error Back-Propagation in the Brain.

Trends Cogn Sci. 2019;23(3):235-250.

15. DeLong MR. Primate models of movement disorders of basal ganglia origin.

Trends Neurosci. 1990;13(7):281-285.

16. Nambu A. Globus pallidus internal segment. Prog Brain Res. 2007;160:135-150.

17. Amemori K, Gibb LG, Graybiel AM. Shifting responsibly: the importance of

striatal modularity to reinforcement learning in uncertain environments. Front

Hum Neurosci. 2011;5:47.

18. Collins AG, Frank MJ. Opponent actor learning (OpAL): modeling interactive

effects of striatal dopamine on reinforcement learning and choice incentive.

Psychol Rev. 2014;121(3):337-366.

19. Meredith GE, Baldo BA, Andrezjewski ME, Kelley AE. The structural basis for

mapping behavior onto the ventral striatum and its subdivisions. Brain Struct Funct.

2008;213(1-2):17-27.

20. Schultz W. Neuronal Reward and Decision Signals: From Theories to Data.

Physiol Rev. 2015;95(3):853-951.

21. Tepper JM, Abercrombie ED, Bolam JP. Basal ganglia macrocircuits. Prog Brain

Res. 2007;160:3-7.

22. Reynolds JN, Hyland BI, Wickens JR. A cellular mechanism of reward-related

learning. Nature. 2001;413(6851):67-70.

23. Surmeier DJ, Shen W, Day M, Gertler T, Chan S, Tian X, et al. The role of

dopamine in modulating the structure and function of striatal circuits. Prog Brain

Res. 2010;183:149-167.

24. Yagishita S, Hayashi-Takagi A, Ellis-Davies GC, Urakubo H, Ishii S, Kasai H. A

critical time window for dopamine actions on the structural plasticity of dendritic

spines. Science. 2014;345(6204):1616-1620.

25. Hikida T, Yawata S, Yamaguchi T, Danjo T, Sasaoka T, Wang Y, et al.

Pathway-specific modulation of nucleus accumbens in reward and aversive

behavior via selective transmitter receptors. Proc Natl Acad Sci USA.

2013;110(1):342-347.

26. Mikhael JG, Bogacz R. Learning reward uncertainty in the basal ganglia. PLoS

Comput Biol. 2016;12(9):e1005062.

27. Elfwing S, Seymour B. Parallel reward and punishment control in humans and

robots: Safe reinforcement learning using the MaxPain algorithm. In: Proceedings

of the 2017 Joint IEEE International Conference on Development and Learning

and Epigenetic Robotics (ICDL-EpiRob), September 18–21, 2017. IEEE:

Piscataway, NJ. 2017. pp. 140-147.

28. Cox J, Witten IB. Striatal circuits for reward learning and decision-making. Nat

Rev Neurosci. 2019;20(8):482-494.

29. Huang G-B, Zhu Q-Y, Siew C-K. Extreme learning machine: Theory and

applications. Neurocomputing. 2006;70(1-3):489-501.

30. Lukoševičius M, Jaeger H. Reservoir computing approaches to recurrent neural

network training. Comput Sci Rev. 2009;3(3):127-49.

31. Maass W, Natschläger T, Markram H. Real-time computing without stable states: a

new framework for neural computation based on perturbations. Neural Comput.

2002;14(11):2531-2360.

32. Ralph DE. Stimulus generalization among schizophrenics and normal subjects. J

Abnorm Psychol. 1968;73(6):605-609.

33. Buss AH, Daniell EF. Stimulus generalization and schizophrenia. J Abnorm

Psychol. 1967;72(1):50-53.

34. Bordi F, LeDoux J. Sensory tuning beyond the sensory system: an initial analysis of auditory response properties of neurons in the lateral amygdaloid nucleus and overlying areas of the striatum. J Neurosci. 1992;12(7):2493-2503.

35. Sutton RS, Barto AG. Reinforcement Learning: An Introduction. 2nd ed. MIT Press: Cambridge, MA. 2018.

36. Rummery G, Niranjan M. On-Line Q-Learning Using Connectionist Systems. Technical Report CUED/F-INFENG/TR 166. Cambridge University Engineering Department, Cambridge, United Kingdom. 1994.

37. Hyvärinen A, Hoyer PO. A two-layer sparse coding model learns simple and complex cell receptive fields and topography from natural images. Vision Res. 2001;41(18):2413-2423.

38. Terashima H, Okada M. The topographic unsupervised learning of natural sounds in the auditory cortex. In: Advances in Neural Information Processing Systems 25. Neural Information Processing Systems Foundation: San Diego, CA. 2012. pp. 2312-2320.

39. Hoffman RE, Dobscha SK. Cortical pruning and the development of schizophrenia: a computer model. Schizophr Bull. 1989;15(3):477-490.

40. Hoffman RE, McGlashan TH. Synaptic elimination, neurodevelopment, and the mechanism of hallucinated "voices" in schizophrenia. Am J Psychiatry. 1997;154(12):1683-1689.

41. van den Heuvel MP, Scholtens LH, de Reus MA, Kahn RS. Associated Microscale Spine Density and Macroscale Connectivity Disruptions in Schizophrenia. Biol Psychiatry. 2016;80(4):293-301.

42. Garey LJ, Ong WY, Patel TS, Kanani M, Davis A, Mortimer AM, et al. Reduced dendritic spine density on cerebral cortical pyramidal neurons in schizophrenia. J Neurol Neurosurg Psychiatry. 1998;65(4):446-453.

43. Ellison-Wright I, Bullmore E. Meta-analysis of diffusion tensor imaging studies in
schizophrenia. Schizophr Res. 2009;108(1-3):3-10.

44. Deserno L, Boehme R, Heinz A, Schlagenhauf F. Reinforcement learning and
dopamine in schizophrenia: dimensions of symptoms or specific features of a
disease group? Front Psychiatry. 2013;4:172.

45. Maia TV, Frank MJ. An Integrative Perspective on the Role of Dopamine in
Schizophrenia. Biol Psychiatry. 2017;81(1):52-66.

46. Katahira K, Yamashita Y. A Theoretical Framework for Evaluating Psychiatric
Research Strategies. Comput Psychiatr. 2017;1:184-207.

47. Kapur S. Psychosis as a state of aberrant salience: a framework linking biology,
phenomenology, and pharmacology in schizophrenia. Am J Psychiatry.
2003;160(1):13-23.

48. Howes OD, Kambeitz J, Kim E, Stahl D, Slifstein M, Abi-Dargham A, et al. The
nature of dopamine dysfunction in schizophrenia and what this means for
treatment. Arch Gen Psychiatry. 2012;69(8):776-786.

49. Daberkow DP, Brown HD, Bunner KD, Kraniotis SA, Doellman MA, Ragozzino
ME, et al. Amphetamine paradoxically augments exocytotic dopamine release and
phasic dopamine signals. J Neurosci. 2013;33(2):452-463.

719
720

Supporting information

S1 Fig. The grid-world configurations used in the painful grid-world navigation task. The grid-world shown in Fig 1B is displayed again at the left top. These five grid-world configurations were generated under the following rules, while avoiding symmetric or similar structures. A wide passage consists of rectangles in which the shorter width/height is 5 (based on the number of grids) and the longer width/height is more than 7; the wide passage does not have a dead end. A narrow passage exists with a width of 2 and a length of 6. The starting position and a goal with a lower reward of 1 are located two grids away from the end of the wide passage and three grids away from side walls (i.e., relatively apart from the walls). The passages have to be surrounded by walls. If the passages are separated by walls, the distance between these passages has to be more than three grids. A goal with a higher reward of 2 is one grid away from the end of the narrow passage (i.e., relatively close to the walls). The shortest path to either of the goal requires 26 steps if the agent has to move to the center of the wide passage before turning to the narrow passage.

739 **Fig 1.**

Fig 2.

Fig 3.

744
745
746

748   **Fig 4.**

Fig 5.