Nonparametric Anomaly Detection on Time Series of Graphs

Dorcas Ofori-Boateng, Yulia R.Gel[*]
Department of Mathematical Sciences, University of Texas at Dallas, U.S.A.
and
Ivor Cribben[†]
Alberta School of Business, University of Alberta, Canada

Abstract

Identifying change points and/or anomalies in dynamic network structures has become increasingly popular across various domains, from neuroscience to telecommunication to finance. One of the particular objectives of the anomaly detection task from the neuroscience perspective is the reconstruction of the dynamic manner of brain region interactions. However, most statistical methods for detecting anomalies have the following unrealistic limitation for brain studies and beyond: that is, network snapshots at different time points are assumed to be independent. To circumvent this limitation, we propose a distribution-free framework for anomaly detection in dynamic networks. First, we present each network snapshot of the data as a linear object and find its respective univariate characterization via local and global network topological summaries. Second, we adopt a change point detection method for (weakly) dependent time series based on efficient scores, and enhance the finite sample properties of change point method by approximating the asymptotic distribution of the test statistic using the sieve bootstrap. We apply our method to simulated and to real data, particularly, two functional magnetic resonance imaging (fMRI) datasets and the Enron communication graph. We find that our new method delivers impressively accurate and realistic results in terms of identifying locations of true change points compared to the results reported by competing approaches. The new method promises to offer a deeper insight into the large-scale characterizations and functional dynamics of the brain and, more generally, into intrinsic structure of complex dynamic networks.
Keywords: Dynamic Networks, Multivariate Time Series, Change point, Sieve Bootstrap

1 Introduction

Identifying and analyzing change points and/or anomalies (which we will use interchangeably) has become an increasingly active area of research in network sciences (Host-Madsen and Zhang, 2018; Messer et al., 2018). For example, in financial trading, a regime shift in the network of transactions is frequently linked to various (often upcoming) insolvencies such as bankruptcies, defaults, and recessions while a change in the network topology of cryptocurrency transactions may suggest a potential money laundering scheme (e.g., Elliott et al., 2014; Vandermarliere et al., 2015). Similar to other biological networks (Wig et al., 2011), the idea of studying the brain as a dynamic functional network is helpful in understanding the complex network organization of the brain and can lead to profound clinical breakthroughs (Bassett and Bullmore, 2006; Rubinov and Sporns, 2010).

Most currently available statistical methods for anomaly detection in dynamic networks have the following limitation: network snapshots at different time points are assumed to be independent (e.g., Peel and Clauset, 2015; Akoglu and Faloutsos, 2010; Harshaw et al., 2016). This assumption appears to be unrealistic in many applications. For example, cryptocurrency entities and their interactions in a network of transactions evolve in time but obviously daily snapshots of the same network cannot be assumed to be independent. This dependence or autocorrelation effect is well documented in the time series literature since the 1960s (Zellner, 1962; Wolff et al., 1967). However, in many cases, this effect is often overlooked in practice, which leads to unreliable and false conclusions. Neglecting the dependence among the network snapshots at different time points leads to inflated false-positive rates of change points or anomalies, especially for small and moderate sample sizes.

To overcome this limitation, we propose a new distribution-free framework, named Network Evolution Detection Method ($NEDM$), for anomaly detection in dynamic networks and evolution network structures of high dimensional time series. The setup for the proposed methodology entails the following: With each network snapshot

[*]The work of D.O.B and Y.R.G. was partially supported by NSF grant numbers IIS 1633331 and DMS 1736368).

[†]The work of I.C was partially supported by NSERC: Grant/Award Number: RGPIN-2018-06638 and the Xerox Faculty Fellowship, Alberta School of Business.

as a graph object, we find its unique univariate characterization, for example, mean degree, clustering coefficient, and clique number. As a result, a series of possibly very high dimensional network snapshots is transformed into a time series of scalars. Given the temporal dependence of network snapshots, it is infeasible to assume that the resulting time series of linear characteristics is independent. Next, we adopt a change point detection method (Gombay, 2008) for (weakly) dependent time series that is based on efficient scores. To enhance the finite sample properties of detected change points, we approximate the asymptotic distribution of the test statistic with a sieve bootstrap procedure (Kreiss, 1988, 1992; Bühlmann et al., 1997). We derive asymptotic properties for the $NEDM$ statistic, validate its performance in respect to competing anomaly detection methods via synthetic and real data experiments. We illustrate utility of the $NEDM$ method in application to two input data types: two multivariate functional magnetic resonance imaging (fMRI) time series data and a dynamic network of the Enron email communication (Park et al., 2012; Priebe et al., 2005; Diesner et al., 2005). For the sake of brevity, we defer the analysis of one fMRI data to Appendix B.

In application, we find that the $NEDM$ has the potential to unveil the time-varying cognitive states of both controls and subjects with neuropsychiatric diseases such as Alzheimer's, dementia, autism and schizophrenia in order to develop new understandings of these diseases. By applying the $NEDM$, we can consider whole brain dynamics, which promises to offer deeper insight into the large scale characterizations of functional architecture of the whole brain.

To sum up, the proposed $NEDM$ has the following unique and significant attributes:

1. It is, to the best of our knowledge, the first paper to consider estimating change points in any graph summary statistic for the time-evolving network structure in a multivariate time series context.

2. It can consider thousands of time series and, in particular, the case where P, the number of time series is much greater than T ($P >> T$), the number of time points.

3. Unlike existing methods it is not limited by assuming that network snapshots at different time points are independent.

4. It enhances the finite sample properties of the change point method by approximating the asymptotic distribution of the test statistic using the sieve bootstrap.

5. Although it is inspired by and developed for brain connectivity studies, it pertains to a general setting and can also be used in a variety of situations where one wishes to study the evolution of a high dimensional network over time.

The remainder of the paper is organized as follows. We introduce the $NEDM$ in Section 3. A simulation study that examines the finite sample performance of our method via sieve bootstrapping (Kreiss, 1988, 1992; Bühlmann et al., 1997) is also covered in Section 3. In Section 4, we describe the properties for building synthetic data and then provide background information on the fMRI and Enron dynamic network datasets in Section 5. The performance of the proposed algorithm, on both the synthetic and real world data, is detailed in Section 6. Conclusion and future work is provided in Section 7. Finally, proofs, supplementary material and processes are deferred to the Appendix.

2 Related Work

There exists a vast body of studies on dynamic network models across various disciplines (see, Barabási and Albert (1999) and references therein). One method based on the minimum description length (MDL) principle and compression techniques (Sun et al., 2007) flattens the adjacency matrices into binary strings and use compression cost to derive data specific features. Another procedure (DELTACON) proposed by Koutra et al. (2013) relies on the similarity measures between a pair of equal node networks. However, anomalous points reported by this procedure tend to suffer from limited interpretability due to their lack of statistical quantifiers (such as critical numbers or p-values).

The first comprehensive treatment of high dimensional time series factor models with multiple change points in their second-order structure has been put forward by Barigozzi et al. (2018). To detect changes in the covariance matrix of a multivariate time series, Aue et al. (2009) introduced a method using a nonparametric CUSUM type test, and Dette and Wied (2016) proposed a test where the dimension of the data is fixed. Furthermore, Cribben et al. (2012, 2013) put forward a method for detecting change in the precision matrices (or undirected graph) from a multivariate time series. In turn, Cribben and Yu (2017) introduced a graph-based multiple change point method for changes in the community network structure between high dimensional time series, called Network Change Point Detection, that uses an eigen-space based statistic for testing the community structures changes in stochastic block model sequences. In addition, Barnett and Onnela (2016) developed a method for detecting change points in correlation networks that, unlike previous change point detection methods designed for time series data, requires no distributional assumptions.

3   Methodology

In this section, we describe the proposed contribution intended to track structural changes within the network structure of datasets. We use the terms change point detection and anomaly detection as well as the terms graphs and networks interchangeably. Table 1 in Appendix A details the notation and symbols for the rest of the paper.

3.1   Input Data: Graphs and Multivariate Time Series

Our proposed methodology is applicable to two types of the input data: data that are originally in a form of a graph, and multivariate time series that are used to construct a graph, based on a certain similarity measure, e.g., correlation. Since one of our primary motivating applications is multivariate fMRI time series, below we describe in details how networks can be constructed from such data sets.

Networks from a multivariate time series In many applications such as, for instance, neuroscience and finance, input data are multivariate time series, and the first step consists of constructing a graph structure based on a user-selected (dis)similarity measure. That is, suppose $\boldsymbol{D}$ is a $T \times P$ multivariate time series, where T and P are the number of time points and the number of time series, respectively. From the multivariate $\boldsymbol{D}$, we take a q-row sample, $\boldsymbol{F} \in \mathbb{R}^{q \times P}$, in a sequential "one-in, one-out" manner. This mode of data segmentation is known as the *overlapping/sliding window* technique ([Keogh et al., 2001](#)) and is ideal for maintaining the time dependency structure within $\boldsymbol{D}$, while taking as many samples as possible from the data matrix, $\boldsymbol{D}$. Because each q-row sample contains information from previous or successive samples, this segmentation procedure has the advantage of capturing all (and any) network structure disturbance. Note that, depending on the window length q, some data information may not adequately captured because not every row in the data matrix has an equal number of appearances in all the $\boldsymbol{F}$ folds created. For instance, the first row ($\boldsymbol{D}_{[1, \ ]}$) and the last row ($\boldsymbol{D}_{[T, \ ]}$) are least likely to be included in the collection of all $\boldsymbol{F}$s. However, because we hypothesize that the changes points occur within the data and not at the end points (at the beginning and end of the time series) our detection procedure and results will not suffer.

Armed with $\boldsymbol{F}$, we compute a correlation matrix $\boldsymbol{R} = (\rho_{rs}) \in \mathbb{R}^{P \times P}$ by quantifying the linear association between the P vertices in $\boldsymbol{F}$. With $\boldsymbol{R}$ and a pre-defined threshold ω[1], we define the finite graph-associated adjacency matrix $\boldsymbol{A} = (a_{rs}) \in \mathbb{R}^{P \times P}$ using

$$a_{rs} = \begin{cases} 1 & \text{if } \rho_{rs} \geqslant \omega \\ 0 & \text{otherwise.} \end{cases}$$

Given each such adjacency matrix $\boldsymbol{A}$, we then construct a graph object $G_t = (V_t, E_t)$.

Input data as a graph structure Alternatively, the original input data can take form of a graph G_t observed at time point $t, t = 1, 2, \ldots$. Such examples include communication networks (see, for instance, the Enron study in Section 5 and 6), power grid networks, and the emerging blockchain technology. Indeed, one of the salient blockchain features is that all transactions are permanently recorded on distributed ledgers and publicly available. As a result, blockchain graph G_t can be constructed directly on each transaction, bypassing application of correlation and other similarity measures.

Finally, armed with the sequence of the graph objects G_t, we then calculate various global and local graph summary statistics ([Newman, 2003](#); [Barabási and Pósfai, 2016](#)). In particular, from each graph, we estimate the following graph summaries (Y_t): Average Clustering Coefficient (ACC), Average Path Length (APL), Maximum Node Betweenness centrality ($maxBETW$), Clique number ($CLQNUM$), Mean Degree (MD) and Minimum Local Clustering Coefficient ($minLCC$).

3.2   Detection procedure and the sieve bootstrap

Following the dimension reduction and data structure simplification in Section [3.1](#), our next task is to identify the time(s) at which the regime shift(s) occur in the series of lower dimensional embeddings. In our case, we are interested in testing the following hypotheses:

H_0 : There is no change in the underlying structure of
$\quad \{Y_t\}_{t=1}^n$

H_a : At an unknown time $t \in \{1, \ldots, n\}$ a change occurs in
$\quad \{Y_t\}_{t=1}^n$.

We assume that the appropriate model to fit to $\{Y_t\}_{t=1}^n$ is a strictly stationary and purely non-deterministic autoregressive $[AR(p)]$ model with Gaussian independent and identically distributed (i.i.d.) white noise ε_t. The assumption of Gaussianity for ε_t can be relaxed and substituted by the appropriate moment conditions ([Gombay, 2008](#)). (We run experiments on time series with non-Gaussian innovations and find that while the proposed change point detection is applicable to a non-Gaussian case, performance largely depends on deviations from the normality assumption and sample size. For instance, under the null hypothesis of no change, nominal α-level of 0.05, and an $AR(1)$

---

[1]In the experimental analysis we select parameters q and ω based on our previous neuroscience studies. Alternatively, q and ω can be selected via cross-validation (see the Conclusion for more detailed discussion).

process with φ of 0.5, it takes approximately 100 observations to achieve an approximate size of the test of 0.05 for a case of t-distribution with 9 degrees of freedom; in turn, it requires about 200 observations from uniform distribution to achieve a similar empirical size of the test.) In turn, approximation of time series via AR(p) models, including the case of $p \to \infty$, is widely used in theory and methodology of time series analysis (for overview see, for instance, Pourahmadi (2001); Shumway and Stoffer (2017), and references therein).

Remark Note that under the considered problem of change point detection on networks, network topological summary statistic $\{Y_t\}_{t=1}^n$ is estimated from the data. There currently exist no theoretical results on asymptotic properties of network statistics, especially in a conjunction with dynamic networks; that is, besides invoking central limit theorem for network mean degree, nothing can be formally said on a linear process representation of $\{Y_t\}_{t=1}^n$ or its distributional properties. As a result, our approach is approximation-based and data-driven; that is, while we cannot provide theoretical bounds on the linear process approximation of $\{Y_t\}_{t=1}^n$, we validate performance of the proposed *NEDM* against known ground truth change points.

In particular, we define Y_t as

$$Y_t - \mu = \sum_{k=1}^p \varphi_k(Y_{t-k} - \mu) + \varepsilon_t \ , \quad t \geqslant p+1 \qquad (1.1)$$

with $\mathbf{E}[Y_t] = \mu$ and let $\boldsymbol{\xi} = (\mu, \sigma^2, \varphi_1, \ldots, \varphi_p)^T$. Given equation (1.1), we formally test the null hypothesis of no change

$$H_0 : \boldsymbol{\xi} = \boldsymbol{\xi}_0, \forall \ t \in \{1, \ldots, n\} \quad \text{against}$$
$$H_a : \boldsymbol{\xi} = \boldsymbol{\xi}_0, \ \forall \ 1 \leqslant t \leqslant \tau - 1, \ at \ \tau = [\rho n], \ \rho \in (0,1) ;$$
$$\boldsymbol{\xi} = \boldsymbol{\xi}_a, \ \forall \ t \geqslant \tau.$$

Most studies on change point detection calculate the pre-regime switch and post-regime switch parameter values of all possible change points $\tau \in (1, n)$, and then either use the strength of their differences to determine a regime switch or use these parameter values in the likelihood function (Picard, 1985; Davis et al., 1995; Inoue, 2001). However, we use a detection algorithm that involves a one-time parameter estimation and allows us to test for change in the individual elements of $\boldsymbol{\xi}$. In line with allowing for one-sided tests and for flexibility, we adopt the change point statistic of Gombay (2008) which utilizes the efficient score vector $\nabla_{\boldsymbol{\xi}} \ell_k(Y_1, \ldots, Y_n; \boldsymbol{\xi}) = \nabla_{\boldsymbol{\xi}} \ell_k(\boldsymbol{\xi})$ with ℓ_k as the log-likelihood function on $\{Y_t\}_{t=1}^n$. For for $1 \leqslant r \leqslant p+2$ denote $\hat{\mu}, \hat{\sigma}^2, \hat{\varphi}_1, \ldots, \hat{\varphi}_p$ as the simultaneous solutions of the $p+2$

equations $\partial/\partial \xi_r \ell_n(\boldsymbol{\xi}) = 0$, and let

$$\hat{\mathbf{B}}(u) = n^{-1/2} I^{-1/2}(\widehat{\xi_n}) \begin{pmatrix} \dfrac{\partial}{\partial \mu} \ell_{[nu]}(\widehat{\xi_n}) \\ \dfrac{\partial}{\partial \sigma^2} \ell_{[nu]}(\widehat{\xi_n}) \\ \nabla_{\varphi} \ell_{[nu]}(\widehat{\xi_n}) \end{pmatrix} \qquad (1.2)$$

be a Gaussian process (a partial sums process approximation for the structure of $\nabla_{\boldsymbol{\xi}} \ell_k(\boldsymbol{\xi})$).

If ξ_r, for $1 \leqslant r \leqslant p+2$, changes at $\tau = [\rho n]$ with $0 < \rho < 1$, then the estimator $\hat{\tau}$ is defined by:

$$\hat{\tau}_n = \min_n \left\{ \frac{\partial}{\partial \xi_r} \ell_k(\widehat{\xi_n}) = \max_{1 < m \leqslant n} \frac{\partial}{\partial \xi_r} \ell_m(\widehat{\xi_n}) \right\}, \qquad (1.3)$$

and

$$\hat{\tau}_n = \min_n \left\{ \frac{\partial}{\partial \xi_r} \ell_k(\widehat{\xi_n}) = \min_{1 < m \leqslant n} \frac{\partial}{\partial \xi_r} \ell_m(\widehat{\xi_n}) \right\}, \qquad (1.4)$$

for one-sided tests (both left and right respectively); and for two-sided tests

$$\hat{\tau}_n = \min_n \left\{ \left| \frac{\partial}{\partial \xi_r} \ell_k(\widehat{\boldsymbol{\xi}_n}) \right| = \max_{1 < m \leqslant n} \left| \frac{\partial}{\partial \xi_r} \ell_m(\widehat{\boldsymbol{\xi}_n}) \right| \right\}. \qquad (1.5)$$

Proof for the consistency of $\hat{\tau}$ is provided in Gombay (2008). The asymptotic independence of the components of $\hat{B}(u)$ allows us define the change point test statistic for each $\xi_r \in \boldsymbol{\xi}$ (see Gombay (2008) for the related discussion). Hence, we reject the null hypothesis, for *one-sided tests* along the sequence $\{Y_t\}_{t=1}^n$, if

$$\sup_{0 \leqslant u \leqslant 1} \hat{B}^{(r)}(u) \geqslant C_1(\alpha), \qquad (1.6)$$

where $C_1(\alpha)$ is calculated from

$$\left\{ x : P\left(\sup_{0 \leqslant u \leqslant 1} B^{(1)}(u) \geqslant x \right) = e^{-2x^2} = \alpha \right\}.$$

If we are interested in *two-sided* hypothesis testing, a change in ξ_r (along the sequence $\{Y_t\}_{t=1}^n$) is acknowledged whenever

$$\sup_{0 \leqslant u \leqslant 1} |\hat{B}^{(r)}(u)| \geqslant C_2(\alpha), \qquad (1.7)$$

such that $C_2(\alpha)$ is calculated from

$$\left\{ x : P\left(\sup_{0 \leqslant u \leqslant 1} |B^{(1)}(u)| > x \right) = \sum_{k \neq 0} (-1)^{k+1} e^{-2(kx)^2} = \alpha \right\}.$$

Convergence of the test statistic $\hat{B}^{(r)}(u)$ to its asymptotic distribution can be relatively slow. The Type I error estimates tend to be conservative with lower power of the test. Under the premise that $\{Y_t\}_{t=1}^n$ follows an AR(p) model with Gaussian i.i.d. white noise, we propose to adopt a

sieve bootstrap procedure for constructing the distribution of the change point test statistic $\hat{B}^{(j)}(u)$ for finite samples. The idea of such bootstrap for time dependent data – originally named AR(∞) bootstrap –goes back to the results of Kreiss (1988, 1992). The approach was later further investigated by Bühlmann et al. (1997) who coined the term *sieve* for this bootstrap method. The procedure is outlined in the Algorithm 1, and its theoretical properties are stated in Theorem 1.

To compare finite sample performance of the asymptotic distribution to the sieve bootstrap method, we simulate data (with a total of 5000 Monte Carlo iterations) from an AR(1) model in equation 1.1 and evaluate the following: the size and power of the test [for precise details on the simulation procedure used, please see Appendix D]. The choice of the model coefficient (φ) depends on ensuring the assumption of weak stationarity for the simulated AR(1) series. Indeed note that as φ approaches 1, the time series gets closer to a random walk process, i.e., we approach to a boundary case of violating the assumptions of weak stationarity, outlined for the change point statistic based on the efficient scores (Theorem 1 of Gombay (2008)). As a result, performance of the change point detection method deteriorates.

The size of the test for the simulated data, as shown in Table 1, suggests that the asymptotic distribution behaves more conservatively. As φ in the AR(1) model (1.1) increases from -0.5 to 0.5, the size of the test decreases for the asymptotic distribution case. However, the bootstrap technique has size closer to the 5% level of significance. This supports our assertion that the asymptotic distribution of the change point test statistic has relatively conservative Type I error, and validates the creation of the second part of our algorithm.

The power of the test is also displayed in Figure 1. Evidently, as φ increases from -0.5 to 0.5, there is a drop in the power values for both the asymptotic and sieve bootstrap (with the larger values occurring when $\varphi = -0.5$). Furthermore, it is apparent here that the power obtained by using sieve bootstrap exceeds that which is reported by the asymptotic distribution.

Theorem 1 (Sieve bootstrap) *Let Y_t be an AR(p) process as defined in equation (1.1). Under the assumption of Theorem 1 in Gombay (2008) (stated in Appendix A), the following holds for the bootstrap estimate $\hat{B}^{*(r)}(u)$:*

$$\max_{1 \leqslant r \leqslant p+2} \sup_{0 \leqslant u \leqslant 1} |\hat{B}^{*(r)}(u) - \hat{B}^{(r)}(u)| \longrightarrow 0 \quad in\ probability,$$
$$(1.8)$$

that is, $\max_{1 \leqslant r \leqslant p+2} d_K\{\hat{B}^{*(r)}(u), \hat{B}^{(r)}(u)\} = o_p(1)$*, where d_K is the Kolmogorov distance.*

Algorithm 1: Nonparametric sieve bootstrap procedure for the change point statistic under an $AR(p)$ process

---

Input : Time series $\{Y_t\}_{t=1}^n$; Change point test statistic $T_n(.)$; Level of significance α; Number of bootstrap replications Γ.

1 For $\{X_t\}_{t=1}^n = \{Y_t - \hat{\mu}\}_{t=1}^n$, fit an $AR(p)$ process and extract the coefficients $\{\hat{\varphi}_r\}_{r=1}^p$.

2 Calculate $T_n(X_1, X_2..., X_n)$.

3 Obtain $\widetilde{\varepsilon}_t$ from the residuals $\hat{\varepsilon}_t = X_t - \sum_{k=1}^p \hat{\varphi}_k X_{t-k}$.

(**Note**: $\widetilde{\varepsilon}_t = \hat{\varepsilon}_t - \bar{\varepsilon}_n$, where $\bar{\varepsilon}_n = \frac{1}{n}\sum_{t=1}^n \hat{\varepsilon}_t$).

4 for $i \leftarrow 1 : \Gamma$ **do**

5   Sample, with replacement, $\{\widetilde{\varepsilon}_t^*\}_{t=1}^n$ from $\{\widetilde{\varepsilon}_t\}_{t=1}^n$.

6   Simulate $\{X_t^*\}_{t=1}^n$, with innovation $\{\widetilde{\varepsilon}_t^*\}_{t=1}^n$ and coefficients $\{\hat{\varphi}_r\}_{r=1}^p$.

7   Calculate the change point test statistic $T_n^*(X_1^*, X_2^*, ..., X_n^*)$.

8   Define Z_i for each Monte-Carlo iteration as:

9 $Z_i = \begin{cases} 1 & |T_n^*| \geqslant |T_n| \\ 0 & \text{otherwise.} \end{cases}$

10 end

11 The bootstrap p-value for testing H_0 is given by

$\sum_{i=1}^{\Gamma} \dfrac{Z_i}{\Gamma}$.

Proof of Theorem 1 is in the Appendix.

Suppose $\widetilde{\varepsilon}_t = \hat{\varepsilon}_t - \bar{\varepsilon}_n$, with $\bar{\varepsilon}_n = 1/n \sum_{t=1}^n \hat{\varepsilon}_t$, the nonparametric sieve bootstrap estimate $\hat{B}^{*(r)}(u)$ can be replaced with a hybrid parametric bootstrap estimate $\hat{B}^{\diamond(r)}(u)$ by generating a Gaussian sample $\{\widetilde{\varepsilon}_t^{\diamond}\}_{t=1}^n \sim N(0, s_n^2)$, with $s_n^2 = \sum_{t=1}^n (\widetilde{\varepsilon}_t - \bar{\widetilde{\varepsilon}}_t)^2/(n-1)$ as the sample variance of $\{\widetilde{\varepsilon}_t\}_{t=1}^n$. This yields a finite sample performance similar to that of $\{\widetilde{\varepsilon}_t^*\}_{t=1}^n$, with reduced computing time.

Corollary 1 If Y_t satisfies equation (1.1), then under H_0

$$\max_{1 \leqslant r \leqslant p+2} d_K\{\hat{B}^{\diamond(r)}(u), \hat{B}^{(r)}(u)\} \longrightarrow 0 \quad in\ probability \quad (1.9)$$

with d_K as the Kolmogorov distance.

Proof of Corollary 1 is in the Appendix.

4 Simulations

To validate of the $NEDM$, we compare it with the BOM (Barnett and Onnela, 2016) but not with the $KVFM$ (Koutra et al., 2013) using simulated data. In particular, we provide sensitivity analysis for the $NEDM$ under diverse q, ω and ROI choices. We do not compare the $NEDM$ to the $KVFM$ because it does not provide a quantifier for the statistical significance, such as a p-value, of the change

Table 1: The size of the test for simulated data from an $AR(1)$ model for various samples sizes (n), change point locations (τ) and φ values.

n	τ	$\varphi = -0.5$		$\varphi = 0.1$		$\varphi = 0.5$	
		Asym.	Boot.	Asym.	Boot.	Asym.	Boot.
100	50	0.0394	0.0578	0.0280	0.0500	0.0232	0.0508
200	100	0.0408	0.0506	0.0348	0.0474	0.0314	0.0494
300	180	0.0372	0.0486	0.0380	0.0460	0.0410	0.0538

Figure 1: The power of the test ($n = 100$) plotted against φ for the asymptotic distribution and sieve bootstrap procedure when testing for a change in the mean of an $AR(1)$ model.

point detected. Such a quantifier is necessary for deducing the Power and Size of the test for the methods under study. The simulation study covers two scenarios: a no-change point and a one-change point scenarios. As evaluation metrics, we use the true detection rates (i.e., power of the test) and the false alarm levels under a pre-defined significance level (*i.e.* size of the test). A total of 100 Monte Carlo simulations is run in each scenario under diverse window length q, threshold parameter ω, two different time series lengths ($T = 200, 300$) and for two graph node sizes ($P = 5, 10$).

The first simulation illustrates the baseline (no change point) scenario using a vector autoregression (VAR; Zellner, 1962; Hamilton, 1995) model; the VAR model is a generalization of the univariate AR process with more than one time-evolving component. Given the ($p \times 1$) vector of time series variables $\boldsymbol{F}_t = (f_{1t}, f_{2t}, \ldots, f_{pt})^T$, the w-lag vector autoregressive (VAR(w)) process is defined as

$$\boldsymbol{F}_t = \boldsymbol{a} + \boldsymbol{\Pi}_1 \boldsymbol{F}_{t-1} + \boldsymbol{\Pi}_2 \boldsymbol{F}_{t-2} + \cdots + \boldsymbol{\Pi}_w \boldsymbol{F}_{t-w} + \boldsymbol{\epsilon}_t, \quad (1.10)$$
$$t = 1, \ldots, T.$$

where $\boldsymbol{\Pi}_i$ is an ($p \times p$) coefficient matrix and $\boldsymbol{\epsilon}_t$ is an ($p \times 1$)

unobservable mean white noise vector process with time invariant covariance matrix $\boldsymbol{\Sigma}$ (Zivot and Wang, 2007). The VAR model is used to reconstruct the linear interdependency element prevalent among multivariate time series applications such as fMRI data.

The second simulation, which depicts a single change point scenario, is created by concatenating two data streams from distinct multivariate Gaussian distributions: $(\boldsymbol{D}_1, \boldsymbol{D}_2)$ where $\boldsymbol{D}_1 \sim N(\boldsymbol{\mu} = \boldsymbol{0}, \boldsymbol{\Sigma}_1 = (\Sigma_{1ij}))$ and $\boldsymbol{D}_2 \sim N(\boldsymbol{\mu} = \boldsymbol{0}, \boldsymbol{\Sigma}_2 = (\Sigma_{2ij}))$ with

$$\Sigma_{1ij} = \begin{cases} 1 & \text{if } i = j \\ 0 & \text{otherwise} \end{cases} \qquad \Sigma_{2ij} = \begin{cases} 1 & \text{if } i = j \\ 0.9 & \text{otherwise.} \end{cases}$$

The results for this analysis are presented in Figures 3 and 4, and a discussion of the sensitivity results is provided in Section 6.

5   Experimental Data

Next, we demonstrate the $NEDM$'s application to two input data types: multivariate fMRI time series with known

change point locations and a portion of the Enron emails network. In the fMRI case study, we compare the performance of the $NEDM$ against two other techniques for anomaly (change point) detection in the multivariate setting: the $KVFM$ from (Koutra et al., 2013) and the BOM from (Barnett and Onnela, 2016). With the Enron networks, we only implement the $NEDM$ with the APL network summary (because from our experiments the APL-based analysis produced the best outcome), and compare the significant change points we find with various events that characterized the timeframe of the Enron scandal. In addition, we compare the performance of the $NEDM$ to results obtained by the $KVFM$. We do not compare our results with the BOM because the BOM is only applicable to multivariate time series data.

5.1   Case study: fMRI data 1

The data was taken from an anxiety-inducing experiment (Cribben et al., 2012, 2013). The task was a variant of a well-studied laboratory paradigm for eliciting social threat, in which participants must give a speech under evaluative pressure. The design was an off-on-off design, with an anxiety-provoking speech preparation task occurring beween lower anxiety resting periods. Participants were informed that they were to be given $2\,min$ to prepare a $7\,min$ speech, and that the topic would be revealed to them during scanning. They were told that after the scanning session they would deliver the speech to a panel of expert judges, though there was "a small chance" they would be randomly selected not to give the speech. After the start of fMRI acquisition, participants viewed a fixation cross for $2\ min$ (resting baseline). At the end of this period, participants viewed an instruction slide for $15\,s$ that described the speech topic, which was "why you are a good friend". The slide instructed participants to be sure to prepare enough for the entire $7\ min$ period. After $2\ min$ of silent preparation, another instruction screen appeared (a relief instruction, $15\ s$ duration) that informed participants that they would not have to give the speech. An additional $2\ min$ period of resting baseline completed the functional run. Data were acquired and preprocessed as described in previous work (Wager et al., 2009). During the course of the experiment a series of 215 images were acquired ($TR = 2\ s$). In order to create ROIs, time series were averaged across the entire region. The data consists of 4 ROIs and heart rate for $n = 23$ subjects. The regions in the data were chosen because they showed a significant relationship to heart rate in an independent data. The temporal resolution of the heart rate was $1\ s$ compared to $2\ s$ for the fMRI data. Hence, the heart rate was down-sampled by taking every other measurement.

5.2   Case study: Enron email networks

This input data are the Enron emails dataset, a benchmark dataset applied in numerous instances of anomaly detection (e.g., Peel and Clauset, 2015; Park et al., 2012; Priebe et al., 2005; Diesner et al., 2005). More information on this dataset can be found online (http://www.cs.cmu.edu/~enron/). We used the cleaned version of the employee -to - employee email (sent and received) network over the period November 1998 to July 2001. We initialize each employee as a single node and aggregate the data by month. This implies that if there is at least one email between two employees within the month under study, an edge is connected to the respective nodes. Figure 2 displays the cumulative nature of the Enron network between November 1998 to July 2001, and the state of the network after two specific month/year periods. In total, we obtain 33 networks with 102 nodes in each network.

6   Results

The $NEDM$ uses the following summary statistics: Average clustering coefficient (ACC), Average Path Length (APL), Maximum Node Betweenness Centrality ($maxBETW$), Clique number ($CLQNUM$), Mean degree (MD) and Minimum Local Clustering Coefficient ($minLCC$). As we already mentioned in the previous section, we compare our method to Barnett's method (BOM) in the simulation study. However, we will include results by Koutra et al.'s DELTACON ($KVFM$) for further verification.

6.1   Simulation study

Figure 3 presents the results for the no-change point scenario. We find that as q increases the size of the test reported by all network summaries under the $NEDM$ increase, leading to more liberal results. Moreover, we find that as ω increases, the size reported by all network summaries under the $NEDM$ improve (and become closer to the 5% level of significance). In particular, we find that the size of the test reported by the $NEDM$ under the $maxBETW$ network summary almost always outperforms the size reported by the BOM (except for one situation when $w = 0.05, T = 200$ and $q = 30$). Furthermore, we notice that two other network summaries (ACC and MD) are highly sensitive to increasing ω, and that their size values improve substantially as ω increases from 0.05 to 0.15. For the BOM results, we find that the size of the test tends to be more liberal as P increases (*i.e.,* size increases from 18% to 20%), and that its performance is inferior to the $NEDM$ with the $maxBETW$ network summary. In conclusion, many of the graph summary statistics appear su-

Figure 2: Enron employee-to-employee email network (November 1998 - July 2001). Top: Cumulative network from November 1998 to July 2001; Bottom (Left): Email network as at November 1998, (Right): Email network as at July 2001.

perior to the BOM in terms of the size of the test.

The results for the one-change point simulation is presented in Figure 4. Overall, the BOM appears to attain the highest power (*i.e.,* it correctly flags the one-change scenario every time). However, this performance is equally matched by the $NEDM$ with the $maxBETW$ network summary. In addition, for other network summaries utilized in the $NEDM$, we found that power drops as ω and T increase, and that power increases as q increases. Furthermore, we notice that as T increases from 200 to 300, the power reported by our $NEDM$ with the $CLQNUM$ summary statistic experiences a substantial drop, but this also improves as q rises.

In summary, we found that both the power and the size of the test (detection ability) are sensitive to the choice of parameters (q, ω and T). In addition, while the BOM has excellent power, it suffers from liberal Type I errors. Overall, we found that the $NEDM$ in combination with the $maxBETW$ has the best performance in terms of maintain-

ing the size of the test while also having excellent power.

6.2 Case study: fMRI data 1

From our analyses, we obtained the results displayed in Figure 5 for the $NEDM$ (with ACC, APL, $maxBETW$ and $minLCC$ as summary statistics), the BOM and the $KVFM$. Results generated by the $NEDM$ with $CLQNUM$ and MD as the network topological summary statistic are deferred to Appendix B. Previous analyses of these data found change points at the times of the speech instruction slides, primarily time points 60 and 130 (Cribben et al., 2012, 2013). Additionally, all results obtained by the $NEDM$ (plus the plot in Appendix B) found many of the expected change points at (and between) the time points of the speech instruction slides, and also during the speech preparation phase (time points 60-130).

While the $KVFM$ method (Koutra et al., 2013) found more significant changes points at the time points of the

Figure 3: Size of the test for the no-change (change in mean) scenario with $T = \{200, 300\}$, $\omega = \{0.05, 0.1, 0.15\}$, $q = \{5, 10, 15, 20, 25, 30\}$ and $P = 5$.

speech instruction slides and also during the speech preparation phase, many of the change points for the subjects were very close to one another which makes them unrealistic for fMRI data. While the BOM also found some significant changes points at the speech instruction slides time points, the $NEDM$ found significantly more. In addition, having change points so close to one another (as is the $KVFM$ cases) makes it impossible to estimate the network structure between each pair of significant change points and also breaks down the ability to interpret and apportion the change phenomenon to a biological process (as in the case of the fMRI data used here). In turn, the framework of the $NEDM$ allows for an estimation which depends on a visual display of the underlying dynamic brain networks with the advantage of noticing structural changes within these embeddings.

6.3 Case study: Enron email networks

We now turn to the anomaly detection problem for data in a form of a graph, that is, the Enron email network.

From our list of network summary statistics, we utilize the APL because APL appears to be fairly sensitive to intrinsic properties of data in the form of dynamic networks. We link the results (Figure 6) obtained in this analysis to various events in the Enron scandal timeline. With the $NEDM$, the times for significant detection points occur at months 2, 7, 12, 15, 18 and 24. In comparison, the time period for month 2 (November 1998 to December 1998) is linked to the hire of Andrew Fastow as the finance chief. The time period of month 7 was from April 1999 to June 1999. This is around the time when Enron's CFO was exempted by the Board of Directors from the company's code of ethics so that he could run the private equity fund LJM1, and also around the time when the head of Enron's West Coast Trading Desk in Portland Oregon Timothy Biden began his first experiment to exploit the new rules of California's deregulated energy market.

Next to this, month 12 is linked to the period August 1999 to October 1999 which was around the time when Enron's CFO started to raise money for two LJM funds (LJM1 and LJM2), which was later used to buy Enron's

Figure 4: Power of the test for the one-change (change in variance) scenario with $\omega = \{0.05, 0.1, 0.15\}$, $q = \{5, 10, 15, 20, 25, 30\}$, $T = \{200, 300\}$, $\tau = \{88, 156\}$ and $P = 10$.

poorly performing assets in order to make its financial statement look better. The time period for months 15 and 18 was from December 1999 to March 2000. This was around the time the energy prices in California rose significantly and the power reserves became low, which was followed by the blackouts in metropolitan areas. Many believed that one of the reasons for California's energy crisis was Enron's trading, which leaded to the investigation of Federal Energy Regulatory Commission (FERC). This investigation was connected with our next detection point at month 24, which was from August 2000 to December 2000, since it was the time the FERC investigation exonerated Enron from wrongdoings in the California energy crisis. The time period around month 24 is a very interesting one not only because it is connected with FERC investigation, but also because Enron's share price hit all-time high of $90.56 and then Enron used "aggressive" accounting to declare $53 million in earnings on a collapsing deal that hadn't earned anything at all in profit.

Figure 8 in the Appendix displays the outcome of the $KVFM$ analysis. Note that, because the $KVFM$ is based on graph similarity scores, we only have results from December 1998 to June 2001 (Time point 0 is November 1998, and there are no more networks for comparison after July 2001). With the $KVFM$, anomalies are reported at times

2, 6 and 23. These times coincide with time periods [December 1998 - January 1999], [April 1999 - June 1999] and [September 2000 - November 2000]. In Figure 8 (in Appendix B), we notice that the $KVFM$ is only able to flag 3 out 5 anomalous time points that the $NEDM$ reported.

7 Conclusion

In this paper, we develop a new approach, the $NEDM$, for analyzing and modeling the network structure between (possibly) high dimensional multivariate time series from an fMRI study which consists of realizations of complex and dynamic brain processes. The method adds to the literature by improving understanding of the brain processes measured using fMRI. The $NEDM$ is, to the best of our knowledge, the first paper to consider estimating change points for time evolving graph summary statistics in a multivariate time series context. Although this paper is inspired by and developed for brain connectivity studies, our proposed method is applicable to more general settings and can also be used in a variety of situations where one wishes to study the evolution of a high dimensional graph over time, e.g., in conjunction with telecommunication, financial, and blockchain networks.

Figure 5: Change point detection for fMRI data set 1.

There are several novel aspects of the $NEDM$. First, it allows for estimation of graph summary statistics in a (possible) very high-dimensional multivariate time series setting, in particular, in situations where the number of time series is much greater than the number of time points ($P >> T$). Hence, in a biomedical neuroimaging setting, it can consider the dynamics of the whole brain or a very large number of brain time series, thereby providing deeper insights into the large-scale functional architecture of the brain and the complex processes within. Second, the $NEDM$ is, to the best of our knowledge, the first piece of work to consider estimating change points of time evolving graph summary structure in a multivariate time series con-

text. We introduced a novel statistical test for the candidate change points using the sieve bootstrap and showed that it outperformed the asymptotic distribution. However, as the $NEDM$ is based on binary segmentation it is restricted by the minimum distance between change points.

It has been shown that neurological disorders disrupt the connectivity pattern or structural properties of the brain. Future work entails applying the $NEDM$ to resting state fMRI data from subjects with brain disorders such as depression, Alzheimer's disease and schizophrenia and to control subjects who have been matched using behavioural data. By comparing change points and partition specific networks, the $NEDM$ may lead to the robust identifica-

Figure 6: Detection of Enron Email Networks from November 1998 - July 2001.

tion of cognitive states at rest for both controls and subjects with these disorders. It is hoped that the large-scale temporal features resulting from the accurate description of brain connectivity from our novel method will lead to better diagnostic and prognostic indicators of the brain disorders. More specifically, by comparing the change points of healthy controls to patients with these disorders, we may be able understand the key differences in functional brain processes that may eventually lead to the identification of biomarkers for the disease.

As an extension to monitoring change points in graph objects, we intend to incorporate higher order structures, such as tensors, in the network snapshot characterization procedure of the $NEDM$. Moreover, we intend to extend our analysis to include the estimation of network summaries that are based on the *local* topology and geometry of the graph. In particular, we intend to incorporate a motif-based analysis and the concepts of topological data analysis (TDA), particularly, persistent homology, in the derivation of graph summary statistics (Carlsson, 2009; Patania et al., 2017). Indeed, tracking local network topological summaries based on graph persistent homology offers multifold benefits. First, this approach enables us to consider edge-weighted networks. Second, it allows for enhancing analysis of the underlying network organization at multi-resolution levels. Third, simultaneously considering multiple local network topological statistics based on graph persistent homology will minimize loss of network information that currently occurs due to reducing a high dimensional structure to a univariate time series representation of a single network summary.

Another interesting theoretical direction is to explore var-ious types of approximation models for dynamics of local and global network topological summaries and the associated error bounds, which as a result, can also yield an insight on theoretical guarantees of resampling and sub-sampling procedures in application to (non)linear processes of network topological descriptors Kreiss et al. (2011) and related uncertainty quantification in network anomaly detection.

Acknowledgements

The work of D.O.B and Y.R.G. was partially supported by the National Science Foundation (NSF) of the United States (grant numbers IIS 1633331 and DMS 1736368). The work of I.C was partially supported by Natural Sciences and Engineering Research Council of Canada (NSERC: Grant/Award Number: RGPIN-2018-06638) and the Xerox Faculty Fellowship, Alberta School of Business. The authors would like to thank Gagan S. Wig for stimulating discussions on brain networks.

8 Appendix A: Definitions and Theorem

Definition 1 (Kolmogorov Distance; Kestemont (1987)) *For any two probability measures, μ and ν defined on $\mathbb{R}$, the Kolmogorov distance $d_K\{.\}$ is defined as :*

$$d_K(\mu, \nu) := \sup_{x \in \mathbb{R}} |\mu((-\infty, x]) - \nu((-\infty, x])|.$$

Table 2: Notation and symbols

Symbol	Description
$G = (V, E)$	graph/network; V set of vertices, E set of edges
$q; \omega$	window length, threshold parameter
$\mathbf{D}$	$T \times P$ multivariate time series; T number of time points, P number of time series
$\mathbf{F}$	q-row fold of $\mathbf{D}$
$\mathbf{R}$; $\mathbf{A}$	correlation matrix; adjacency matrix
$CLQNUM$	clique number
MD	mean node degree
ACC	average clustering coefficient
APL	average path length coefficient
BOM	Barnett & Onnela's change detection method
$KVFM$	Koutra et al.'s DELTACON method
$NEDM$	network-evolution detection method
$minLCC$	minimum local clustering coefficient
$maxBETW$	maximum node betweenness centrality

Definition 2

$$Y_t - \mu = \sum_{k=1}^{p} \varphi_k (Y_{t-k} - \mu) + \varepsilon_t \ , \quad t \geqslant p + 1 \qquad (1.1)$$

with $\mathbf{E} Y_t = \mu$. Let $\boldsymbol{\xi} = (\mu, \sigma^2, \varphi_1, \ldots, \varphi_p)^T$, and for $1 \leqslant r \leqslant p + 2$ denote $\hat{\mu}$, $\hat{\sigma}^2$, $\hat{\varphi}_1$, $\ldots$, $\hat{\varphi}_p$ as the simultaneous solutions of the $p + 2$ equations $\partial / \partial \xi_r \ell_n(\boldsymbol{\xi}) = 0$

Theorem 2 (Gombay (2008)) *Assume the sequence of observations $\{Y_t\}$ satisfy model (1.1) with Gaussian i.i.d. white noise $\{\varepsilon_t\}$, $var(\varepsilon_t) = \sigma^2$, and characteristic polynomial $\varphi(z) = 1 - \varphi_1 z - \ldots - \varphi_p z^p$ has roots outside the unit circle. Then there exists a $(p + 2)$ - dimensional Gaussian process $\mathbf{B}(u)$ with independent Brownian bridge components $B^{(r)}(u), j = 1, \ldots, p + 2$, such that :*

$$\max_{1 \leq j \leq p+2} \sup_{0 \leq u \leq 1} |\hat{B}^{(r)}(u) - B^{(r)}(u)| = o_p(1). \qquad (1.11)$$

9 Appendix B: Experimental data analysis

9.1 Case study: fMRI data 1 - *additional results*

Figure 7 presents additional results for the fMRI data 1 case study based on the $NEDM$ with $CLQNUM$ and MD as the network summary statistics. Table 3 presents the numerical change points obtained for the fMRI 1 case study.

9.2 Case study: fMRI data 2

We apply the $NEDM$, with all network summary statistics except the $CLQNUM$, to a resting-state fMRI data as described in Habeck et al. (2012); Cribben and Yu (2017). The $CLQNUM$ summary is omitted due to computational challenges encountered during the analysis. Participants ($n = 45$) are instructed to rest in the scanner for 9.5 minutes, with the instruction to keep their eyes open for the duration of the scan. We apply the Anatomical Automatic Labeling (Tzourio-Mazoyer et al., 2002) atlas to the adjusted voxel-wise time series and produce time series for 116 Regions of Interest (ROIs) for each subject by averaging the voxel time series within the ROIs. In total, each time series contained 285 time points (9.5 minutes with $TR = 2$ s).

Results

Results obtained in this case study (as seen in Figure 9) show significant change point locations for all 45 subjects. As resting state data is unconstrained, we do not know where the true network change points occur. However, the $NEDM$ finds significant change points in the network structure for many subjects with the maximum number of change points being 4 which lines up with the results in Cribben and Yu (2017). From Figure 9, we find a high indication that change points vary highly across network summaries and that some change states endure longer periods while others transition more quickly. On the other hand, results by the BOM and by the $KVFM$ appear to suggest the detection of a much larger number of significant change points for each subject. Judging from the close proximity and the total number of change points reported by these two methodologies, we deduce that some of the change points

Figure 7: Change points detection for fMRI data 1 - additional results.

Table 3: Summary of change points detected for data 1

Subject	ACC	APL	$maxBETW$	$CLQNUM$	MD	$minLCC$	BOM	$KVFM$
1	94	62,93				94		92
2						72		111,112,120
3	138	134	134	72	134	134		92,94
4					115			69,70,76,117
5	63	63,70	68,131	63	64	64		108
6			106					90
7	63						61	
8		109					102	77,78
10	99	126					67	
11								92,93
12		99					116	75,90,94
13		65,66			71			62,65
14	106	104		97				88,111
15								65,66,98
16	140						92	
17		77	97			97,104		
18					130			
19			93					
20	65				70		100	61,62,86

* Subjects not included have no change points detected across all methods.

Figure 8: KVFM Detection of Enron Email Networks from November 1998 - July 2001.

for the subjects are unrealistic for resting state fMRI data. As noted above, having change points so close to one another makes it impossible to estimate the network structure between each pair of significant change points.

10 Appendix C: Proofs for Theorem 1 and Corollary 1

Theorem 1

Given the Kolmogorov distance

$$\sup_{0 \leqslant u \leqslant 1} |\hat{B}^{(r)}(u) - B^{(r)}(u)| = d_K\{\hat{B}^{(r)}(u), B^r(u)\},$$

Theorem 1 in Gombay (2008) (1.11) can be equivalently summarized as

$$\max_{1 \leqslant r \leqslant p+2} d_K\{\hat{B}^{(r)}(u), B^{(r)}(u)\} = o_p(1). \qquad (1.12)$$

In turn, under the assumption of weak stationarity, equation (1.1) can be re-written as

$$Y_t - \mu = \sum_{r=0}^{\infty} \varphi_r \varepsilon_{t-r}. \qquad (1.13)$$

Let $X_t := Y_t - \mu$, and let X_t^* be the corresponding sieve bootstrap counterpart. Then, given (1.13) and under the assumption that $\{\varepsilon_t\}_{t=1}^n$ are Gaussian i.i.d. (or i.i.d. with

$E|\varepsilon_t|^4 < \infty$) (see Assumption A1' and Lemma 5.5 of Bühlmann et al. (1997)),

$$X_t^* \xrightarrow{d^*} X_t \quad in \quad probability, \qquad (1.14)$$

with d^* denoting convergence in distribution, conditionally on the observed sample $Y_1, \ldots, Y_t$.

Hence, in view of Theorem 1 of Gombay (2008) and given the sample $Y_1, \ldots, Y_t$,

$$\max_{1 \leqslant r \leqslant p+2} d_K\{\hat{B}^{*(r)}(u), B^{(r)}(u)\} = o_p(1). \qquad (1.15)$$

Then, by (1.12), (1.15) and triangle inequality, we find that conditionally on the sample $Y_1, \ldots, Y_t$,

$$\max_{1 \leqslant r \leqslant p+2} d_K\{\hat{B}^{*(r)}(u), \hat{B}^{(r)}(u)\} = o_p(1),$$

which is equivalent to

$$\max_{1 \leqslant r \leqslant p+2} d_K\{\hat{B}^{*(r)}(u), \hat{B}^{(r)}(u)\} \longrightarrow 0 \qquad in \quad probability.$$

Corollary 1

Note that s_n^2 is a consistent estimator of $E(\varepsilon_t^2) = \sigma^2$ (Lehmann and Casella, 2006). Hence, given that $\tilde{\varepsilon}^\diamond_t$ are independent random variables drawn from $N(0, s_n^2)$,

$$\{\tilde{\varepsilon}^\diamond_t\}_{t=1}^n \xrightarrow{D} \{\tilde{\varepsilon}_t\}_{t=1}^n.$$

Figure 9: Change point detection for fMRI data 2

As a result,

$$X_t^{\diamond} \xrightarrow{d^*} X_t \ \ in \ \ probability, \qquad (1.16)$$

and in view of the proof for Theorem 1 above and Theorem 1 in Gombay (2008),

$$\max_{1 \leqslant r \leqslant p+2} d_K\{\hat{B}^{\diamond(r)}(u), \hat{B}^{(r)}(u)\} \ \longrightarrow \ 0 \qquad in \ \ probability.$$

11 Appendix D: Asymptotic and Sieve bootstrap distribution simulations

The procedure for assessing the performance of the sieve bootstrap technique to the asymptotic distribution is set up as follows:

1. Simulate $5,000$ Monte Carlo simulations of an $AR(1)$ time series with different samples ($n = 100, 200, 300$) and change point times ($\tau = 50, 100, 180$).

2. Consider the following scenario for identifying change points in the $AR(1)$ time series: change in mean (μ). We use $\Gamma = 1000$ replications for the sieve bootstrap procedure (as expressed in Algorithm 1).

3. With equation (1.1) as reference, the $AR(1)$ model is defined as

   $$Y_t - \mu = \varphi(Y_{t-1} - \mu) + \varepsilon_t; t \in [1, n]; \varepsilon_t \sim \text{Gaussian} WN(0, \sigma^2).$$

4. For each sample n, with σ^2 and φ as nuisance parameters, we test the following:

   $H_0 : \mu = \mu_0, \forall \ t \in [1, n]$ against

   $H_a : \mu = \mu_0, \ \forall \ 1 \leqslant t \leqslant \tau - 1, \ at \ \tau = [\rho n], \ \rho \in (0, 1)$;
   $\mu = \mu_a, \ \forall \ \tau \geqslant n.$

5. With $\sigma^2 = 1$ and $\mu_0 = 0$, we use the values $\varphi = (-0.5, 0.1, 0.5)$.

References

Akoglu, L., and Faloutsos, C. (2010), "Event detection in time series of mobile communication graphs," Army science conference, pp. 77–79.

Aue, A., Hörmann, S., Horváth, L., Reimherr, M. et al. (2009), "Break detection in the covariance structure of multivariate time series models," *The Annals of Statistics*, 37, 4046–4087.

Barabási, A.-L., and Albert, R. (1999), "Emergence of scaling in random networks," *science*, 286, 509–512.

Barabási, A.-L., and Pósfai, M. (2016), *Network science*, Cambridge university press.

Barigozzi, M., Cho, H., and Fryzlewicz, P. (2018), "Simultaneous multiple change-point and factor analysis for high-dimensional time series," *Journal of Econometrics*.

Barnett, I., and Onnela, J.-P. (2016), "Change point detection in correlation networks," *Scientific reports*, 6, 18893.

Bassett, D. S., and Bullmore, E. (2006), "Small-world brain networks," *The neuroscientist*, 12, 512–523.

Bühlmann, P. et al. (1997), "Sieve bootstrap for time series," *Bernoulli*, 3, 123–148.

Carlsson, G. (2009), "Topology and data," *Bulletin of the American Mathematical Society*, 46.

Cribben, I., Haraldsdottir, R., Atlas, L. Y., Wager, T. D., and Lindquist, M. A. (2012), "Dynamic connectivity regression: determining state-related changes in brain connectivity," *Neuroimage*, 61, 907–920.

Cribben, I., Wager, T., and Lindquist, M. (2013), "Detecting functional connectivity change points for single-subject fMRI data," *Frontiers in computational neuroscience*, 7, 143.

Cribben, I., and Yu, Y. (2017), "Estimating whole-brain dynamics by using spectral clustering," *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, 66, 607–627.

Davis, R. A., Huang, D., and Yao, Y.-C. (1995), "Testing for a change in the parameter values and order of an autoregressive model," *The Annals of Statistics*, 282–304.

Dette, H., and Wied, D. (2016), "Detecting relevant changes in time series models," *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 78, 371–394.

Diesner, J., Frantz, T. L., and Carley, K. M. (2005), "Communication networks from the Enron email corpus It's always about the people. Enron is no different," *Computational & Mathematical Organization Theory*, 11, 201–228.

Elliott, M., Golub, B., and Jackson, M. O. (2014), "Financial networks and contagion," *American Economic Review*, 104, 3115–53.

Gombay, E. (2008), "Change detection in autoregressive time series," *Journal of Multivariate Analysis*, 99, 451–464.

Habeck, C., Steffener, J., Rakitin, B., and Stern, Y. (2012), "Can the default-mode network be described with one spatial-covariance network?" *Brain research*, 1468, 38–51.

Hamilton, J. D. (1995), "Time series analysis," *Economic Theory. II, Princeton University Press, USA*, 625–630.

Harshaw, C. R., Bridges, R. A., Iannacone, M. D., Reed, J. W., and Goodall, J. R. (2016), "Graphprints: Towards a graph analytic method for network anomaly detection," in *Proceedings of the 11th Annual Cyber and Information Security Research Conference*, ACM, p. 15.

Host-Madsen, A., and Zhang, J. (2018), "Coding of Graphs with Application to Graph Anomaly Detection," *arXiv preprint arXiv:1804.02469*.

Inoue, A. (2001), "Testing for distributional change in time series," *Econometric theory*, 17, 156–187.

Keogh, E., Chu, S., Hart, D., and Pazzani, M. (2001), "An online algorithm for segmenting time series," in *Data Mining, 2001. ICDM 2001, Proceedings IEEE International Conference on*, IEEE, pp. 289–296.

Kestemont, M.-P. (1987), "The Kolmogorov distance as comparison measure between parametric and non-parametric Bayesian predictions," *The Statistician*, 259–264.

Koutra, D., Vogelstein, J. T., and Faloutsos, C. (2013), "Deltacon: A principled massive-graph similarity function," in *Proceedings of the 2013 SIAM International Conference on Data Mining*, SIAM, pp. 162–170.

Kreiss, J.-P. (1988), "Asymptotic statistical inference for a class of stochastic processes," Ph.D. thesis, Verlag nicht ermittelbar.

— (1992), "Bootstrap procedures for AR ()processes," in *Bootstrapping and Related Techniques*, Springer, pp. 107–113.

Kreiss, J.-P., Paparoditis, E., Politis, D. N. et al. (2011), "On the range of validity of the autoregressive sieve bootstrap," *The Annals of Statistics*, 39, 2103–2130.

Lehmann, E. L., and Casella, G. (2006), *Theory of point estimation*, Springer Science & Business Media.

Messer, M., Albert, S., and Schneider, G. (2018), "The multiple filter test for change point detection in time series," *Metrika*, 81, 589–607.

Newman, M. E. (2003), "The structure and function of complex networks," *SIAM review*, 45, 167–256.

Park, Y., Priebe, C. E., and Youssef, A. (2012), "Anomaly detection in time series of graphs using fusion of graph invariants," *IEEE journal of selected topics in signal processing*, 7, 67–75.

Patania, A., Vaccarino, F., and Petri, G. (2017), "Topological analysis of data," *EPJ Data Science*, 6.

Peel, L., and Clauset, A. (2015), "Detecting Change Points in the Large-Scale Structure of Evolving Networks," in *Twenty-Ninth AAAI Conference on Artificial Intelligence*.

Picard, D. (1985), "Testing and estimating change-points in time series," *Advances in applied probability*, 17, 841–867.

Pourahmadi, M. (2001), *Foundations of time series analysis and prediction theory*, vol. 379, John Wiley & Sons.

Priebe, C. E., Conroy, J. M., Marchette, D. J., and Park, Y. (2005), "Scan statistics on enron graphs," *Computational & Mathematical Organization Theory*, 11, 229–247.

Rubinov, M., and Sporns, O. (2010), "Complex network measures of brain connectivity: uses and interpretations," *Neuroimage*, 52, 1059–1069.

Shumway, R. H., and Stoffer, D. S. (2017), *Time series analysis and its applications: with R examples*, Springer.

Sun, J., Faloutsos, C., Papadimitriou, S., and Yu, P. S. (2007), "Graphscope: parameter-free mining of large time-evolving graphs," in *Proceedings of the 13th ACM SIGKDD international conference on Knowledge discovery and data mining*, ACM, pp. 687–696.

Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N., Mazoyer, B., and Joliot, M. (2002), "Automated anatomical labeling of activations in SPM using a macroscopic anatomical parcellation of the MNI MRI single-subject brain," *Neuroimage*, 15, 273–289.

Vandermarliere, B., Karas, A., Ryckebusch, J., and Schoors, K. (2015), "Beyond the power law: Uncovering stylized facts in interbank networks," *Physica A: Statistical Mechanics and its Applications*, 428, 443–457.

Wager, T. D., Waugh, C. E., Lindquist, M., Noll, D. C., Fredrickson, B. L., and Taylor, S. F. (2009), "Brain mediators of cardiovascular responses to social threat: part I: reciprocal dorsal and ventral sub-regions of the medial prefrontal cortex and heart-rate reactivity," *Neuroimage*, 47, 821–835.

Wig, G. S., Schlaggar, B. L., and Petersen, S. E. (2011), "Concepts and principles in the analysis of brain networks," *Annals of the New York Academy of Sciences*, 1224, 126–146.

Wolff, S., Gastwirth, J., and Rubin, H. (1967), "The effect of autoregressive dependence on a nonparametric test (corresp.)," *IEEE Transactions on Information Theory*, 13, 311–313.

Zellner, A. (1962), "An efficient method of estimating seemingly unrelated regressions and tests for aggregation bias," *Journal of the American statistical Association*, 57, 348–368.

Zivot, E., and Wang, J. (2007), *Modeling financial time series with S-Plus®*, vol. 191, Springer Science & Business Media.

References

Akoglu, L., and Faloutsos, C. (2010), "Event detection in time series of mobile communication graphs," Army science conference, pp. 77–79.

Aue, A., Hörmann, S., Horváth, L., Reimherr, M. et al. (2009), "Break detection in the covariance structure of multivariate time series models," *The Annals of Statistics*, 37, 4046–4087.

Barabási, A.-L., and Albert, R. (1999), "Emergence of scaling in random networks," *science*, 286, 509–512.

Barabási, A.-L., and Pósfai, M. (2016), *Network science*, Cambridge university press.

Barigozzi, M., Cho, H., and Fryzlewicz, P. (2018), "Simultaneous multiple change-point and factor analysis for high-dimensional time series," *Journal of Econometrics*.

Barnett, I., and Onnela, J.-P. (2016), "Change point detection in correlation networks," *Scientific reports*, 6, 18893.

Bassett, D. S., and Bullmore, E. (2006), "Small-world brain networks," *The neuroscientist*, 12, 512–523.

Bühlmann, P. et al. (1997), "Sieve bootstrap for time series," *Bernoulli*, 3, 123–148.

Carlsson, G. (2009), "Topology and data," *Bulletin of the American Mathematical Society*, 46.

Cribben, I., Haraldsdottir, R., Atlas, L. Y., Wager, T. D., and Lindquist, M. A. (2012), "Dynamic connectivity regression: determining state-related changes in brain connectivity," *Neuroimage*, 61, 907–920.

Cribben, I., Wager, T., and Lindquist, M. (2013), "Detecting functional connectivity change points for single-subject fMRI data," *Frontiers in computational neuroscience*, 7, 143.

Cribben, I., and Yu, Y. (2017), "Estimating whole-brain dynamics by using spectral clustering," *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, 66, 607–627.

Davis, R. A., Huang, D., and Yao, Y.-C. (1995), "Testing for a change in the parameter values and order of an autoregressive model," *The Annals of Statistics*, 282–304.

Dette, H., and Wied, D. (2016), "Detecting relevant changes in time series models," *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 78, 371–394.

Diesner, J., Frantz, T. L., and Carley, K. M. (2005), "Communication networks from the Enron email corpus It's always about the people. Enron is no different," *Computational & Mathematical Organization Theory*, 11, 201–228.

Elliott, M., Golub, B., and Jackson, M. O. (2014), "Financial networks and contagion," *American Economic Review*, 104, 3115–53.

Gombay, E. (2008), "Change detection in autoregressive time series," *Journal of Multivariate Analysis*, 99, 451–464.

Habeck, C., Steffener, J., Rakitin, B., and Stern, Y. (2012), "Can the default-mode network be described with one spatial-covariance network?" *Brain research*, 1468, 38–51.

Hamilton, J. D. (1995), "Time series analysis," *Economic Theory. II, Princeton University Press, USA*, 625–630.

Harshaw, C. R., Bridges, R. A., Iannacone, M. D., Reed, J. W., and Goodall, J. R. (2016), "Graphprints: Towards a graph analytic method for network anomaly detection," in *Proceedings of the 11th Annual Cyber and Information Security Research Conference*, ACM, p. 15.

Host-Madsen, A., and Zhang, J. (2018), "Coding of Graphs with Application to Graph Anomaly Detection," *arXiv preprint arXiv:1804.02469*.

Inoue, A. (2001), "Testing for distributional change in time series," *Econometric theory*, 17, 156–187.

Keogh, E., Chu, S., Hart, D., and Pazzani, M. (2001), "An online algorithm for segmenting time series," in *Data Mining, 2001. ICDM 2001, Proceedings IEEE International Conference on*, IEEE, pp. 289–296.

Kestemont, M.-P. (1987), "The Kolmogorov distance as comparison measure between parametric and non-parametric Bayesian predictions," *The Statistician*, 259–264.

Koutra, D., Vogelstein, J. T., and Faloutsos, C. (2013), "Deltacon: A principled massive-graph similarity function," in *Proceedings of the 2013 SIAM International Conference on Data Mining*, SIAM, pp. 162–170.

Kreiss, J.-P. (1988), "Asymptotic statistical inference for a class of stochastic processes," Ph.D. thesis, Verlag nicht ermittelbar.

— (1992), "Bootstrap procedures for AR ()processes," in *Bootstrapping and Related Techniques*, Springer, pp. 107–113.

Kreiss, J.-P., Paparoditis, E., Politis, D. N. et al. (2011), "On the range of validity of the autoregressive sieve bootstrap," *The Annals of Statistics*, 39, 2103–2130.

Lehmann, E. L., and Casella, G. (2006), *Theory of point estimation*, Springer Science & Business Media.

Messer, M., Albert, S., and Schneider, G. (2018), "The multiple filter test for change point detection in time series," *Metrika*, 81, 589–607.

Newman, M. E. (2003), "The structure and function of complex networks," *SIAM review*, 45, 167–256.

Park, Y., Priebe, C. E., and Youssef, A. (2012), "Anomaly detection in time series of graphs using fusion of graph invariants," *IEEE journal of selected topics in signal processing*, 7, 67–75.

Patania, A., Vaccarino, F., and Petri, G. (2017), "Topological analysis of data," *EPJ Data Science*, 6.

Peel, L., and Clauset, A. (2015), "Detecting Change Points in the Large-Scale Structure of Evolving Networks," in *Twenty-Ninth AAAI Conference on Artificial Intelligence*.

Picard, D. (1985), "Testing and estimating change-points in time series," *Advances in applied probability*, 17, 841–867.

Pourahmadi, M. (2001), *Foundations of time series analysis and prediction theory*, vol. 379, John Wiley & Sons.

Priebe, C. E., Conroy, J. M., Marchette, D. J., and Park, Y. (2005), "Scan statistics on enron graphs," *Computational & Mathematical Organization Theory*, 11, 229–247.

Rubinov, M., and Sporns, O. (2010), "Complex network measures of brain connectivity: uses and interpretations," *Neuroimage*, 52, 1059–1069.

Shumway, R. H., and Stoffer, D. S. (2017), *Time series analysis and its applications: with R examples*, Springer.

Sun, J., Faloutsos, C., Papadimitriou, S., and Yu, P. S. (2007), "Graphscope: parameter-free mining of large time-evolving graphs," in *Proceedings of the 13th ACM SIGKDD international conference on Knowledge discovery and data mining*, ACM, pp. 687–696.

Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N., Mazoyer, B., and Joliot, M. (2002), "Automated anatomical labeling of activations in SPM using a macroscopic anatomical parcellation of the MNI MRI single-subject brain," *Neuroimage*, 15, 273–289.

Vandermarliere, B., Karas, A., Ryckebusch, J., and Schoors, K. (2015), "Beyond the power law: Uncovering stylized facts in interbank networks," *Physica A: Statistical Mechanics and its Applications*, 428, 443–457.

Wager, T. D., Waugh, C. E., Lindquist, M., Noll, D. C., Fredrickson, B. L., and Taylor, S. F. (2009), "Brain mediators of cardiovascular responses to social threat: part I: reciprocal dorsal and ventral sub-regions of the medial prefrontal cortex and heart-rate reactivity," *Neuroimage*, 47, 821–835.

Wig, G. S., Schlaggar, B. L., and Petersen, S. E. (2011), "Concepts and principles in the analysis of brain networks," *Annals of the New York Academy of Sciences*, 1224, 126–146.

Wolff, S., Gastwirth, J., and Rubin, H. (1967), "The effect of autoregressive dependence on a nonparametric test (corresp.)," *IEEE Transactions on Information Theory*, 13, 311–313.

Zellner, A. (1962), "An efficient method of estimating seemingly unrelated regressions and tests for aggregation bias," *Journal of the American statistical Association*, 57, 348–368.

Zivot, E., and Wang, J. (2007), *Modeling financial time series with S-Plus®*, vol. 191, Springer Science & Business Media.