Automatic and fast encoding of representational uncertainty underlies probability distortion

Xiangjuan Ren[1,2,3]   Huan Luo[1,4,5*]   Hang Zhang[1,3,4,5*]

1. School of Psychological and Cognitive Sciences and Beijing Key Laboratory of Behavior and Mental Health, Peking University, Beijing, China

2. Academy for Advanced Interdisciplinary Studies, Peking University, Beijing, China

3. Peking-Tsinghua Center for Life Sciences, Peking University, Beijing, China

4. PKU-IDG/McGovern Institute for Brain Research, Peking University, Beijing, China

5. Key Laboratory of Machine Perception, Ministry of Education, Peking University, Beijing, China

*Corresponding authors:

Huan Luo, email: huan.luo@pku.edu.cn

Hang Zhang, email: hang.zhang@pku.edu.cn

Keywords: judgment; decision making; probability distortion; MEG; steady-state response (SSR); time-resolved decoding

Short title: Encoding of representational uncertainty

Abstract

Humans do not have an accurate representation of probability information in the environment but distort it in a surprisingly stereotyped way ("probability distortion"), as shown in a wide range of judgment and decision-making tasks. Many theories hypothesize that humans automatically compensate for the uncertainty inherent in probability information ("representational uncertainty") and probability distortion is a consequence of uncertainty compensation. Here we examined whether and how the representational uncertainty of probability is quantified in the human brain and its relevance to probability distortion behavior. Human subjects kept tracking the relative frequency of one color of dot in a sequence of dot arrays while their brain activity was recorded by magnetoencephalography (MEG). We found converging evidence from both neural entrainment and time-resolved decoding analysis that a mathematically-derived measure of representational uncertainty is automatically computed in the brain, despite it is not explicitly required by the task. In particular, the encodings of relative frequency and its representational uncertainty respectively occur at latencies of approximately 300 ms and 400 ms. The relative strength of the brain responses to these two quantities correlates with the probability distortion behavior. The automatic and fast encoding of the representational uncertainty provides neural basis for the uncertainty compensation hypothesis of probability distortion. More generally, since representational uncertainty is closely related to confidence estimation, our findings exemplify how confidence might emerge prior to perceptual judgment.

Introduction

Humans do not have an accurate representation of probability or relative-frequency information in the environment but distort it in a surprisingly stereotyped way. Typically, small probability is overestimated and large probability underestimated, which can be well fit by a linear-in-log-odds (LLO) model with two parameters (see [1] for a review). Such "probability distortion" phenomena occur in a variety of judgment and decision-making tasks such as relative-frequency estimation [2-4], confidence rating [5-7], decision under risk [8-11], and are also widely reported in animal behaviors [12-14]. However, the neural computations that accompany such probability distortions remain largely unknown.

One computation that is assumed to be central to probability distortion [9, 15-17] is compensation for the uncertainty inherent in the representation of noisy probability information ("representational uncertainty"). In particular, recent comparison among an extensive set of computational models of probability distortion [9] suggests that in their judgment and decision-making people take into account representational uncertainty that is proportional to $p(1-p)$, where p denotes probability or relative frequency. That is, representational uncertainty is zero at $p = 0$ or 1 and maximal at $p = 0.5$. The $p(1-p)$ form had also been proved by Lebreton et al. [18] as a measure of uncertainty that correlates with the explicitly reported confidence for a specific judged value. Specifically, their fMRI results showed that during the valuation process, this uncertainty measure is automatically encoded in the ventromedial prefrontal cortex (vmPFC) — the brain region known for encoding value—even in the absence of explicit

confidence rating. Motivated by previous neuroimaging studies and computational

modelling, we ask whether representational uncertainty of probability information can

be automatically encoded in human brain and if yes, whether this encoding can

precede the explicit judgment of probability, as theories of probability distortion would

expect [9, 15-17].

In the present study, we designed a new experimental paradigm where a major

component of the representational uncertainty of probability information (i.e. $p(1-p)$,

see Results for details) was varied continuously over time. By using time-resolved

neural measurements and assessing the temporal coupling between stimulus

variables and ongoing brain activities, we examined whether and how the encoding of

representational uncertainty proceeds in time and relates to probability distortion.

Twenty-two human subjects participated in the study and were instructed to

continuously track the relative-frequency (p) of one color of dots in a sequence of dot

arrays (Fig 1A), during which their brain activities were recorded by

magnetoencephalography (MEG). First, we found that, though p was the only variable

that subjects needed to track while $p(1-p)$ was task-irrelevant, the periodic changes of

$p(1-p)$ as well as p entrained neural rhythms, supporting an automatic tracking of

representational uncertainty in the brain even when it is task-relevant. Next, by using

a time-resolved decoding analysis to delineate the temporal course, we further found

that the encoding of p and $p(1-p)$ peaked around 300 and 400 ms, respectively. Finally,

the relative strength of the neural responses to the two variables (p and $p(1-p)$) in the

parietal region correlated with the variation of probability distortion behavior across

individuals. Taken together, our results provide neural evidence for an automatic, fast

encoding of representational uncertainty in the human brain that might underlie

probability distortion observed in a wide range of human behaviors.

Results

As shown in Fig 1A, on each trial, subjects saw a sequence of displays consisting of isoluminant orange and blue dots that was refreshed every 150 ms, and were instructed to track the relative-frequency of dots in one color (i.e. orange or blue, counterbalanced across subjects). To ensure subjects' persistent tracking throughout the trial, the sequence of displays ended after random duration and subjects needed to report the relative-frequency of the last display by clicking on a percentage scale afterwards.

Fig 1. Experimental design and behavioral results.
(A) Relative-frequency tracking and judgment task. On each trial, a sequence of orange and blue dot arrays was presented at a rate of 150 ms per display. Subjects were asked to fixate on the central fixation cross and track the relative frequency of orange (or blue) dots in each display until a 0–100% response scale appeared. Subjects then clicked on the scale to report the relative frequency in the last display. **(B)** The p and $p(1-p)$ sequences in an example P-cycle or U-cycle trial. The value of p on each display was randomly chosen from a uniform distribution ranging from 0.1 to 0.9. In P-cycles (left

panels), the p sequence was generated in such a way that the p value in different displays

alternated between lower (<0.5) and higher (>0.5) values, resulting in a frequency

spectrum peaking at 3.33 Hz (solid line), while the corresponding $p(1–p)$ sequence was

aperiodic (dashed line). In U-cycles (right panels), it was the reverse: the $p(1–p)$ sequence

alternated between lower (<0.21) and higher (>0.21) values in cycles of 3.33 Hz (dashed

line), while the p sequence was aperiodic (solid line). To illustrate the periodicity or

aperiodicity in the p and $p(1–p)$ sequences, the lower and higher p values, and lower and

higher $p(1–p)$ values are coded in different discrete colors in the bars above the frequency

spectrum plots. Note that this discretization is only for illustration purposes and all data

analyses were still based on continuous values of p or $p(1–p)$.

A 2 (P-cycle or U-cycle) by 2 (N-small or N-large) experimental design was used,

as we describe below. Specifically, for P-cycle trials, the sequence of displays was

generated according to the p value and the displays alternated between lower values

of p (<0.5) and higher values of p (>0.5), with every two displays forming a cycle. As

the consequence, the values of p in P-cycle trials varied at a rhythm of 3.33 Hz, while

the values of $p(1–p)$ would be aperiodic. In contrast, for U-cycle trials (U for uncertainty),

the sequence of displays was generated according to the value of $p(1–p)$ in a similar

way so that the displays alternated between lower values of $p(1–p)$ (<0.21) and higher

values of $p(1–p)$ (>0.21) in cycles of 3.33 Hz, while the values of p were aperiodic. In

other words, in P-cycle trials, the p value underwent a rhythmic fluctuation and the $p(1–$

$p)$ value followed an aperiodic random course, whereas the opposite pattern occurred

for U-cycle trials. Fig 1B illustrates the P-cycle (left) and U-cycle (right) conditions. Note

that the discrete colors used in Fig 1B to code the values of p and $p(1–p)$ are only for

visualization purposes. The actual values of p and $p(1–p)$ were randomly chosen from

continuous uniform distributions (see Methods).

Our experimental design had two important features. First, the values of *p* and

p(1–*p*) were statistically independent of each other. Second, the values of *p* and *p*(1–

p) were dissociated in periodicity. Note that subjects' task was always to attend to *p*

(relative frequency), and *p*(1–*p*) was completely task-irrelevant in both *P*-cycle and *U*-

cycle trials.

Besides, the total number of dots in a display (numerosity, denoted *N*) was not

constant but varied from display to display, independently of *p* or *p*(1–*p*), ranging from

10 to 90 (*N*-small trials) or from 100 to 900 (*N*-large trials). The introduction of *N*-small

versus *N*-large trials served as a means to manipulate the slope of probability distortion

[1] so as to reveal the possible links between behavior and brain activity.

Behavioral probability distortions quantified by LLO

All the 22 subjects performed well on reporting the relative-frequency of the last display,

whose subjective estimate $\pi(p)$ was highly correlated with the objective relative-

frequency *p* (all Pearson's *r* > 0.71, *P* < 0.001). Given that the stimulus sequence might

end unexpectedly, if subjects had failed to track the sequence, they might have missed

the last stimulus. Subjects' sensible reports thus provide evidence that they had

tracked the change of *p* throughout the trial as instructed.

Fig 2A shows the reported $\pi(p)$ of one representative subject, who showed a

typical inverted-*S*-shaped probability distortion—overestimating small *p* and

underestimating large *p*. To better visualize the deviation of $\pi(p)$ from *p*, we plot

$\pi(p)-p$ as a function of p for each individual subject (S1 Fig). As expected, most

subjects exhibited the typical inverted-S-shaped probability distortion and a few

subjects exhibited the opposite S-shaped distortion, a profile also consistent with

previous findings [1, 4].

Fig 2. Behavioral and modeling results.

(A) Distortion of relative-frequency of one representative subject. The subject's

reported relative-frequency $\pi(p)$ is plotted against objective relative frequency p,

separately for the *N*-small and *N*-large conditions. Each dot is for one trial. Black curves

denote LLO model fits. **(B) Slope of distortion $\hat{\gamma}$ for the *N*-small and *N*-large**

conditions. Each gray line is for one subject. The thick green line denotes the group mean.

Error bars denote SEM. **(C) Illustration of representational uncertainty ($V(\hat{p})$) as a**

function of *p* and *N*. Larger values of *N* are coded in darker colors (same as **D**). The

maximal sample size is assumed to follow the form $n_s = b + N^a$, with *a*=0.42 and *b*=1.91

(median estimates across subjects). **(D) Illustration of probability distortion predicted**

by BLO: $\pi(p)$ as a function of *p* and *N*. Larger values of *N* are coded in darker colors.

(E) Slopes of distortion: data versus model fits. According to the value of *N* in the last

display, all trials were divided into four bins and the slope of distortion, $\hat{\gamma}$, was estimated

separately for each bin. Gray filled circles denote data. Error bars denote SEM. Red and

blue circles respectively denote BLO and LLO model fits. **(F) $\pi(p) - p$ as a function of**

***p* and *N*.** Black curves denote smoothed data on the group level, separately for the *N*-

small and *N*-large conditions. Shadings denote SEM. Red and blue curves respectively

denote BLO and LLO model fits. **(G) Results of factorial model comparison: summed**

Δ**AICc.** Lower values of ΔAICc indicate better fits. The BLO model outperformed all the

alternative models. **(H) Protected exceedance probability on each model dimension.**

Each panel is for model comparison on one dimension. Each assumption of the BLO model

outperformed the alternative assumptions on its dimension. **(I) Response time as an**

additional index for representational uncertainty. The mean response time (RT) for

subjects to initiate their relative-frequency report is plotted against binned *p* or *p*(1–*p*),

separately for the *N*-small and *N*-large conditions. Error bars denote SEM.

We next used the LLO model to quantify such inverted-*S*- or *S*-shaped distortions,

summarizing each subject's probability distortion behavior for each trial type (*P*-cycle

or *U*-cycle) and dot numerosity (*N*-small or *N*-large) conditions by two parameters fitted

from $\pi(p)$ (see Methods): slope $\hat{\gamma}$ and crossover point $\hat{p}_0$. According to 2 (*P*-cycle

or *U*-cycle) by 2 (*N*-small or *N*-large) repeated-measures ANOVAs separately

performed for the estimated $\hat{\gamma}$ and $\hat{p}_0$, numerosity showed a significant influence on

$\hat{\gamma}$ (F(1, 63) = 57.82, *P* < 0.001, $\eta_p^2 = 0.48$) and a statistically significant but small

influence on $\hat{p}_0$ (F(1, 63)=4.24, *P* = 0.044, η_p^2=0.06). No other main effects or

interactions reached significance (all $P > 0.26$). In particular, the $\hat{\gamma}$ estimated from N-

large trials was greater than that of N-small trials by 25.75% (Fig 2B). Thus our

subsequent analysis would mainly focus on $\hat{\gamma}$ and collapse the two cycle conditions

to estimate $\hat{\gamma}$. As illustrated in Fig 2A, a greater $\hat{\gamma}$ implies a less curved inverted-S-

shaped distortion (for $\hat{\gamma} < 1$) or a more curved S-shaped distortion (for $\hat{\gamma} > 1$).

It is noteworthy that LLO was only used as a way to quantify probability distortions

and their differences between conditions. The LLO model by itself could not explain

why the slope of distortion would differ between numerosity conditions, as observed

here (Fig 2AB). In contrast, the observed different $\hat{\gamma}$ between the N-small and N-

large conditions could be well captured by the bounded log-odds (BLO) model [9],

which compensates for the $p(1-p)$ form of representational uncertainty, with greater

$\hat{\gamma}$ implying lower representational uncertainty. Next we will present the BLO model

and how it may account for our behavioral results.

Bounded Log-Odds model and its behavioral evidence

Zhang, Ren, and Maloney [9] proposed the BLO model as a rational account of

probability distortion, which can explain why probability distortion may vary with task

or individual. BLO has three main assumptions: (1) probability is internally represented

as log-odds, (2) representation is truncated to a bounded scale, and (3)

representational uncertainty is compensated in the final estimate of probability, so that

estimates associated with higher uncertainty will be discounted to a greater extent.

See S1 Text for details. A full description of BLO would be out of the scope of the

present article and below we only focus on the uncertainty compensation assumption.

According to BLO, when representational uncertainty (denoted $V(\hat{p})$) is higher,

the subjective estimate of probability is less contributed by the percept of the objective

probability and more by a prior estimate, which implies that the higher the

representational uncertainty, the shallower the slope of probability distortion. As

illustrated in Fig 2C, the representational uncertainty modeled in our experiment (see

S1 Text) is proportional to $p(1–p)$, that is, an inverted-U-shaped function of p.

Meanwhile, for a median subject, $V(\hat{p})$ first slightly increases with N (Fig 2C, from

N=10 to N=20) and then dramatically decreases with N (Fig 2C, from N=20 to N=900).

Consequently, BLO predicts that the slope of distortion $\hat{\gamma}$ is not necessarily constant,

but may slightly decrease with N for very small N and mostly increase with N (Fig 2D),

which is indeed observed in our experiment (Fig 2B & 2E).

We are aware that representational uncertainty $V(\hat{p})$ here is not equivalent but

proportional to $p(1–p)$. In the neural analysis we will present, we chose to focus on the

encoding of $p(1–p)$ (as a proxy for representational uncertainty) instead of $V(\hat{p})$,

because $V(\hat{p})$ was highly correlated with numerosity N and thus would be difficult to

be separated from the latter in brain activities. In contrast, $p(1–p)$ and N were

independent of each other by design. Besides, $p(1–p)$ has a nice connection with the

"second-order valuation" proposed by Lebreton et al. [18].

Model versus data. Zhang et al. [9] has provided behavioral evidence for the BLO

model in two different tasks including relative-frequency judgment. Here we performed

similar tests on our behavioral data and fit the BLO model to the reported $\pi(p)$ for

each subject using maximum likelihood estimates. The performance of the LLO model

served as a baseline. When evaluating LLO's performance in fitting the data, we

estimated one set of parameters for all conditions instead of estimating different

parameters for different conditions as when we applied LLO as a measuring tool for

probability distortions. In Fig 2F, we plot the observed $\pi(p)-p$ (smoothed and

averaged across subjects) as a function of p separately for different numerosity

conditions and contrasted it with the BLO and LLO model predictions. The BLO

prediction agreed well with the observed probability distortion function, while LLO

largely failed. The advantage of BLO over LLO was even more pronounced in plots for

individual subjects (S1 Fig).

We further examined how well BLO could predict the observed numerosity effect

in the slope of distortion. For each subject, we divided the trials of each numerosity

condition evenly into two bins according to the value of N in the last display (i.e., the

display that was reported) and then estimated $\hat{\gamma}$ for each of the four bins. The pattern

of $\hat{\gamma}$ in real data—initial slight decrease and subsequent dramatic increase with N—

was quantitatively predicted by the fitted BLO model (Fig 2E).

Factorial model comparison. Similar to Zhang et al. [9], we performed a factorial

model comparison [19] to test whether each of the three assumptions in the BLO model

outperformed plausible alternative assumptions in fitting behavioral data. Accordingly

we constructed $3 \times 3 \times 2 = 18$ models and fit each model for each subject using

maximum likelihood estimates (see S2 Text for details). The Akaike information

criterion with a correction for sample sizes, AICc [20, 21], was used as the metric of

goodness-of-fit. Lower AICc indicates better fit. For each subject, the model with lowest

AICc was used as a reference to compute ΔAICc for each model. According to the

summed ΔAICc across subjects, BLO was the best model among the 18 models (Fig

2G).

We also evaluated whether each of BLO's three assumptions was the best among

its alternatives on the same dimension. In particular, we used the group-level Bayesian

model selection [22-24] to compute the probability that each specific model

outperforms the other models in the model set ("protected exceedance probability")

and marginalized the protected exceedance probabilities for each dimension (i.e.,

adding up the protected exceedance probabilities across the other two dimensions).

Indeed, all three assumptions of the BLO model in the present study—log-odd,

bounded, and compensation for $V(\hat{p})$ (with $n_s = b + N^a$)—outperformed their

alternatives with probabilities of 87.7%, 94.6% and 99.8%, respectively (Fig 2H).

Furthermore, we performed a model recovery analysis (similar to [25]) to confirm

that the advantage of BLO in factorial model comparison is real and does not result

from model mis-identification. In particular, we generated 50 synthetic datasets for

each of the 18 models. All the datasets generated from BLO were best fit by BLO. Out

of the 850 datasets generated from the other models, only 0.24% were mis-identified

to BLO (see S2A Fig for details).

We also verified that the parameters of BLO could be reasonably well identified

(S2B Fig). Even if some of the BLO parameters were not perfectly identified, it would

not influence the results of the neural analysis we report below, most of which did not

rely on the estimated BLO parameters.

Evidence for representational uncertainty in response time

The above modeling analysis on subjects' reported relative frequency (i.e. model fits

as well as the factorial model comparison) suggests that subjects might compensate

for representational uncertainty that is proportional to $p(1-p)$ and the N-large condition

was associated with lower uncertainty than the N-small condition.

The response time (RT) of reporting relative frequency (defined as the interval

between the response screen onset and the first mouse move) provides an additional

index for representational uncertainty, given that lower uncertainty would lead to

shorter RTs. We divided the values of p into five bins and computed RT for each bin

and separately for the N-small and N-large trials. According to a 5 (p bins) by 2 (N-

small vs. N-large) repeated-measures ANOVA on RTs, both the main effects of the p

value ($F(4, 189) = 29.02$, $P < 0.001$, $\eta_p^2 = 0.38$) and numerosity ($F(1, 189) = 25.61$, P

< 0.001, $\eta_p^2 = 0.12$) were significant. Consistent with Lebreton et al. [18], RTs were

longest at $p=0.5$ and shortest when p was close to 0 or 1 (Fig 2I, left). More precisely,

RTs increased almost linearly with $p(1-p)$ (Fig 2I, right), in agreement with what one

would expect if representational uncertainty is proportional to $p(1-p)$. Besides, RTs

were shorter in N-large trials than in N-small trials, which echoes the lower $V(\hat{p})$ for

larger N (Fig 2C) and provides further evidence that the N-large condition was

accompanied by lower representational uncertainty.

In sum, we found that a considerable portion of variability in subjects' probability

distortion functions and RT patterns can be accounted by differences in

representational uncertainty. One may wonder whether the effects of representational

uncertainty can be explained away by task difficulty. We doubt not, because higher

representational uncertainty does not necessarily correspond to higher task difficulty.

For example, representational uncertainty for relative-frequency estimation is

proportional to $p(1–p)$, which is maximal at p=0.5 and minimal when p is close to 0 or

1. In contrast, regarding difficulty, there seems to be little reason to expect that relative-

frequency estimation should be more difficult for p=1/2 than for p=1/3, or be more

difficult for p=1/3 than for p=1/4. As another counter-example, representational

uncertainty modeled in the present study is higher in the *N*-small condition than in the

N-large condition (Fig 2C), but there seems to be little reason to expect relative-

frequency estimation to be more difficult for displays with fewer dots.

Neural entrainment to periodic changes of *p* or *p*(1–*p*)

After showing that the BLO models can well capture the behavioral results, we next

examined whether the brain response could track the periodically changing *p* values

(*P*-cycle) or *p*(1–*p*) values (*U*-cycle) in the stimulus sequence. Recall that the *P*-cycle

and *U*-cycle trials had identical individual displays and differed only in the ordering of

the displays: In *P*-cycle trials, *p* alternated between small and large values in cycles of

3.33 Hz while *p*(1–*p*) was aperiodic; in *U*-cycle trials, *p*(1–*p*) alternated in cycles of 3.33

Hz while *p* was aperiodic.

As shown in Fig 3, the brain response indeed tracked the periodic changes of *p*

and *p*(1–*p*). In particular, in *P*-cycle trials (Fig 3, left), the phase coherence between

the periodic *p* values and the MEG time series reached significance at 3.33 Hz

(permutation test, *FDR* corrected P_{FDR} < 0.05), mainly in the occipital and parietal

sensors. Importantly, significant phase coherence was also found at 3.33 Hz in *U*-cycle

trials between the periodic *p*(1–*p*) values and the MEG time series (Fig 3, right). That

is, the brain activity was also entrained to the periodic changes of the representational

uncertainty of *p* (i.e. *p*(1–*p*)). Given that subjects were only asked to track the value of

p but not *p*(1–*p*), the observed neural entrainment to the task-irrelevant *p*(1–*p*)

suggests an automatic encoding of representational uncertainty in the brain.

Fig 3. Results of phase coherence analysis.

Grand-averaged phase coherence spectrum for magnetometers. **Left**: The phase

coherence (κ) between the periodic *p* values and MEG time series in *P*-cycle trials. **Right**:

The phase coherence between the periodic *p*(1–*p*) values and MEG time series in *U*-cycle

trials. Light and dark green curves respectively denote the *N*-small and *N*-large conditions.

Shadings denote SEM across subjects. The vertical line marks 3.33 Hz. Dots above the

spectrum mark the frequency bins whose phase coherence was significantly above chance

level (permutation tests, P_{FDR} <0.05 with *FDR* correction across frequency bins). **Insets:**

Grand-averaged phase coherence topography at 3.33 Hz for each cycle and numerosity

condition. Solid black dots denote sensors whose phase coherence at 3.33 Hz was

significantly above chance level (permutation tests, P_{FDR}<0.05 with *FDR* corrected across

magnetometers).

Notably, the significant phase coherences between the periodic *p* or *p*(1–*p*) values

and MEG time series were not simply because the MEG time series consisted of 3.33

Hz frequency components. In a control analysis, we calculated the phase coherence

between the aperiodic variable (i.e. *p* in *U*-cycle trials or *p*(1–*p*) in *P*-cycle trials) and

the same MEG time series, and found that there were no significant peaks at 3.33 Hz

(S5B Fig). Moreover, we had carefully controlled potential confounding variables in our

experimental design. For example, *p* and *p*(1–*p*) were linearly independent of each

other, both of which had negligible correlations with numerosity or low-level visual

features such as luminance, contrast, and color variance (S5A Fig). Furthermore,

different from *p* and *p*(1–*p*), these potential confounding variables were associated with

similar entrainment responses in *P*-cycles and *U*-cycles (S5B Fig).

Behavioral probability distortion and the neural entrainment to *p* and *p*(1–

***p*)**

We next examined the relationship between behavioral probability distortion and the

neural entrainment to *p* and *p*(1–*p*) on a subject-by-subject basis. Specifically, the

phase coherence between a specific variable (*p* or *p*(1–*p*)) and the MEG time series

can be considered as a measure of the strength of neural responses to the variable

[26]. We defined

$$\beta = \frac{\kappa_p}{\kappa_{p(1-p)}} \tag{1}$$

to quantify the relative strength of p to $p(1–p)$ in neural responses, where κ_p denotes

the phase coherence for p in P-cycle trials, and $\kappa_{p(1-p)}$ denotes the phase coherence

for $p(1–p)$ in U-cycle trials. A higher value of β would imply a stronger neural

encoding of relative-frequency or a weaker encoding of representational uncertainty

and is thus supposed to yield probability distortions of a greater slope [9]. Note that

both the behavioral and neural measures we defined below were intra-subject ratios

that were unitless and scale free, thus not subject to the potential scaling issues in

inter-individual correlation [27].

Given that the estimated slope of distortion $\hat{\gamma}$ was greater in N-large trials than

in N-small trials, we would expect β to change in the same direction across the

numerosity conditions. That is, suppose we define $\Delta\hat{\gamma} = \ln\left(\dfrac{\hat{\gamma}_{N\text{-large}}}{\hat{\gamma}_{N\text{-small}}}\right)$ and

$\Delta\beta = \ln\left(\dfrac{\beta_{N\text{-large}}}{\beta_{N\text{-small}}}\right)$, there should be a positive correlation between $\Delta\hat{\gamma}$ and $\Delta\beta$.

As shown in Fig 4, there was indeed a significant correlation between behavioral

and neural measures across subjects in the parietal region (Pearson's $r = 0.67$, *FDR*-

corrected one-tailed $P_{FDR} = 0.033$), associating the neural entrainment to p and $p(1–p)$

with probability distortion behaviors.

Fig 4. Neural responses to *p* and *p(1–p)* predict the slope of probability distortion.

We defined $\Delta\hat{\gamma} = \ln\left(\dfrac{\hat{\gamma}_{N\text{-large}}}{\hat{\gamma}_{N\text{-small}}}\right)$ and $\Delta\beta = \ln\left(\dfrac{\beta_{N\text{-large}}}{\beta_{N\text{-small}}}\right)$ to respectively quantify how much the

behavioral measure of the slope of distortion, $\hat{\gamma}$, and the relative strength of *p* to *p(1–p)*

in neural responses, β, changed across the two numerosity conditions. **Main plot**:

Correlation between $\Delta\hat{\gamma}$ and the $\Delta\beta$ at the parietal magnetometer channel MEG0421.

The logarithm transformation was used only for visualization. Each dot denotes one

subject. **Inset**: Correlation coefficient topography between $\Delta\hat{\gamma}$ and $\Delta\beta$, on which

MEG0421 is marked by a solid black dot.

Neural encoding of *p* and *p(1–p)* over time and the associated brain

regions

After establishing the automatic tracking of cyclic changes in *p(1–p)* and its behavioral

relevance, we next aimed to delineate the temporal dynamics of *p* and *p(1–p)* in the

brain signals. Recall that on each trial one of the two variables of our interest (*p* or *p(1–*

p)) changed periodically and the other was aperiodic. Therefore, we could decode the

temporal course of aperiodic *p(1–p)* in *P*-cycles trials and aperiodic *p* in *U*-cycle trials.

In particular, we performed a time-resolved decoding analysis based on all 306

sensors (see Methods) using a regression approach that has been employed in

previous EEG and MEG studies [28, 29] including ours [30-32]. The intuition of the

time-resolved decoding analysis is as follows. Suppose the onset of each new p or

$p(1-p)$ value in the stimulus sequence evokes phase-locked brain responses that

extend across time and whose magnitudes are proportional to the encoded value. The

resulting MEG time series would then be a superposition of the responses to all the

preceding stimuli in the sequence. But as soon as the values of an encoded variable

are not correlated over time (i.e. free of autocorrelation), their brain response profiles

are separable. In particular, for any stimulus in the sequence, we can use the MEG

signals at a specific delay after the stimulus onset to predict the value of the stimulus.

Importantly, different from the phase coherence analysis (Fig 3) that only reflects the

overall strength of the brain responses, this time-resolved decoding analysis allows us

to assess how p and $p(1-p)$ are encoded over time.

Fig 5 plots the temporal course of the decoding performance for p (left) and $p(1-$

$p)$ (right). We found that both p and $p(1-p)$ were successfully decoded from the MEG

signals in N-large trials (cluster-based permutation test, $P_{cluster} < 0.05$). In particular, the

decoding performance for p peaked around 327 ms after stimulus onset (Fig 5, left),

while that for $p(1-p)$ peaked around 419 ms (Fig 5, right). In other words, the neural

encodings of relative frequency and its representational uncertainty had distinct time

courses, with the latter occurring approximately 100 ms later than the former (also see

S8 Fig for the decoding performance of individual subjects).

In contrast, none of the potential confounding variables (numerosity, luminance,

etc.) showed temporal courses similar to p or $p(1-p)$ when the same time-resolved

decoding procedure was applied (S5C Fig). The automatic encoding of the task-

relevant $p(1-p)$ might seem surprising. To further verify that this was not an artifact of

potential low-level confounds, we performed an additional decoding analysis for $p(1-$

$p)$ based on the cross-validated version of confound regression (CVCR) [33], where

the confounding variables were regressed out from MEG time series before time-

resolved decoding analysis (see S7 Text for details). The decoded temporal course for

$p(1-p)$ was little changed (S9A Fig). A similar decoding analysis for the complete form

of representational uncertainty $V(\hat{p})$ resulted in similar temporal course as that of

$p(1-p)$ (S9B Fig). In sum, we found automatic encoding of $p(1-p)$ in brain signals even

when it was task-irrelevant and when low-level confounding factors were excluded.

Further, based on the time windows that achieved the highest time-resolved

decoding performance, we performed a similar decoding analysis at each sensor

location (including one magnetometer and two orthogonal planar gradiometers)

separately for p and $p(1-p)$ to assess the associated brain regions (see Methods). We

found that the encoding of the two variables involved overlapping parietal-occipital

regions (Fig 5, see S7 Fig for the results of the other above-chance time windows),

including the parietal region where $\Delta\beta$ and $\Delta\hat{\gamma}$ were positively correlated (Fig 4).

Fig 5. Results of decoding analyses.

Main plots: Time-resolved decoding performance over different time lags for p (left panel) and $p(1–p)$ (right panel), separately for the N-small (light green) and N-large (dark green) conditions. Shadings denote SEM across subjects. Symbols above the curves indicate time lags that had above-chance decoding performance (cluster-based permutation tests), with vertical bars representing $P_{cluster}<0.01$ and dots representing $0.01≤P_{cluster}<0.05$. The decoding performance for p peaked at around 327 ms after stimulus onset, while that for $p(1–p)$ peaked at around 419 ms. **Insets**: Topography of spatial decoding performance for the time window (highlighted by the funnel-shaped dashed lines) that contained the peak decoding performance in the time-resolved decoding analysis. Solid black dots indicate the sensor locations with above-chance decoding performance ($P_{FDR} < 0.05$) for the N-large condition. (Spatial decoding in the same time windows for the N-small condition resulted in no statistically significant sensors.) The encodings of p and $p(1–p)$ involved overlapping parietal-occipital regions, including the parietal region where $\Delta\beta$ and $\Delta\hat{\gamma}$ were positively correlated (Fig 4).

Discussion

We used MEG to investigate probability distortions in a relative-frequency estimation task and found that the human brain encodes not only the task-relevant relative frequency but also its task-irrelevant representational uncertainty. The neural encoding of the representational uncertainty occurs at as early as approximately 400 ms. These results suggest that the human brain automatically and quickly quantifies the uncertainty inherent in probability information. Our findings provide neural evidence for the theoretical hypothesis that probability distortion is related to representational uncertainty. More generally, these findings may connect to the functional role of confidence (estimation of uncertainty) during judgment and decision making.

Neural computations underlying probability distortions

Humans show highly similar probability distortions in tasks involving probability or relative frequency, with the subjective probability typically an inverted-*S*-shaped function of the objective probability [1]. Why do people distort probability information in such a systematic way? Though inverted-*S*-shaped distortions of probability had been found in the activity of a few brain regions [34, 35], the neural computations involved in transforming objective probabilities to subjective probabilities were largely unknown. Several theories [9, 15-17] rationalize probability distortion as a consequence of compensating for representational uncertainty, in accordance with the framework of Bayesian Decision Theory [36]. In brief, the brain will discount an internal

representation of probability according to the level of uncertainty so that it can achieve

a more reliable estimate of the objective probability. The higher the uncertainty

associated with a representation, to a greater extent the representation is discounted.

By modeling human subjects' probability distortion behavior in two representative

tasks—relative-frequency estimation and decision under risk—Zhang et al. [9] found

evidence that representational uncertainty proportional to $p(1-p)$ is compensated in

human representation of probability or relative frequency.

What we found in the present study is neural evidence for the encoding of $p(1-p)$

during the evaluation of p. For the first time, we have shown that representational

uncertainty $p(1-p)$ is not just virtual quantities assumed in computational models of

probability distortions but is really computed in the brain.

Representational uncertainty and confidence

The representational uncertainty that concerns us lies in the internal representation of

probability or relative-frequency. One concept that may occasionally coincide with such

epistemological uncertainty but is entirely different is outcome uncertainty, which is

widely studied in the literature of decision under risk [37, 38], prediction error [37] and

surprise [39, 40]. For example, for a two-outcome gamble with probability p to receive

x_1 and probability $1-p$ to receive x_2, the variance of the outcomes is proportional to

$p(1-p)$. In the present study, the relative-frequency estimation task we chose to

investigate does not involve similar binary uncertain outcomes and thus avoids the

possible confusion of outcome uncertainty with representational uncertainty.

Therefore, the neural encoding of $p(1-p)$ we found here cannot be attributed to the

perception of outcome uncertainty.

In fact, representational uncertainty is more closely related to confidence, except

that it is not necessarily bound to any specific judgment or decision [41]. Specifically,

the encoding of representational uncertainty may be understood as a special case of

the "second-order valuation" proposed by Lebreton et al. [18]. As described earlier,

Lebreton et al. [18] found a principled relationship between an overt numerical

judgment and the individual's confidence about the judgment, with the latter being a

quadratic function of the former. They showed in fMRI studies that such quadratic

form—as a proxy to confidence—is automatically encoded in vmPFC, even when

confidence rating is not explicitly required of. Using the same quadratic form as the

proxy, here we found automatic encoding of the representational uncertainty of relative

frequency during the tracking of a visual sequence. Meanwhile, our findings extend

previous work and contribute to the confidence literature in the following three aspects.

First, we found automatic encoding of representational uncertainty even in the

absence of overt judgment, not just in the absence of overt confidence estimation. In

our experiment, subjects were asked to track the relative frequency in the stimulus

sequence but made no overt judgment except for the last display. Moreover, displays

were refreshed every 150 ms, apparently leaving no time for deliberation.

Second, we resolved the temporal course of the encoding of representational

uncertainty, which would be inaccessible under the low temporal resolution of fMRI. In

particular, representational uncertainty is encoded as early as 400 ms upon stimulus

onset, approximately 100 ms after the encoding of relative frequency itself. The

occipital-parietal region is involved in the processing of both relative-frequency and its

representational uncertainty but during different time windows. The fast encoding of

representational uncertainty we found echoes recent psychophysiological findings in

humans [42-44] and non-human primates [45] that the confidence encoding for

perceptual judgments can be detected in the brain far before confidence rating and

even prior to the overt judgment or decision making.

Third, our findings connect to the functional importance of confidence encoding in

information processing [41, 46, 47] that is still not well understood but receives growing

attention. In particular, here we ask how the neural encoding of representational

uncertainty may relate to probability distortion. By comparing experimental conditions

under which the same individuals' distortions of relative frequency differed, we found

that a relatively stronger response to representational uncertainty in the parietal region

corresponds to a shallower slope of distortion. We conjecture that the automatic, fast

encoding of representational uncertainty might not just be *post hoc* evaluation but

indeed regulate probability distortion. Meanwhile, we are aware that our current

findings are based on correlational analyses and whether there is causality between

the neural encoding of representational uncertainty and probability distortion still

awaits future empirical tests.

Methodology implications

The "steady-state responses" (SSR) technique [48]—using rapid periodic stimulus sequence to entrain brain responses—has been widely used with EEG/MEG to investigate low-level perceptual processes, which increases the signal-to-noise ratio of detecting the automatic brain responses to the stimuli by sacrificing temporal information. In our experiment, we constructed periodic p or $p(1–p)$ sequences and showed that SSR can also be used to reveal the brain's automatic responses to these more abstract variables. Moreover, we demonstrate the feasibility to perform time-resolved decoding for the other aperiodic variable embedded in the same sequence, whereby exploiting the advantages of both the SSR and time-resolved decoding techniques. Such design would be useful for a broad range of problems that need to dissociate the processing of two or more variables in brain activities.

Materials and Methods

Ethics Statement

The study had been approved by the Institutional Review Board of School of Psychological and Cognitive Sciences at Peking University (#2015-03-13c). Subjects provided written informed consent in accordance with the Declaration of Helsinki.

Subjects

Twenty-two human subjects (aged 18–27, 13 female) participated. All of them had normal or corrected-to-normal vision and passed the Farnsworth-Munsell 100 Hue Color Vision Test [49].

Experimental Procedures

Apparatus. Subjects were seated approximately 86 cm in front of a projection screen (Panasonic PT-DS12KE: 49.6 × 37.2 cm, 1024 × 768 pixels, 60-Hz refresh rate) inside the magnetically shielded room. Stimuli were controlled by a Dell computer using Matlab and PsychToolbox-3 [50, 51]. Subjects' behavioral responses were recorded by a MEG-compatible mouse system (FOM-2B-10B from Nata technologies) and their brain activities by a 306-channel MEG system (see MEG Acquisition and Preprocessing for details).

Task. Each trial started with a white fixation cross on a blank screen for 600 ms, following which a sequence of displays of orange and blue dots was presented on a gray background at a rate of 150 ms per display (Fig 1A). Subjects were asked to fixate

on the central fixation cross and track the relative-frequency of each display. After the

sequence ended for 1000 ms, a horizontal scale (0 to 100%) appeared on the screen

and subjects were required to click on the scale to indicate the relative-frequency of

orange (or blue) dots on the last display. Half of the subjects reported relative frequency

for orange dots and half for blue dots.

To encourage subjects to pay attention to each display, one out of six trials were

catch trials whose duration followed a truncated exponential distribution (1–6 s, mean

3 s), such that almost each display could be the last display. The duration of formal

trials was 6 or 6.15 s. Only the formal trials were submitted to behavioral and MEG

analyses.

On each display, all dots were randomly scattered without overlapping within an

invisible circle that subtended a visual angle of 12°. The visual angle of each dot was

0.2° and the center-to-center distance between any two dots was at least 0.12°. The

two colors of the dots were isoluminant (CIE_{orange}=[43, 19.06, 52.33], CIE_{blue}=[43, -

15.49, -23.72]). Isoluminant dark gray pixels (CIE_{gray}=[43, 0, 0]) were filled on the gray

background ($CIE_{background}$=[56.5, 0, 0]) between the dots as needed to guarantee each

display had equal overall luminance, which prevented luminance from being a

confounding factor for any abstract variables of interest.

Design. We adopted a steady-state response (SSR) design, which could achieve a

higher signal-to-noise ratio than the conventional event-related design [48]. The basic

idea was to vary the value of a variable periodically at a specific temporal frequency

and to observe the brain activities at the same frequency as an idiosyncratic response

to the variable. The variables of most interest in the present study were relative

frequency p and its representational uncertainty quantified by $p(1-p)$.

For half of the trials (referred as the P-cycle condition), the value of p in the

sequence was chosen from uniform distributions with the ranges alternatively being

(0.1, 0.5) and (0.5, 0.9) so that the sequence of p formed cycles of 3.33 Hz. For the

other half trials (referred as the U-cycle condition), the value of p was chosen

alternatively from (0.1 0.3) U (0.7, 0.9) and (0.3, 0.7) so that the sequence of $p(1-p)$

(i.e. proxy for uncertainty) was in cycles of 3.33 Hz. That is, the two cycle conditions

had matched individual displays but differed in which variable formed a periodic

sequence. Accordingly, the $p(1-p)$ sequence in the P-cycle condition and the p

sequence in the U-cycle condition were aperiodic, which had little autocorrelations (S3

Text & S4 Fig).

The total number of dots on a display (numerosity, denoted N) was varied across

trials as well as across individual displays of the same trial. The value of N for a specific

display was independent of the value of p and generated as a linear transformation of

a beta random variable following Beta(0.1, 10) so that the number of dots in each color

(pN or $(1-p)N$), a possible confounding variable of p, would only have moderate

correlations (Pearson's $|r| < 0.5$) with p. The linear transformation was chosen to locate

N to the range of [10, 90] for half of the trials (the N-small condition) and to [100, 900]

for the other half (the N-large condition).

The numbers of dots in each color was pN or $(1-p)N$ rounded to the nearest integer.

As the result of rounding, the actual relative-frequency was slightly different from the

originally chosen *p*. In data analysis, we would use *p* to denote the actual relative-

frequency that was presented to subjects.

To summarize, there were 2 (*P*-cycle vs. *U*-cycle) by 2 (*N*-small vs. *N*-large)

experimental conditions, with all conditions interleaved and each condition repeated

for 6 trials in each block. Each subject completed 10 blocks of 24 trials, resulting in 50

formal trials and 10 catch trials for each condition. Before the formal experiment, there

were 32 practice trials (the first 20 trials consisted of one display and the following 12

trials had the same settings as the formal experiment) for subjects to be familiar with

the procedure. No feedback was available during the experiment.

Behavioral Analysis

Measures of probability distortion. According to Zhang and Maloney [1], inverted-

S- or *S*-shaped probability distortions can be well captured by the LLO model

639
$$\lambda\big[\pi(p)\big]=\gamma\lambda\big[p\big]+(1-\gamma)\lambda\big[p_0\big]+\varepsilon_\lambda, \tag{2}$$

where p and $\pi(p)$ respectively denote the objective and subjective probability or

relative-frequency, $\lambda\big[p\big]=\log\dfrac{p}{1-p}$ is the log-odds transformation, and ε_λ is

Gaussian error on the log-odds scale with mean 0 and variance σ_λ^2. The γ, p_0, and

σ_λ are free parameters. The parameter γ is the slope of distortion, with $\gamma<1$

corresponding to inverted-*S*-shaped distortion, $\gamma=1$ to no distortion, and $\gamma>1$ to *S*-

shaped distortion. The parameter p_0 is the crossover point where $\pi(p)=p$.

For each subject and condition, we fit the reported relative-frequency to the LLO

model (Eq. 2) and used the estimated $\hat{\gamma}$ and $\hat{p}_0$ as the measures of relative-

frequency distortions.

Response time. The response time (RT) was defined as the interval between the

response screen onset and subjects' first mouse move. The RT of the first trial of three

subjects was mis-recorded due to technical issues and was excluded from further

analysis. We divided all trials evenly into 5 bins based on the to-be-reported p, and

computed the mean p and mean RT for each bin. A 5 (p bins) by 2 (numerosity

conditions) repeated-measures ANOVA was performed on the mean RTs. A similar

binning procedure was applied to $p(1-p)$ to visualize the relationship of RT to $p(1-p)$.

Non-parametric measures of probability distortion. As a complement to the LLO

model (Eq. 2), we used a non-parametric method to visualize the probability distortion

curve for each subject. In particular, we smoothed $\pi(p) - p$ using a kernel regression

method with the commonly-used Nadaraya-Watson kernel estimator [52-54]:

660
$$\hat{M}_h(x) = \frac{\sum_{i=1}^{m} K\left(\frac{x - x_i}{h}\right) y_i}{\sum_{i=1}^{m} K\left(\frac{x - x_i}{h}\right)} \ , \tag{3}$$

661   where x_i and y_i ($i = 1, 2, ..., m$) denote observed pairs of stimuli and responses,

662    $\hat{M}_h(x)$ denotes the smoothed response at the stimulus value x, and h is a parameter

663   that controls the degree of smoothing and were set to be 0.03. The $K(\cdot)$ denotes the

664   Gaussian kernel function:

665
$$K(z) = \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{z^2}{2}\right). \tag{4}$$

Model fitting. For each subject, we fit the BLO model to the subject's $\pi(p)$ in each

trial using maximum likelihood estimates. The *fminsearchbnd* (J. D'Errico), a function

based on *fminsearch* in MATLAB (MathWorks), was used to search for the parameters

that minimized negative log likelihood.

We compared the goodness-of-fit of the BLO model with all of the alternative

models based on the Akaike information criterion with a correction for sample sizes

(AICc) [20, 21] and group-level Bayesian model selection [22-24]. To verify that we had

found the global minimum, we repeated the searching process for 1000 times with

different starting points.

MEG Acquisition and Preprocessing

Subjects' brain activity was recorded by a 306-channel whole-head MEG system

(Elekta-Neuromag, 102 magnetometers and 102 pairs of orthogonal planar

gradiometers). Head position was measured before each block by an isotrack

polhemus system with four head position indicator coils (two on the left and right

mastoid, the other two on the left and right forehead below the hairline). Subjects

whose between-block head movement exceeded 3 mm would be excluded from further

analysis. Horizontal and vertical Electro-oculograms were recorded to monitor eye-

movement artifacts. Sampling rate was set to be 1000 Hz and an analog band-pass

filter from 0.1 to 330 Hz was applied. Maxwell filtering was used to minimize external

magnetic interference and to compensate for head movements [55, 56].

Standard preprocessing procedures were applied using Matlab 2016b and the

FieldTrip package [57]. The MEG data of each block was first low-pass filtered below

690 20-Hz and then segmented into epochs of 7.6 s relative to trial onset (–0.6 s to 7 s).

691 Independent component analysis (ICA) was applied to aggregated epoch data to

692 remove artifacts including blinks, eye movements, breaths and heart activity. No

693 subject was excluded for excessive head movement or other artifacts. For two subjects,

694 the first trial of one block was excluded due to the failure of synchronization between

695 stimulus onset and MEG recording onset at the beginning of the block.

697 **Phase Coherence Analysis**

698 Given a periodically-changed stimulus sequence (p in P-cycle or $p(1-p)$ in U-cycle),

699 stimulus-evoked brain responses imply that the phase difference between the stimulus

700 and response time series should be coherent across trials at the stimulus frequency

701 [58]. The phase coherence across trials is defined as [26]:

702
$$\kappa = \frac{\left|\bar{P}_{rs}\right|}{\sqrt{\bar{P}_{ss}}\sqrt{\bar{P}_{rr}}} \quad , \tag{5}$$

703 where $\bar{P}_{ss}$ and $\bar{P}_{rr}$ respectively denote the trial-averaged power spectrum for

704 stimulus and response time series, and $|\bar{P}_{rs}|$ denotes the magnitude of the trial-

705 averaged cross-spectrum between stimuli and responses. The value of κ for any

706 specific frequency is between 0 and 1, with larger κ indicating stronger phase-locked

707 responses.

708  For a specific variable (p or $p(1-p)$), we computed the phase coherence between

709 stimulus sequence and MEG signals separately for each subject, each magnetometer

710 and each cycle and numerosity condition. In particular, we down-sampled epoched

711 MEG time series to 300 Hz, applied zero padding and Hanning window to single trials,

and used Fast Fourier Transformation (FFT) to calculate power spectrum. The

resulting frequency resolution was 0.03 Hz.

To evaluate the chance-level phase coherence, we shuffled the MEG time series

across different time points within each trial and computed phase coherence for the

permutated time series. This permutation procedure was repeated for 500 times to

produce a distribution of chance-level phase coherences.

Decoding Analysis

Time-resolved decoding. For an aperiodic stimulus sequence ($p(1–p)$ in P-cycle or p

in U-cycle), we could infer the brain's encoding of the stimulus variable at a specific

time lag to stimulus onset by examining how well the value of the variable could be

reconstructed from the neural responses at the time lag. In particular, we performed a

time-resolved decoding analysis using regression methods [28, 29, 59, 60]:

$$S(t) = \sum_{n} g(\tau,n) R(t+\tau,n) + \varepsilon(t) \ ,$$ (6)

where $S(t)$ denotes the value of the stimulus that starts at time t, $g(\tau,n)$ denotes

the to-be-estimated decoding weight for channel n at time lag , $R(t+\tau,n)$ denotes

the response of channel n at time $t+\tau$, and $\varepsilon(t)$ is a Gaussian noise term.

We used the MEG signals of all 306 sensors (102 magnetometers and 204

gradiometers) at single time lags to decode p from U-cycle trials or $p(1–p)$ from P-cycle

trials, separately for each subject, each cycle and numerosity condition, and each time

lag between 0 and 900 ms. Epoched MEG time series were first down-sampled to 120

Hz. To eliminate multicollinearity and reduce overfitting, we submitted the time series

of the 306 sensors to a principal component analysis (PCA) and used the first 30

components (explaining approximately 95% variance) as the regressors. The decoding

weights (i.e. regression coefficients) were estimated for normalized stimuli and

responses using the L2-rectified regression method implemented in the mTRF toolbox

[28] , with the ridge parameter set to 1.

We used a leave-one-out cross-validation [61] to evaluate the predictive power of

decoding performance as the following. Out of the 50 trials in question (or 49 trials in

the case of trial exclusion), each time one trial served as the test set and the remaining

trials as the training set. The decoding weights estimated from the training set were

applied to the test set, for which Pearson's r was calculated between the predicted and

the ground-truth stimulus sequence. Such computation was repeated for each trial as

the test set and the averaged Pearson's r was used as the measure for decoding

performance.

We identified time windows that had above-chance decoding performance using

cluster-based permutation tests [62] as follows. Adjacent time lags with significantly

positive decoding performance at the uncorrected significance level of .05 by right-

sided one-sample t tests were grouped into clusters and the summed t-value across

the time lags in a cluster was defined as the cluster-level statistic. We randomly

shuffled the stimulus sequence of each trial, performed the time-resolved decoding

analysis on the shuffled sequence and recorded the maximum cluster-level statistic.

This procedure was repeated for 500 times to produce a reference distribution of

chance-level maximum cluster-level statistic, based on which we calculated the P

value for each cluster in real data. This test effectively controls the Type Ⅰ error rate

in situations involving multiple comparisons. For each subject, we defined the median

of all time points for which the decoding performance exceeded the 95% percentile of

the distribution as the time lag of the peak [63].

Spatial decoding. For the conditions and time windows that had above-chance

performances in the time-resolved decoding analysis, we further performed a spatial

decoding analysis at individual sensor location to locate the brain regions that are

involved in encoding the variable in question. For a specific senor location, the MEG

signals at its three sensors (one magnetometer and two gradiometers) within the time

window were used for decoding. The time window that enclosed the peak in the time-

resolved decoding was 125-ms and 167-ms wide respectively for p and $p(1\text{-}p)$ under

N-large condition. The decoding procedure was similar to that of the time-resolved

decoding described above, except that the number of PCA component used was 19

and 24 respectively for decoding p and $p(1-p)$, which explained approximately 99%

variance of the original 48 (16 time lags × 3 sensors) and 63 (21 time lags × 3 sensors)

channels.

Statistical Analysis

For phase coherence or decoding performance, grand averages across subjects were

computed and permutation tests described above were used to assess their statistical

significance over chance [62]. The false discovery rate (*FDR*) method [64, 65] was

778 used for multiple comparison corrections whenever applicable. For the phase

779 coherence spectrum averaged across magnetometers, *FDR* corrections were

780 performed among the 235 frequency bins within 0–7 Hz. For the phase coherence

781 topography at 3.33 Hz, *FDR* corrections were performed among all 102

782 magnetometers.

References

1. Zhang H and Maloney LT, *Ubiquitous log odds: a common representation of probability and frequency distortion in perception, action, and cognition.* Frontiers in Neuroscience, 2012. **6**: 1

2. Attneave F, *Psychological probability as a function of experienced frequency.* Journal of Experimental Psychology, 1953. **46**(2): 81-86

3. Lichtenstein S, Slovic P, Fischhoff B, Layman M, and Combs B, *Judge Frequency of Lethal Events.* Journal of Experimental Psychology: Human Learning and Memory, 1978. **4**(6): 551-578

4. Varey CA, Mellers BA, and Birnbaum MH, *Judgments of Proportions.* Journal of Experimental Psychology: Human Perception and Performance, 1990. **16**(3): 613-625

5. Erev I, Wallsten TS, and Budescu DV, *Simultaneous over- and underconfidence: the role of error in judgment processes.* Psychological Review, 1994. **101**(3): 519-527

6. Gigerenzer G, Hoffrage U, and Kleinbölting H, *Probabilistic mental models: a Brunswikian theory of confidence.* Psychological Review, 1991. **98**(4): 506-528

7. Wallsten TS, Budescu DV, Erev I, and Diederich A, *Evaluating and combining subjective probability estimates.* Journal of Behavioral Decision Making, 1997. **10**: 243-268

8. Gonzalez R and Wu G, *On the Shape of the Probability Weighting Function.* Cognitive Psychology, 1999. **38**: 129-166

9. Zhang H, Ren X, and Maloney LT, *The bounded rationality of probability distortion.* bioRxiv [Preprint]. 2019 bioRxiv 662429 [posted 2019 Jun 6; revised 2019 Nov 14; revised 2020 May 23; cited 2020 May 31] Available from: https://www.biorxiv.org/content/10.1101/662429v3 doi: 10.1101/662429

10. Tversky A and Kahneman D, *Advances in Prospect Theory: Cumulative Representation of Uncertainty.* Journal of Risk and Uncertainty, 1992. **5**: 297-323

11. Luce RD, *Utility of gains and losses: measurement – theoretical, and experimental approaches*, ed. S.W. Link and J.T. Townsend. 2000, Mahwah, New Jersey, London: Lawrence Erlbaum Associates, Inc.

12. Stauffer WR, Lak A, Bossaerts P, and Schultz W, *Economic Choices Reveal Probability Distortion in Macaque Monkeys.* The Journal of Neuroscience, 2015. **35**(7): 3146-3154

13. Ferrari-Toniolo S, Bujold PM, and Schultz W, *Probability distortion depends on choice sequence in Rhesus Monkeys.* The Journal of Neuroscience, 2019. **39**(15): 2915-2929

14. Yang T and Shadlen MN, *Probabilistic reasoning by neurons.* Nature, 2007. **447**: 1075-1080

15. Fennell J and Baddeley R, *Uncertainty plus prior equals rational bias: an*
intuitive Bayesian probability weighting function. Psychological Review, 2012.
119(4): 878-887

16. Martins ACR, *Probability biases as Bayesian inference.* Judgment and
Decision Making, 2006. **1**(2): 108-117

17. See KE and Fox CR, *Between ignorance and truth: partition dependence and*
learning in judgment under uncertainty. Journal of Experimental Psychology:
Learning, Memory, and Cognition, 2006. **32**(6): 1385-1402

18. Lebreton M, Abitbol R, Daunizeau J, and Pessiglione M, *Automatic integration*
of confidence in the brain valutation signal. Nature Neuroscience, 2015. **18**(8):
1159-1167

19. van den Berg R, Awh E, and Ma WJ, *Factorial comparison of working memory*
models. Psychological Review, 2014. **121**(1): 124-149

20. Akaike H, *A new look at the statistical model identification.* IEEE Transactions
on Automatic Control, 1974. **19**(6): 716-723

21. Hurvich CM and Tsai CL, *Regression and time series model selection in small*
samples. Biometrika, 1989. **76**(2): 297-307

22. Stephan KE, Penny WD, Daunizeau J, Moran RJ, and Friston KJ, *Bayesian*
model selection for group studies. NeuroImage, 2009. **46**: 1004-1017

23. Rigoux L, Stephan KE, Friston KJ, and Daunizeau J, *Bayesian model selection*
for group studies - Revisited. NeuroImage, 2014. **84**: 971-985

24. Daunizeau J, Adam V, and Rigoux L, *VBA: a probabilistic treatment of nonlinear*
models for neurobiological and behavioural data. PLoS Computational Biology,
2014. **10**(1)

25. Correa CMC, Noorman S, Jiang J, Palminteri S, Cohen MX, Lebreton M, et al.,
How the level of reward awareness changes the computational and
electrophysiological signature of reinforcement learning. The Journal of
Neuroscience, 2018. **38**(48): 10338-10348

26. Kramer MA and Eden UT, *Case studies in neural data analysis: A guide for the*
practicing neuroscientist. Computational Neuroscience, ed. T.J. Sejnowski and
T.A. Poggio. Vol. 11. 2016, the United States of America: Massachusetts
Institute of Technology.

27. Lebreton M, Bavard S, Daunizeau J, and Palminteri S, *Assessing inter-*
individual differences with task-related functional neuroimaging. Nature Human
Behaviour, 2019. **3**: 897-905

28. Crosse MJ, Liberto GM, Bednar A, and Lalor EC, *The Multivariate Temporal*
Response Function (mTRF) Toolbox: A MATLAB Toolbox for Relating Neural
Signals to Continuous Stimuli. frontiers in Human Neuroscience, 2016. **10**: 604-
617

29. Wyart V, Gardelle Vd, Scholl J, and Summerfield C, *Rhythmic Fluctuations in*
Evidence Accumulation during Decision Making in the Human Brain. Neuron,
2012. **76**: 847-858

30. Jia J, Liu L, Fang F, and Luo H, *Sequential sampling of visual objects during*
sustained attention. PLOS Biology, 2017. **15**(6): 1-19

31.   Liu L, Wang F, Zhou K, Ding N, and Luo H, *Perceptual integration rapidly*
870   *activates dorsal visual pathway to guide local processing in early visual areas.*
871   PLoS Biology, 2017. **15**(11): e2003646

872   32.   Huang Q, Jia J, Han Q, and Luo H, *Fast-backward replay of sequentially*

873   *memorized items in humans.* eLIFE, 2018. **7**: e35164.

874   33.   Snoek L, Miletić S, and Scholte HS, *How to control for confounds in decoding*
875   *analyses of neuroimaging data.* NeuroImage, 2019. **184**: 741-760

876   34.   Hsu M, Krajbich I, Zhao C, and Camerer CF, *Neural Response to Reward*
877   *Anticipation under Risk Is Nonlinear in Probabilities.* The Journal of
878   Neuroscience, 2009. **29**(7): 2231–2237

879   35.   Tobler PN, Christopoulos GI, O'Doherty JP, Dolan RJ, and Schultz W, *Neuronal*
880   *Distortions of Reward Probability without Choice.* The Journal of Neuroscience,
881   2008. **28**(45): 11703–11711

882   36.   Maloney LT and Zhang H, *Decision-theoretic models of visual perception and*
883   *action.* Vision Research, 2010. **50**(23): 2362-2374

884   37.   Fiorillo CD, Tobler PN, and Schultz W, *Discrete coding of reward probability*
885   *and uncertainty by dopamine neurons.* Science, 2003. **299**(5614): 1898-1902

886   38.   Tobler PN, O'Doherty JP, Dolan RJ, and Schultz W, *Reward value coding*
887   *distinct from risk attitude-related uncertainty coding in human reward systems.*
888   J Neurophysiol, 2007. **97**: 1621-1632

889   39.   Preuschoff K, 't Hart BM, and Einhäuser W, *Pupil dilation signals surprise:*
890   *evidence for noradrenaline's role in decision making.* frontiers in Neuroscience,
891   2011. **5**(115): 1-12

892   40.   van Lieshout LLF, Vandenbroucke ARE, Müller NCJ, Cools R, and de Lange
893   FP, *Induction and relief of curiosity elicit parietal and frontal activity.* The Journal
894   of Neuroscience, 2018. **38**(10): 2579-2588

895   41.   Pouget A, Drugowitsch J, and Kepecs A, *Confidence and certainty: distinct*
896   *probabilistic quantities for different goals.* Nature Neuroscience, 2016. **19**(3):
897   366-374

898   42.   Gherman S and Philiastides MG, *Neural representations of confidence emerge*
899   *from the process of decision formation during perceptual choices.* NeuroImage,
900   2015. **106**: 134-143

901   43.   Gherman S and Philiastides MG, *Human VMPFC encodes early signatures of*

902   *confidence in perceptual decisions.* eLIFE, 2018. **7**: e38293.

903   44.   Zizlsperger L, Sauvigny T, Händel B, and Haarmeier T, *Cortical representations*
904   *of confidence in a visual perceptual decision.* Nature Communications, 2014.
905   **5**: 3940

906   45.   Kiani R and Shadlen MN, *Representation of confidence associated with a*
907   *decision by neurons in the parietal cortex.* Science, 2009. **324**(8): 759-763

908   46.   Bahrami B, Olsen K, Latham PE, Roepstorff A, Rees G, and Frith CD, *Optimally*
909   *interacting minds.* Science, 2010. **329**: 1081-1085

47.   Koriat A, *Metacognition: decision-making processes in self-monitoring and self-*

regulation, in *The Wiley Blackwell handbook of judgment and decision making*,
G. Keren and G. Wu, Editors. 2015, Wiley Blackwell: Malden, MA. p. 356-379.

48.   Norcia AM, Appelbaum LG, Ales JM, Cottereau BR, and Rossion B, *The*
steady-state visual evoked potential in vision research: A review. Journal of
Vision, 2015. **15**(6): 1-46

49.   Farnsworth D, *The Farnsworth-Munsell 100 Hue and Dichotomous Test for*
Color Vision. Journal of the Optical Society if America, 1943. **33**(10): 568-578

50.   Brainard DH, *The psychophysics toolbox.* Spatial Vision, 1997. **10**: 433-436

51.   Pelli DG, *The VideoToolbox software for visual psychophysics: transforming*
numbers into movies. Spatial Vision, 1997. **10**(4): 437-442

52.   Aljuhani KH and Al turk LI, *Modification of the adaptive Nadaraya-Watson*
kernel regression estimator. Scientific Research and Essays, 2014. **9**(22): 966-
971

53.   Nadaraya EA, *On Estimating Regression.* Theory of Probability and its
Applications, 1964. **9**(1): 141-142

54.   Watson GS, *Smooth regression analysis.* Sankhyā: The Indian Journal of
Statistics, Series A, 1964. **26**(4): 359-372

55.   Taulu S and Kajola M, *Presentation of electromagnetic multichannel data: The*
signal space separation method. Journal of Applied Physics, 2005. **97**: 124905
1-10

56.   Taulu S and Simola J, *Spatiotemporal signal space separation method for*
rejecting nearby interference in MEG measurements. Physics in Medicine and
Biology, 2006. **51**: 1759-1768

57.   Oostenveld R, Fries P, Maris E, and Schoffelen J-M, *FieldTrip: open source*
software for advanced analysis of MEG, EEG and invasive electrophysiological
data. Computational Intelligence and Neuroscience, 2011. **2011**: 1-9

58.   Summerfield C and Mangels JA, *Coherent theta-band EEG activity predicts*
item-context binding during encoding. NeuroImage, 2004. **24**: 692-703

59.   Gonçalves NR, Whelan R, Foxe JJ, and Lalor EC, *Towards obtaining*
spatiotemporally precise responses to continuous sensory stimuli in humans:
A general linear modeling approach to EEG. NeuroImage, 2014. **97**: 196-205

60.   Lalor EC, Pearlmutter BA, Reilly RB, McDarby G, and Foxe JJ, *The VESPA: A*
method for the rapid estimation of a visual evoked potential. NeuroImage, 2006.
32: 1549-1561

61.   Arlot S and Celisse A, *A survey of cross-validation procedures for model*

selection. Statistics Surveys, 2010. **4**: 40-79. doi: 10.1214/09–SS054.

62.   Maris E and Oostenveld R, *Nonparametric statistical testing of EEG- and MEG-*
data. Journal of Neuroscience Methods, 2007. **164**: 177-190

63.   Marti S, King J-R, and Dehaene S, *Time-resolved decoding of two processing*
chains during dual-task interference. Neuron, 2015. **88**: 1297-1307

64.   Benjamini Y and Hochberg Y, *Controlling the false discovery rate: a practical*
and powerful approach to multiple testing. Journal of the Royal Statistical
Society, 1995. **57**(1): 289-300

65. Benjamini Y and Yekutieli D, *The control of the false discovery rate in multiple*
testing under dependency. The Annals of Statistics, 2001. **29**(4): 1165-1188
956

Supporting Information

S1 Text. Bounded Log-Odds (BLO) model.

S2 Text. Factorial model comparison.

S3 Text. Autocorrelation analysis for periodic and aperiodic stimulus sequences.

S4 Text. Phase coherence and time-resolved decoding analyses for confounding factors.

S5 Text. Explaining the "bumps" in the phase coherence spectra of the confounding factors.

S6 Text. Explaining the higher phase coherence and decoding performance for *p* or *p*(1-*p*) in the *N*-large condition than in the *N*-small condition.

S7 Text. Time-resolved decoding analyses based on cross-validated version of confound regression (CVCR).

S1 Fig. Individual subjects' $\pi(p) - p$ as a function of *p*.
The deviation of the subjective from objective relative-frequency, $\pi(p) - p$, is plotted as a function of *p*, separately for the *N*-small (left panel) and *N*-large (right panel) conditions of each subject. Black curves denote smoothed data. Red and blue curves respectively denote BLO and LLO model fits.

S2 Fig. Results of model recovery analysis.
Model parameters had been estimated for individual subjects and the 22 subjects' fitted models were used to generate synthetic datasets of 22 virtual subjects. We generated 50 synthetic datasets for each of the 18 models considered in our factorial model comparison analysis. **(A) Model identifiability analysis.** We fit all the 18 models to each synthetic dataset and identified the best fitting model. The heatmaps represent confusion matrix that quantifies how likely a specific model was correctly identified as the best fitting model for the datasets generated by itself and how likely mistakenly as the best model for the datasets generated by the other models. Each column is for one specific model that was used to generate the datasets. Each row is for one model that was fit to the datasets generated by 18 models. **Top:** Summed ΔAICc was used to identify the best model for each dataset. The color of each cell codes the proportion

that the model on its row was identified as the best model for the 50 datasets generated

by the model on its column. Synthetic datasets that were generated by BLO were all

best fit by BLO (see the leftmost column). Out of the 850 datasets generated from the

other 17 models, only 0.24% were mis-identified to BLO (see the bottom row). **Bottom**:

The group-level Bayesian model selection was used to quantify the probability for each

specific model to be the best model for the dataset. The color of each cell codes the

mean protected exceedance probability of the model on its row had for the 50 datasets

generated by the model on its column. Higher value is coded as more reddish and

lower value as more bluish. Values in each column add up to 1. From left (bottom) to

right (top), the 18 models are 111, 112, 113, 121, 122, 123, 211, 212, 213, 221, 222,

223, 311, 312, 313, 321, 322, 323, where the first digit indexes the D1 assumption (1

for log-odds, 2 for Prelec, and 3 for linear), the second digit indexes the D2 assumption

(1 for bounded and 2 for bounds-free), and the third digit indexes the D3 assumption

(1 for $V(\hat{p})$ with $n_s = b + N^a$, 2 for $V(\hat{p})$ with constant n_s, and 3 for constant $V(\hat{p})$).

The BLO model with sample size $n_s = b + N^a$ is the first model (111), corresponding

to the leftmost column and the bottom row, which is indicated by an arrow in the plot.

We can see the synthetic data that were generated by BLO were all best by BLO (see

leftmost column) and those generated by the other models were seldom best fit by

BLO (see bottom row). **(B) Parameter recovery analysis for BLO.** For the

50×22=1100 virtual subjects generated by the BLO model with $n_s = b + N^a$, the

recovered parameters of BLO are plotted against the estimated parameters that were

used to generate synthetic data. Each panel is for one parameter. Each dot is for one

virtual subject. The parameters η, α and b that had positively skewed distributions

were transformed into log scale for better visualization. A small proportion of extreme

values (1.55%, 1.55% and 0.19%, respectively for η, α and b) are outside the display

range. The value of r_s on each panel indicates Spearman's correlation coefficient

between the estimated and recovered parameters.

1021

1022   **S3 Fig. Estimated parameters for the BLO model.**

1023   In the box plot, the middle line denotes the median estimate across subjects, the

1024   bottom and top lines respectively denote the lower and upper quartiles, and the error

1025   bars denote the 99% confidence interval. Dots denote estimates for individual subjects.

1026   The parameters η, a and b were transformed into log scale for better visualization.

1027

1028   **S4 Fig**. **Autocorrelations of stimulus sequences as functions of time lags.**

1029   Left: the *P*-cycle condition. Right: the *U*-cycle condition. Solid and dashed lines are

1030   respectively for the *p* and *p*(1-*p*) sequences. The stimulus sequences used for

1031   autocorrelation calculations were from the representative subject whose behavior

1032   results are showed in Fig 2A. All other subjects had similar autocorrelation patterns.

S5 Fig. **Results of control analysis for the confounding variables.**
(A) Correlation analysis. Top row: Pearson's correlations between the *p* sequence and the eight confounding variables (N, N_t, N_o, *AvgLumi*, *vCIE-L**, *vCIE-a**, *vCIE-b** and *M-contrast*) separately for the four cycle and numerosity conditions. Bottom row: Pearson's correlations between the $p(1-p)$ sequence and the eight confounding variables for each condition. The results confirmed our design that all of the confounding variables had negligible or moderate correlations with *p* and $p(1-p)$. **(B) Phase coherence analysis.** Grand-averaged phase coherence spectrum between the sequences of the eight confounding variables and neural responses from magnetometers. Here we have reproduced the results of the phase coherence analysis for *p* and $p(1-p)$ (inside the black frame) to facilitate a comparison between the main analysis and the control analysis. The observed phase coherence spectra of the confounding variables had different patterns than those of *p* or $p(1-p)$. The vertical line marks 3.33 Hz. See S5 Text and S6 Fig for the possible cause of the "bumps" between 0 and 6.67 Hz. **(C) Time-resolved decoding analysis.** The same time-resolved decoding procedures as Fig 5 were applied to the eight confounding variables. Here we have reproduced the results of the time-resolved decoding analysis for *p* and $p(1-p)$ (inside the black frame) to facilitate a comparison between the main analysis and the control analysis. The time-resolved decoding performance of the confounding variables had different patterns than those of *p* or $p(1-p)$. For **(A)**–**(C)**, light and dark green respectively code the *N*-small and *N*-large conditions. For **(B)** and **(C)**, solid and dashed lines respectively denote the *P*-cycle and *U*-cycle conditions. Shadings denote SEM across subjects.

S6 Fig. **Explaining the "bumps" in the phase coherence of numerosity.**
Simulated neural signals were generated through convolution of TRF estimated from the MEG2521 sensor (located right occipital) with the *N* sequence, perturbed by Gaussian nose whose standard deviation was set to 4. The simulated neural signals were then submitted to the phase coherence analysis (see Materials and Methods). Light and dark green curves denote the phase coherence across magnetometers of real data from one example subject. Orange curves denote the average across 500 simulations. The "bump" across 0–6.67 Hz observed in real data was reproduced in the simulated data.

S7 Fig. **Spatial decoding topography for the other three statistically significant time windows in time-resolved decoding analysis.** Black dots mark the sensor locations with above-chance decoding performance ($P_{FDR} < 0.05$).

S8 Fig. Individual subjects' time-resolved decoding performance for *p* (left column) and *p*(1–*p*) (right column), separately for the *N*-small (top row) and *N*-large (bottom row) conditions.

Each row on the heatmap is for one subject. Higher level of decoding performance is coded as more reddish and lower level as more bluish. The green curve superimposed on the heatmap denotes grand-averaged decoding performance across subjects (see the right y-axis). Symbols on the top of each panel indicate time lags that had above-chance decoding performance (cluster-based permutation tests), with vertical bars representing $P_{cluster}$<0.01 and dots representing 0.01≤$P_{cluster}$<0.05.

S9 Fig. Time-resolved decoding analysis based on cross-validated version of confound regression (CVCR).

(A) Decoding performance for *p*(1–*p*). **(B)** Decoding performance for $V(\hat{p})$. The $V(\hat{p})$ was computed according to each subject's fitted BLO model (with sample size $n_s = b + N^a$). Curves denote grand-averaged decoding performance over different time lags, separately for the *N*-small (light green) and *N*-large (dark green) conditions. Shadings denote SEM across subjects. Vertical bars above the curves indicate time lags that had above-chance decoding performance (cluster-based permutation tests, $P_{cluster}$<0.01). The eight confounding variables we considered in S4 Text (*N*, N_t, N_o, *AvgLumi*, *vCIE-L**, *vCIE-a**, *vCIE-b** and *M-contrast*) were regressed out from MEG time series before decoding analysis. See S7 Text for methodological details. The decoded time course from CVCR for *p*(1–*p*) was similar to that of the standard time-resolved decoding analysis (Fig 5, right panel). The decoded time course was also similar for $V(\hat{p})$.

S10 Fig. Consequences of random sampling errors.

The *p* or *p*(1–*p*) estimated from a sample of dots from a display might deviate from the true value of *p* or *p*(1–*p*) in the display. As an evaluation of the fidelity of the sampled value, we used numerical simulations to compute the correlation (Pearson's *r*) between the true value and the sampled value, based on the BLO parameters estimated from individual subjects. Triangles and circles respectively denote *p* and *p*(1–*p*). The truth-sample correlation was higher in the *N*-large condition than in the *N*-small condition.