Automatic and fast encoding of representational uncertainty underlies probability distortion

Xiangjuan Ren[1,2]   Huan Luo[3,4]*   Hang Zhang[2,3,4]*

1. Academy for Advanced Interdisciplinary Studies, Peking University, Beijing, China

2. Peking-Tsinghua Center for Life Sciences, Peking University, Beijing, China

3. School of Psychological and Cognitive Sciences and Beijing Key Laboratory of

 Behavior and Mental Health, Peking University, Beijing, China

4. PKU-IDG/McGovern Institute for Brain Research, Peking University, Beijing, China

*Corresponding authors:

Huan Luo, email: huan.luo@pku.edu.cn

Hang Zhang, email: hang.zhang@pku.edu.cn

Keywords: judgment; decision making; probability distortion; MEG; steady-state

response (SSR); time-resolved decoding

Short title: Encoding of representational uncertainty

Abstract

Humans do not have an accurate representation of the probability information in the environment but distort it in a surprisingly stereotyped way ("probability distortion"), as shown in a wide range of judgment and decision-making tasks. Many theories hypothesize that humans automatically compensate for the uncertainty inherent in probability information ("representational uncertainty") and probability distortion is a consequence of uncertainty compensation. Here we tested whether the representational uncertainty of probability is really quantified by the human brain and how its encoding contributes to probability distortion. Human subjects kept tracking the relative frequency of one color of dots in a sequence of dot arrays while their brain activity was recorded by magnetoencephalography (MEG). We found converging evidence from neural entrainment and time-resolved decoding that a mathematically-derived measure of representational uncertainty is automatically computed in the brain, despite it is not explicitly required by the task. In particular, the encodings of relative frequency and its representational uncertainty respectively occur approximately 300 ms and 400 ms after stimulus onset. Moreover, the relative strength of the brain responses to these two quantities predicts the subject's probability distortion behavior. The automatic and fast encoding of the representational uncertainty provides neural basis for the uncertainty compensation hypothesis of probability distortion. More generally, the representational uncertainty is closely related to confidence and our findings thus exemplify how confidence may emerge even earlier than and influence the final judgment.

Introduction

Humans do not have an accurate representation of the probability or

relative-frequency information in the environment but distort it in a surprisingly

stereotyped way. Typically, small probability is overestimated and large probability

underestimated, which can be well fit by a linear-in-log-odds (LLO) model with two

parameters (Zhang & Maloney, 2012). Such "probability distortion" phenomena occur

in a variety of judgment and decision-making tasks such as relative-frequency

estimation (Attneave, 1953; Lichtenstein, Slovic, Fischhoff, Layman, & Combs, 1978;

Varey, Mellers, & Birnbaum, 1990), confidence rating (Erev, Wallsten, & Budescu,

1994; Gigerenzer, Hoffrage, & Kleinbölting, 1991; Wallsten, Budescu, Erev, &

Diederich, 1997), decision under risk (Gonzalez & Wu, 1999; Luce, 2000; Tversky &

Kahneman, 1992; Zhang, Ren, & Maloney, 2019), and are also widely reported in

animal behaviors (Ferrari-Toniolo, Bujold, & Schultz, 2019; Stauffer, Lak, Bossaerts,

& Schultz, 2015; Yang & Shadlen, 2007). However, the neural computations that

cause such probability distortions remain largely unknown.

One computation that is assumed to be central to probability distortion (Fennell &

Baddeley, 2012; Martins, 2006; See & Fox, 2006; Zhang et al., 2019) is compensation

for the uncertainty inherent in the representation of noisy probability information

("representational uncertainty"). In particular, comparison among an extensive set of

computational models of probability distortions (Zhang et al., 2019) suggests that the

representational uncertainty in the form of $p(1–p)$ is compensated in human behaviors,

where p denotes the probability or relative frequency to be represented. That is,

representational uncertainty is zero at $p = 0$ or 1 and maximal at $p = 0.5$. The $p(1–p)$

form had been reached by Lebreton et al. (2015) as a measure of uncertainty that

correlates with the explicitly reported confidence for a specific judged value. As shown

in their functional MRI experiments, during the valuation process, this uncertainty

measure is automatically encoded in the ventromedial prefrontal cortex

(vmPFC)—the brain region known for encoding value—even in the absence of explicit

confidence rating. We thus hypothesize that the neural encoding of $p(1–p)$ is essential

to the emergence of probability distortion. Here we ask whether such representational

uncertainty of probability information is automatically encoded in the brain and

whether this encoding is fast enough to precede the explicit judgment of probability

and to influence probability distortion, as theories of probability distortion would

expect (Fennell & Baddeley, 2012; Martins, 2006; See & Fox, 2006; Zhang et al.,

2019).

In the present study, we designed a novel experimental paradigm where the

representational uncertainty of probability information (i.e. $p(1–p)$) was varied

continuously over time. By using time-resolved neural measurements and assessing

the temporal coupling between stimulus variables and ongoing brain activities, we

examined how the encoding of representational uncertainty proceeds in the brain and

drives probability distortion. In particular, 22 human subjects were instructed to track

the relative-frequency (p) of one color of dots in a sequence of dot arrays (Figure 1A),

during which their brain activities were recorded by magnetoencephalography (MEG).

We first found that, though p was the only variable subjects needed to track and

$p(1–p)$ was task-irrelevant, the periodic changes of $p(1–p)$ as well as p entrained

neural rhythms, supporting an automatic encoding of representational uncertainty in

the brain. By using a time-resolved decoding analysis to delineate the temporal

course, we further found that the encoding of p and $p(1–p)$ peaked respectively

around 300 and 400 ms. Finally, the relative strength of the neural responses to the

two variables (p and $p(1–p)$) in the parietal region could predict the variation of

probability distortion behavior across individuals. Our results thus provide neural

evidence for an automatic, fast encoding of representational uncertainty in the brain

and indicate how this encoding may influence the probability distortion observed in a

wide range of human behaviors.

Results

As shown in Figure 1A, on each trial, subjects saw a sequence of displays consisting

of isoluminant yellow and cyan dots, refreshed every 150 ms, and were instructed to

track the relative-frequency of dots in one color (i.e. yellow or cyan). To ensure

persistent tracking throughout the trial, the sequence of displays might end after some

random duration and subjects needed to report the relative-frequency of the last

display by clicking on a percentage scale.

Figure 1. Experimental design and behavioral results. (A) Relative-frequency tracking
and judgment task. On each trial, a sequence of yellow and cyan dot arrays was
presented at a rate of 150 ms per display. Subjects were asked to fixate on the central
fixation cross and track the relative frequency of yellow (or cyan) dots in each display until
a 0–100% response scale appeared. Subjects then clicked on the scale to report the
relative frequency in the last display. **(B)** The p and $p(1–p)$ sequences in an example
P-cycle or *U*-cycle trial. The value of p of each display was categorized into the smaller
(<0.5) and the larger (>0.5), coded by different colors. Similarly, the smaller (<0.21) and
the larger (>0.21) $p(1–p)$ were coded by different colors. In *P*-cycles (left panels), the p
sequence alternated between smaller and larger values, resulting in a frequency
spectrum peaking at 3.33 Hz (solid line), while the $p(1–p)$ sequence was aperiodic
(dashed line). In *U*-cycles (right panels), it was the reverse: the $p(1–p)$ sequence
alternated between smaller and larger values in cycles of 3.33 Hz (dashed line), while the
p sequence was aperiodic (solid line). **(C)** Distortion of relative frequency observed in one
subject. The subject's reported relative-frequency $\pi(p)$ is plotted against the objective

relative frequency p, both in the log-odds scale ($\lambda[p] = \log\frac{p}{1-p}$), separately for the
N-small (light green) and *N*-large (dark green) conditions. Each dot denotes one trial.
Lines denote linear fits (i.e. LLO model fits). **(D)** Estimated slope of distortion $\hat{\gamma}$ for
different dot numerosity conditions. Each gray line is for one subject. The thick green line
denotes the group mean, with error bars for SEM. The mean $\hat{\gamma}$ across the 22 subjects
increased by 25.75% from the *N*-small to *N*-large condition. **(E)** Response time as an
additional index for representational uncertainty. The mean response time (RT) for
subjects to initiate their relative-frequency report (i.e. the interval between the response
screen onset and the first mouse move) was plotted against binned p (left panel) or
binned $p(1–p)$ (right panel), separately for the *N*-small and *N*-large conditions. Error bars
denote SEM. Consistent with our assumption that representational uncertainty is
proportional to $p(1–p)$, the RT was an inverted *U*-shaped function of p and increased
almost linearly with $p(1–p)$.

On each trial, the value of either p or $p(1–p)$ was varied periodically at 3.33 Hz

while the value of the other variable (i.e. $p(1–p)$ or p) was controlled to be aperiodic

(see Methods). The resulting two types of trials were referred as *P*-cycle and *U*-cycle

(*U* for uncertainty) trials respectively (Figure 1B). In other words, in *P-cycle* trials, the

p value underwent a rhythmic fluctuation and the *p(1–p)* value followed an aperiodic

random course, whereas the opposite pattern occurred for *U*-cycle trials. Note that

subjects' task was always to attend to the relative frequency (the *p* value*)*, while the

representational uncertainty of *p* (the *p(1-p)* value) was task-irrelevant. The values of

p and *p(1-p)* were statistically independent of each other.

To dissociate the processing of the relative frequency and the total number of

dots in a display (numerosity, denoted *N*), the numerosity was not constant but varied

from display to display independently of *p* or *p(1–p)*, ranging from 10 to 90 (*N*-small

trials) or from 100 to 900 (*N*-large trials). The introduction of *N*-small trials and *N*-large

trials served as a means to manipulate the slope of probability distortion (Zhang &

Maloney, 2012) so as to reveal the possible links between behavior and brain activity.

Behavioral and modeling results

All the 22 subjects performed well on reporting the relative-frequency of the last

display, whose subjective estimate $\pi(p)$ was highly correlated with the objective

relative-frequency *p* (all Pearson's *r* > 0.71, *P* < 0.001), suggesting that subjects had

successfully tracked the change of *p* throughout the trial. As expected, most subjects

showed the typical inverted-*S*-shaped "probability distortion", overestimating small *p*

and underestimating large *p* (see Figure 1C for an example subject), a profile

consistent with previous findings (Varey et al., 1990; Zhang & Maloney, 2012). We

next quantified each subject's probability distortion using the two parameters

estimated from the LLO model (see Methods): slope $\hat{\gamma}$ and crossover point $\hat{p}_0$,

separately for each cycle (*P*-cycle or *U*-cycle) and dot numerosity (*N*-small or *N*-large)

condition. According to 2 (*P*-cycle, *U*-cycle) by 2 (*N*-small, *N*-large)

repeated-measures ANOVAs separately performed for the estimated $\hat{\gamma}$ and $\hat{p}_0$,

numerosity showed a significant influence on $\hat{\gamma}$ ($F(1, 63) = 57.82$, $P < 0.001$, $\eta_p^2 =$

0.48), with the $\hat{\gamma}$ estimated from *N*-large trials greater than that of *N*-small trials by

25.75% (Figure 1D), and a statistically significant but small influence on $\hat{p}_0$ ($F(1,$

63)=4.24, $P = 0.044$, $\eta_p^2 =0.06$). No other main effects or interactions reached

significance (all $P > 0.26$).

We found that the observed difference in $\hat{\gamma}$ between the *N*-small and *N*-large

conditions could be well captured by the bounded log-odds model (Zhang et al., 2019)

that assumes compensation for the $p(1-p)$ form of representational uncertainty (see

Supplement S1 and Figure S1), with a greater $\hat{\gamma}$ implying lower representational

uncertainty. That is, the *N*-large condition was associated with lower uncertainty than

the *N*-small condition.

The response time (RT) of reporting relative frequency (defined as the interval

between the response screen onset and the first mouse move) provides an additional

index for representational uncertainty, given that lower uncertainty would lead to

shorter RTs. We divided the values of *p* into five bins and computed RT for each bin

and separately for the *N*-small and *N*-large trials. According to a 5 (*p* bins) by 2

(*N*-small vs. *N*-large) repeated-measures ANOVA on RTs, both the main effects of the

p value ($F(4, 189) = 29.02$, $P < 0.001$, $\eta_p^2 = 0.38$) and numerosity ($F(1, 189) = 25.61$,

$P < 0.001$, $\eta_p^2 = 0.12$) were significant. Consistent with Lebreton et al. (2015), RTs

were longest at $p=0.5$ and shortest when p was close to 0 or 1 (Figure 1E, left). More

precisely, RTs increased almost linearly with $p(1–p)$ (Figure 1E, right), in agreement

with what one would expect if representational uncertainty is proportional to $p(1–p)$.

Besides, RTs were shorter in N-large trials than in N-small trials, which is in accord

with the two conditions' difference in $\hat{\gamma}$ and provides further evidence that the

N-large condition was accompanied by lower representational uncertainty.

191
192

Neural entrainment to periodic changes of p or $p(1–p)$

We next examined whether the brain response could track the periodically changing p

values (P-cycle condition) or $p(1–p)$ values (U-cycle condition) in the stimulus

sequence. Recall that the P-cycle and U-cycle trials had identical individual displays

and differed only in the ordering of the displays: In P-cycle trials, p alternated between

small and large values in cycles of 3.33 Hz while $p(1–p)$ was aperiodic; in U-cycle

trials, $p(1–p)$ alternated in cycles of 3.33 Hz while p was aperiodic.

As summarized in Figure 2, the brain response indeed tracked the periodic

changes of p and $p(1–p)$. In particular, in P-cycle trials (Figure 2, left), the phase

coherence between the periodic p values and the MEG time series reached

significance at 3.33 Hz (permutation test, FDR corrected $P_{FDR} < 0.05$), mainly for the

occipital and parietal sensors. Surprisingly, significant phase coherence was also

found at 3.33 Hz in U-cycle trials between the periodic $p(1–p)$ values and the MEG

time series (Figure 2, right). That is, the brain activity was also entrained to the

periodic changes of the representational uncertainty of *p* (i.e. *p(1–p))*. Given that

subjects were only asked to track the value of *p* but not *p(1–p)*, the observed neural

entrainment to the task-irrelevant *p(1–p)* suggests an automatic encoding of

representational uncertainty in the brain.

Figure 2. Results of phase coherence analysis. Grand-averaged phase coherence

spectrum for magnetometers. Left: The phase coherence (κ) between the periodic *p*

values and MEG time series in *P*-cycle trials. Right: The phase coherence between the

periodic *p(1–p)* values and MEG time series in *U*-cycle trials. Light and dark green curves

respectively denote the *N*-small and *N*-large conditions. Shadings denote SEM across

subjects. The vertical line marks 3.33 Hz. Dots above the spectrum mark the frequency

bins whose phase coherence was significantly above chance level (permutation tests,

P_{FDR} <0.05 with *FDR* correction across frequency bins). **Insets:** Grand-averaged phase

coherence topography at 3.33 Hz for each cycle and numerosity condition. Solid black

dots denote sensors whose phase coherence at 3.33 Hz was significantly above chance

level (permutation tests, P_{FDR}<0.05 with *FDR* corrected across magnetometers).

Notably, the significant phase coherences between the periodic *p* or *p(1–p)*

values and MEG time series were not simply because the MEG time series consisted

of 3.33 Hz frequency components. In a control analysis, we calculated the phase

coherence between the aperiodic variable (i.e. *p* in *U*-cycle trials or *p(1–p)* in *P*-cycle

trials) and the same MEG time series, for which there were no significant peaks at

3.33 Hz (Figure S5). Moreover, we had carefully controlled potential confounding

variables in our experimental design. For example, *p* and *p(1–p)* were linearly

independent of each other, both of which had negligible correlations with numerosity

or low-level visual features such as luminance, contrast, and color variance (Figure

S3A). We further confirmed that none of these variables led to different responses in

P-cycles and *U*-cycles as reported above for *p* and *p(1–p)* (Figure S3B).

Behavioral probability distortion and the neural entrainment to *p* and *p(1–p)*

We next examined the relationship between behavioral probability distortion and the

neural entrainment to *p* and *p(1–p)* on a subject-by-subject basis. Specifically, the

phase coherence between a specific variable (*p* or *p(1–p)*) and the MEG time series

can be considered as a measure of the strength of neural responses to the variable

(Kramer & Eden, 2016). We defined

$$\beta = \frac{\kappa_p}{\kappa_{p(1-p)}}$$ (1)

to quantify the relative strength of *p* to *p(1–p)* in neural responses, where κ_p

denotes the phase coherence for *p* in *P*-cycle trials, and $\kappa_{p(1-p)}$ denotes the phase

coherence for *p(1-p)* in *U*-cycle trials. A higher value of β would imply a stronger

neural encoding of relative-frequency or a weaker encoding of representational

uncertainty and is thus supposed to yield probability distortions of a greater slope

(Zhang et al., 2019).

Given that the estimated slope of distortion $\hat{\gamma}$ was greater in *N*-large trials than

in *N*-small trials, we would expect β to change in the same direction across the

numerosity conditions. That is, suppose we define $\Delta\hat{\gamma} = \ln\left(\dfrac{\hat{\gamma}_{N\text{-large}}}{\hat{\gamma}_{N\text{-small}}}\right)$ and

$\Delta\beta = \ln\left(\dfrac{\beta_{N\text{-large}}}{\beta_{N\text{-small}}}\right)$, there should be a positive correlation between $\Delta\hat{\gamma}$ and $\Delta\beta$. As

shown in Figure 3, there was indeed a significant correlation between behavioral and

neural measures across subjects in the parietal region (Pearson's *r* = 0.67,

FDR-corrected one-tailed P_{FDR} = 0.033), associating the neural entrainment to *p* and

p(1–p) with subsequent probability distortion behaviors.

Figure 3. Neural responses to *p* and *p(1–p)* predict the slope of probability

distortion. We defined $\Delta\hat{\gamma} = \ln\left(\dfrac{\hat{\gamma}_{N\text{-large}}}{\hat{\gamma}_{N\text{-small}}}\right)$ and $\Delta\beta = \ln\left(\dfrac{\beta_{N\text{-large}}}{\beta_{N\text{-small}}}\right)$ to respectively quantify

how much the behavioral measure of the slope of distortion, $\hat{\gamma}$, and the relative strength

of *p* to *p(1–p)* in neural responses, β, changed across the two numerosity conditions.

Main plot: Correlation between $\Delta\hat{\gamma}$ and the $\Delta\beta$ at the parietal magnetometer channel

MEG0421, Pearson's *r* = 0.67, P_{FDR} = 0.033. Each dot denotes one subject. **Inset**:

Correlation coefficient topography between $\Delta\hat{\gamma}$ and $\Delta\beta$, on which MEG0421 is marked

by a solid black dot.

Neural encoding of *p* and *p(1–p)* over time and the associated brain regions

Our experiment was designed such that on each trial one of the two variables of our

interest (*p* or *p(1–p)*) changed periodically and the other was aperiodic. The encoding

of a periodic variable led to periodic brain responses that were specifically

phase-locked to the variable, as revealed by the phase coherence analysis above.

However, it remained unknown how the aperiodic *p(1–p)* in *P*-cycles or aperiodic *p* in

U-cycles was encoded over time.

To address this issue, we performed a time-resolved decoding analysis based on

all 306 sensors (see Methods) using a regression approach that has been employed

in a variety of EEG and MEG studies (Crosse, Liberto, Bednar, & Lalor, 2016; Wyart,

Gardelle, Scholl, & Summerfield, 2012) including our previous studies (Huang, Jia,

Han, & Luo, 2018; Jia, Liu, Fang, & Luo, 2017; Liu, Wang, Zhou, Ding, & Luo, 2017).

The intuition of the time-resolved decoding analysis is as follows. Suppose the onset

of each new *p* or *p(1–p)* value in the stimulus sequence evokes phase-locked brain

responses that extend across time and whose magnitudes are proportional to the

encoded value. The resulting MEG time series is a superposition of the responses to

all the preceding stimuli in the sequence. But as soon as the values of an encoded

variable are not correlated over time (i.e. free of autocorrelation), their brain response

profiles are separable. In particular, for any stimulus in the sequence, we can use the

MEG signals at a specific delay after the stimulus onset to predict the value of the

stimulus. Importantly, different from the phase coherence analysis (Figure 2) that only

reflects the overall strength of the brain responses, this time-resolved decoding

analysis allows us to assess how p and $p(1–p)$ were encoded over time.

Figure 4 plots the temporal course of the decoding performance for p (left) and

$p(1–p)$ (right). Both p and $p(1–p)$ were successfully decoded from the MEG signals in

N-large trials (cluster-based permutation test, $P_{cluster} < 0.05$). In particular, the

decoding performance for p peaked around 327 ms after stimulus onset (Figure 4,

left), while that for $p(1–p)$ peaked around 419 ms (Figure 4, right). In other words, the

neural encodings of relative frequency and its representational uncertainty had

distinct time courses, with the latter occurring approximately 100 ms later than the

former. None of the potential confounding variables (numerosity, luminance, etc.)

showed temporal courses similar to p or $p(1-p)$ when the same time-resolved

decoding procedure was applied (Figure S3C).

Based on the time windows that achieved the highest time-resolved decoding

performance, we further performed a similar decoding analysis at each sensor

location (including one magnetometer and two orthogonal planar gradiometers)

separately for p and $p(1–p)$ to assess the associated brain regions (see Methods). We

found that the encoding of the two variables involved overlapping parietal-occipital

regions (Figure 4, see Figure S6 for the results of the other above-chance time

 windows), including the parietal region where $\Delta\beta$ and $\Delta\hat{\gamma}$ were positively

311   correlated (Figure 3).

Figure 4. Results of decoding analyses. Main plots: Time-resolved decoding performance over different time lags for *p* (left panel) and *p(1–p)* (right panel), separately for the *N*-small (light green) and *N*-large (dark green) conditions. Shadings denote SEM across subjects. Dots and xs above the curves indicate time lags that had above-chance decoding performance (cluster-based permutation tests; dot: $P_{cluster}$<0.01, x: 0.01≤$P_{cluster}$<0.05). The decoding performance for *p* peaked at around 327 ms after stimulus onset, while that for *p(1–p)* peaked at around 419 ms. **Insets**: Topography of spatial decoding performance for the time window (highlighted by the funnel-shaped dashed lines) that contained the peak decoding performance in the time-resolved decoding analysis. Solid black dots indicate the sensor locations with above-chance decoding performance (P_{FDR} < 0.05). The encodings of *p* and *p(1–p)* involved overlapping parietal-occipital regions, including the parietal region where $\Delta\beta$ and $\Delta\hat{\gamma}$ were positively correlated (Figure 3).

Discussion

We used MEG to investigate probability distortions in a relative-frequency estimation task and found that the human brain encodes not only the task-relevant relative frequency but also its task-irrelevant representational uncertainty. The neural encoding of the representational uncertainty occurs as early as approximately 400 ms and influences the probability distortion in the subsequent behavioral judgment. These results suggest that the human brain automatically and quickly quantifies the uncertainty inherent in probability information. As we discuss below, our findings provide neural basis for the theoretical hypothesis that probability distortion is a consequence of uncertainty compensation and, more generally, shed light on the functional role of confidence (estimate of uncertainty) during the process of judgment and decision making.

Neural computations underlying probability distortions

Humans show highly similar probability distortions in tasks involving probability or relative frequency, with the subjective probability typically an inverted-*S*-shaped function of the objective probability (Zhang & Maloney, 2012). Why do people distort probability information in such a systematic way? Though inverted-*S*-shaped distortions of probability had been found in the activity of a few brain regions (Hsu, Krajbich, Zhao, & Camerer, 2009; Tobler, Christopoulos, O'Doherty, Dolan, & Schultz, 2008), the neural computations involved in transforming objective probabilities to subjective probabilities were largely unknown.

Several theories (Fennell & Baddeley, 2012; Martins, 2006; See & Fox, 2006;

Zhang et al., 2019) rationalize probability distortion as a consequence of

compensating for representational uncertainty that is in accordance with the

framework of Bayesian Decision Theory (Maloney & Zhang, 2010). In brief, the brain

will discount an internal representation of probability according to the level of

uncertainty so that it can achieve a more reliable estimate of the objective probability.

The higher the uncertainty associated with a representation, to a greater extent the

representation is discounted. By modeling human subjects' probability distortion

behaviors in two representative tasks—relative-frequency estimation and decision

under risk—Zhang et al. (2019) found evidence that the representational uncertainty

of probability or relative frequency p is proportional to $p(1-p)$.

What we found in the present study is neural evidence for the encoding of $p(1-p)$

during the evaluation of p. For the first time, we have shown that representational

uncertainty $p(1-p)$ is not just virtual quantities assumed in the computational models

of probability distortions but is really computed in the brain.

Representational uncertainty and confidence

The representational uncertainty that concerns us lies in the internal representation of

probability or relative-frequency. One concept that may occasionally coincide with

such epistemological uncertainty but is entirely different is outcome uncertainty, which

is widely studied in the literature of decision under risk (Fiorillo, Tobler, & Schultz,

2003; Tobler, O'Doherty, Dolan, & Schultz, 2007), prediction error (Fiorillo et al., 2003)

and surprise (Preuschoff, 't Hart, & Einhäuser, 2011; van Lieshout, Vandenbroucke,

Müller, Cools, & de Lange, 2018). For example, for a gamble with probability p to

receive x_1 and probability $1–p$ to receive x_2, the variance of the outcomes is

proportional to $p(1–p)$. In the present study, the relative-frequency estimation task we

chose to investigate has nothing to do with uncertain outcomes and thus avoids the

possible confusion of outcome uncertainty with representational uncertainty.

Representational uncertainty is closely related to confidence, except that it is not

necessarily bound to any specific judgment or decision (Pouget, Drugowitsch, &

Kepecs, 2016). Specifically, the encoding of representational uncertainty may be

understood as a special case of the "second-order valuation" proposed by Lebreton et

al. (2015). As described earlier, Lebreton et al. (2015) found a principled relationship

between an overt numerical judgment and the individual's confidence about the

judgment, with the latter being a quadratic function of the former. They showed in

fMRI studies that such quadratic form—as a proxy to confidence—is automatically

encoded in vmPFC, even when confidence rating is not explicitly required of. Using

the same quadratic form as the proxy, here we found automatic encoding of the

representational uncertainty of relative frequency during the tracking of a visual

sequence. Our findings go beyond previous work and contribute to the confidence

literature in the following three aspects.

First, we found that the encoding of representational uncertainty is even more

automatic than the automatic encoding of confidence considered by Lebreton et al.

(2015). In our experiment, subjects were asked to track the relative frequency in the

stimulus sequence but made no overt judgment except for the last display. Moreover,

displays were refreshed every 150 ms, apparently leaving no time for deliberation.

Second, we resolved the temporal course of the encoding of representational

uncertainty, which would be inaccessible under the low temporal resolution of fMRI. In

particular, representational uncertainty is encoded as early as 400 ms upon stimulus

onset, approximately 100 ms after the encoding of relative frequency itself. The

occipital-parietal region is involved in the processing of both relative-frequency and its

representational uncertainty but during different time windows. The fast encoding of

representational uncertainty we found echoes recent psychophysiological findings in

humans (Gherman & Philiastides, 2015, 2018; Zizlsperger, Sauvigny, Händel, &

Haarmeier, 2014) and non-human primates (Kiani & Shadlen, 2009) that the

confidence encoding for perceptual judgments can be detected in the brain far before

confidence rating and even prior to the overt judgment or decision making.

Third, our findings shed light on the functional importance of confidence encoding

in information processing (Bahrami et al., 2010; Koriat, 2015; Pouget et al., 2016) that

is still not well understood but receives growing attention. In particular, we asked how

the neural encoding of representational uncertainty may relate to probability distortion.

By comparing experimental conditions under which the same individuals' distortions

of relative frequency differed, we found that a relatively stronger response to

representational uncertainty in the parietal region corresponds to a shallower slope of

distortion. That is, the automatic, fast encoding of representational uncertainty is not

just a *post hoc* evaluation but regulates probability distortion.

Methodology implications and future directions

The "steady-state responses" (SSR) technique (Norcia, Appelbaum, Ales, Cottereau,

& Rossion, 2015)—using rapid periodic stimulus sequence to entrain brain

responses—has been widely used with EEG/MEG to investigate low-level perceptual

processes, which sacrifices temporal information to increase the signal-to-noise ratio

of detecting the automatic brain responses to the stimuli. In our experiment, we

constructed periodic p or $p(1–p)$ sequences and showed that SSR can also be used to

reveal the brain's automatic responses to these more abstract variables. Moreover,

we demonstrated that it is possible to perform time-resolved decoding for the other

aperiodic variable embedded in the same sequence. In this way, our experimental

design exploited the advantages of both the SSR and time-resolved decoding

techniques. Such design can be useful for a broad range of problems where the

processing of two or more variables needs to be dissociated.

   In conclusion, we found a correlation between the neural encoding of

representational uncertainty and the slope of behavioral probability distortion. One

question is whether there is a causal relationship between the two. A second future

question is how our findings for relative frequency can apply to probability distortions

with other types of probability information.

Materials and Methods

Ethics Statement

The MEG experiment had been approved by the Institutional Review Board of School of Psychological and Cognitive Sciences at Peking University (#2015-03-13c). Subjects gave written informed consent in accordance with the Declaration of Helsinki.

Subjects

Twenty-two human subjects (aged 18–27, 13 female) participated. All of them had normal or corrected-to-normal vision and passed the Farnsworth-Munsell 100 Hue Color Vision Test (Farnsworth, 1943).

Experimental Procedures

Apparatus. Subjects were seated approximately 86 cm in front of a projection screen (Panasonic PT-DS12KE: 49.6 × 37.2 cm, 1024 × 768 pixels, 60-Hz refresh rate) inside the magnetically shielded room. Stimuli were controlled by a Dell computer using Matlab and PsychToolbox-3 (Brainard, 1997; Pelli, 1997). Subjects' behavioral responses were recorded by an MEG-compatible mouse system (FOM-2B-10B from Nata technologies) and their brain activities by a 306-channel MEG system (see MEG Acquisition and Preprocessing for details).

Task. Each trial started with a white fixation cross on a blank screen for 600 ms, following which a sequence of displays of yellow and cyan dots was presented on a

gray background at a rate of 150 ms per display (Figure 1A). Subjects were asked to

fixate on the central fixation cross and track the relative-frequency of each display.

After the sequence ended for 1000 ms, a horizontal scale (0 to 100%) appeared on

the screen and subjects were required to click on the scale to indicate the

relative-frequency of yellow (or cyan) dots on the last display. Half of the subjects

reported relative frequency for yellow dots and half for cyan dots.

To encourage subjects to pay attention to each display, one out of six trials were

catch trials whose duration followed a truncated exponential distribution (1–6 s, mean

3 s), such that almost each display could be the last display. The duration of formal

trials was 6 or 6.15 s. Only the formal trials were submitted to behavioral and MEG

analyses.

On each display, all dots were randomly scattered without overlapping within an

invisible circle that subtended a visual angle of 12°. The visual angle of each dot was

0.2° and the center-to-center distance between any two dots was at least 0.12°. The

two colors of the dots were isoluminant (CIE_{yellow}=[43, 19.06, 52.33], CIE_{cyan}=[43,

-15.49, -23.72]). Isoluminant dark gray pixels (CIE_{gray}=[43, 0, 0]) were filled on the

gray background ($CIE_{background}$=[56.5, 0, 0]) between the dots as needed to guarantee

each display had equal overall luminance, which prevented luminance from being a

confounding factor for any abstract variables of interest.

Design. We adopted a steady-state response (SSR) design, which could achieve a

higher signal-to-noise ratio than the conventional event-related design (Norcia et al.,

2015). The basic idea was to vary the value of a variable periodically at a specific

temporal frequency and to observe the brain activities at the same frequency as an

idiosyncratic response to the variable. The variables of most interest in the present

study were relative frequency p and its representational uncertainty quantified by $p(1-$

$p)$.

For half of the trials (referred as the *P*-cycle condition), the value of p in the

sequence was chosen from uniform distributions with the ranges alternatively being

(0.1, 0.5) and (0.5, 0.9) so that the sequence of p formed cycles of 3.3 Hz. For the

other half trials (referred as the *U*-cycle condition), the value of p was chosen

alternatively from (0.1 0.3) U (0.7, 0.9) and (0.3, 0.7) so that the sequence of $p(1-p)$

(i.e. proxy for uncertainty) was in cycles of 3.3 Hz. That is, the two cycle conditions

had matched individual displays but differed in which variable formed a periodic

sequence. Accordingly, the $p(1-p)$ sequence in the *P*-cycle condition and the p

sequence in the *U*-cycle condition were aperiodic, which had no autocorrelations

(Figure S2).

The total number of dots on a display (numerosity, denoted N) was varied across

trials as well as across individual displays of the same trial. The value of N for a

specific display was independent of the value of p and generated as a linear

transformation of a beta random variable following Beta(0.1, 10) so that the number of

dots in each color (pN or $(1-p)N$), a possible confounding variable of p, would only

have moderate correlations (Pearson's $|r| < 0.5$) with p. The linear transformation was

chosen to locate N to the range of [10, 90] for half of the trials (the *N*-small condition)

and to [100, 900] for the other half (the *N*-large condition).

The numbers of dots in each color was *pN* or (1–*p*)*N* rounded to the nearest

integer. As the result of rounding, the actual relative-frequency was slightly different

from the originally chosen *p*. In data analysis, we would use *p* to denote the actual

relative-frequency that was presented to subjects.

To summarize, there were 2 (*P*-cycle vs. *U*-cycle) by 2 (*N*-small vs. *N*-large)

experimental conditions, with all conditions interleaved and each condition repeated

for 6 trials in each block. Each subject completed 10 blocks of 24 trials, resulting in 50

formal trials and 10 catch trials for each condition. Before the formal experiment, there

were 32 practice trials (the first 20 trials consisted of one display and the following 12

trials had the same settings as the formal experiment) for subjects to be familiar with

the procedure. No feedback was available during the experiment.

Behavioral Analysis

Measures of probability distortion. According to Zhang and Maloney (2012),

inverted-*S*- or *S*-shaped probability distortions can be well captured by the LLO model

$$\lambda\big[\pi(p)\big]=\gamma\lambda\big[p\big]+(1-\gamma)\lambda\big[p_0\big]+\varepsilon_\lambda, \tag{2}$$

where p and $\pi(p)$ respectively denote the objective and subjective probability or

relative-frequency, $\lambda\big[p\big]=\log\dfrac{p}{1-p}$ is the log-odds transformation, and ε_λ is

Gaussian error on the log-odds scale with mean 0 and variance σ_λ^2. The γ, p_0,

and σ_λ are free parameters. The parameter γ is the slope of distortion, with $\gamma<1$

corresponding to inverted-*S*-shaped distortion, $\gamma=1$ to no distortion, and $\gamma>1$ to

S-shaped distortion. The parameter p_0 is the crossover point where $\pi(p)=p$.

For each subject and condition, we fit the reported relative-frequency to the LLO

model (Eq. 2) and used the estimated $\hat{\gamma}$ and $\hat{p}_0$ as the measures of

relative-frequency distortions.

Response time. The response time (RT) was defined as the interval between the

response screen onset and subjects' first mouse move. The RT of the first trial of

three subjects was mis-recorded due to technical issues and was excluded from

further analysis. We divided all trials evenly into 5 bins based on the to-be-reported p,

and computed the mean p and mean RT for each bin. A 5 (p bins) by 2 (numerosity

conditions) repeated-measures ANOVA was performed on the mean RTs. A similar

binning procedure was applied to $p(1-p)$ to visualize the relationship of RT to $p(1-p)$.

MEG Acquisition and Preprocessing

Subjects' brain activity was recorded by a 306-channel whole-head MEG system

(Elekta-Neuromag, 102 magnetometers and 102 pairs of orthogonal planar

gradiometers). Head position was measured before each block by an isotrack

polhemus system with four head position indicator coils (two on the left and right

mastoid, the other two on the left and right forehead below the hairline). Subjects

whose between-block head movement exceeded 3 mm would be excluded from

further analysis. Horizontal and vertical Electro-oculograms were recorded to monitor

eye-movement artifacts. Sampling rate was set to be 1000 Hz and an analog

band-pass filter from 0.1 to 330 Hz was applied. Maxwell filtering was used to

minimize external magnetic interference and to compensate for head movements

(Samu Taulu & Kajola, 2005; S. Taulu & Simola, 2006).

Standard preprocessing procedures were applied using Matlab 2016b and the

FieldTrip package (Oostenveld, Fries, Maris, & Schoffelen, 2011). The MEG data of

each block was first low-pass filtered below 20-Hz and then segmented into epochs of

7.6 s relative to trial onset (–0.6 s to 7 s). Independent component analysis (ICA) was

applied to aggregated epoch data to remove artifacts including blinks, eye

movements, breaths and heart activity. No subject was excluded for excessive head

movement or other artifacts. For two subjects, the first trial of one block was excluded

due to the failure of synchronization between stimulus onset and MEG recording

onset at the beginning of the block.

Phase Coherence Analysis

Given a periodically-changed stimulus sequence (p in P-cycle or $p(1–p)$ in U-cycle),

stimulus-evoked brain responses imply that the phase difference between the

stimulus and response time series should be coherent across trials at the stimulus

frequency (Summerfield & Mangels, 2004). The phase coherence across trials is

defined as (Kramer & Eden, 2016):

$$\kappa = \frac{\left|\overline{P}_{rs}\right|}{\sqrt{\overline{P}_{ss}}\sqrt{\overline{P}_{rr}}} \ ,$$ (3)

where $\overline{P}_{ss}$ and $\overline{P}_{rr}$ respectively denote the trial-averaged power spectrum for

stimulus and response time series, and $\left|\overline{P}_{rs}\right|$ denotes the magnitude of the

trial-averaged cross-spectrum between stimuli and responses. The value of κ for

any specific frequency is between 0 and 1, with larger κ indicating stronger

phase-locked responses.

For a specific variable (p or $p(1–p)$), we computed the phase coherence between

stimulus sequence and MEG signals separately for each subject, each magnetometer

and each cycle and numerosity condition. In particular, we down-sampled epoched

MEG time series to 300 Hz, applied zero padding and Hanning window to single trials,

and used Fast Fourier Transformation (FFT) to calculate power spectrum. The

resulting frequency resolution was 0.03 Hz.

To evaluate the chance-level phase coherence, we shuffled the MEG time series

across different time points within each trial and computed phase coherence for the

permutated time series. This permutation procedure was repeated for 500 times to

produce a distribution of chance-level phase coherences.

Decoding Analysis

Time-resolved decoding. For an aperiodic stimulus sequence ($p(1–p)$ in *P*-cycle or *p*

in *U*-cycle), we could infer the brain's encoding of the stimulus variable at a specific

time lag to stimulus onset by examining how well the value of the variable could be

reconstructed from the neural responses at the time lag. In particular, we performed a

time-resolved decoding analysis using regression methods (Crosse, Liberto, Bednar,

& Lalor, 2016; Gonçalves, Whelan, Foxe, & Lalor, 2014; Lalor, Pearlmutter, Reilly,

McDarby, & Foxe, 2006; Wyart, Gardelle, Scholl, & Summerfield, 2012):

591
$$S(t) = \sum_{n} g(\tau, n) R(t+\tau, n) + \varepsilon(t) \ , \qquad (4)$$

where $S(t)$ denotes the value of the stimulus that starts at time t, $g(\tau, n)$ denotes

the to-be-estimated decoding weight for channel n at time lag τ, $R(t+\tau,n)$

denotes the response of channel n at time $t+\tau$, and $\varepsilon(t)$ is a Gaussian noise

term.

We used the MEG signals of all 306 sensors (102 magnetometers and 204

gradiometers) at single time lags to decode p from U-cycle trials or $p(1–p)$ from

P-cycle trials, separately for each subject, each cycle and numerosity condition, and

each time lag between 0 and 900 ms. Epoched MEG time series were first

down-sampled to 120 Hz. To eliminate multicollinearity and reduce overfitting, we

submitted the time series of the 306 sensors to a principal component analysis (PCA)

and used the first 30 components (explaining approximately 95% variance) as the

regressors. The decoding weights (i.e. regression coefficients) were estimated for

normalized stimuli and responses using the L2-rectified regression method

implemented in the mTRF toolbox (Crosse et al., 2016) , with the ridge parameter set

to 1.

We used a leave-one-out cross-validation procedure to evaluate the predictive

power of decoding performance as the following. Each time one of the 50 trials in

question (or 49 trials in the case of trial exclusion) served as the test set and the

remaining trials as the training set. The decoding weights estimated from the training

set were applied to the test set, for which Pearson's r was calculated between the

predicted and the ground-truth stimulus sequence. Such computation was repeated

for each trial as the test set and the averaged Pearson's r was used as the measure

for decoding performance.

We identified time windows that had above-chance decoding performance using

cluster-based permutation tests (Maris & Oostenveld, 2007) as follows. Adjacent time

lags with significantly positive decoding performance at the uncorrected significance

level of .05 by right-sided one-sample t tests were grouped into clusters and the

summed t-value across the time lags in a cluster was defined as the cluster-level

statistic. We randomly shuffled the stimulus sequence of each trial, performed the

time-resolved decoding analysis on the shuffled sequence and recorded the

maximum cluster-level statistic. This procedure was repeated for 500 times to

produce a reference distribution of chance-level maximum cluster-level statistic,

based on which we calculated the P value for each cluster in real data. This test

effectively controls the Type Ⅰ error rate in situations involving multiple comparisons.

For each subject, we defined the median of all time points for which the decoding

performance exceeded the 95% percentile of the distribution as the time lag of the

peak (Marti, King, & Dehaene, 2015).

Spatial decoding. For the conditions and time windows that had above-chance

performances in the time-resolved decoding analysis, we further performed a spatial

decoding analysis at individual sensor location to locate the brain regions that are

involved in encoding the variable in question. For a specific senor location, the MEG

signals at its three sensors (one magnetometer and two gradiometers) within the time

window were used for decoding. The time window that enclosed the peak in the

time-resolved decoding was 125-ms and 167-ms wide respectively for p and $p(1-p)$

under *N*-large condition. The decoding procedure was similar to that of the

time-resolved decoding described above, except that the number of PCA component

used was 19 and 24 respectively for decoding p and $p(1\text{-}p)$, which explained

approximately 99% variance of the original 48 (16 time lags $\times$ 3 sensors) and 63 (21

time lags $\times$ 3 sensors) channels.

Statistical Analysis

For phase coherence or decoding performance, grand averages across subjects were

computed and permutation tests described above were used to assess their statistical

significance over chance (Maris & Oostenveld, 2007). The false discovery rate (*FDR*)

method (Benjamini & Hochberg, 1995; Benjamini & Yekutieli, 2001) was used for

multiple comparison corrections whenever applicable. For the phase coherence

spectrum averaged across magnetometers, *FDR* corrections were performed among

the 235 frequency bins within 0–7 Hz. For the phase coherence topography at 3.33

Hz, *FDR* corrections were performed among all 102 magnetometers.

References

Attneave, F. (1953). Psychological probability as a function of experienced frequency.

Journal of Experimental Psychology, 46(2), 81-86.

Bahrami, B., Olsen, K., Latham, P. E., Roepstorff, A., Rees, G., & Frith, C. D. (2010).

Optimally interacting minds. *Science, 329*, 1081-1085.

Benjamini, Y., & Hochberg, Y. (1995). Controlling the false discovery rate: a practical

and powerful approach to multiple testing. *Journal of the Royal Statistical*

Society, 57(1), 289-300.

Benjamini, Y., & Yekutieli, D. (2001). The control of the false discovery rate in multiple

testing under dependency. *The Annals of Statistics, 29*(4), 1165-1188.

Brainard, D. H. (1997). The psychophysics toolbox. *Spatial Vision, 10*, 433-436.

Crosse, M. J., Liberto, G. M., Bednar, A., & Lalor, E. C. (2016). The Multivariate

Temporal Response Function (mTRF) Toolbox: A MATLAB Toolbox for

Relating Neural Signals to Continuous Stimuli. *frontiers in Human*

Neuroscience, 10, 604-617.

Erev, I., Wallsten, T. S., & Budescu, D. V. (1994). Simultaneous over- and

underconfidence: the role of error in judgment processes. *Psychological*

Review, 101(3), 519-527.

Farnsworth, D. (1943). The Farnsworth-Munsell 100 Hue and Dichotomous Test for

Color Vision. *Journal of the Optical Society if America, 33*(10), 568-578.

Fennell, J., & Baddeley, R. (2012). Uncertainty plus prior equals rational bias: an

intuitive Bayesian probability weighting function. *Psychological Review, 119*(4),

878-887. doi:10.1037/a0029346

Ferrari-Toniolo, S., Bujold, P. M., & Schultz, W. (2019). Probability distortion depends

on choice sequence in Rhesus Monkeys. *The Journal of Neuroscience, 39*(15),

2915-2929.

Fiorillo, C. D., Tobler, P. N., & Schultz, W. (2003). Discrete coding of reward probability

and uncertainty by dopamine neurons. *Science, 299*(5614), 1898-1902.

Gherman, S., & Philiastides, M. G. (2015). Neural representations of confidence

emerge from the process of decision formation during perceptual choices.

NeuroImage, 106, 134-143.

Gherman, S., & Philiastides, M. G. (2018). Human VMPFC encodes early signatures

of   confidence   in   perceptual   decisions.   *eLIFE,   7*,   e38293.

doi:https://doi.org/10.7554/eLife.38293

Gigerenzer, G., Hoffrage, U., & Kleinbölting, H. (1991). Probabilistic mental models: a

Brunswikian theory of confidence. *Psychological Review, 98*(4), 506-528.

Gonçalves, N. R., Whelan, R., Foxe, J. J., & Lalor, E. C. (2014). Towards obtaining

spatiotemporally precise responses to continuous sensory stimuli in humans:

A general linear modeling approach to EEG. *NeuroImage, 97*, 196-205.

Gonzalez, R., & Wu, G. (1999). On the Shape of the Probability Weighting Function.

Cognitive Psychology, 38, 129-166.

Hsu, M., Krajbich, I., Zhao, C., & Camerer, C. F. (2009). Neural Response to Reward

Anticipation   under   Risk   Is   Nonlinear   in   Probabilities.   *The   Journal   of*

Neuroscience, 29(7), 2231–2237

Huang, Q., Jia, J., Han, Q., & Luo, H. (2018). Fast-backward replay of sequentially

memorized items in humans. *eLIFE, 7,* e35164.

doi:https://doi.org/10.7554/eLife.35164

Jia, J., Liu, L., Fang, F., & Luo, H. (2017). Sequential sampling of visual objects during

sustained attention. *PloS Biology, 15*(6), 1-19.

Kiani, R., & Shadlen, M. N. (2009). Representation of confidence associated with a

decision by neurons in the parietal cortex. *Science, 324*(8), 759-763.

Koriat, A. (2015). Metacognition: decision-making processes in self-monitoring and

self-regulation. In G. Keren & G. Wu (Eds.), *The Wiley Blackwell handbook of*

judgment and decision making (Vol. 1, pp. 356-379). Malden, MA: Wiley

Blackwell.

Kramer, M. A., & Eden, U. T. (2016). *Case studies in neural data analysis: A guide for*

the practicing neuroscientist (Vol. 11). the United States of America:

Massachusetts Institute of Technology.

Lalor, E. C., Pearlmutter, B. A., Reilly, R. B., McDarby, G., & Foxe, J. J. (2006). The

VESPA: A method for the rapid estimation of a visual evoked potential.

NeuroImage, 32, 1549-1561.

Lebreton, M., Abitbol, R., Daunizeau, J., & Pessiglione, M. (2015). Automatic

integration of confidence in the brain valutation signal. *Nature Neuroscience,*

18(8), 1159-1167.

Lichtenstein, S., Slovic, P., Fischhoff, B., Layman, M., & Combs, B. (1978). Judge

Frequency of Lethal Events. *Journal of Experimental Psychology: Human*

Learning and Memory, 4(6), 551-578.

Liu, L., Wang, F., Zhou, K., Ding, N., & Luo, H. (2017). Perceptual integration rapidly

721   activates dorsal visual pathway to guide local processing in early visual areas.

722   *PloS Biology, 15*(11), e2003646.

723   Luce, R. D. (2000). *Utility of gains and losses: measurement -- theoretical, and*

724   *experimental approaches* Mahwah, New Jersey, London: Lawrence Erlbaum

725   Associates, Inc.

726   Maloney, L. T., & Zhang, H. (2010). Decision-theoretic models of visual perception

727   and action. *Vision Research, 50*(23), 2362-2374.

728   Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and

729   MEG-data. *Journal of Neuroscience Methods, 164*, 177-190.

730   Marti, S., King, J.-R., & Dehaene, S. (2015). Time-resolved decoding of two

731   processing chains during dual-task interference. *Neuron, 88*, 1297-1307.

732   Martins, A. C. R. (2006). Probability biases as Bayesian inference. *Judgment and*

733   *Decision Making, 1*(2), 108-117.

734   Norcia, A. M., Appelbaum, L. G., Ales, J. M., Cottereau, B. R., & Rossion, B. (2015).

735   The steady-state visual evoked potential in vision research: A review. *Journal*

736   *of Vision, 15*(6), 1-46.

737   Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: open source

738   software for advanced analysis of MEG, EEG and invasive

739   electrophysiological data. *Computational Intelligence and Neuroscience, 2011*,

740   1-9.

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: transforming

numbers into movies. *Spatial Vision, 10*(4), 437-442.

Pouget, A., Drugowitsch, J., & Kepecs, A. (2016). Confidence and certainty: distinct

probabilistic quantities for different goals. *Nature Neuroscience, 19*(3),

366-374.

Preuschoff, K., 't Hart, B. M., & Einhäuser, W. (2011). Pupil dilation signals surprise:

evidence for noradrenaline's role in decision making. *frontiers in Neuroscience,*

5(115), 1-12.

See, K. E., & Fox, C. R. (2006). Between ignorance and truth: partition dependence

and learning in judgment under uncertainty. *Journal of Experimental*

Psychology: Learning, Memory, and Cognition, 32(6), 1385-1402.

Stauffer, W. R., Lak, A., Bossaerts, P., & Schultz, W. (2015). Economic Choices

Reveal Probability Distortion in Macaque Monkeys. *The Journal of*

Neuroscience, 35(7), 3146-3154.

Summerfield, C., & Mangels, J. A. (2004). Coherent theta-band EEG activity predicts

item-context binding during encoding. *NeuroImage, 24*, 692-703.

Taulu, S., & Kajola, M. (2005). Presentation of electromagnetic multichannel data: The

signal space separation method. *Journal of Applied Physics, 97*, 124905

124901-124910.

Taulu, S., & Simola, J. (2006). Spatiotemporal signal space separation method for

rejecting nearby interference in MEG measurements. *Physics in Medicine and*

Biology, 51, 1759-1768.

Tobler, P. N., Christopoulos, G. I., O'Doherty, J. P., Dolan, R. J., & Schultz, W. (2008).

Neuronal Distortions of Reward Probability without Choice. *The Journal of*

Neuroscience, 28(45), 11703–11711.

Tobler, P. N., O'Doherty, J. P., Dolan, R. J., & Schultz, W. (2007). Reward value coding

distinct from risk attitude-related uncertainty coding in human reward systems.

J Neurophysiol, 97, 1621-1632.

Tversky, A., & Kahneman, D. (1992). Advances in Prospect Theory: Cumulative

Representation of Uncertainty. *Journal of Risk and Uncertainty, 5*, 297-323.

van Lieshout, L. L. F., Vandenbroucke, A. R. E., Müller, N. C. J., Cools, R., & de Lange,

F. P. (2018). Induction and relief of curiosity elicit parietal and frontal activity.

The Journal of Neuroscience, 38(10), 2579-2588.

Varey, C. A., Mellers, B. A., & Birnbaum, M. H. (1990). Judgments of Proportions.

Journal of Experimental Psychology: Human Perception and Performance,

16(3), 613-625.

Wallsten, T. S., Budescu, D. V., Erev, I., & Diederich, A. (1997). Evaluating and

combining subjective probability estimates. *Journal of Behavioral Decision*

Making, 10, 243-268.

Wyart, V., Gardelle, V. d., Scholl, J., & Summerfield, C. (2012). Rhythmic Fluctuations

in Evidence Accumulation during Decision Making in the Human Brain.

Neuron, 76, 847-858.

Yang, T., & Shadlen, M. N. (2007). Probabilistic reasoning by neurons. *Nature, 447*,

1075-1080.

Zhang, H., & Maloney, L. T. (2012). Ubiquitous log odds: a common representation of

probability and frequency distortion in perception, action, and cognition.

frontiers in Neuroscience, 6, 1.

Zhang, H., Ren, X., & Maloney, L. T. (2019). The bounded rationality of probability

distortion: the bounded log-odds model. *bioRxiv*.

doi:https://doi.org/10.1101/662429

Zizlsperger, L., Sauvigny, T., Händel, B., & Haarmeier, T. (2014). Cortical

representations of confidence in a visual perceptual decision. *Nature*

Communications, 5, 3940.

Supplement S1. Fitting the Bounded Log-Odds (BLO) model to subjects' $\pi(p)$

Please refer to Zhang, Ren, & Maloney (2019) for a full description of the BLO model, which we briefly formulize below. BLO assumes that any probability or relative frequency, *p*, is internally represented as a linear transformation of log-odds,

$$\lambda(p) = \log\frac{p}{1-p} \quad . \tag{S1}$$

A bounding operation

$$\Gamma[\lambda] = \begin{cases} \Delta^-, & \lambda < \Delta^- \\ \lambda, & \Delta^- \leq \lambda \leq \Delta^+ \\ \Delta^+, & \lambda > \Delta^+ \end{cases} \tag{S2}$$

is defined to confine the representation of log-odds λ to the interval $[\Delta^-, \Delta^+]$, where Δ^- and Δ^+ are free parameters. $\Lambda(p) = \Gamma(\lambda[p])$ is referred as "truncated log-odds".

In our relative-frequency judgment task, we assume representational uncertainty partly arises from random variation of sampling. Suppose subjects may not access to all of the dots in a display. For a display of N dots, a sample of n_s dots is randomly drawn from the display without replacement and used to infer the relative frequency. The resulting variance of $\hat{p}$ is thus (Cochran, 1977; Zhang et al., 2019):

$$V(\hat{p}) = \frac{p(1-p)}{n_s}\frac{N-n_s}{N-1} \quad . \tag{S3}$$

Here n_s is modeled as an increasing function of numerosity:

$$n_s = b + N^a \quad , \tag{S4}$$

where $a \geq 0$ and $b \geq 0$ are free parameters.

To compensate for this representational uncertainty, the internal representation $\Lambda(p)$ further undergoes a non-linear contraction or expansion around a fixed point Λ_0 on the log-odds scale so that the log-odds of the reported relative frequency

$$\lambda\big[\pi(p)\big] = \eta\Big[\ \omega_p \Lambda(p) + (1-\omega_p)\Lambda_0\ \Big] + \varepsilon_\lambda\ ,\tag{S5}$$

where $\omega_p = \dfrac{1}{1+\alpha V(\hat{p})}$ is a measure of the reliability of the internal representation, and ε_λ is Gaussian error on the log-odds scale with mean 0 and variance σ_λ^2. The α, η, Λ_0, and σ_λ are free parameters. Along with the Δ^-, Δ^+, a and b, the BLO model has 8 parameters. Finally, the scaling factor η adjusts the bounded interval to the fixed Thurstone scale (Thurstone, 1927; Zhang et al., 2019).

For each subject, we fit the BLO model to the subject's $\pi(p)$ in each trial using maximum likelihood estimates. The *fminsearchbnd* (J. D'Errico), a function based on *fminsearch* in MATLAB (MathWorks), was used to search for the parameters that minimized negative log likelihood.

To summarize how the slope of distortion changed with numerosity, for each subject, we divided the trials of each numerosity condition equally into two sub-conditions according to the value of *N* and then estimated $\hat{\gamma}$ for each of the four sub-conditions (Figure S1). The pattern of $\hat{\gamma}$ in real data was well predicted by the fitted BLO model (based on 500 times of simulations).

We also compared the goodness-of-fit of the BLO model with that of the LLO model (Eq. 2 in the main text), which separately fit the slopes of the *N*-small and *N*-large conditions (4 parameters in total, $\gamma_{N\text{-small}}$, $\gamma_{N\text{-large}}$, p_0 and ε). According to the Akaike information criterion with a correction for sample sizes (AICc) (Akaike, 1974; Hurvich & Tsai, 1989), the BLO model outperformed the LLO model (the summed AICc difference across subjects between the LLO and BLO models was 285.33).

Figure S1. Estimated slopes of distortion: data versus BLO model fits. According to the numerosity of the last display, the trials in the *N*-small and *N*-large conditions were further divided into two equal halves, whose slopes of distortions, $\hat{\gamma}$, were estimated separately. Light and dark green dots denote data. Orange circles denote BLO fits. Error bars for data and BLO fits respectively denote SEM and the 95% confidence interval. The BLO model, which assumes compensation for representational uncertainty in the p(1-p) form, well captures how $\hat{\gamma}$ varies with numerosity.

Supplement S2. Autocorrelation analysis for periodic and aperiodic stimulus sequences

We applied an autocorrelation analysis to the stimulus sequences in each trial to confirm their periodicity or aperiodicity. Autocorrelations were calculated for individual trials and then averaged across trials in each condition. As designed, the *p* sequence in *P*-cycle trials and the *p(1–p)* sequence in *U*-cycle trials had periodic autocorrelations, while the *p* sequence in *U*-cycle trials and the *p*(1-*p*) sequence in *P*-cycle trials were free of autocorrelations (Figure S2).

Figure S2. **Autocorrelations of stimulus sequences as functions of time lags.**

Left: the *P*-cycle condition. Right: the *U*-cycle condition. Solid and dashed lines are respectively for the *p* and *p*(1-*p*) sequences. The stimulus sequences used for autocorrelation calculations were from the example subject whose behavior results are showed in Figure 1C. All other subjects had similar autocorrelation patterns.

Supplement S3. Phase coherence and time-resolved decoding analyses for confounding factors

We considered the following eight variables in the stimuli as potential confounding factors, which may covary with p or $p(1–p)$ across displays.

(1) N: the total number of dots (numerosity) in the display, which by design was independent of both p and $p(1–p)$.

(2) N_t: the number of dots in the target color in the display, that is, $N_t = Np$.

(3) N_o: the number of dots in the other color in the display, that is, $N_o = N(1–p)$.

(4) *AvgLumi*: the mean luminance of the display, which was kept constant across different displays and different trials and was thus independent of both p and $p(1–p)$.

(5) *vCIE-L**: the color variance of the display on the L* dimension in the CIELAB color space, where L* ranges from black to white.

(6) *vCIE-a**: the color variance of the display on the a* dimension in the CIELAB color space, where a* ranges from green to red.

(7) *vCIE-b**: the color variance of the display on the b* dimension in the CIELAB color space, where b* ranges from blue to yellow.

(8) *M-contrast*: the *Michelson* luminance contrast (Wiebel, Singh, & Maertens, 2016).

According to our design, most of these variables had negligible correlations with p and $p(1–p)$ and none of the absolute values of correlation coefficients exceeded 0.53 (Pearson's r, Figure S3A). The numerosity (N) had considerable correlations (Pearson's $|r| > 0.79$) with all other confounding factors except for the mean luminance (*AvgLumi*), which was constant across displays. We performed similar phase coherence (Figure S3B) and time-resolved decoding analyses (Figure S3C) for these variables as we did for p and $p(1–p)$ but obtained very different patterns, which suggests that the findings we reported for p and $p(1–p)$ in the main text are unlikely to be effects of confounding factors. The patterns of all these confounding factors expect for *AvgLumi* were almost identical, which may have the same

origins such as the automatic encoding of numerosity (Fornaciai, Brannon, Woldorff, & Park, 2017; Park, DeWind, Woldorff, & Brannon, 2016).

Figure S3. **Analysis for the confounding variables. (A) Correlation analysis.** Top row: Pearson's correlations between the p sequence and the eight confounding variables (N, N_t, N_o, *AvgLumi*, *vCIE-L**, *vCIE-a**, *vCIE-b** and *M-contrast*) separately for the four cycle and numerosity conditions. Bottom row: Pearson's correlations between the $p(1-p)$ sequence and the eight confounding variables for each condition. The results confirmed our design that all of the confounding variables had negligible or moderate correlations with p and *p(1–p)*. **(B) Phase coherence analysis.** Grand-averaged phase coherence spectrum between the sequences of the eight confounding variables and neural responses from magnetometers. The observed phase coherence spectra of the confounding variables had different patterns than those of p or $p(1-p)$. See the Supplement S4 for the possible cause of the "bumps" between 0 and 6.67 Hz. **(C) Time-resolved decoding analysis.** The same time-resolved decoding procedures as Figure 4 were applied to the eight confounding variables. For **(A)–(C)**, light and dark green respectively code the N-small and N-large conditions. For **(B)** and **(C)**, solid and dashed lines respectively denote the *P*-cycle and *U*-cycle conditions. Shadings denote SEM across subjects.

Supplement S4. Explaining the "bumps" in the phase coherence spectra of the confounding factors

As shown in the Figure S3B, there was a "bump" spanning across 0–6.67 Hz in the phase coherence spectrum of *N*. So did all of the confounding variables we considered above that had high correlations with *N*. Though also centering at 3.33 Hz, these "bumps" were much wider than the 3.33 Hz peak we observed for the *p* sequence in the *P*-cycle condition or the *p(1–p)* sequence in the *U*-cycle condition. Besides, the "bumps" were similar across all four cycle and numerosity conditions, which were unlikely due to the periodicity of *p* or *p(1–p)*. We found in a simulation analysis that these "bumps" could simply result from the particular temporal course of the neural responses to the variables.

In particular, we first estimated the temporal course of stimulus-evoked brain responses to *N* using a computational technique known as Temporal Response Function (TRF) analysis (Crosse, Liberto, Bednar, & Lalor, 2016; Gonçalves, Whelan, Foxe, & Lalor, 2014; Lalor, Pearlmutter, Reilly, McDarby, & Foxe, 2006). The TRF for a specific stimulus dimension describes how the brain responds to a unit change in stimulus magnitude at different time lags. The brain is modeled as a linear system, whose response at a specific time point is the summation of the responses to all previous stimuli, that is, a convolution of the stimulus sequence with TRF plus Gaussian random noise:

$$R(t,n) = \sum_{\tau} w(\tau,n) S(t-\tau) + \varepsilon(t,n), \tag{S6}$$

where *t* denotes time, *n* denotes sensor number, τ denotes the time lag to stimulus onset, $R(\cdot)$, $w(\cdot)$, $S(\cdot)$ and $\varepsilon(\cdot)$ respectively denote the magnitude of sensor response, the to-be-estimated TRF, the stimulus sequence, and Gaussian noise term. The stimulus sequence was modeled as the summation of pulses at display onsets. For the TRF analysis, epoched MEG data were down-sampled to 120 Hz. The TRF $w(\tau,n)$ was estimated for a maximum delay of 900 ms using a rectified regression method, with the ridge parameter set to 1. Both the stimulus sequence and sensor responses were normalized before the analysis.

We estimated the TRF for *N* and then convolved it with the *N* sequence and added a Gaussian noise to generate virtual neural responses. We then applied the phase coherence analysis to the virtual neural responses. This simulation was repeated for 500 times, based on which we computed the mean phase coherence spectrum for the simulated data. We found that the resulting phase coherence spectrum resembled that of real data, reproducing the "bump" between 0 and 6.67 Hz (Figure S4).

Figure S4. **Explaining the "bumps" in the phase coherence of numerosity.** Simulated neural signals were generated through convolution of TRF estimated from the MEG2521 sensor (located right occipital) with the *N* sequence, perturbed by Gaussian nose whose standard deviation was set to 4. The simulated neural signals were then submitted to the phase coherence analysis (see Materials and Methods). Light and dark green curves denote the phase coherence across magnetometers of real data from one example subject. Orange curves denote the average across 500 simulations. The "bump" across 0–6.67 Hz observed in real data was reproduced in the simulated data.

Figure S5. **Phase coherence analysis for the aperiodic sequences.** Grand-averaged phase coherence spectrum across 102 magnetometers. Left: The phase coherence (κ) between the (aperiodic) $p(1-p)$ sequence and MEG signals in *P*-cycle trials. Right: The phase coherence between the (aperiodic) p sequence and MEG signals in *U*-cycle trials. Shadings denote SEM across subjects. The vertical line marks the 3.33 Hz. As expected, none of the aperiodic sequences had phase coherence peaks at 3.33 Hz.

Figure S6. **Topography of spatial decoding performance for the other three statistically significant time windows in the time-resolved decoding analysis.** Black dots mark the sensor locations with above-chance decoding performance ($P_{FDR} < 0.05$).

Supplement References

Akaike, H. (1974). A new look at the statistical model identification. *IEEE Transactions on Automatic Control, 19*(6), 716-723.

Cochran, W. G. (1977). *Sampling techniques*. New York: John Wiley & Sons.

Crosse, M. J., Liberto, G. M., Bednar, A., & Lalor, E. C. (2016). The Multivariate Temporal Response Function (mTRF) Toolbox: A MATLAB Toolbox for Relating Neural Signals to Continuous Stimuli. *frontiers in Human Neuroscience, 10*, 604-617.

Fornaciai, M., Brannon, E. M., Woldorff, M. G., & Park, J. (2017). Numerosity processing in early visual cortex. *NeuroImage, 157*, 429-438.

Gonçalves, N. R., Whelan, R., Foxe, J. J., & Lalor, E. C. (2014). Towards obtaining spatiotemporally precise responses to continuous sensory stimuli in humans: A general linear modeling approach to EEG. *NeuroImage, 97*, 196-205.

Hurvich, C. M., & Tsai, C. L. (1989). Regression and time series model selection in small samples. *Biometrika, 76*(2), 297-307.

Lalor, E. C., Pearlmutter, B. A., Reilly, R. B., McDarby, G., & Foxe, J. J. (2006). The VESPA: A method for the rapid estimation of a visual evoked potential. *NeuroImage, 32*, 1549-1561.

Park, J., DeWind, N. K., Woldorff, M. G., & Brannon, E. M. (2016). Rapid and direct encoding of numerosity in the visual stream. *Cerebral Cortex, 26*, 748-763.

Thurstone, L. L. (1927). A law of comparative judgment. *Psychological Review, 34*, 273-286.

Wiebel, C. B., Singh, M., & Maertens, M. (2016). Testing the role of Michelson contrast for the perception of surface lightness. *Journal of Vision, 16*(11), 17, 11-19.

Zhang, H., Ren, X., & Maloney, L. T. (2019). The bounded rationality of probability distortion: the bounded log-odds model. *bioRxiv*. doi:https://doi.org/10.1101/662429