Accuracy and Reproducibility of Somatic Point Mutation Calling in Clinical-Type Targeted Sequencing Data

Ali Karimnezhad, Gareth A. Palidwor, Kednapa Thavorn, David J. Stewart,
Pearl A. Campbell, Bryan Lo, Theodore J. Perkins

Contact: tperkins@ohri.ca

Abstract

Background: Successful treatment of cancer depends in part on identifying the particular mutations driving each patient's disease. Many clinical laboratories are adopting high-throughput sequencing as a means of assaying patients' tumours. However, most benchmarking and best practices studies have been conducted on large solid tumour specimens and whole genome or exome sequencing. Our motivation comes from the treatment of non-small cell lung cancer, where minimally-invasive fine-needle aspiration biopsies can be used to produce samples for somatic mutation detection. The number of cancerous cells in such biopsies may number only in the hundreds or thousands. In this context, definitive guidance on best choices for sequencing platforms, sequencing strategies, and variant calling is lacking.

Results: Because ground truth for clinical specimens is rarely known, we used the well-characterized Coriell cell lines GM12878 and GM12877 to generate data. However, we prepared samples to mimic as closely as possible clinical biopsies, including formalin fixation and paraffin embedding. We evaluated two well-known targeted sequencing panels, Illumina's TruSight 170 panel and the Oncomine Focus panel. Sequencing was performed on an Illumina NextSeq500 and an Ion Torrent PGM respectively. We performed multiple biological replicates of each assay, to test reproducibility. Finally, we applied five different public and freely-available somatic single-nucleotide variant (SNV) callers to the data, MuTect2, SAMtools, VarScan2, Pisces and VarDict. Although the TruSight 170 and Oncomine Focus panels cover different amounts of the genome, we did not observe major differences in variant calling success within the regions that each covers. We observed substantial discrepancies between the five variant callers. All had high sensitivity, detecting known SNVs, but highly varying and non-overlapping false positive detections. Manually "harmonizing" various parameters of the variant callers reduced disagreements, but still left substantial numbers of false positives. Intersecting the results of multiple variant callers or, even better, biological replicates can nearly eliminate false positives.

Conclusion: Reproducibility and accuracy of targeted clinical sequencing results appears to depend less on sequencing platform and panel than they do on downstream bioinformatics. We recommend against using a variant caller with its default parameters, as many clinical labs do, as differences in default parameters are a greater influence on algorithm disagreement than other differences between algorithms. Our analysis suggests that intersecting VarDict and Pisces with harmonized parameters leads to the best combined mutation caller. Contrary to typical clinical practice, we also recommend analyzing replicate samples, as this greatly decreases false positive calls.

Keywords: Cancer genomics, Clinical genomics, High-throughput sequencing, Somatic point mutations, Personalized medicine, Single-nucleotide variants, Variant-calling

1 Background

Next generation sequencing (NGS) technologies have been used to catalogue genetic mutations in cancer. Recent studies employing NGS have identified specific genetic mutations that reliably predict therapeutic success with targeted treatment regimens in many forms of cancer, including non-small cell lung cancer (NSCLC), which is our long-term focus. Importantly, patients with oncogenic driver mutations have better tumour control with targeted agents than with chemotherapy, while those lacking such a mutation derive more benefit from chemotherapy [19]. To detect actionable mutations all patients with metastatic disease must be tested. Mutation assays are generally developed using tissues derived from surgical samples. However, for most patients with metastatic NSCLC the only tissue available is from fine needle aspirates (FNAs). Given the limited number and heterogeneity of cells found in FNAs and the expanding number of clinically actionable mutations, the development of testing strategies that can rapidly and accurately identify driver mutations in NSCLC remains a challenge. This study focuses on the identification of best methods (pre-analytical, analytical, and bioinformatic) to identify mutations in samples similar to lung FNAs.

Developments in NGS technologies are empowering the analyses of whole cancer genomes, providing insights into the task of somatic mutation calling [27] and have made it possible to characterize the genomic alterations in a tumour in an unbiased manner [20]. With the advancement of NGS technologies, the number of large-scale projects (especially cancer projects) dealing with somatic point mutation in various tumour types has been increasing rapidly. However, in clinical practice, there is only a limited number of actionable mutations that are of interest—those for which a specific therapy is recommended, or perhaps for which a clinical trial may be ongoing. In such cases, targeted sequencing is the preferred option, offering lower cost and higher coverage of areas of interest [6].

The majority of mutation callers available in the literature have been designed to analyze matched tumour-normal samples [28]. However, performing variant calling using both tumour and normal samples in some cases might not be feasible. Tumour-only mutation callers have also been developed. A few mutation callers such as Mutect2 and VarDict are versatile enough to analyze both matched tumour-normal and tumour-only samples. For a recent up-to-date list of mutation callers, readers may refer to [28], where 46 mutation callers are reviewed.

Variant callers are expected to detect mutations with either high read depth or high allele frequency. However, the confidence might not be high due to noise in the reads [28]. On the other hand, the resulting list of mutations detected by any mutation caller is error-prone due to the fact that the caller relies on some statistical assumptions and performs according to some pre-set parameters in a built-in algorithm.

A typical workflow of mutation calling can be divided into three steps. First, reads are processed and low-quality bases and any exogenous sequences such as sequencing adapters are excluded from the reads. This can be performed by using tools such as Cutadapt [18] and NGS QC Toolkit [22]. Second, the cleaned reads are mapped to a reference genome.

This base-to-base alignment can be done by using common tools such as BWA aligner [15] for DNA sequencing or TopHat [26] for RNA sequencing. The last step of this process is to separate real mutations from artifacts that might be present due to a process of library preparation, read errors, mapping errors, and so on. Some mutation callers perform the above three-step process as a built-in procedure (see [28]), but must start from the point of mapped reads.

Several analysis packages with different algorithms have been introduced in recent years to increase mutation detection accuracy. Significant discrepancies among the different algorithms used in each package have been observed, which leads to a difficulty in selecting candidate mutations for validation [10]. Such disagreement seems to partially root from different error models and assumptions made in each algorithm. In addition, various sources of errors such as sequencing errors and read alignment errors make the process more challenging. Thus, detection accuracy remains questionable and in fact, has become a major challenge.

Previous benchmarking studies offer some guidance in this regard, each having its strengths and weaknesses. For example, Spencer et al. [25] evaluated four mutation callers on a compendium of data from several cell lines and mixtures of DNA from those cell lines—artificially "creating" mutations at different allele frequencies. However, they focused on only one targeting panel, the Washington University comprehensive cancer set WUCaMP27 version 1.0, and one sequencing platform, the Illumina HiSeq 2000. Also problematically, they defined gold standard mutations by intersecting variant calls from GATK and SAMtools, two of the four programs they benchmarked. Derryberry et al. [5] focused on the technical reproducibility of variant calls, studying 55 replicate pairs of data from gliobastoma tumours. However, this was whole genome sequencing data, where coverage was substantially lower than for targeted panels. Xu et al. [29] performed a thorough comparison of mutation callers on exome sequencing data of pure and admixed cell lines, where gold-standard mutations where established by prior independent work. Moreover, they explored, to some extent, the effects of varying variant-calling thresholds. However, their work was limited to tumour-normal variant calling. Numerous other benchmarking studies have been performed; we mention these only as examples. Of note, new "best practices" for benchmarking variant calling have recently been proposed [13].

Of course, no single study can exhaustively address all possible relevant issues in variant calling. We seek here to add to the conversation by comparing five variant callers, on data from two cell lines, sequenced on two different platforms using two different targeted panels, in multiple biological replicates. We minimize circularity in defining gold-standard mutations by relying on previous high-quality work using independent data and variant calling methods. We study agreements and disagreements in variant calls, depending on algorithms, algorithm settings, and between replicates. Our key findings are: that sequencing platforms are not a major influence on variant calling; that variant callers can disagree wildly when used with default/recommended settings, but that they agree much more when settings are harmonized; and that intersecting the results from different algorithms (which is not unusual in research practice, though possibly unusual in clinical practice) or from replicate

samples (which is definitely unusual in clinical practice), can greatly reduce false positive calls while maintaining sensitivity for detecting genuine mutations.

2   Materials and Methods

Cell lines and DNA sequencing data generation: Data was generated from two Coriell cell lines, GM12878 and GM12877. Cells were prepared as standard for targeted clinical sequencing. Briefly, cells were expanded as per the ATCC recommended protocol, harvested, and processed into FFPE cytoblocks. DNA and RNA were isolated for each cell line using minimum of 6 x 10 um sections and AllPrep DNA/RNA FFPE Kit (Qiagen) according to vendor's recommended protocol. Nucleic acid quality assessment and quantitation were respectively performed using the Fragment Analyzer (AATI) and Qubit (Thermo Fisher Scientific). One or two sets of biological triplicates were prepared for each cell line. TruSight 170 (Illumina) libraries were prepared using 40 ng DNA or RNA input. Oncomine Focus Libraries (Thermo Fisher Scientific) were prepared using 10 ng DNA or RNA as input. Illumina libraries were sequenced on the NextSeq 500, with 8 RNA and DNA libraries pooled in each High Output 300 cycle run. Oncomine Focus libraries were sequenced on the Ion Torrent, with 6 RNA and DNA libraries pooled on each 318 chip. The Illumina TST170 assay provides full exonic coverage for 170 cancer-associated genes, covering 527,121 total bases, with 3064 genomic intervals. The Oncomine Focus panel covers 29008 total bases in 47 genes, using 269 genomic intervals. In this study, we use only the DNA sequencing data from either panel.

DNA sequencing data processing: TruSight sequencing data in FASTQ format was quality checked and mapped to the hg19 genome using the recommended BaseSpace pipeline, which relies on Isaac DNA aligner v3.16.02.19. For the Oncomine data, BAM files were obtained from the Ion Torrent online workflow. But because of indexing issues, reads were extract from the BAM files back into FASTQ format using Picard v2.10.7. Then the reads were mapped to hg19 using BWA aligner version v0.7.17-r1188, producing the BAM files to be used for variant calling.

Single nucleotide variant calling: We evaluated five publicly available software packages capable of single nucleotide variant (SNV) calling: SAMtools v1.9 [16], VarScan2 v2.3.9 [11], Mutect2 v4.beta.3-SNAPSHOT [1], VarDict [14], and Pisces v5.2.0.1 [7]. All versions were the most recent available at the time of our study. We downloaded all software packages and installed them on our local compute cluster. Each takes as input BAM files of mapped reads or pileups computed from BAM files, e.g. by the mpileup function of SAMtools. Each was used to call variants in tumor-only mode, meaning mutations were called relative to the hg19 genome. Each program outputs some form of variant call file (VCF), from which we extracted SNV calls along with associated information provided by the variant caller, such as depth of coverage, alternative allele frequency, p-value, etc.

Each variant caller has some pre-defined but adjustable parameters, such as: minimum

Table 1: Various parameters along with their default values defined in each mutation caller. A dash means that the corresponding parameter was not defined in the caller's settings.

Option	MuTect2	VarScan2	SAMtools	VarDict	Pisces
threshold for allele frequency	–	0.01	–	0.05	0.01
base quality score threshold	18	–	–	–	–
max base quality score	–	–	–	–	100
min map quality	20	null	0	null	1
mean map quality	–	null	–	null	–
max map quality	null	–	–	–	–
min coverage	–	8	–	–	10
max coverage	–	–	250	–	–
min supporting variant reads	–	2	–	–	–
min variant quality score	–	–	–	–	20
strand bias filter	–	–	–	–	0.5
min reads to strand bias	2	–	–	–	–

variant frequency, minimum coverage, minimum base quality score and minimum mapping quality score. In our initial tests, we ran each software with its default, recommended parameters. Table 1 summarizes key parameters and their default values for different programs. In later testing, we "harmonized" the parameters of different algorithms to be as similar as possible. Specifically, we set the minimum variant allele frequence to 0.01, the minimum read depth for variant calling to 10 reads, the minimum base call quality to 20, and the minimum read mapping quality to 20.

Performance assessment: For the GM12878 and GM12877 cell lines, we obtained gold-standard variant calls from [8]. We assumed that these an only these SNVs should be present in our cell lines. We intersected the SNVs provided by that study with the genomic intervals covered by the TruSight170 or Oncomine Focus panels, to determine which should be detected. If a caller identifies one of these mutations in a particular dataset, it is designated a true positive (TP). If a mutation within the genomic intervals for a panel is not identified by a caller from that dataset, it is designated a false negative (FN). Any called mutation that falls within the genomic regions but that is not on the gold-standard list is considered a false positive (FP). Variant callers are compared based on their TP, FN, FP numbers and scores derived from these, particularly precision, = TP / (TP+FP) and sensitivity = TP / (TP+FN).

Table 2: Summary of read depth and coverage (average reads covering each basepair covered by the panel) for TST170 and Oncomine Focus panels.

Rep	TST170 - GM12878		TST170 - GM12877		Oncomine - GM12878		Oncomine - GM12877	
	Reads	Coverage	Reads	Coverage	Reads	Coverage	Reads	Coverage
1	13275831	1056	3526629	300	835719	2437	602628	1829
2	7598224	659	3285901	280	213469	625	769173	2252
3	8279644	725	2440647	203	138350	415	1566916	4338
4	7435784	640	3640546	323	–	–	–	–
5	7519631	648	4731704	412	–	–	–	–
6	7775631	672	4101646	366	–	–	–	–

3 Results

3.1 Sequencing data shows expected SNVs in GM12878 and GM12877 cell lines

For the purpose of benchmarking different variant callers, we used clinical sample handling protocols to perform targeted DNA or DNA/RNA sequencing on multiple biological replicates of multiple cell lines. Because accuracy assessment requires us to know which mutations should be present in the samples, we selected two very well characterized Coriel Cell lines, GM12878 and GM12877. As our long-term goal is understanding best methods for variant calling in formalin-fixed, paraffin-embedded (FFPE) lung cancer fine-needle aspirates (FNAs), we performed independent preparations of the GM12878 and GM128977 cells for analysis in FFPE cytoblocks. We selected two targeted assays for testing. One was the TruSight170 Tumor Assay (TST170) from Illumina. TST170 is a comprehensive RNA/DNA hybrid-capture assay that provides full coverage for 170 solid tumor-associated genes. It is amenable to testing on FFPE samples of relatively limited sample availability. This assay tests for the presence of multiple classes of structural variants that are relevant to clinical diagnostics including SNVs, fusions, copy number variation, and INDELs. Here, however, we will focus only on the SNVs. The TST170 sequencing was performed on an Illumina NextSeq500 sequencer. We also tested the Oncomine Focus panel, which again is amenable to FFPE samples with limited material. Oncomine Focus covers 47 genes, and sequencing was performed on an Ion Torrent PGM.

Table 2 summarizes several key features of the sequencing data we generated. For the TST170 panel, read depths varied from approximately 2.4 million to over 13 million per sample. Within the genomic regions covered by the panel, this resulted in average coverage levels ranging from 203 to over 1000 reads per basepair. For the Oncomine data, read depths ranged from 1.3 million to over 15 million, resulting in coverages ranging from 415 to over 4000 reads per basepair.

Recent work has established a comprehensive and genome-wide catalog of high-confidence variants mutations for a collection of Coriell cell lines, including GM12878 and GM12877 [8]. That work relied on whole-genome sequencing data of 17 individuals in a three-generation

pedigree, and variant calling using programs: FreeBayes [17], Platypus [23], GATK3 [4] and Strelka [24]. By intersecting the locations of these known mutations with the TST170 genomic regions, we determined that our GM12878 and GM12877 data should contain 343 and 336 of these mutations, respectively. Intersecting with the Oncomine Focus genomic regions, we predicted that 26 and 24 known mutations should appear in GM12878 and GM12877 data respectively.

The first thing we checked was whether there was indeed evidence for these high-confidence, gold-standard mutations in our data. While the ability to call a variant depends on many factors, two key factors are the coverage (or read depth) at the site, and the frequency of the alternative (i.e. non-reference) allele frequence (AF). Figure 1 shows the empirical AFs and read depths for the known mutations for both cell lines and both panels. These numbers were computed from the associated BAM files of mapped reads using Bam-readcount (https://github.com/genome/bam-readcount).

Figure 1A, for example, shows AF and and read depth for the gold-standard mutations in all six replicates of our TST170 data from the GM12878 cell line, with the mutations in each replicate denoted by a different color and shape of mark. We also show the marginal histograms of AF and read depth for these mutations. Several points are worth nothing. First, regardless of replicate, there are two main clusters of points. One cluster is at or very near AF = 1, representing homozygous mutations relative to hg19. The other cluster centers near AF = 0.5, but with substantially greater spread, and represents heterozygous mutations. As would be expected on simple random-sampling grounds, there is more spread in empirical AF around AF = 0.5 when read depth is lower, with some heterozgyous variants having AF near 0.1 and others over 0.8. Remarkably, in all six replicates, there is no known mutation with zero alternative AF (nor zero read depth). Thus we can say that every dataset contains at least some evidence for every known gold-standard mutation.

Figure 1B shows the same type of plot for our TST170 GM12877 data. The patterns of AF and depth are similar, although we observe several qualitative differences from Figure 1A. First, the spread in empirical AF for the heterozygous mutations is greater. We suspect this is due in part to the lower overall read depths of these experiments, which came out at roughly half compared to GM12878. Few mutations exceed a coverage of 1000 reads in our GM12877 data, whereas that is the approximate median for our GM12878 data. It is not clear if this is the only factor leading to the greater AF spread. We also observe slightly greater frequency of mutations just below the level of AF=1. This may suggest a slightly higher per-base read error rate or possibly alignment errors. Excepting one mutation in replicate 3, there is no known mutation with zero alternative AF.

Figures 1C-D show similar plots for the Oncomine Focus data sets. The plots are much sparser, because these panels cover so much less genomic territory and so many fewer mutations. But the same broad pattern emerges. We see the gold-standard mutations having observed alternative AFs either near 0.5 or 1. In our Oncomine Focus data, there is greater difference in total read depth between replicates, and so unsurprisingly there is greater disparity in read depths at the mutation sites between replicates. Again, we see that every mutation is supported by at least some evidence. Collectively then, with the exception

Figure 1: Distribution of alternative allele frequency and read depth of known gold-standard mutations in the data.

of just a single site in one TST170 replicate of GM12877 data, our data contains evidence of all the expected gold-standard mutations.

The converse question is whether our data contain evidence of other mutations. These may be genuine mutations that have been missed by other variant calling efforts, or that arose spontaneously in our copies of the cell lines. Or they may be artifacts of some sort masquerading as genuine mutations. To study this question, we produced the same type of AF-versus-read-depth plots as in Figure 1, but for all the genomic positions covered by the panels that are not on the gold-standard list of mutations. The results can be seen in Figure 2. Panel A in particular shows the results for all six replicates of GM12878 using the TST170 panel. Unlike in Figure 1, where we saw substantial clouds of points suggesting heterozygous and homozygous mutations, the vast majority of these positions hover around low allele frequency. If these are non-mutated positions, then ideally the AF should read as zero; or, allowing for a small per-base read error rate below 1%, small non-zero AFs could be expected. We see a substantial number of positions with AF at 0.2 or higher, even at relatively high coverage like 1000 reads or more. The fact that the apparent distribution of AFs gravitates towards zero as coverage increases suggests these higher AFs may be errors of some kind. Regardless, some of these positions have the potential to be confused with the genuine, gold-standard mutations. Comparing Figures 1A and 2A, we can see that in terms of AF and coverage, there is some overlap between gold-standard and presumed non-mutated sites. The data in Figure 2A also suggests a small number of sites that may be genuine mutations—sites where coverage is high (at least 500bp) and AF is also high (0.5 or more). From this plot, one cannot tell whether different replicates support potential genuine mutations at the same or different sites. We will return to this question later, when we analyze agreement in mutation calls across replicates. Figures 2B-D show similar results for the other three conditions.

3.2 Variant callers disagree greatly under default configurations

We investigated the performance of several popular variant callers in separating the gold-standard mutations from the non-mutated sites, based on our data. For the TST170 data, we report performance of five variant callers: SAMtools [16], VarScan2 [12], MuTect2 [1], VarDict [14] and Pisces [7]. For the Oncomine Focus data, we additional used the online tool offered by Ion Torrent. See Materials and Methods for exact version numbers and other details. These five callers were chosen for different reasons. The SAMtools package is one of the most highly cited programs in all of bioinformatics, and its variant-calling facilities in particular have been used widely. VarScan2 is another highly cited and well-established package for mutation calling. MuTect2 is the latest version of the MuTect program, which won a DREAM somatic genotyping contest [9]. VarDict is a more recent program and has facilities designed specifically for clinical-type sequencing protocols. Finally, we included Pisces and the Ion Torrent tool as the manufacturer-recommended variant callers associated to the two sequencing platforms we employed. Importantly, all are capable of variant calling in a tumor-only mode, and all output VCF files containing SNV calls that can readily be compared to our gold-standard mutation list and to each other.

Figure 2: Distribution of alternative allele frequency and read depth at non-gold-standard mutation sites in the data.

Some clinical sequencing centers have the expertise to carefully tune the bioinformatics tools they employ. Many simply use some established or recommended pipeline with default settings for all parameters and filters. We first compared the variant callers under default settings, as downloaded and/or recommended in their associated publications (see Material and Methods for details). Figure 3 summarizes the results of applying the five variant callers to each of the TST170 samples, while Figure 4 summarizes the results of applying the five variant callers to each of the Oncomine Focus samples. The first and second row of the figures refer to the GM12878 and GM12877 results, respectively.

The barplots in Figure 3A show the number of mutations detected by each of the five callers in each of the six replicates of TST170 data. The highlighted black bars inside the barplots refer to the number of true positives. In immediate observation is that the various programs call wildly different numbers of SNVs from the same datasets. The most extreme is SAMtools, which calls between 128000 and 325000 mutations per replicate, compared to 340-1000 for the other callers. Keeping in mind that the TST170 panel covers just over half a million bases, this is an astonishingly high call rate. This happens because SAMtools's default behavior is more or less to report anything that has any chance of being a mutation. Even a single read with a non-reference basepair is enough to cause SAMtools to flag a site. (We do not intend to criticize SAMtools here, but merely to warn about its default behaviour.) With the depth of coverage in our data and even a relatively low per-base error rate, many positions end up with some non-reference reads. Pisces is the next most profligate caller, reporting on average approximately three times as many sites as in our gold-standard list. At the opposite end of the spectrum, VarDict appears quite strict, calling only a few more sites than expected from the gold-standard. The good news is that all five variant callers correctly call almost all of the gold-standard mutations.

The Venn diagrams in Figures 3B and C break down in more detail the true and fale positive calls of the variant callers, and their agreements with each other, for replicate 1 specifically. The numbers in parenthesis in Figure 3B denote the number of false negatives. In that panel, we see that all five variant callers agree on 340 of the 343 gold-standard mutations, and two more gold-standard mutations are called by all programs except Mutect2. All five programs miss one of the gold-standard mutations. In panel C, we see that although SAMtools calls a very large number of false positives, there remains a small number of false positives called uniquely by other programs. Pisces calls SNVs at 14 sites not called by any other program, and Mutect2 calls three unique SNVs. Varscan does not call any unique false positives, although it shares 104 calls with SAMtools that are not called by any other program. VarDict reports only five false positives, and these five are also reported by every other program. In terms of empirical false discovery rate (EFDR), performance ranges from an excellent 1% for VarDict, to a poor 99.9% for SAMtools.

For GM12877 data (Figure 3D-F) we see similar patterns. In panel D, we see that SAMtools call many possible variants, although not quite as many as for the GM12878 data. VarDict is again the most stringent caller, and others are in between. Figure 3E shows that all five callers agree on 333 of the 336 gold standard mutations, and the remaining three are picked up by four of five callers (Mutect2 misses 2, and VarScan2 misses the other). In

Figure 3: Comparison of five SNV calling approaches on TST 170 data sets using default parameters. (A,D) Numbers of variants called by each algorithm for GM12878 and GM12877 data respectively. (B,E) True positive and detections by the different algorithms on replicate 1 on GM12878 and GM12877. The numbers in parentheses represent total false negatives for each variant caller, i.e., the number of true variants not detected by the corresponding algorithm. (C,F) False positive calls by the different algorithms on replicate 1. Diagrams in this and subsequent figures made using the online tool http://bioinformatics.psb.ugent.be/webtools/Venn/.

Figure 3F we see that, perhaps as a consequence of SAMtools reporting fewer false positives, other programs report more unique false positives. Mutect2 reports over 1000, and Pisces over 100. Even VarDict calls seven false positives not called by any other algorithm. For these data, EFDR ranges from 5% (VarDict) to 99.3% (SAMtools).

Figure 4 presents the analogous results for the Oncomine Focus data. Absolute numbers are generally smaller, because the panel covers fewer total basepairs and fewer gold-standard mutations than the TST170 panel. But qualitative results are very similar. SAMtools calls large numbers of variants, almost all of which are false positives. VarDict calls very few false positives. All algorithms correctly detect most gold-standard mutations. In replicate 1, 25 of 26 for GM12878 (Figure 4B), and 21 of 24 for GM12877 (Figure 4E). Of the four gold-standard mutations not fully agreed-upon, MuTect2 is responsible for missing three and VarDict for missing one. VarDict had only one false over all, while other algorithm had roughly as many false positives and true positives, if not more.

3.3 Harmonizing parameters makes variant calls more similar

Although each variant caller relies on a distinct statistical model, they also filter both inputs and results in various ways. Differences in the default parameters of these filters are an obvious possible explanation for divergent variant calls see above. Thus, we re-analyzed both the TST170 and Oncomine Focus data with the same five algorithms but setting their filtering parameters to be as similar as possible. We set the minimum alternative allele frequency for a called variant to 0.01, the minimum coverage to 10 reads, the minimum base call quality to 20, and the minimum mapping quality to 20. These are not especially restrictive parameter choices, aimed at eliminating false positives calls. Later, we will return to the question of whether more restrictive filtering can improve performance and/or agreement between callers. Here, the focus is on making the filtering criteria of the algorithms as similar as possible.

Figure 5 summarizes the results of SNV calling with the harmonized parameters for the TST170 data sets, and can be compared to Figure 3, where results for default parameters are reported. In panels 5A and 5D, we see that harmonizing parameters greatly reduces the number of variants called by SAMtools. On the GM12878 data, the numbers are roughly on par with the other callers. On the GM12877 data, the numbers are still higher than for other callers, but they are 10 times or more lower than before parameter harmonization. Those panels also show a substantial increase in the number of mutations being called by VarDict. Much of this is due to our lowering of VarDict's alternative allele frequency threshold from the default value of 0.05 to our harmonized value of 0.01. In panels 5B and 5E we see that the five variant callers continue to correctly identify and agree on most of the gold-standard variants. For GM12878, all five callers identify 340 of the 343 variants, and all programs except MuTect2 identify two more. For GM12878 the story is similar, with 333 of 336 fully agreed upon, and two more identified by all programs except MuTect2. The landscape of false positive calls is much different after parameter harmonization, however, as seen in panels 5C and 5F. Of course, there are many fewer false positives, because there are fewer

Figure 4: Comparison of five SNV calling approaches on Oncomine Focus data sets using default parameters. A,D) Numbers of variants called by each algorithm for GM12878 and GM12877 data respectively. (B,E) True positive and detections by the different algorithms on replicate 1 on GM12878 and GM12877. The numbers in parentheses represent total false negatives for each variant caller. (C,F) False positive calls by the different algorithms on replicate 1.

variants being called over all. There are also many more variants being called uniquely by one caller and none of the four others. We also see all five callers agreeing on a total of 10 false positives, across both the GM12878 and GM12877 replicate 1 data, whereas there was only one before parameter harmonization. For GM12878, Pisces has the highest empirical false discovery rate (EFDR) at 64%, while VarDict has the lowest, at 9%. For GM12877 data, SAMtools has the highest EFDR at 91%, while Pisces has the lowest, at 50%.

We see similar overall trends in the Oncomine Focus data, as shown in Figure 6. SAM-tools calls fewer variants after harmonization, while VarDict calls more. Most gold-standard variants are still identified, while false positives are greatly reduced. Still, the numbers of false positives are rather higher than would be desired, particularly for clinical sequencing where accuracy is key.

To further investigate the false positive variant calls, we focused on replicate 1 of each of rthe four conditions (GM12878 and GM12877, sequencing using TST170 or Oncomine Focus panels). Figure 7 shows the false positive called by each algorithm as a function of read coverage and allele frequency. Unsurprisingly, false positives tend to come a lower coverages and/or allele frequencies. However, there is a substantial number of errors at, for example, coverage of 500 or more reads and allele frequency of 0.1 or more, which would normally be considered well-supported. We also see that, for the most part, the errors of the algorithms are intermingled. One algorithm will make an error at a given coverage and allele frequency, while another algorithm avoids that error. Yet the second algorithm will make a different error at a site with similar coverage and allele frequency. Thus, other features besides these two are driving differences in the errors between algorithms. We also see a very small number of sites with high allele frequencies, above 0.4 say, and high coverage, 500 or 1000 reads or more. Again, however, only some algorithms call these variants. From these plots, and comparing to Figure 1, it is clear that stricter thresholding on coverage and/or allele frequency is not a sufficient means to eliminate false positives or eliminate algorithm disagreements. For example, from Figure 7A we observe that to eliminate all false positives we could choose a coverage threshold of 1500 and a minimum allele frequency of 0.25, selecting out the empty upper right corner of the plot. However, from Figure 1A, we see that applying the same thresholds would eliminate from consideration a large number of the gold-standard mutations, resulting in an unacceptable loss of false positives.

Tables 3 to 6 report the complete true positive, false positive, false negative, precision and sensitivity numbers for each algorithm on each dataset, while Figure 8 summarizes precision and sensitivity visually. In terms of sensitivity and precision, there is no absolute winner. In two conditions, the TruSight170 GM12877 data (panel B) and the Oncomine Focus GM12878 data (panel C), Pisces is tied for first in sensitivity while offering higher precision. For the Oncomine Focus Gm12877 data (panel D), it is VarDict that offer the highest precision while still maintaining perfect sensitivity. For the TruSight 170 GM12878 data (panel A), VarDict has the highest average precision but falls slightly short of the sensitivity of Pisces and SAMtools, although these have much lower precision. VarScan has the same (Oncomine) or slightly lower (TruSight 170) sensitivity as Pisces, VarDict and SAMtools, with intermediate precision. MuTect2 misses slightly more gold-standard SNV

Figure 5: Comparison of five SNV calling approaches on TST 170 data sets using harmonized parameters. (A) Numbers of variants called by each algorithm, (B,C) distribution of true positive and false positives detections by the different algorithms. The numbers in parentheses represent total false negatives for each variant caller, i.e., the number of true variants not detected by the corresponding algorithm. (D-F) Same for GM12877.

Figure 6: Comparison of five SNV calling approaches on Oncomine data sets using harmonized parameters. (A) Numbers of variants called by each algorithm, (B,C) distribution of true positive and false positives detections by the different algorithms. The numbers in parentheses represent total false negatives for each variant caller, i.e., the number of true variants not detected by the corresponding algorithm. (D-F) Same for GM12877.

Figure 7: False positive variant calls by each algorithm, as a function of coverage and allele frequency, for replicate 1 of each condition.

Table 3: Variant calling performance with harmonized parameters on TST170-GM12878.

	Rep 1	Rep 2	Rep 3	Rep 4	Rep 5	Rep 6	AvgPrec	AvgSens
MuTect2	341 161 2	337 135 6	339 70 4	340 363 3	340 415 3	340 414 3	0.60117	0.9898
VarScan2	343 342 0	338 202 5	341 239 2	343 293 0	343 262 0	343 272 0	0.56309	0.9966
SAMtools	343 441 0	340 1014 3	342 737 1	343 357 0	343 388 0	343 372 0	0.40742	0.99806
VarDict	343 35 0	340 339 3	342 204 1	343 72 0	342 123 1	343 92 0	0.73084	0.99757
Pisces	343 618 0	340 367 3	342 357 1	343 461 0	343 506 0	343 437 0	0.43291	0.99806

Table 4: Variant calling performance with harmonized parameters on TST170-GM12877.

	Rep 1	Rep 2	Rep 3	Rep 4	Rep 5	Rep 6	AvgPrec	AvgSens
MuTect2	333 1540 3	333 1418 3	331 1091 5	335 962 1	334 1644 2	334 1261 2	0.20621	0.99206
VarScan2	335 827 1	333 861 3	333 740 3	336 1231 0	336 1149 0	335 1093 1	0.2588	0.99603
SAMtools	335 3574 1	334 4085 2	334 4160 2	336 3547 0	336 3135 0	335 4236 1	0.082037	0.99702
VarDict	335 1071 1	334 1184 2	334 1704 2	336 828 0	335 721 1	335 766 1	0.25539	0.99653
Pisces	335 341 1	334 321 2	334 292 2	336 384 0	336 407 0	335 354 1	0.49069	0.99702

than the other algorithms, so ends up with the lowest sensitivity. It has variable precision.

3.4 Intersecting mutation callers' results reduces false positives, while maintaining sensitivity

From Figures 5 and 6, it is clear that each individual mutation caller has reported many false positives. Intersecting at least two mutation callers can remarkably reduce the number of such false positives. For example, the list of known mutations created by [8] applies the same idea to the calls made by FreeBayes, Platypus GATK3 and Strelka. To take an example from our data, in Figure 5C we observe that in replicate 1 of TST170-GM12878, VarDict makes 26 false positive calls that are not made by Pisces, and Pisces makes 609 false positive calls that are not made by VarDict. At the same time, from the corresponding Venn diagram in Figure 5B, it is evident that both callers are able to detect the 343 known mutations. Thus, intersecting these two mutation callers can exclude a significant percentage of the false positives. In fact, it reduces the number of false positives to 9, and an EFDR of just 2.56%. This raises questions such as how many mutation callers should be combined or what are the best combinations of mutation callers in order to get best performance.

We analyzed all the data sets and calculated the performance obtained by intersecting every possible combination of the five programs' SNV calls. Tables 7 to 10 present the results

Table 5: Variant calling performance with harmonized parameters on Oncomine-GM12878.

	Rep 1	Rep 2	Rep 3	AvgPrec	AvgSens
MuTect2	25 30 1	26 21 0	26 16 0	0.54226	0.98718
VarScan2	26 38 0	26 117 0	26 199 0	0.23454	1
SAMtools	26 37 0	26 167 0	26 278 0	0.21098	1
VarDict	26 8 0	26 77 0	26 142 0	0.39063	1
Pisces	26 18 0	26 20 0	26 18 0	0.58235	1

Table 6: Variant calling performance with harmonized parameters on Oncomine-GM12877.

	Rep 1	Rep 2	Rep 3	AvgPrec	AvgSens
MuTect2	22 19 2	23 30 1	22 36 2	0.44995	0.93056
VarScan2	24 22 0	24 25 0	24 23 0	0.50739	1
SAMtools	24 29 0	24 36 0	24 24 0	0.45094	1
VarDict	24 3 0	24 3 0	24 2 0	0.90028	1
Pisces	24 11 0	24 15 0	24 12 0	0.65592	1

Figure 8: Precision and Sensitivity of the five variant callers: MuTect2 (M), SAMtools (S), VarScan (V), Pisces (P) and VarDict (D). Larger circles represent mean precision and sensitivity across replicates, while smaller circles represent performance on individual replicates.

in detail. The numbers in each cell refer to true positives, false positives and false negatives. From the tables, we observe that intersecting exactly two mutation callers leads to an improved performance. For example, for replicate 1 of TST170-GM12878 data, intersecting MuTect2 and VarDict led to 341 true positives and only 11 false positives (with an EFDR of 3%). It seems that interesting VarDict and Pisces leads to the lowest false detection but intersecting VarScan2 and SAMtools, or SAMtools and Pisces, MuTect2 and VarScan2, or MuTect2 and SAMtools leads to many false positives. This may suggest that VarScan2 and SAMtools are not doing the detection job very well. Table 3 also shows that intersecting three of the five mutation callers leads to an improved performance. For example, for replicate 1 of TST170-GM12878 data, combining VarDict, Pisces and SAMtools leads to 343 true detections and 8 false positives (with an EFDR of 2.2%). Intersecting VarDict, Pisces and MuTect2 leads to 341 true detections and 8 false positives (with an EFDR of 2.3%). Analyzing the number of true and false detections in any combination of the mutation callers across all replicates suggests that the combination of VarDict, Pisces and MuTect2 (if the interest is in choosing 3 out 5 callers) or the combination of VarDict and Pisces (if the interest is in choosing 2 out 5 callers) significantly improves the performance compared to each individual caller.

Figure 9 summarizes mean precision and sensitivity for select combinations. Intersecting the results of two or more algorithms cannot increase the number of true positive detections; the number can only stay the same or decrease. Thus, the sensitivity of a combination is no higher than that of its individual algorithms. By ruling out false positives, however, precision can increase. So a combination is good to the extent that it remains at high sensitivity while increasing precision. We see, for example, intersecting SAMtools and Pisces (SP) loses no sensitivity on these datasets, while substantially improving precision. Still, that precision remains between 0.7 and 0.8. The VarDict-Pisces combination (DP) has equal or slightly lower sensitivity (due to VarDict), but much better precision, at over 0.9. Indeed this was the highest-precision pair for all four conditions. We can intersect even more algorithms, including all five, to obtain yet higher precision, but only slightly, and at substantial cost of sensitivity due to the inclusion of MuTect2.

3.5 Replicate analysis increases the accuracy of an individual mutation caller

We also analyzed the data by combining the mutations detected by an individual caller across the replicates. Tables 11 to ?? report true positives, false positives, false negatives. precision and sensitivity when mutations are only accepted when appear in at least N replicates. For example, from Table 11, we observe that for TST170-GM12878 data, when we looked at common mutations detected by MuTect2 in at least two of six replicates, we get 341 TPs, 82 FPs, and 2 FNs. By comparison, the average performance across single replicates was 339.5 TPs, 259.6 FPs, and 3.5 FNs.

Figure 10 summarizes the precision and sensitivity. Requiring mutations to occur in increasing number of replicates N cannot improve sensitivity, but can improve precision.

Table 7: Performance of algorithm combinations on TST170-GM12878 data.

	Rep 1	Rep 2	Rep 3	Rep 4	Rep 5	Rep 6	AvgPrec	AvgSens
MV	341 69 2	336 23 7	339 28 4	340 28 3	340 43 3	340 41 3	0.89923	0.98931
MS	341 70 2	337 25 6	339 29 4	340 27 3	340 46 3	340 40 3	0.8973	0.9898
MD	341 11 2	337 9 6	339 11 4	340 16 3	340 38 3	340 29 3	0.94787	0.9898
MP	341 43 2	337 17 6	339 22 4	340 18 3	340 20 3	340 27 3	0.93328	0.9898
VS	343 311 0	338 180 5	341 224 2	343 245 0	343 228 0	343 231 0	0.59368	0.9966
VD	343 15 0	338 44 5	341 34 2	343 14 0	342 22 1	343 13 0	0.93601	0.99611
VP	343 180 0	338 69 5	341 86 2	343 136 0	343 118 0	343 122 0	0.74711	0.9966
SD	343 23 0	340 279 3	342 144 1	343 26 0	342 51 1	343 40 0	0.81424	0.99757
SP	343 189 0	340 73 3	342 96 1	343 131 0	343 128 0	343 127 0	0.73841	0.99806
DP	343 9 0	340 13 3	342 12 1	343 11 0	342 9 1	343 9 0	0.97024	0.99757
MVS	341 68 2	336 22 7	339 28 4	340 27 3	340 42 3	340 40 3	0.9012	0.98931
MVD	341 11 2	336 7 7	339 10 4	340 6 3	340 11 3	340 9 3	0.9742	0.98931
MVP	341 40 2	336 15 7	339 22 4	340 18 3	340 18 3	340 26 3	0.93662	0.98931
MSD	341 10 2	337 7 6	339 10 4	340 6 3	340 11 3	340 9 3	0.97467	0.9898
MSP	341 39 2	337 16 6	339 22 4	340 18 3	340 19 3	340 26 3	0.93614	0.9898
MDP	341 8 2	337 7 6	339 8 4	340 5 3	340 7 3	340 7 3	0.97981	0.9898
VSD	343 14 0	338 44 5	341 34 2	343 14 0	342 21 1	343 13 0	0.93689	0.99611
VSP	343 172 0	338 62 5	341 84 2	343 122 0	343 111 0	343 113 0	0.75978	0.9966
VDP	343 9 0	338 10 5	341 8 2	343 11 0	342 8 1	343 7 0	0.97481	0.99611
SDP	343 8 0	340 10 3	342 10 1	343 11 0	342 8 1	343 8 0	0.97392	0.99757
MVSD	341 10 2	336 7 7	339 10 4	340 6 3	340 10 3	340 9 3	0.97512	0.98931
MVSP	341 39 2	336 15 7	339 22 4	340 18 3	340 17 3	340 26 3	0.93746	0.98931
MVDP	341 8 2	336 7 7	339 8 4	340 5 3	340 6 3	340 7 3	0.98027	0.98931
MSDP	341 7 2	337 7 6	339 8 4	340 5 3	340 6 3	340 7 3	0.98075	0.9898
VSDP	343 8 0	338 10 5	341 8 2	343 11 0	342 7 1	343 7 0	0.97574	0.99611
MVSDP	341 7 2	336 7 7	339 8 4	340 5 3	340 5 3	340 7 3	0.98121	0.98931

Table 8: Performance of algorithm combinations on TST170-GM12877 data.

	Rep 1	Rep 2	Rep 3	Rep 4	Rep 5	Rep 6	AvgPrec	AvgSens
MV	333 50 3	332 71 4	330 60 6	335 57 1	334 83 2	334 60 2	0.84045	0.99107
MS	333 81 3	333 90 3	331 75 5	335 74 1	334 98 2	334 79 2	0.8013	0.99206
MD	333 273 3	333 295 3	331 303 5	335 206 1	334 240 2	334 225 2	0.56674	0.99206
MP	333 8 3	333 12 3	331 6 5	335 12 1	334 18 2	334 16 2	0.96542	0.99206
VS	335 707 1	333 732 3	333 624 3	336 920 0	336 870 0	335 902 1	0.29985	0.99603
VD	335 91 1	333 117 3	333 191 3	336 110 0	335 83 1	335 87 1	0.75175	0.99554
VP	335 58 1	333 67 3	333 58 3	336 87 0	336 101 0	335 87 1	0.8156	0.99603
SD	335 468 1	334 572 2	334 962 2	336 347 0	335 223 1	335 300 1	0.4439	0.99653
SP	335 78 1	334 88 2	334 73 2	336 114 0	336 113 0	335 116 1	0.77684	0.99702
DP	335 12 1	334 14 2	334 15 2	336 13 0	335 18 1	335 13 1	0.95944	0.99653
MVS	333 50 3	332 70 4	330 59 6	335 55 1	334 79 2	334 58 2	0.8439	0.99107
MVD	333 26 3	332 43 4	330 41 6	335 29 1	334 38 2	334 31 2	0.90594	0.99107
MVP	333 7 3	332 10 4	330 6 6	335 8 1	334 16 2	334 13 2	0.97097	0.99107
MSD	333 45 3	333 52 3	331 50 5	335 36 1	334 44 2	334 36 2	0.88399	0.99206
MSP	333 7 3	333 10 3	331 6 5	335 8 1	334 16 2	334 13 2	0.97099	0.99206
MDP	333 3 3	333 4 3	331 4 5	335 3 1	334 10 2	334 7 2	0.9848	0.99206
VSD	335 90 1	333 117 3	333 190 3	336 109 0	335 83 1	335 84 1	0.75349	0.99554
VSP	335 54 1	333 65 3	333 55 3	336 79 0	336 94 0	335 83 1	0.82476	0.99603
VDP	335 6 1	333 10 3	333 9 3	336 9 0	335 14 1	335 11 1	0.97149	0.99554
SDP	335 9 1	334 12 2	334 12 2	336 11 0	335 16 1	335 12 1	0.96543	0.99653
MVSD	333 26 3	332 43 4	330 40 6	335 28 1	334 38 2	334 30 2	0.90718	0.99107
MVSP	333 7 3	332 10 4	330 6 6	335 8 1	334 16 2	334 13 2	0.97097	0.99107
MVDP	333 3 3	333 4 3	331 4 5	335 3 1	334 10 2	334 6 2	0.98528	0.99206
MSDP	333 3 3	332 4 4	330 4 6	335 3 1	334 10 2	334 6 2	0.98527	0.99107
VSDP	335 6 1	333 10 3	333 9 3	336 9 0	335 14 1	335 11 1	0.97149	0.99554
MVSDP	333 3 3	332 4 4	330 4 6	335 3 1	334 10 2	334 6 2	0.98527	0.99107

Table 9: Performance of algorithm combinations on Oncomine-GM12878 data.

	Rep 1	Rep 2	Rep 3	AvgPrec	AvgSens
MV	25 5 1	26 11 0	26 7 0	0.77464	0.98718
MS	25 5 1	26 11 0	26 8 0	0.76691	0.98718
MD	25 3 1	26 6 0	26 3 0	0.8673	0.98718
MP	25 5 1	26 3 0	26 2 0	0.88615	0.98718
VS	26 35 0	26 115 0	26 174 0	0.24688	1
VD	26 8 0	26 67 0	26 124 0	0.40587	1
VP	26 11 0	26 11 0	26 12 0	0.69654	1
SD	26 8 0	26 67 0	26 107 0	0.41325	1
SP	26 10 0	26 12 0	26 11 0	0.70305	1
DP	26 4 0	26 3 0	26 3 0	0.88659	1
MVS	25 5 1	26 11 0	26 7 0	0.77464	0.98718
MVD	25 3 1	26 6 0	26 3 0	0.8673	0.98718
MVP	25 4 1	26 3 0	26 2 0	0.89573	0.98718
MSD	25 3 1	26 6 0	26 3 0	0.8673	0.98718
MSP	25 4 1	26 3 0	26 2 0	0.89573	0.98718
MDP	25 2 1	26 2 0	26 1 0	0.93915	0.98718
VSD	26 8 0	26 65 0	26 106 0	0.4158	1
VSP	26 10 0	26 11 0	26 11 0	0.70921	1
VDP	26 4 0	26 2 0	26 2 0	0.90794	1
SDP	26 4 0	26 2 0	26 2 0	0.90794	1
MVSD	25 3 1	26 6 0	26 3 0	0.8673	0.98718
MVSP	25 4 1	26 3 0	26 2 0	0.89573	0.98718
MVDP	25 2 1	26 2 0	26 1 0	0.93915	0.98718
MSDP	25 2 1	26 2 0	26 1 0	0.93915	0.98718
VSDP	26 4 0	26 2 0	26 2 0	0.90794	1
MVSDP	25 2 1	26 2 0	26 1 0	0.93915	0.98718

Table 10: Performance of algorithm combinations on Oncomine-GM12877 data.

	Rep 1	Rep 2	Rep 3	AvgPrec	AvgSens
MV	22 1 2	23 4 1	22 3 2	0.89612	0.93056
MS	22 1 2	23 4 1	22 3 2	0.89612	0.93056
MD	22 0 2	23 2 1	22 1 2	0.95884	0.93056
MP	22 1 2	23 5 1	22 3 2	0.88598	0.93056
VS	24 19 0	24 24 0	24 21 0	0.53049	1
VD	24 3 0	24 2 0	24 2 0	0.91168	1
VP	24 5 0	24 7 0	24 8 0	0.78393	1
SD	24 2 0	24 2 0	24 2 0	0.92308	1
SP	24 6 0	24 7 0	24 7 0	0.7828	1
DP	24 2 0	24 2 0	24 1 0	0.93538	1
MVS	22 1 2	23 4 1	22 3 2	0.89612	0.93056
MVD	22 0 2	23 2 1	22 1 2	0.95884	0.93056
MVP	22 1 2	23 4 1	22 3 2	0.89612	0.93056
MSD	22 0 2	23 2 1	22 1 2	0.95884	0.93056
MSP	22 1 2	23 4 1	22 3 2	0.89612	0.93056
MDP	22 0 2	23 2 1	22 1 2	0.95884	0.93056
VSD	24 2 0	24 2 0	24 2 0	0.92308	1
VSP	24 5 0	24 6 0	24 7 0	0.80059	1
VDP	24 2 0	24 2 0	24 1 0	0.93538	1
SDP	24 2 0	24 2 0	24 1 0	0.93538	1
MVSD	22 0 2	23 2 1	22 1 2	0.95884	0.93056
MVSP	22 1 2	23 4 1	22 3 2	0.89612	0.93056
MVDP	22 0 2	23 2 1	22 1 2	0.95884	0.93056
MSDP	22 0 2	23 2 1	22 1 2	0.95884	0.93056
VSDP	24 2 0	24 2 0	24 1 0	0.93538	1
MVSDP	22 0 2	23 2 1	22 1 2	0.95884	0.93056

Figure 9: Mean precision and sensitivity values by individual variant callers and some selected combinations. M, V, S, D and P stands for MuTect2, VarScan2, SAMtools, VarDict and Pisces, respectively. Colored circles refer to individual algorithms, while grey ellipses refer to intersetions of results from the specified algorithms.

Table 11: Performance of intersecting two or more replicates to obtain variant calls on the TST170-GM12878 data. In each cell, the top three numbers are TP, FP and FN. The bottom two numbers are precision and sensitivity.

	≥2 reps	≥3 reps	≥4 reps	≥5 reps	all 6 reps
MuTect2	341 82 2	341 47 2	341 31 2	338 22 5	335 12 8
	0.806 0.994	0.879 0.994	0.917 0.994	0.939 0.985	0.965 0.977
VarScan2	343 304 0	343 216 0	343 148 0	341 114 2	338 80 5
	0.530 1.000	0.614 1.000	0.699 1.000	0.749 0.994	0.809 0.985
SAMtools	343 379 0	343 225 0	343 149 0	342 112 1	340 74 3
	0.475 1.000	0.604 1.000	0.697 1.000	0.753 0.997	0.821 0.991
VarDict	343 24 0	343 11 0	343 8 0	342 7 1	339 6 4
	0.935 1.000	0.969 1.000	0.977 1.000	0.980 0.997	0.983 0.988
Pisces	343 659 0	343 455 0	343 297 0	342 168 1	340 100 3
	0.342 1.000	0.430 1.000	0.536 1.000	0.671 0.997	0.773 0.991

Table 12: Performance of intersecting two or more replicates to obtain variant calls on the TST170-GM12877 data. In each cell, the top three numbers are TP, FP and FN. The bottom two numbers are precision and sensitivity.

	≥2 reps	≥3 reps	≥4 reps	≥5 reps	all 6 reps
MuTect2	335 213 1	334 22 2	334 10 2	333 6 3	329 3 7
	0.611 0.997	0.938 0.994	0.971 0.994	0.982 0.991	0.991 0.979
VarScan2	336 319 0	335 140 1	335 104 1	334 85 2	332 45 4
	0.513 1.000	0.705 0.997	0.763 0.997	0.797 0.994	0.881 0.988
SAMtools	336 1433 0	335 264 1	335 131 1	334 89 2	334 41 2
	0.190 1.000	0.559 0.997	0.719 0.997	0.790 0.994	0.891 0.994
VarDict	336 120 0	335 9 1	335 7 1	334 5 2	333 4 3
	0.737 1.000	0.974 0.997	0.980 0.997	0.985 0.994	0.988 0.991
Pisces	336 511 0	335 324 1	335 187 1	334 107 2	334 53 2
	0.397 1.000	0.508 0.997	0.642 0.997	0.757 0.994	0.863 0.994

Generally, we see that requiring mutations to occur in more than one replicate increases precision without any cost to sensitivity up to some point, but that requiring mutations to occur in too many replicates (including all) can have a substantial sensitivity cost. On the other hand, we can push precision above 0.9, and on most datasets, near to 1.0. VarDict generally performs best in this scenario, occupying the upper right hand corner of the plots, although for the Oncomine-GM12878 dataset, the strict three-way intersection of Pisces results performs identically with the three-way VarDict intersection. (This cannot be seen from the plot, because the Pisces P3 bubble is on top of the VarDict D3 ubble, but the result is apparent from Table 14.) Also importantly, the best performances obtained by the replicate analysis exceed the performance of intersecting different variant callers results. For example, on the TST170-GM12878 data, the best algorithm intersection was VarDict-Pisces, with mean precision 0.935 and sensitivity 1.0. In the replicate analysis, focusing on VarDict results that appear in at least three replicates produces precision 0.977 and sensitivity 1.0.

Table 13: Performance of intersecting two or more replicates to obtain variant calls on the Oncomine-GM12878 data. In each cell, the top three numbers are TP, FP and FN. The bottom two numbers are precision and sensitivity.

	≥2 reps	all 3 reps
MuTect2	26 8 0	25 3 1
	0.765 1.000	0.893 0.962
VarScan2	26 34 0	26 7 0
	0.433 1.000	0.788 1.000
SAMtools	26 48 0	26 11 0
	0.351 1.000	0.703 1.000
VarDict	26 7 0	26 3 0
	0.788 1.000	0.897 1.000
Pisces	26 13 0	26 3 0
	0.667 1.000	0.897 1.000

Table 14: Performance of intersecting two or more replicates to obtain variant calls on the Oncomine-GM12877 data. In each cell, the top three numbers are TP, FP and FN. The bottom two numbers are precision and sensitivity.

	≥2 reps	all 3 reps
MuTect2	23 8 1	21 4 3
	0.742 0.958	0.840 0.875
VarScan2	24 19 0	24 11 0
	0.558 1.000	0.686 1.000
SAMtools	24 27 0	24 16 0
	0.471 1.000	0.600 1.000
VarDict	24 2 0	24 1 0
	0.923 1.000	0.960 1.000
Pisces	24 11 0	24 8 0
	0.686 1.000	0.750 1.000

Figure 10: Precision and sensitivity when each variant caller's results are filtered so that they must appear in at least 2 replicates, or at least 3, etc. Each bubble specifies an algorithm (M=MuTect2, V=VarScan2, S=SAMtools, D=VarDict, P=Pisces) and the minimum number of replicates in which a variant call appears.

4 Conclusions and Future Work

In this work, we have looked at factors contributing to the success of SNV calling in clinical-style samples, including different sequencing platforms, targeting panels, variant callers, and replication. We generally found similar results for the TruSight 170 data sequenced on an Illumina platform and for the Oncomine Focus data sequenced on an Ion Torrent platform. Thus, we concluded that sequencing platform and targeting panel are not major influences on performance, although certainly the two panels offer different coverage of cancer-related genes. We found, as have other groups [21, 10, 29], that different variant callers can disagree widely on the same data. However, we went farther than previous efforts in explaining these differences. First, we found that much can be attributed to various default filtering settings of the algorithms. When harmonized as much as possible, disagreements between algorithms shrinks considerably. Importantly, all five algorithms that we tested—MuTect2, SAMtools, VarScan2, Pisces and VarDict—displayed excellent sensitivity for detecting true mutations. The problem is with false positives. Here we found that, using the old bioinformatics strategy of intersecting results, combining results from multiple mutation callers can eliminate many false positives. Other groups have found similar results in variant calling, using simple intersections or more sophisticated combination methods [2, 3]. Importantly, we found that intersecting the results from multiple biological replicates was an even more powerful way of filtering out false positives while maintaining detection sensitivity. Although a costlier option than running multiple algorithms, more research should be done into the tradeoff between accuracy and cost of this strategy, and whether it is relevant to clinical practice.

Our study is not without limitations. We have focused on just five variant callers, chosen on the basis of offering tumour-only mode, and being publicly available, free to use, easy to install, and robustly running. We also limited ourselves to five variant callers in part because Venn diagrams become essentially unreadable when trying to intersect more than five different sets, and we found visualization by Venn diagrams important in understanding the relationships between algorithms. Still, there are other variant callers that could be tested in similar fashion. Another limitation is that the gold-standard variants we wanted the algorithms to identify were either heterzygous or homozygous in comparison with the hg19 human genome. Thus, their allele frequencies were clustered around 50% or 100%. Other studies have used mixtures of DNA from different cell lines to "create" mutations at lower allele frequencies (e.g. [25]), and better probe the relationship between allele frequency and detectability. We currently have similar efforts under way. That being said, some of our heterzygous mutations were coming in at apparent allele frequencies as low as 0.1 or 0.2, particularly when coverage was lower. So we were able to derive some understanding of the relationships between coverage, allele frequency and detectability. Another of our long-term goals is to apply similar analyses to real lung cancer specimens in which gold-standard mutations have been identified, so that we can assess detection rates specifically for cancer-relevant mutations in real data. Further, we intend to incorporate those results into broader health economic analyses, going beyond mere accuracy to estimate the value of different sequencing platforms, targeting panels, and bioinformatics pipelines to ultimately improving clinical outcomes.

5 Acknowledgements

The Authors wish to acknowledge the technical support of the Ottawa Hospital Research Institute Bioinformatics Facility and StemCore Laboratories for their expert technical assistance. This Project is funded by the Government of Canada through Genome Canada and Ontario Genomics, and by the Government of Ontario.

References

[1] Lei Cai, Wei Yuan, Zhou Zhang, Lin He, and Kuo-Chen Chou. In-depth comparison of somatic point mutation callers based on different tumor next-generation sequencing depth data. *Scientific reports*, 6:36540, 2016.

[2] Maurizio Callari, Stephen-John Sammut, Leticia De Mattos-Arruda, Alejandra Bruna, Oscar M Rueda, Suet-Feung Chin, and Carlos Caldas. Intersect-then-combine approach: improving the performance of somatic variant calling in whole exome sequencing data using multiple aligners and callers. *Genome medicine*, 9(1):35, 2017.

[3] Brandi L Cantarel, Daniel Weaver, Nathan McNeill, Jianhua Zhang, Aaron J Mackey, and Justin Reese. Baysic: a bayesian method for combining sets of genome variants with improved specificity and sensitivity. *BMC bioinformatics*, 15(1):104, 2014.

[4] Mark A DePristo, Eric Banks, Ryan Poplin, Kiran V Garimella, Jared R Maguire, Christopher Hartl, Anthony A Philippakis, Guillermo Del Angel, Manuel A Rivas, Matt Hanna, et al. A framework for variation discovery and genotyping using next-generation dna sequencing data. *Nature genetics*, 43(5):491, 2011.

[5] Dakota Z Derryberry, Matthew C Cowperthwaite, and Claus O Wilke. Reproducibility of snv-calling in multiple sequencing runs from single tumors. *PeerJ*, 4:e1508, 2016.

[6] Eric J Duncavage, Haley J Abel, Philippe Szankasi, Todd W Kelley, and John D Pfeifer. Targeted next generation sequencing of clinically significant gene mutations and translocations in leukemia. *Modern pathology*, 25(6):795, 2012.

[7] Tamsen Dunn, Gwenn Berry, Dorothea Emig-Agius, Yu Jiang, Anita Iyer, Nitin Udar, and Michael Strömberg. Pisces: An accurate and versatile single sample somatic and germline variant caller. In *Proceedings of the 8th ACM International Conference on Bioinformatics, Computational Biology, and Health Informatics*, pages 595–595. ACM, 2017.

[8] Michael A Eberle, Epameinondas Fritzilas, Peter Krusche, Morten Källberg, Benjamin L Moore, Mitchell A Bekritsky, Zamin Iqbal, Han-Yu Chuang, Sean J Humphray, Aaron L Halpern, et al. A reference data set of 5.4 million phased human variants validated by genetic inheritance from sequencing a three-generation 17-member pedigree. *Genome research*, 27(1):157–164, 2017.

[9] Alexander C Huang, Robert J Orlowski, Xiaowei Xu, Rosemarie Mick, Sangeeth M George, Patrick K Yan, Sasikanth Manne, Adam A Kraya, Bradley Wubbenhorst, Liza Dorfman, et al. A single dose of neoadjuvant pd-1 blockade predicts clinical outcomes in resectable melanoma. *Nature medicine*, 25(3):454, 2019.

[10] Su Yeon Kim and Terence P Speed. Comparing somatic mutation-callers: beyond venn diagrams. *BMC bioinformatics*, 14(1):189, 2013.

[11] Daniel C Koboldt, Ken Chen, Todd Wylie, David E Larson, Michael D McLellan, Elaine R Mardis, George M Weinstock, Richard K Wilson, and Li Ding. Varscan: variant detection in massively parallel sequencing of individual and pooled samples. *Bioinformatics*, 25(17):2283–2285, 2009.

[12] Daniel C Koboldt, Qunyuan Zhang, David E Larson, Dong Shen, Michael D McLellan, Ling Lin, Christopher A Miller, Elaine R Mardis, Li Ding, and Richard K Wilson. Varscan 2: somatic mutation and copy number alteration discovery in cancer by exome sequencing. *Genome research*, 22(3):568–576, 2012.

[13] Peter Krusche, Len Trigg, Paul C Boutros, Christopher E Mason, M Francisco, Benjamin L Moore, Mar Gonzalez-Porta, Michael A Eberle, Zivana Tezak, Samir Lababidi, et al. Best practices for benchmarking germline small-variant calls in human genomes. *Nature biotechnology*, 37(5):555, 2019.

[14] Zhongwu Lai, Aleksandra Markovets, Miika Ahdesmaki, Brad Chapman, Oliver Hofmann, Robert McEwen, Justin Johnson, Brian Dougherty, J Carl Barrett, and Jonathan R Dry. Vardict: a novel and versatile variant caller for next-generation sequencing in cancer research. *Nucleic acids research*, 44(11):e108–e108, 2016.

[15] Ben Langmead and Steven L Salzberg. Fast gapped-read alignment with bowtie 2. *Nature methods*, 9(4):357, 2012.

[16] Heng Li, Bob Handsaker, Alec Wysoker, Tim Fennell, Jue Ruan, Nils Homer, Gabor Marth, Goncalo Abecasis, and Richard Durbin. The sequence alignment/map format and samtools. *Bioinformatics*, 25(16):2078–2079, 2009.

[17] Gabor T Marth, Ian Korf, Mark D Yandell, Raymond T Yeh, Zhijie Gu, Hamideh Zakeri, Nathan O Stitziel, LaDeana Hillier, Pui-Yan Kwok, and Warren R Gish. A general approach to single-nucleotide polymorphism discovery. *Nature genetics*, 23(4):452, 1999.

[18] Marcel Martin. Cutadapt removes adapter sequences from high-throughput sequencing reads. *EMBnet. journal*, 17(1):10–12, 2011.

[19] Tony S Mok, Yi-Long Wu, Sumitra Thongprasert, Chih-Hsin Yang, Da-Tong Chu, Nagahiro Saijo, Patrapim Sunpaweravong, Baohui Han, Benjamin Margono, Yukito Ichinose, et al. Gefitinib or carboplatin–paclitaxel in pulmonary adenocarcinoma. *New England Journal of Medicine*, 361(10):947–957, 2009.

[20] Daniel Morgensztern, Siddhartha Devarakonda, Tetsuya Mitsudomi, Christopher Maher, and Ramaswamy Govindan. Mutational events in lung cancer: Present and developing technologies. In *IASLC Thoracic Oncology (Second Edition)*, pages 95–103. Elsevier, 2018.

[21] Jason O'Rawe, Tao Jiang, Guangqing Sun, Yiyang Wu, Wei Wang, Jingchu Hu, Paul Bodily, Lifeng Tian, Hakon Hakonarson, W Evan Johnson, et al. Low concordance of multiple variant-calling pipelines: practical implications for exome and genome sequencing. *Genome medicine*, 5(3):28, 2013.

[22] Ravi K Patel and Mukesh Jain. Ngs qc toolkit: a toolkit for quality control of next generation sequencing data. *PloS one*, 7(2):e30619, 2012.

[23] A Rimmer, H Phan, I Mathieson, G Lunter, and G McVean. Platypus: A haplotype-based variant caller for next generation sequence data, 2013.

[24] Christopher T Saunders, Wendy SW Wong, Sajani Swamy, Jennifer Becq, Lisa J Murray, and R Keira Cheetham. Strelka: accurate somatic small-variant calling from sequenced tumor–normal sample pairs. *Bioinformatics*, 28(14):1811–1817, 2012.

[25] David H Spencer, Manoj Tyagi, Francesco Vallania, Andrew J Bredemeyer, John D Pfeifer, Rob D Mitra, and Eric J Duncavage. Performance of common analysis methods for detecting low-frequency single nucleotide variants in targeted next-generation sequence data. *The Journal of Molecular Diagnostics*, 16(1):75–88, 2014.

[26] Cole Trapnell, Lior Pachter, and Steven L Salzberg. Tophat: discovering splice junctions with rna-seq. *Bioinformatics*, 25(9):1105–1111, 2009.

[27] Kit Man Wong, Thomas J Hudson, and John D McPherson. Unraveling the genetics of cancer: genome sequencing and beyond. *Annual review of genomics and human genetics*, 12:407–430, 2011.

[28] Chang Xu. A review of somatic single nucleotide variant calling algorithms for next-generation sequencing data. *Computational and structural biotechnology journal*, 16:15–24, 2018.

[29] Huilei Xu, John DiCarlo, Ravi Vijaya Satya, Quan Peng, and Yexun Wang. Comparison of somatic mutation calling methods in amplicon and whole exome sequence data. *BMC genomics*, 15(1):244, 2014.