Improving Deconvolution Methods in Biology through Open Innovation Competitions: An Application to the Connectivity Map

Andrea Blasco*[1,2,3], Ted Natoli†[3], Michael G. Endres[1,2], Rinat A. Sergeev[1,2], Steven Randazzo[1,2], Jin H. Paik[1,2], N. J. Maximilian Macaluso[3], Rajiv Narayan[3], Xiaodong Lu[3], David Peck[3], Karim R. Lakhani[1,2,4], and Aravind Subramanian[3]

[1]Laboratory for Innovation Science at Harvard, Cambridge, MA, USA
[2]Harvard Business School, Harvard University, Boston, MA, USA
[3]Broad Institute of Harvard and MIT, Cambridge, MA, USA
[4]National Bureau of Economic Research, Cambridge, MA, USA

Last updated: October 8, 2020

Abstract

Do machine learning methods improve standard deconvolution techniques for gene expression data? This paper uses a unique new dataset combined with an open innovation competition to evaluate a wide range of gene-expression deconvolution approaches developed by 294 competitors from 20 countries. The objective of the competition was to separate the expression of individual genes from composite measures of gene pairs. Outcomes were evaluated using direct measurements of single genes from the same samples. Results indicate that the winning algorithm based on random forest regression outperformed the other methods in terms of accuracy and reproducibility. More traditional gaussian-mixture methods performed well and tended to be faster. The best deep learning approach yielded outcomes slightly inferior to the above methods. We anticipate researchers in the field will find the dataset and algorithms developed in this study to be a powerful research tool for benchmarking their deconvolution methods and a useful resource for multiple applications.

---

*ablasco@hbs.edu
†tnatoli@broadinstitute.org

1 Introduction

A recurring problem in biomedical research is how to isolate signals of distinct populations (cell types, tissues, and genes) from composite measures obtained by a single analyte or sensor. This deconvolution problem often stems from the prohibitive cost of profiling each population separately[1,2] and has important implications for the analysis of transcriptional data in mixed samples[3–6], single-cell data[7], the study of cell dynamics[8], and imaging data[9].

In the context of gene expression analysis, available deconvolution approaches offer several advantages but also have various limitations[3,10]. Machine learning approaches present a promising route towards improvement but implementing and benchmarking these methods can be challenging. A prominent issue is the scarcity of realistic "ground truth" data for training and validation. Existing methods are often trained, and have their results validated, on synthetic data rather than biologically mixed expression data, which are more difficult to generate and evaluate. But even when ground truth data is available, other difficulties arise that may prevent an effective evaluation of machine learning approaches, such as complex parameter optimization which requires substantial experience in more advanced machine learning techniques.

In this paper, we addressed these challenges using an open innovation competition. The goal of the competition was to solve a gene-expression deconvolution problem with application to the Connectivity Map (CMap), a catalog of over 1.3 million human gene-expression profiles[1]. To reach such a massive scale, CMap focuses on a reduced representation of the transcriptome, consisting of approximately 1,000 human genes, called "landmarks." These genes were selected to capture a large portion of the cell's transcriptional state, thus yielding significant cost reductions compared to traditional methods (RNA-sequencing). However, the data-generation technology (a bead-based multiplex assay called L1000) is limited to 500 different bead colors per sample. Hence, to measure 1,000 genes per sample, CMap coupled each of the available bead types with a gene pair, using a k-means algorithm called "dpeak" to separate the expression of 1,000 genes from the 500 bead measurements.

The goal of the competition was to develop methods to improve upon the dpeak algorithm. Examples from past competitions have shown that machine learning algorithms developed through open competitions tend to outperform solutions derived through conventional means[11–13]. Accordingly, we wanted to see if machine learning solutions developed through the contest could yield considerable improvements over the current dpeak algorithm.

We generated a novel dataset for the contest, which is now available online (S1 Data). The dataset consists of a collection of gene-expression profiles for 122 different perturbagens, both short hairpin RNA (shRNA) and compound treatments at multiple replicates, for a total of over 2,200 gene expression experiments. The same set of experiments was profiled twice while varying the detection mode for acquiring the data. Detection varied between a dual procedure (DUO), two genes per bead barcode, and a uni procedure (UNI), one gene per bead barcode. The UNI data served as the ground truth against which deconvolution procedures applied to the DUO data were compared.

The contest lasted 21 days and was run on Topcoder (Wipro, India), a popular crowd-sourcing platform. Competitors had access to both UNI and DUO datasets, which could

be used to inform the development of their deconvolution solutions. Performance evaluation was based on pre-specified metrics of accuracy and computational speed. A prize purse of $23,000 in cash was offered to competitors as an incentive to be divided among the top 9 submissions. To align incentives and prevent problems like overfitting, the cash prizes were awarded based on the performance evaluation on the *holdout* (not seen by the competitors during the competition) subset of the data.

2   Methods

Figure 1 shows a schematic illustration of the contest's main features including a problem statement, the data, and the scoring function used to evaluate submissions.

The contest's problem statement described the deconvolution task and the current solution in detail. The key insight was that the typical distribution of measurements for each gene pair has two peaks, the size of which should reflect the relative proportion of the genes in the sample. L1000 takes full advantage of this statistical property by: (1) pairing genes optimally, trying to maximize the average difference in their expression levels, and (2) mixing genes in a 2:1 proportion, which enables the correct assignment of peaks to each gene within the pair (see Subramanian et al.[1] for details). Then, it uses a deconvolution approach to partition the composite measurements for each profile into k clusters (by minimizing the within-cluster sum of squares) and associate the largest (smallest) cluster to the gene with higher (lower) bead proportion, assigning the cluster's median value to the corresponding gene.

The datasets consisted of six 384-well perturbagen plates, each containing mutually exclusive sets of compound and shRNA treatments (S1 Table and S2 Table show a complete list). Multiple cell lines and perturbagen were used to avoid any potential over-fitting. The compound and shRNA plates were arbitrarily grouped into pairs, and to avoid any potential 'information leakage' each pair was profiled in a different cell line. The resulting lysates were amplified by Ligation Mediated Amplification (LMA, Subramanian et al.[1]). The amplicon was then split and detected in both UNI and DUO detection modes, resulting in three pairs of data generated under comparable circumstances. The training data was available for all the contestants to develop and validate their solutions offline. The testing data was used for submission evaluation during the contest and to populate a live leaderboard. The holdout data was used for final evaluation, thus guarding against over-fitting. Prizes were awarded based on performance on the holdout dataset.

The scoring function combined measures of accuracy and computational speed (S1 Appendix). The accuracy metric was the product of two different metrics. The first was the average genewise Spearman's rank correlation between the deconvoluted expression values and the ground truth. The second was the Area Under the receiver operating characteristic Curve (AUC) in the prediction of extremely modulated genes. Speed was measured by executing each submission on comparable multi-core machines, thus allowing competitors to employ multithreading techniques, and the corresponding score was the average runtime in units of the benchmark runtime.

3 Results

The contest attracted 294 participants who made 820 submissions using a variety of different methods (S1 Table).

3.1 Top four ranked approaches

The winning solution (by a competitor from the United States with a degree in Physics from the University of Kansas) used a random forest algorithm. The algorithm combined predictions from 10 different trees trained on 60 derived data features. These features included a combination of low-peak and high-peak estimates for each gene pair and aggregate measures that are sensitive to systematic bias at the perturbagen, analyte, and plate level.

The second solution (by a competitor from Poland with a Master's degree in Computer Science from the Lodz University of Technology) used the Expectation-Maximization (EM) algorithm to fit a mixture of two log-normal models to the data for each gene pair. Instead of assuming a priori probability (the 2:1 ratio) of assignment to clusters, the algorithm learned it from the data by fitting a plate-wide distribution of cluster sizes.

The third solution (by a competitor from India with a bachelor's degree in Computer Science) was a fast k-means algorithm with a random initialization procedure that tends to avoid local minima and is more robust to extreme outliers.

The fourth solution (by a competitor from Ukraine with a bachelor's degree in Computer Science from the Cherkasy National University) used a Convolutional Neural Network (CNN). This algorithm first filters and transforms the data into a 32-bin histogram for each pair of genes. Then, it uses the U-net architecture[14] to provide an adequate representation of the data. Then, it assigns each of the 32 bins to one of the two genes for each pair and predicts the median value. This final step uses two subnetworks with the same architecture with a mean squared error loss function (instead of the Spearman correlation used for scoring).

For each method, we generated the deconvolution data (DECONV) and the corresponding differential expression (DE) values as in[1]. Performance was then evaluated on the hold-out data.

3.2 Clustering by method and perturbagen type

First, we visually examined the quality of solutions using a two-dimensional t-SNE projection[15], which was run once on each of the entire DECONV and DE datasets.

The DECONV data clustered well by perturbagen type and less by algorithm type (Figure 2), although with some notable commonalities in the predictions generated by similar approaches (Figure 2, **d**). For example, the decision tree regressor (DTR) algorithms had similar 'footprints' in the projection, as do the k-means and Gaussian mixture model (GMM) algorithms.

After the transformation to DE data, however, the t-SNE projection was more homogenous, with no particular clustering by perturbagen and algorithm type (Figure 2, **c**). The

lack of clustering in the DE data was reassuring given standard CMap analysis is performed on DE values.

3.3 Deconvolution accuracy

Then, we assessed the deconvolution accuracy of each approach by looking at the genewise Spearman rank correlation between the UNI and DUO values.

Based on the analysis of the benchmark, we expected: 1) a higher deconvolution accuracy in samples from shRNA experiments than in those from compounds (Figure 3, a), and 2) a higher deconvolution accuracy for genes in high bead-proportion relative to those in low bead-proportion (Figure 3, b). Intuitively, the deconvolution accuracy should be higher in more focused experiments and for genes with a higher number of beads.

On average across all samples, eight out of the top nine ranked approaches (90%) were significantly better than the benchmark (Figure 3, c). However, at a disaggregated level, improvements were significant for the 488 genes in low bead-proportion and not significant for those in high bead-proportion (Figure 3, d-g). Only the winning method achieved significant improvements in accuracy for genes in both high and low bead proportions.

To evaluate the extent to which the winning algorithm outperformed the others, we ranked the top-nine algorithms by the average correlation metric for each gene (1 = highest, 9 = lowest). We then computed the percentage of genes for which a given algorithm was ranked first. The winner was ranked first for 30% of the genes, followed at some distance by the second-placed gaussian-mixture method (20%), and by the CNN method (13%). Thus, the top two submissions combined outperformed the rest for about half of the genes. Even so, all but a few algorithms were the best performers for at least 5% of the genes, suggesting some complementarity between these algorithms.

3.4 Detection of extreme modulations

To evaluate the accuracy at the DE level, we used the detection accuracy of extreme modulations (genes notably up- or down-regulated by perturbation). We used the UNI data with DE values above a threshold as the ground truth; and we evaluated the detection accuracy of each solution by computing the corresponding AUC for each perturbagen type.

The detection accuracy of extreme modulations was generally high for both shRNA and compound samples ($AUC > 0.87$ and $AUC > 0.91$, respectively), with the competitors achieving notable improvements over the benchmark (Figure 4, a). Compared to the benchmark, the winning solution detected about 4,000 less extreme modulations (40,800 and 44,200, respectively), thus being more conservative. However, when we restricted the comparison to extreme modulations detected by UNI as well (thus controlling for detection precision), the winning solution detects about 1,500 more extreme modulations than the benchmark (27,100 and 25,600, respectively), representing a sensible 6% increase in "true" detections.[1]

---

[1]These results are for the dataset with shRNA experiments for which we know the targeted genes. We expect similar results for the dataset of compound experiments.

We complemented the above analysis by using targeted gene knockdown (KD) experiments as the ground truth for a subset of data. These are experiments in which a landmark gene was targeted by an shRNA, and hence we expect to observe a significant decrease in expression for the targeted gene. We evaluated the KD detection accuracy of each solution by computing the corresponding percentage of successful KD genes identified or recalled by the algorithm (defining a successful KD as one gene in which the DE value and the corresponding gene-wise rank in the experiment are less than a given threshold, -2 and 10 respectively). We computed the percentage recall for the UNI data as well, which yielded an estimate of the maximum achievable recall of 0.80. Relative to this level, nearly all algorithms achieved a good recall and precision, with values that were higher than the benchmark solution for all but two methods (Figure 4, b).

3.5 Reduced variation across replicate samples

To evaluate the reproducibility of the results, we leveraged the several replicate samples for each shRNA and compound experiment in our dataset (about 4 and 10 replicates, respectively). We computed the mean gene-wise coefficient of variation (CV) for each method, which is a measure of inter-replicate variability computed as the average ratio between the interquartile range and the median value across all the replicates. Using this measure, we found all solutions achieved significant improvements over the benchmark (Figure 5); and the winning method, which was the most accurate on average, also achieved the lowest inter-replicate variation overall.

3.6 Computational speed

The speed improvements over the benchmark were substantial. While dpeak took about 4-5 minutes per plate, the fastest algorithm took as little as 5 seconds per plate (more than a 60x speedup compared to the benchmark) and the slowest was well below one minute. These speed improvements are not directly attributable to the use of multiple cores, since both the benchmark and contestant algorithms leverage multi-core techniques. We observed no particular trade-off between speed and accuracy.

3.7 Ensembles

Lastly, we assessed the performance of ensembles combining the predictions of different computational methods by taking the median value across all 10 predictions (including the benchmark). By focusing on the subset of the data with shRNA experiments (ignoring the data with compound experiments), the performance in both Spearman correlation and the AUC metrics of the ensemble tended to increase with the number of models involved (Figure 6). However, the maximum performance in both metrics tended to plateau (or even decrease) after combining the results of 3 or more models. This result suggested limited gains from having ensembles, although it may be worth exploring more sophisticated aggregation approaches.

4   Discussion

We created a novel dataset of L1000 profiles for over 120 shRNA and compound experiments with several replicates for a total of 2,200 gene expression profiles of genes measured independently, and in tandem. This dataset constitutes now a public resource (S1 Data) to all the researchers in this area who are interested in testing their deconvolution approaches.

Using an open innovation competition, we collected and evaluated multiple and diverse deconvolution methods. The best approach was based on a random forest, which is a collection of decision tree regressors. This method achieved: (i) the highest global correlation between the ground-truth and the corresponding deconvoluted data, (ii) the lowest inter-replicate variation, and (iii), compared to the benchmark, was able to detect more than a thousand additional extremely modulated genes, while reducing the false positives at the same time. Our analysis further showed that these gains are considerable when the gene populations were sampled in different proportions (here, genes in high and low bead proportions), with the k-means benchmark approach being systematically less accurate because it does little to mitigate the discrepancy in variability between the genes measured with high and low bead proportion.

In addition, the random-forest approach achieved these improvements with only 10 trees on 60 features. Thus, the algorithm is also relatively fast and easy to implement. By comparison, the fastest approach used a more traditional Gaussian mixture model (with plate-level adjustments), which turned out to be less accurate. Hence, and overall, our analysis provided evidence of the tremendous potential of using random-forest methods for deconvolution problems in biology.

5   Acknowledgements

This work was funded by the Eric and Wendy Schmidt Foundation, NASA Center of Collaborative Excellence, and the Kraft Precision Medicine Accelerator & Division of Research and Faculty Development at the Harvard Business School. The CMap competitions were supported in part by the NIH Common Funds Library of Integrated Network-based Cellular Signatures (LINCS) program U54HG006093 and NIH Big Data to Knowledge (BD2K) program 5U01HG008699.

6 Tables and Figures

Figure 1

Schematic illustrating the computational problem, generated data, and scoring function. Panel (**a**) provides a schematic description of the L1000 DUO detection mode and the associated deconvolution problem to be addressed by the contestants. Panel (**b**) shows the data generated for the contest comprising 6 different sets of perturbational experiments with 3 plates of compound (CP) and shRNA treatments (KD) each. Each plate was detected using DUO (2 genes per analyte) and UNI (one gene per analyte) with UNI serving as the ground truth. Contestants were given two plates of data for training their models offline; a second set of two plates was used during the contest for testing and to populate the live leaderboard; and the third set of two was used as holdout to determine the final contestant placements. Panel (**c**) illustrates the accuracy component of the scoring function that was used to evaluate the solutions submitted by the competitors. A solution's overall accuracy score was the product of the genewise Spearman rank correlations with ground truth (DECONV data) and the AUC of extreme modulations (DE data).

Figure 2

Clustering of solutions. Plot of two-dimensional t-SNE projection with all the samples generated by UNI ground truth (GT) and by applying a deconvolution algorithm to DUO data. t-SNE was run once on all deconvolution data (DECONV) and once on all differential-expression (DE) data that include the 2 plates of holdout data, one each containing compound and shRNA treatments. The resulting projections were colored and subset to generate the following panels: **a**, DECONV data colored by perturbagen type; **b**, DECONV data colored by algorithm type; **c**, DE data colored by algorithm type; and **d**, DECONV data colored by algorithm type and stratified by each implementation.

Figure 3

Correlation between ground-truth and deconvolution samples. a, b show the empirical distributions of the median correlation between the ground-truth and the deconvolution data for the holdout plates. The median correlation was computed across all the submissions, including the benchmark. **a** shows the distributions for the samples of shRNA and compound treatments. **b** shows the distributions for the subset of genes in low and high bead proportion. **c, d** show the gene-wise mean and confidence intervals (95%) for the correlation coefficient for each of the top-nine performing solutions and the benchmark (BM). **c** shows the gene-wise mean correlation by implementation for the full sample. **d** shows the gene-wise mean correlation by implementation stratified by perturbagen type and bead proportion.

Figure 4

Detection of extreme modulations and targeted knockdown genes. This figure shows the AUC for the predicted differential expressions (DE data) obtained by the top-nine performing methods and the k-means benchmark (dpeak) and the corresponding ground-truth extreme modulations (as detected in the UNI data) both for the shRNA and compound samples (**a**). It also shows the computed recall and precision of the top-nine methods and the benchmark for the detection of the targeted knockdown genes for a subset of shRNA experiments (**b**).

Figure 5

Variation across replicates for the top-four performing methods and the (dpeak) benchmark. This figure shows the mean coefficient of variation for each compound perturbagen in our sample. The mean coefficient of variation is computed as the average of the ratio between the interquartile-range and the median of the deconvoluted values across 10 replicates. The perturbagens on the x-axis are ordered by increasing mean coefficient of variation of the benchmark and split into separate panels by quantiles to make differences more visible.

Figure 6

Performance of ensembles. This figure shows the performance in the (**a**) correlation metric and (**b**) AUC metric of the ensemble based on the median prediction of all possible combinations of a given size of the top 9 algorithms plus the benchmark. The median performance of the ensemble tends to increase with its size. However, the maximum performance in both metrics tends to plateau (or even decrease) after the ensemble reaches a size equal to 3.

Supporting information

S1 Table

Top-nine performing solutions and benchmark. This table lists the top-nine solutions and the languages and algorithms each used, as well as the average speedup per plate relative to the k-means benchmark.

rank	handle	language	method	category	speedup
1	gardn999	Java	random forest regressor	DTR	17x
2	Ardavel	C++	Gaussian mixture model	GMM	62x
3	mkagenius	C++	modified k-means	k-means	24x
4	Ramzes2	Python/C++	ConvNet	CNN	10x
5	vladaburian	Python/C++	Gaussian mixture model	GMM	7x
6	balajipro	Python/C++	modified k-means	k-means	21x
7	AliGebily	Python	boosted tree regressor	DTR	5x
8	LastEmperor	Python	modified k-means	k-means	7x
9	mvaudel	Java	other	other	55x
benchmark	benchmark	Matlab	k-means	k-means	1x

S2 Table

Compound perturbagens descriptives. This table shows componud perturbagen names (`pert_iname`), unique id (`pert_id`), time of treatment (`pert_itime`), dose (`pert_idose`), and number of replicates (`num_replicates`).

pert_iname	pert_id	pert_itime	pert_idose	num_replicates
abiraterone(cb-7598)	BRD-K50071428	24 h	10 um	11
acalabrutinib	BRD-K64034691	24 h	10 um	11
afatinib	BRD-K66175015	24 h	10 um	11
artesunate	BRD-K54634444	24 h	10 um	11
azithromycin	BRD-K74501079	24 h	10 um	11
betamethasone dipropionate (diprolene)	BRD-K58148589	24 h	10 um	11
CGS-21680	BRD-A81866333	24 h	10 um	11
chelidonine	BRD-K32828673	24 h	10 um	11
clobetasol	BRD-K84443303	24 h	10 um	11
digoxin	BRD-A91712064	24 h	10 um	11
disulfiram	BRD-K32744045	24 h	10 um	10
emetine hcl	BRD-A77414132	24 h	10 um	10
eplerenone	BRD-K19761926	24 h	10 um	11
epothilone-a	BRD-K71823332	24 h	10 um	9
flumetasone	BRD-K61496577	24 h	10 um	11
fluocinolone	BRD-K94353609	24 h	10 um	11
genipin	BRD-K28824103	24 h	10 um	11
hydrocortisone	BRD-K93568044	24 h	10 um	10
hyoscyamine	BRD-K40530731	24 h	10 um	11
indirubin	BRD-K17894950	24 h	10 um	10
L-745870	BRD-K05528470	24 h	10 um	10
nTZDpa	BRD-K54708045	24 h	10 um	11
oligomycin-a	BRD-A81541225	24 h	10 um	11
PRIMA1	BRD-K15318909	24 h	10 um	11
RITA	BRD-K00317371	24 h	10 um	11
spironolactone	BRD-K90027355	24 h	10 um	11
tanespimycin	BRD-K81473043	24 h	10 um	11
tretinoin	BRD-K71879491	24 h	10 um	10
UB-165	BRD-A14574269	24 h	10 um	11
ursolic-acid	BRD-K68185022	24 h	10 um	11
WAY-161503	BRD-A62021152	24 h	10 um	11
ZM-39923	BRD-K40624912	24 h	10 um	11

S3 Table

Short-hairpin (shRNA) perturbagens descriptives. This table shows shRNA perturbagen names (`pert_iname`), unique id (`pert_id`), and number of replicates (`num_replicates`).

pert_iname	pert_id	num_replicates
ABCB6	TRCN0000060320	4
ADI1	TRCN0000052275	4
ALDOA	TRCN0000052504	4
ANXA7	TRCN0000056304	4
ARHGAP1	TRCN0000307776	4
ASAH1	TRCN0000029402	4
ATMIN	TRCN0000141397	4
ATP2C1	TRCN0000043279	4
B3GNT1	TRCN0000035909	4
BAX	TRCN0000033471	4
BIRC5	TRCN0000073718	4
BLCAP	TRCN0000161355	4
BLVRA	TRCN0000046391	4
BNIP3L	TRCN0000007847	4
CALU	TRCN0000053792	4
CCDC85B	TRCN0000242754	4
CCND1	TRCN0000040038	4
CD97	TRCN0000008234	4
CHMP4A	TRCN0000150154	4
CNOT4	TRCN0000015216	4
DDR1	TRCN0000000618	4
DDX10	TRCN0000218747	4
DECR1	TRCN0000046516	4
DNM1L	TRCN0000001097	3
ECH1	TRCN0000052455	4
EIF4EBP1	TRCN0000040206	4
EMPTY_VECTOR	TRCN0000208001	15
ETFB	TRCN0000064432	4
FDFT1	TRCN0000036327	4
GALE	TRCN0000049461	4
GFP	TRCN0000072181	16
GRN	TRCN0000115978	4
GTPBP8	TRCN0000343727	4
HDGFRP3	TRCN0000107348	4
HIST1H2BK	TRCN0000106710	4
IKBKAP	TRCN0000037871	4
INPP4B	TRCN0000230838	4

pert_iname	pert_id	num_replicates
INSIG1	TRCN0000134159	4
ITFG1	TRCN0000343702	3
JMJD6	TRCN0000063340	4
LBR	TRCN0000060460	4
LGMN	TRCN0000029255	4
LPGAT1	TRCN0000116066	4
LSM6	TRCN0000074719	4
MAPKAPK2	TRCN0000002285	4
MAPKAPK3	TRCN0000006154	4
MAPKAPK5	TRCN0000000684	4
MIF	TRCN0000056818	4
MRPL12	TRCN0000072655	4
NT5DC2	TRCN0000350758	4
NUP88	TRCN0000145079	4
PARP2	TRCN0000007933	4
PLCB3	TRCN0000000431	4
POLE2	TRCN0000233181	4
PPIE	TRCN0000049371	4
PRKAG2	TRCN0000003146	4
PSMB10	TRCN0000010833	4
PTPN6	TRCN0000011052	4
RAB11FIP2	TRCN0000322640	4
RALB	TRCN0000072956	4
RHEB	TRCN0000010425	3
RNF167	TRCN0000004100	4
RPN1	TRCN0000072588	4
SLC25A4	TRCN0000044967	4
SNX11	TRCN0000127684	4
STK25	TRCN0000006270	4
STUB1	TRCN0000007525	4
STXBP1	TRCN0000147480	4
SYPL1	TRCN0000059926	4
TATDN2	TRCN0000049828	4
TM9SF3	TRCN0000059371	4
TMEM110	TRCN0000127960	4
TMEM50A	TRCN0000129223	4
trcn0000014632	TRCN0000014632	4
trcn0000040123	TRCN0000040123	4
trcn0000220641	TRCN0000220641	4
trcn0000221408	TRCN0000221408	4
trcn0000221644	TRCN0000221644	4

pert_iname	pert_id	num_replicates
TSKU	TRCN0000005222	4
UGDH	TRCN0000028108	4
USP14	TRCN0000007428	4
USP6NL	TRCN0000253832	4
VAT1	TRCN0000038193	4
VDAC1	TRCN0000029126	4
WIPF2	TRCN0000029833	4
YME1L1	TRCN0000073864	4
ZW10	TRCN0000155335	4

S1 Data

LINK TO DATA REPOSITORY on http://CLUE.io WILL BECOME AVAILABLE AFTER PUBLICATION

S1 Appendix

Scoring function. This appendix describes the scoring function used in the contest to evaluate the performance of the competitors' submissions.

Submissions were scored based on a scoring function that combines measures of accuracy and computational speed. Accuracy measures were obtained by comparing the contestant's predictions, which were derived from DUO data, to the equivalent UNI ground truth data generated from the same samples.

The scoring function combines two measures of accuracy: correlation and AUC, which are applied to deconvoluted ($DECONV$) data and one to differential expression (DE) data, respectively.

DE is derived from DECONV by applying a series of transformations (parametric scaling, quantile normalization, and robust z-scoring) that are described in detail in Subramanian et al.[1]. The motivation for scoring DE data in addition to $DECONV$ is because it is at this level where the most biologically interesting gene expression changes are observed. Of particular interest is obtaining significant improvement in the detection of, so called, "extreme modulations." These are genes that notably up- or down-regulated by perturbation and hence exhibit an exceedingly high (or low) DE values relative to a fixed threshold.

The first accuracy component is based on the Spearman rank correlation between the predicted $DECONV$ data and the corresponding UNI ground truth data.

For a given dataset p, let $M_{\mathrm{DUO},p}$ and $M_{\mathrm{UNI},p}$ denote the matrices of the estimated gene intensities for $G = 976$ genes (rows) and $S = 384$ experiments (columns) under DUO and UNI detection. Compute the Spearman rank correlation matrix, ρ, between the rows of these matrices and take the median of the diagonal elements of the resulting matrix (i.e., the values corresponding to the matched experiments between UNI and DUO) to compute the median correlation per dataset,

$$\mathrm{COR}_p = median(diag(\rho(M_{\mathrm{DUO},p}, M_{\mathrm{UNI},p}))).$$

The second component of the scoring function is based on the Area Under the receiver operating characteristic Curve (AUC) that uses the competitor's DE values at various thresholds to predict the UNI's DE values being higher than 2 ("high") or lower than -2 ("low").

For a given dataset p, let $\mathrm{AUC}_{p,c}$ denote the corresponding area under the curve where $c = \{\mathrm{high}, \mathrm{low}\}$; then, compute the arithmetic mean of the area under the curve per class to obtain the corresponding score per dataset:

$$\mathrm{AUC}_p = (\mathrm{AUC}_{p,\mathrm{high}} + \mathrm{AUC}_{p,\mathrm{low}})/2.$$

These accuracy components were integrated into a single aggregate scores:

$$\mathrm{SCORE} = \mathrm{SCORE}_{\max} \cdot (\max(\mathrm{COR}_p, 0))^2 \cdot \mathrm{AUC}_p \cdot \exp(-T_{\mathrm{solution}}/(3 \cdot T_{\mathrm{benchmark}})),$$

where T_{solution} is the run time for deconvoluting the data in each plate, and $T_{\mathrm{benchmark}}$ is the deconvolution time required by the benchmark dpeak implementation.

S2 Appendix

L1000 Experimental Scheme The L1000 assay uses Luminex bead-based fluorescent scanners to detect gene expression changes resulting from treating cultured human cells with chemical or genetic perturbations [Subramanian 2017]. Experiments are performed in 384-well plate format, where each well contains an independent sample. The Luminex scanner is able to distinguish between 500 different bead types, or colors, which CMap uses to measure the expression levels of 978 landmark genes using two detection approaches.

In the first detection mode, called UNI, each of the 978 landmark genes is measured individually on one of the 500 Luminex bead colors. In order to capture all 978 genes, two detection plates are used, each measuring 489 landmarks. The two detection plates' worth of data are then computationally combined to reconstruct the full 978-gene expression profile for each sample.

By contrast, in the DUO detection scheme two genes are measured using the same bead color. Each bead color produces an intensity histogram which characterizes the expression of the two distinct genes. In the ideal case, each histogram consists of two peaks each corresponding to a single gene. The genes are mixed in a 2:1 ratio, thus the areas under the peaks have a 2:1 ratio (see Figure 1), which enables the association of each peak with the specific gene. The practical advantage of the DUO detection mode is that it uses half of the laboratory reagents as UNI mode, and hence DUO is and has been the main detection mode used by CMap. After DUO detection, the expression values of the two genes are computationally extracted in a process called 'peak deconvolution.' See Subramanian et al. [1] for more details.

References

[1] Aravind Subramanian, Rajiv Narayan, Steven M Corsello, David D Peck, Ted E Natoli, Xiaodong Lu, Joshua Gould, John F Davis, Andrew A Tubelli, Jacob K Asiedu, et al. A next generation connectivity map: L1000 platform and the first 1,000,000 profiles. *Cell*, 171(6):1437–1452, 2017.

[2] Brian Cleary, Le Cong, Anthea Cheung, Eric S Lander, and Aviv Regev. Efficient generation of transcriptomic profiles by random composite measurements. *Cell*, 171(6): 1424–1436, 2017.

[3] Shai S Shen-Orr, Robert Tibshirani, Purvesh Khatri, Dale L Bodian, Frank Staedtler, Nicholas M Perry, Trevor Hastie, Minnie M Sarwal, Mark M Davis, and Atul J Butte. Cell type–specific gene expression differences in complex tissues. *Nature methods*, 7(4): 287, 2010.

[4] Yi Zhong and Zhandong Liu. Gene expression deconvolution in linear space. *Nature methods*, 9(1):8, 2012.

[5] Aaron M Newman, Chih Long Liu, Michael R Green, Andrew J Gentles, Weiguo Feng, Yue Xu, Chuong D Hoang, Maximilian Diehn, and Ash A Alizadeh. Robust enumeration of cell subsets from tissue expression profiles. *Nature methods*, 12(5):453, 2015.

[6] Konstantin Zaitsev, Monika Bambouskova, Amanda Swain, and Maxim N Artyomov. Complete deconvolution of cellular mixtures based on linearity of transcriptional signatures. *Nature communications*, 10(1):2209, 2019.

[7] Yue Deng, Feng Bao, Qionghai Dai, Lani F Wu, and Steven J Altschuler. Scalable analysis of cell-type composition from single-cell transcriptomics using deep recurrent learning. *Nature methods*, 16(4):311, 2019.

[8] Peng Lu, Aleksey Nakorchevskiy, and Edward M Marcotte. Expression deconvolution: a reinterpretation of dna microarray data reveals dynamic changes in cell populations. *Proceedings of the National Academy of Sciences*, 100(18):10370–10375, 2003.

[9] Stephan Preibisch, Fernando Amat, Evangelia Stamataki, Mihail Sarov, Robert H Singer, Eugene Myers, and Pavel Tomancak. Efficient bayesian-based multiview deconvolution. *Nature methods*, 11(6):645, 2014.

[10] Shai S Shen-Orr and Renaud Gaujoux. Computational deconvolution: extracting cell type-specific information from heterogeneous samples. *Current opinion in immunology*, 25(5):571–578, 2013.

[11] Karim R Lakhani, Kevin J Boudreau, Po-Ru Loh, Lars Backstrom, Carliss Baldwin, Eric Lonstein, Mike Lydon, Alan MacCormack, Ramy A Arnaout, and Eva C Guinan. Prize-based contests can provide solutions to computational biology problems. *Nature biotechnology*, 31(2):108, 2013.

[12] Benjamin M Good and Andrew I Su. Crowdsourcing for bioinformatics. *Bioinformatics*, 29(16):1925–1933, 2013.

[13] Andrea Blasco, Michael G. Endres, Rinat A. Sergeev, Anup Jonchhe, N. J. Maximilian Macaluso, Rajiv Narayan, Ted Natoli, Jin H. Paik, Bryan Briney, Chunlei Wu, Andrew I. Su, Aravind Subramanian, and Karim R. Lakhani. Advancing computational biology and bioinformatics research through open innovation competitions. *PLOS ONE*, 14(9): 1–17, 09 2019. doi: 10.1371/journal.pone.0222165. URL `https://doi.org/10.1371/journal.pone.0222165`.

[14] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

[15] Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(Nov):2579–2605, 2008.