15   Prospective rewards enhance motor skill performance and skill coding in LPFC
16   Tyler J. Adkins
17   Taraz G. Lee
18   University of Michigan

41 **Abstract**
42
People are capable of rapid improvements in skill performance when they are presented
with large prospective incentive cues. We investigated this phenomenon by offering
prospective offers of monetary reward to human participants, contingent on their
successful production of discrete motor sequences. We found that people executed
cued motor sequences more quickly and accurately when they were offered large
rewards. Reward offers were associated with elevated activity throughout the brain and
fine-grained patterns in these regions encoded information about sequence identity.
Follow-up analyses provided evidence that sequence-coding in LPFC was enhanced by
reward and related to subsequence performance. This work sheds light on the
neurocognitive mechanisms underlying incentive-motivated skill performance,
suggesting that it may depend critically on executive-control related processes in the
LPFC.
55
56 **Introduction**
57
People perform better when they are highly motivated. In experimental settings,
motivation has been shown to enhance motor skills (Mosberger et al., 2016; Wächter et
al., 2009), working memory (Kennerley and Wallis, 2009; Krawczyk et al., 2007),
attention (Engelmann and Pessoa, 2007), cognitive control (Etzel et al., 2016), model-
based decision-making (Patzelt et al., 2018), and perception (Serences, 2008).
Motivation is often manipulated using prospective cues that involve offers of future
monetary gains or threats of future losses. People are capable of rapid improvements in
skill performance when they are presented with large prospective incentive cues. This
capacity suggests that people update their expectations of future reward prospectively,
leading to more attention and effort being invested in the task, and ultimately increasing
the probability of success (Kool and Botvinick, 2018).
69
Motor skill learning is often studied in the context of motor sequencing tasks such as the
serial reaction time task (SRTT) or the Discrete Sequence Production (DSP) task
(Krakauer et al., 2019). In these tasks, participants train to quickly and accurately
perform specific sequences of finger movements. Early on in skill learning, performance
is slow, effortful, and unstructured and appears to rely heavily on cognitive processes
such as attention and working memory. This is evidenced by the susceptibility of novice
skills to distraction effects (Nissen and Bullemer, 1987), the dependency of skill
acquisition on working memory capacity (Anguera et al., 2011; Seidler et al., 2012), and
the increased activity in brain regions important for cognitive control such as lateral
prefrontal cortex (LPFC) during the performance of novice skills (Grafton et al., 1995;
Schendan et al., 2003; Willingham et al., 2002). After extensive training, however,

previously independent movements that comprise the skill become concatenated and
organized into chunks (Sakai et al., 2003), a process which is accompanied by
measurable changes in skill representation in the primary motor cortex (Diedrichsen and
Kornysheva, 2015; Wiestler and Diedrichsen, 2013) (M1). With sufficient practice, skill
performance becomes automatized, less reliant on cognitive control circuits, and more
reliant on cortical motor regions and the sensorimotor striatum (Dayan and Cohen,
2011). Since novice and well-trained motor skills depend on distinct psychological and
neuronal mechanisms, motivational effects on their performance will also likely depend
on distinct mechanisms. However, no study to date has tested whether the mechanisms
of motivational enhancement are different for novice and well-trained skills.
91
One specific mechanism by which motivation might enhance skill performance is by
enhancing the fidelity of neuronal representations of skill. Several studies show that
motor skills can be decoded from patterns of brain activity using multivariate techniques
such as pattern classification and representational similarity analysis. For example,
discrete motor sequences can be decoded from brain activity before and during
movement (Nambu et al., 2015; Wiestler and Diedrichsen, 2013) and representational
similarity analysis has recently been used to model the structure of motor-skill
representations in a motor planning hierarchy spanning from pre-SMA to M1 (Yokoi and
Diedrichsen, 2019). In the context of a cognitive control task, one recent study showed
that motivation enhances temporary goal representations in the prefrontal cortex and
that this enhancement mediated the effect of motivation on performance (Etzel et al.,
2016). This work suggests that increased motivation may also enhance motor skill
representations, especially if they are still reliant on mechanisms of cognitive control.
However, no study to date has examined this possibility.
106
We administered a discrete sequence production task during functional magnetic
resonance imaging (fMRI) to 30 healthy human participants. Participants trained for 40
trials on one sequence and 200 trials on another and returned 48 hours later to perform
these sequences for prospective rewards ($5, $10, or $30). We found that skill
performance was enhanced for $30 trials compared to $5 trials. Our data revealed a
widespread network of brain areas whose activity scaled linearly with reward
magnitude. From this reward-responsive network, we decoded novice and well-trained
skill identity from patterns of activity preceding movement. This distributed
representation included clusters in M1, SMA, and LPFC. We then examined whether
skill decoding in these ROIs was influenced by reward magnitude. We found that novice
skill decoding in LPFC was enhanced for $30 trials compared to $5 trials and that this
decoding was associated with improved behavior in the upcoming trial. These results
did not hold for the well-trained skill or the other ROIs. These results suggest that the

motivated performance of novice skills depends on enhanced skill coding in LPFC, but
the motivated performance of well-trained skills does not.
122
123   **Results**
124
30 human participants performed a discrete sequence production (DSP) task (Figure 1)
with concurrent fMRI. This task required participants to quickly produce 8-item
sequences of button presses following a cue indicating sequence identity. Participants
trained extensively on one sequence (200 trials) and minimally on another (40 trials).
Two days after training, they returned to perform the practiced sequences with trial-wise
offers of performance-contingent monetary rewards ($5, $10, or $30). To perform the
sequence "successfully", participants had to produce all 8 button presses without error
under an assigned time-limit. Time-limits were calibrated separately for each person
and each sequence based on performance during a warm-up phase in the scanner on
day 2. Our behavioral analyses focused on trial-wise behavioral success and our
neuroimaging analyses focused on trial-wise cue-related activity.
136
137

Figure 1. Discrete sequence production task. To study the effects of motivation on skilled action, participants
performed two 8-item motor sequences for monetary incentives. The diagram above depicts an example trial from the
reward session. Reward and sequence (color) were cued at the start of each trial. Our fMRI analyses focused on
hemodynamic responses to this cue. After a brief delay, the sequence was performed. If it was completed under a
specific time limit, the trial was successful.

Motivation enhanced skilled performance
144
We fit a multilevel logistic regression model to participants' accuracies to test whether
they were more likely to succeed on trials with large rewards ($30) compared to trials
with small rewards ($5). To estimate the effect of reward magnitude on accuracy, we
used Bayesian parameter estimation with weakly informative priors ($\mathcal{N}(0,1)$). Since our
predictors were binary, these priors assigned low prior probabilities to large effects and
high prior probabilities to small effects (especially null effects). We performed Bayesian
null hypothesis testing by examining whether the 90% credible interval (CI) for a
parameter excluded zero. If it did, then there was less than a 5% posterior probability
that the effect was null (or in the opposite direction), which we take as evidence against
the null hypothesis. We use 90% CIs rather than 95% because the former is more
stable than the latter (Kruschke, 2014) and because the 90% CI lets enables easy 1-
tailed null hypothesis testing at the conventional $p < 0.05$.
157
We found evidence that our participants were more likely to succeed in the DSP task on
trials with large rewards compared to trials with small rewards ($\beta = 0.30$, CI = [0.14,
0.45], $p < 0.05$; Figure 2). However, we did not find evidence that accuracy improved on

trials with medium rewards compared to trials with small rewards ($\beta = 0.04$, CI = [-0.12,
0.19], $p > 0.05$). To our surprise, we found evidence that accuracy was higher for the
novice sequence compared to the well-trained sequence ($\beta = 0.23$, CI = [0.01, 0.44], $p <$
0.05). Although the time limits were chosen in part to match accuracy across the two
sequences (see Methods), the time limits of the well-trained sequences were likely too
strict, as evidenced by the disproportionate number of 'too slow' trials for well-trained
sequences (36%) compared to novice sequences (28%). However, we found no
evidence of an interaction between reward and sequence on performance ($p > 0.05$).
These results suggest that offering large performance-contingent rewards motivated
people to perform skilled actions more efficiently.
171
172   *Figure 2. Reward enhanced skill performance.* We tested for effects of prospective reward on skill performance using
173   a Bayesian multilevel logistic regression model. The line plot shows mean skill performance (i.e., DSP success rate)
174   for each reward condition with standard error bars. The density plot shows the posterior probability density over the
175            $5 vs $30 reward effect in our model. The bold blue line is the median parameter estimate, the shaded region
176   indicates the 90% credible interval, and the red dashed lines indicate the point null hypotheses. More than 95% of the
177   posterior estimates were greater than zero, which provides evidence that skill performance was higher on $30 trials
178   compared to $5 trials.

179   *Reward modulated activity in motor planning regions*
180
We first asked which regions of the brain were linearly responsive to motivation (i.e.,
prospective reward value) just prior to movement. We used generalized linear models
(GLM) to estimate the neuronal responses to the sequence/reward cue. To determine
which brain areas were responsive to prospective rewards, we fit GLMs with reward-
magnitude regressors, which predict that the amplitude of the hemodynamic response
in a voxel will increase linearly with reward magnitude. We used a standard 2_{nd} level
analysis to identify brain areas whose activity increased in response to reward at the
group-level. Our group-level inferences assume a cluster-corrected alpha threshold of p
< 0.05.
190
This analysis revealed clusters of reward-related activity in most of the brain regions
that we expected to be engaged during the DSP task, including LPFC, supplementary
motor area (SMA), premotor cortex (PMC), and primary motor cortex (M1).
Unsurprisingly, we also observed clusters of reward-related activity in reward regions
such as the striatum and the pallidum. This analysis provided a reliable map of the brain
regions whose activity was modulated by prospective rewards. Of particular interest to
this study is the finding that many regions involved in motor-skill performance were
responsive to reward, including the primary motor cortex, premotor cortex and prefrontal
cortex.
200

201
202   *Figure 3. Reward-responsive brain areas.* We used GLMs to test for effects of reward on hemodynamic responses to
203   the pre-movement cue. The images above show the results of a group-level analysis of subject-level coefficient
204   maps. For visualization, we used threshold-free cluster correction and projected the results to surface space. The
205   ellipses indicate the approximate locations of our ROIs.

Skill decoding in reward-responsive brain areas

We performed whole-brain MVPA to localize a network of areas whose patterns of
activity contained information about motor skill. Whole-brain MVPA is often performed
using an iterative searchlight approach, however this technique only performs decoding
in small neighborhoods of voxels but does not consider representations distributed
across the cortex. For this reason, we used SpaceNet, a whole-brain multivariate
decoding method that employs spatial priors to produce sparse and clustered coefficient
maps. SpaceNet has been shown to yield higher classification scores and more
interpretable maps than alternative whole brain decoding techniques for classic brain
decoding problems (Baldassarre et al., 2012; Dohmatob et al., 2014; Grosenick et al.,
2013; Michel et al., 2012). In order to uncover regions that contain a dual code for both
motor skill and reward information, we restricted our whole-brain MVPA to voxels that
were reward-responsive at the group level (uncorrected $p < 0.001$) (Figure 3). We
created individualized reward-related masks using a leave-one-subject-out (LOSO)
approach to ensure that feature selection was independent from the MVPA. The
SpaceNet classifiers were trained on coefficient maps from a GLM with trial-wise
regressors predicting a canonical hemodynamic response to cue-onset. We used a
standard 2_{nd} level analysis to identify brain areas that contained information about motor
sequence at the group-level. Our inferences assume a cluster-corrected alpha threshold
of $p < 0.05$.

Our first set of SpaceNet classifiers were trained to predict the identity of the intended
motor sequence from patterns of brain activity preceding movement. At the group level,
these classifiers predicted the intended motor sequence (on a held-out 20% of data)
with a mean accuracy of 0.61 and a standard deviation of 0.12 across subjects (Figure
4a). We found skill representations distributed across the cortex including LPFC, SMA,
and M1 (Figure 4b). Importantly, this analysis considered only voxels that were
responsive to reward magnitude. The regions in Figure 4b therefore simultaneously
respond to changes in motivation and contribute to a representation of the motor skill
being prepared. These findings are consistent with prior work showing converging
reward and action signals in prefrontal areas and motor areas.

Figure 4. Skill coding in reward-responsive brain areas. We trained multivariate classifiers to decode motor sequence
identity from patterns of hemodynamic responses to the pre-movement cue. This analysis only considered voxels that
were responsive to reward (see Figure 3). (a) Box plot of mean SpaceNet decoding accuracies for each subject. (b)

Performance-relevant patterns in reward-responsive brain areas

While information about reward and skill appear to converge in the LPFC, SMA, and

M1, it remains a possibility that these areas have no practical relevance to future

behavior. To test this, we ran a second set of whole-brain classifiers that used patterns

of activity prior to movement to predict whether a participant would be successful in the

forthcoming DSP trial. At the group level, the classifiers predicted future behavioral

performance (on a held-out 20% of data) with a mean accuracy of 0.79 and standard

deviation of 0.09 across subjects. This decoding analysis revealed a more restricted

information map than the analysis of skill decoding, but the map still included

informative clusters in LPFC, SMA, and M1 (Figure 5). These results suggest that the

reward-related regions identified previously are not only responsive to changes in

motivation, but also relevant to future behavior. Furthermore, the information maps from

our two MVPAs (Figures 4 and 5) were found to overlap in LPFC, SMA, and M1. This

conjunction map delineates voxels that (1) respond to changes in motivation, (2) carry

information about motor sequence, and (2) carry information about future behavioral

success. Therefore, we used this conjunctive information map as a mask for our

subsequent ROI analyses.

Figure 5. Performance-prediction with patterns in reward-responsive brain areas. We trained multivariate classifiers to

predict future behavioral success from patterns of hemodynamic responses to the pre-movement cue. This analysis

only considered voxels that were responsive to reward (see Figure 3). (a) Box plot of mean classification accuracies

for each subject. (b) Results of a group-level analysis of subject-level SpaceNet coefficient maps. For visualization,

we used threshold-free cluster correction, spatial smoothing with a 2mm kernel, and projected the results to surface

272   space. The ellipses indicate the approximate locations of our ROIs.

Skill decoding in LPFC predicts improved novice performance

We hypothesized that motivation preferentially enhances skill representations based on

their relevance to future performance. While our whole-brain analysis above revealed a

widely distributed cortical representation of motor skills, we were interested in effects of

motivation on local skill representations in specific ROIs. We therefore performed follow-

up ROI analyses, focusing on skill decoding in lateral prefrontal cortex (LPFC),

supplementary motor area (SMA), and primary motor cortex (M1). We expected that

skill decoding in LPFC would be predictive of behavioral success for the novice skill but

not the well-trained skill. We initialized our ROIs using the multi-modal Glasser atlas

which provided a priori masks (see Methods). Next, we excluded voxels that were *not*
contained in the overlap of our two group-level information maps (Figure 6). This
functional masking was performed using a LOSO approach to ensure that feature
selection was independent from the MVPA.
288
289   *Figure 6.* Conjunction of group-level sequence and performance information maps. This map only includes voxels
290   that were significant in the earlier group analyses of the information maps. We intersect this conjunction map with a
291   priori ROIs to obtain our ROIs for the follow-up decoding analysis.

292
Next, we used linear support vector machines (SVM) to decode motor sequence identity
from patterns of cue-related activity in our ROIs. To ensure that our classifiers had
enough samples to estimate a reliable classification boundary, we used a leave-one-trial
out (LOTO) cross-validation procedure, which provided trial-wise binary decoding
accuracies. Finally, we used multilevel logistic regression models to test whether skill
decoding in our ROIs was predictive of future performance for the novice or well-trained
skills. As with our Bayesian analysis of DSP performance, we estimated posteriors over
parameters and performed null-hypothesis testing using 90% credible intervals.
301
302   This analysis showed that skill decoding in LPFC was more strongly associated with
303   successful performance of novice but not well-trained skills ($\beta = 0.23$, CI = [0.07, 0.40],
304     $p < 0.05$). However, we found no evidence of a relationship between behavior and
305   sequence decoding in SMA or M1 ($p > 0.05$). These results show that skill decoding in
306   LPFC had high utility for novice skills but not well-trained skills.
307
Figure 7. Novice skill decoding in LPFC enhanced novice skill performance. We tested for effects of skill decoding in
LPFC on future skill performance using a Bayesian multilevel logistic regression model. This was the same model
whose results were reported in Figure 2. The line plot shows observed group mean skill performance (i.e., DSP
success rate) for each skill-decoding outcome and each skill (i.e., novice vs well-trained sequences); error bars show
standard errors of subject means. The density plot shows posterior probability density over the decoding by skill-level
interaction effect in the model. The bold blue line is the median estimate, the shaded region is the 90% credible
314   interval, and the red dashed line indicates the point null hypotheses.

315
316
317
318   *Motivation enhanced novice skill decoding in LPFC*
319
The above analysis provided evidence that skill decoding in LPFC was linked to
improved behavior for novice skills only, which suggests that skill representations in
LPFC have high utility for novice skills only. We hypothesized that rewards would
preferentially enhance skill representations that are useful for performance, so we
predicted that motivation (a la reward magnitude) would enhance skill decoding in LPFC
for novice skills but not well-trained skills. To test this, we used the same ROI decoding

data from the previous analysis, but this time we fit multilevel logistic regression models
to trial-wise decoding accuracies (with separate models for each ROI) to test for effects
of reward on skill decoding.
329
We observed a positive effect of motivation on novice skill decoding in LPFC, which was
much stronger than the motivation effect on well-trained skill decoding ($\beta = 0.34$, CI =
[0.15, 0.52], $p < 0.05$). Our analyses of decoding from SMA and M1 returned null
results, suggesting that the skill coding locally in these regions was not affected by
reward. Overall, these results suggest that motivation enhanced novice but not well
trained skill coding in LPFC. This is significant because skill decoding in LPFC is only
behaviorally relevant for the novice skill, suggesting that motivation preferentially
modulated skill representations according to their utility for future performance.
338
Figure 8. Reward enhanced novice skill decoding in LPFC. We tested for effects of reward on skill decoding in LPFC
using a Bayesian multilevel logistic regression model. The line plot shows observed group mean skill decoding (i.e.,
correct classification rate) with standard errors for reward condition and each skill-level (i.e., novice vs well-trained
sequences). The density plot shows posterior probability density over the reward by skill-level interaction effect in the
model. The bold green line is the median estimate, the shaded region is the 90% credible interval, and the red
dashed line indicates the point null hypotheses. 95+% of the posterior was greater than zero, which provides
evidence that the reward ($30 - $5) effect on skill decoding in LPFC was greater for the novice skill compared to the
well-trained skill.
347

Discussion

349
We sought to examine the neural mechanisms that contribute to the motivation-based
enhancement of motor skills. We found that performance on a motor sequencing task
improved as prospective reward values grew larger. When examining cue-related
whole-brain activity just before movement onset, we uncovered distributed patterns of
activity across a relatively large network of regions important for visuo-motor skill that
simultaneously coded for reward value, motor skill identity, and the quality of skill
execution. Importantly, we found a dissociation between the neuronal mechanisms of
incentive-motivated performance of novice and well-trained motor skills. While both
novice and well-trained skills were performed more quickly and accurately on high-value
trials (Figure 2), the underlying changes in brain activity preceding performance was
different for the two skills (Figure 6). Our results suggest that the incentive-motivated
performance of novice motor skills depends on enhanced representations of skill in the
LPFC.
363
364   *Reward modulates a widespread task-relevant network*
365
Our results show that motivation (i.e, prospective reward value) modulated a
widespread task network prior to movement (Figure 3). In these regions, the amplitude

of the hemodynamic response to the cue was larger for high-value trials compared to
low-value trials. This motivation-modulated network included canonical reward regions
such as the striatum (Apicella et al., 1991; Balleine et al., 2007; Delgado, 2007;
Samejima et al., 2005) and ventromedial frontal cortex. However, we also found that
prospective reward magnitude parametrically increased activity in many regions thought
to be involved in motor planning including lateral frontal cortex, premotor cortex, primary
motor cortex, and parietal cortex. This finding is consistent with prior work showing
anticipatory reward modulation in task-relevant brain areas across a variety of both
cognitive and motor tasks (Galaro et al., 2018; Kennerley and Wallis, 2009; Knutson et
al., 2003; Leon and Shadlen, 1999; Marsh et al., 2015; Peterson and Seger, 2013;
Ramakrishnan et al., 2017; Ramkumar et al., 2016; Roesch and Olson, 2004, 2003;
Wallis and Kennerley, 2010; Wallis and Miller, 2003)(Peterson and Seger, 2013; Ramkumar
et al., 2016; Roesch and Olson, 2003)(Galaro et al., 2018; Marsh et al., 2015; Ramakrishnan et
al., 2017; Ramkumar et al., 2016).

Multiplexed code for reward, skill identity, and the quality of performance

To investigate how prospective reward enhances the neural coding of motor skills, we
sought to determine which of these reward-responsive areas specifically carried
information about both the identity and the quality of the upcoming action. Using a
whole-brain decoding technique, we found that distributed patterns of activity across
fronto-parietal cortices, visual cortex, and the striatum simultaneously carried
information about prospective reward value, motor skill identity and the quality of future
performance. Previous studies have shown that reward signals and action signals
converge in including the prefrontal cortex (Cai and Padoa-Schioppa, 2014; FitzGerald
et al., 2012; Hunt et al., 2015; Kargo et al., 2007; McNamee et al., 2015), the striatum
(Cai and Padoa-Schioppa, 2014; FitzGerald et al., 2012; Hunt et al., 2015; Kargo et al.,
2007; McNamee et al., 2015), anterior cingulate cortex (Hayden and Platt, 2010), and
primary motor cortex (Galaro et al., 2018; Ramakrishnan et al., 2017). Our work adds to
these findings by showing that information about reward, skill, and future performance
converge across a more widespread task network, spanning areas specialized for
sensory, cognitive, motor, and affective processing.

Prospective rewards enhance motor skill decoding in LPFC

Our whole-brain analyses showed that motivational signals and preparatory action
representations converge in several brain areas. While such convergence is likely
necessary for motivation to enhance behavior, it is unclear exactly what happens when
these signals converge. One possibility is that motivation enhances cortical skill
representations on which performance depends. We addressed this possibility in follow-

up ROI analyses and found evidence for such enhancement in LPFC, but not in more
downstream regions in the hierarchy of action control (SMA and M1). We quantified the
utility of skill representations in LPFC by estimating the effect of skill decoding on future
behavioral success. Our results show that anticipatory skill decoding in LPFC was more
strongly linked to future performance of novice skills compared to well-trained skills
(Figure 7), indicating that skill representations in LPFC had greater utility for the novice
skill compared to the well-trained skill. This is consistent with the research showing that
novice skill performance depends more on skill-focused attention, working memory, and
planning (Anguera et al., 2011; Doyon et al., 2003; Galaro et al., 2018; Marsh et al.,
2015; Ramakrishnan et al., 2017; Ramkumar et al., 2016; Seidler et al., 2012; Yokoi et
al., 2018).
419
LPFC is perhaps ideally suited to modulate skilled motor behavior due to increases in
motivation. Explicit cueing of sequence a motor sequence as employed in this study
enables advanced motor planning (Diedrichsen and Kornysheva, 2015). Especially
early on in training, cognitive control processes have been shown to aid in the
performance of motor sequencing skills. For example, working memory capacity relates
to the rate of skill learning (Anguera et al., 2011) and novice motor sequencing
performance coincides with increased activity in LPFC (Grafton et al., 1995; Schendan
et al., 2003; Willingham et al., 2002). Performance-contingent rewards can enhance
these control processes. In particular, rewards have been associated with
improvements in the advanced maintenance of goal information (Botvinick and Braver,
2014; Etzel et al., 2016; Jimura et al., 2010). Additionally, prior work has shown that
information about reward and simple action choices converge in LPFC (McNamee et al.,
2015) and that information about prospective rewards is introduced to goal-directed
action networks through LPFC (Ballard et al., 2011) We propose that motivation
facilitates the preferential enhancement of task-relevant representations—that is,
representations that have high utility for future performance (Botvinick and Braver,
2014; Westbrook and Braver, 2015; Yee and Braver, 2018).
437
Crucially, motivation increased the novice skill decoding in LPFC, but not well-trained
skill decoding (Figure 6). This suggests that skill representations in LPFC were
enhanced preferentially in contexts where doing so would be useful for achieving
greater success (i.e., for novice skills). As noted above, prior research has
demonstrated motivational enhancements of representations in PFC (Etzel et al., 2016;
Kargo et al., 2007; Kobayashi et al., 2002; Leon and Shadlen, 1999; Parro et al., 2018;
Watanabe et al., 2002). Our results go beyond this work by showing that this
motivational effect on task coding in PFC generalizes to motor skills. Our findings
support the hypothesis that motivation enhances skill coding in a goal-directed manner,

preferentially amplifying representations that are poised to positively impact future
behavior.
449
However, it must be noted that we did not find any analogous increased skill decoding
for the more highly trained skill despite the fact that behavioral performance showed
similar motivation-based enhancements. We also did not observe any increase in skill
decoding in downstream motor areas (i.e. M1 and SMA) although clearly any skill
enhancement must ultimately involve altered activity in these areas. This study was
focused on skill coding in the neocortex prior to movement because we believed that
processing at this stage would best dissociate novice and well-trained skill performance.
It is possible that enhanced performance for more well-trained skills is supported by
altered processing during the execution period itself. Unfortunately, there were several
factors that made reliably measuring brain activity during movement a challenge. Aside
from simple movement artifacts, the duration of the movement period varied
considerably across time, skill, and participant. Additionally, relatively strict time limits
were necessary to prevent the strategic slowing of execution speed on high reward
trials. This design choice led to a relatively high number of errors during execution,
limiting the number of successfully completed trials that could be used for analysis of
the movement period itself. Nonetheless, it is important to consider the effects of
motivation on brain activity during execution, especially because this may be the locus
of enhancement for skills that depend less on anticipatory cognitive processing (e.g.,
well-trained motor sequences).
469
470   *Further limitations*
471
Our results show that the neuronal mechanisms by which motivation enhances skill
performance differ as a function of skill-level. However, we cannot rule out the
possibility that our decoding analyses merely distinguished neuronal patterns based on
skill-level rather than skill-identity per se. However, we believe that our key theoretical
inferences do not critically depend on this distinction. As discussed above, prior work
has implicated the lateral PFC in the performance and acquisition of relatively novice
motor skills. We show that we can more readily decode the pattern of activity during the
preparation of a novice skill when prospective reward value is higher. Although it is
possible that our classifier was able to distinguish the two motor sequences based on
the differential recruitment of a given region due to differences in expertise, our results
suggest that this distinction was sharpest at higher levels of motivation.
483
Our analyses also focused heavily on decoding skill information from patterns of cortical
activity. We focused on this aspect of our dataset because prior work validated the
approach of measuring cortical skill representations using MVPA (Nambu et al., 2015;

Wiestler and Diedrichsen, 2013; Yokoi et al., 2018; Yokoi and Diedrichsen, 2019) and
because recent work has shown that multivariate decoding from cortex can be affected
by motivation (Etzel et al., 2016; Parro et al., 2018). However, incentive-motivated
performance depends on dynamic coordination between cortical and sub-cortical
systems, as evidenced by the well-documented function of cortico-striatal loops in skill
learning and performance (Dayan and Cohen, 2011; Doyon et al., 2003; Dudman and
Krakauer, 2016; Frank, 2011; Hikosaka et al., 2018; Turner and Desmurget, 2010) and
the convergence of action, reward, and performance information in the striatum in the
present work. Future analyses should examine whether changes in functional
connectivity between the striatum and the cortex drive motivational enhancements of
cortical representations of skill.

Closing remarks

In sum, we provide evidence that both novice and well-trained motor skills are
enhanced by motivation and that a widespread network of visuomotor regions jointly
contain information about motor skill and reward value. We also showed that the
underlying neuronal mechanisms of motivational enhancement differs between novice
and well-trained skills. The motivated performance of novice skills was preceded by
enhanced skill coding in LPFC, but we observed no such relationship for well-trained
skills. This asymmetry likely results from the differential cognitive demands imposed by
novice and well-trained skills, with novice skill performance depending more on
prospective goal representations in WM. We propose that motivation increases the
expected value of deploying sustained attention to skill relevant representations,
thereby increasing their signal to noise ratio and consequently improving behavioral
performance.

Methods

Participants
30 undergraduate students from the University of Michigan participated in this study. All
participants gave written informed consent to participate and were compensated at a
rate of $15 per hour plus cash bonuses for successful performance. All materials and
methods were approved by the University of Michigan Institutional Review Board.

Behavioral task
Participants learned to perform two sequences of eight keypresses. Before each
trial, participants were instructed by a color cue (1.5 s) to perform one of the two
sequences. After a brief delay (2-6 s), participants could perform the instructed

sequence using the A-S-D-F keys. During movement, an array of 4 grey rectangles
(representing the keys) 'lit up' in sequence to remind the participant of which key to
press next. We expected that our participants would rely less on these on-line visual
cues, and more on advanced planning, as learning progressed. In the reward session,
sequence cues were presented concurrently with incentive. We imposed movement
time limits on performance during the reward session, defined as the 70th percentile of
movement times in a warm-up session. Separate time limits were assigned for each
sequence and each participant with a maximum of 3 s, and the time limit was reset to
be stricter each block if participants' accuracy was above 70% on the previous block.
Stimulus orderings for sequence identity and the duration of cue-to-execution intervals
(2-6 s) and inter-trial intervals (2-6s) were optimized to estimate effects of interest using
AFNI's make_random_timing tool by running 5000 iterations of different random
orderings/timings and selecting those explained the most variance in simulated GLM
analyses.
541
542   *Experimental Protocol*
543   The experiment included two sessions on separate days 48 hours apart. In
session one, participants performed eight blocks of 35 trials each. During this training
session, participants performed 200 trials of one sequence ("heavily trained"), 40 trials
of a second sequence ("lightly trained"), and 40 trials of un-cued pseudorandom
sequences ("random"). The identity of each of the two sequences was counterbalanced
across participants. In session two, participants performed 8 blocks of 30 trials, 120
heavily trained trials and 120 lightly trained trials. Session two also introduced monetary
incentives of varying magnitude. Each trial was associated with one of three incentive
magnitudes: $5, $10, or $30. The order of reward values was set to be an m-sequence
to mitigate carryover effects (Buracas and Boynton, 2002). Participants were informed that
a trial would be selected at random at the end of the experiment, and that they would
earn the associated reward provided they performed the target sequence without error
under the time limit. Our metric of task performance therefore incorporated both speed
and accuracy per se.
557
558   *Incentive-behavior analysis*
559   We used a multilevel Logistic regression model with Bayesian parameter
560   estimation to examine the effects of incentive magnitude (r) and skill-level (k) on the
561   probability of behavioral success. This formula can be expressed as follows, where s is
562   a subject ID:
563
564                    $$p(success) \sim 1 + r + k + r * k + (1 + r + k \,|\, s)$$
565

566   The reward variable *r* was coded using a treatment contrast, such that it decomposed
567   into to two binary comparisons: $5 vs $10 and $5 vs $30. The final parenthetical term in
568   the model is the random effects term, which forces the model to estimate the variation in
569   intercepts and main effects across subjects.
570
fMRI acquisition and pre-processing
MR data were acquired with a 3T GE scanner (MR 750) with a 32-channel head
coil. Functional data were obtained using a 1-shot multi-band T_2^*-weighted echo-planar
imaging (EPI) sequence sensitive to blood oxygenation level-dependent (BOLD)
contrast (TR = 1200 msec, TE = 30 msec, flip angle = 70º, 21 cm field of view, in-plane
resolution = 2.4 mm × 2.4 mm, MB acceleration = 3). Each functional volume contained
51 contiguous 2.5 mm-thick axial slices separated by a 0 mm inter- slice gap acquired in
an interleaved manner. Whole-brain T_1-weighted scans were acquired for anatomical
localization. Functional data were realigned to the third volume acquired, slice-time
corrected, and registered to the MNI-152 template using a non-linear warp. Functional
data were smoothed with a 6mm FWHM kernel for the whole-brain univariate analysis
but left unsmoothed for all multivariate analyses (see below).
583
Whole-brain Univariate Analysis
We modeled BOLD responses to the preparatory cue using generalized linear
models (GLM). The preparatory cue conveyed information about the reward that could
be obtained (e.g., "$30") and the sequence that should be performed (e.g., a blue
square for sequence A). One GLM was used to capture the spatially distributed patterns
of brain responses to the cue on each trial. This GLM modeled each trial's response to
the cue as a separate regressor, enabling us to obtain separate coefficient maps for
each trial. The resulting coefficient maps were used as samples in a multivariate
decoding analysis. Motor execution regressors were created by convolving a gamma
function with a square wave starting at movement onset with duration equal to the
movement time. Another GLM was used to measure the extent to which BOLD
responses were larger for larger monetary incentives. This GLM used the same motor
execution regressors, but contained 2 separate regressors for the cue period. One
regressor captured the mean response to the cue, while the other captured parametric
modulation due to reward magnitude. This latter regressor was coded to predict linear
changes in activity with reward magnitude while accounting for the mean response to
the cue. The resulting coefficient maps (one per participant) were fed into a second-
level group analysis which helped us identify the voxels whose activity reliably scaled
with reward magnitude across participants.
603
Whole-brain Multivariate Analysis

We used multivariate pattern analysis (MVPA) localize the areas in the brain that
contained information about the identity of an upcoming action and whether the action
will be performed successfully. Multivariate techniques—such as machine learning
classifiers—are powerful tools for measuring information in the brain, because they are
capable of discovering complex, high-dimensional mappings between spatially
distributed patterns of brain activity and stimuli (or behaviors, or many other things the
brain might contain information about). We performed an initial round of MVPAs using a
SpaceNet classifier, which uses spatial priors and TV-L1 regularization to construct
sparse but blobby coefficient maps. These maps can then be used to perform
classification of whole-brain patterns of activity. When the classifier achieves high out-
of-sample classification accuracy, it's coefficient maps can be interpreted as information
maps specifying which voxels contain information about the class. We ran one round of
SpaceNets to classify patterns according to the motor sequence that was cued (A vs B)
and another set of SpaceNet classifiers which predicted whether the forthcoming trial
would be performed successfully.
The classifiers were run separately on each subject and were given the trial-wise
cue-related activity maps as input. Importantly, these maps were filtered using a binary
mask encoding which voxels were reward responsive. The group map from the
univariate GLM was thresholded at an alpha level of 0.05 and converted to a mask. This
mask was then applied), to exclude from our multivariate decoding analysis the voxels
that were not reliably reward-responsive at the group level. We used a leave-one-
participant-out approach to ensure that the reward-related group maps and masks were
independent from each participant's trial-wise cue-related activity maps. This masking
greatly reduced the dimensionality of the decoding problem and ensured that the
decoders only used voxels that were modulated by incentives. One round of classifiers
constructed maps of voxels that were informative about which motor sequence
participants were preparing to perform (Sequence A vs Sequence B), and another
round of classifiers constructed maps of voxels that were informative of the future
behavioral performance (success vs failure). We fed the resulting maps into a second-
level conjunction analysis, with an alpha cutoff of 0.05, to produce a mask of voxels that
were informative about both action and performance at the group level (Fgure 6).
636
Post-hoc Multivariate Analysis
Next, we took a closer look at the anatomical sub-components of the action and
performance information maps. After conjoining the action and performance information
maps, we intersected the conjunction map with specific anatomical regions of interest,
defined using the multi-modal Glasser atlas (Glasser et al., 2016). We focused here on
the lateral prefrontal cortex (parcel indices: 67, 70, 71, 73, 79, 80, 81, 83, 84, 86),
supplementary motor area (43, 44), and primary motor cortex (8). Next, for each
subject, we performed a leave-one-trial-out cross-validated MVPA using a linear support

vector classifier with default parameters (Pedregosa et al., 2012). The classification
target here was motor sequence (A vs B) and the analysis yielded binary accuracy
scores for each trial, representing whether the motor sequence cued on a trial could be
successfully decoded. Since we obtained decoding performance for each trial, we were
able to test whether sequence decoding was enhanced for trials with large incentives
($30) compared to small incentives ($5). We used multilevel logistic regression models
with Bayesian parameter estimation to test for effects of incentive magnitude on
sequence decoding accuracy in our LPFC, SMA, and M1 ROIs. These models had the
same structure as the model used to test for effects of incentives on behavior.
654
Brain-behavior Analysis
Lastly, we examined the link between brain activity and behavior. We used a
multilevel logistic regression model with Bayesian parameter estimation to model our
participants' behavioral accuracy, defined as performing the correct motor sequence
under the time limit. The model included skill and skill-decoding predictors. This model
was designed to test whether higher sequence decoding accuracy in these regions was
associated with higher behavioral accuracy.
662
663
Bayesian Hyperparameters
We used Bayesian parameter estimation to quantify the size and uncertainty of
various effects in included in various regression models of behavior and brain activity.
We used weakly informative priors (Gelman et al., 2008) on all effects, specified as
normal distributions around zero with standard deviations of one. These priors assign
high probabilities to small effects and low probabilities to large effects. All continuous
predictors were mean-centered and scaled to have standard-deviation of 0.5, putting
them on the same scale as binary predictors and allowing us to responsibly apply the
same N(0,1) priors to all effects (Gelman, 2008). We estimated posteriors on effects
using a No-U-Turn MCMC sampler provided via Stan (Carpenter et al., 2017). All
Bayesian models were specified using the R package brms (Bürkner, 2018, 2017). In
the results section, we report 90% credible intervals (a.k.a. highest density intervals,
uncertainty intervals), as well as well as whether these credible intervals exclude zero.
When a 90% credible interval excludes zero, 95% of the corresponding posterior
probability mass is beyond (greater than or less than) zero. For example, if the 90%
credible interval for a parameter β excludes zero and the median estimate of β is
positive, then $p(\beta > 0 \mid data) > 0.95$ and $p(\beta < 0 \mid data) < 0.05$. For brevity, we report
such cases as simply having $p < 0.05$.
682
683
684

685
686
687   Works Cited
688
689   Anguera JA, Reuter-Lorenz PA, Willingham DT, Seidler RD. 2011. Failure to Engage
690   Spatial Working Memory Contributes to Age-related Declines in Visuomotor Learning.
691   *Journal of Cognitive Neuroscience* **23**:11–25. doi:10.1162/jocn.2010.21451
692
693   Apicella P, Ljungberg T, Scarnati E, Schultz W. 1991. Responses to reward in monkey
694   dorsal and ventral striatum. *Experimental brain research* **85**:491–500.
695   doi:10.1007/BF00231732
696
697   Baldassarre L, Mourão-Miranda J, Pontil M. 2012. Structured Sparsity Models for Brain
698   Decoding from fMRI data. *2012 Second International Workshop on Pattern Recognition*
699   *in NeuroImaging* **1**:5–8. doi:10.1109/PRNI.2012.31
700
701   Ballard IC, Murty VP, Carter MR, MacInnes JJ, Huettel SA, Adcock AR. 2011.
702   Dorsolateral Prefrontal Cortex Drives Mesolimbic Dopaminergic Regions to Initiate
703   Motivated Behavior. *The Journal of Neuroscience* **31**:10340–10346.
704   doi:10.1523/JNEUROSCI.0895-11.2011
705
706   Balleine BW, Delgado MR, Hikosaka O. 2007. The Role of the Dorsal Striatum in
707   Reward and Decision-Making. *The Journal of Neuroscience* **27**:8161–8165.
708   doi:10.1523/JNEUROSCI.1554-07.2007
709
710   Botvinick M, Braver T. 2014. Motivation and cognitive control: from behavior to neural
711   mechanism. *Annual review of psychology* **66**:83–113. doi:10.1146/annurev-psych-
712   010814-015044
713
714   Buracas GT, Boynton GM. 2002. Efficient design of event-related fMRI experiments
715   using M-sequences. *NeuroImage* **16**:801–13. doi:10.1006/nimg.2002.1116
716
717   Bürkner P-C. 2018. Advanced Bayesian Multilevel Modeling with the R Package brms.
718   *The R Journal* **10**:395. doi:10.32614/RJ-2018-017
719
720   Bürkner P-C. 2017. brms : An R Package for Bayesian Multilevel Models Using Stan.
721   *Journal of Statistical Software* **80**. doi:10.18637/jss.v080.i01
722
723   Cai X, Padoa-Schioppa C. 2014. Contributions of Orbitofrontal and Lateral Prefrontal
724   Cortices to Economic Choice and the Good-to-Action Transformation. *Neuron* **81**:1140–

725   1151. doi:10.1016/j.neuron.2014.01.008
726
727   Carpenter B, Gelman A, Hoffman MD, Lee D, Goodrich B, Betancourt M, Brubaker M,
728   Guo J, Li P, Riddell A. 2017. Stan : A Probabilistic Programming Language. *Journal of*
729   *Statistical Software* **76**. doi:10.18637/jss.v076.i01
730
731   Dayan E, Cohen LG. 2011. Neuroplasticity Subserving Motor Skill Learning. *Neuron*
732   **72**:443–454. doi:10.1016/j.neuron.2011.10.008
733
734   Delgado MR. 2007. Reward-related responses in the human striatum. *Annals of the*
735   *New York Academy of Sciences* **1104**:70–88. doi:10.1196/annals.1390.002
736
737   Diedrichsen J, Kornysheva K. 2015. Motor skill learning between selection and
738   execution. *Trends in Cognitive Sciences* **19**:227–233. doi:10.1016/j.tics.2015.02.003
739
740   Dohmatob E, Gramfort A, Thirion B, Varoquaux G. 2014. Benchmarking solvers for TV-
741   L1 least-squares and logistic regression in brain imaging. *Int Workshop Pattern* 1–4.
742   doi:10.1109/PRNI.2014.6858516
743
744   Doyon J, Penhune V, Ungerleider LG. 2003. Distinct contribution of the cortico-striatal
745   and cortico-cerebellar systems to motor skill learning. *Neuropsychologia* **41**:252–62.
746   doi:10.1016/S0028-3932(02)00158-6
747
748   Dudman JT, Krakauer JW. 2016. The basal ganglia: from motor commands to the
749   control of vigor. *Current Opinion in Neurobiology* **37**:158–166.
750   doi:10.1016/j.conb.2016.02.005
751
752   Engelmann JB, Pessoa L. 2007. Motivation sharpens exogenous spatial attention.
753   *Emotion (Washington, DC)* **7**:668–74. doi:10.1037/1528-3542.7.3.668
754
755   Etzel JA, Cole MW, Zacks JM, Kay KN, Braver TS. 2016. Reward Motivation Enhances
756   Task Coding in Frontoparietal Cortex. *Cerebral Cortex* **26**:1647–1659.
757   doi:10.1093/cercor/bhu327
758
759   FitzGerald TH, Friston KJ, Dolan RJ. 2012. Action-Specific Value Signals in Reward-
760   Related Regions of the Human Brain. *The Journal of Neuroscience* **32**:16417–16423.
761   doi:10.1523/JNEUROSCI.3254-12.2012
762
Frank MJ. 2011. Computational models of motivated action selection in corticostriatal
circuits. *Current Opinion in Neurobiology* **21**:381–386. doi:10.1016/j.conb.2011.02.013

Galaro JK, Celnik P, Chib VS. 2018. Motor Cortex Excitability Reflects the Subjective
Value of Reward and Mediates Its Effects on Incentive-Motivated Performance. *The*
Journal of Neuroscience **39**:1236–1248. doi:10.1523/JNEUROSCI.1254-18.2018

Gelman A. 2008. Scaling regression inputs by dividing by two standard deviations.
Statistics in Medicine **27**:2865–2873. doi:10.1002/sim.3107

Gelman A, Jakulin A, Pittau M, Su Y-S. 2008. A weakly informative default prior
distribution for logistic and other regression models. *The Annals of Applied Statistics*
2:1360–1383. doi:10.1214/08-AOAS191

Glasser MF, Coalson TS, Robinson EC, Hacker CD, Harwell J, Yacoub E, Ugurbil K,
Andersson J, Beckmann CF, Jenkinson M, ith S, Essen DC. 2016. A multi-modal
parcellation of human cerebral cortex. *Nature* **536**:171–8. doi:10.1038/nature18933

Grafton S, Hazeltine E, Ivry R. 1995. Functional mapping of sequence learning in
normal humans. *Journal of cognitive neuroscience* **7**:497–510.
doi:10.1162/jocn.1995.7.4.497

Grosenick L, Klingenberg B, Katovich K, Knutson B, Taylor JE. 2013. Interpretable
whole-brain prediction analysis with GraphNet. *NeuroImage* **72**:304–21.
doi:10.1016/j.neuroimage.2012.12.062

Hayden BY, Platt ML. 2010. Neurons in Anterior Cingulate Cortex Multiplex Information
about Reward and Action. *The Journal of Neuroscience* **30**:3339–3346.
doi:10.1523/JNEUROSCI.4874-09.2010

Hikosaka O, Ghazizadeh A, Griggs W, Amita H. 2018. Parallel basal ganglia circuits for
decision making. *Journal of Neural Transmission* **125**:515–529. doi:10.1007/s00702-
017-1691-1

Hunt LT, Behrens TE, Hosokawa T, Wallis JD, Kennerley SW. 2015. Capturing the
temporal evolution of choice across prefrontal cortex. *eLife* **4**:e11945.
doi:10.7554/eLife.11945

Jimura K, Locke HS, Braver TS. 2010. Prefrontal cortex mediation of cognitive
enhancement in rewarding motivational contexts. *Proceedings of the National Academy*
of Sciences **107**:8871–8876. doi:10.1073/pnas.1002007107

Kargo WJ, Szatmary B, Nitz DA. 2007. Adaptation of Prefrontal Cortical Firing Patterns
and Their Fidelity to Changes in Action–Reward Contingencies. *The Journal of*
Neuroscience **27**:3548–3559. doi:10.1523/JNEUROSCI.3604-06.2007
808
809   Kennerley SW, Wallis JD. 2009. Reward-dependent modulation of working memory in
810   lateral prefrontal cortex. *The Journal of neuroscience : the official journal of the Society*
811   *for Neuroscience* **29**:3259–70. doi:10.1523/JNEUROSCI.5353-08.2009
812
813   Knutson B, Fong GW, Bennett SM, Adams CM, Hommer D. 2003. A region of mesial
814   prefrontal cortex tracks monetarily rewarding outcomes: characterization with rapid
815   event-related fMRI. *NeuroImage* **18**:263–272. doi:10.1016/S1053-8119(02)00057-5
816
817   Kobayashi S, Lauwereyns J, Koizumi M, Sakagami M, Hikosaka O. 2002. Influence of
818   Reward Expectation on Visuospatial Processing in Macaque Lateral Prefrontal Cortex.
819   *Journal of Neurophysiology* **87**:1488–1498. doi:10.1152/jn.00472.2001
820
821   Kool W, Botvinick M. 2018. Mental labour. *Nature human behaviour* **2**:899–908.
822   doi:10.1038/s41562-018-0401-9
823
824   Krakauer JW, Hadjiosif AM, Xu J, Wong AL, Haith AM. 2019. Motor Learning.
825   *Comprehensive Physiology* 613–663. doi:10.1002/cphy.c170043
826
827   Krawczyk DC, Gazzaley A, D'Esposito M. 2007. Reward modulation of prefrontal and
828   visual association cortex during an incentive working memory task. *Brain research*
829   **1141**:168–77. doi:10.1016/j.brainres.2007.01.052
830
831   Kruschke J. 2014. Doing Bayesian data analysis: A tutorial with R, JAGS, and Stan ,
832   Academic Press. Academic Press.
833
834   Leon MI, Shadlen MN. 1999. Effect of Expected Reward Magnitude on the Response of
835   Neurons in the Dorsolateral Prefrontal Cortex of the Macaque. *Neuron* **24**:415–425.
836   doi:10.1016/S0896-6273(00)80854-5
837
838   Marsh BT, Tarigoppula VS, Chen C, Francis JT. 2015. Toward an Autonomous Brain
839   Machine Interface: Integrating Sensorimotor Reward Modulation and Reinforcement
840   Learning. *The Journal of Neuroscience* **35**:7374–7387. doi:10.1523/JNEUROSCI.1802-
841   14.2015
842
McNamee D, Liljeholm M, Zika O, O'Doherty JP. 2015. Characterizing the Associative
Content of Brain Structures Involved in Habitual and Goal-Directed Actions in Humans:

A Multivariate fMRI Study. *The Journal of Neuroscience* **35**:3764–3771.
doi:10.1523/JNEUROSCI.4677-14.2015

Michel V, Gramfort A, Eger E, Varoquaux G, Thirion B. 2012. A Comparative Study of
Algorithms for Intra- and Inter-subjects fMRI DecodingMachine Learning and
Interpretation in Neuroimaging, International Workshop, MLINI 2011, Held at NIPS
2011, Sierra Nevada, Spain, December 16-17, 2011, Revised Selected and Invited
Contributions. springer. pp. 1–8. doi:10.1007/978-3-642-34713-9_1

Mosberger AC, de Clauser L, Kasper H, Schwab ME. 2016. Motivational state, reward
value, and Pavlovian cues differentially affect skilled forelimb grasping in rats. *Learning
& memory (Cold Spring Harbor, NY)* **23**:289–302. doi:10.1101/lm.039537.115

Nambu I, Hagura N, Hirose S, Wada Y, Kawato M, Naito E. 2015. Decoding sequential
finger movements from preparatory activity in higher-order motor regions: a functional
magnetic resonance imaging multi-voxel pattern analysis. *European Journal of
Neuroscience* **42**:2851–2859. doi:10.1111/ejn.13063

Nissen M, Bullemer P. 1987. Attentional requirements of learning: Evidence from
performance measures. *Cognitive Psychology* **19**:1–32. doi:10.1016/0010-
0285(87)90002-8

Parro C, Dixon ML, Christoff K. 2018. The neural basis of motivational influences on
cognitive control. *Human Brain Mapping* **39**:5097–5111. doi:10.1002/hbm.24348

Patzelt EH, Kool W, Millner AJ, Gershman SJ. 2018. Incentives Boost Model-Based
Control Across a Range of Severity on Several Psychiatric Constructs. *Biological
Psychiatry* **85**:425–433. doi:10.1016/j.biopsych.2018.06.018

Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, Blondel M,
Müller A, Nothman J, Louppe G, Prettenhofer P, Weiss R, Dubourg V, Vanderplas J,
Passos A, Cournapeau D, Brucher M, Perrot M, Duchesnay É. 2012. Scikit-learn:
Machine Learning in Python. *arXiv*.

Peterson EJ, Seger CA. 2013. Many hats: intratrial and reward level-dependent BOLD
activity in the striatum and premotor cortex. *Journal of neurophysiology* **110**:1689–702.
doi:10.1152/jn.00164.2012

Ramakrishnan A, Byun Y, Rand K, Pedersen CE, Lebedev MA, Nicolelis MA. 2017.
Cortical neurons multiplex reward-related signals along with sensory and motor

information. *Proceedings of the National Academy of Sciences* **114**:E4841–E4850.
doi:10.1073/pnas.1703668114
887
888   Ramkumar P, Dekleva B, Cooler S, Miller L, Kording K. 2016. Premotor and Motor
889   Cortices Encode Reward. *PLOS ONE* **11**:e0160851. doi:10.1371/journal.pone.0160851
890
891   Roesch MR, Olson CR. 2004. Neuronal activity related to reward value and motivation
892   in primate frontal cortex. *Science (New York, NY)* **304**:307–10.
893   doi:10.1126/science.1093223
894
895   Roesch MR, Olson CR. 2003. Impact of Expected Reward on Neuronal Activity in
896   Prefrontal Cortex, Frontal and Supplementary Eye Fields and Premotor Cortex. *Journal*
897   *of Neurophysiology* **90**:1766–1789. doi:10.1152/jn.00019.2003
898
899   Sakai K, Kitaguchi K, Hikosaka O. 2003. Chunking during human visuomotor sequence
900   learning. *Experimental brain research* **152**:229–42. doi:10.1007/s00221-003-1548-8
901
902   Samejima K, Ueda Y, Doya K, Kimura M. 2005. Representation of Action-Specific
903   Reward Values in the Striatum. *Science* **310**:1337–1340. doi:10.1126/science.1115270
904
905   Schendan HE, arl M, Melrose RJ, Stern CE. 2003. An fMRI Study of the Role of the
906   Medial Temporal Lobe in Implicit and Explicit Sequence Learning. *Neuron* **37**:1013–
907   1025. doi:10.1016/S0896-6273(03)00123-5
908
909   Seidler RD, Bo J, Anguera JA. 2012. Neurocognitive Contributions to Motor Skill
910   Learning: The Role of Working Memory. *Journal of Motor Behavior* **44**:445–453.
911   doi:10.1080/00222895.2012.672348
912
913   Serences JT. 2008. Value-based modulations in human visual cortex. *Neuron* **60**:1169–
914   81. doi:10.1016/j.neuron.2008.10.051
915
916   Turner RS, Desmurget M. 2010. Basal ganglia contributions to motor control: a vigorous
917   tutor. *Current Opinion in Neurobiology* **20**:704–716. doi:10.1016/j.conb.2010.08.022
918
919   Wächter T, Lungu OV, Liu T, Willingham DT, Ashe J. 2009. Differential effect of reward
920   and punishment on procedural learning. *The Journal of neuroscience : the official*
921   *journal of the Society for Neuroscience* **29**:436–43. doi:10.1523/JNEUROSCI.4132-
922   08.2009
923
924   Wallis JD, Kennerley SW. 2010. Heterogeneous reward signals in prefrontal cortex.

925   *Current opinion in neurobiology* **20**:191–8. doi:10.1016/j.conb.2010.02.009
926

927   Wallis JD, Miller EK. 2003. Neuronal activity in primate dorsolateral and orbital
928   prefrontal cortex during performance of a reward preference task. *European Journal of*
929   *Neuroscience* **18**:2069–2081. doi:10.1046/j.1460-9568.2003.02922.x
930

931   Watanabe M, Hikosaka K, Sakagami M, Shirakawa S. 2002. Coding and monitoring of
932   motivational context in the primate prefrontal cortex. *The Journal of neuroscience : the*
933   *official journal of the Society for Neuroscience* **22**:2391–400.
934   doi:10.1523/JNEUROSCI.22-06-02391.2002
935

936   Westbrook A, Braver TS. 2015. Cognitive effort: A neuroeconomic approach. *Cognitive,*
937   *affective & behavioral neuroscience* **15**:395–415. doi:10.3758/s13415-015-0334-y
938

939   Wiestler T, Diedrichsen J. 2013. Skill learning strengthens cortical representations of
940   motor sequences. *eLife* **2**:e00801. doi:10.7554/eLife.00801
941

942   Willingham DB, Salidis J, Gabrieli JD. 2002. Direct Comparison of Neural Systems
943   Mediating Conscious and Unconscious Skill Learning. *Journal of Neurophysiology*
944   **88**:1451–1460. doi:10.1152/jn.2002.88.3.1451
945

946   Yee DM, Braver TS. 2018. Interactions of motivation and cognitive control. *Current*
947   *Opinion in Behavioral Sciences* **19**:83–90. doi:10.1016/j.cobeha.2017.11.009
948

949   Yokoi A, Arbuckle SA, Diedrichsen J. 2018. The Role of Human Primary Motor Cortex in
950   the Production of Skilled Finger Sequences. *Journal of Neuroscience* **38**:1430–1442.
951   doi:10.1523/JNEUROSCI.2798-17.2017
952

953   Yokoi A, Diedrichsen J. 2019. Neural Organization of Hierarchical Motor Sequence
954   Representations in the Human Neocortex. *Neuron* **103**:1178-1190.e7.
955   doi:10.1016/j.neuron.2019.06.017
956

Sequence Identity Cue

$10 ▮ 1.5 s

2-6 s

DSP Task Execution

Stimulus-Response
Mapping

Variable ITI

+ 2-6 s

Lateral

M1

LPFC

Left

Right

SMA

Medial

Lateral

M1

Left   *Right*

LPFC

SMA

Medial