A hierarchical clustering and data fusion approach for disease subtype discovery

Bastian Pfeifer[1*] and Michael G. Schimek[1*]

1 Research Unit of Statistical Bioinformatics, Institute for Medical Informatics, Statistics and Documentation, Medical University, Graz, Austria

* bastian.pfeifer@medunigraz.at, michael.schimek@medunigraz.at

Abstract

Recent advances in multi-omics clustering methods enable a more fine-tuned separation of cancer patients into clinical relevant clusters. These advancements have the potential to provide a deeper understanding of cancer progression and may facilitate the treatment of cancer patients. Here, we present a simple hierarchical clustering and data fusion approach, named *HC-fused*, for the detection of disease subtypes. Unlike other methods, the proposed approach naturally reports on the individual contribution of each single-omic to the data fusion process. We perform multi-view simulations with *disjoint* and *disjunct* cluster elements across the views to highlight fundamentally different data integration behaviour of various *state-of-the-art* methods. *HC-fused* combines the strengths of some recently published methods and shows good performance on real world cancer data from the TCGA (The Cancer Genome Atlas) database. An R implementation of our method is available on GitHub (*pievos101/HC-fused*).

1 Introduction

The analyses of multi-omic data has great potential to improve disease subtyping of cancer patients and may facilitate personalized treatment [1, 2]. While single-omic studies have been conducted extensively in the last years, multi-omics approaches taking into account data from different biological layers, may reveal more fine-grained insights on the systems-level. However, the analyses of data sets from different sources like DNA sequences, RNA expression, and DNA methylation brings great challenges to the computational biology community. One of the major goals in integrative analysis is to cluster patients based on features from different biological layers to identify disease subtypes with enriched clinical parameters. Integrative clustering can be divided into two groups. Horizontal integration on the one side, which is the aggregation of the same type of data, and vertical integration on the other side, which concerns the analyses of heterogeneous omics data sets for the same group of patients [3]. In addition to this classification, one distinguishes between early and late integration approaches. Late integration-based methods first analyze each omics data set separately and then concatenate the information of interest to a global view. Early integration first concatenates the data sets and then performs the data analysis.

In vertical integration tasks, one major problem is that the data sets are often highly diverse with regard to their probabilistic distributions. Thus, simply concatenating them and applying single-omics tools is most likely to bias the results. Another issue arises when the number of features differs across the data sets with the effect that more

importance is assigned to a specific single-omics input. The recent years have seen a wide range of methods that aim to tackle some of these problems. Most prominent is *SNF* (*Similar Network Fusion*) [4]. For each data type it models the similarity between patients as a network and then fuses these networks via an interchanging diffusion process [4]. Spectral clustering is applied to the fused network to infer the final cluster assignments. An extension of this method is called *NEMO* and was recently introduced in [5]. It provides solutions to spatial data and implements a modified *eigen-gap* method [6] to infer the optimal number of clusters. *SNF* was also improved in [7]. Its authors present a method called *rMKL-LPP* which makes use of dimension reduction via multiple kernel learning [8]. They take overfitting into account via a regularization term.

Spectrum [9] is another recently published multi-omics clustering method and R-package. It also performs spectral clustering but provides a data integration method which is significantly different from *NEMO* and *SNF*. In addition, *Spectrum* provides a novel method to infer the optimal number of clusters k based on eigenvector distribution analyses. Statistical solutions for the clustering of heterogeneous data sets are introduced by [10]. In their approach (*iClusterPlus*) the authors simultaneously regress the observations from different genomic data types under their proper distributional assumptions to a common set of latent variables [10]. A computational intensive Monte-Carlo Newton-Raphson algorithm is used to estimate the parameters. Also, a fully Bayesian version of *iClusterPlus* was recently put forward in [11]. A number of additional techniques have been developed as outlined in [12]. One of these techniques is called *PINSPlus* [13,14]. Its authors suggest to systematically add noise to the data sets and to infer the best number of clusters based on the stability against this noise. When the best k (number of clusters) is detected, connectivity matrices are formulated and a final agreement matrix is derived for a standard clustering method.

In this article we introduce a new method called *HC-fused* for hierarchical data fusion and integrative clustering. First we cluster each data type with a standard hierarchical clustering algorithm. We than form network structured views of the omics data sets, and finally apply a novel approach to combine these views via a hierarchical data fusion algorithm. In contrast to other methods, *HC-fused* naturally reports on the contribution of the views to the data fusion process. Its advantage is the adoption of simple data analytic concepts with the consequence that results can be easily interpreted.

2   Materials and methods

2.1   Data preprocessing

Data normalization and imputation is done as suggested by [4]. When a patient has more than 20% missing values we do not consider this patient in further investigations. When a specific feature has more than 20% missing values across the patients, we remove this feature from further investigation. The remaining missing values are imputed with the k-Nearest Neighbor method (kNN). Finally, the normalization is performed as folllows:

$$\hat{f} = \frac{f - E(f)}{\sqrt{Var(f)}}, \tag{1}$$

where f is a biological feature.

2.2 Transforming the views into network structured data

Given is a set of data views $\mathbf{V}_1, \mathbf{V}_2, \ldots, \mathbf{V}_l \in \mathbb{R}^{m \times n}$, where m is the number of observations (e.g. patients), and n is the number of biological features. We transform these views into connectivity matrices $\mathbf{G}_1, \mathbf{G}_2, \ldots, \mathbf{G}_l \in \{0, 1\}^{m \times m}$. This is done by clustering the views with a hierarchical clustering algorithm using Ward's method [15]. We then infer the best number of clusters k via the silhouette coefficient. The produced matrices $\mathbf{G}_1, \mathbf{G}_2, \ldots, \mathbf{G}_l$ are binary matrices with entry 1 when two elements are connected (being in the same cluster), and 0 otherwise. In addition, we construct a $\mathbf{G}_\wedge$ matrix as follows:

$$\mathbf{G}_\wedge = \mathbf{G}_1 \wedge \mathbf{G}_2 \wedge \ldots \wedge \mathbf{G}_l. \tag{2}$$

The matrix $\mathbf{G}_\wedge$ reflects the connectivity between patients confirmed by all views.

2.3 Generating the fused distance matrix P

For data fusion we apply a bottom-up hierarchical clustering approach to the binary matrices $\mathbf{G}$. Initially, the patients are assigned to their own cluster and in each iteration two cluster ($c_x \in C$ and $c_y \in C$) with minimal distance (d_{min}) fuse until just a single cluster remains. The distance between two clusters is calculated as follows:

$$d(c_x, c_y) = \frac{\#0_{\mathbf{G}[c_x, c_y]}}{\#1_{\mathbf{G}[c_x, c_y]} + \#0_{\mathbf{G}[c_x, c_y]}}, \tag{3}$$

where $\#$ means count. In case of binary entries we calculate the Euclidean distance.

In our approach, a fusion event between two cluster is denoted as $(c_x + c_y)$ or $fuse(c_x, c_y)$. In each iteration the algorithm is allowed to use the distances from any given binary matrix $\mathbf{G}_1, \mathbf{G}_2, \ldots, \mathbf{G}_l, \mathbf{G}_\wedge$. We refer to $\mathbf{G}_{min}$ as the matrix containing the minimal distance, where $min \in 1 \ldots l, \wedge$. In cases where the minimal distance is shared by multiple matrices we give preference to fusing the clusters in $\mathbf{G}_\wedge$. During the fusion process we count how many times a patient pair (i, j) occurs in the same cluster. This information is captured in the fused distance matrix $\mathbf{P} \in \mathbb{R}^{m \times m}$.

$$\mathbf{P}(i, j) = \sum_k \mathbb{1}((i, j) \in C), \tag{4}$$

where $\mathbb{1}$ is the indicator function.

Finally, the matrix $\mathbf{P}$ is normalized by its maximal entry. The distance matrix $\mathbf{P}$ can be used as an input for any clustering algorithm. Currently we apply agglomerative hierarchical clustering using Ward's method [15] as implemented in [16].

2.4 Contribution of the views to the data fusion

We define matrices $\mathbf{S}_1, \mathbf{S}_2, \ldots, \mathbf{S}_l, \mathbf{S}_\wedge \in \mathbb{R}^{m \times m}$ providing information about the contribution of the views to data fusion process, and have

$$\mathbf{S}(i, j) = \sum_k \mathbb{1}(i, j \in (c_x + c_y)). \tag{5}$$

We count how many times a patient is member of a fusion process $(c_x + c_y)$ and in what view the fusion is executed. It should be noted, however, that in each fusion step there might occur multiple minimal distances across the views. In that case we randomly pick one item and thus the algorithm needs to be run multiple times in order to get an adequate estimate of the view-specific contributions to data fusion. We introduce the parameter `HC.iter` which is set to a minimum limit of 10 as a default.

Algorithm 1: Data fusion with hierarchical clustering

Given the network views $\mathbf{G}_1, \mathbf{G}_2, \ldots, \mathbf{G}_l, \mathbf{G}_\wedge$;
$\#cluster = \#patients$;
$k = \#cluster$;
while $k \neq 0$ **do**
$d_1 = dist(c_x, c_y | \mathbf{G}_1)$;
$d_2 = dist(c_x, c_y | \mathbf{G}_2)$;
$\vdots$
$d_l = dist(c_x, c_y | \mathbf{G}_l)$;
$d_\wedge = dist(c_x, c_y | \mathbf{G}_\wedge)$;
if $min(d_1, d_2, \ldots, d_l, d_\wedge) == d_\wedge$ **then**
$d_{min} = d_\wedge$;
$fuse(c_x, c_y | \mathbf{G}_{min}, d_{min})$;
$\mathbf{S}_{min}(i, j \in (c_x + c_y)) ++$;
else
$d_{min} = min(d_1, d_2, \ldots, d_l)$;
$fuse(c_x, c_y | \mathbf{G}_{min}, d_{min})$;
$\mathbf{S}_{min}(i, j \in (c_x + c_y)) ++$;
end
$\mathbf{P}((i, j) \in C) ++$;
$k - -$;
end

2.5   Simulation 1: Disjoint inter-cluster elements

In a first simulation we generate two data views represented as numerical matrices ($\mathbf{V}_1 \in \mathbb{R}^{m \times n}$ and $\mathbf{V}_2 \in \mathbb{R}^{m \times n}$). The first matrix reflects three clusters, sampled from Gaussian distributions ($c_1 = \mathcal{N}(-10, \sigma), c_2 = \mathcal{N}(0, \sigma), c_3 = \mathcal{N}(10, \sigma)$). The three clusters contain four elements each. The numbers of features are 100 supporting these cluster assignments. For the second data view we generate two cluster ($c_1 = \mathcal{N}(0, \sigma)$ and $c_2 = \mathcal{N}(10, \sigma)$). In this case the number of features is 1000. The two views are denoted as follows:

$$\mathbf{V}_1 = \begin{bmatrix} \mathcal{N}_{1,1}(-10, \sigma^2) & \ldots & \mathcal{N}_{1,100}(-10, \sigma^2) \\ \vdots & \ddots & \vdots \\ \mathcal{N}_{4,1}(-10, \sigma^2) & \ldots & \mathcal{N}_{4,100}(-10, \sigma^2) \\ \mathcal{N}_{5,1}(0, \sigma^2) & \ldots & \mathcal{N}_{5,100}(0, \sigma^2) \\ \vdots & \ddots & \vdots \\ \mathcal{N}_{8,1}(0, \sigma^2) & \ldots & \mathcal{N}_{8,100}(0, \sigma^2) \\ \mathcal{N}_{9,1}(10, \sigma^2) & \ldots & \mathcal{N}_{9,100}(10, \sigma^2) \\ \vdots & \ddots & \vdots \\ \mathcal{N}_{12,1}(10, \sigma^2) & \ldots & \mathcal{N}_{12,100}(10, \sigma^2) \end{bmatrix} \quad \mathbf{V}_2 = \begin{bmatrix} \mathcal{N}_{1,1}(0, \sigma^2) & \ldots & \mathcal{N}_{1,1000}(0, \sigma^2) \\ \vdots & \ddots & \vdots \\ \mathcal{N}_{8,1}(0, \sigma^2) & \ldots & \mathcal{N}_{8,1000}(0, \sigma^2) \\ \mathcal{N}_{9,1}(10, \sigma^2) & \ldots & \mathcal{N}_{9,1000}(10, \sigma^2) \\ \vdots & \ddots & \vdots \\ \mathcal{N}_{12,1}(10, \sigma^2) & \ldots & \mathcal{N}_{12,1000}(10, \sigma^2) \end{bmatrix}.$$

From these views we see that the first two cluster in $\mathbf{V}_1$ ($\{1, \ldots, 4\}$ and $\{5, \ldots, 8\}$) are a subset of the first cluster in $\mathbf{V}_2$ ($\{1, \ldots, 8\}$). After data integration we expect a final cluster solution of three clusters ($c_1 = \{1, \ldots, 4\}$, $c_2 = \{5, \ldots, 8\}$, and $c_1 = \{9, \ldots, 12\}$) because these clusters are confirmed in both views. However, since cluster c_1 and c_2 are fully connected in the second view, we expect these two clusters to be closer to each other than to c_3.

We vary the parameter $\sigma^2 = [0.1, 0.5, 1, 5, 10, 20]$ and expect that the cluster quality decreases the higher the variances for the specific groups. We analyze how *HC-fused* is

effected.

2.6 Simulation 2: Disjunct inter-cluster elements

For the second simulation we formulate two views $\mathbf{V}_1 \in \mathbb{R}^{m \times n}$ and $\mathbf{V}_2 \in \mathbb{R}^{m \times n}$. The first view reflects three clusters ($c_1 = \mathcal{N}(-10, \sigma)$, $c_2 = \mathcal{N}(0, \sigma)$, and $c_3 = \mathcal{N}(10, \sigma)$). In this case, the first and third cluster contain two elements each, and the second cluster six elements. The second view represents four clusters ($c_1 = \mathcal{N}(-10, \sigma)$, $c_2 = \mathcal{N}(0, \sigma)$, $c_3 = \mathcal{N}(10, \sigma)$ and $c_4 = \mathcal{N}(30, \sigma)$). The only difference between $\mathbf{V}_1$ and $\mathbf{V}_2$ is that in view $\mathbf{V}_2$ the last two elements are not connected.

$$
\mathbf{V}_1 = \begin{bmatrix} \mathcal{N}_{1,1}(-10,\sigma^2) & \dots & \mathcal{N}_{1,100}(-10,\sigma^2) \\ \mathcal{N}_{2,1}(-10,\sigma^2) & \dots & \mathcal{N}_{2,100}(-10,\sigma^2) \\ \mathcal{N}_{3,1}(0,\sigma^2) & \dots & \mathcal{N}_{3,100}(0,\sigma^2) \\ \vdots & \ddots & \vdots \\ \mathcal{N}_{8,1}(0,\sigma^2) & \dots & \mathcal{N}_{8,100}(0,\sigma^2) \\ \mathcal{N}_{9,1}(10,\sigma^2) & \dots & \mathcal{N}_{9,100}(10,\sigma^2) \\ \mathcal{N}_{10,1}(10,\sigma^2) & \dots & \mathcal{N}_{12,100}(10,\sigma^2) \end{bmatrix} \mathbf{V}_2 = \begin{bmatrix} \mathcal{N}_{1,1}(-10,\sigma^2) & \dots & \mathcal{N}_{1,1000}(-10,\sigma^2) \\ \mathcal{N}_{2,1}(-10,\sigma^2) & \dots & \mathcal{N}_{2,1000}(-10,\sigma^2) \\ \mathcal{N}_{3,1}(0,\sigma^2) & \dots & \mathcal{N}_{3,1000}(0,\sigma^2) \\ \vdots & \ddots & \vdots \\ \mathcal{N}_{8,1}(0,\sigma^2) & \dots & \mathcal{N}_{8,1000}(0,\sigma^2) \\ \mathcal{N}_{9,1}(10,\sigma^2) & \dots & \mathcal{N}_{9,1000}(10,\sigma^2) \\ \mathcal{N}_{10,1}(30,\sigma^2) & \dots & \mathcal{N}_{10,1000}(30,\sigma^2) \end{bmatrix}.
$$

After data integration we expect a final solution of three clusters ($c_1 = \{1, 2\}$, $c_2 = \{3, \dots, 8\}$ and $c_1 = \{9, 10\}$). With high confidence the cluster c_1 and c_2 should be inferred as these are confirmed in both data views. A lower confidence should be assigned to the third cluster c_1 because it is just confirmed in the second view. Again, we vary the parameter $\sigma^2 = [0.1, 0.5, 1, 5, 10, 20]$.

2.7 Comparison with other methods

We compare *HC-fused* to the *state-of-the-art methods SNF* [4], *PINSPlus* [14], and *NEMO* [5]. In addition, we match the performance of these methods to a baseline approach (*HC-concatenate*) where data are simply concatenated, and a single-omics hierarchical clustering approach based on Ward's method is applied. We apply the Adjusted Rand Index (ARI) [17] as a performance measure and the silhouette coefficient (SIL) [18] for cluster quality assessment. Figures are generated using the R-package *ggnet* [19] and *ggplot2* [20]. Simulation results can be easily reproduced by the R-scripts provided in our GitHub repository (pievos101/HC-fused).

3 Results

3.1 Disjoint inter-cluster elements

The results from the simulations with disjoint inter-cluster elements are illustrated in Fig. 1. *HC-fused* infers three clusters for the first view and two clusters for the second view. At this stage, the similarity weightings of the vertices are all equal to 1. After applying our proposed algorithm for data fusion, a fused network is constructed as seen in Fig. 1C. The optimal number of clusters is $k = 3$, as inferred by the silhouette coefficient based on the matrix $\mathbf{P}$. Panel D shows the dendrogram when the hierarchical clustering algorithm based on Ward's method is applied to the fused matrix $\mathbf{P}$. The cluster elements $\{9, \dots, 12\}$ are most distant to the other elements because they are disconnected from these elements in both views. The elements within the three clusters are all equally distant to each other because all connections within these clusters are confirmed in the $\mathbf{G}_\wedge$ view.

Fig 1. Results from simulation 1 (disjoint inter-cluster elements with $\sigma^2 = 1$). **A.** Shown is $\mathbf{G}_1$ from the first view ($\mathbf{V}_1$). **B.** Shown is $\mathbf{G}_2$ from the second view ($\mathbf{V}_2$). **C.** The fused network based on the fused distance matrix $\mathbf{P}$. Three clusters are suggested by the silhouette coefficient. **D.** The resulting dendrogram when hierarchical clustering is applied to the fused distance matrix $\mathbf{P}$.

Fig 2. Results for simulation 1. Contribution of the views to the hierarchical data fusion.

Fig. 2 highlights the contributions of the views to the data fusion process. The cluster members $\{9, \ldots, 12\}$ are fully supported by the $\mathbf{G}_\wedge$ view, whereas the view $\mathbf{G}_2$, also contributes to the other elements. That is not surprising because the concerned elements are all connected in the second view.

It can be seen that *HC-fused* is competing well with the *state-of-the-art* methods (Fig. 3). To our surprise, *SNF* performs very weak. The *eigen-gaps* method, as mentioned by its authors, infers two cluster as the optimal solution. It does not take into account that cluster c_1 and cluster c_2 are disconnected in the first view. Also, the silhouette method applied to the fused affinity matrix infers only two cluster. We observe similar ARI values for *HC-fused*, *PINSPlus* and *NEMO*. Compared to *HC-fused*, *PINSPlus* and *NEMO* are more robust against increased within-cluster variances.

Starting with a within-cluster variance of $\sigma^2 = 1$, *HC-fused* frequently behaves like *SNF* and infers the cluster assignments as represented by the second view (Fig. 1). Simply concatenating the data views (*HC-concatenate*) has an overall low accuracy. This is expected because the second view contains 10 times more features and thus gives more weights to the cluster assignments in $\mathbf{V}_2$. The silhouette coefficient, as a measure of cluster quality, is highest for the *HC-concatenate* approach from low to medium variances. However, it suggests even higher silhouette values for a $k = 2$ cluster solution. The silhouette coefficient of *HC-fused* is significantly higher than those from *SNF* and *NEMO*. We cannot report on any cluster quality measure for *PINSPlus* because the corresponding R-package does not provide a single fused distance or a similarity matrix.

Fig 3. Results from simulation 1 (disjoint inter-cluster elements with $\sigma^2 = [0.1, 0.5, 1, 5, 10, 15, 20]$). We compare *HC-fused* with *SNF, PINSPlus, NEMO*, and *HC-concatenate*. The true number of clusters is $k = 3$, with the cluster assignments $c_1 = \{1, \ldots, 4\}$, $c_2 = \{4, \ldots, 8\}$ and $c_3 = \{9, \ldots, 12\}$. The performance is measured by ARI. For each σ^2 we performed 100 runs and show the mean ARI value. The panel in the bottom right shows the mean SIL for the true cluster assignments ($k = 3$).

3.2 Disjunct inter-cluster elements

The hierarchical fusion process via *HC-fused* is illustrated in Fig. 4. The only difference between the two network views shown in Fig. 4A and Fig. 4B is, that in Fig. 4B the elements 9 and 10 are not connected. After data fusion (Fig. 4C) the silhouette coefficient infers three clusters as the optimal solution. The cluster elements in $c_3 = \{9, 10\}$ are most distant from each other (Fig. 4D) and signify a contribution from view 1, as shown in Fig. 5. This is expected because they are only connected in the first view and thus the confidence about this cluster is reduced. The cluster elements $c_2 = \{3, \ldots, 8\}$ are mainly fused in matrix $G_\wedge$ because the cluster is confirmed by both views (Fig. 5). The same applies to the cluster $c_1 = \{1, 2\}$ and thus the elements within c_1 and c_2 have equal distances to each other (Fig. 4C, 4D).

Fig 4. Results from simulation 2 (disjunct inter-cluster elements with $\sigma^2 = 1$). **A.** Shown is $\mathbf{G}_1$ from the first view ($\mathbf{V}_1$). **B.** Shown is $\mathbf{G}_2$ from the second view ($\mathbf{V}_2$). **C.** The fused network based on the fused distance matrix $\mathbf{P}$. Three clusters are suggested by the silhouette coefficient. **D.** The resulting dendrogram when hierarchical clustering is applied to the fused distance matrix $\mathbf{P}$.

Fig 5. Results for simulation 2. Contribution of the views to the hierarchical data fusion.

Overall, the results of the simulation with disjunct cluster elements are the best for *HC-fused*. *PINSplus* cannot compete with *HC-fused* (Fig. 4), it constantly infers four clusters as the optimal solution and does not take into account the connectivity between element 9 and 10 in the first view. Starting with a within-cluster variance of $\sigma^2 = 1$ the same happens with *HC-fused* (see Fig. 4). *NEMO* performs surprisingly weak. The modified *eigen-gap* method as suggested by the authors purely performs in this specific simulation scenario. *NEMO* infers far more than three clusters and the elements seem to be randomly connected with each other. When reducing the number of neighborhood points in the diffusion process, the total number of clusters is slightly decreasing but with no relevant gain in accuracy. Interestingly, with the same number of neighborhood points *SNF* performs much better. In a further investigation, when the silhouette method was adopted to the fused similarity matrix from *NEMO*, the true number of clusters was obtained. This fact points at a potential problem with the *eigen-gap* method as implemented in *NEMO* for data sets with disjunct inter-cluster elements.

When conducting cluster quality assessments we again observe low silhouette coefficient values for the fused affinity matrix resulting from *SNF* (see Fig. 6). For low to medium within-cluster variances, *NEMO*'s results are comparable to those of *HC-fused*. A value for cluster quality cannot be reported for *PINSPlus* because no single fused data view is available.

Fig 6. Results from simulation 2 (disjunct inter-cluster elements with
$\sigma^2 = [0.1, 0.5, 1, 5, 10, 15, 20]$). We compare *HC-fused* with *SNF*, *PINSPlus*, *NEMO* and
HC-concatenate. The true number of clusters is $k = 3$, with the cluster assignments
$c_1 = \{1, 2\}$, $c_2 = \{3, \ldots, 8\}$ and $c_3 = \{9, 10\}$. The performance is measured by the
Adjusted Rand Index (ARI). For each σ^2 we performed 100 runs and show the mean
ARI value. The panel at the bottom right shows the mean SIL coefficients for the true
cluster assignments ($k = 3$).

3.3   Disjoint & disjunct inter-cluster elements

In addition to the above studied simulation scenarios, which represent two
fundamentally different cluster patterns across the views, we also studied a mixture of
both. We simulated two views comprising disjoint and disjunct inter-cluster elements.
This particular simulation is described in detail in the supplementary material. We
found that *HC-fused* clearly outperforms the competing methods (supplementary Fig.
3). Amazingly, none of the *state-of-the-art* methods (*SNF*, *NEMO*, and *PINSPlus*)
infers the correct number of clusters, even when the *within-cluster* variances are very
low. Right behind *HC-fused* is *PINSPlus* which gives more accurate results than
HC-fused, in case of medium variances. The cluster quality of *HC-fused*, as judged by
the silhouette coefficients, is higher than those from *NEMO* and *SNF* (supplementary
Fig. 3, bottom right).

3.4 Robustness analyses

We randomly permuted a set of features across the patients in order to test the available
approaches with respect to their ability to predict the correct number of clusters. As
seen from the supplementary Fig. 4, *NEMO* and *PINSPlus* are more stable against
noise compared to *HCfused*. When the number of permuted features is greater than one,
the accuracy of *HC-fused* drops. This is most likely due to the fact that *HC-fused* uses
the Euclidean distance to generate the connectivity matrices **G**. It is well known that
the Euclidean distance is prone to outliers and removing such data points prior to the
analysis may be a necessary initial step. Another possible approach would be a
principal component analyses (PCA) on the feature space.

In case of disjunct cluster elements (supplementary Fig. 5) we observe a slightly
different outcome situation. *HC-fused* is definitely more robust against noise compared
to *SNF. PINSPlus* provides also stable results, but as already pointed out in the
previous section, produces a wrong cluster assignment.

3.5 Integrative clustering of TCGA cancer data

To benchmark our *HC-fused* approach we used the TCGA cancer data as provided
by [12], for which mRNA, methylation data, and miRNA are available for a fixed set of
patients. We tested our approach on nine different cancer types: glioblastoma
multiforme (GBM), kidney renal clear cell carcinoma (KIRC), colon adenocarcinoma
(COAD), liver hepatocellular carcinoma (LIHC), skin cutaneous melanoma (SKCM),
ovarian serous cystadenocarcinoma (OV), sarcoma (SARC), acute myeloid leukemia
(AML), and breast cancer (BIC). In contrast to other benchmark studies, that apply the
multi-omics approaches to a static data set, we randomly sample 20 times 100 patients
from the data pool, performed survival analyses and calculated the Cox log-rank
p-values [21] represented by boxplots (Fig. 7). We are convinced that this approach is
conveying a less biased picture of the clustering performance. Surprisingly, we observe
overall weaker performance than previously reported in [12] (Fig. 7). *HC-fused* is best
for KIRC, LIHC, SKCM, OV, and SARC when the median log-rank p-values are used
for comparison. Global best results are observed for the KIRC and SARC data sets.
The method implemented in the R-package *NEMO* performs best for the GBM and
AML cancer types. *PINSplus* has overall low performance in almost all cases. Notably,
all methods studied in this work perform weak on the COAD data set.

Fig 7. TCGA integrative clustering results. Shown are the log-rank *p*-values on a logarithmic scale for nine different cancer types. The red line refers to $\alpha = 0.05$ significance level.

Beyond the results shown in Fig. 7, we applied our *HC-fused* approach to the TCGA breast cancer data as allocated by [4]. In the supplementary material we provide a *step-by-step* guide on how to analyze this data set within the R environment using *HC-fused*. *HC-fused* infers seven cluster (supplementary Fig. 6) as the optimal solution with a significant Cox log-rank *p*-value of 3.2^{-5}. Previously reported *p*-values on the same data set are: *SNF* = 1.1^{-3} and *rMKL-LPP* = 3.0^{-4}. Clusters 1,2,4 and 5 are mainly confirmed by all biological layers, whereas cluster 3,6 and 7 signify some exclusive contributions from the single-omics views to the data fusion process. Especially, the mRNA expression data has some substantial contribution on cluster 3 and 7 (supplementary Fig. 7).

4 Discussion

In this article, we have developed a hierarchical clustering approach for multi-omics data fusion based on simple and well established concepts. Simulations on disjoint and disjunct cluster elements across simulated data views indicate superior results over

recently published methods. In fact, we provide two simulation scenarios in which $\qquad$ 262
state-of-the-art methods behave substantially different. For example, we discovered that $\qquad$ 263
NEMO performs well on data sets with *disjoint inter-cluster elements* whereas *SNF* $\qquad$ 264
does a much better job on *disjunct inter-cluster elements* across the data views. We $\qquad$ 265
hope that our synthetic data sets may act as a useful benchmark for future efforts in the $\qquad$ 266
field. $\qquad$ 267

    Applications on real multi-omics TCGA cancer data suggest promising results and $\qquad$ 268
HC-fused competes well with *state-of-the-art* methods. Out of nine studied cancer types, $\qquad$ 269
HC-fused performs best on five cases. Importantly and in contrast to other methods, $\qquad$ 270
HC-fused provides information about the contribution of the single-omics to the data $\qquad$ 271
fusion process. It should be noted, however, that our algorithm requires multiple $\qquad$ 272
iterations to achieve a good estimate of the contributions. The reason is that in each $\qquad$ 273
integration step the single views may contain equal minimal distances. As a $\qquad$ 274
consequence it is not certain in which view data points should be fused. Currently, we $\qquad$ 275
solve this issue by a uniform sampling scheme plus running the proposed algorithm $\qquad$ 276
multiple times. At the moment it is not entirely clear how many iterations are required. $\qquad$ 277
We suggest to use a minimum limit of `HC.iter`$>= 10$ as it produced good results in our $\qquad$ 278
investigations. However, we plan to solve this task in a computational more feasible way $\qquad$ 279
in the next releases of the corresponding *HC-fused* R-package. A promising approach $\qquad$ 280
would be to model the fusion algorithm as a Markov process where each view represents $\qquad$ 281
a state and the transition probabilities depend on the number of view-specific items $\qquad$ 282
providing the same minimal distance. $\qquad$ 283

    Unlike other approaches, the *HC-fused* workflow does not depend on a specific $\qquad$ 284
clustering algorithm. This means, with the current release, any hierarchical clustering $\qquad$ 285
method provided by the native R function `hclust` can be used to create the $\qquad$ 286
connectivity matrices $\mathbf{G}$. Also, the final fused matrix P can be calculated by any $\qquad$ 287
user-defined clustering algorithm. $\qquad$ 288

    Further investigations are needed to study a wide range of clustering algorithms $\qquad$ 289
within the proposed *HC-fused* workflow to see how they perform on different cancer $\qquad$ 290
types. Given the substantial heterogeneity between omics data sets we believe that a $\qquad$ 291
combination of different clustering algorithms may be worthwhile to test. We will $\qquad$ 292
include this feature into our software implementation. Another characteristic of $\qquad$ 293
HC-fused is its independence of a specific technique to infer the best number of clusters. $\qquad$ 294
While, in this work, the silhouette coefficient was adopted, other methods might further $\qquad$ 295
improve the outcomes. $\qquad$ 296

5   Conclusion $\qquad$ 297

Multi-omics clustering approaches have a great potential to discover cancer subtypes $\qquad$ 298
and thus may facilitate the treatment of cancer patients in future personalized routines. $\qquad$ 299
We provide a novel hierarchical data fusion approach embedded in the versatile $\qquad$ 300
R-package *HC-fused* available on GitHub (pievos101/HC-fused). Simulations and $\qquad$ 301
applications to real-world TCGA cancer data indicate that *HC-fused* is more accurate $\qquad$ 302
in most cases and in the others it is performing equivalent to current *state-of-the-art* $\qquad$ 303
methods. In contrast to other approaches, *HC-fused* naturally reports on the $\qquad$ 304
contribution of the single-omics to the data fusion process and its overall simplicity $\qquad$ 305
fosters the interpretability of the final results. $\qquad$ 306

Acknowledgments

We would like to gratefully acknowledge the support of the Kurt und Senta Herrmann-Stiftung, Vaduz, Liechtenstein. We thank Luca Vitale and José Antonio Vera-Ramos for helpful discussions.

References

1. Karczewski KJ, Snyder MP. Integrative omics for health and disease. Nature Reviews Genetics. 2018;19(5):299.

2. van der Wijst MG, de Vries DH, Brugge H, Westra HJ, Franke L. An integrative approach for building personalized gene regulatory networks for precision medicine. Genome Medicine. 2018;10(1):96.

3. Richardson S, Tseng GC, Sun W. Statistical methods in integrative genomics. Annual Review of Statistics and its Application. 2016;3:181–209.

4. Wang B, Mezlini AM, Demir F, Fiume M, Tu Z, Brudno M, et al. Similarity network fusion for aggregating data types on a genomic scale. Nature Methods. 2014;11(3):333.

5. Rappoport N, Shamir R. NEMO: Cancer subtyping by integration of partial multi-omic data. Bioinformatics. 2019;35(18):3348–3356.

6. Von Luxburg U. A tutorial on spectral clustering. Statistics and Computing. 2007;17(4):395–416.

7. Speicher NK, Pfeifer N. Integrating different data types by regularized unsupervised multiple kernel learning with application to cancer subtype discovery. Bioinformatics. 2015;31(12):i268–i275.

8. Lin YY, Liu TL, Fuh CS. Multiple kernel learning for dimensionality reduction. IEEE Transactions on Pattern Analysis and Machine Intelligence. 2010;33(6):1147–1160.

9. John CR, Watson D, Barnes MR, Pitzalis C, Lewis MJ. Spectrum: fast density-aware spectral clustering for single and multi-omic data. Bioinformatics. 2019;doi:10.1093/bioinformatics/btz704.

10. Mo Q, Wang S, Seshan VE, Olshen AB, Schultz N, Sander C, et al. Pattern discovery and cancer gene identification in integrated cancer genomic data. Proceedings of the National Academy of Sciences. 2013;110(11):4245–4250.

11. Mo Q, Shen R, Guo C, Vannucci M, Chan KS, Hilsenbeck SG. A fully Bayesian latent variable model for integrative clustering analysis of multi-type omics data. Biostatistics. 2017;19(1):71–86.

12. Rappoport N, Shamir R. Multi-omic and multi-view clustering algorithms: review and cancer benchmark. Nucleic Acids Research. 2018;46(20):10546–10562.

13. Nguyen T, Tagett R, Diaz D, Draghici S. A novel approach for data integration and disease subtyping. Genome Research. 2017;27(12):2025–2039.

14. Nguyen H, Shrestha S, Draghici S, Nguyen T. PINSPlus: a tool for tumor subtype discovery in integrated genomic data. Bioinformatics. 2018;.

15. Murtagh F, Legendre P. Ward's hierarchical agglomerative clustering method: which algorithms implement Ward's criterion? Journal of Classification. 2014;31(3):274–295.

16. Müllner D, et al. fastcluster: Fast hierarchical, agglomerative clustering routines for R and Python. Journal of Statistical Software. 2013;53(9):1–18.

17. Santos JM, Embrechts M. On the use of the adjusted rand index as a metric for evaluating supervised classification. In: International Conference on Artificial Neural Networks. Springer; 2009. p. 175–184.

18. Rousseeuw PJ. Silhouettes: a graphical aid to the interpretation and validation of cluster analysis. Journal of Computational and Applied Mathematics. 1987;20:53–65.

19. Briatte F. ggnet: Functions to plot networks with ggplot2; 2019. Available from: `https://github.com/briatte/ggnet`.

20. Wickham H. ggplot2: elegant graphics for data analysis. Springer; 2016.

21. Hosmer Jr DW, Lemeshow S, May S. Applied survival analysis: regression modeling of time-to-event data. vol. 618. Wiley-Interscience; 2008.