Computational Biology

A Self-Attention Model for Inferring Cooperativity between Regulatory Features

Fahad Ullah [1] and Asa Ben-Hur [1,*]

[1] Computer Science Department, Colorado State University, Fort Collins, 80523, USA.

*To whom correspondence should be addressed.

Abstract

Motivation: Deep learning has demonstrated its predictive power in modeling complex biological phenomena such as gene expression. The value of these models hinges not only on their accuracy, but also on the ability to extract biologically relevant information from the trained models. While there has been much recent work on developing feature attribution methods that discover the most important features for a given sequence, inferring cooperativity between regulatory elements, which is the hallmark of phenomena such as gene expression, remains an open problem.

Results: We present SATORI, a **S**elf-**AT**tenti**O**n based model to predict **R**egulatory element **I**nteractions. Our approach combines convolutional and recurrent layers with a self-attention mechanism that helps us capture a global view of the landscape of interactions between regulatory elements in a sequence. We evaluate our method on simulated data and three complex datasets: human TAL1-GATA1 transcription factor ChIP-Seq, DNase I Hypersensitive Sites (DHSs) in human promoters across 164 cell lines, and genome-wide DNase I-Seq and ATAC-Seq peaks across 36 arabidopsis samples. In each of the three experiments SATORI identified numerous statistically significant TF-TF interactions, many of which have been previously reported. Our method is able to detect higher numbers of these experimentally verified TF-TF interactions than the existing Feature Interaction Score, and also has the advantage of not requiring a computationally expensive post-processing step. Finally, SATORI can be used for detection of any type of feature interaction in models that use a similar attention mechanism, and is not limited to the detection of TF-TF interactions.

Availability: The source code for SATORI is available at https://github.com/fahadahaf/SATORI.

Contact: asa@colostate.edu

1 Introduction

High-throughput sequencing techniques are producing an abundance of transcriptome and epigenetic datasets that can be used to generate genome-wide maps of different aspects of regulatory activity. The complexity and magnitude of these data has made deep neural networks an appealing choice for a variety of modeling tasks, including transcription factor (TF) binding prediction [Alipanahi *et al.*, 2015, Hassanzadeh and Wang, 2016, Zhou and Troyanskaya, 2015, Quang and Xie, 2016, Qin and Feng, 2017], chromatin accessibility analysis [Kelley *et al.*, 2016, Banovich *et al.*, 2018, Angermueller *et al.*, 2017], prediction of chromatin structure and its modifications [Koh *et al.*, 2017, Schreiber *et al.*, 2018], and identification of RNA-binding sites [Pan and Shen, 2017, Zhang *et al.*, 2015]. Besides providing improvement in accuracy over traditional machine learning models, deep learning methods typically require less feature engineering, and can learn directly from sequence and other data. Moreover, deep learning models are able to capture non-linear feature interactions that can help explain the underlying regulatory phenomena.

The discovery that TFs work in tandem to regulate the expression of their targets [Wasserman and Fickett, 1998] has sparked the development of a variety of computational methods for predicting cooperativity among TFs and other regulatory proteins by looking at regulatory element co-occurrences [Hannenhalli and Levy, 2002, GuhaThakurta and Stormo, 2001, Pilpel *et al.*, 2001, Sudarsanam *et al.*, 2002, Roca and Franceschi, 2008, Safe, 2015, Ceddia *et al.*, 2019]. Despite the demonstrated ability of deep neural networks to extract regulatory signals directly from sequence, there are very few studies that explore cooperativity between regulatory features in genomic data using these methods. Deep Feature Interaction Maps (*DFIM*) uses a network attribution method called DeepLIFT [Shrikumar *et al.*, 2017] to estimate interactions between regulatory elements, tested for one pair at a time [Greenside *et al.*, 2018]. The major drawback of DFIM is that it is computationally expensive: the interactions are inferred in a separate post-processing step and involves recalculation of network gradients. We note that the recent *DeepResolve* method infers feature importance and whether a feature participates in interactions with other features, but does not infer pairs of interacting features explicitly [Liu *et al.*, 2019].

Fig. 1. Model architecture variants. We use a convolutional layer followed by a multi-head self-attention layer (a); optionally, we add a recurrent layer between the two (b). The input in both cases is a one-hot encoding of the DNA sequence. The output of the model is either be a binary or multi-label prediction.

Recently, neural networks that use the concepts of *attention* and *self-attention* [Parikh *et al.*, 2016, Lin *et al.*, 2017] have achieved remarkable success in natural language processing tasks, specifically in machine translation [Vaswani *et al.*, 2017]. One of the strengths of attention is that it can capture associations between features regardless of the distance between them, addressing a major shortcoming of convolutional and recurrent networks. This is particularly useful for tasks in computational biology where our goal is to identify regulatory elements and their associations/interactions in DNA or RNA sequences. The value of attention for modeling transcription factor binding site prediction was recently demonstrated, and their work was motivated by the greater interpretability of the resulting networks [Chen *et al.*, 2019]. However, to the best of our knowledge, it has not been employed for inferring regulatory interactions between TFs and other regulatory elements.

To this end, we propose **SATORI**, a self-attention based deep learning model to capture regulatory element interactions in genomic sequences. The primary components of the architecture of our model are a CNN layer and a multi-head self-attention layer. Optionally, we also incorporate an RNN layer between the two primary layers. The convolutional layer discovers features/motifs in the input sequences. The self-attention layer then captures potential interactions between those features without the need for explicitly testing all possible combinations of motifs. That enables us to infer a global landscape of interactions in a given genomic dataset, without a computationally-expensive post-processing step.

We test SATORI on several simulated and real datasets, including data on chromatin accessibility in 164 cell lines in all human promoters and genome-wide chromatin accessibility data across 36 samples in Arabidopsis. To compare our method to DFIM, we incorporate their Feature Interaction Scores (FIS) [Greenside *et al.*, 2018] into our framework. In all our experiments, SATORI and FIS scoring return highly consistent sets of interactions, with SATORI returning a much larger

number of biologically confirmed interactions. Due to the relative paucity of experimentally determined TF-TF interactions it is important to have multiple independent methods for this task. We believe this work will assist researchers in improving the interpretability of complex deep learning methods and providing actionable hypotheses for follow up experiments.

2 Methods

2.1 Model architecture

We present a self-attention based deep neural network to capture interactions between regulatory features in genomic sequences. Figure 1 depicts the two main architectures we explored in our work. Note that the input to the model—DNA/RNA sequences—was represented as a one-hot encoding: a sequence of length L is transformed into a matrix of size $4 \times L$ where each position in the sequence is represented by a column in the matrix as a non-zero value at location corresponding to one of the four DNA nucleotides.

The first component of our model is a CNN layer where a finite set of filters are scanned against the input sequence/matrix. Formally, we can write the convolution operation as:

$$X'_{i,j} = \sum_{a=0}^{A-1} \sum_{b=0}^{B-1} \omega_{a,b}^{j} X_{i+a,b}, \tag{1}$$

where X is the input matrix, i is the position at which convolution is performed, j is the index of the filter, and ω^j is the weight matrix of the filter with size $A \times B$ where A is the length of the filter (window size) and B is the number of input channels (four in the case of one-hot encoded input DNA sequences). After the convolution operation, we use

Fig. 2. Summary of the process of inferring interactions from self-attention layer values. For a given example, we collapse the attention heads into a single matrix. Next, at each pair of positions, the corresponding active CNN filters are identified and the attention value is assigned to the interacting pair. This is repeated for all examples to generate interaction profiles for all filter-pairs. Finally, we use a background set to test the significance of filter-filter interactions.

the Rectified Linear Unit activation function (ReLU), which is given by:

$$f(x) = \max(0, x). \tag{2}$$

Next, we reduce the output size using max-pooling by taking the maximum value in a window of a pre-determined size. This reduces the input size for the next layer and also provides invariance to small shifts in the input sequence.

Optionally, as shown in Figure 1(b), we use an RNN layer following the CNN layer. RNNs have an internal state that enables them to capture distant feature interactions in the input sequence. Specifically, we employ a bi-directional RNN with Long Short-Term Memory (LSTM) units [Hochreiter and Schmidhuber, 1997].

2.1.1 Multi-head self-attention

The core component of our network is a multi-head self-attention layer. Attention mechanism can model dependencies within the input sequence regardless of their distance [Vaswani *et al.*, 2017]. By doing so, it guides the network to focus on relevant features within the input and ignore irrelevant information. Pertinent to the problem at hand, a self-attention layer can help us identify interacting regions within the input sequences. Consequently, we can capture interactions between regulatory events.

To define self-attention, consider the input X to this layer, which is the output of the convolutional/recurrent layer and two linear transformations of it, called the Query Q, and Key K which are defined by:

$$Q = W_Q^\top X, \tag{3}$$

$$K = W_K^\top X, \tag{4}$$

where W_Q, and W_K are the corresponding weight matrices for the Query and Key, respectively. The attention matrix A is then computed using the following expression:

$$A(Q, K) = \operatorname{softmax}\left(\frac{QK^\top}{\sqrt{d_k}}\right), \tag{5}$$

where d_k is the dimension of the Key K and the ith component of the softmax function is defined by:

$$\operatorname{softmax}(\mathrm{x})_i = \frac{e^{x_i}}{\sum_j e^{x_j}}. \tag{6}$$

The scaling by $\frac{1}{\sqrt{d_k}}$ in Equation (5) ensures more stable gradients of the softmax function for large values of d_k [Vaswani *et al.*, 2017]. The matrix The attention matrix A, defined in Equation (5), is a $d \times d$ matrix where $d = \frac{L}{M_p}$, L is the length of the input sequence, and M_p is the size of the window used in the max-pooling operation. For every position in the max-pooled output, the attention matrix summarizes the influence of all other locations on that position. To generate the output of the attention layer, we first define the Value matrix

$$V = W_V^\top X \tag{7}$$

using the associated weight matrix W_V. Finally, we define the output of the attention layer as:

$$Z = A \times V. \tag{8}$$

Intuitively, Equation (8) allows us to generate the output using the parts of the input that we want to focus on—those which exhibit strong interdependencies—and ignore irrelevant information.

For multi-head self-attention, we concatenate the N single-heads followed by a linear transformation. The final output is then collapsed along the hidden (attention) layer dimensions through addition and normalized by the mean and the standard deviation of the result. Empirically we find

Table 1. Dataset summary. The first two datasets are binary classification problems whereas the last two experiments are multi-label problems.

Dataset	Description	Size
Simulated	Simulated DNA sequences	120,000 (total)
	ELF1 and SIX5 embedded in positive examples	40,000 (positive), 80,000 (negative)
	ELF1 or SIX5 embedded in negative examples	
	Instances of AP3 or TAL1 are also randomly embedded	
TAL-GATA ChIP-Seq	DNA sequences for TAL1, GATA1, and GATA2	105,134 (total)
	ChIP-peaks in K562. Positive examples were peaks	25,134 (positive), 80,000 (negative)
	that overlapped DHSs. Negative examples were all	
	other DHSs.	
Human promoter open chromatin	DHSs overlapping human promoters	20,613 examples across 164 cell types
Arabidopsis open chromatin	DHSs and Transposase Hypersensitive Sites (THSs)	88,245 examples across 36 samples
	across the arabidopsis genome	

that this step is not only computationally efficient but also leads to better model accuracy in comparison to flattening the attention layer output. The final fully connected read-out layer outputs the model's prediction: either binary or multi-label classification, depending on the experiment. For binary classification, we use the standard cross entropy loss function. For multi-label classification, we use the binary cross entropy with logits loss function:

$$L(y, \hat{y}) = -\frac{1}{C} \sum_{i=1}^{C} \left[y_i \log \sigma(\hat{y}_i) + (1 - y_i) \log(1 - \sigma(\hat{y}_i)) \right],$$

where y is the vector of ground truth labels, $\hat{y}$ are the network predictions, C is the number of classes, and σ is the sigmoid function.

2.2 Network training and evaluation

For model selection and optimization, we employ a random search algorithm to tune the network's hyperparameters. For the convolutional layers we considered filter size, number of filters, and size of window over which pooling is performed. For the multi-head attention layer we tuned the dimensionality of the features generated, and the size of the output of the multi-head attention layer. Details are provided in Table S1 in the Supplementary material. To evaluate the model, we use a simple strategy of splitting the data into 80%, 10%, and 10% for train, test, and validation sets, respectively; we use Area Under the ROC Curve (AUC) to assess model performance. The package was implemented in PyTorch [Paszke *et al.*, 2019] and all the experiments were ran on a Ubuntu server with a 12 GB TITAN V GPU.

2.3 Motif extraction

To interpret the deep learning model, we extract sequence motifs from the weights matrices (filters) of the first convolutional layer, similarly to the methodology used in [Kelley *et al.*, 2016]. For binary classification problems, we use the positive test set examples that achieve a probability score greater than 0.70. This cutoff was chosen as a good trade-off between the number of qualifying examples and confidence in the prediction. We use all test set examples when dealing with a multi-class or multi-label problems. Next, for each filter we identify regions in the set of sequences that activate the filter with a value greater than half of the filter's maximum score over all sequences. The resulting substrings are stacked and for each filter, a position weight matrix (PWM) is calculated using the nucleotide frequency and background information. Sequence logos are generated using the WebLogo tool [Crooks *et al.*, 2004]. The PWMs are searched against appropriate TF databases using the TomTom tool [Gupta *et al.*, 2006] with distance metric set to Euclidean. For searching we use the human CISBP [Weirauch *et al.*, 2014] and arabiodpsis DAP [O'Malley

et al., 2016] databases. In the benchmark experiments, we use custom TF databases, details of which are provided in the supplementary material.

Recently, it has been reported that exponential activation functions such as Softplus in the convolutional layer improve motif information content [Koo and Ploenzke, 2019]. In our experiments this led to a slight improvement in the information content of the CNN filters when the Softplus function was used instead of ReLU activation (median information content = 4.12 with Softplus compared to 4.00 with ReLU).

2.4 Quantifying feature interactions

In this section we describe the process of inferring motif interactions from the self-attention layer. The attention matrix for each head is calculated using Equation (5). Next, we collapse the N heads to a single $d \times d$ matrix by taking the maximum at each position (see Figure 2). This step summarizes the self-attention values from multiple subspaces associated with the corresponding single-heads to a single, attention profile.

The attention matrix provides information about interactions between positions in the sequence. That is next converted into interactions between filters by retrieving the filters that are active in those positions. Finally, for each identified filter-filter interaction, we generate the attention profile across all testing examples. For a given pair, this profile consists of a vector of its attention values at positions where the corresponding filters were active. An interaction pair is discarded if its maximum attention value is below a certain threshold. By default we used the value 0.10; in the human promoter data we used 0.08 to increase sensitivity. We note that the distribution of attention values tends to be bi-modal, with most of the values close to 0 or 1 (see supplementary figure F1).

Filter-filter interactions are then translated to motif interactions by picking the most significant TomTom hits in the appropriate TF database. Note that we might not find significant matches for every CNN filter in the database; it can be expected that our model is capturing interactions of un-characterized regulatory elements. However, in this paper we focus on the interactions between known TFs. To test the statistical significance of motif interactions, we first generate their attention profiles in the background data (described next). Then the non-parametric Mann-Whitney U Test is used to calculate their significance. All the p-values are adjusted for multiple hypothesis testing using Benjamini-Hochberg method [Benjamini and Hochberg, 1995].

2.4.1 Background selection
As mentioned above, to test the statistical significance of regulatory interactions, we need to compare them to a background. We use a biologically relevant background depending on the experiment:

(a)   (b)

Fig. 3. The most frequent TF interactions in human promoters (a). The distribution of TF-TF interaction distances (b).

- For binary classification problems, the negative test set is used as the background.
- For multi-label, multi-class or regression problems we generate a background set by shuffling the test set sequences while preserving their di-nucleotide frequencies. Next, in the shuffled sequences, we randomly embed motifs that are generated based on the CNN filters, interpreted as probability distributions, taking into account the number of times a filter is active in the original test sequences.

2.4.2 Quantifying interactions using FIS scoring

To infer interactions between motifs using the FIS method, we closely follow the strategy described in [Greenside *et al.*, 2018]. Given a test sequence and all of its activated first layer CNN filters, first a source motif is selected. The remaining filters serve as the target motifs for the given source motif. Using Integrated Gradients [Sundararajan *et al.*, 2017], we calculate the attribution scores for all the target motifs in the given test sequence. The attribution score determines how important a motif is for the model to accurately predict the test example. Next, the source motif is mutated based on the GC-content of the given sequence and the attribution scores are recalculated for all targets. Finally, to infer interactions, for each source and target pair, the FIS score is calculated as the difference between the attribution scores for each target motif, before and after mutating the source motif. Intuitively, if modifying the source motif affects the attribution of the target motif, this suggests a potential interaction, and the magnitude of the change in attribution scores is used to quantify this potential. We compute FIS scores for all unique pairs of source and target motifs across all test sequences and identify statistically significant interactions using the the same approach used in SATORI (see Figure 2).

2.4.3 Selecting test examples

To quantify interactions using SATORI or the FIS-based approach, we use the high-confidence predictions of the model. For binary classification, we pick all positive examples that are assigned prediction confidence above a specified threshold. We use a threshold of $p = 0.70$ in our experiments. For the background examples, we pick all the negative test examples that score below $1 - p$. In case of the multi-label classification problem, we

Table 2. The most frequent interacting families of human transcription factors in the TAL-GATA ChIP-peaks in human K562 cell-line. All interactions are significant with adjusted p-value < 0.05.

TF Family Interaction	Frequency	Percent of total interactions
C2H2 ZF $\longleftrightarrow$ CxxC	170	14.36%
Homeodomain $\longleftrightarrow$ C2H2 ZF	121	10.22%
C2H2 ZF $\longleftrightarrow$ C2H2 ZF	90	7.60%
GATA $\longleftrightarrow$ C2H2 ZF	79	6.67%
Homeodomain $\longleftrightarrow$ CxxC	72	6.08%
C2H2 ZF $\longleftrightarrow$ Sox	62	5.24%
C2H2 ZF $\longleftrightarrow$ bHLH	53	4.48%
GATA $\longleftrightarrow$ CxxC	51	4.31%
Sox $\longleftrightarrow$ CxxC	39	3.29%
C2H2 ZF $\longleftrightarrow$ THAP finger	21	1.77%
CxxC $\longleftrightarrow$ bHLH	19	1.60%
Nuclear receptor $\longleftrightarrow$ C2H2 ZF	19	1.60%
GATA $\longleftrightarrow$ bHLH	18	1.27%
Homeodomain $\longleftrightarrow$ bHLH	17	1.44%
SAND $\longleftrightarrow$ C2H2 ZF	17	1.44%

pick our test examples based on the precision of the model's prediction probabilities: for a test example to qualify, the precision value—calculated using the given labels and their model assigned probabilities—must be above a specified threshold (default precision threshold $= 0.50$). We note that for FIS scoring of multi-label classification problems, we only use the attribution values of the true positive predictions. These values are summed and used in calculating the final FIS score.

2.5 Data collection and processing

We use four datasets to evaluate the ability of SATORI to capture interactions between regulatory elements. The datasets are summarized in Table 1, and specific details are provided in the Methods section of the supplementary material.

Fig. 4. The regulatory interaction landscape in accessible chromatin in the arabipdosis genome. The most frequently interacting families of plant transcription factors (a). The distribution of distances between inferred TF-TF interactions (b).

3 Results and Discussion

3.1 Benchmark 1: embedded motif interactions in simulated genomic sequences

In this experiment we used SATORI to test if it can recover interactions embedded in simulated DNA sequences. The dataset was created similarly to the simulated dataset of Greenside et al. [Greenside *et al.*, 2018]: $120,000$ random DNA sequences were generated; in $40,000$ sequences we embedded motifs of the transcription factors SIX5 and ELF1. Motifs from both TFs were present in each sequence, simulating an interaction. These sequences were labelled as positive examples. In the rest sequences we embedded only one of the two motifs in each sequence. In addition, motifs occurrences of TAL1 and AP3 were embedded at random across the whole dataset.

Not surprisingly, both variants of our deep learning architectures achieved perfect classification accuracy on the test set for this data. We then analyzed the attention layer weights and inferred statistically significant motif interactions and found that all the significant interactions returned by our model involve SIX5 and ELF1 as expected. These interactions are summarized in Supplementary Table S2.

3.2 Benchmark 2: Inferring TAL-GATA motif interactions from ChIP-Seq data

The TFs TAL1 and GATA1 have been reported to interact: GATA1 requires a prior or simultaneous binding of TAL1 before it can bind DNA [Kassouf *et al.*, 2010]. To investigate these interactions in this experiment, which follows a similar experiment performed by the authors of DFIM, we formulated a binary classification problem where the positive set consisted of sequences of the TAL1, GATA1, and GATA2 ChIP-Seq peaks that overlapped regions of open chromatin (DHSs) in the human K562 cell-line. For the negative set, sequences of all other K562 DHSs that didn't overlap any of the ChIP-Seq peaks were used. This experiment serves as another benchmark for our model, and was also used by Greenside et al. to test their model's ability uncover interactions between TAL1 and

GATA1/GATA2 [Greenside *et al.*, 2018]. Further details regarding the dataset are provided in the supplementary material.

We trained both variants of our model on this dataset; in this harder dataset the variant with an RNN layer performed much better with an AUC of 0.94 on the test set compared to 0.85 for the model without an RNN. The authors of DFIM achieved similar accuracy using five layers of convolution. Please note that we do not seek to demonstrate better model accuracy. Our focus is on model interpretability, which we seek to achieve without compromising in that regard. Using SATORI we recovered multiple significant filter-filter interactions that mapped to TAL1 and GATA motifs with highly significant p-values (see supplementary table S3), demonstrating the ability of our model to recover biologically relevant interactions between TFs.

Since this dataset uses ChIP-Seq peaks of TAL and GATA transcription factors that occur in regions of open chromatin, other TF-TF interactions might present in these regions. Therefore, we also let SATORI search for interactions among all known human transcription factors. As expected, we found numerous other interactions. Table 2 summarizes the 15 most frequent TF family-family interactions, consisting predominantly of interactions between members of the C2H2 ZF, Homeodomain, CxxC, and GATA families (see Supplementary Table S4 for the list of individual TF interactions). An interesting observation is that the interactions between the GATA and bHLH (TAL1) families are not the most frequent, despite the fact that the model used their ChIP-Seq peaks. This is likely because of the differences in size of these TF families: the C2H2 ZF and Homeodomain families are the largest TF families in humans, whereas bHLH and particularly GATA, are much smaller in size.

Because of the similarity between some TF motifs, the matching between filters and motifs is not without errors. In this second experiment GATA was predicted to interact with TCF15, which has a motif that closely resembles that of TAL1. In fact, both of them belong to the same bHLH family. Figure F2 in the Supplement shows the similarity between these motifs.

Fig. 5. Common interactions in the top predictions of SATORI and FIS. Interactions predicted by FIS are sorted by frequency. Those predicted by both methods are shown in blue, and ones predicted only by FIS are shown in red. Top predictions are shown for the TAL-GATA dataset (a) the human promoter dataset (b), and the genomewide arabidopsis dataset (c). For each experiment, the 10 most frequent TF family interactions are shown in (d), (e), and (f) respectively.

3.3 The TF interaction landscape across human promoters

In this experiment we investigated regulatory interactions between TFs in all human promoter regions using DNase I hypersentivity data (DHSs) across 164 immortalized cell lines and tissues. This experiment was based on the work of Kelley et al. [Kelley *et al.*, 2016] which used convolutional networks to predict chromatin accessibility from sequence information alone across the entire human genome. We chose to focus on a subset of the data that consists of DHSs in human promoters to determine interactions relevant to the regulation of gene expression. The labels in this data represent presence/absence of a given DHS across each of the 164 cell lines, and is a multi-label classification problem. Additional details are found in the supplementary material. We trained both network variants (see Figure 1) and observed that with the optional RNN layer, the network performed better in terms AUC scores (see Supplementary Figure F3). SATORI results are presented for this architecture variant.

The trained network yielded filters that matched 93 TFs with known motifs (counting only filters that had information content greater than 3.0). Among those 93 TFs, our model identified 234 unique pairs of motifs that interact. The 20 most frequent interactions are shown in Figure 3(a). For the complete list, refer to Supplementary Table S5. We also looked at the distribution of the distances between interacting motifs, and observed that, as expected, interactions tend to occur in close proximity with a median distance of interaction of 168 bp (see Figure 3(b)). Overall, the Homeodomain, C2H2 ZF, and CxxC families were the most frequent families of interacting TFs (see supplementary figure F5). Finally, it is

worth mentioning that for twelve interactions out of the total of 234, we found evidence in the TRRUST database [Han *et al.*, 2017] which lists 58 interactions among the 93 TFs (see Table S6 in the Supplementary Material for details). This overlap is statistically significant with a p-value of 4.66×10^{-7} using the hypergeometric test.

We note that in this work we only analyzed interactions between motifs of known TFs. Not all filters can be mapped to characterized regulatory proteins. In this dataset, TomTom returned no significant matches for 80 out of the CNN filters with motif information content greater than 3.0. The interactions of such filters require further investigation to discover the regulatory molecules associated with them.

As mentioned above, the motif matching results returned by TomTom are noisy and imperfect. For example, some of the statistically significant matches are clearly incorrect, as shown in Supplementary Figure F4. However, this is not a shortcoming of our model, but rather a limitation of the interpretation of filter-filter interactions.

3.4 Genome-wide regulatory interactions in arabidopsis

In the next experiment we evaluated the ability of SATORI to detect interactions on a genome-wide scale. For this task we chose to focus on regions of accessible chromatin in arabidopsis in a manner similar to our experiment in human promoter regions. More specifically, we predict chromatin accessibility from sequence across 36 arabidopsis samples from recently published arabidopsis DNase I-Seq and ATAC-Seq studies (GEO accession numbers provided in the Supplementary Methods section). Like

the previous dataset, this too is a multi-label prediction problem, where the labels indicates whether a given region has a peak in each of the 36 samples of DNase I-Seq and ATAC-Seq. We trained both deep learning architectures and as in the other datasets, the network that included an RNN layer performed better in terms of median AUC across samples (0.86 compared to 0.85).

In the next step, we investigated genome-wide regulatory interactions in those regions of open-chromatin. The trained network yielded 189 filters with information content above 3.0, and we obtained 100 unique matches for those filters in the DAP-Seq arabidopsis TF database [O'Malley *et al.*, 2016]. Among these 100 TFs, our model identified interactions between 230 pairs of of motifs involving diverse plant transcription factors (see Figure 4(a)). G2like, MYB, C2C2dof, and AP2 were the most frequently represented TF families in those interactions. Similarly to our findings in human, plant TF interactions tend to occur in relative proximity (median distance = 138 bp) as shown in Figure 4(b). Arabidopsis does not have a database of known interactions between TFs, so our results could not be validated. Targeted experimental validation of these predictions can thus significantly enrich our knowledge of the combinatorial regulation of gene expression in plants.

Fig. 6. Run time in minutes for SATORI and FIS-based interaction estimation for the four datasets.

3.5 Comparison: SATORI and FIS-based interactions

To compare our model to DFIM [Greenside *et al.*, 2018], we incorporated its FIS scoring method as a feature in our framework and tested it on the three real-world datasets. A key observation is that among the top scoring interactions predicted by the two methods there is very high overlap: In the TAL-GATA dataset the top 15 interactions predicted by FIS scoring were also predicted by SATORI; for the human promoter dataset 14 out of the top 15 FIS predictions were detected by SATORI; finally, for the arabidopsis genome-wide dataset, nine out of the top FIS predictions were predicted by SATORI. At the TF family level, we observed perfect agreement in the top ten predictions. These results are summarized in Figure 5. The agreement on the top predictions suggests their high likelihood of being biologically relevant, and make them promising candidates for experimental validation.

Among the three real-world datasets the lowest agreement was observed for the arabidopsis dataset. This is likely due to its complexity, as it probes interactions on a genome-wide scale across all accessible regions of the arabidopsis genome. Nevertheless, there is a high level of agreement at the level of TF families. We also compared the computation

times for the two methods. As discussed earlier, unlike the FIS method, SATORI does not require re-calculation of the gradients to estimate the interactions, leading to much faster computation times: it processed all motif interactions 8 to 20 times faster than FIS (see Figure 6).

In our experiments SATORI reported more interactions for the human and arabidopsis chromatin accessibility datasets, while the FIS method identified more motif interactions for the TAL-GATA experiment (see Supplementary Table S7). For the human promoter dataset, we searched the interactions identified by the two methods in the TRRUSTv2 database. Interestingly, for SATORI we found matches for 12 TF-TF interactions; in comparison only a single FIS interaction was found in the TRRUSTv2 database. Due to the small number of experimentally verified interactions more extensive wet-lab validation is needed to test the quality of the reported interactions by the two methods. High-frequency interactions consistently detected by both methods can be used as the most promising candidates for experimental follow-up.

4 Conclusions and Future Work

In this work we presented SATORI — a method for extracting interactions between the learned features of an attention-based deep learning model. Unlike existing methods, it does not require any post-processing and uses the sparsity of the attention matrix to infer the most salient interactions. We compared SATORI to the FIS interaction estimation method and reported a 10x speed-up in its computation time in most cases. Furthermore, the top predictions made by both methods show very high overlap, suggesting such interactions as promising targets for follow-up biological experiments. This high overlap, despite the big difference in the approach provides good evidence for their potential biological relevance.

The proposed method can be extended in several ways. In this work we focused on globally scoring interactions between TFs with known PWMs. This is in contrast to feature attribution methods that score the contribution of features in genomic regions of interest. We believe that the sparsity of the attention matrix could make it useful as an attribution method as well, but further experiments are required in order to validate that. SATORI is able to detect interactions between filters, even if they do not correspond to known TFs. Furthermore, the proposed methodology is flexible enough to be applied to deep networks that integrate multiple data modalities, and has potential applications outside of computational biology. For example, it can allow discovery of interactions between different characteristics of chromatin structure to provide a better understanding of the relationship between epigenetic markers such as histone modifications, DNA methylation, and nucleosome positioning and their contribution to the regulation of gene expression.

References

Alipanahi, B., Delong, A., Weirauch, M. T., and Frey, B. J. (2015). Predicting the sequence specificities of dna-and rna-binding proteins by deep learning. *Nature biotechnology*, **33**(8), 831.

Angermueller, C., Lee, H. J., Reik, W., and Stegle, O. (2017). Deepcpg: accurate prediction of single-cell dna methylation states using deep learning. *Genome biology*, **18**(1), 67.

Banovich, N. E., Li, Y. I., Raj, A., Ward, M. C., Greenside, P., Calderon, D., Tung, P. Y., Burnett, J. E., Myrthil, M., Thomas, S. M., *et al.* (2018). Impact of regulatory variation across human ipscs and differentiated cells. *Genome research*, **28**(1), 122–131.

Benjamini, Y. and Hochberg, Y. (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the Royal statistical society: series B (Methodological)*, **57**(1), 289–300.

Ceddia, G., Martino, L. N., Parodi, A., Secchi, P., Campaner, S., and Masseroli, M. (2019). Association rule mining to identify transcription factor interactions in genomic regions. *Bioinformatics (Oxford, England)*.

Chen, C., Hou, J., Shi, X., Yang, H., Birchler, J. A., and Cheng, J. (2019). Interpretable attention model in transcription factor binding site prediction with deep neural networks. *bioRxiv*, page 648691.

Crooks, G. E., Hon, G., Chandonia, J. M., and Brenner, S. E. (2004). Weblogo: A sequence logo generator. *Genome Research*, **14**, 1188–90.

Greenside, P., Shimko, T., Fordyce, P., and Kundaje, A. (2018). Discovering epistatic feature interactions from neural network models of regulatory dna sequences. *Bioinformatics*, **34**(17), i629–i637.

GuhaThakurta, D. and Stormo, G. D. (2001). Identifying target sites for cooperatively binding factors. *Bioinformatics*, **17**(7), 608–621.

Gupta, S., Stamatoyannopoulos, J. A., Bailey, T. L., and Noble, W. S. (2006). Quantifying similarity between motifs. *Genome Biology*, **8**, R24 – R24.

Han, H., Cho, J.-W., Lee, S., Yun, A., Kim, H., Bae, D., Yang, S., Kim, C. Y., Lee, M., Kim, E., *et al.* (2017). Trrust v2: an expanded reference database of human and mouse transcriptional regulatory interactions. *Nucleic acids research*, **46**(D1), D380–D386.

Hannenhalli, S. and Levy, S. (2002). Predicting transcription factor synergism. *Nucleic acids research*, **30**(19), 4278–4284.

Hassanzadeh, H. R. and Wang, M. D. (2016). Deeperbind: Enhancing prediction of sequence specificities of dna binding proteins. In *2016 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pages 178–183. IEEE.

Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, **9**(8), 1735–1780.

Kassouf, M. T., Hughes, J. R., Taylor, S., McGowan, S. J., Soneji, S., Green, A. L., Vyas, P., and Porcher, C. (2010). Genome-wide identification of tal1's functional targets: insights into its mechanisms of action in primary erythroid cells. *Genome research*, **20**(8), 1064–1083.

Kelley, D. R., Snoek, J., and Rinn, J. L. (2016). Basset: learning the regulatory code of the accessible genome with deep convolutional neural networks. *Genome research*, **26**(7), 990–999.

Koh, P. W., Pierson, E., and Kundaje, A. (2017). Denoising genome-wide histone chip-seq with convolutional neural networks. *Bioinformatics*, **33**(14), i225–i233.

Koo, P. K. and Ploenzke, M. (2019). Improving convolutional network interpretability with exponential activations. *bioRxiv*, page 650804.

Lin, Z., Feng, M., Santos, C. N. d., Yu, M., Xiang, B., Zhou, B., and Bengio, Y. (2017). A structured self-attentive sentence embedding. *arXiv preprint arXiv:1703.03130*.

Liu, G., Zeng, H., and Gifford, D. K. (2019). Visualizing complex feature interactions and feature sharing in genomic deep neural networks. *BMC bioinformatics*, **20**(1), 1–14.

O'Malley, R. C., Huang, S.-s. C., Song, L., Lewsey, M. G., Bartlett, A., Nery, J. R., Galli, M., Gallavotti, A., and Ecker, J. R. (2016). Cistrome and epicistrome features shape the regulatory dna landscape. *Cell*, **165**(5), 1280–1292.

Pan, X. and Shen, H.-B. (2017). Rna-protein binding motifs mining with a new hybrid deep learning based cross-domain knowledge integration approach. *BMC bioinformatics*, **18**(1), 136.

Parikh, A. P., Täckström, O., Das, D., and Uszkoreit, J. (2016). A decomposable attention model for natural language inference. *arXiv preprint arXiv:1606.01933*.

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., Bai, J., and Chintala, S. (2019). Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc.

Pilpel, Y., Sudarsanam, P., and Church, G. M. (2001). Identifying regulatory networks by combinatorial analysis of promoter elements. *Nature genetics*, **29**(2), 153.

Qin, Q. and Feng, J. (2017). Imputation for transcription factor binding predictions based on deep learning. *PLoS computational biology*, **13**(2), e1005403.

Quang, D. and Xie, X. (2016). Danq: a hybrid convolutional and recurrent deep neural network for quantifying the function of dna sequences. *Nucleic acids research*, **44**(11), e107–e107.

Roca, H. and Franceschi, R. T. (2008). Analysis of transcription factor interactions in osteoblasts using competitive chromatin immunoprecipitation. *Nucleic acids research*, **36**(5), 1723–1730.

Safe, S. (2015). Microrna-specificity protein (sp) transcription factor interactions and significance in carcinogenesis. *Current pharmacology reports*, **1**(2), 73–78.

Schreiber, J., Libbrecht, M., Bilmes, J., and Noble, W. (2018). Nucleotide sequence and dnasei sensitivity are predictive of 3d chromatin architecture. *bioRxiv*, page 103614.

Shrikumar, A., Greenside, P., and Kundaje, A. (2017). Learning important features through propagating activation differences. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 3145–3153. JMLR. org.

Sudarsanam, P., Pilpel, Y., and Church, G. M. (2002). Genome-wide co-occurrence of promoter elements reveals a cis-regulatory cassette of rrna transcription motifs in saccharomyces cerevisiae. *Genome research*, **12**(11), 1723–1731.

Sundararajan, M., Taly, A., and Yan, Q. (2017). Axiomatic attribution for deep networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 3319–3328. JMLR. org.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008.

Wasserman, W. W. and Fickett, J. W. (1998). Identification of regulatory regions which confer muscle-specific gene expression. *Journal of molecular biology*, **278**(1), 167–181.

Weirauch, M. T., Yang, A., Albu, M., Cote, A. G., Montenegro-Montero, A., Drewe, P., Najafabadi, H. S., Lambert, S. A., Mann, I., Cook, K. B., Zheng, H. Y., Goity, A., van Bakel, H., Lozano, J. F., Galli, M., Lewsey, M. G., Huang, E., Mukherjee, T., Chen, X., Reece-Hoyes, J. S., Govindarajan, S., Shaulsky, G., Walhout, A. J. M., Bouget, F.-Y., Ratsch, G., Larrondo, L. F., Ecker, J. R., and Hughes, T. R. (2014). Determination and inference of eukaryotic transcription factor sequence specificity. *Cell*, **158**, 1431–1443.

Zhang, S., Zhou, J., Hu, H., Gong, H., Chen, L., Cheng, C., and Zeng, J. (2015). A deep learning framework for modeling structural features of rna-binding protein targets. *Nucleic acids research*, **44**(4), e32–e32.

Zhou, J. and Troyanskaya, O. G. (2015). Predicting effects of noncoding variants with deep learning–based sequence model. *Nature methods*, **12**(10), 931.