Arbitrary Boolean logical search operations on massive molecular file systems

James L. Banal[1†], Tyson R. Shepherd[1†], Joseph Berleant[1†], Hellen Huang[1], Miguel Reyes[1,2],

Cheri M. Ackerman[2], Paul C. Blainey[1,2,3], and Mark Bathe[1,2*]

[1]Department of Biological Engineering, Massachusetts Institute of Technology, Cambridge, MA 02139 USA.

[2]Broad Institute of MIT and Harvard, Cambridge, MA 02142 USA.

[3]Koch Institute for Integrative Cancer Research at MIT, Cambridge, MA 02142 USA.

[*]Correspondence should be addressed to: mark.bathe@mit.edu

[†]These authors contributed equally to this work.

DNA is an ultra-high-density storage medium that could meet exponentially growing worldwide data storage demand. However, accessing arbitrary data subsets within exabyte-scale DNA data pools is limited by the finite addressing space for individual DNA-based blocks of data. Here, we form files by encapsulating data-encoding DNA within silica capsules that are surface-labeled with multiple unique barcodes. Barcoding is performed with single-stranded DNA representing file metadata that enables Boolean logic selection on the entire pool of data. We demonstrate encapsulation and Boolean selection of sub-pools of image files using fluorescence-activated sorting, with selection sensitivity of 1 in 10^6 files per channel. Our strategy in principle enables retrieval of targeted data subsets from exabyte- and larger-scale data pools, thereby offering a random access file system for massive molecular data sets.

DNA is the polymer used for storage and transmission of genetic information in biology. In principle, DNA can also be used as a medium for the storage of arbitrary digital information at densities far exceeding existing commercial data storage technologies and at scales well beyond the capacity of current data centers [1]. Ongoing advances in nucleic acid synthesis and sequencing technologies also continue to reduce dramatically the cost of writing and reading DNA, thereby rendering DNA-based digital information storage potentially viable economically in the near future [2-5]. As demonstrations of its viability as a general information storage medium, to date books, images, computer programs, audio clips, works of art, and Shakespeare's sonnets have all been stored in DNA using a variety of encoding schemes [6-12]. In each case, digital information was converted to DNA sequences and typically fragmented into 100–200 nucleotide (nt) blocks of data

for ease of chemical synthesis and sequencing. Sequence fragments were then assembled to

reconstruct the original, encoded information.

While significant research effort has focused on improving DNA synthesis and encoding

schemes, an additional, crucial aspect of digital data storage and retrieval is the ability to access

specific subsets of a data pool on demand, which is conventionally achieved using polymerase

chain reaction (PCR) [8,10,12]. PCR-based strategies take advantage of the ease of replication of DNA

to extract specific DNA sequences from a DNA data pool using custom-designed forward and

reverse primers that are complementary to the flanking sequences of interest. Nested addressing

barcodes [13-15] can also be used to uniquely identify files using multiple barcodes. For an exabyte-

scale data pool, each file requires at least four barcodes, or up to one hundred nucleotides in total

barcode sequence length, thereby nearly eliminating the number of nucleotides that can be used

for data encoding. Further, orthogonality of barcodes to other barcodes and file sequences present

in the data pool is essential for reliable data access. To overcome these limitations, previous

approaches have used spatial segregation of data into distinct pools [16]. While PCR is typically

known for its ease of amplifying specific DNA sequences, errors in priming via strand crosstalk

can lead to information loss. In addition, selective amplification of a specific file using PCR

requires access to the entire data pool for each query, which is also destructive to the sample

queried. Finally, PCR-based approaches do not allow for physical deletion of specific files from a

data pool, other than implementing an address overwrite [10].

As an alternative to PCR-based data access, inspired by genomic segmentation within

biological cells, here we physically encapsulate and thereby isolate DNA-based molecular data

within discrete silica capsules, which we subsequently label to enable random access of the data

pool via hybridization and subsequent optical selection. Each unit of information encoded in DNA

we term a *file*, which includes both the DNA encoding the main data as well as any additional

components used for addressing, storage, and retrieval. Each file contains a *file sequence*,

consisting of the DNA encoding the main data, and *addressing barcodes*, or simply *barcodes*,

which are additional short DNA sequences used to identify the file in solution using hybridization.

We refer to a collection of files as a *data pool* or *database*, and the procedures for storing,

retrieving, and reading out files is termed a *file system* (see **Supplementary Section S0** for a full

list of terms).

As a proof-of-principle of our file system, we encapsulated 3,000-nt plasmids encoding 85-

byte images, the files, within monodisperse, 6-µm spherical silica particles that were chemically

surface-labeled using up to three 25-mer single-stranded DNA (ssDNA) oligonucleotides, the

barcodes, chosen from a library of 240,000 orthogonal primers, allowing identification of up to

~10^{15} possible distinct files using only three unique barcodes per file [17] (**Fig. 1**). Twenty icon-

resolution images were chosen in the data pool to represent diverse subject matter including

animals, plants, transportation, and buildings, and labeled with DNA barcodes that represent the

categories to which each image belongs (**Supplementary Fig. 1**). Fluorescence-activated sorting

(FAS) was used to select target subsets of the complete data pool by first annealing fluorescent

oligonucleotide probes that are complementary to the barcodes, in order to address the DNA

database [18]. Retrieval of specific, individual files and collections of files described by Boolean

AND, OR, and NOT logic was achieved using combinations of distinct barcodes to query the data

pool. Because physical encapsulation separates file sequences from barcodes used to describe the

encapsulated information, our file system offers highly specific, robust data retrieval operations;

the ability to delete specific subsets of data; in addition to long-term environmental protection of

encoded file sequences via silica encapsulation [9,19,20]. While we apply our proposed file system to

a prototypical kilobyte-scale image database here, our approach is fully scalable to massive

molecular data pools at the exabyte- and larger-scales, as well as alternative encapsulation

strategies [21,22], barcode implementations [23-27], and physical or other sorting strategies using

biochemical affinity, optical, or other labeling approaches [28-30].

File Synthesis

Digital information in the form of 20 icon-resolution images was stored in a data pool, with each

image encoded into DNA and synthesized on a plasmid. We selected images of broad diversity,

representative of distinct and shared subject categories, which included several domestic and wild

cats and dogs, US presidents, and several human-made objects such as an airplane, boats, and

buildings (**Fig. 1** and **Supplementary Fig. 1**). To implement this image database, the images were

substituted with black-and-white, 26×26-pixel images to minimize synthesis costs, compressed

using run-length encoding, and converted to DNA (**Supplementary Fig. 1**, **2**). Following

synthesis, bacterial amplification, and sequencing validation (**Supplementary Fig. 3**), each

plasmid DNA was separately encapsulated into silica particles containing a fluorescein dye core

and a positively charged surface [19,20]. Because the negatively charged phosphate groups of the

DNA interact with positively charged silica particles, plasmid DNA condensed on the silica

surface, after which N-[3-(trimethoxysilyl)propyl]-N,N,N-trimethylammonium chloride

(TMAPS) was co-condensed with tetraethoxysilane to form an encapsulation shell after four days

of incubation at room-temperature [9,20] (**Fig. 2a**) to form discrete silica capsules containing the file

sequence that encodes for the image file. Quantitative PCR (qPCR) of the reaction supernatant

after encapsulation (**Supplementary Fig. 4**) showed full encapsulation of plasmids without

residual DNA in solution. To investigate the fraction of capsules that contained plasmid DNA, we

compared the fluorescence intensity of the intercalating dye TO-PRO when added pre- versus post-

encapsulation (**Supplementary Fig. 2**). All capsules synthesized in the presence of both DNA and

TO-PRO showed a distinct fluorescence signal, consistent with the presence of plasmid DNA in

the majority of capsules, compared with a silica particle negative control that contained no DNA.

In order to test whether plasmid DNA was fully encapsulated versus partially exposed at the

surface of capsules, capsules were also stained separately with TO-PRO post-encapsulation (**Fig.

2b**). Using qPCR, we estimated 10^6 plasmids per capsule assuming quantitative recovery of DNA

post-encapsulation (**Supplementary Fig. 5**).

Next, we chemically attached unique content addresses on the surfaces of silica capsules

using orthogonal 25-mer ssDNA barcodes (**Supplementary Fig. 6**) describing selected features of

the underlying image. For example, the image of an orange tabby house cat (**Supplementary Fig.

1**) was described with *cat*, *orange*, and *domestic*, whereas the image of a tiger was described with

cat, *orange*, and *wild* (**Supplementary Fig. 1** and **Supplementary Table 2**). To attach the

barcodes, we activated the surface of the silica capsules through a series of chemical steps.

Condensation of γ-aminopropyltriethoxysilane with the hydroxy-terminated surface of the

encapsulated plasmid DNA provided a primary amine chemical handle that supported further

conjugation reactions (**Fig. 2c**). We modified the amino-modified surface of the silica capsules

with β-azidoacetic acid N-hydroxysuccinimide (NHS) ester followed by an oligo(ethylene glycol)

that contained two chemically orthogonal functional groups: the dibenzocyclooctyne functional

group reacted with the surface-attached azide through strain-promoted azide-alkyne cycloaddition

while the NHS ester functional group was available for subsequent conjugation with a primary

amine. Each of the associated barcodes contained a 5'-amino modification that could react with

the NHS-ester groups on the surface of the silica capsules, thereby producing the complete form

of our file. Notably, the sizes of bare, hydroxy-terminated silica particles representing capsules

without barcodes were comparable with complete files consisting of capsules with barcodes

attached, confirmed using scanning electron microscopy (**Fig. 2d** and **2e**, left). These results were

anticipated given that the encapsulation thickness was only on the order of 10 nm [20] and that

additional steps to attach functional groups minimally increases the capsule diameter. We also

observed systematic shifts in the surface charge of the silica particles as different functional groups

were introduced onto their surfaces (**Fig. 2e**). Using hybridization assays with fluorescently-

labelled probes [31-33], we estimated the number of barcodes available for hybridization on our files

to be on the order of 10^8 (**Supplementary Fig. 7**). Following synthesis, files were pooled and

stored together for subsequent retrieval. Illumina MiSeq was used to read each file sequence and

reconstruct the encoded image following selection and de-encapsulation, in order to validate the

complete process of image file encoding, encapsulation, barcoding, selection, de-encapsulation,

sequencing, and image file reconstruction (**Supplementary Figs. 9**, **10**).

File Selection

Following file synthesis and pooling, we used FAS to select specific targeted file subsets from the

entire data pool. All files contained a fluorescent dye, fluorescein, in their core as a marker to

distinguish files from other particulates such as spurious silica particles that nucleated in the

absence of a core or insoluble salts that may have formed during the sorting process. Each detected

fluorescein event was therefore interpreted to indicate the presence of an individual file at

sufficiently low concentrations queried using FAS (**Supplementary Fig. 11**). For any query

applied to the entire image database, a fluorescently-labelled ssDNA probe hybridized to its

complementary barcode displayed externally on the surface of the silica capsule (**Fig. 3a**).

We subjected the entire data pool to a series of experiments to test selection sensitivity of

target subsets using distinct queries. First, we evaluated single-barcode selection of an individual

file, specifically *Airplane*, out of a pool of varying concentrations of the nineteen other files as

background (**Fig. 3b**). To select the *Airplane* file, we hybridized an AFDye 647-labelled ssDNA

probe that is complementary to the barcode *flying*, which is unique to *Airplane*. We were able to

detect and select the desired *Airplane* file through FAS even at a relative abundance of 10^{-6}

compared with each other file (**Fig. 3c).** Comparison of the retrieved sequences between the flying

gate and the NOT flying gate after chemical release of the file sequences from silica encapsulation

revealed that 60–95% of the *Airplane* files were sorted into the flying gate (**Supplementary Figs.**

18–21). Note that any sort probability above 50% indicates enrichment of *Airplane* within the

correct population subset (flying) relative to the incorrect subset (NOT flying), while a sort

probability of 100% would indicate ideal performance.

Boolean Search

Aside from selecting single files, Boolean logic can be used to select a specific subset of the data

pool. We demonstrated AND, OR, and NOT logical operations by first adding to the data pool

fluorescently-labelled ssDNA probes that were complementary to the barcodes (**Fig. 4**, left). This

hybridization reaction was used to distinguish one or several files in the data pool, which were

then sorted using FAS. We used two to four fluorescence channels simultaneously to create the

FAS gates that executed the target Boolean logic queries (**Fig. 4,** middle). To demonstrate a NOT

query, we added to the data pool an AFDye 647-labelled ssDNA probe that hybridized to files that

contained the *cat* barcode. Files that did not show AFDye 647 signal were sorted into the NOT cat

subset (**Fig. 4a**). An example of an OR gate was applied to the data pool by simultaneously adding

dog and *building* probes that both had the TAMRA label (**Fig. 4b**). All files that showed TAMRA

signal were sorted into the dog OR building subset by the FAS. Finally, an example of an AND

gate was achieved by adding *fruit* and *yellow* probes that were labelled with AFDye 647 and

TAMRA, respectively. Files showing signal for both AFDye 647 and TAMRA were sorted into

the fruit AND yellow subset in the FAS (**Fig. 4c**). For each example query, we validated our sorting

experiments by releasing the file sequence from silica encapsulation and sequencing the released

DNA with Illumina MiniSeq (**Fig. 4**, right). Sort probabilities of each file for each search query

are shown in **Supplementary Figs. S22–S24**.

The preceding demonstrations of Boolean logic gates enable sorting of files with varying

specificity of selection criteria for the retrieval of different subsets of the data pool. FAS can also

be used to create multiple gating conditions simultaneously, thereby increasing the specificity of

file selections. To demonstrate increasingly complex Boolean search queries, we selected the file

containing the image of Abraham Lincoln from the data pool, which included images of two

presidents, George Washington and Abraham Lincoln. The *president* ssDNA probe, fluorescently-

labeled with TAMRA, selected both *Lincoln* and *Washington* files from the data pool. The

simultaneous addition of the *18th century* ssDNA probe, fluorescently-labeled with AFDye 647

(**Fig. 5a**, left), discriminated *Washington*, which contained the *18th century* barcode, from the

Lincoln file (**Fig. 5a**, middle). The combination of these two ssDNA probes permitted the complex

search query president AND (NOT 18th century). Sequencing analysis of the gated populations

after reverse encapsulation validated that the sorted populations matched search queries for

president AND (NOT 18th century), president AND 18th century, and NOT president (**Fig. 5a**,

right; **Supplementary Fig. 25**).

To demonstrate the possibility of performing Boolean search using more than three

fluorescence channels for sorting, we selected the *Wolf* file from the data pool using the query dog

AND wild, and used the *black & white* probe to validate the selected file (**Fig. 5b**, left). Because

conventional FAS software is only capable of sorting using 1D and 2D gates, we first selected one

out of the three possible 2D plots (**Fig. 5b**, left and bottom): *dog*-TAMRA against *wild*-AFDye

647. We examined the *black & white*-TYE705 channel on members of the dog AND wild subset

(**Fig. 5b**, left and bottom). Release of the encapsulated file sequence and subsequent sequencing

of each gated population from the *dog* versus *wild* 2D plot validated sorting (**Fig. 5b**, right;

Supplementary Fig. 26).

The use of plasmids as a substrate for encoding information offered a convenient workflow

for restoring files into the data pool after retrieval. In cases where single images were sorted (**Figs.**

4c, **5a**, **b**), we were able to transform competent bacteria from each search query that resulted in a

single file (**Supplementary Fig. 27**). Amplified material was pure and ready for re-encapsulation

into silica particles, which could be re-introduced directly back into the data pool. Importantly, our

molecular file system and file selection process thereby represents a complete write-access-read

cycle that can in principle be applied to exabyte and larger-scale datasets. While sort probabilities

were typically below the perfect 100% targeted for a specific file or file subset query, future work

would be required to better characterize sources of error that may be due to sample contamination,

FAS error, or imperfect orthogonality of barcode sequences employed (**Supplementary Fig. 6**) [17].

Outlook

We present a non-destructive molecular file system that is capable of both specific file selection

and Boolean logic search operations for random access of single files or file subsets in a data pool.

Our implementation easily scales by increasing the numbers of barcodes per file and query

fluorophores used for file selection, which can thereby address files in a larger-scale database for

random access and computation. For example, labeling each file using four distinct barcodes

instead of only the three used here renders it possible to label $\binom{2.4\times10^5}{4} \approx 10^{20}$ files uniquely using

the existing pool of ~10^5 orthogonal barcodes [17]. Assuming an FAS system is capable of sorting a

single file from 10^6 others using each fluorescent channel alone, as demonstrated in this work using

a commercial FAS, one may theoretically sort a single file from 10^{24} others using a conventional

four-channel FAS system. This file system would then in principle offer sufficient sensitivity and

specificity to select a single file from an exabyte or even yottabyte data pool. However, the time

needed to perform FAS scales linearly with the size of the data pool, which may be prohibitively

long even for exabyte-scale data pools using only 10–100 bytes per file. For example, 12 minutes

was required to select at least one hundred copies of the *Airplane* file in a data pool in which this

file has a relative abundance of 10^{-6} compared with other files (**Fig. 3**). This is in contrast to

selecting one hundred copies of the *Airplane* file in a data pool that contained equivalent numbers

of nineteen other files, which required only ~30 seconds. Thus, in order to search through an entire

exabyte-scale data pool within 24 hours, each file should consist of approximately 100 gigabytes,

assuming a typical commercial FAS device that searches at 10,000 files per second. In order to

reduce file selection time, future implementations of our molecular file system should therefore

leverage parallel microfluidics-based optical sorting procedures and brighter fluorescence probes

to increase selection throughput and sensitivity, and thereby reduce the pool search time.

Alternatively, direct magnetic pulldown of files labelled with biochemical or affinity tags may be

employed [30].

Aside from speed and specificity of data access, data density is also of importance to DNA

data storage. Notably, both file size and data density can be tuned independently in our file system

by changing the information content of loaded DNA and the size of the silica particles employed

for encapsulation. While we used 6-µm silica core particles here in order to maximize fluorescence

signal-to-noise ratios for a commercial FAS instrument, this also limited volumetric density of our

DNA file system [3]. Specifically, using this approach an exabyte-scale data pool consisting of a

100-byte file per particle would require approximately 10^{16} files and 1 m^3 total dry volume, or 10^{18}

bytes per m^3. In comparison, PCR-based random access has a theoretical volumetric density limit

of 10^{24} bytes per m^3 [3], although additional methods are required to prevent crosstalk between file

sequences and barcodes. To further increase the data density of our file system, future

implementations may benefit from using nanoparticles ~100–200 nm in diameter to encode files

[9,19,20] and higher sensitivity FAS systems [34,35] or direct biochemical, magnetic, or other pulldown

for file and data subset selection from the data pool.

Beyond increasing file selection speed and data density, utilization of spectrally distinct

fluorescent probes and discrete labeling intensities [26] would allow for far more complex and

efficient logical operations than demonstrated here [36]. Physical particle parameters including

forward and side-scatter could additionally be used to perform multi-dimensional sorting of

particles with different scattering cross-sections, with or without additional fluorescence channels

[37]. Repeated cycles of file selection in series could also further increase selection fidelity. While

our technical approach differs significantly from approaches that rely on selective amplification

for block selection [8,12,16], in which amplifications may reduce fidelity of file selection, PCR-based

random access approaches will typically have faster read-write times because they forgo

encapsulation and de-encapsulation steps required by our approach [9,19,20], which is therefore ideally

suited to long-term, archival data storage and retrieval with periodic file and barcode renewal.

Aside from DNA data storage, population enrichment on our prototypical database of 20 unique

files encoded in DNA plasmids with silica encapsulation and retrieval demonstrated using

barcodes labels may alternatively be applied directly to biological DNA and other nanoscale

sample management, such as genomic samples in biobanking or protein-encoding databases [38]. In

either case, subsets of data or genomic sample pools may be enriched using Boolean AND, OR,

and NOT logic, which complements existing PCR-based approaches. These operations enrich the

capabilities of performing computation and sorting on underlying molecular data pools, moving

us closer to realizing an economically viable, functional, massive molecular file and operating

system [18,39,40].

References

1   Ceze, L., Nivala, J. & Strauss, K. Molecular digital data storage using DNA. *Nature*

264   *Reviews Genetics* **20**, 456-466, doi:10.1038/s41576-019-0125-3 (2019).

265 2   Kosuri, S. & Church, G. M. Large-scale de novo DNA synthesis: technologies and

266   applications. *Nature Methods* **11**, 499-507, doi:10.1038/nmeth.2918 (2014).

267 3   Zhirnov, V., Zadegan, R. M., Sandhu, G. S., Church, G. M. & Hughes, W. L. Nucleic

268   acid memory. *Nature Materials* **15**, 366, doi:10.1038/nmat4594 (2016).

269 4   Palluk, S. *et al.* De novo DNA synthesis using polymerase-nucleotide conjugates. *Nature*

270   *Biotechnology* **36**, 645-650, doi:10.1038/nbt.4173 (2018).

271 5   Lee, H. H., Kalhor, R., Goela, N., Bolot, J. & Church, G. M. Terminator-free template-

272   independent enzymatic DNA synthesis for digital information storage. *Nature*

273   *Communications* **10**, 2383, doi:10.1038/s41467-019-10258-1 (2019).

6   Church, G. M., Gao, Y. & Kosuri, S. Next-generation digital information storage in

DNA. *Science* **337**, 1628, doi:10.1126/science.1226355 (2012).

7   Goldman, N. *et al.* Towards practical, high-capacity, low-maintenance information

storage in synthesized DNA. *Nature* **494**, 77-80, doi:10.1038/nature11875 (2013).

8   Yazdi, S. M. H. T., Yuan, Y., Ma, J., Zhao, H. & Milenkovic, O. A rewritable, random-

access DNA-based storage system. *Scientific Reports* **5**, 14138, doi:10.1038/srep14138

(2015).

9   Grass, R. N., Heckel, R., Puddu, M., Paunescu, D. & Stark, W. J. Robust chemical

preservation of digital information on DNA in silica with error-correcting codes.

Angewandte Chemie International Edition **54**, 2552-2555, doi:10.1002/anie.201411378

(2015).

10   Yazdi, S. M. H. T., Gabrys, R. & Milenkovic, O. Portable and error-free DNA-based data

storage. *Scientific Reports* **7**, 5011, doi:10.1038/s41598-017-05188-1 (2017).

11   Erlich, Y. & Zielinski, D. DNA Fountain enables a robust and efficient storage

architecture. *Science* **355**, 950-954, doi:10.1126/science.aaj2038 (2017).

12   Organick, L. *et al.* Random access in large-scale DNA data storage. *Nature*

Biotechnology **36**, 242–248, doi:10.1038/nbt.4079 (2018).

13   Kashiwamura, S., Yamamoto, M., Kameda, A., Shiba, T. & Ohuchi, A. in *DNA 2002:*

DNA Computing. (eds M. Hagiya & A. Ohuchi) 112–123 (Lecture Notes in Computer

Science, Vol. 2568, Springer, 2003).

14   Yamamoto, M., Kashiwamura, S., Ohuchi, A. & Furukawa, M. Large-scale DNA

memory based on the nested PCR. *Natural Computing* **7**, 335-346 (2008).

15   Yamamoto, M., Kashiwamura, S. & Ohuchi, A. in *DNA 2007: DNA Computing.* (eds

M.H. Garzon & H. Yan) 99–108 (Lecture Notes in Computer Science, Vol. 4848,

Springer).

16   Newman, S. *et al.* High density DNA data storage library via dehydration with digital

microfluidic retrieval. *Nature Communications* **10**, 1706 (2019).

17   Xu, Q., Schlabach, M. R., Hannon, G. J. & Elledge, S. J. Design of 240,000 orthogonal

25mer DNA barcode probes. *Proceedings of the National Academy of Sciences* **106**,

2289-2294, doi:10.1073/pnas.0812506106 (2009).

18   Reif, J. H. *et al.* in *DNA 2001: DNA Computing.* (eds N. Jonoska & N.C. Seeman) 231–

247 (Lecture Notes in Computer Science, Vol. 2340, Springer, 2002).

19   Paunescu, D., Fuhrer, R. & Grass, R. N. Protection and deprotection of DNA--high-

temperature stability of nucleic acid barcodes for polymer labeling. *Angewandte Chemie*

International Edition **52**, 4269-4272, doi:10.1002/anie.201208135 (2013).

20   Paunescu, D., Puddu, M., Soellner, J. O. B., Stoessel, P. R. & Grass, R. N. Reversible

DNA encapsulation in silica to produce ROS-resistant and heat-resistant synthetic DNA

"fossils". *Nature Protocols* **8**, 2440, doi:10.1038/nprot.2013.154 (2013).

21   Alexakis, T. *et al.* Microencapsulation of DNA within alginate microspheres and

crosslinked chitosan membranes for in vivo application. *Applied Biochemistry and*

Biotechnology **50**, 93-106 (1995).

22   Borodina, T. *et al.* Controlled release of DNA from self-degrading microcapsules.

Macromolecular Rapid Communications **28**, 1894-1899, doi:10.1002/marc.200700409

(2007).

23   Braeckmans, K. *et al.* Encoding microcarriers by spatial selective photobleaching. *Nature*

Materials **2**, 169-173, doi:10.1038/nmat828 (2003).

24   Wilson, R., Cossins, A. R. & Spiller, D. G. Encoded microcarriers for high-throughput

multiplexed detection. *Angewandte Chemie International Edition* **45**, 6104-6117,

doi:10.1002/anie.200600288 (2006).

25   Pregibon, D. C., Toner, M. & Doyle, P. S. Multifunctional encoded particles for high-

throughput biomolecule analysis. *Science* **315**, 1393-1396, doi:10.1126/science.1134929

(2007).

26   Dagher, M., Kleinman, M., Ng, A. & Juncker, D. Ensemble multicolour FRET model

enables barcoding at extreme FRET levels. *Nature Nanotechnology* **13**, 925-932,

doi:10.1038/s41565-018-0205-0 (2018).

27   Martino, N. *et al.* Wavelength-encoded laser particles for massively multiplexed cell

tagging. *Nature Photonics* **13**, 720-727, doi:10.1038/s41566-019-0489-0 (2019).

28   Lee, H., Kim, J., Kim, H., Kim, J. & Kwon, S. Colour-barcoded magnetic microparticles

for multiplexed bioassays. *Nature Materials* **9**, 745-749, doi:10.1038/nmat2815 (2010).

29   Stewart, K. *et al.* in *International Conference on DNA Computing and Molecular*

Programming. 55-70 (Vol. Springer).

30   Tomek, K. J. *et al.* Driving the scalability of DNA-based information storage systems.

ACS Synthetic Biology **8**, 1241-1248, doi:10.1021/acssynbio.9b00100 (2019).

31   Pillai, P. P., Reisewitz, S., Schroeder, H. & Niemeyer, C. M. Quantum-dot-encoded silica

nanospheres for nucleic acid hybridization. *Small* **6**, 2130-2134,

doi:10.1002/smll.201000949 (2010).

32   Leidner, A. *et al.* Biopebbles: DNA-functionalized core–shell silica nanospheres for

cellular uptake and cell guidance studies. *Advanced Functional Materials* **28**, 1707572,

doi:10.1002/adfm.201707572 (2018).

33   Sun, P. *et al.* Biopebble containers: DNA-directed surface assembly of mesoporous silica

nanoparticles for cell studies. *Small* **15**, 1900083, doi:10.1002/smll.201900083 (2019).

34   van Gaal, E. V. B., Spierenburg, G., Hennink, W. E., Crommelin, D. J. A. &

Mastrobattista, E. Flow cytometry for rapid size determination and sorting of nucleic acid

containing nanoparticles in biological fluids. *Journal of Controlled Release* **141**, 328-

338, doi:10.1016/j.jconrel.2009.09.009 (2010).

35   Lian, H., He, S., Chen, C. & Yan, X. Flow cytometric analysis of nanoscale biological

particles and organelles. *Annual Review of Analytical Chemistry* **12**, 389-409,

doi:10.1146/annurev-anchem-061318-115042 (2019).

36   Perfetto, S. P., Chattopadhyay, P. K. & Roederer, M. Seventeen-colour flow cytometry:

unravelling the immune system. *Nature Reviews Immunology* **4**, 648-655,

doi:10.1038/nri1416 (2004).

37   Mage, P. L. *et al.* Shape-based separation of synthetic microparticles. *Nature Materials*

18, 82-89, doi:10.1038/s41563-018-0244-9 (2019).

38   Plesa, C., Sidore, A. M., Lubock, N. B., Zhang, D. & Kosuri, S. Multiplexed gene

synthesis in emulsions for exploring protein functional landscapes. *Science* **359**, 343-347,

doi:10.1126/science.aao5167 (2018).

39   Baum, E. B. Building an associative memory vastly larger than the brain. *Science* **268**,

583-585 (1995).

40 Song, X. & Reif, J. Nucleic acid databases and molecular-scale computing. *ACS Nano*

13, 6256-6268, doi:10.1021/acsnano.9b02562 (2019).

Acknowledgments. We gratefully acknowledge fruitful discussions with Charles Leiserson and

Tao B. Schardl on the scalability and generalizability of our barcoding approach. We thank Glenn

Paradis, Michael Jennings, and Michele Griffin of the Flow Cytometry Core at the Koch Institute

in MIT and Patricia Rogers of the Flow Cytometry Facility at the Broad Institute of Harvard and

MIT for assistance and fruitful discussions in developing the flow cytometry workflow. We also

thank David Mankus of the Nanotechnology Materials Core Facility at the Koch Institute in MIT

for assistance in the imaging of the particles using the scanning electron microscope and Alla

Leshinsky of the Biopolymer and Proteomics Core at the Koch Institute at MIT for assistance in

mass spectrometry.

Funding. M.B., J.L.B., T.R.S., and J.B. gratefully acknowledge funding from the Office of Naval

Research N00014-17-1-2609, N00014-16-1-2506, N00014-12-1-0621, and N00014-18-1-2290

and the National Science Foundation CCF-1564025 and CBET-1729397. Additional funding to

J.B. was provided through an NSF Graduate Research Fellowship (Grant # 1122374). P.C.B. was

supported by a Career Award at the Scientific Interface from the Burroughs Wellcome Fund.

C.M.A. was supported by NIH grant F32CA236425.

Author contributions. J.L.B., T.R.S., and M.B. designed the file labeling and selection scheme.

J.L.B, T.R.S., and C.M.A. implemented the file selection scheme using FAS. J.B. and T.R.S.

developed the encoding scheme and metadata tagging of the images to DNA. T.R.S. designed the

plasmid for encoding imaging. H.H. and T.R.S. performed the cloning, transformation, and

purification of the plasmids. J.L.B. synthesized and purified all the TAMRA and AFDye 647-

labelled DNA oligonucleotides. J.L.B. characterized the particles. J.L.B. developed the synthetic route to attach DNA barcodes on the surface of the particles. J.L.B. performed the encapsulation, barcoding, sorting, reverse encapsulation of the particles after sorting, and desalting. T.R.S., H.H., and M.R. performed the sequencing. J.B. performed computational validation of the orthogonality of barcode sequences. J.B. developed the computational workflow to analyze the sequencing data, including statistical analyses. M.B. conceived of the file system and supervised the entire project. P.C.B. supervised the FAS selection and supervised the sequencing workflow. All authors analyzed the data and equally contributed to the writing of the manuscript.

Competing interests. T.R.S., J.L.B., J.B. & M.B. have filed provisional patents (17/029,948 and 16/012,583) related to this work.

Materials and correspondence. Gene sequences and plasmid maps are available from AddGene (https://www.addgene.org/depositing/77231/). Software for sequence encoding and decoding is publicly available on GitHub (https://github.com/lcbb/DNA-Memory-Blocks/). All the data files used to generate the plots in this manuscript are available from M.B. upon request.

Online content. Any methods, additional references, and supplementary information are available at https://doi.org/10.10XX/XXXXX.

Figure 1 | Write-access-read cycle for a content-addressable molecular filesystem. Colored images were converted into 26×26-pixel, black-and-white icon bitmaps. The black-and-white images were then converted into DNA sequences using ternary encoding scheme [7]. The DNA sequences that encoded the images (file sequences) were inserted into a pUC19 plasmid vector and encapsulated into silica particles using sol-gel chemistry. Silica capsules were then addressed with content barcodes using orthogonal 25-mer single-stranded DNA strands, which were the final forms of the files. Files were pooled to form the molecular file database. To query a file or several files, fluorescently-labelled 15-mer ssDNA probes that are complementary to file barcodes were added to the data pool. Particles were then sorted with fluorescence-activated sorting (FAS) using two to four fluorescence channels simultaneously. Addition of a chemical etching reagent into the sorted populations released the encapsulated DNA plasmid. Sequences for the encoded images were validated using Sanger sequencing or Illumina MiniSeq. Because plasmids were used to encode information, re-transformation of the released plasmids into bacteria to replenish the molecular file database thereby closed the write-access-read cycle.

Figure 2 | Encapsulation of DNA plasmids into silica and surface barcoding. a, Workflow of

silica encapsulation [20]. **b**, Raw fluorescence data from FAS experiments to detect DNA staining of

TO-PRO during or after encapsulation. **c**, Functionalization of encapsulated DNA particles. **d,**

Scanning electron microscopy images of bare silica particles, silica particles functionalized with

TMAPS, and the file. **e,** Distribution of particle sizes determined from microscopy data (left) and

zeta potential analyses of silica particles and files.

Figure 3 | Single-barcode sorting. a, Schematic diagram of file sorting using FAS. **b**, Sorting of

Airplane from varying relative abundance of the other nineteen files as background. Percentages

represent the numbers of particles that were sorted in the gate. Colored traces in each of the sorting

plots indicate the target population. **c,** Sequencing validation using Illumina MiniSeq. Sort

probability is the probability that a file is sorted into one gated population over the other gated

populations. Boxes with solid outlines indicate files that should be sorted into the specified gate.

Other files have dashed outlines.

Figure 4 | Fundamental Boolean logic gates. a, `NOT cat` selection. Raw fluorescence trace from the FAS system (left) plotted on a 1D sorting plot showing the percent of particles that were sorted in each gate. Sequencing using Illumina MiniSeq tested selection specificity (right). **b,** `dog OR building` selection. Raw fluorescence trace from the FAS system (left) plotted on a 1D sorting plot showing the percent of particles that were sorted in each gate. Sequencing using Illumina MiniSeq evaluated sorting using the OR gate (right). **c,** A 2D sorting plot to perform a

444   `yellow AND fruit` gate. Percentages in each quadrant show the percentages of particles that

445   were sorted in each gate. Colored traces in all of the sorting plots indicate the target populations.

446   Sort probability is the probability that a file is sorted into one gated population versus the other

447   gated populations. Boxes with solid outlines indicate files that were intended to sort into the

448   specified gate. Other files have dashed outlines.

Figure 5 | Arbitrary logic searching. a, `president AND (NOT 18th century)` sorting. A 2D sorting plot (middle) was used to sort *Lincoln* by selecting a population that has high TAMRA fluorescence but low AFDye 647 fluorescence. Sequencing using MiniSeq offered quantitative evaluation of the sorted populations. **b,** Multiple fluorescence channels were projected into a 3D FAS plot (left and top). There are three possible 2D plots that can be used for sorting. To select the *Wolf* image using the query wild AND dog, a 2D plot of *wild* versus *dog* was first selected and then populations selected using quadrant gates (left and bottom). One of the quadrants were then selected where the *Wolf* image should belong based on the `wild AND dog` query in

460   order to test whether only a single population was present in the TYE705 fluorescence channel.

461   Sequencing quantified the sorted populations (right) using Illumina MiniSeq. Sort probability is

462   the probability that a file was sorted into one gated population over the other gated populations.

463   Boxes with solid outlines indicate files that would ideally be sorted into the specified gate. Other

464   files have dashed outlines.