Metagenomics workflow for hybrid assembly, differential coverage binning, transcriptomics and pathway analysis (MUFFIN)

Renaud Van Damme[1,2], Martin Hölzer[4], Adrian Viehweger[3,4], Bettina Müller[1], Erik Bongcam-Rudloff[2], Christian Brandt[2,5]

1. Department of Molecular Sciences, Swedish University of Agricultural Sciences, Uppsala, Sweden

2. Dept. Animal Breeding and Genetics, Bioinformatics section. Swedish University of Agricultural, Sciences, Uppsala, Sweden

3. Department of Medical Microbiology, University Hospital Leipzig, Germany

4. RNA Bioinformatics and High-Throughput Analysis, Friedrich Schiller University Jena, Jena, Germany

5. Institute for Infectious Diseases and Infection Control, Jena University Hospital, Jena, Germany

Abstract

Metagenomics has redefined many areas of microbiology. However, metagenome-assembled genomes (MAGs) are often fragmented, primarily when sequencing was performed with short reads. Recent long-read sequencing technologies promise to improve genome reconstruction. However, the integration of two different sequencing modalities makes downstream analyses complex. We, therefore, developed MUFFIN, a complete metagenomic workflow that uses short and long reads to produce high-quality bins and their annotations. The workflow is written by using Nextflow, a workflow orchestration software, to achieve high reproducibility and fast and straightforward use. This workflow also produces the taxonomic classification and KEGG pathways of the bins and can be further used by providing RNA-Seq data (optionally) for quantification and annotation. We tested the workflow using twenty biogas reactor samples and assessed the capacity of MUFFIN to process and output relevant files needed to analyze the microbial community and their function. MUFFIN produces functional pathway predictions and if provided *de novo* transcript annotations across the metagenomic sample and for each bin.

Author Summary

RVD did the development and design of MUFFIN and wrote the first draft; BM and EBR did the critical reading and correction of the manuscript; MH did the critical reading of the manuscript and the general adjustments for the metagenomic workflow; AV did the critical reading of the manuscript and adjustments for the taxonomic classifications. CB supervised the project, did the workflow design, helped with the implementation, and revised the manuscript.

Introduction

Metagenomics is widely used to analyze the composition, structure, and dynamics of microbial communities, as it provides deep insights into uncultivatable organisms and their relationship to each other [1–5]. In this context, whole metagenome sequencing is mainly performed using short-read sequencing technologies, predominantly provided by Illumina. Not surprisingly, the vast majority of tools and workflows for the analysis of metagenomic samples are designed around short reads. However, long-read sequencing technologies such as provided by PacBio or Oxford Nanopore Technologies (ONT) retrieve genomes from metagenomic datasets with higher completeness and less contamination [6]. The long-read information bridges gaps in a short-read-only assembly that often occur due to intra- and interspecies repeats [6]. Complete viral genomes can be already identified from environmental samples without any assembly step via nanopore-based sequencing [7]. Combined with a reduction in cost per gigabase [8] and an increase in data output, the technologies for sequencing long reads quickly became suitable for metagenomic analysis [9–12]. In particular, with the MinION, ONT offers mobile and cost-effective sequencing device for long reads that paves the way for the real-time analysis of metagenomic samples. Currently, the combination of both worlds (long reads and high-precision short reads) allows the reconstruction of more complete and more accurate metagenome-assembled genomes (MAGs) [6].

One of the main challenges and bottlenecks of current metagenome sequencing studies is the orchestration of various computational tools into stable and reproducible workflows to

analyze the data. A recent study from 2019 involving 24,490 bioinformatics software

resources showed that 26 % of all these resources are not currently online accessible [13].

Among 99 randomly selected tools, 49 % were deemed 'difficult to install,' and 28 %

ultimately failed the installation procedure. For a large-scale metagenomics study, various

tools are needed to analyze the data comprehensively. Thus, already during the installation

procedure, various issues arise related to missing system libraries, conflicting dependencies

and environments or operating system incompatibilities. Even more complicating,

metagenomic workflows are computing intense and need to be compatible with high-

performance compute clusters (HPCs), and thus different workload managers such as

SLURM or LSF. We combined the workflow manager Nextflow[14] with virtualization software

(so-called 'containers') to generate reproducible results in various working environments and

allow full parallelization of the workload on a higher degree.

Several workflows for metagenomic analyses have been published, including

MetaWRAP(v1.2.1)[15], Anvi'o[16], SAMSA2[17], Humann[18], or MG-Rast[19]. Unlike those, MUFFIN

allows for a hybrid metagenomic approach combining the strengths of short and long reads.

It ensures reproducibility through the use of a workflow manager and reliance on either install

recipes (Conda [20]) or containers (Docker[21]).

74   Design and implementation

MUFFIN integrates state-of-the-art bioinformatic tools via Conda recipes or Docker

containers for the processing of metagenomic sequences in a Nextflow workflow

environment (Figure 1). MUFFIN executes three steps subsequently or separately if

intermediate results, such as MAGs, are available. As a result, a more flexible workflow

execution is possible. The three steps represent common metagenomic analysis tasks and

are summarized in Figure 1:

1. Assemble: Hybrid assembly and binning

2. Classify: Bin quality control and taxonomic assessment

3. Annotate: Bin annotation and KEGG pathway summary

The workflow takes paired-end Illumina reads (short reads) and nanopore-based reads (long

reads) as input for the assembly and binning and allows for additional user-provided read

sets for differential coverage binning. Differential coverage binning facilitates genome bins

with higher completeness than other currently used methods [22]. Step 2 will be executed

automatically after the assembly and binning procedure or can be executed independently by

providing MUFFIN a directory containing MAGs in FASTA format. In step 3, paired-end RNA-

Seq data can be optionally supplemented to improve the annotation of bins.

On completion, MUFFIN provides various outputs such as the MAGs, KEGG pathways, and

bin quality/annotations. Additionally, all mandatory databases are automatically downloaded

and stored in the working directory or can be alternatively provided via an input flag.

Step 1 - Assemble: Hybrid assembly and binning

The first step (**Assembly and binning**), uses metagenomic nanopore-based long reads and

Illumina paired-end short reads to obtain high-quality and highly complete bins. The short-

read quality control is operated using fastp (v0.20.0) [23]. Optionally, Filtlong (v0.2.0) [24] can be

used to discard long reads below a length of 1000 bp [24]. The hybrid assembly can be

performed according to two principles, which differ substantially in the read set to begin with.

The default approach starts from a short-read assembly where contigs are bridged via the

long reads using metaSPAdes (v3.13.1) [25–27]. Alternatively, MUFFIN can be executed starting

from a long-read-only assembly using metaFlye (v2.6) [28,29] followed by polishing the

assembly with the long reads using Racon (v1.4.7) [30] and medaka (v0.11.0) [31] and finalizing

the error correction by incorporating the short reads using multiple rounds of Pilon (v1.23) [32].

Binning is the most crucial step during metagenomic analysis. Therefore, MUFFIN combines

three different binning software tools, respectively CONCOCT (v1.0.0) [33], MaxBin2 (v2.2.4)

[34], and MetaBAT2 (v2.14) [35] and refine these bins via MetaWRAP (v1.2.1)[15]. The user can

provide additional read data sets (short or long reads) to perform automatically differential

coverage binning to assign contigs to their bins better.

Moreover, an additional reassembly of bins has shown the capacity to increase the

completeness and N50 while decreasing the contamination of the bins[15]. Therefore, MUFFIN

allows for an optional reassembly to improve the continuity of the MAGs further. This re-

assembly is performed by retrieving the reads belonging to one bin and doing an assembly

with Unicycler (v0.4.8) [36].

To support a transparent and reproducible metagenomics workflow, all reads that cannot be

mapped back to the existing high-quality bins (after the refinement) are available as an

output for further analysis. These reads could be further analyzed by other tools or, e.g.,

used as a new input to run MUFFIN while providing other read sets for the differential

coverage binning to extract additional high-quality bins.

Step 2 - Classify: Bin quality control and taxonomic assessment

In the second step (**Bin quality control and taxonomic assessment**), the quality of the

bins is evaluated with CheckM (v1.0.18) [37] followed by assigning a taxonomic classification

to the bins using sourmash (v2.0.0a10) [38] and the Genome Taxonomy Database (GTDB

release r89) [39]. The GTDB was chosen as it contains many unculturable bacteria and

archaea – this allows for monophyletic species assignments, which other databases do not

assure [40,41]. GTDB substantially improved overall downstream results [40]. The user can also

analyze other bin sets in this step regardless of their origin by providing a directory with

multiple FASTA files (bins).

Step 3 - Annotate: Bin annotation and KEGG pathway summary

The last step of MUFFIN (**Bin annotation and output summary**) comprises the annotation

of the bins using eggNOG-mapper (v2.0.1) [42] and the eggNOG database (v5) [43]. If RNA-Seq

data of the metagenome sample is provided (Illumina, paired-end), quality control using fastp

(v0.20.0) [23] and a *de novo* transcript assembly using Trinity (v2.8.5) [44] followed by a quasi-

mapping transcript quantification using Salmon (v0.15.0) [45] are performed. Lastly, the

transcripts are annotated using eggNOG-mapper (v2.0.1) [42] again, followed by a parser to

output the activity of the pathway graphically in relation to the sample level. The expression

of low and high abundant genes present in the bins is shown. If only bin sets are provided

without any RNA-Seq data, the pathways of all the bins are created based on gene presence

alone. The KEGG pathway results are summarized in detail as interactive HTML files

(example snippet: **Error! Not a valid bookmark self-reference.**).

Like step 2, this step can be directly performed with a bin set created via another workflow.

Figure 2: Example snippets of the sub-workflow results of step 3 (Annotate).

Running MUFFIN and version control

MUFFIN requires only two dependencies, which allows an easy and user-friendly workflow execution. One of them is the workflow management system Nextflow [14] and the other can be either Conda [20] as a package manager or Docker [21] to use containerized tools. A detailed Installation process is available on https://github.com/RVanDamme/MUFFIN. Each MUFFIN release specifies the Nextflow version it was tested on, to avoid any version conflicts between MUFFIN and Nextflow at any time. A Nextflow-specific version can always be directly downloaded as an executable file from https://github.com/nextflow-io/nextflow/releases, which can then be paired with a compatible MUFFIN version via the -r flag.

Results

We chose Nextflow for the development of our metagenomic workflow because of its direct cloud computing support (Amazon AWS, Google Life Science, Kubernetes), various ready-to-use batch schedulers (SGE, SLURM, LSF), state-of-the-art container support (Docker, Singularity) and accessibility of a widely used software package manager (Conda). Moreover, Nextflow [14] provides a practical and straightforward intermediary file handling with process-specific work directories and the possibility to resume failed executions where the work ceased. Additionally, the workflow code itself is separated from the 'profile' code (which contains Docker, Conda, or cluster related code), which allows for a convenient and fast workflow adaptation to different computing clusters without touching or changing the actual workflow code.

The entire MUFFIN workflow was executed on 20 samples from the Bioproject PRJEB34573 (available at ENA or NCBI) using the Cloud Life Sciences API (google cloud) with docker containers. This metagenomic bioreactor study provides paired-end Illumina and nanopore-based data for each sample [41]. We used five different Illumina read sets of the same project for differential coverage binning, and the workflow runtime was less than two days for all samples. MUFFIN was able to retrieve 1122 MAGs with genome completeness of at least 70 % and contamination of less than 10 % (Figure 3). In total, MUFFIN retrieved 654 MAGs with genome completeness of over 90 %, of which 456 have less than 2% contamination out of the 20 datasets. For comparison, a recent study was using 134 publicly available datasets from different biogas reactors and retrieved 1,635 metagenome-assembled genomes with genome completeness of over 50% [46].

Exemplarily, we investigated the impact of additional re-assembly of each bin for five samples (Figure 3). The N50 was increased by an average of 6-7 fold across all samples. Twenty-six bins of the five samples had an N50 ranging between 1 to 3 Mbases. Some bins benefit more of this step as the re-assembly performance depends on the number of reads available for each bin.

Figure 3: A: Quality overview of 1122 meta-assembled genomes (MAGs) by plotting size to completeness and coloring based on contamination level. B: N50 comparison between each bin of five selected samples from the Bioproject PRJEB34573 before and after individual bin reassembly.

Discussion

The analysis of metagenomic sequencing data evolved as an emerging and promising

research field to retrieve, characterize, and analyze organisms that are difficult to cultivate.

There are numerous tools available for individual metagenomics analysis tasks, but they are

mainly developed independently and are often difficult to install and run. The MUFFIN

workflow gathers the different steps of a metagenomics analysis in an easy-to-install, highly

reproducible, and scalable workflow using Nextflow which makes them easily accessible to

researchers.

MUFFIN utilizes the advantages of two sequencing technologies, whereas short reads can

provide a better representation of low abundant species due to their higher coverage. This

aspect is further utilized via the final re-Assembly step after binning, which is an optional step

due to the additional computational burden which solely aims to improve genome continuity.

Another critical aspect is the full support of differential binning, for both long and short reads,

via a single input option. The additional coverage information from other read sets of similar

habitats allows for the generation of more concise bins with higher completeness and less

contamination because more coverage information is available for each binning tool to

decide which bin each contig belongs.

With supplied RNA-Seq data, MUFFIN is capable of enhancing the pathway results present

in the metagenomic sample by incorporating this data as well as the general expression level

of the genes. Such information is essential to further analyze a metagenomic data sets in-

depth, for example, to define the origin of a sample or to improve environmental parameters

for production reactors such as biogas reactors. Knowing whether an organism expresses a

gene is a crucial element in deciding whether a more detailed analysis of that organism in the

biotope where the sample was taken is necessary or not.

Availability and future directions

MUFFIN is an ongoing workflow project that gets further improved and adjusted. The

modular workflow setup of MUFFIN using Nextflow allows for fast adjustments as soon as

future developments in hybrid metagenomics arise, including the pre-configuration for other

workload managers. MUFFIN can directly benefit from the addition of new bioinformatics

software such as for differential expression analysis and short-read assembly that can be

easily plugged into the modular system of the workflow. Another improvement is the creation

of an advanced user and wizard user configuration file, allowing experienced users to tweak

all the different parameters of all the different software as desired.

MUFFIN will further benefit from different improvements, in particular by graphically

comparing the generated MAGs via a phylogenetic tree. Furthermore, a convenient approach

to include negative controls is under development to allow the reliable analysis of super-low

abundant organisms in metagenomic samples.

MUFFIN is publicly available at https://github.com/RVanDamme/MUFFIN under the GNU

general public license v3.0. Detailed information about the program versions used and

additional information can be found in the GitHub repository. All tools used by MUFFIN are

listed in the supplementary table S1. The Docker images used in MUFFIN are prebuilt and

publicly available at https://hub.docker.com/u/nanozoo, and the GTDB formatted for

sourmash(v2.0.0a10)[38] usage is publicly available at https://osf.io/wxf9z / and was created

by C. Titus Brown (associate professor at UC DAVIS, http://ivory.idyll.org/blog/2019-

sourmash-lca-db-gtdb.html).

Acknowledgment

236 We want to thank Hadrien Gourlé and Moritz Buck for the valuable insights into metagenomic

237 analysis and Annotation.

References

1. Handelsman, J., Rondon, M. R., Brady, S. F., Clardy, J. & Goodman, R. M. Molecular

biological access to the chemistry of unknown soil microbes: a new frontier for natural

products. *Chemistry & Biology* **5**, R245–R249 (1998).

2. De, R. Metagenomics: aid to combat antimicrobial resistance in diarrhea. *Gut Pathogens*

11, 47 (2019).

3. Mukherjee, A. & Reddy, M. S. Metatranscriptomics: an approach for retrieving novel

eukaryotic genes from polluted and related environments. *3 Biotech* **10**, 71 (2020).

4. Grossart, H.-P., Massana, R., McMahon, K. D. & Walsh, D. A. Linking metagenomics to

aquatic microbial ecology and biogeochemical cycles. *Limnology and Oceanography* **65**,

S2–S20 (2020).

5. Carabeo-Pérez, A., Guerra-Rivera, G., Ramos-Leal, M. & Jiménez-Hernández, J.

Metagenomic approaches: effective tools for monitoring the structure and functionality of

microbiomes in anaerobic digestion systems. *Appl Microbiol Biotechnol* **103**, 9379–9390

(2019).

6. Overholt, W. A. *et al.* Inclusion of Oxford Nanopore long reads improves all microbial and

phage metagenome-assembled genomes from a complex aquifer system. *bioRxiv*

2019.12.18.880807 (2019) doi:10.1101/2019.12.18.880807.

7. Beaulaurier, J. *et al.* Assembly-free single-molecule nanopore sequencing recovers

complete virus genomes from natural microbial communities. *bioRxiv* 619684 (2019)

doi:10.1101/619684.

8. Wetterstrand, K. A. DNA Sequencing Costs: Data.

www.genome.gov/sequencingcostsdata www.genome.gov/sequencingcostsdata.

9. Somerville, V. *et al.* Long-read based de novo assembly of low-complexity metagenome

samples results in finished genomes and reveals insights into strain diversity and an active

phage system. *BMC Microbiol* **19**, 143 (2019).

10.   Warwick-Dugdale, J. *et al.* Long-read viral metagenomics captures abundant and

microdiverse viral populations and their niche-defining genomic islands. *PeerJ* **7**, (2019).

11.   Driscoll, C. B., Otten, T. G., Brown, N. M. & Dreher, T. W. Towards long-read

metagenomics: complete assembly of three novel genomes from bacteria dependent on a

diazotrophic cyanobacterium in a freshwater lake co-culture. *Stand Genomic Sci* **12**,

(2017).

12.   Suzuki, Y. *et al.* Long-read metagenomic exploration of extrachromosomal mobile

genetic elements in the human gut. *Microbiome* **7**, 119 (2019).

13.   Mangul, S., Martin, L. S., Eskin, E. & Blekhman, R. Improving the usability and

archival stability of bioinformatics software. *Genome Biol.* **20**, 47 (2019).

14.   Tommaso, P. D. *et al.* Nextflow enables reproducible computational workflows. *Nat*

Biotechnol **35**, 316–319 (2017).

15.   Uritskiy, G. V., DiRuggiero, J. & Taylor, J. MetaWRAP—a flexible pipeline for

genome-resolved metagenomic data analysis. *Microbiome* **6**, 158 (2018).

16.   Eren, A. M. *et al.* Anvi'o: an advanced analysis and visualization platform for 'omics

data. *PeerJ* **3**, e1319 (2015).

17.   Westreich, S. T., Treiber, M. L., Mills, D. A., Korf, I. & Lemay, D. G. SAMSA2: a

standalone metatranscriptome analysis pipeline. *BMC Bioinformatics* **19**, 175 (2018).

18.   Abubucker, S. *et al.* Metabolic Reconstruction for Metagenomic Data and Its

Application to the Human Microbiome. *PLOS Computational Biology* **8**, e1002358 (2012).

19.   Meyer, F. *et al.* The metagenomics RAST server – a public resource for the automatic

phylogenetic and functional analysis of metagenomes. *BMC Bioinformatics* **9**, 386 (2008).

20.   Anaconda Software distribution. Anaconda | The World's Most Popular Data Science

Platform. *https://anaconda.com* https://www.anaconda.com/.

21.   Boettiger, C. An introduction to Docker for reproducible research. *SIGOPS Oper.*

Syst. Rev. **49**, 71–79 (2015).

22.   Albertsen, M. *et al.* Genome sequences of rare, uncultured bacteria obtained by

differential coverage binning of multiple metagenomes. *Nat Biotechnol* **31**, 533–538

(2013).

23.   Chen, S., Zhou, Y., Chen, Y. & Gu, J. fastp: an ultra-fast all-in-one FASTQ

preprocessor. *Bioinformatics* **34**, i884–i890 (2018).

24.   Wick, R. *rrwick/Filtlong.* (2020).

25.   Bankevich, A. *et al.* SPAdes: A New Genome Assembly Algorithm and Its

Applications to Single-Cell Sequencing. *Journal of Computational Biology* **19**, 455–477

(2012).

26.   Antipov, D., Korobeynikov, A., McLean, J. S. & Pevzner, P. A. hybridSPAdes: an

algorithm for hybrid assembly of short and long reads. *Bioinformatics* **32**, 1009–1015

(2016).

27.   Nurk, S., Meleshko, D., Korobeynikov, A. & Pevzner, P. A. metaSPAdes: a new

versatile metagenomic assembler. *Genome Res.* **27**, 824–834 (2017).

28.   Kolmogorov, M., Yuan, J., Lin, Y. & Pevzner, P. A. Assembly of long, error-prone

reads using repeat graphs. *Nat Biotechnol* **37**, 540–546 (2019).

29.   Kolmogorov, M., Rayko, M., Yuan, J., Polevikov, E. & Pevzner, P. metaFlye: scalable

long-read metagenome assembly using repeat graphs. *bioRxiv* 637637 (2019)

doi:10.1101/637637.

30.   Vaser, R., Sović, I., Nagarajan, N. & Šikić, M. Fast and accurate de novo genome

assembly from long uncorrected reads. *Genome Res.* **27**, 737–746 (2017).

31.   *nanoporetech/medaka*. (Oxford Nanopore Technologies, 2020).

32.   Pilon: An Integrated Tool for Comprehensive Microbial Variant Detection and

Genome Assembly Improvement.

https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0112963.

33.   Alneberg, J. *et al.* Binning metagenomic contigs by coverage and composition. *Nat*

Methods **11**, 1144–1146 (2014).

34.   Wu, Y.-W., Tang, Y.-H., Tringe, S. G., Simmons, B. A. & Singer, S. W. MaxBin: an

automated binning method to recover individual genomes from metagenomes using an

expectation-maximization algorithm. *Microbiome* **2**, 26 (2014).

35.   MetaBAT, an efficient tool for accurately reconstructing single genomes from complex

microbial communities [PeerJ]. https://peerj.com/articles/1165/.

36.   Unicycler: Resolving bacterial genome assemblies from short and long sequencing

reads. https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1005595.

37.   Parks, D. H., Imelfort, M., Skennerton, C. T., Hugenholtz, P. & Tyson, G. W. CheckM:

assessing the quality of microbial genomes recovered from isolates, single cells, and

metagenomes. *Genome Res.* **25**, 1043–1055 (2015).

38.   Brown, C. & Irber, L. sourmash: a library for MinHash sketching of DNA. *Journal of*

Open Source Software https://joss.theoj.org (2016) doi:10.21105/joss.00027.

39.   Parks, D. H. *et al.* A standardized bacterial taxonomy based on genome phylogeny

substantially revises the tree of life. *Nat Biotechnol* **36**, 996–1004 (2018).

40.   Méric, G., Wick, R. R., Watts, S. C., Holt, K. E. & Inouye, M. Correcting index

databases improves metagenomic studies. *bioRxiv* 712166 (2019) doi:10.1101/712166.

41.   Brandt, C., Bongcam-Rudloff, E. & Müller, B. *Abundance tracking by long-read*

nanopore sequencing of complex microbial communities in samples from 20 different

biogas/wastewater plants. https://www.researchsquare.com/article/d9fdc53c-a0a7-44a1-

bce4-4d1fafa60f9e/v1 (2019) doi:10.21203/rs.2.17734/v1.

42.   Huerta-Cepas, J. *et al.* Fast Genome-Wide Functional Annotation through Orthology

Assignment by eggNOG-Mapper. *Mol Biol Evol* **34**, 2115–2122 (2017).

43.   Huerta-Cepas, J. *et al.* eggNOG 5.0: a hierarchical, functionally and phylogenetically

annotated orthology resource based on 5090 organisms and 2502 viruses. *Nucleic Acids*

Res **47**, D309–D314 (2019).

44.   Haas, B. J. *et al.* De novo transcript sequence reconstruction from RNA-seq using the

Trinity platform for reference generation and analysis. *Nat Protoc* **8**, 1494–1512 (2013).

45.   Patro, R., Duggal, G., Love, M. I., Irizarry, R. A. & Kingsford, C. Salmon provides fast

and bias-aware quantification of transcript expression. *Nat Methods* **14**, 417–419 (2017).

46.   Campanaro, S. *et al.* The anaerobic digestion microbiome: a collection of 1600

metagenome-assembled genomes shows high species diversity related to methane

production. *bioRxiv* 680553 (2019) doi:10.1101/680553.

Funding Disclosure

This study was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research

Foundation) – BR 5692/1-1 and BR 5692/1-2. This material is based upon work supported by

Google Cloud.

BM was funded by FORMAS, grant number 942-2015-1008. The funders had no role in

study design, data collection and analysis, decision to publish, or preparation of the

manuscript.

MH is supported by the Collaborative Research Centre AquaDiva (CRC 1076 AquaDiva) of

the Friedrich Schiller University Jena, funded by the DFG. MH appreciates the support of the

Joachim Herz Foundation by the add-on fellowship for interdisciplinary life science.

360