1   Predicting brain function from anatomy using geometric deep learning

3   Fernanda L. Ribeiro[a,b], Steffen Bollmann[c], Alexander M. Puckett[a,b]

[a]School of Psychology, The University of Queensland; Brisbane QLD 4072; Australia

[b]Queensland Brain Institute, The University of Queensland; Brisbane QLD 4072; Australia

[c]Centre for Advanced Imaging, The University of Queensland; Brisbane QLD 4072; Australia

Corresponding author:

Fernanda L. Ribeiro

School of Psychology

University of Queensland

St. Lucia QLD 4072

Australia

Email: fernanda.ribeiro@uq.edu.au

Phone: +61432643672

Abstract

Whether it be in a single neuron or a more complex biological system like the human

brain, form and function are often directly related. The functional organization of

human visual cortex, for instance, is tightly coupled with the underlying anatomy. This

is seen in properties such as cortical magnification (i.e., there is more cortex dedicated

to processing foveal vs. peripheral information) as well as in the presence, placement,

and connectivity of multiple visual areas – which is critical for the hierarchical

processing underpinning the rich experience of human vision. Here we developed a

geometric deep learning model capable of exploiting the actual structure of the cortex

to learn the complex relationship between brain function and anatomy in human visual

cortex. We show that our neural network was not only able to predict the functional

organization throughout the visual cortical hierarchy, but that it was also able to predict

nuanced variations across individuals. Although we demonstrate its utility for modeling

the relationship between structure and function in human visual cortex, geometric

deep learning is flexible and well-suited for a range of other applications involving data

structured in non-Euclidean spaces.

Keywords

Introduction

The modern-day study of visual perception has led to an unprecedented understanding of the neurobiological mechanisms underlying sensory information processing in the brain. Although first being of interest to those pursuing basic science, this understanding has since translated to more practical applications, notably by inspiring the development of convolutional neural networks (CNNs) [1] which have revolutionized the field of artificial intelligence [2]. In the human visual system, light reaches the retina where it is converted into electrical impulses that are transferred to the lateral geniculate nucleus and then through a hierarchy of cortical areas (Figure 1) [3,4]. At the bottom level of the hierarchy (primary visual cortex), neurons with small receptive fields (i.e., the coverage area in the visual field to which a neuron is responsive) capture simple visual features such as spatial orientation [3]. As those signals travel through higher order visual areas (comprised of neurons with increasing receptive field sizes) those simple visual features are combined, enabling complex features to be mapped from the visual input. These more complex features range from contours and textures (low to mid-level) to complete faces near the top of the hierarchy [5]. This type of hierarchical processing is imitated by CNNs by using filters with learnable parameters which are convolved across data representations with the aim of capturing common features in the input. At early layers of CNNs, those filters capture simple features, while in deeper layers more complex features are detected due to the complex combination of the inputs of previous layers. Here, we report that the story has – in a sense – come full circle. By leveraging recent advances in the application of CNNs to non-Euclidean spaces [6], we show that deep learning can be used to predict the functional organization of the very brain regions that inspired them (i.e., the areas of the visual cortical hierarchy). Importantly, these predictions are made

from anatomical properties alone and vary according to each individual's specific brain

anatomy.

Figure 1 - Hierarchical organization of the visual cortex. The 21 atlas-based [7] visual
areas in both left (LH) and right (RH) hemispheres displayed on spherical surface and fiducial
surface (lateral and posterior views) models. Different colors represent different visual areas.
Central legend indicates the name of each visual area.

Convolutional neural networks are conventionally applied to data represented in two-

or three-dimensional Euclidean space (Figure 2a). A great deal of data, however, is not

best represented in such a simple and regular domain [6]. In the field of neuroscience,

for instance, data are often represented on surface models of the brain as many

cortical properties only make sense considering their specific location with respect to

the various sulci and gyri [8]. These surface models are essentially sheet-like meshes

that are intricately folded in three-dimensional space, maintaining the geometrical

structure of the brain [9]. Importantly, two points on the surface model might be close

to one another in Euclidean space but far apart in terms of cortical distance following

the surface (e.g., on opposing banks in a sulcus). To account for this and other non-

Euclidean properties, techniques have recently been developed that generalize deep

neural network models to non-Euclidean spaces such as surfaces (Figure 2b) and

graphs – with these techniques collectively being referred to as geometric deep

learning [6].

Figure 2 - Predicting brain function with geometric deep learning. a, Convolution in 3D
Euclidean space involves convolving a conventional 3D kernel across multiple slices of 2D
images. **b,** Convolution on a surface, a non-Euclidean space, involves convolving a B-spline
kernel directly on the surface, in which the kernel is able to aggregate information in local
neighborhoods. **c**, Geometric convolutional neural network architecture. Input data included
curvature and myelin values (vertex features) and the arrangement of vertices within the
region of interest on the cortical surface. The output data is the vertex-wise polar
angle/eccentricity values. Network parameters were optimized to reduce the difference
between prediction and ground truth using a smooth L1 loss function.

Using geometric deep learning, we developed a neural network capable of predicting

the functional organization of the human visual hierarchy (Figure 2c). The visual

hierarchy is comprised of a number of functionally specialized cortical visual areas

[10], nearly all of which are organized retinotopically [11,12]. That is, the spatial

organization of the retina (and hence the visual field) is maintained in each of these

cortical visual areas - albeit in a distorted fashion due to properties such as cortical

magnification (i.e., there are more neurons dedicated to processing foveal vs.

peripheral information) [13,14]. Although distorted, this retinotopic mapping is known

to be similar across individuals and the mapping functions between the visual field and

the brain, at least in early visual cortex, can be described by relatively simple

mathematical models [15,16]. However, considerable inter-individual variation does

exist, and this variation has been shown to be directly related to variability in cortical

folding patterns and other anatomical features such as the degree of myelination [17–

23]. It was our aim, therefore, to develop a neural network capable of learning the

complex relationship between the functional organization of visual cortex and the

underlying anatomy. To this end, we trained our network using the most

comprehensive and detailed retinotopy dataset openly available – that from the

Human Connectome Project (HCP) [24]. This dataset includes ultra-high field (7T)

fMRI retinotopic mapping data of a large number of participants along with their

anatomical data, serving as an ideal dataset for our endeavor. Although we show its

utility for retinotopic mapping, geometric deep learning is flexible and well-suited for

an abundance of other applications, both within the field of neuroscience [25–27] and

beyond.

Results

Retinotopic mapping with deep learning

Retinotopic mapping typically involves empirical data collection performed by showing

visual stimuli, which are temporally and spatially controlled, to a participant lying in an

MRI scanner [28,29]. Analysis of the fMRI signals elicited by such stimuli allows the

visual field location encoded by each responsive voxel to be estimated. The visual

field locations are usually defined in polar coordinates resulting in two retinotopic

maps: one representing the polar angle (or clock position) and the other representing

the eccentricity (or distance away from fixation). An example of these empirically

derived retinotopic maps for a single individual is shown in Figure 3 (top row). From

these, it can be seen that the polar angle and eccentricity maps are organized roughly

orthogonal to one another – most easily discerned in early visual cortex (V1, V2, and

V3). Since the human visual system is comprised of multiple retinotopically organized

cortical areas, these maps are also used to demarcate the boundaries of the various

areas. The polar angle maps are particularly useful for this as the boundaries between

areas can be identified by reversals in the progression of the polar angle values. In

Figure 3, for example, the superior boundary between V1 and V2 is found by locating

the band at which the polar angle reverses from progressing from red to yellow, back

to red. Likewise the inferior boundary between V1 and V2 is found where the polar

angle representation reverses from progressing from red to purple, back to red.

To map retinotopically organized areas without the need to collect functional data, we

built a geometric convolutional neural network by stacking spline-based convolution

layers [30] to compute convolutions on a manifold (i.e., the cortical surface model)

(Figure 2c). The data serving as input to the network included curvature and myelin

values as well as the connectivity among vertices forming the surface (i.e., the surface

topology) and their spatial disposition (i.e., their 3D coordinates). The output of the

model was either the polar angle or eccentricity value for each vertex of the cortical

surface model. Developing the neural network involved three main steps: (1) *training*

the neural network, (2) hyperparameter *tuning*, and (3) *testing* the model. Prior to the

training step, the 181 participants from the HCP dataset were randomly separated into

three datasets: training (161 participants), development (10 participants) and test (10

participants). These datasets were used in each of the above three steps, respectively.

During *training*, the network learned the correspondence between the retinotopic maps

and the anatomical features by exposing the network to each example in the training

dataset. Hence, the empirically-derived retinotopic maps served as the ground truth

and the parameters of the neural network were optimized to minimize the difference

between the predicted and empirical retinotopic maps. Note that the objective function,

smooth L1 loss, was weighted by explained variance from the population receptive

field (pRF) modeling procedure used to generate the retinotopic maps [24]. Model

hyperparameters, such as the number of layers, were *tuned* (i.e., optimized) by

inspecting model performance using the development dataset. Finally, once the final

model was selected, the network was *tested* by assessing the predicted maps for each

participant in the test dataset. This procedure was followed for each hemisphere and

each type of retinotopic mapping data separately, resulting in four predictive models.

Figure 3 illustrates the predicted retinotopic maps with their correspondent ground truth

(i.e., empirically measured retinotopic maps) for a single participant in the test dataset.

Qualitatively, the predicted maps bear a remarkable resemblance to the ground truth,

appearing to accurately predict the main features of both polar angle and eccentricity

maps. To aid comparison between the empirical and predicted maps a grid of isopolar

angle and isoeccentricity lines has been overlaid upon the maps in early visual cortex.

The grid was drawn based on the ground truth data and then positioned identically on

the predicted maps. Note how well the visual area boundaries (i.e., the isopolar angle

contours) match the predicted maps, running directly through the polar angle

reversals. A similar quality of fit can be seen for the isoeccentricity lines. Although the

grid is focused on early visual areas (due to their organization being most well

understood and hence most reliable to outline), it is important to note that the neural

networks are able to predict the retinotopic organization far beyond early visual cortex,

throughout the visual hierarchy. Being smaller in size, it is difficult to see the finer

retinotopic details in these areas, however, the predicted maps in these areas do

appear to reflect the general organizational features present in the empirical data –

such as additional polar angle reversals throughout the hierarchy (i.e., ventral, lateral,

and dorsal to early visual cortex).

Polar angle   **Eccentricity**

Ground truth

Prediction

LH   RH   LH   RH

Figure 3 - Retinotopic mapping with geometric deep learning. Upper row shows empirical (ground truth) polar angle and eccentricity maps for both left (LH) and right (RH) hemispheres of a single individual from the test dataset (Participant 1). Lower row shows the predicted polar angle and eccentricity maps for each hemisphere of the same participant. Polar angles vary from 0º to 360º, while eccentricity values varied from 0º to 12º as indicated by the color wheels. The white grid illustrates isoeccentricity (dashed) and isopolar angle (solid) lines associated with early visual cortex (V1, V2, and V3). Note that V2 and V3 are split around V1 and are comprised of dorsal and ventral components.

Individual variability in predicted maps

It is clear that the geometric deep learning models can predict the basic retinotopic

organization of human visual cortex and that the predicted maps appear to be in line

with the empirically measured maps for one participant, but are these models capable

of predicting individual variability across participants? Figure 4 shows the results for 4

additional participants from the test dataset. For brevity, we only show the polar angle

maps from the left hemisphere, but all the predicted maps for each test dataset

participant are included as supplementary material (Supplementary Figures 1 and 2).

Additionally, the mean prediction error of each of the four predictive models are

summarized in Supplementary Table 2. In Figure 4a, the empirical polar angle maps

are marked by unusual and/or discontinuous polar angle reversals. In the first three

maps (Figure 4a, Participants 2-4), a discontinuous representation of the lower vertical

meridian (that is, the boundaries between V1 and dorsal V2 as well as between dorsal

V2 and dorsal V3) can be observed – indicated by the gray lines. Importantly, these

unique variations were correctly predicted by our model. Perhaps even more striking,

we see that these borders have merged to form a Y-shape for Participant 5, which was

also observed in the predicted map.

Figure 4 - Individual variability in retinotopic maps. a, Upper row shows empirical (ground
truth) polar angle maps and lower row shows their respective predicted polar angle maps for
four participants in the test dataset. Grey lines indicate unique polar angle representations that
were predicted by our model. **b**, Upper row shows the prediction error of each individual map
and lower row shows how variable the same given map is from all the other predicted maps
in the test dataset. White arrows indicate regions that differed the most among predicted maps.

To further assess the performance of our models, the difference (given by the smallest

difference between two angles – Equation 2) between the predicted and the empirical

(ground truth) polar angle values was determined in a vertex-wise manner (upper row,

Figure 4b). This error estimate was then displayed on the cortical surface meshes to

inspect where our models perform well and where they suffer. Predictions differed

most from the ground truth near the foveal confluence (i.e., where the V1, V2, and V3

foveal representations merge), at the most peripheral eccentricities, and in some of

the higher order visual areas (particularly those located dorsally in the intraparietal

sulcus). Notably, each of these regions are known to be problematic when measuring

retinotopic maps empirically. For example, it has been shown that retinotopic

measurements within the foveal confluence are often not well represented due to

instrumental and measurement limitations [31]. The errors seen at the most peripheral

eccentricities likely manifest from the suppressive effects seen in the cortex for

retinotopic locations immediately outside the most peripheral limit of the visual stimuli

[32,33]. Finally, the higher order areas are also known to be more difficult to map

empirically using conventional procedures due to their smaller size and their higher

degree of selectivity to specific types of stimuli [31]. Together, this brings us to an

important caveat: the empirical maps, although treated as ground truth, may

themselves misrepresent the underlying retinotopic organization. Accordingly, Figure

5 shows the average explained variance (R^2) associated with the original pRF analysis

of the empirical retinotopic mapping data [24] and as such, can be seen as a proxy for

the quality of our ground truth. Pertinently, it shows that quality of the empirical data is

indeed lowest in the regions where our model predictions were most error-prone –

e.g., in the foveal confluence (Figure 5, arrow a), at the most peripheral eccentricities

(Figure 5, arrow b), and in some of the higher-order areas (Figure 5, arrow c).

Figure 5 – Quality of the empirical retinotopic mapping data. Average explained variance (R^2) map of pRF modeling [24] from all participants in the test dataset.

Similar to the error estimates, we were interested in quantifying the extent to which

each individual's predicted map within the test dataset varied from the others. For this

we computed an individual variability estimate as the difference (Equation 2) between

a particular predicted map and each of the other predicted maps in the test dataset in

a vertex-wise manner and averaged across all comparisons. Results are shown in

Figure 4b, lower row. As expected, locations that more prominently differed among

predicted maps in early visual cortex were the areas in and near the unique

discontinuities seen around the lower vertical meridian lines in the polar angle maps

(Figure 4, white arrows).

Variability guided by anatomical features

To demonstrate the importance of the anatomical features in shaping individual

differences in the functional organization of the visual cortex, we predicted three new

sets of retinotopic maps for each participant after (1) randomly shuffling the anatomical

input features, (2) setting the input features equal to a constant value (equal to the

mean curvature and myelin values), and for a more extreme scenario (3) setting the

input features equal to zero. We expected that disrupting the input features in these

ways would result in both higher error and lower individual variability across predicted

maps. Figure 6a (upper row) shows the average error and the individual variability

estimates across all participants. The highest errors were again present in the foveal

confluence, higher-order visual areas, and near the outermost eccentricities. These

errors, however, can be seen when using the actual empirical values as input as well

as the disrupted values, and likely reflect the lack of reliable training data in these

regions (Figure 5). Contrasting the four sets of maps, however, reveals that the errors

were generally higher throughout visual cortex when the input values were either

shuffled or constant when compared to intact input values, indicating that the spatial

organization of the anatomical features is being used by the network for accurate

predictions. Interestingly, disrupting the input features particularly increases the error

in the dorsal regions of early visual cortex (Figure 6a), which is where most of the

variability was seen across individuals in Figure 4. Complementary to this, we also see

that the proper spatial organization of the anatomical features is important for

generating individual variability in our model predictions (Figure 6a, lower row). The

variability across predicted maps decreased when the input values were randomly

shuffled. Moreover, as expected, the variability between predicted maps was equal to

zero when the input values were the same across all vertices; without variability in the

input features, the model will always predict the same maps.

To summarize the vertex-wise error and individual variability estimates in Figure 6a,

we computed the mean error and the mean individual variability across the visual

cortex (Figure 6b). For this, we first grouped the 21 visual areas (Figure 1) into six

different clusters (i.e., anatomically contiguous areas with similar positions in the

hierarchy), as indicated in Figure 6b. Disrupting the spatial organization of input

features led to both an increased mean error between predicted maps and ground

truth as well as decreased mean individual variability across all clusters. Together,

 these results show that the anatomical features were critical for predicting the

 functional organization of the visual cortex at the individual level.

Figure 6 - Individual variability in predicted maps is determined by anatomical features.
a, Upper row shows the prediction error across participants in the test dataset using the empirical input features, shuffled input features, constant input features, and zeros. Lower row shows how variable predicted maps are from all the other predicted maps in the test dataset on average for each input condition. **b**, Mean and bootstrapped (n=1,000) 95% confidence interval of the average error and individual variability of predicted maps for each input condition within different visual area clusters.

Individual variability and genetic dependency

Although the HCP 7T retinotopy dataset contained mapping data for 181 different

participants, not all datasets were strictly independent due to the presence of a large

number of twin pairs (50 pairs of monozygotic and 34 pairs of dizygotic twins). For the

previous results, we used data from all the participants to maximize the number of

training examples seen by our network. However, given the genetic dependency

among participants in our training and test data (all 10 of our test participants had a

twin in the training set), we repeated the model training with a reduced training sample

by excluding the twins of the participants in the test dataset from the training dataset.

Importantly, the resulting model was still able to predict the retinotopic organization of

visual cortex as well as unique variations in polar angle maps without exposure to the

genetically-related mapping data (Supplementary Figure 3).

Discussion

This study shows that deep learning can be used to predict the functional organization

of visual cortex from anatomical features alone by building neural networks able to

predict retinotopic maps throughout the visual cortical hierarchy. Remarkably, the

networks were able to predict unique features in these maps showing sensitivity to

individual differences. Previous work has been done to map the correspondence

between brain anatomy and retinotopic maps in individuals by warping an atlas or

template [17–19] according to their specific anatomical data. While these approaches

are able to provide reasonable estimates of their retinotopic maps, they have not –

when using anatomical information alone – been able to capture the detailed

idiosyncrasies seen in the actual measured maps of those individuals. By not

assuming an explicit structure-function relationship our deep learning framework

provides a more flexible approach, able to produce more specific retinotopic maps.

Although our neural network was able to predict the main features of retinotopic maps

as well as nuanced differences across individuals, there were regions where prediction

accuracy suffered. The highest errors were seen near the foveal confluence, at the

most peripheral eccentricities, and in some of the higher order visual areas. Amongst

the possible reasons for this discrepancy, we have already mentioned one: the

network's ability to generate accurate predictions is determined largely by the quality

of the training data. The quality of the training data is reflected in the explained

variance associated with the original pRF analysis [24], which suggests that the

retinotopic mapping values given by the pRF analysis are least reliable (i.e., lowest

explained variance) in exactly the same regions where our model predictions were

most error-prone (Figure 5). Considering the intrinsic difficulty of mapping these

regions and the fact that fMRI data cannot offer perfect representations of the

underlying neuronal activity, we weighted the loss function by the fraction of variance

explained from the pRF solution of each vertex [19,24] (see Methods), and hence by

design, our model was trained to generate better predictions in regions with more

reliable pRF estimates. Future work using stimuli tailored for the activation of these

regions could be performed to test the assertion that the predictions would improve by

providing the neural network with higher quality training data.

Another possible reason for less accurate predictions in some regions of visual cortex,

especially the higher-order areas, is that the functional organization of these regions

may simply not be as strongly coupled with the underlying anatomical properties. The

location and organization of many visual areas outside early visual cortex (V1/V2/V3)

remain controversial, and this can be attributed to a variety of reasons, ranging from

instrumental and measurement limitations [31] to data pre-processing steps (e.g.,

inaccurate cortical surface alignment). Hence, it has proven difficult to study the

particular structure-function relationship in these areas compared to early visual

cortex. A systematic assessment of the effects of training data on predictions may

provide insight into the degree to which the functional organization is coupled to the

underlying anatomical properties. For example, if model accuracy does not improve in

the higher-order areas despite better training data, it may indicate that the functional

organization is less tightly coupled with the underling anatomical properties – at least

the ones used here (i.e., curvature and myelin). Note that in such case, and even for

the regions that are well-predicted, another future direction to improve the model

predictions might be to include different input features. Although we tested two

anatomical features known to be related to retinotopic organization, other anatomical

parameters can be drawn from T1-weighted images, such as cortical thickness, which

can easily be incorporated as input features to train new models. Moreover, one could

also include non-anatomical features known to vary according to retinotopic

organization such as functional connectivity measures [34,35] in order to improve

prediction accuracy.

A key aspect of this work was the use of a geometric approach, which permitted deep

learning to be performed directly on the cortical surface model. Doing so, we were able

to take advantage of the actual structure of the brain and hence more appropriately

represent the data to the neural network. Here, the approach was used to model the

relationship between structural brain data and functional brain data; however, the

potential for this technique transcends this particular use case as geometric deep

learning can be applied to model relationships among task-based activation patterns,

functional connectivity, structural information, sensory spaces, behavioral measures,

and much more.

Importantly, it is not at all rare for data to better be represented in a non-Euclidean

space than in the Euclidean one. For example, also within the field of neuroscience,

brain functional networks are often represented as graphs (i.e., connectomes) in which

connections between two brain regions do not necessarily represent the physical

distance between them (in contrast to cortical surface models). Geometric deep

learning, being also well-suited for graph data [6], offers the field a powerful tool given

the growing interest in predicting aspects of human behavior from these functional

connectivity graphs [36–41]. Beyond neuroscience lies a wide range of other potential

applications for these geometric deep learning techniques – including application to

topological data in earth science [42], genetic and protein structure data in biological

science [43–45], drug discovery in chemistry science [46], and cosmological data in

physical science [47].

Methods

Participant information and data overview

Comprehensive information about the HCP 7T retinotopy dataset is given elsewhere

[24]. Briefly, complete retinotopic mapping and structural data were acquired for 181

participants (109 females, age 22-35) following the HCP protocol [24,48]. All

participants had normal or corrected-to-normal visual acuity. Among these

participants, 100 individuals are genetically confirmed monozygotic twins (50 pairs),

68 individuals are dizygotic twins (34 pairs), 4 individuals are non-twin siblings (2

pairs), and 9 individuals whose twin/siblings were not included and/or were not

genetically tested. Structural image acquisition included T1w and T2w structural scans

at 0.7 mm isotropic resolution at a customized Siemens 3T Connectome scanner [48].

White and pial cortical surfaces were reconstructed from the structural scans using

FreeSurfer (http://surfer.nmr.mgh.harvard.edu/) and were aligned across participants

to the HCP 32k fs_LR standard surface space [49]. Myelin maps were determined by

the ratio of T1w/T2w images [50] and appropriately normalized to account for B1+

transmit effects [49].

Whole-brain fMRI data were acquired using a Siemens 7T Magnetom scanner at a

resolution of 1.6mm isotropic and 1s TR. The data were processed using the HCP

pipeline [49], which involved correction for head motion and EPI spatial distortion,

alignment of the fMRI data with the HCP standard surface space, and denoising for

spatially specific structured noise. The data produced (in CIFTI format) by the pipeline

consists of 91,282 grayordinates: 32,492 cortical vertices per hemisphere and 26,298

subcortical voxels with approximately 2mm spatial resolution. All data are publicly

available on the ConnectomeDB database (https://db.humanconnectome.org).

Retinotopic mapping details

To build our deep learning model, we used previously analyzed retinotopic mapping

data [24] – made available at https://balsa.wustl.edu/study/show/9Zkk as scene files.

These files can be visualized using Connectome Workbench and are efficiently

handled using the MATLAB GIFTI library and Fieldtrip toolbox. For complete details

on the experimental design and analysis procedure used to produce the maps, please

refer to Benson et al. (2018) [24]. In brief, retinotopic stimuli were constrained to a

circular region with a diameter of 16º. They consisted of slowly moving apertures of

achromatic pink-noise background with dynamic colorful texture object, which was

designed to elicit strong neural responses throughout the visual hierarchy – including

in higher order visual areas. The experiment consisted of 6 runs with different set of

apertures: wedges, rings and bars. Each aperture was presented twice, changing the

direction of movement between runs, except for bar stimuli runs which were identical.

Ring stimuli consisted of 8 cycles of a ring expanding away from the center or

contracting towards the center with a period of 32s. Wedges stimuli consisted of 8

cycles of 90º wedges rotating across the visual field counterclockwise or clockwise

with a period of 32s. Finally, each bar stimuli run consisted of bars with different

orientations (4 orientations) moving across different directions in visual field. During

each condition, participants were to attend to a semitransparent dot located at the

center of the display and report whenever the color of the dot changed (via a button

press) to ensure their gaze were fixed at the center of the display.

A pRF modeling procedure was then used to construct the retinotopic maps [24,51].

Essentially, this modeling procedure estimates the spatial sensitivity profile within the

visual field to which a grayordinate is responsive (i.e., its receptive field). For this, the

fMRI time series elicited by the retinotopic mapping stimuli described above are

modeled as the sum of a stimulus-related time series and a baseline time series. The

stimulus-related response is then obtained by computing the dot product between the

stimulus aperture time series and a 2D isotropic Gaussian (representing the pRF),

applying a non-linearity component and rescaling the result by a gain factor, and then

convolving it with a canonical hemodynamic response function. The modeled fMRI

time series is optimized in order to best match the real fMRI time series by changing

the 2D isotropic Gaussian parameters, such as its center position (x and y coordinates)

and size, as well as the gain factor. Once the best parameters are determined, it is

possible to construct retinotopic maps using each grayordinate's preferred location in

the visual field (i.e., its pRF's center location). Polar angle maps reflect the polar angle

in visual field to which a grayordinate is most responsive, while eccentricity maps

reflect the distance from the center of the visual field (i.e., the fixation point) to which

a grayordinate is most responsive. Note that the pRF modeling procedure is fully

described in Benson et al. (2018).

Definition of the region of interest

As mentioned, the data files consisted of 91,282 grayordinates: 32,492 cortical surface

vertices per hemisphere and 26,298 subcortical voxels. Here, we restricted the

analysis to the cortical surface, hence ignoring the subcortical voxels. We further

restricted our region of interest (ROI) to only include vertices within visual cortex using

a surface-based probabilistic atlas [7]. We modified the atlas slightly by extending the

early visual cortex (V1, V2, V3) ROIs to include the foveal confluence [52] as well as

combining ventral and dorsal components which are labelled separately in the original

atlas (Figure 1). We also excluded the frontal eye fields (FEF) due to its discontinuity

with the remaining areas. After selecting only vertices within this region of interest, we

were left with 3,267 vertices for the left hemisphere (3,219 vertices of the right

hemisphere), adding up to 19,024 connections (edges) between pairs of vertices

(18,760 edges for the right hemisphere).

Data for deep learning

Our goal was to develop and train a deep neural network to predict the functional

organization of the visual cortex (i.e., the retinotopic maps) from underlying anatomical

properties (Figure 2). The anatomical data serving as input to the neural network

included the mean curvature and myelin values (both of which have been shown to be

related to the functional organization of visual cortex) as well as the connectivity

among the ROI surface vertices (i.e., the surface topology) and their spatial disposition

(i.e., their 3D coordinates). The output of the model was either the polar angle or

eccentricity value for each vertex of the cortical surface model. Note that polar angle

values are cyclical (i.e., 360º = 0º). To avoid issues with the discontinuity in values, we

shifted the polar angle values so that each hemisphere was trained with the point of

wrap-around (from 360º to 0º) positioned at the horizontal meridian in the contralateral

hemifield. After training, the values were shifted back to their original range.

For the modeling procedure, the data was represented on the midthickness cortical

surface model (S1200_7T_Retinotopy181.L(R).midthickness_MSMAll.32k_fs_LR.

surf.gii). Importantly, this model is a fiducial surface that maintains the actual geometry

of the brain. Our results are, however, displayed using a spherical surface model

(S1200_7T_Retinotopy181.L(R).sphere.32k_fs_LR.surf.gii)   for   visualization

purposes. This permits all visual areas to be displayed in a single view.

Developing the neural network

Developing the neural network involved three main steps: (1) *training* the neural

network, (2) hyperparameter *tuning*, and (3) *testing* the model. Prior to the training

step, the 181 participants from the HCP dataset were randomly separated into three

datasets: training (161 participants), development (10 participants) and test (10

participants) datasets. These datasets were used in each of the above three steps,

respectively. During *training*, the network learned the correspondence between the

retinotopic maps and the anatomical features by exposing the network to each

example in the training dataset. Hence, the empirically-derived retinotopic maps

served as the "ground truth" and the parameters of the neural network were optimized

to minimize the difference between the predicted and empirical retinotopic maps.

Model hyperparameters, such as the number of layers, were *tuned* (i.e., optimized) by

inspecting model performance using the development dataset. Finally, once the final

model was selected, the network was *tested* by assessing the predicted maps for each

participant in the test dataset. This procedure was followed for each hemisphere and

each type of retinotopic mapping data (i.e., polar angle and eccentricity) separately,

resulting in four predictive models.

Model architecture and training

We implemented a spline-based convolutional neural network (SplineCNN) [30] on

cortical surfaces using PyTorch Geometric [53], a geometric deep learning extension

of PyTorch. Among the broad range of methods defining convolution operations on

irregular structured data, such as graphs and surfaces, spline-based convolution is

amidst the spatial filtering approaches. In these approaches, filters aggregate

information locally, around a vertex's neighborhood. These filters exploit information

given by relative positions of the neighbor vertices with respect to the reference vertex

in addition to the information encoded in the connectivity, edge weights, and vertex

features. Thus, SplineCNN aggregates vertex features in local neighborhoods

weighted by learnable parameters of a continuous kernel function [30].

Following the original study, we denote spline-based convolutional layers as

SConv(k,M_{in},M_{out}) of which k is the kernel size, M_{in} is the number of input feature maps,

and M_{out} is the number of output feature maps (Figure 2). Our final model architecture

included 12 convolutional layers with the number of feature maps increasing to a

maximum of 32 feature maps per layer, and then decreasing back to one final feature

map. A non-linear activation function, the exponential linear unit (ELU), was used after

each convolution layer. Batch normalization and dropout (p=0.10) were applied to all

layers, except the last. Batch normalization is an approach commonly used in the field

of machine learning to automatically normalize each layer's input data, preventing the

shift of the input data distribution during training, which results in faster training and

lower variability among models [54,55]. Dropout refers to a regularization method used

to reduce model bias (overfitting) [56]. In our model, we only used Cartesian

coordinates to compute relative distance between vertices and the degree of B-spline

basis m = 1, due to the fact that models with those parameters showed better

performance than the models using higher degree of B-spline basis or using spherical

coordinates in previous experiments [30]. Training was carried out for 200 epochs

with a batch size of 1 and a learning rate at 0.01 for 100 epochs that was then adjusted

to 0.005, using Adam optimizer. Our models' learning objective was to reduce the

difference between predicted retinotopic map and ground truth (i.e., the empirical

retinotopic map). This mapping objective is measured by the smooth L1 loss function

(Equation 1).

520
$$loss(\hat{y}^*, y^*) = \frac{1}{n} \sum_i z_i \qquad \textbf{(1)}$$

521   where y^* and $\hat{y}^*$ are, respectively, the empirical and predicted value weighted by the

522   explained variance (R^2) from the pRF modeling procedure [24], n is the total number

523   of vertices, and z_i is given by:

524
$$z_i = \begin{cases} 0.5(\hat{y}^*_i - y^*_i)^2, if \left|\hat{y}^*_i - y^*_i\right| < 1 \\ \left|\hat{y}^*_i - y^*_i\right| - 0.5, \qquad otherwise \end{cases}$$

Models were implemented using Python 3.7.3 and Pytorch 1.2.0. Training was

performed on a high-performance computing cluster using NVIDIA Tesla V100

Accelerator units.

Hyperparameter tuning

Hyperparameter tuning was conducted by considering the performance of the model

on predicting retinotopic maps of participants within the development dataset. We

used the mean absolute error to compute the difference between predicted and

expected values (ground truth). During the training stage, we monitored the decrease

of the loss function (i.e., the prediction error on the training dataset) and the decrease

of the mean absolute error (i.e., the prediction error on the development dataset). We

also visually monitored predicted retinotopic maps using the development dataset, as

we observed that despite the prediction error within the development dataset reaching

a plateau around 100 epochs, some of the details in the predicted retinotopic maps

continued to vary with additional training. To allow for some of this additional fine

tuning, we fixed our training to 200 epochs.

To find the most appropriate number of layers, we trained five different models per

number of layers, varying from 1 to 20 layers, as the performance of the final model

fluctuated due to random initialization of the learnable parameters. We selected the

number of layers based on the performance of the trained network, which was

estimated by the smallest difference between two angles, given by:

$$\mathrm{MIN}(|\hat{\theta} - \theta|, |\hat{\theta} - \theta + 2\pi|, |\hat{\theta} - \theta - 2\pi|) \qquad \textbf{(2)}$$

for $0 < \theta < 2\pi$. To this end, we considered two factors: (1) how well model prediction

matched the ground truth (error) and (2) how much a predicted map differed from the

others (individual variability). To estimate the error, we computed the difference (given

by Equation 2) between the predicted and the empirical (ground truth) polar angle

values in a vertex-wise manner and averaged across all participants in the

development dataset and within the various ROIs. The other factor, individual

variability, was determined by the difference between a specific predicted map and

each other predicted map in the development dataset in a vertex-wise manner and

averaged across all combinations (there are 10 participants in the development

dataset, hence 9 combinations), and then averaged across participants and within the

various ROIs. This was performed for all models (5 models per number of layers) and

we selected the number of layers that resulted in the best performance across all the

ROIs in both metrics (12 layers; see Supplementary Figure 4). This selection was

based on mapping polar angle values in the left hemisphere; however, we tested a

range of layers using the right hemisphere data and found similar results. Finally, once

the appropriate number of layers was established, we chose the best model among

the 5 models that were trained with the same hyperparameters but with different

learnable parameters (due to the random initialization) to evaluate on the test dataset.

For the eccentricity models (left and right hemispheres), we kept the same

hyperparameters as optimized for polar angle models.

Model testing and evaluation metric

The selected models were evaluated based on their performance on the test dataset

considering the same two factors, error and individual variability. Importantly, the test

dataset was never seen by the network nor by the researchers until the deep learning

architecture was finalized and the final model selected. Again, the error was

determined by the difference between the predicted and the empirical polar angle

values in a vertex-wise manner and averaged across all participants – this time in the

test dataset. Individual variability was determined by the difference between a specific

predicted map and each other predicted map in the test dataset in a vertex-wise

manner and averaged across all combinations (9 combinations), and then averaged

across participants.

To evaluate the importance of the spatial organization of the anatomical features and

their variability for the prediction of individual differences in retinotopic maps, the

effects of modifying the input data in three ways was tested: (1) randomly shuffling the

anatomical features, (2) setting the input features equal to a constant value, and (3)

setting the input features equal to zero. By randomly shuffling the features across the

ROI vertices for each participant in the test dataset, the spatial organization of the

anatomical information was disrupted. If the spatial disposition of anatomical features

on the cortical surface is indeed important for predicting individual variability in

retinotopic maps, it would then be expected that the model would generate less

accurate retinotopic maps (i.e., higher error between the predicted and empirical maps

and less variable across individuals) compared to those predicted when using intact

anatomical features. Next, to test the effect of completely removing the variability

present in the input features, all curvature and myelin values of each participant in the

test dataset was set equal to the mean curvature (0.027) and the mean myelin (1.439)

values, respectively. Note that the mean values were computed using all participants

from the training dataset. By removing the variability of anatomical features, the model

was expected to generate the same retinotopic map for all participants (i.e., no

individual variability). Hence without the ability to vary across participants, less

accurate predictions (i.e., greater error measures) were expected compared to using

the intact (and variable) features. Finally, in a more extreme scenario, all curvature

and myelin values of each participant in the test dataset was set equal to zero.

Similarly, we expected that by removing the variability of anatomical features and by

selecting a more extreme constant value, which is different from the mean curvature

and mean myelin, less accurate predictions would be generated compared to the other

cases.

Data and code availability

The data used in this study in publicly available at BALSA

(https://balsa.wustl.edu/study/show/9Zkk). The pre-trained models with

accompanying Python source code will be available upon publication.

Acknowledgments

This work was supported by the Australian Research Council (DE180100433). Data were provided by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University. The authors acknowledge Jake Carroll and Irek Porebski for their great support with the high-performance computing facilities of the Research Computing Centre at the University of Queensland.

Author contributions

F.L.R., S.B., and A.M.P. conceptualized the study. F.L.R. and A.M.P. designed the study and analyses. F.L.R. carried out the modeling procedure and analyses. F.L.R. and A.M.P. wrote the manuscript. All authors reviewed the manuscript.

Competing financial interests

The authors declare no competing financial interests.

References

1. Fukushima, K. (1980). Neocognition: A Self-organizing Neural Network Model for a Mechanism of Pattern Recognition Unaffected by Shift in Position. Biol. Cybern. *36*, 193–202. Available at: https://www.rctn.org/bruno/public/papers/Fukushima1980.pdf.

2. Lecun, Y., Bengio, Y., and Hinton, G. (2015). Deep learning. Nature *521*, 436–444.

3. Hubel, D.H., and Wiesel, T.N. (1962). Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. J. Physiol. *160*, 106–154.

4. Felleman, D.J., and Van Essen, D.C. (1991). Distributed hierarchical processing in the primate cerebral cortex. Cereb. Cortex *1*, 1–47.

5. Kanwisher, N., McDermott, J., and Chun, M.M. (1997). The Fusiform Face

Area: A Module in Human Extrastriate Cortex Specialized for Face Perception.
J. Neurosci. *17*, 4302–4311.

6. Bronstein, M.M., Bruna, J., Lecun, Y., Szlam, A., and Vandergheynst, P.
(2017). Geometric Deep Learning: Going beyond Euclidean data. IEEE Signal
Process. Mag. *34*, 18–42.

7. Wang, L., Mruczek, R.E.B., Arcaro, M.J., and Kastner, S. (2015). Probabilistic
maps of visual topography in human cortex. Cereb. Cortex *25*, 3911–3931.

8. Van Essen, D.C., Drury, H.A., Joshi, S., and Miller, M.I. (1998). Functional and
structural mapping of human cerebral cortex: solutions are in the surfaces.
Proc. Natl. Acad. Sci. U. S. A. *95*, 788–795.

9. Dale, A.M., Fischl, B., and Sereno, M.I. (1999). Cortical surface-based
analysis: I. Segmentation and surface reconstruction. Neuroimage *9*, 179–194.

10. Zeki, S., Watson, J.D.G., Lueck, C.J., Friston, K.J., Kennard, C., and
Frackowiak, R.S.J. (1991). A direct demonstration of functional specialization
in human visual cortex. J. Neurosci. *11*, 641–649.

11. Grill-Spector, K., and Malach, R. (2004). The Human Visual Cortex. Annu.
Rev. Neurosci. *27*, 649–677.

12. Van Essen, D.C. (2004). Organization of visual areas in macaque and human
cerebral cortex. In In The Visual Neuroscience, L. Chapula and J. Werner, eds.
(Cambridge: MIT), pp. 507–521.

13. Cohen, R.A. (2011). Cortical Magnification. In Encyclopedia of Clinical
Neuropsychology, J. S. Kreutzer, J. DeLuca, and B. Caplan, eds. (New York,
NY: Springer New York), pp. 718–719. Available at:
https://doi.org/10.1007/978-0-387-79948-3_1355.

14. Cowey, A., and Rolls, E.T. (1974). Human cortical magnification factor and its
relation to visual acuity. Exp. Brain Res. *21*, 447–454.

15. Schira, M.M., Wade, A.R., and Tyler, C.W. (2007). Two-Dimensional Mapping
of the Central and Parafoveal Visual Field to Human Visual Cortex. J.
Neurophysiol. *97*, 4284–4295. Available at:
http://jn.physiology.org/cgi/doi/10.1152/jn.00972.2006.

16. Balasubramanian, M., Polimeni, J., and Schwartz, E.L. (2002). The V1-V2-V3
complex: quasiconformal dipole maps in primate striate and extra-striate
cortex. Neural Networks *15*, 1157–1163.

17. Benson, N.C., Butt, O.H., Datta, R., Radoeva, P.D., Brainard, D.H., and
Aguirre, G.K. (2012). The retinotopic organization of striate cortex is well
predicted by surface topology. Curr. Biol. *22*, 2081–2085. Available at:
http://dx.doi.org/10.1016/j.cub.2012.09.014.

18. Benson, N.C., Butt, O.H., Brainard, D.H., and Aguirre, G.K. (2014). Correction
of Distortion in Flattened Representations of the Cortical Surface Allows
Prediction of V1-V3 Functional Organization from Anatomy. PLoS Comput.
Biol. *10*.

19. Benson, N.C., and Winawer, J. (2018). Bayesian analysis of retinotopic maps.

Elife *7*, 1–29.

20.   Hinds, O.P., Rajendran, N., Polimeni, J.R., Augustinack, J.C., Wiggins, G.,
Wald, L.L., Rosas, H.D., Potthast, A., Schwarts, E.L., and Fischl, B. (2009).
Accurate prediction of V1 location from cortical folds in a surface coordinate
system. Neuroimage *39*, 1585–1599.

21.   Abdollahi, R.O., Kolster, H., Glasser, M.F., Robinson, E.C., Coalson, T.S.,
Dierker, D., Jenkinson, M., Van Essen, D.C., and Orban, G.A. (2014).
Correspondences between retinotopic areas and myelin maps in human visual
cortex. Neuroimage *99*, 509–524. Available at:
http://dx.doi.org/10.1016/j.neuroimage.2014.06.042.

22.   Wu, J., Yan, T., Zhang, Z., Jin, F., and Guo, Q. (2012). Retinotopic mapping of
the peripheral visual field to human visual cortex by functional magnetic
resonance imaging. Hum. Brain Mapp. *33*, 1727–1740.

23.   Rajimehr, R., and Tootell, R.B.H. (2009). Does retinotopy influence cortical
folding in primate visual cortex? J. Neurosci. *29*, 11149–11152.

24.   Benson, N.C., Jamison, K.W., Arcaro, M.J., Vu, A.T., Glasser, M.F., Coalson,
T.S., Van Essen, D.C., Yacoub, E., Ugurbil, K., Winawer, J., *et al.* (2018). The
Human Connectome Project 7 Tesla retinotopy dataset : Description and
population receptive field analysis Essen. J. Vis. *18*, 1–22. Available at:
https://www.rctn.org/bruno/public/papers/Fukushima1980.pdf.

25.   Seong, S.-B., Pae, C., and Park, H.-J. (2018). Geometric Convolutional Neural
Network for Analyzing Surface-Based Neuroimaging Data. Front. Neuroinform.
12, 1–13. Available at:
https://www.frontiersin.org/article/10.3389/fninf.2018.00042/full.

26.   Zhao, F., Xia, S., Wu, Z., Duan, D., Wang, L., Lin, W., Gilmore, J.H., Shen, D.,
and Li, G. (2019). Spherical U-Net on Cortical Surfaces: Methods and
Applications. 1–12. Available at: http://arxiv.org/abs/1904.00906.

27.   Gopinath, K., Desrosiers, C., and Lombaert, H. (2018). Graph Convolutions on
Spectral Embeddings for Cortical Surface Parcellation. Med. Image Anal. *54*,
297–305. Available at: http://arxiv.org/abs/1803.10336.

28.   DeYoe, E.A., Carman, G.J., Bandettini, P., Glickman, S., Wieser, J., Cox, R.,
Miller, D., and Neitz, J. (1996). Mapping striate and extrastriate visual areas in
human cerebral cortex. Proc. Natl. Acad. Sci. *93*, 2382–2386.

29.   Dumoulin, S.O., and Wandell, B.A. (2008). Population receptive field estimates
in human visual cortex. Neuroimage *39*, 647–660.

30.   Fey, M., Lenssen, J.E., Weichert, F., and Muller, H. (2018). SplineCNN: Fast
Geometric Deep Learning with Continuous B-Spline Kernels. Proc. IEEE
Comput. Soc. Conf. Comput. Vis. Pattern Recognit., 869–877.

31.   Wandell, B.A., and Winawer, J. (2010). Imaging retinotopic maps in the human
brain. Vision Res. *51*, 718–737. Available at:
http://www.qaa.ac.uk/en/Publications/Documents/contact-hours.pdf.

32.   Puckett, A.M., Mathis, J.R., and Deyoe, E.A. (2014). An investigation of
positive and inverted hemodynamic response functions across multiple visual

areas. Hum. Brain Mapp. *35*, 5550–5564.

33. Shmuel, A., Yacoub, E., Pfeuffer, J., Van de Moortele, P.F., Adriany, G., Hu,
X., and Ugurbil, K. (2002). Sustained negative BOLD, blood flow and oxygen
consumption response and its coupling to the positive response in the human
brain. Neuron *36*, 1195–1210.

34. Griffis, J.C., Elkhetali, A.S., Burge, W.K., Chen, R.H., Bowman, A.D.,
Szaflarski, J.P., and Visscher, K.M. (2017). Retinotopic patterns of functional
connectivity between V1 and large-scale brain networks during resting fixation.
Neuroimage *176*, 1071–1083.

35. Park, B.Y., Tark, K.J., Shim, W.M., and Park, H. (2018). Functional
connectivity based parcellation of early visual cortices. Hum. Brain Mapp. *39*,
1380–1390.

36. Finn, E.S., Shen, X., Scheinost, D., Rosenberg, M.D., Huang, J., Chun, M.M.,
Papademetris, X., and Constable, R.T. (2015). Functional connectome
fingerprinting: identifying individuals using patterns of brain connectivity. Nat.
Neurosci. *18*, 1664–1671. Available at:
http://www.nature.com/doifinder/10.1038/nn.4135.

37. Shen, X., Finn, E.S., Scheinost, D., Rosenberg, M.D., Chun, M.M.,
Papademetris, X., and Constable, R.T. (2017). Using connectome-based
predictive modeling to predict individual behavior from brain connectivity. Nat.
Protoc. *12*, 506–518.

38. Gao, S., Greene, A.S., Constable, R.T., and Scheinost, D. (2019). Combining
multiple connectomes improves predictive modeling of phenotypic measures.
Neuroimage *201*, 116038. Available at:
https://doi.org/10.1016/j.neuroimage.2019.116038.

39. Cai, H., Chen, J., Liu, S., Zhu, J., and Yu, Y. (2020). Brain functional
connectome-based prediction of individual decision impulsivity. Cortex *125*,
288–298. Available at: https://doi.org/10.1016/j.cortex.2020.01.022.

40. Dadi, K., Rahim, M., Abraham, A., Chyzhyk, D., Milham, M., Thirion, B., and
Varoquaux, G. (2019). Benchmarking functional connectome-based predictive
models for resting-state fMRI. Neuroimage *192*, 115–134.

41. Fountain-Zaragoza, S., Samimy, S., Rosenberg, M.D., and Prakash, R.S.
(2019). Connectome-based models predict attentional control in aging adults.
Neuroimage *186*, 1–13. Available at:
https://doi.org/10.1016/j.neuroimage.2018.10.074.

42. Muszynski, G., Kashinath, K., Kurlin, V., Wehner, M., and Prabhat (2019).
Topological data analysis and machine learning for recognizing atmospheric
river patterns in large climate datasets. Geosci. Model Dev. *12*, 613–625.

43. Gainza, P., Sverrisson, F., Monti, F., Rodolà, E., Boscaini, D., Bronstein, M.M.,
and Correia, B.E. (2020). Deciphering interaction fingerprints from protein
molecular surfaces using geometric deep learning. Nat. Methods *17*, 184–192.
Available at: http://dx.doi.org/10.1038/s41592-019-0666-6.

44. Rossi, E., Monti, F., Bronstein, M., and Liò, P. (2019). ncRNA Classification

with Graph Convolutional Networks. ArXiv. Available at:
http://arxiv.org/abs/1905.06515.

45.   Eraslan, G., Avsec, Ž., Gagneur, J., and Theis, F.J. (2019). Deep learning:
new computational modelling techniques for genomics. Nat. Rev. Genet.
Available at: http://www.nature.com/articles/s41576-019-0122-6.

46.   Hop, P., Allgood, B., and Yu, J. (2018). Geometric Deep Learning
Autonomously Learns Chemical Features That Outperform Those Engineered
by Domain Experts. Mol. Pharm. *15*, 4371–4377.

47.   Perraudin, N., Defferrard, M., Kacprzak, T., and Sgier, R. (2019). DeepSphere:
Efficient spherical convolutional neural network with HEALPix sampling for
cosmological applications. Astron. Comput. *27*, 130–146.

48.   Van Essen, D.C., Smith, S.M., Barch, D.M., Behrens, T.E.J., Yacoub, E., and
Ugurbil, K. (2013). The WU-Minn Human Connectome Project: An overview.
Neuroimage *80*, 62–79. Available at:
http://dx.doi.org/10.1016/j.neuroimage.2013.05.041.

49.   Glasser, M.F., Sotiropoulos, S.N., Wilson, J.A., Coalson, T.S., Fischl, B.,
Andersson, J.L., Xu, J., Jbabdi, S., Webster, M., Polimeni, J.R., *et al.* (2013).
The minimal preprocessing pipelines for the Human Connectome Project.
Neuroimage *80*, 105–124. Available at:
http://dx.doi.org/10.1016/j.neuroimage.2013.04.127.

50.   Glasser, M.F., and Van Essen, D.C. (2011). Mapping human cortical areas in
vivo based on myelin content as revealed by T1- and T2-weighted MRI. J.
Neurosci. *31*, 11597–11616.

51.   Kay, K.N., Winawer, J., Mezer, A., and Wandell, B.A. (2013). Compressive
spatial summation in human visual cortex. J. Neurophysiol. *110*, 481–494.

52.   Schira, M.M., Tyler, C.W., Breakspear, M., and Spehar, B. (2009). The foveal
confluence in human visual cortex. J. Neurosci. *29*, 9050–9058.

53.   Fey, M., and Lenssen, J.E. (2019). Fast Graph Representation Learning with
PyTorch Geometric. Prepr. http//arxiv.org/abs/1903.02428, 1–9. Available at:
http://arxiv.org/abs/1903.02428.

54.   Ioffe, S., and Szegedy, C. (2015). Batch Normalization: Accelerating Deep
Network Training by Reducing Internal Covariate Shift. In International
Conference on Machine Learning, pp. 448–456.

55.   Frankle, J., Schwab, D.J., and Morcos, A.S. (2020). Training BatchNorm and
Only BatchNorm: On the Expressive Power of Random Features in CNNs
Jonathan. ArXiv.

56.   Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., and Salakhutdinov, R.
(2014). Dropout: A simple way to prevent neural networks from overfitting. J.
Mach. Learn. Res. *15*, 1929–1958.